

## R2. Model fitting and evaluation

2020 - 2021 Skagit River steelhead forecast.

### Contents

<b>Requirements</b>	<b>2</b>
<b>User inputs</b>	<b>11</b>
<b>Loading the fish data</b>	<b>12</b>
<b>Loading the covariates</b>	<b>13</b>
<b>Specifying models in JAGS</b>	<b>13</b>
Beverton-Holt with covars and AR1 process errors (MA1 recruitment residuals). Here we will print out the model (contained in a separate text file) . . . . .	13
Beverton-Holt with covars and AR1MA1 recruitment residuals . . . . .	17
Beverton-Holt with covars and AR1 recruitment residuals . . . . .	20
<b>Fitting the models and generating the one year ahead forecasts</b>	<b>23</b>
<b>Model selection</b>	<b>24</b>
<b>Model Selection Via Approximate Leave-Future-Out Cross Validation following the methods here: <a href="#">link</a>.</b>	<b>25</b>
<b>Model Averaging and 2020 forecast</b>	<b>28</b>
<b>Compare sib adjusted forecasts with unadjusted</b>	<b>31</b>

---

This is version 0.21.01.07.

---

## Requirements

All analyses require the R software (v3.4.3) for data retrieval, data processing, and summarizing model results, and the JAGS software (v4.2.0) for Markov chain Monte Carlo (MCMC) simulation. Please note that some of the R code below may not work with older versions of JAGS due to some changes in the ways that arrays are handled.

We also need a few packages that are not included with the base installation of R, so we begin by installing them (if necessary) and then loading them.

```
if(!require("here")) {  
  install.packages("here")  
  library("here")  
}  
if(!require("readr")) {  
  install.packages("readr")  
  library("readr")  
}  
if(!require("rjags")) {  
  install.packages("rjags")  
  library("rjags")  
}  
if(!require("loo")) {  
  install.packages("loo")  
  library("loo")  
}  
if(!require("ggplot2")) {  
  install.packages("ggplot2")  
  library("ggplot2")  
}  
if(!require("coda")) {  
  install.packages("coda")  
  library("coda")  
}  
if(!require("shinystan")) {  
  install.packages("shinystan")  
  library("shinystan")  
}  
if(!require("R2jags")) {  
  install.packages("R2jags")  
  library("R2jags")  
}  
if(!require("dclone")) {  
  install.packages("dclone")  
  library("dclone")  
}  
if(!require("snow")) {  
  install.packages("snow")  
  library("snow")  
}  
if(!require("rstan")) {  
  install.packages("rstan")  
  library("rstan")  
}
```

```

if(!require("RColorBrewer")) {
  install.packages("RColorBrewer")
  library("RColorBrewer")
}
if(!require("gtools")) {
  install.packages("gtools")
  library("gtools")
}

## set directory locations
datadir <- here("data")
jagsdir <- here("jags")
analdir <- here("analysis")
savedir <- here("analysis/cache")

```

We also need a couple of helper functions.

```

## better round
Re2prec <- function(x, map = "round", prec = 1) {
  ## 'map' can be "round", "floor", or "ceiling"
  ## 'prec' is nearest value (eg, 0.1 means to nearest tenth; 1 gives normal behavior)
  if(prec<=0) { stop("\n\"prec\" cannot be less than or equal to 0") }
  do.call(map,list(x/prec))*prec
}

## wrapper function to fit JAGS models & rearrange output
fit_jags <- function(model, data, params, inits, ctrl, dir = jagsdir) {
  jm <- jags.model(file.path(jagsdir, model),
    data,
    inits,
    ctrl$chains,
    ctrl$burn,
    quiet = TRUE)
  return(coda.samples(jm, params, ctrl$length, ctrl$thin))
}

#alternative wrapper to fit model in parallel; one chain per core
fit_jags2<-function(model,data,params,inits,ctrl,dir=jagsdir){
  cl <- makeCluster(3, type = "SOCK")
  inits2 <- jags.fit(data=data,
    params=params,
    model=file.path(jagsdir, model),
    inits=inits,
    n.chains=ctrl$chains,
    n.adapt = 0,
    n.update = 0,
    n.iter = 0)$state(internal = TRUE)
  jm <- jags.parfit(cl=cl,
    data = data,
    params = params,
    model = file.path(jagsdir, model),
    inits = inits2,
    n.adapt = ctrl$burn*0.5,

```

```

        n.update = ctrl$burn*0.5,
        n.iter = ctrl$length-ctrl$burn,
        thin = ctrl$thin,
        n.chains = ctrl$chains
    )

    stopCluster(cl)
    return(jm)
}

#generate summary stats file from MCMC object
sum_stats<-function(mcmccllist){
  ESS<-apply(as.matrix(mcmccllist),2,ess_bulk)
  Rhat<-apply(as.matrix(mcmccllist),2,Rhat)
  summary_stats<-summary(mcmccllist)
  summary_stats<-data.frame(summary_stats$statistics,summary_stats$quantiles,ESS,Rhat)
}

# functions for approximate LFO
# many functions modified from:
# https://github.com/paul-buerkner/LFO-CV-paper/blob/master/case-study-LFO-CV.Rmd

#load complete model fits & model refits with subset data
loadmodfits<-function(modelnames){
  mod_fits<-list(NULL)
  for(i in 1:length(modelnames)){
    mod_fits[[i]] <- readRDS(file.path(savedir,paste0(modelnames[i],"_y",n_forecasts+1,".rds")))
    #mod_fits[[i]] <- readRDS(file.path(savedir,paste0("fit_",modelnames[i],".rds")))
  }
  return(mod_fits)
}

#refits
loadrefits<-function(refitname,N,L){
  numrefits<-N-L+1
  re_fits<-list()
  for(i in 1:numrefits){
    re_fits[[i]] <- readRDS(file.path(savedir,paste0(refitname,"_y",i,".rds")))
  }
  return(re_fits)
}

# more stable than log(sum(exp(x)))
log_sum_exp <- function(x) {
  max_x <- max(x)
  max_x + log(sum(exp(x - max_x)))
}

# more stable than log(mean(exp(x)))
log_mean_exp <- function(x) {
  log_sum_exp(x) - log(length(x))
}

# compute log of raw importance ratios

```

```

# sums over observations *not* over posterior samples
sum_log_ratios <- function(ll, ids = NULL) {
  if (!is.null(ids)) ll <- ll[, ids, drop = FALSE]
  - rowSums(ll)
}

# for printing comparisons later
rbind_print <- function(...) {
  round(rbind(...), digits = 2)
}

#function to extract log likelihood from fitted model
extract_log_lik<-function(m,esc_only,N,mod_fits){
  #extract pontwise log likelihoods
  tmp_lp <- as.matrix(mod_fits[[m]])
  ## extract pointwise likelihoods
  tmp_lp <- tmp_lp[,grepl("lp_", colnames(tmp_lp))]
  ## if numerical underflows, convert -Inf to 5% less than min(likelihood)
  if(any(is.infinite(tmp_lp))) {
    tmp_lp[is.infinite(tmp_lp)] <- NA
    tmp_min <- min(tmp_lp, na.rm = TRUE)
    tmp_lp[is.na(tmp_lp)] <- tmp_min * 1.05
  }
  if(esc_only == "Yes"){
    tmp_lp<-tmp_lp[,grepl("esc", colnames(tmp_lp))]
  }
  #get yrs assoc
  names_loglik<-data.frame(strsplit(colnames(tmp_lp),"\\[|\\]"))
  yrnames<-as.numeric(names_loglik[2,])

  loglik <- matrix(NA,ncol=N,nrow=dim(tmp_lp)[1])
  for(i in 1:N){
    if(!is.null(ncol(tmp_lp[,yrnames==i]))){
      loglik[,i] = apply(tmp_lp[,yrnames==i],1,sum)
    }else(loglik[,i] = tmp_lp[,yrnames==i])
  }
  return(loglik)
}

approx_LFO<-function(N=N,L=L,m=m,esc_only,mod_fits,userefits,refitname,thres){
  loglik = extract_log_lik(m=m, esc_only = esc_only,N=N,mod_fits = mod_fits)
  ## look at Pareto k's
  k_L00IC<-pareto_k_values(loo(loglik))[(L+1):N]
  if(userefits=="Yes"){
    re_fits =loadrefits(refitname=refitname,N=N,L=L)
  }
  i_refit <- L
  refits <- L
  ks <- NULL
  approx_elpds_1sap <- rep(NA, N)
  for (i in (N - 1):L) {
    logratio <- sum_log_ratios(loglik, (i + 1):N)
    psis_obj <- suppressWarnings(psis(logratio))
  }
}

```

```

k<-pareto_k_values(psis_obj)
ks <- c(ks, k)
if(k>thres & userefits=="Yes"){
  #use_refit of model based on the first[i] observations
  i_refit <- i
  refits <- c(refits, i)
  loglik = extract_log_lik(m=(i+1)-L+1, esc_only = esc_only, N=N, mod_fits = re_fits)
  approx_elpds_1sap[i + 1] <- log_mean_exp(loglik[, i + 1])
}else{
  lw <- weights(psis_obj, normalize = TRUE)[, 1]
  approx_elpds_1sap[i + 1] <- log_sum_exp(lw + loglik[, i + 1])
}
}
results<-list(approx_elpds_1sap,ks,k_L00IC)
names(results)<-c("LF0","ks","k_L00IC")
return(results)
}

plot_ks <- function(ks, thres = 0.7,N,L) {
  ids = N:(L + 1)
  dat_ks <- data.frame(ks = ks, ids = ids)
  ggplot(dat_ks, aes(x = ids, y = ks)) +
    geom_point(aes(color = ks > thres), shape = 3, show.legend = FALSE) +
    geom_hline(yintercept = thres, linetype = 2, color = "red2") +
    scale_color_manual(values = c("cornflowerblue", "darkblue")) +
    labs(x = "Data point", y = "Pareto k") +
    ylim(-0.5, max(dat_ks$ks))
}

#function for printing out a read text file
processFile = function(filepath) {
  con = file(filepath, "r")
  while ( TRUE ) {
    line = readLines(con, n = 1)
    if ( length(line) == 0 ) {
      break
    }
    cat(paste0(noquote(line)), "\n")
  }
  close(con)
}

#calculate stacking weights
find_stack_weights<-function(tau,metric,n,initial_weights,preds,obs){
  tweights<-initial_weights
  preds<-as.matrix(preds)
  obs<-obs
  tau=tau
  skill_list<-c(NULL)
  metric=metric
  for(i in 1:n){
    pred_trs_ensemble<- preds %*% as.vector(tweights)
    Error <- pred_trs_ensemble - obs
    SE <- Error^2
    PE <- Error/obs_trs
  }
}

```

```

APE <- abs(PE)
LAR <- log(obs_trs/pred_trs_ensemble)

RMSE <- apply(SE,2,function(x){sqrt(mean(x))})
MPE <- apply(PE,2,function(x){mean(x)})
MAPE <- apply(APE,2,function(x){mean(x)})
MSA <- apply(LAR,2,function(x){100*(exp(mean(abs(x))-1))})

if(i==1){
  skill=get(metric)
  weights=tweights
}
if(get(metric)<skill){
  skill=get(metric)
  weights=tweights
}
skill_list<-c(skill_list,min(get(metric),skill))
keep<-rbinom(1,prob=skill/get(metric),1)
if(keep==1){tweights=tweights }else{tweights=weights}
tweights = rdirichlet(n=1,alpha = tweights*tau+0.001)
}
results<-list(weights,skill,skill_list)
return(results)
}

#####
#function to fit or load modelfits
#####
fit_load_mods<-function(models){
  ## empty list for fits
  mod_fits <- vector("list", n_mods*(n_forecasts+1))
  ## counter to index fitted jags models (33 in total: 3 models x 11 1 year ahead forecasts including up
  ## return year)
  t <- 1
  for(n in 1:n_mods){
    ## counter to index data to feed model for year specific forecasts
    ## first forecast will be for 10 years prior to the most recent return year;
    ## last forecast will be current forecast for the upcoming return year
    c <- 0
    #n <-2
    model <- models[n]

    for(i in 1:(n_forecasts+1)){
      if(file.exists(file.path(savedir,paste(model,"_", "y",i,".rds",sep = "")))) {
        mod_fits[[t]] <- readRDS(file.path(savedir,paste(model,"_", "y",i,".rds",sep = "")))
        c <- c + 1
        t <- t + 1
      } else { ## else, fit & save
        ## cnt & time stamp
        cat("Count =", t, "; Time =", round(((proc.time()-timer_start)/60)["elapsed"], 1), "\n",
          file="cnt_time.txt", append=TRUE)

        #range of years. Last year in range

```

```

dat_yrs <- seq(yr_first,(yr_last - n_forecasts + c),1)

## number of years of data
n_yrs <- length(dat_yrs)

## get first & last years
yr_first_forecast <- min(dat_yrs)
yr_last_forecast <- max(dat_yrs)

## get escapement data
dat_esc_forecast <- dat_esc[which(dat_esc$year %in% dat_yrs),]

## log of escapement
ln_dat_esc <- c(log(dat_esc_forecast$escapement),rep(NA,n_fore))

## get age data
dat_age_forecast <- dat_age[which(dat_age$year %in% dat_yrs),]
## drop year col & first age_min+age_skip rows
dat_age_forecast <- dat_age_forecast[-(1:(age_min+age_skip)),-1]

## add row(s) of NA's for forecast years
if(n_fore > 0) {
  dat_age_forecast <- rbind(dat_age_forecast,
                           matrix(0, n_fore, A,
                                   dimnames = list(n_yrs+seq(n_fore),colnames(dat_age_forecast)
}
## total num of age obs by cal yr
dat_age_forecast[, "sum"] <- apply(dat_age_forecast, 1, sum)
## row indices for any years with no obs age comp
idx_NA_yrs <- which(dat_age_forecast$sum<A, TRUE)
## replace 0's in yrs w/o any obs with NA's
dat_age_forecast[idx_NA_yrs,(1:A)] <- NA
## change total in yrs w/o any obs from 0 to A to help dmulti()
dat_age_forecast[idx_NA_yrs,"sum"] <- A
## convert class
dat_age_forecast <- as.matrix(dat_age_forecast)

## get harvest data
dat_harv_forecast <- dat_harv[which(dat_harv$year %in% dat_yrs),]
## drop year col & first age_max rows
dat_harv_forecast <- c(dat_harv_forecast$catch,rep(NA,n_fore))

## get covariate data
dat_cvrs_forecast <- dat_cvrs[which(dat_cvrs$year <= yr_last + n_fore - age_min),1:4]
## drop year col
dat_cvrs_forecast <- dat_cvrs_forecast[,-1]
## transform the covariates to z-scores
scl_cvrs_forecast <- scale(dat_cvrs_forecast)
## total number of covariates
n_cov <- dim(dat_cvrs_forecast)[2]

```



```

## ----jags_setup-----
## 1. Data to pass to JAGS
dat_jags <- list(dat_age = dat_age_forecast,
                ln_dat_esc = ln_dat_esc,
                dat_harv = dat_harv_forecast,
                A = A,
                age_min = age_min,
                age_max = age_max,
                age_skip = age_skip,
                n_yrs = n_yrs,
                n_fore = n_fore)

## 2. Model params/states for JAGS to return
## These are specific to the process model,
## so we define them in 'par_jags' below.

if(model == "IPM_BH_cov_AR" | model == "IPM_BH_cov_AR_resid"){
  init_vals_cov <- function() {
    list(alpha = 5,
         beta_inv = exp(mean(ln_dat_esc, na.rm = TRUE)),
         gamma = rep(0, 3),
         pi_tau = 10,
         pi_eta = rep(1,A),
         pi_vec = matrix(c(0.01,0.35,0.47,0.15,0.01,0.01),
                        n_yrs-age_min+n_fore, A,
                        byrow = TRUE),
         Rec_mu = log(1000),
         Rec_sig = 0.1,
         tot_ln_Rec = rep(log(1000), n_yrs - age_min + n_fore),
         phi_prior = 0.5,
         innov_1 = 0)
  }

  ## params/states to return
  par_jags<- c("alpha","E_BH_a","ln_BH_a",
              "beta",
              "gamma",
              "Sp","Rec","tot_ln_Rec","ln_RS",
              "pi_eta","pi_tau",
              "sigma_r","sigma_s","w","res_ln_Rec",
              "lp_age","lp_esc","phi","Run"
              )
}else{
  init_vals_cov <- function() {
    list(alpha = 5,
         beta_inv = exp(mean(ln_dat_esc, na.rm = TRUE)),
         gamma = rep(0, 3),
         pi_tau = 10,
         pi_eta = rep(1,A),
         # pi_vec = matrix(c(0.01,0.35,0.47,0.15,0.01,0.01),
         #                  n_yrs-age_min+n_fore, A,
         #                  byrow = TRUE),

```

```

        Rec_mu = log(1000),
        Rec_sig = 0.1,
        tot_ln_Rec = rep(log(1000), n_yrs - age_min + n_fore),
        phi_prior = 0.5, theta_res_prior = 0.5,
        innov_1 = 0)
    }

    ## params/states to return
    par_jags <- c("alpha", "E_BH_a", "ln_BH_a",
                 "beta",
                 "gamma",
                 "Sp", "Rec", "tot_ln_Rec", "ln_RS", "tot_Run",
                 "pi_eta", "pi_tau",
                 "sigma_r", "sigma_s", "res_ln_Rec", "w", "theta_res", "phi",
                 "lp_age", "lp_esc", "Run"
                 )

}#endif

## set of multi-covariate models
cset <- colnames(scl_cvrs_forecast)
dat_jags$n_cov <- length(cset)
dat_jags$mod_cvrs <- scl_cvrs_forecast[1:(n_yrs-age_min+1), cset]

## fit model & save it
# mod_fits[[t]] <- fit_jags(paste(model, ".txt", sep = ""), dat_jags, par_jags,
#                           init_vals_cov, mcmc_ctrl)
mod_fits[[t]] <- fit_jags2(model=paste(model, ".txt", sep = ""),
                          data=dat_jags,
                          params=par_jags,
                          inits=init_vals_cov,
                          ctrl=mcmc_ctrl
                          )
saveRDS(mod_fits[[t]], file.path(savedir, paste(model, "_", "y", i, ".rds", sep = "")))
summary_stats <- NULL
summary_stats <- sum_stats(mcmclist= mod_fits[[t]])
write.csv(summary_stats, file.path(savedir, paste(model, "_", "y", i, "_summary_stats.csv", sep = "")))
c <- c + 1
t <- t + 1
}## end if

}##next forecast year(i)
}## next model(n)
return(mod_fits)
}

```

## User inputs

We begin by supplying values for the following parameters, which we need for model fitting and evaluation.

```
## first & last years of fish data
yr_first <- 1978
yr_last <- 2020

## min & max adult age classes
age_min <- 3
age_max <- 8

## years (if any) of age-comp to skip; see below
age_skip <- 0

## number of years ahead for run forecasts from the most recent year of data
n_fore <- 1

## number of recent year forecasts
n_forecasts <- 10

## first year of 1 step ahead forecast
yr_begin <- 2011

## last year of 1 step ahead forecast
yr_end <- 2020

## upper threshold for Gelman & Rubin's potential scale reduction factor (Rhat).
Rhat_thresh <- 1.1
```

Next we specify the names of three necessary data files containing the following information:

1. observed total number of adult spawners (escapement) by year;
2. observed age composition of adult spawners by year;
3. observed total harvest by year;

```
## 1. file with escapement data
## [n_yrs x 2] matrix of obs counts; 1st col is calendar yr
fn_esc <- "skagit_sthd_esc.csv"

## 2. file with age comp data
## [n_yrs x (1+A)]; 1st col is calendar yr
fn_age <- "skagit_sthd_age.csv"

## 3. file with harvest data
## [n_yrs x 2] matrix of obs catch; 1st col is calendar yr
fn_harv <- "skagit_sthd_catch.csv"
```

## Loading the fish data

Here we load in the first three data files and do some simple calculations and manipulations. First the spawner data:

```
## escapement
dat_esc <- read_csv(file.path(datadir, fn_esc))
## years of data
dat_yrs <- dat_esc$year

## number of years of data
n_yrs <- length(dat_yrs)

## log of escapement
ln_dat_esc <- c(log(dat_esc$escapement), rep(NA, n_fore))
```

Next the age composition data:

```
## age comp data
dat_age <- read_csv(file.path(datadir, fn_age))
## num of age classes
A <- age_max - age_min + 1

# ## drop year col & first age_min+age_skip rows
# dat_age <- dat_age[-(1:(age_min+age_skip)), -1]
#
# ## add row(s) of NA's for forecast years
# if(n_fore > 0) {
#   dat_age <- rbind(dat_age,
#                     matrix(0, n_fore, A,
#                             dimnames = list(n_yrs+seq(n_fore),
#                                                  colnames(dat_age))))
# }
# ## total num of age obs by cal yr
# dat_age[, "sum"] <- apply(dat_age, 1, sum)
# ## row indices for any years with no obs age comp
# idx_NA_yrs <- which(dat_age$sum < A, TRUE)
# ## replace 0's in yrs w/o any obs with NA's
# dat_age[idx_NA_yrs, (1:A)] <- NA
# ## change total in yrs w/o any obs from 0 to A to help dmulti()
# dat_age[idx_NA_yrs, "sum"] <- A
# ## convert class
# dat_age <- as.matrix(dat_age)
```

And then the harvest data:

```
## harvest
dat_harv <- read_csv(file.path(datadir, fn_harv))
## drop year col & first age_max rows
# dat_harv <- c(dat_harv$catch, rep(NA, n_fore))
```

## Loading the covariates

Our analysis investigates 5 covariates as possible drivers of the population's intrinsic growth rate:

1. Maximum river discharge in winter;
2. Minimum river discharge in summer;
3. North Pacific Gyre Oscillation;

All of the covariates are contained in the file `/data/skagit_sthd_covars.csv`. We will load and then standardize them to have zero-mean and unit-variance.

```
dat_cvrs <- read_csv(file.path(datadir, "skagit_sthd_covars.csv"))
## drop year col
# dat_cvrs <- dat_cvrs[,-1]
# ## transform the covariates to z-scores
# scl_cvrs <- as.matrix(scale(dat_cvrs))
# ## total number of covariates
# n_cov <- dim(dat_cvrs)[2]
```

## Specifying models in JAGS

Now we can specify the model in JAGS. We fit a total one model, which we outline below, based on a beverton holt process model with covariates.

**Beverton-Holt with covars and AR1 process errors (MA1 recruitment residuals).**  
Here we will print out the model (contained in a separate text file)

```
processFile(file.path(jagsdir, "IPM_BH_cov_AR.txt"))

##
##   model {
##
##   ##-----
##   ## PRIORS
##   ##-----
##   ## alpha = intrinsic productivity
##   alpha ~ dnorm(0,0.001) T(0,);
##   mu_BH_a <- log(alpha);
##   E_BH_a <- mu_BH_a + sigma_r/(2 - 2*phi^2);
##
##   ## strength of dens depend
##   beta_inv ~ dnorm(0, 1e-9) T(0,);
##   beta <- 1/beta_inv;
##
##   ## covariate effects
##   for(i in 1:n_cov) { gamma[i] ~ dnorm(0,0.01) }
##
##   ## AR(1) coef for proc errors
##   #phi ~ dunif(-0.999,0.999);
```

```

##      #phi <- 0;
##      phi_prior ~ dbeta(2,2);
##      phi <- phi_prior*2-1;
##      #phi ~ dunif(0,0.999);
##
##      ## innovation in first year
##      innov_1 ~ dnorm(0,tau_r*(1-phi*phi));
##
##      ## process variance for recruits model
##      sigma_r ~ dnorm(0, 2e-2) T(0,);
##      tau_r <- 1/sigma_r;
##
##      ## obs variance for spawners
##      tau_s <- 1/sigma_s;
##      sigma_s ~ dnorm(0, 0.001) T(0,);
##
##      ## unprojectable early recruits;
##      ## hyper mean across all popns
##      Rec_mu ~ dnorm(0,0.001);
##      ## hyper SD across all popns
##      Rec_sig ~ dunif(0,100);
##      ## precision across all popns
##      Rec_tau <- pow(Rec_sig,-2);
##      ## multipliers for unobservable total runs
##      ttl_run_mu ~ dunif(1,5);
##      ttl_run_tau ~ dunif(1,20);
##
##      ## get total cal yr returns for first age_min yrs
##      for(i in 1:(age_min+age_skip)) {
##      ln_tot_Run[i] ~ dnorm(ttl_run_mu*Rec_mu,Rec_tau/ttl_run_tau);
##      tot_Run[i] <- exp(ln_tot_Run[i]);
##      }
##
##      ## maturity schedule
##      ## unif vec for Dirch prior
##      theta <- c(1,10,10,5,1,1)
##      ## hyper-mean for maturity
##      pi_eta ~ ddirch(theta);
##      ## hyper-prec for maturity
##      pi_tau ~ dnorm(0, 0.01) T(0,);
##      for(t in 1:(n_yrs-age_min+n_fore)) { pi_vec[t,1:A] ~ ddirch(pi_eta*pi_tau) }
##
##      ## estimated harvest rate
##      for(t in 1:(n_yrs+n_fore)) { h_rate[t] ~ dunif(0,1) }
##      ##-----
##      ## LIKELIHOOD
##      ##-----
##      ## predicted recruits in BY t
##      covar[1] <- inprod(gamma,mod_cvrs[1,]);
##      ln_BH_a[1] <- mu_BH_a + covar[1];
##      E_ln_Rec[1] <- ln_BH_a[1] + ln_Sp[1] - log(1 + beta*Sp[1]) + phi*innov_1;
##      tot_ln_Rec[1] ~ dnorm(E_ln_Rec[1],tau_r);
##      res_ln_Rec[1] <- tot_ln_Rec[1] - E_ln_Rec[1];
##      w[1] <- phi * innov_1 + res_ln_Rec[1];

```

```

##
## median of total recruits
## tot_Rec[1] <- exp(tot_ln_Rec[1]);
##
## R/S
## ln_RS[1] <- tot_ln_Rec[1] - ln_Sp[1];
##
## brood-yr recruits by age
## for(a in 1:A) {
## Rec[1,a] <- tot_Rec[1] * pi_vec[1,a];
## }
##
## brood years 2:(n_yrs-age_min)
## for(t in 2:(n_yrs-age_min+n_fore)) {
## ## predicted recruits in BY t
## covar[t] <- inprod(gamma, mod_cvrs[t,]);
## ln_BH_a[t] <- mu_BH_a + covar[t];
## E_ln_Rec[t] <- ln_BH_a[t] + ln_Sp[t] - log(1 + beta*Sp[t]) + phi*res_ln_Rec[t-1];
## tot_ln_Rec[t] ~ dnorm(E_ln_Rec[t],tau_r);
## res_ln_Rec[t] <- tot_ln_Rec[t] - E_ln_Rec[t];
## w[t] <- phi * res_ln_Rec[t-1] + res_ln_Rec[t];
##
## median of total recruits
## tot_Rec[t] <- exp(tot_ln_Rec[t]);
##
## R/S
## ln_RS[t] <- tot_ln_Rec[t] - ln_Sp[t];
##
## brood-yr recruits by age
## for(a in 1:A) {
## Rec[t,a] <- tot_Rec[t] * pi_vec[t,a];
## }
## } ## end t loop over year
##
## get predicted calendar year returns by age
## ## matrix Run has dim [(n_yrs-age_min) x A]
## ## step 1: incomplete early broods
## ## first cal yr of this grp is first brood yr + age_min + age_skip
##
## for(i in 1:(age_max-age_min-age_skip)) {
## ## projected recruits
## for(a in 1:(i+age_skip)) {
## Run[i,a] <- Rec[(age_skip+i)-a+1,a];
## }
##
## ## imputed recruits
## for(a in (i+1+age_skip):A) {
## lnRec[i,a] ~ dnorm(Rec_mu,Rec_tau);
## Run[i,a] <- exp(lnRec[i,a]);
## }
##
## ## total run size
## tot_Run[i+age_min+age_skip] <- sum(Run[i,1:A]);
##

```

```

##      ## predicted age-prop vec for multinom
##      for(a in 1:A) {
##      age_v[i,a] <- Run[i,a] / tot_Run[i+age_min];
##      }
##
##      ## multinomial for age comp
##      dat_age[i,1:A] ~ dmulti(age_v[i,1:A],dat_age[i,A+1]);
##      lp_age[i] <- logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]);
##      }
##
##      ## step 2: info from complete broods
##      ## first cal yr of this grp is first brood yr + age_max
##      for(i in (A-age_skip):(n_yrs-age_min-age_skip+n_fore)) {
##      for(a in 1:A) {
##      Run[i,a] <- Rec[(age_skip+i)-a+1,a];
##      }
##
##      ## total run size
##      tot_Run[i+age_min+age_skip] <- sum(Run[i,1:A]);
##
##      ## predicted age-prop vec for multinom
##      for(a in 1:A) {
##      age_v[i,a] <- Run[i,a] / tot_Run[i+age_min];
##      }
##
##      ## multinomial for age comp
##      dat_age[i,1:A] ~ dmulti(age_v[i,1:A],dat_age[i,A+1]);
##      lp_age[i] <- ifelse(i < n_yrs-age_min-age_skip+n_fore, logdensity.multi(dat_age[i,1:A],age_v[i,1:A],
##      dat_age[i,A+1]), logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]));
##
##      ## get predicted calendar year spawners
##      ## first cal yr is first brood yr
##      for(t in 1:(n_yrs+n_fore)) {
##      ## obs model for spawners
##      #Sp[t] <- max(10,tot_Run[t] - dat_harv[t]);
##      est_harv[t] = ifelse(t > n_yrs,1,h_rate[t] * tot_Run[t]);
##      dat_harv[t] ~ dlnorm(log(est_harv[t]), 20);
##      Sp[t] = tot_Run[t] - est_harv[t];
##      ln_Sp[t] <- log(Sp[t]);
##      ln_dat_esc[t] ~ dnorm(ln_Sp[t], tau_s);
##
##      lp_esc[t] <- ifelse(t < n_yrs + 1,logdensity.norm(ln_dat_esc[t],ln_Sp[t], tau_s),0);
##      }
##      } ## end model description
##
## Warning in readLines(con, n = 1): incomplete final line found on 'C:/Users/buehrtwb/OneDrive -
## Washington State Executive Branch Agencies/Documents/Scripts/Skagit-River-Steelhead-Forecast-Laptop/
## jags/IPM_BH_cov_AR.txt'

```



## Beverton-Holt with covars and AR1MA1 recruitment residuals

```
processFile(file.path(jagsdir, "IPM_BH_cov_MA1_AR1.txt"))
```

```
##
## model {
##
##   ##-----
##   ## PRIORS
##   ##-----
##   ## alpha = intrinsic productivity
##   alpha ~ dnorm(0,0.001) T(0,);
##   mu_BH_a <- log(alpha);
##   E_BH_a <- mu_BH_a + sigma_r/(2 - 2*phi^2);
##
##   ## strength of dens depend
##   beta_inv ~ dnorm(0, 1e-9) T(0,);
##   beta <- 1/beta_inv;
##
##   ## covariate effects
##   for(i in 1:n_cov) { gamma[i] ~ dnorm(0,0.01) }
##
##   ## AR(1) coef for recruitment residual
##   #phi ~ dunif(-0.999,0.999);
##   #phi <- 0;
##   phi_prior ~ dbeta(2,2);
##   phi <- phi_prior*2-1;
##   #phi ~ dunif(0,0.999);
##
##   ## MA(1) coef recruitment residual
##   theta_res_prior ~ dbeta(2,2);
##   theta_res <- theta_res_prior*2-1;
##   #theta_res ~ dunif(0,0.999);
##
##   ## innovation in first year
##   #innov_1 ~ dnorm(0,tau_r*(1-phi*phi));#AR1
##   innov_1 ~ dnorm(0,(1-phi^2)/((1+2*phi*theta_res+theta_res^2)*sigma_r^2));#AR1MA1
##
##   ## process variance for recruits model
##   sigma_r ~ dnorm(0, 2e-2) T(0,);
##   tau_r <- 1/sigma_r;
##
##   ## obs variance for spawners
##   tau_s <- 1/sigma_s;
##   sigma_s ~ dnorm(0, 0.001) T(0,);
##
##   ## unprojectable early recruits;
##   ## hyper mean across all popns
##   Rec_mu ~ dnorm(0,0.001);
##   ## hyper SD across all popns
##   Rec_sig ~ dunif(0,100);
##   ## precision across all popns
##   Rec_tau <- pow(Rec_sig,-2);
```

```

## ## multipliers for unobservable total runs
## ttl_run_mu ~ dunif(1,5);
## ttl_run_tau ~ dunif(1,20);
##
## ## get total cal yr returns for first age_min yrs
## for(i in 1:(age_min+age_skip)) {
##   ln_tot_Run[i] ~ dnorm(ttl_run_mu*Rec_mu,Rec_tau/ttl_run_tau);
##   tot_Run[i] <- exp(ln_tot_Run[i]);
## }
##
## ## maturity schedule
## ## unif vec for Dirch prior
## theta <- c(1,10,10,5,1,1)
## ## hyper-mean for maturity
## pi_eta ~ ddirch(theta);
## ## hyper-prec for maturity
## pi_tau ~ dnorm(0, 0.01) T(0,);
## for(t in 1:(n_yrs-age_min+n_fore)) { pi_vec[t,1:A] ~ ddirch(pi_eta*pi_tau) }
##
## ## estimated harvest rate
## for(t in 1:(n_yrs+n_fore)) { h_rate[t] ~ dunif(0,1) }
##
## ##-----
## ## LIKELIHOOD
## ##-----
## ## predicted recruits in BY t
## covar[1] <- inprod(gamma,mod_cvrs[1,]);
## ln_BH_a[1] <- mu_BH_a + covar[1];
## E_ln_Rec[1] <- ln_BH_a[1] + ln_Sp[1] - log(1 + beta*Sp[1]) + phi * innov_1 + theta_res * 0;
## tot_ln_Rec[1] ~ dnorm(E_ln_Rec[1], tau_r);
## res_ln_Rec[1] <- tot_ln_Rec[1] - E_ln_Rec[1];
## w[1] <- phi * innov_1 + theta_res * 0 + res_ln_Rec[1]
##
## ## median of total recruits
## tot_Rec[1] <- exp(tot_ln_Rec[1]);
##
## ## R/S
## ln_RS[1] <- tot_ln_Rec[1] - ln_Sp[1];
##
## ## brood-yr recruits by age
## for(a in 1:A) {
##   Rec[1,a] <- tot_Rec[1] * pi_vec[1,a];
## }
##
## ## brood years 2:(n_yrs-age_min)
## for(t in 2:(n_yrs-age_min+n_fore)) {
##   ## predicted recruits in BY t
##   covar[t] <- inprod(gamma, mod_cvrs[t,]);
##   ln_BH_a[t] <- mu_BH_a + covar[t];
##
##   #=====
##   #version 4; more similar to AR1 original model
##   #=====
##   E_ln_Rec[t] <- ln_BH_a[t] + ln_Sp[t] - log(1 + beta*Sp[t]) + phi * w[t-1] + theta_res * res_ln_R

```

```

##      tot_ln_Rec[t] ~ dnorm(E_ln_Rec[t], tau_r);
##      res_ln_Rec[t] <- tot_ln_Rec[t] - E_ln_Rec[t];
##      w[t] <- phi * w[t-1] + theta_res * res_ln_Rec[t-1] + res_ln_Rec[t];
##
##
##      ## median of total recruits
##      tot_Rec[t] <- exp(tot_ln_Rec[t]);
##      ## R/S
##      ln_RS[t] <- tot_ln_Rec[t] - ln_Sp[t];
##      ## brood-yr recruits by age
##      for(a in 1:A) {
##          Rec[t,a] <- tot_Rec[t] * pi_vec[t,a];
##      }
##  } ## end t loop over year
##
##  ## get predicted calendar year returns by age
##  ## matrix Run has dim [(n_yrs-age_min) x A]
##  ## step 1: incomplete early broods
##  ## first cal yr of this grp is first brood yr + age_min + age_skip
##  for(i in 1:(age_max-age_min-age_skip)) {
##      ## projected recruits
##      for(a in 1:(i+age_skip)) {
##          Run[i,a] <- Rec[(age_skip+i)-a+1,a];
##      }
##      ## imputed recruits
##      for(a in (i+1+age_skip):A) {
##          lnRec[i,a] ~ dnorm(Rec_mu,Rec_tau);
##          Run[i,a] <- exp(lnRec[i,a]);
##      }
##      ## total run size
##      tot_Run[i+age_min+age_skip] <- sum(Run[i,1:A]);
##      ## predicted age-prop vec for multinom
##      for(a in 1:A) {
##          age_v[i,a] <- Run[i,a] / tot_Run[i+age_min];
##      }
##      ## multinomial for age comp
##      dat_age[i,1:A] ~ dmulti(age_v[i,1:A],dat_age[i,A+1]);
##      lp_age[i] <- logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]);
##  }
##
##  ## step 2: info from complete broods
##  ## first cal yr of this grp is first brood yr + age_max
##  for(i in (A-age_skip):(n_yrs-age_min-age_skip+n_fore)) {
##      for(a in 1:A) {
##          Run[i,a] <- Rec[(age_skip+i)-a+1,a];
##      }
##      ## total run size
##      tot_Run[i+age_min+age_skip] <- sum(Run[i,1:A]);
##      ## predicted age-prop vec for multinom
##      for(a in 1:A) {
##          age_v[i,a] <- Run[i,a] / tot_Run[i+age_min];
##      }
##      ## multinomial for age comp
##      dat_age[i,1:A] ~ dmulti(age_v[i,1:A],dat_age[i,A+1]);

```

```

##      #lp_age[i] <- logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]);
##      lp_age[i] <- ifelse(i < n_yrs-age_min-age_skip+n_fore,
##      logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]),0)
##    }
##
##    ## get predicted calendar year spawners
##    ## first cal yr is first brood yr
##    for(t in 1:(n_yrs+n_fore)) {
##      ## obs model for spawners
##      # Sp[t] <- max(10,tot_Run[t] - dat_harv[t]);
##      est_harv[t] = ifelse(t > n_yrs,1,h_rate[t] * tot_Run[t]);
##      dat_harv[t] ~ dlnorm(log(est_harv[t]), 20);
##      Sp[t] = tot_Run[t] - est_harv[t];
##      ln_Sp[t] <- log(Sp[t]);
##      ln_dat_esc[t] ~ dnorm(ln_Sp[t], tau_s);
##      lp_esc[t] <- ifelse(t < n_yrs + 1,logdensity.norm(ln_dat_esc[t],ln_Sp[t], tau_s),0);
##    }
##
## } ## end model description
##

## Warning in readLines(con, n = 1): incomplete final line found on 'C:/Users/buehrtwb/OneDrive -
## Washington State Executive Branch Agencies/Documents/Scripts/Skagit-River-Steelhead-Forecast-Laptop/
## jags/IPM_BH_cov_MA1_AR1.txt'

```

## Beverton-Holt with covars and AR1 recruitment residuals

```
processFile(file.path(jagsdir, "IPM_BH_cov_AR_resid.txt"))
```

```

##
## model {
##
##   ##-----
##   ## PRIORS
##   ##-----
##   ## alpha = intrinsic productivity
##   alpha ~ dnorm(0,0.001) T(0,);
##   mu_BH_a <- log(alpha);
##   E_BH_a <- mu_BH_a + sigma_r/(2 - 2*phi^2);
##
##   ## strength of dens depend
##   beta_inv ~ dnorm(0, 1e-9) T(0,);
##   beta <- 1/beta_inv;
##
##   ## covariate effects
##   for(i in 1:n_cov) { gamma[i] ~ dnorm(0,0.01) }
##
##   ## AR(1) coef for recruitment residual
##   #phi ~ dunif(-0.999,0.999);
##   #phi <- 0;
##   phi_prior ~ dbeta(2,2);

```

```

## phi <- phi_prior*2-1;
## #phi ~ dunif(0,0.999);
##
## ## innovation in first year
## innov_1 ~ dnorm(0,tau_r*(1-phi*phi));#AR1
##
## ## process variance for recruits model
## sigma_r ~ dnorm(0, 2e-2) T(0,);
## tau_r <- 1/sigma_r;
##
## ## obs variance for spawners
## tau_s <- 1/sigma_s;
## sigma_s ~ dnorm(0, 0.001) T(0,);
##
## ## unprojectable early recruits;
## ## hyper mean across all popns
## Rec_mu ~ dnorm(0,0.001);
## ## hyper SD across all popns
## Rec_sig ~ dunif(0,100);
## ## precision across all popns
## Rec_tau <- pow(Rec_sig,-2);
## ## multipliers for unobservable total runs
## ttl_run_mu ~ dunif(1,5);
## ttl_run_tau ~ dunif(1,20);
##
## ## get total cal yr returns for first age_min yrs
## for(i in 1:(age_min+age_skip)) {
##   ln_tot_Run[i] ~ dnorm(ttl_run_mu*Rec_mu,Rec_tau/ttl_run_tau);
##   tot_Run[i] <- exp(ln_tot_Run[i]);
## }
##
## ## maturity schedule
## ## unif vec for Dirch prior
## theta <- c(1,10,10,5,1,1)
## ## hyper-mean for maturity
## pi_eta ~ ddirch(theta);
## ## hyper-prec for maturity
## pi_tau ~ dnorm(0, 0.01) T(0,);
## for(t in 1:(n_yrs-age_min+n_fore)) { pi_vec[t,1:A] ~ ddirch(pi_eta*pi_tau) }
##
## ## estimated harvest rate
## for(t in 1:(n_yrs+n_fore)) { h_rate[t] ~ dunif(0,1) }
##
## ##-----
## ## LIKELIHOOD
## ##-----
## ## predicted recruits in BY t
## covar[1] <- inprod(gamma,mod_cvrs[1,]);
## ln_BH_a[1] <- mu_BH_a + covar[1];
## E_ln_Rec[1] <- ln_BH_a[1] + ln_Sp[1] - log(1 + beta*Sp[1]) + phi * innov_1;
## tot_ln_Rec[1] ~ dnorm(E_ln_Rec[1], tau_r);
## res_ln_Rec[1] <- tot_ln_Rec[1] - E_ln_Rec[1];
## w[1] <- phi * innov_1 + res_ln_Rec[1];
##

```

```

## median of total recruits
tot_Rec[1] <- exp(tot_ln_Rec[1]);
##
## R/S
ln_RS[1] <- tot_ln_Rec[1] - ln_Sp[1];
##
## brood-yr recruits by age
for(a in 1:A) {
  Rec[1,a] <- tot_Rec[1] * pi_vec[1,a];
}
##
## brood years 2:(n_yrs-age_min)
for(t in 2:(n_yrs-age_min+n_fore)) {
  ## predicted recruits in BY t
  covar[t] <- inprod(gamma, mod_cvrs[t,]);
  ln_BH_a[t] <- mu_BH_a + covar[t];
  E_ln_Rec[t] <- ln_BH_a[t] + ln_Sp[t] - log(1 + beta*Sp[t]) + phi * w[t-1];
  tot_ln_Rec[t] ~ dnorm(E_ln_Rec[t], tau_r);
  res_ln_Rec[t] <- tot_ln_Rec[t] - E_ln_Rec[t];
  w[t] <- phi * w[t-1] + res_ln_Rec[t];
}
##
## median of total recruits
tot_Rec[t] <- exp(tot_ln_Rec[t]);
##
## R/S
ln_RS[t] <- tot_ln_Rec[t] - ln_Sp[t];
##
## brood-yr recruits by age
for(a in 1:A) {
  Rec[t,a] <- tot_Rec[t] * pi_vec[t,a];
}
## } ## end t loop over year
##
## get predicted calendar year returns by age
## matrix Run has dim [(n_yrs-age_min) x A]
## step 1: incomplete early broods
## first cal yr of this grp is first brood yr + age_min + age_skip
for(i in 1:(age_max-age_min-age_skip)) {
  ## projected recruits
  for(a in 1:(i+age_skip)) {
    Run[i,a] <- Rec[(age_skip+i)-a+1,a];
  }
  ## imputed recruits
  for(a in (i+1+age_skip):A) {
    lnRec[i,a] ~ dnorm(Rec_mu,Rec_tau);
    Run[i,a] <- exp(lnRec[i,a]);
  }
  ## total run size
  tot_Run[i+age_min+age_skip] <- sum(Run[i,1:A]);
  ## predicted age-prop vec for multinom
  for(a in 1:A) {
    age_v[i,a] <- Run[i,a] / tot_Run[i+age_min];
  }
  ## multinomial for age comp
  dat_age[i,1:A] ~ dmulti(age_v[i,1:A],dat_age[i,A+1]);
  lp_age[i] <- logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]);
}

```

```

##   }
##
##   ## step 2: info from complete broods
##   ## first cal yr of this grp is first brood yr + age_max
##   for(i in (A-age_skip):(n_yrs-age_min-age_skip+n_fore)) {
##     for(a in 1:A) {
##       Run[i,a] <- Rec[(age_skip+i)-a+1,a];
##     }
##     ## total run size
##     tot_Run[i+age_min+age_skip] <- sum(Run[i,1:A]);
##     ## predicted age-prop vec for multinom
##     for(a in 1:A) {
##       age_v[i,a] <- Run[i,a] / tot_Run[i+age_min];
##     }
##     ## multinomial for age comp
##     dat_age[i,1:A] ~ dmulti(age_v[i,1:A],dat_age[i,A+1]);
##     #lp_age[i] <- logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]);
##     lp_age[i] <- ifelse(i < n_yrs-age_min-age_skip+n_fore,
##       logdensity.multi(dat_age[i,1:A],age_v[i,1:A],dat_age[i,A+1]),0)
##   }
##
##   ## get predicted calendar year spawners
##   ## first cal yr is first brood yr
##   for(t in 1:(n_yrs+n_fore)) {
##     ## obs model for spawners
##     # Sp[t] <- max(10,tot_Run[t] - dat_harv[t]);
##     est_harv[t] = ifelse(t > n_yrs,1,h_rate[t] * tot_Run[t]);
##     dat_harv[t] ~ dlnorm(log(est_harv[t]), 20);
##     Sp[t] = tot_Run[t] - est_harv[t];
##     ln_Sp[t] <- log(Sp[t]);
##     ln_dat_esc[t] ~ dnorm(ln_Sp[t], tau_s);
##     lp_esc[t] <- ifelse(t < n_yrs + 1,logdensity.norm(ln_dat_esc[t],ln_Sp[t], tau_s),0);
##   }
##
## } ## end model description
##

```

```

## Warning in readLines(con, n = 1): incomplete final line found on 'C:/Users/buehrtwb/OneDrive -
## Washington State Executive Branch Agencies/Documents/Scripts/Skagit-River-Steelhead-Forecast-Laptop/
## jags/IPM_BH_cov_AR_resid.txt'

```

---

## Fitting the models and generating the one year ahead forecasts

Before fitting the model in JAGS, we need to specify the MCMC control parameters.

```

## 1. MCMC control params
mcmc_ctrl <- list(
  chains = 4,
  length = 200000, #5e5,
  burn = 100000, #2e5,

```

```

  thin = 100#400
)
## total number of MCMC samples after burnin
mcmc_samp <- mcmc_ctrl$length*mcmc_ctrl$chains/mcmc_ctrl$thin

## fit or load models
models=c("IPM_BH_cov_MA1_AR1",
         "IPM_BH_cov_AR",
         "IPM_BH_cov_AR_resid",
         "IPM_BH_cov_MA1_AR1_age",
         "IPM_BH_cov_AR_age",
         "IPM_BH_cov_AR_resid_age"
        )
n_mods<-length(models)
mod_fits <- fit_load_mods(models=models)

```

## Model selection

```

tot_mods <- n_forecasts*n_mods

# get escapement data
dat_esc_forecast <- dat_esc[which(dat_esc$year %in% seq(yr_begin,yr_end,1)),]

## get harvest data
dat_harv_forecast <- dat_harv[which(dat_harv$year %in% seq(yr_begin,yr_end,1)),]

## observed terminal run size
obs_trs <- dat_esc_forecast$escapement + dat_harv_forecast$catch

pred_trs <- NULL
for(n in 1:n_mods){
  #n <- 1
  pred_esc <- NULL
  for(i in 1:(n_forecasts)){
    #i <- 1
    mod_res<-NULL
    mod_res<-as.matrix(readRDS(file.path(savedir,paste0(models[n],"_y",i,".rds"))))
    p_dat <- mod_res[,grep("Sp", colnames(mod_res))]
    p_dat <- round(median(p_dat[,dim(p_dat)[2]]))

    pred_esc[i] <- p_dat
  }

  pred_trs_mod <- pred_esc + 1#+ dat_harv_forecast$catch #you don't need to add catch in because it is

  pred_trs <- cbind(pred_trs,pred_trs_mod)
  #names(pred_trs) <- paste(models[n],"_", "pred_trs", sep = "")
}

```



```

colnames(pred_trs) <- models

## compute model performance statistics
Error <- pred_trs - obs_trs
SE <- Error^2
PE <- Error/obs_trs
APE <- abs(PE)
LAR <- log(obs_trs/pred_trs)

RMSE <- apply(SE,2,function(x){sqrt(mean(x))})
MPE <- apply(PE,2,function(x){mean(x)})
MAPE <- apply(APE,2,function(x){mean(x)})
MSA <- apply(LAR,2,function(x){100*(exp(mean(abs(x))-1))})

model_selection <- data.frame(RMSE,MPE,MAPE,MSA)
weights<-apply(model_selection[,!colnames(model_selection)=="MPE"], 2,function(x) (1/x)/sum(1/x))
colnames(weights)<-paste0(colnames(weights),"_weight")
model_selection<-data.frame(model_selection,weights)

```

Model Selection Via Approximate Leave-Future-Out Cross Validation following the methods here: [link](#).

```

N=yr_last-yr_first+1
L=N-n_forecasts
thres=0.1
esc_only="No"
userefits="Yes"
mod_fits<-loadmodfits(modelnames=models)

LF01<-approx_LFO(N=N,L=L,m=1,esc_only=esc_only,mod_fits=mod_fits,userefits=userefits,refitname=models[1])

## Warning: Relative effective sample sizes ('r_eff' argument) not specified.
## For models fit with MCMC, the reported PSIS effective sample sizes and
## MCSE estimates will be over-optimistic.

## Warning: Some Pareto k diagnostic values are too high. See help('pareto-k-diagnostic') for details.

# plot_ks(LF01$ks,N=N,L=L,thres=thres)
# plot_ks(LF01$k_LOOIC,N=N,L=L,thres=thres)

LF02<-approx_LFO(N=N,L=L,m=2,esc_only=esc_only,mod_fits=mod_fits,userefits=userefits,refitname=models[2])

## Warning: Relative effective sample sizes ('r_eff' argument) not specified.
## For models fit with MCMC, the reported PSIS effective sample sizes and
## MCSE estimates will be over-optimistic.

## Warning: Some Pareto k diagnostic values are too high. See help('pareto-k-diagnostic') for details.

```

```

# plot_ks(LF02$ks, N=N,L=L,thres=thres)
# plot_ks(LF02$k_LOOIC, N=N,L=L,thres=thres)

LF03<-approx_LF0(N=N,L=L,m=3,esc_only=esc_only,mod_fits=mod_fits,userefits=userefits,refitname=models[3])

## Warning: Relative effective sample sizes ('r_eff' argument) not specified.
## For models fit with MCMC, the reported PSIS effective sample sizes and
## MCSE estimates will be over-optimistic.

## Warning: Some Pareto k diagnostic values are too high. See help('pareto-k-diagnostic') for details.

# plot_ks(LF03$ks, N=N,L=L,thres=thres)
# plot_ks(LF03$k_LOOIC, N=N,L=L,thres=thres)

LF04<-approx_LF0(N=N,L=L,m=4,esc_only=esc_only,mod_fits=mod_fits,userefits=userefits,refitname=models[4])

## Warning: Relative effective sample sizes ('r_eff' argument) not specified.
## For models fit with MCMC, the reported PSIS effective sample sizes and
## MCSE estimates will be over-optimistic.

## Warning: Some Pareto k diagnostic values are too high. See help('pareto-k-diagnostic') for details.

# plot_ks(LF03$ks, N=N,L=L,thres=thres)
# plot_ks(LF03$k_LOOIC, N=N,L=L,thres=thres)

LF05<-approx_LF0(N=N,L=L,m=5,esc_only=esc_only,mod_fits=mod_fits,userefits=userefits,refitname=models[5])

## Warning: Relative effective sample sizes ('r_eff' argument) not specified.
## For models fit with MCMC, the reported PSIS effective sample sizes and
## MCSE estimates will be over-optimistic.

## Warning: Some Pareto k diagnostic values are too high. See help('pareto-k-diagnostic') for details.

# plot_ks(LF03$ks, N=N,L=L,thres=thres)
# plot_ks(LF03$k_LOOIC, N=N,L=L,thres=thres)

LF06<-approx_LF0(N=N,L=L,m=6,esc_only=esc_only,mod_fits=mod_fits,userefits=userefits,refitname=models[6])

## Warning: Relative effective sample sizes ('r_eff' argument) not specified.
## For models fit with MCMC, the reported PSIS effective sample sizes and
## MCSE estimates will be over-optimistic.

## Warning: Some Pareto k diagnostic values are too high. See help('pareto-k-diagnostic') for details.

# plot_ks(LF03$ks, N=N,L=L,thres=thres)
# plot_ks(LF03$k_LOOIC, N=N,L=L,thres=thres)

ELPD<-c(sum(LF01$LF0,na.rm=T),

```

```

      sum(LF02$LF0,na.rm=T),
      sum(LF03$LF0,na.rm=T),
      sum(LF04$LF0,na.rm=T),
      sum(LF05$LF0,na.rm=T),
      sum(LF06$LF0,na.rm=T)
    )
LFOIC<--2*(ELPD)
delta_LFOIC<-LFOIC-min(LFOIC)
LFOIC_weight<-exp(ELPD)/sum(exp(ELPD))
LFOIC_results<-data.frame(ELPD,LFOIC,delta_LFOIC, LFOIC_weight)
rownames(LFOIC_results)<-models
model_selection<-data.frame(model_selection,LFOIC_results)

```

Calculating Stacking Weights (finding model averaging weights based on one-step-ahead performance of weighted average models). This is an experimental calculation of stacking weights based on linear combinations of model forecasts to optimize one step ahead RMSE, MSA, or MAPE... it is not ready for prime time yet. An alternative is to figure out how to use methods similar to “stacking weights” here for LFOIC: [link](#)

```

stack_weights<-find_stack_weights(tau=1,
                                   n=10000,
                                   metric="MSA",
                                   initial_weights=rep(1/length(models),length(models)),
                                   preds=pred_trs,
                                   obs=obs_trs
                                   )
stacking_weights<-as.vector(round(unlist(stack_weights[[1]]),4))
model_selection$stacking_weights<-stacking_weights

```

Model Selection Via loo() and compare() with full table of results. Note that elpd\_diff will be negative (positive) if the expected predictive accuracy for the first (second) model is higher.

```

LOOIC <- vector("list", n_mods)
## extract log densities from JAGS objects
for(i in 1:n_mods) {
  #i <- 1
  ## convert mcmc.list to matrix
  tmp_lp <- as.matrix(readRDS(file.path(savedir,paste0(models[i],"_y",11,".rds"))))
  ## extract pointwise likelihoods
  tmp_lp <- tmp_lp[,grepl("lp_", colnames(tmp_lp))]
  ## if numerical underflows, convert -Inf to 5% less than min(likelihood)
  if(any(is.infinite(tmp_lp))) {
    tmp_lp[is.infinite(tmp_lp)] <- NA
    tmp_min <- min(tmp_lp, na.rm = TRUE)
    tmp_lp[is.na(tmp_lp)] <- tmp_min * 1.05
  }
  ## calculate LOOIC
  LOOIC[[i]] <- loo(tmp_lp)
}

## compute pseudo weights
#model_weights <- loo_model_weights(LOOIC, method = "pseudobma",optim_method = "BFGS", optim_control = list())

model_weights <- loo_model_weights(LOOIC, method = "stacking",optim_method = "BFGS", optim_control = list())

```

```
## LOOIC for all data
tbl_LOOIC <- round(loo_compare(x = LOOIC), 2)
rownames(tbl_LOOIC) <- sub("model", "", rownames(tbl_LOOIC))
tbl_LOOIC <- tbl_LOOIC[order(as.numeric(rownames(tbl_LOOIC))), ]
tbl_LOOIC <- cbind(model = models,
                   as.data.frame(tbl_LOOIC), LOOIC_weight = as.matrix(model_weights))
tbl_LOOIC$delta_LOOIC <- tbl_LOOIC$looic - min(tbl_LOOIC$looic)
model_selection$LOOIC <- tbl_LOOIC$looic
model_selection$delta_LOOIC <- tbl_LOOIC$delta_LOOIC
model_selection$LOOIC_weight <- round(tbl_LOOIC$LOOIC_weight, 4)
```

## Model Averaging and 2020 forecast

```
## extract median 2020 forecast from each model
f_dat <- data.frame(
  sort(unlist(mod_fits[[1]][, paste0("Sp", "[", n_yrs + n_fore, "]")])),
  sort(unlist(mod_fits[[2]][, paste0("Sp", "[", n_yrs + n_fore, "]")])),
  sort(unlist(mod_fits[[3]][, paste0("Sp", "[", n_yrs + n_fore, "]")])),
  sort(unlist(mod_fits[[4]][, paste0("Sp", "[", n_yrs + n_fore, "]")])),
  sort(unlist(mod_fits[[5]][, paste0("Sp", "[", n_yrs + n_fore, "]")])),
  sort(unlist(mod_fits[[6]][, paste0("Sp", "[", n_yrs + n_fore, "]")]))
)
colnames(f_dat) <- models

model_selection[, "2020_forecast"] <- apply(f_dat, 2, median)

weighted_forecast_dist <- (
  as.matrix(f_dat) %*% (as.vector(model_selection[, "LFOIC_weight"]))
)
weighted_forecast_quantiles <- quantile(weighted_forecast_dist, c(0.025, 0.25, 0.50, 0.75, 0.975))
weighted_forecast <- weighted_forecast_quantiles[3]
print(model_selection)
```

	RMSE	MPE	MAPE	MSA	RMSE_weight	MAPE_weight	MSA_weight
## IPM_BH_cov_MA1_AR1	1568.000	0.10751942	0.2240939	45.11414	0.1536565	0.1565110	0.1641179
## IPM_BH_cov_AR	1642.006	0.11174421	0.2396936	45.71892	0.1467311	0.1463250	0.1619469
## IPM_BH_cov_AR_resid	1525.042	0.09448217	0.2155400	44.83824	0.1579847	0.1627223	0.1651277
## IPM_BH_cov_MA1_AR1_age	1334.804	0.12616270	0.1951553	43.59182	0.1805008	0.1797193	0.1698492
## IPM_BH_cov_AR_age	1319.431	0.12904289	0.1969258	43.55082	0.1826040	0.1781034	0.1700091
## IPM_BH_cov_AR_resid_age	1349.594	0.11806776	0.1985809	43.82403	0.1785228	0.1766190	0.1689492
##	ELPD	LFOIC	delta_LFOIC	LFOIC_weight	stacking_weights	L00IC	
## IPM_BH_cov_MA1_AR1	6.974438	-13.94888	1.7034433	0.1124354	0.0000	808.47	
## IPM_BH_cov_AR	7.826160	-15.65232	0.0000000	0.2635125	0.0000	790.64	
## IPM_BH_cov_AR_resid	7.200095	-14.40019	1.2521297	0.1408980	0.0000	819.28	
## IPM_BH_cov_MA1_AR1_age	7.274766	-14.54953	1.1027870	0.1518218	0.4857	826.69	
## IPM_BH_cov_AR_age	7.309776	-14.61955	1.0327684	0.1572311	0.5143	836.05	
## IPM_BH_cov_AR_resid_age	7.411696	-14.82339	0.8289274	0.1741013	0.0000	825.47	
##	delta_L00IC	L00IC_weight	2020_forecast				
## IPM_BH_cov_MA1_AR1	17.83	0.0000	4692.778				
## IPM_BH_cov_AR	0.00	0.4761	5094.126				

```
## IPM_BH_cov_AR_resid      28.64      0.1428      4610.069
## IPM_BH_cov_MA1_AR1_age   36.05      0.0000      3380.080
## IPM_BH_cov_AR_age        45.41      0.0000      3916.261
## IPM_BH_cov_AR_resid_age  34.83      0.3811      3297.029
```

```
print("The model-averaged forecast is:")
```


```
## [1] "The model-averaged forecast is:"
```

```
print(weighted_forecast_quantiles)
```

```
##      2.5%      25%      50%      75%      97.5%
## 2248.432 3400.362 4222.494 5254.219 8114.161
```

```
ensemble_median<-as.matrix(pred_trsr)%*(as.vector(model_selection[, "LFOIC_weight"]))
```


```
cols<-brewer.pal(length(models), "Spectral")
matplot(as.matrix(data.frame(pred_trsr, ensemble_median)), type="l", lty=1, col=c(cols, "grey40"), lwd=c(rep(2,
axis(1, 1:n_forecasts, (yr_last-n_forecasts+1):(yr_last))
points(x=1:n_forecasts, y=obs_trsr, cex=1.5, pch=20, col="red")
legend("topright", legend=c(models, "Observed", "Ensemble"), lty=c(rep(1, length(models)), NA), col=c(cols, "red", "grey40"))
```



```
#density plot for final forecasts and ensemble
res<-apply(f_dat,2,function(x) density(x))
plot(x=1,y=1,ylim=c(0,0.001),xlim=c(0,10000),ylab="density",xlab="2021 Runsize")
lapply(res,function(x) lines(x$y~x$x))
```

```
## $IPM_BH_cov_MA1_AR1
## NULL
##
## $IPM_BH_cov_AR
## NULL
##
## $IPM_BH_cov_AR_resid
## NULL
##
## $IPM_BH_cov_MA1_AR1_age
## NULL
##
## $IPM_BH_cov_AR_age
## NULL
##
## $IPM_BH_cov_AR_resid_age
## NULL
```

```
lines(density(weighted_forecast_dist)$y~density(weighted_forecast_dist)$x,lwd=4,col="red")
legend("topright",legend=c(models,"Ensemble"),lwd=c(rep(1,length(models)),4),col=c(rep("black",length(m
```



## Compare sib adjusted forecasts with unadjusted

```
models=c(
  #"IPM_BH_cov_MA1_AR1",
  #"IPM_BH_cov_AR",
  #"IPM_BH_cov_AR_resid",
  "IPM_BH_cov_MA1_AR1_age",
  #"IPM_BH_cov_AR_age",
  "IPM_BH_cov_AR_resid_age"
)
n_mods<-length(models)

mod_fits <- fit_load_mods(models=models)
)
#####new version 1.7
tot_mods <- n_forecasts*n_mods
# get escapement data
dat_esc_forecast <- dat_esc[which(dat_esc$year %in% seq(yr_begin,yr_end,1)),]

## get harvest data
dat_harv_forecast <- dat_harv[which(dat_harv$year %in% seq(yr_begin,yr_end,1)),]
## observed terminal run size
obs_trs <- dat_esc_forecast$escapement + dat_harv_forecast$catch
pred_trs <- NULL
pred_trs_adj <- NULL
for(n in 1:n_mods){
  #n <- 1
  pred_esc <- NULL
  pred_esc_adj <- NULL

  c <- 0
  f <- 2
  adj<- NULL
  for(i in 1:(n_forecasts)){
    #i <- 1

    #range of years. Last year in range
    dat_yrs <- seq(yr_frst,(yr_last - n_forecasts + c),1)

    ## number of years of data
    n_yrs <- length(dat_yrs)

    mod_res<-NULL

    #model refit and one step ahead forecast
    mod_res_pred<-as.matrix(readRDS(file.path(savedir,paste0(models[n],"_y",i,".rds"))))

    #model refit for year i+1 to extract "observed" state
    mod_res_obs<-as.matrix(readRDS(file.path(savedir,paste0(models[n],"_y",i + 1,".rds"))))
    #
    p_dat_pred <- mod_res_pred[,grep("Sp", colnames(mod_res_pred))]
    p_dat_pred <- round(median(p_dat_pred[,n_yrs + 1]))
```

```

p_dat_obs <- mod_res_obs[,grep("Sp", colnames(mod_res_obs))]
p_dat_obs <- round(median(p_dat_obs[,n_yrs + 2]))

pred_esc[i] <- p_dat_pred

#take same model and implement sibling adjustment
## forecast for year t
p_dat_pred_adj <- cbind(((mod_res_pred[,paste0("Run", "[", n_yrs - age_min + 1, ",", "1,")])),
  ((mod_res_pred[,paste0("Run", "[", n_yrs - age_min + 1, ",", "2,")])),
  ((mod_res_pred[,paste0("Run", "[", n_yrs - age_min + 1, ",", "3,")])),
  ((mod_res_pred[,paste0("Run", "[", n_yrs - age_min + 1, ",", "4,")])),
  ((mod_res_pred[,paste0("Run", "[", n_yrs - age_min + 1, ",", "5,")])),
  ((mod_res_pred[,paste0("Run", "[", n_yrs - age_min + 1, ",", "6,")]))))

p_dat_pred_adj_sum <- apply(p_dat_pred_adj, 1, FUN = "sum")
median(p_dat_pred_adj_sum)

## observation for year t+1
p_dat_obs_adj <- cbind(((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 1, ",", "1,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 1, ",", "2,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 1, ",", "3,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 1, ",", "4,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 1, ",", "5,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 1, ",", "6,")]))))

## forecast for year t+1 to be adjusted
p_dat_pred_t <- cbind(((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 2, ",", "1,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 2, ",", "2,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 2, ",", "3,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 2, ",", "4,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 2, ",", "5,")])),
  ((mod_res_obs[,paste0("Run", "[", n_yrs - age_min + 2, ",", "6,")]))))

#median(p_dat_obs_adj[,a-1])/median(p_dat_pred_adj[,a-1])

p_dat_pred_adj_a <- NULL
#adj_a <- NULL
for (a in 2:A){
  #a <- 3
  #adj_a[a] <- median(as.vector(p_dat_obs_adj[,a-1])/as.vector(p_dat_pred_adj[,a-1]))
  p_dat_pred_adj_a_temp <- as.vector(p_dat_pred_t[,a])*(as.vector(p_dat_obs_adj[,a-1])/as.vector(p_
  p_dat_pred_adj_a <- cbind(p_dat_pred_adj_a, p_dat_pred_adj_a_temp)

}

```



```

#adj <- rbind(adj,t(adj_a))
p_dat_pred_adj_a <- apply(p_dat_pred_adj_a,1,FUN = sum)

pred_esc_adj[f] <- round(median(p_dat_pred_adj_a))
#pred_esc_adj[f] <- median(apply(p_dat_pred_t,1,FUN = "sum"))

f <- f+1
c <- c+1
}#next forecast

pred_trs_mod <- pred_esc + 1#+ dat_harv_forecast$catch #you don't need to add catch in because it is
pred_trs_mod_adj <- pred_esc_adj #not adjusted because adjusted prediction comes from "Run" rather th

pred_trs <- cbind(pred_trs,pred_trs_mod)
pred_trs_adj <- cbind(pred_trs_adj,pred_trs_mod_adj)
#names(pred_trs) <- paste(models[n],"_", "pred_trs", sep = "")
}
colnames(pred_trs) <- models
colnames(pred_trs_adj) <- paste(models,"_", "sib_adjust", sep = "")
pred_trs_adj <- pred_trs_adj[-11,]

pred_trs<-data.frame(pred_trs,pred_trs_adj)
pred_trs<-pred_trs[-1,]

## compute model performance statistics
Error <- pred_trs - obs_trs[-1]
SE <- Error~2
PE <- Error/obs_trs[-1]
APE <- abs(PE)
LAR <- log(obs_trs/pred_trs)
RMSE <- apply(SE,2,function(x){sqrt(mean(x))})
MPE <- apply(PE,2,function(x){mean(x)})
MAPE <- apply(APE,2,function(x){mean(x)})
MSA <- apply(LAR,2,function(x){100*(exp(mean(abs(x))-1))})

model_selection <- data.frame(RMSE,MPE,MAPE,MSA)
weights<-apply(model_selection[,!colnames(model_selection)=="MPE"], 2,function(x) (1/x)/sum(1/x))
colnames(weights)<-paste0(colnames(weights),"_weight")
model_selection<-data.frame(model_selection,weights)
print(model_selection)

```

##	RMSE	MPE	MAPE	MSA	RMSE_weight	MAPE_weight
## IPM_BH_cov_MA1_AR1_age	1404.147	0.1454355	0.2115845	39.90132	0.3368552	0.3047165
## IPM_BH_cov_AR_resid_age	1411.751	0.1414614	0.2103704	46.96026	0.3350409	0.3064751
## IPM_BH_cov_MA1_AR1_age_sib_adjust	2967.527	0.3304070	0.3435246	60.49714	0.1593900	0.1876817
## IPM_BH_cov_AR_resid_age_sib_adjust	2803.530	0.3169427	0.3205606	63.56399	0.1687139	0.2011267
##	MSA_weight					
## IPM_BH_cov_MA1_AR1_age	0.3187785					
## IPM_BH_cov_AR_resid_age	0.2708606					
## IPM_BH_cov_MA1_AR1_age_sib_adjust	0.2102526					
## IPM_BH_cov_AR_resid_age_sib_adjust	0.2001083					

```

#sib adjust plot
cols<-brewer.pal(length(models)*2,"Spectral")
matplot(as.matrix(data.frame(pred_trs)),type="l",lty=1,col=c(cols,"grey40"),lwd=c(rep(2,length(models)*2),1),
axis(1,1:(n_forecasts-1),(yr_last-n_forecasts+2):(yr_last))
points(x=1:(n_forecasts-1),y=obs_trs[-1],cex=1.5,pch=20,col="red")
legend("topright",legend=c(rownames(model_selection),"Observed"),lty=c(rep(1,length(models)*2),NA),col=

```

