Laptop0 client 1

Physical   Config   **Desktop**   Programming   Attributes

Command Prompt   X

```
Ping request could not find host epicode.internal. Please check the name and try again.
C:\>ping epicode.internal

Pinging 192.168.1.4 with 32 bytes of data:

Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.1.4:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
C:\>ipconfig

FastEthernet0 Connection:(default port)

    Connection-specific DNS Suffix..:
    Link-local IPv6 Address.........: FE80::2E0:B0FF:FEB6:8162
    IPv6 Address....................: ::
    IPv4 Address....................: 192.168.1.13
    Subnet Mask.....................: 255.255.255.0
    Default Gateway.................:
                                     0.0.0.0

Bluetooth Connection:

    Connection-specific DNS Suffix..:
    Link-local IPv6 Address.........: ::
    IPv6 Address....................: ::
    IPv4 Address....................: 0.0.0.0
    Subnet Mask.....................: 0.0.0.0
    Default Gateway.................:
                                     0.0.0.0

C:\>ping epicode.internal

Pinging 192.168.1.4 with 32 bytes of data:

Reply from 192.168.1.4: bytes=32 time=1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.1.4:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\>
C:\>
```

☐ Top

Laptop1client 2

Physical   Config   **Desktop**   Programming   Attributes

Command Prompt   X

```
C:\>ping epicode.internal

Pinging 192.168.1.4 with 32 bytes of data:

Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.1.4:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
C:\>ping epicode.internal

Pinging 192.168.1.4 with 32 bytes of data:

Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time=2ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128
Reply from 192.168.1.4: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.1.4:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 2ms, Average = 0ms

C:\>ipconfig

FastEthernet0 Connection:(default port)

    Connection-specific DNS Suffix..:
    Link-local IPv6 Address.........: FE80::202:17FF:FE28:246A
    IPv6 Address....................: ::
    IPv4 Address....................: 192.168.1.15
    Subnet Mask.....................: 255.255.255.0
    Default Gateway.................:
                                     0.0.0.0

Bluetooth Connection:

    Connection-specific DNS Suffix..:
    Link-local IPv6 Address.........: ::
    IPv6 Address....................: ::
    IPv4 Address....................: 0.0.0.0
    Subnet Mask.....................: 0.0.0.0
    Default Gateway.................:
                                     0.0.0.0

C:\>
C:\>
```

☐ Top