



## Exercise 9.4: Use Labels to Manage Resources

1. Try to delete all Pods with the `system=secondary` label, in all namespaces.

```
student@cp:~$ kubectl delete pods -l system=secondary \
--all-namespaces
```

```
pod "nginx-one-74dd9d578d-fcpmv" deleted
pod "nginx-one-74dd9d578d-sts51" deleted
```

2. View the Pods again. New versions of the Pods should be running as the controller responsible for them continues.

```
student@cp:~$ kubectl -n accounting get pods
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-one-74dd9d578d-ddt5r	1/1	Running	0	1m
nginx-one-74dd9d578d-hfzml	1/1	Running	0	1m

3. We also gave a label to the deployment. View the deployment in the accounting namespace.

```
student@cp:~$ kubectl -n accounting get deploy --show-labels
```

NAME	READY	UP-TO-DATE	AVAILABLE	AGE	LABELS
nginx-one	2/2	2	2	10m	system=secondary

4. Delete the deployment using its label.

```
student@cp:~$ kubectl -n accounting delete deploy -l system=secondary
```

```
deployment.apps "nginx-one" deleted
```

5. Remove the label from the secondary node. Note that the syntax is a minus sign directly after the key you want to remove, or `system` in this case.

```
student@cp:~$ kubectl label node worker system-
```

```
node/worker labeled
```