

SparkCleaner: A data cleaning toolkits for Spark

Pei-Lun Liao
New York University
pll273@nyu.edu

Chia-Hsien Lin
New York University
chl566@nyu.edu

Shang-Hung Tsai
New York University
st3127@nyu.edu

ABSTRACT

Data cleaning becomes a challenge in data mining and machine learning tasks. In this paper, we propose SparkCleaner, a data cleaning toolkits running on Spark, to provide further solutions to data cleaning tasks. SparkCleaner provides advance cleaning features such as outlier detection, data scaling and text pattern searching and replacement.

1 INTRODUCTION

In recent years, as storage devices become cheaper, storing big data in thousands of computers is easier than before. People start thinking about how to extract useful information from the huge datasets. The term, Big Data, was created to describe this phenomenon[15]. As the result, data mining[11, 19] and machine learning[23] get popular nowadays. The quality of data is one of the key factors to successful data mining[3]. Hence, data cleaning becomes a challenge in the first step of data management and analysis[5, 12, 20].

To process huge dataset efficiently, distributed systems and parallel computing frameworks[6, 7, 24] were introduced. Spark[25] is one of the most popular open source projects for industry and academia. It is built on Hadoop[24] and provides a way to manage distributed memory. PySpark[17] is an extended library for Python programmers to work with Spark.

In the Python machine learning and data mining ecosystem, Pandas[16] is the most popular data management library. Pandas dataframe provides convenient ways to collect data and several data management methods for missing value filling, data indexing and data profiling. In PySpark SQL module, PySpark provides Pandas-like DataFrame to handle data indexing, data intergation, and simple data cleaning tasks such as missing value handling and duplication removing.

However, PySpark DataFrame does not support advance data processing features like outlier detection and data scaling. Although in PySpark ML module, we have several clustering and scaling algorithms, the intergation with PySpark DataFrame is not helpful. User has to go back and forth to handle their dataset. In this paper, we propose SparkCleaner, a data cleaning toolkits built on top of PySpark, that intergrates PySpark ML module to supports user friendly data processing features such as outlier detection and numerical data scaling. These features are important for the machine learning tasks and are supported in Scikit-Learn[18], a mainstream machine learning library, as well.

Furthermore, text data is another common data type in our storage. Text data is hard to process because of different languages, newly invented words, typos, abbreviations, urls and emoji etc. Although we have NLTK[1], a popular text cleaning library, there is no intergation with PySpark DataFrame. In this paper, we also intergate NLTK within our toolkits and provide customized tools for users to clean text easily.

The features of our library are summarized below.

- User friendly data cleaning toolkits built on PySpark
- Outlier detection and numerical data scaling
- Text processing such as url detection, punctuation removing, pattern searching and replacement.

2 RELATED WORK

There exists a number of open-source library for data cleaning and parallel data computing.

- Optimus[13] is a framework that can perform distributed data cleaning and preprocessing. This framework works well with Spark and its DataFrame can scale in big cluster. Optimus comes with helpful tools such as removing special characters and replacing null values.
- Dask[21] is another open-source library that supports parallel analytic computing. It provides scalable parallel data structures that extend interfaces like Pandas. At the same time, it offers low latency and high responsiveness.
- SparklingPandas[14] attempts to combine the power of Spark and Pandas to scale data analysis. It provides a Pandas-like API that is built using Spark's DataFrame class. Unfortunately, it only support spark v1.4 and Python 2.7, and its development has ended.

3 PROBLEM FORMULATION

In this paper, we focus on three major tasks, outlier detection, data scaling, and text pattern searching and replacement.

3.1 Outlier Detection

Outlier or anomalies detection is a challenging task in the filed of data cleaning[4]. In this paper, we simply define outlier as the data that is far away from data centroid. Hence, given a dataset X , a clustering algorithm A [19], a distance measurement d , and the user-defined threshold t , the outlier is simply defined as following.

$$outlier = \{x | x \in X, d(x, x_{A_X(x)}) > t\}$$

where $A_X(x)$ cluster x into a cluster given the dataset X and x_c is the centroid of cluster c .

3.2 Scaling and Normalization

Scaling and normalization are common preprocess in data cleaning. It is crucial to several machine learning models or optimization methods. Scaling increases the convergence speed and chance to find good optimal[2]. The scaling problem could be formulated as below. Given an one dimensional numerical dataset X , we provide a scaling method S such that scaled elements are bouned in same reasonable range $[a, b]$.

$$S_X(x) \in [a, b]$$

where $x \in X$ and $|a - b|$ should not be large.

To define the problem formally, we consider and implement several specific scaling methods.

- Standard scale

$$S(X) = \frac{X - \mu}{\sigma} \in \text{proper deviation range}$$

where μ is the mean of X and σ is the standard deviation of X

- Min-Max scale

$$S(X) = \frac{X - \min(X)}{\max(X) - \min(X)} \in [0.0, 1.0]$$

- Max-Abs scale

$$S(X) = \frac{X}{\max(X)} \in [-1.0, 1.0]$$

- P-norm Normalization

$$S(X) = \frac{X}{\|X\|_p} \in [-1.0, 1.0]$$

3.3 Pattern Searching and Replacment

Pattern searching and replacement is a common technique in cleaning text data. Given a string t and a regular expression[22] re , we replace the matched pattern with a user-defined string s . The replacement function R could be defined as following. Consider t as a concatenation of non-overlaped substrings $t = t_1 \dots t_n$.

$$R(t) = r(t_1) \dots r(t_i) \dots r(t_n)$$

$$r(t) = \begin{cases} s & \text{if } M \text{ accept } t \\ t & \text{otherwise} \end{cases}$$

such that M does not accept any substring of $R(t)$

where M is the generalized nondeterministic finite automaton[22] corresponding to the regular expression re . We do not define replacement order and simply ignore it.

4 METHODS, ARCHITECTURE AND DESIGN

In this project, we will to build our library on top of PySpark[17, 25]. We will handle RDD data structure and implement useful data cleaning fucntions in our library. The ways to do that are collecting common cleaning functions into library and customizing map functions to perform advanced cleaning task such as pattern searching and replacement with regular expression. We will survey the Pandas[16] and Scikit-Learn[18] libraries to find out key features and create Pandas-like and Scikit-Learn-like API to provide easy usage and seamless adaptation.

4.1 Outlier Detection

4.1.1 Design. Outlier detection is a common problem in data cleaning. Outliers affects the experiment results and can lead to false conclusions. The data cleaning library we develop provide user-friendly solution to this problem.

4.1.2 Methods. The data cleaning library uses K-Means clustering method to detect outliers. Users can specify the number of clusters to use based their knowledge about the dataset. The system will choose random initial values, and perform 20 iterations of updates. Finally, a summary of the clusterings will be generated, which includes cluster centers, cluster sizes, distances, etc. User can then filter out outliers in each cluster by specifying a minimum distance from the cluster center, and all data points that are beyond that distance will be removed from the dataset.

4.1.3 Architecture. The implementation of the outlier detection functionality integrates the PySpark ml package. It is based on the KMeans clustering module, and it is very efficient and scalable. In addition, our data cleaning library implements User Defined Functions to compute distance between data points and cluster centers, as well as other summary statistics. The architecture of this feature hides the complexity of K-Means clustering, while it exposes easily accessible APIs for users to remove outliers.

4.2 Scaling and Normalization

4.2.1 Design. Standardization of datasets is a common requirement for many machine learning algorithms, since objective functions will not work properly without scaling or normalization. Therefore, we provide several useful scaling functions and normalizing function. These functions can help standardize the specified columns and improve the performance of learning algorithms.

4.2.2 Methods. The `standard_scale()` function performs basic scaling on a particular column or a list of columns in a dataframe so that the values have unit standard deviation and/or zero mean. The `min_max_scale()` rescales columns to a user-defined range(e.g. [0, 1]) using min max scaling. Another scaling function `max_abs_scale()` transforms columns to range between -1 and 1 by dividing through the maximum absolute value in the columns. This operation does not shift/center the data, and thus does not destroy any sparsity. In addition, we provide `normalize()` function in our library. The `normalize` function can transform the given column(s) to have unit norm. The default p-norm value for normalization is 2.0, yet users can optionally specify the p-norm value.

4.2.3 Architecture. The implementation of the scaling and normalization functionality integrates the PySpark ml package as well. We include three the most commonly used scaling functions and one `normalize` function. The architecture and the API design is based on `scikit-learn`, the most popular machine learning library for the Python, so it is intuitive and easy to use.

5 EXPERIMENT

5.1 Dataset

Three datasets are chosen for the experiments. Each of them has different properties and can be used to test different aspects of the library. The summary of datasets could be found in table 1.

- 311 Service Requests[8] This dataset contains all 311 Service Requests since 2010. The majority of data has string type, including both categorical data (e.g. City, Status) and variable length data (e.g. Address, Description). This can be useful in testing the string-related features of the library.

Table 1: Selected dataset

	(Row, Col)	Size	Missing Value
311 Service Requests	(9M, 53)	6.01 GB	28%
Permit Issuance	(3M, 60)	1.43 GB	20%
Job Application Filings	(5M, 89)	2.88 GB	40%

- DOB Permit Issuance[9] The dataset consists of a list of permits for buildings in NYC issued by Department of Building. It has diverse data types, including categorical, string, numerical, and geographical data. Hence, it provides a good test case for the versatility of the library.
- DOB Job Application Filings[10] The dataset stores job applications filed through the Borough Offices in NYC. There are many columns containing numerical data, such as fee and number of stories. It can be used to test the data scaling and outlier detection features.

5.2 Evaluation

We will evaluate our project by comparing it against other existing open-source libraries, including Optimus[13], Dask[21], and SparklingPandas[14].

5.2.1 Features. We will compare our data cleaning features with previous works, particularly those frequently used functionality in data science such as null value handling, special character removal, duplicate detection, etc.

5.2.2 Performance. We will evaluate the performance of our library by measuring the time and space consumed and drawing comparison with existing libraries. This performance evaluation will show that this library is efficient and can be useful in production.

5.2.3 Usability. We might assess the usability of our library by doing a survey among a random group of users. We will compare the installation process and APIs provided and generate scores of user experience.

5.3 Result

6 CONCLUSIONS

Due to the lack of useful scalable data cleaning library on Spark, we propose PySpark, a scalable data cleaning library. We provide basic data cleaning features such as missing value handling, duplicated data removing and data scaling. Moreover, our library supports text cleaning feature with regular expression.

REFERENCES

- [1] Steven Bird, Ewan Klein, and Edward Loper. 2009. *Natural Language Processing with Python* (1st ed.). O'Reilly Media, Inc.
- [2] Stephen Boyd and Lieven Vandenberghe. 2004. *Convex Optimization*. Cambridge University Press, New York, NY, USA.
- [3] Li Cai and Yangyong Zhu. 2015. The Challenges of Data Quality and Data Quality Assessment in the Big Data Era. *Data Science Journal* 14, 2 (2015), 1–10. <https://doi.org/10.5334/dsj-2015-002>
- [4] Varun Chandola, Arindam Banerjee, and Vipin Kumar. 2009. Anomaly Detection: A Survey. *ACM Comput. Surv.* 41, 3, Article 15 (July 2009), 58 pages. <https://doi.org/10.1145/1541880.1541882>
- [5] Xu Chu, Ihab F. Ilyas, Sanjay Krishnan, and Jiannan Wang. 2016. Data Cleaning: Overview and Emerging Challenges. In *Proceedings of the 2016 International Conference on Management of Data (SIGMOD '16)*. ACM, New York, NY, USA, 2201–2206. <https://doi.org/10.1145/2882903.2912574>
- [6] Jeffrey Dean and Sanjay Ghemawat. 2008. MapReduce: Simplified Data Processing on Large Clusters. *Commun. ACM* 51, 1 (Jan. 2008), 107–113. <https://doi.org/10.1145/1327452.1327492>
- [7] Sanjay Ghemawat, Howard Gobioff, and Shun-Tak Leung. 2003. The Google File System. In *Proceedings of the Nineteenth ACM Symposium on Operating Systems Principles (SOSP '03)*. ACM, New York, NY, USA, 29–43. <https://doi.org/10.1145/945445.945450>
- [8] NYC government. 2018. NYC OpenData. (2018). <https://data.cityofnewyork.us/Social-Services/311-Service-Requests-from-2010-to-Present/erm2-nwe9>
- [9] NYC government. 2018. NYC OpenData. (2018). <https://data.cityofnewyork.us/Housing-Development/DOB-Permit-Issuance/ipu4-2q9a/data>
- [10] NYC government. 2018. NYC OpenData. (2018). <https://data.cityofnewyork.us/Housing-Development/DOB-Job-Application-Filings/ic3t-wcy2>
- [11] Jiawei Han, Micheline Kamber, and Jian Pei. 2011. *Data Mining: Concepts and Techniques* (3rd ed.). Morgan Kaufmann Publishers Inc., San Francisco, CA, USA.
- [12] Ihab F. Ilyas and Xu Chu. 2015. Trends in Cleaning Relational Data: Consistency and Deduplication. *Foundations and Trends in Databases* 5, 4 (2015), 281–393. <https://doi.org/10.1561/19000000045>
- [13] Iron. 2018. Optimus. (2018). <https://github.com/ironmussa/Optimus>
- [14] Holden Karau and Juliet Hougland. 2015. SparklingPandas. (2015). <https://github.com/sparklingpandas/sparklingpandas>
- [15] A. Katal, M. Wazid, and R. H. Goudar. 2013. Big data: Issues, challenges, tools and Good practices. In *2013 Sixth International Conference on Contemporary Computing (IC3)*. 404–409. <https://doi.org/10.1109/IC3.2013.6612229>
- [16] Wes McKinney. [n. d.]. pandas: a Foundational Python Library for Data Analysis and Statistics. ([n. d.]).
- [17] Amit Nandi. 2015. *Spark for Python Developers*. Packt Publishing.
- [18] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. 2011. Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research* 12 (2011), 2825–2830.
- [19] Anand Rajaraman and Jeffrey David Ullman. 2011. *Mining of Massive Datasets*. Cambridge University Press, New York, NY, USA.
- [20] Vijayshankar Raman and Joseph M. Hellerstein. 2001. Potter's Wheel: An Interactive Data Cleaning System. In *Proceedings of the 27th International Conference on Very Large Data Bases (VLDB '01)*. Morgan Kaufmann Publishers Inc., San Francisco, CA, USA, 381–390. <http://dl.acm.org/citation.cfm?id=645927.672045>
- [21] Matthew Rocklin. 2015. Dask: Parallel Computation with Blocked algorithms and Task Scheduling. In *Proceedings of the 14th Python in Science Conference*, Kathryn Huff and James Bergstra (Eds.). 130 – 136.
- [22] Michael Sipser. 1996. *Introduction to the Theory of Computation* (1st ed.). International Thomson Publishing.
- [23] Vladimir N. Vapnik. 1995. *The Nature of Statistical Learning Theory*. Springer-Verlag New York, Inc., New York, NY, USA.
- [24] Tom White. 2009. *Hadoop: The Definitive Guide* (1st ed.). O'Reilly Media, Inc.
- [25] Matei Zaharia, Mosharaf Chowdhury, Michael J. Franklin, Scott Shenker, and Ion Stoica. 2010. Spark: Cluster Computing with Working Sets. In *Proceedings of the 2Nd USENIX Conference on Hot Topics in Cloud Computing (HotCloud'10)*. USENIX Association, Berkeley, CA, USA, 10–10. <http://dl.acm.org/citation.cfm?id=1863103.1863113>