

Chapter 7: Synchronization Examples






Outline

- Explain the bounded-buffer synchronization problem
- Explain the readers-writers synchronization problem
- Explain and dining-philosophers synchronization problems
- Describe the tools used by Linux and Windows to solve synchronization problems.
- Illustrate how POSIX and Java can be used to solve process synchronization problems





Classical Problems of Synchronization

- Classical problems used to test newly-proposed synchronization schemes
 - Bounded-Buffer Problem
 - Readers and Writers Problem
 - Dining-Philosophers Problem





Readers-Writers Problem

- A data set is shared among a number of concurrent processes
 - **Readers** – only read the data set; they do ***not*** perform any updates
 - **Writers** – can both read and write
- Problem – allow multiple readers to read at the same time
 - Only one single writer can access the shared data at the same time
- Several variations of how readers and writers are considered – all involve some form of priorities





Readers-Writers Problem (Cont.)

- Shared Data
 - Data set
 - Semaphore **rw_mutex** initialized to 1
 - Semaphore **mutex** initialized to 1
 - Integer **read_count** initialized to 0





Readers-Writers Problem (Cont.)

- The structure of a writer process

```
while (true) {  
    down(rw_mutex);  
  
    ...  
    /* writing is performed */  
  
    ...  
    up(rw_mutex);  
}
```





Readers-Writers Problem (Cont.)

- The structure of a reader process

```
while (true) {  
    down(mutex);  
    read_count++;  
    if (read_count == 1) /* first reader */  
        down(rw_mutex);  
    up(mutex);  
    ...  
    /* reading is performed */  
    ...  
    down(mutex);  
    read_count--;  
    if (read_count == 0) /* last reader */  
        up(rw_mutex);  
    up(mutex);  
}
```





Readers-Writers Problem Variations

- The solution in previous slide can result in a situation where a writer process never writes. It is referred to as the “First reader-writer” problem.
- The “Second reader-writer” problem is a variation the first reader-writer problem that state:
 - Once a writer is ready to write, no “newly arrived reader” is allowed to read.
- Both the first and second may result in starvation, leading to even more variations
- Problem is solved on some systems by kernel providing reader-writer locks





Dining-Philosophers Problem

- N philosophers' sit at a round table with a bowl of rice in the middle.



- They spend their lives alternating thinking and eating.
- They do not interact with their neighbors.
- Occasionally try to pick up 2 chopsticks (one at a time) to eat from bowl
 - Need both to eat, then release both when done
- In the case of 5 philosophers, the shared data
 - ▶ Bowl of rice (data set)
 - ▶ Semaphore chopstick [5] initialized to 1





Dining-Philosophers Problem Algorithm

- Semaphore Solution
- The structure of Philosopher i :

```
while (true){  
    down (chopstick[i] );  
    down (chopStick[ (i + 1) % 5] );  
  
    /* eat for awhile */  
  
    up (chopstick[i] );  
    up (chopstick[ (i + 1) % 5] );  
  
    /* think for awhile */  
  
}
```

- What is the problem with this algorithm?





Solutie corecta cu semafoare

```
#define THINKING      0
#define HUNGRY        1
#define EATING        2

int state[N];
semaphore_t  mutex = {1};
semaphore_t  ph[N]; // toate initializate cu 0
void philosopher(int i) {
    while(true) {
        think();
        take_forks(i);
        eat();
        put_forks(i);
    }
}
```





Solutie corecta cu semafoare

```
void take_forks(int i) {  
    down(mutex);  
    state[i] = HUNGRY;  
    test(i);  
    up(mutex);  
    down(ph[i]);  
}
```

```
void put_forks(int i) {  
    down(mutex);  
    state[i] = THINKING;  
    test((i - 1) % N);  
    test((i + 1) % N);  
    up(mutex);  
}
```

```
void test(int i) {  
    if(state[i] == HUNGRY &&  
        state[(i-1)%N] != EATING) &&  
        state[(i+1)%N] != EATING)  
    {  
        state[i] = EATING;  
        up(ph[i]);  
    }  
}
```





Monitor Solution to Dining Philosophers

```
monitor DiningPhilosophers
{
    enum {THINKING; HUNGRY, EATING} state [5];
    condition self [5];

    void pickup (int i) {
        state[i] = HUNGRY;
        test(i);
        if (state[i] != EATING) self[i].wait;
    }

    void putdown (int i) {
        state[i] = THINKING;
        // test left and right neighbors
        test((i + 4) % 5);
        test((i + 1) % 5);
    }
}
```





Solution to Dining Philosophers (Cont.)

```
void test (int i) {
    if ((state[(i + 4) % 5] != EATING) &&
        (state[i] == HUNGRY) &&
        (state[(i + 1) % 5] != EATING) ) {
        state[i] = EATING ;
        self[i].signal () ;
    }
}

initialization_code() {
    for (int i = 0; i < 5; i++)
        state[i] = THINKING;
}
}
```





Solution to Dining Philosophers (Cont.)

- Each philosopher “i” invokes the operations **pickup()** and **putdown()** in the following sequence:

```
DiningPhilosophers.pickup(i) ;
```

```
/** EAT **/
```

```
DiningPhilosophers.putdown(i) ;
```

- No deadlock, but starvation is possible





POSIX Semaphores

- POSIX provides two versions – **named** and **unnamed**.
- Named semaphores can be used by unrelated processes, unnamed cannot.





POSIX Named Semaphores

- Creating an initializing the semaphore:

```
#include <semaphore.h>
sem_t *sem;
```

```
/* Create the semaphore and initialize it to 1 */
sem = sem_open("SEM", O_CREAT, 0666, 1);
```

- Another process can access the semaphore by referring to its name **SEM**.
- Acquiring and releasing the semaphore:

```
/* acquire the semaphore */
sem_wait(sem);
```

```
/* critical section */
```

```
/* release the semaphore */
sem_post(sem);
```





POSIX Unnamed Semaphores

- Creating and initializing the semaphore:

```
#include <semaphore.h>
sem_t sem;

/* Create the semaphore and initialize it to 1 */
sem_init(&sem, 0, 1);
```

- Acquiring and releasing the semaphore:

```
/* acquire the semaphore */
sem_wait(&sem);

/* critical section */

/* release the semaphore */
sem_post(&sem);
```





POSIX Condition Variables

- Since POSIX is typically used in C/C++ and these languages do not provide a monitor, POSIX condition variables are associated with a POSIX mutex lock to provide mutual exclusion: Creating and initializing the condition variable:

```
pthread_mutex_t mutex;  
pthread_cond_t cond_var;  
  
pthread_mutex_init(&mutex, NULL);  
pthread_cond_init(&cond_var, NULL);
```





POSIX Condition Variables

- Thread waiting for the condition `a == b` to become true:

```
pthread_mutex_lock(&mutex);  
while (a != b)  
    pthread_cond_wait(&cond_var, &mutex);  
  
pthread_mutex_unlock(&mutex);
```

- Thread signaling another thread waiting on the condition variable:

```
pthread_mutex_lock(&mutex);  
a = b;  
pthread_cond_signal(&cond_var);  
pthread_mutex_unlock(&mutex);
```





Producator-consumator POSIX

```
1 #include <stdio.h>
2 #include <pthread.h>
3
4 #define ITEMS      8
5 #define BUFFER_SIZE 4
6 int buffer[BUFFER_SIZE];
7
8 void *producer(void*);
9 void *consumer(void*);
10
11 int spaces, items, tail;
12 pthread_cond_t space, item;
13 pthread_mutex_t buffer_mutex;
14
15 int main()
16 {
17     pthread_t producer_thread, consumer_thread;
18     void *thread_return;
19     int result;
20
21     spaces = BUFFER_SIZE;
22     items = 0;
23     tail = 0;
24
25     pthread_mutex_init(&buffer_mutex, NULL);
26     pthread_cond_init(&space, NULL);
27     pthread_cond_init(&item, NULL);
28
29     if(pthread_create(&producer_thread, NULL, producer, NULL) ||
30        pthread_create(&consumer_thread, NULL, consumer, NULL))
31         exit(1);
32
33     if(pthread_join(producer_thread, &thread_return))
34         exit(1);
35     else
36         printf("producer returns with %d\n", (int)thread_return);
37
38     if(pthread_join(consumer_thread, &thread_return))
39         exit(1);
40     else
41         printf("consumer returns with %d\n", (int)thread_return);
42     exit(0);
43 }
44
```





Prodicator-consumator POSIX

```
1 void *producer(void *arg)
2 {
3     int i;
4
5     for(i = 0; i < ITEMS; i++)
6     {
7         pthread_mutex_lock(&buffer_mutex);
8         while(spaces == 0)
9             pthread_cond_wait(&space, &buffer_mutex);
10        buffer[(tail + items) % BUFFER_SIZE] = i;
11        items += 1;
12        spaces -= 1;
13        printf("producer puts %d\n", i);
14        pthread_mutex_unlock(&buffer_mutex);
15        pthread_cond_signal(&item);
16    }
17    pthread_exit(0);
18    return (void*)0;
19 }
20
21 void *consumer(void *arg)
22 {
23     int i, b;
24
25     for(i = 0; i < ITEMS; i++)
26     {
27         pthread_mutex_lock(&buffer_mutex);
28         while(items == 0)
29             pthread_cond_wait(&item, &buffer_mutex);
30        b = buffer[tail % BUFFER_SIZE];
31        tail += 1;
32        items -= 1;
33        spaces += 1;
34        printf("consumer gets %d\n", b);
35        pthread_mutex_unlock(&buffer_mutex);
36        pthread_cond_signal(&space);
37    }
38    pthread_exit(0);
39    return (void*)0;
40 }
```





Kernel Synchronization - Windows


- Uses interrupt masks to protect access to global resources on uniprocessor systems
- Uses **spinlocks** on multiprocessor systems
 - Spinlocking-thread will never be preempted
- Also provides **dispatcher objects** user-land which may act mutexes, semaphores, events, and timers
 - **Events**
 - ▶ An event acts much like a condition variable
 - Timers notify one or more thread when time expired
 - Dispatcher objects either **signaled-state** (object available) or **non-signaled state** (thread will block)





Kernel Synchronization - Windows

- Mutex dispatcher object





Linux Synchronization

- Linux:
 - Prior to kernel Version 2.6, disables interrupts to implement short critical sections
 - Version 2.6 and later, fully preemptive
- Linux provides:
 - Semaphores
 - Atomic integers
 - Spinlocks
 - Reader-writer versions of both
- On single-CPU system, spinlocks replaced by enabling and disabling kernel preemption





Linux Synchronization

- Atomic variables

`atomic_t` is the type for atomic integer

- Consider the variables

```
atomic_t counter;  
int value;
```

<i>Atomic Operation</i>	<i>Effect</i>
<code>atomic_set(&counter, 5);</code>	<code>counter = 5</code>
<code>atomic_add(10, &counter);</code>	<code>counter = counter + 10</code>
<code>atomic_sub(4, &counter);</code>	<code>counter = counter - 4</code>
<code>atomic_inc(&counter);</code>	<code>counter = counter + 1</code>
<code>value = atomic_read(&counter);</code>	<code>value = 12</code>





Sincronizare in Solaris

- lock-uri adaptive (adaptive locks), variabile de conditie, semafoare, reader-writer locks, turnstiles
- lock-uri adaptive
 - folosite pt sectiuni critice scurte (cateva sute de instructiuni)
 - comportament polimorf spinlock-semafor
 - daca un thread vrea acces la date protejate de un lock detinut de un alt thread care ruleaza pe alt CPU, lock-ul se comporta ca un spinlock
 - daca lock-ul e detinut de un thread care nu ruleaza momentan pe nici un procesor, threadul care incearca sa obtina lock-ul va fi pus in stare dormanta (sleep), i.e., lock-ul se comporta ca un semafor
 - pe un sistem uniprocessor, cand un thread incearca sa obtina un lock detinut de alt thread, comportamentul lock-ului e intotdeauna de tip semafor





POSIX Synchronization

- POSIX API provides
 - mutex locks
 - semaphores
 - condition variable
- Widely used on UNIX, Linux, and macOS





POSIX Mutex Locks

- Creating and initializing the lock

```
#include <pthread.h>
```

```
pthread_mutex_t mutex;
```

```
/* create and initialize the mutex lock */  
pthread_mutex_init(&mutex, NULL);
```

- Acquiring and releasing the lock

```
/* acquire the mutex lock */  
pthread_mutex_lock(&mutex);
```

```
/* critical section */
```

```
/* release the mutex lock */  
pthread_mutex_unlock(&mutex);
```





Transactional Memory

- Consider a function `update()` that must be called atomically. One option is to use mutex locks:

```
void update ()
{
    acquire();

    /* modify shared data */

    release();
}
```

- A **memory transaction** is a sequence of read-write operations to memory that are performed atomically. A transaction can be completed by adding `atomic{S}` which ensure statements in `S` are executed atomically:

```
void update ()
{
    atomic {
        /* modify shared data */
    }
}
```





Memorie tranzactionala

- software transactional memory, Herlihy & Moss 1993
- am vazut deja ex. LL/SC
- exploateaza ideea de tranzactii din baze de date (v. proprietati ACID) si controlul optimist al concurentei
- un thread termina modificarile operate pe o zona de memorie partajata fara a se coordona cu alte threaduri
- se inregistreaza fiecare operatie de citire/scriere intr-un log
- la finalul tranzactiei se incearca operatia de *commit*
 - daca reuseste (i.e., nici o alta tranzactie nu a apucat sa faca un commit reusit intre timp), tranzactia e validata si modificarile devin permanente
 - daca esueaza, tranzactia e abandonata (aborted) si se re-executa de la inceput pana reuseste (*transaction roll-back*)
- beneficiu major: grad crescut de concurenta, thread-urile nu au nevoie sa se sincronizeze prin lock-uri la accesul memoriei partajate





Suport HW pt. memorie tranzactionala

- ex. Intel TSX (Transactional Synchronization Extension), extensie ISA x86, microarhitectura Haswell (2013)
- accesibila prin intermediul a doua interfete
 - HLE (Hardware Lock Elision) – backward compatibility
 - RTM (Restricted Transactional Memory)
- HLE adauga doua prefixuri de instr. XACQUIRE & XRELEASE
 - se pot folosi doar pt anumite instructiuni care trebuie prefixate explicit cu LOCK
 - permite executia optimista a sectiunii critice sarind scrierea lock-ului, a.i. acesta apare liber pt alte threaduri
 - o tranzactie esuata determina reluarea operatiei de la instructiunea prefixata cu XACQUIRE





Suport HW pt. memorie tranzactionala

- RTM adauga la ISA trei noi instructiuni
 - XBEGIN – marcheaza inceputul zonei de memorie tranzactionala
 - XEND - marcheaza sfarsitul zonei de memorie tranzactionala
 - XABORT – abandoneaza explicit o tranzactie
 - esecul tranzactiei redirecteaza executia catre codul specificat de instr. XBEGIN, iar codul de eroare e stocat in registrul EAX
- instructiunea XTEST permite testarea starii procesorului (este sau nu in mijlocul executiei unei regiuni de memorie tranzactionala)





RTM elision pt. pthread_mutex_lock

```
void elided_lock_wrapper(lock) {  
    if(_xbegin() == _XBEGIN_STARTED) { // start tranzactie  
        if(lock e liber)  
            return; // executa SC in tranzactie  
        _xabort(0xff); // abandoneaza tranzactia  
    }  
    obtine lock  
}  
  
void elided_unlock_wrapper(lock) {  
    if (lock e liber)  
        _xend(); // comite tranzactia  
    else  
        elibereaza lock;  
}
```





Java Synchronization

- Java provides rich set of synchronization features:
 - Java monitors
 - Reentrant locks
 - Semaphores
 - Condition variables





Java Monitors

- Every Java object has associated with it a single lock.
- If a method is declared as **synchronized**, a calling thread must own the lock for the object.
- If the lock is owned by another thread, the calling thread must wait for the lock until it is released.
- Locks are released when the owning thread exits the **synchronized** method.





Bounded Buffer – Java Synchronization

```
public class BoundedBuffer<E>
{
    private static final int BUFFER_SIZE = 5;

    private int count, in, out;
    private E[] buffer;

    public BoundedBuffer() {
        count = 0;
        in = 0;
        out = 0;
        buffer = (E[]) new Object[BUFFER_SIZE];
    }

    /* Producers call this method */
    public synchronized void insert(E item) {
        /* See Figure 7.11 */
    }


    /* Consumers call this method */
    public synchronized E remove() {
        /* See Figure 7.11 */
    }
}
```





Java Synchronization


- A thread that tries to acquire an unavailable lock is placed in the object's **entry set**:





Java Synchronization

- Similarly, each object also has a **wait set**.
- When a thread calls **wait()**:
 1. It releases the lock for the object
 2. The state of the thread is set to blocked
 3. The thread is placed in the wait set for the object





Java Synchronization

- A thread typically calls `wait()` when it is waiting for a condition to become true.
- How does a thread get notified?
- When a thread calls `notify()`:
 1. An arbitrary thread T is selected from the wait set
 2. T is moved from the wait set to the entry set
 3. Set the state of T from blocked to runnable.
- T can now compete for the lock to check if the condition it was waiting for is now true.





Bounded Buffer – Java Synchronization

```
/* Producers call this method */
public synchronized void insert(E item) {
    while (count == BUFFER_SIZE) {
        try {
            wait();
        }
        catch (InterruptedException ie) { }
    }

    buffer[in] = item;
    in = (in + 1) % BUFFER_SIZE;
    count++;

    notify();
}
```





Bounded Buffer – Java Synchronization

```
/* Consumers call this method */
public synchronized E remove() {
    E item;

    while (count == 0) {
        try {
            wait();
        }
        catch (InterruptedException ie) { }
    }

    item = buffer[out];
    out = (out + 1) % BUFFER_SIZE;
    count--;

    notify();

    return item;
}
```





Java Reentrant Locks

- Similar to mutex locks
- The **finally** clause ensures the lock will be released in case an exception occurs in the **try** block.

```
Lock key = new ReentrantLock();

key.lock();
try {
    /* critical section */
}
finally {
    key.unlock();
}
```





Java Semaphores

- Constructor:

```
Semaphore(int value);
```

- Usage:

```
Semaphore sem = new Semaphore(1);

try {
    sem.acquire();
    /* critical section */
}
catch (InterruptedException ie) { }
finally {
    sem.release();
}
```





Java Condition Variables

- Condition variables are associated with an **ReentrantLock**.
- Creating a condition variable using **newCondition()** method of **ReentrantLock**:

```
Lock key = new ReentrantLock();  
Condition condVar = key.newCondition();
```

- A thread waits by calling the **await()** method, and signals by calling the **signal()** method.





Java Condition Variables

- Example:
- Five threads numbered 0 .. 4
- Shared variable `turn` indicating which thread's turn it is.
- Thread calls `doWork()` when it wishes to do some work. (But it may only do work if it is their turn.
- If not their turn, wait
- If their turn, do some work for awhile
- When completed, notify the thread whose turn is next.
- Necessary data structures:

```
Lock lock = new ReentrantLock();  
Condition[] condVars = new Condition[5];  
  
for (int i = 0; i < 5; i++)  
    condVars[i] = lock.newCondition();
```





Java Condition Variables

```
/* threadNumber is the thread that wishes to do some work */
public void doWork(int threadNumber)
{
    lock.lock();

    try {
        /**
         * If it's not my turn, then wait
         * until I'm signaled.
         */
        if (threadNumber != turn)
            condVars[threadNumber].await();

        /**
         * Do some work for awhile ...
         */

        /**
         * Now signal to the next thread.
         */
        turn = (turn + 1) % 5;
        condVars[turn].signal();
    }
    catch (InterruptedException ie) { }
    finally {
        lock.unlock();
    }
}
```





Alternative Approaches

- Transactional Memory
- OpenMP
- Functional Programming Languages





OpenMP

- OpenMP is a set of compiler directives and API that support parallel programming.

```
void update(int value)
{
    #pragma omp critical
    {
        count += value
    }
}
```

- The code contained within the `#pragma omp critical` directive is treated as a critical section and performed atomically.





Functional Programming Languages

- Functional programming languages offer a different paradigm than procedural languages in that they do not maintain state.
- Variables are treated as immutable and cannot change state once they have been assigned a value.
- There is increasing interest in functional languages such as Erlang and Scala for their approach in handling data races.



End of Chapter 7

