


Interactive Computer Graphics: Lecture 11

Ray tracing (cont.)


Ray tracing - Summary




Graphics Lecture 11: Slide 2

Ray tracing - Summary

```
trace ray
  Intersect all objects
  color = ambient term
  For every light
    cast shadow ray
    col += local shading term
  If mirror
    col += k_refl * trace reflected ray
  If transparent
    col += k_trans * trace transmitted ray
```




Ray tracing - Summary



```
→ trace ray  
    Intersect all objects  
    color = ambient term  
    For every light  
        cast shadow ray  
        col += local shading term  
    If mirror  
        col += k_refl * trace reflected ray  
    If transparent  
        col += k_trans * trace transmitted ray
```

Ray tracing - Summary




R_i reflected ray

L_i shadow ray

T_i transmitted (refracted) ray

secondary rays

Graphi




Intersection calculations

- For each ray we must calculate all possible intersections with each object inside the viewing volume
- For each ray we must find the nearest intersection point
- We can define our scene using
 - Solid models
 - sphere
 - cylinder
 - Surface models
 - plane
 - triangle
 - polygon

Rays

- Rays are parametric lines
- Rays can be defined an
 - origin \mathbf{p}_0
 - direction \mathbf{d}
- Equation of ray:

$$\mathbf{p}(\mu) = \mathbf{p}_0 + \mu\mathbf{d}$$



Ray tracing: Intersection calculations

- The coordinates of any point along each primary ray are given by:


$$\mathbf{p} = \mathbf{p}_0 + \mu \mathbf{d}$$

- \mathbf{p}_0 is the current pixel on the viewing plane.
- \mathbf{d} is the direction vector and can be obtained from the position of the pixel on the viewing plane \mathbf{p}_0 and the viewpoint \mathbf{p}_v :

$$\mathbf{d} = \frac{\mathbf{p}_0 - \mathbf{p}_v}{|\mathbf{p}_0 - \mathbf{p}_v|}$$


Ray tracing: Intersection calculations

- The viewing ray can be parameterized by μ :
 - $\mu > 0$ denotes the part of the ray behind the viewing plane
 - $\mu < 0$ denotes the part of the ray in front of the viewing plane
 - For any visible intersection point $\mu > 0$



Graphics Lecture 11: Slide 9

Intersection calculations: Spheres



- For any point on the surface of the sphere

$$|q - p_s|^2 - r^2 = 0$$

- where r is the radius of the sphere

Graphics Lecture 11: Slide 10

Intersection calculations: Spheres

- To test whether a ray intersects a surface we can substitute for \mathbf{q} using the ray equation:

$$|\mathbf{p}_0 + \mu\mathbf{d} - \mathbf{p}_s|^2 - r^2 = 0$$

- Setting $\Delta\mathbf{p} = \mathbf{p}_0 - \mathbf{p}_s$ and expanding the dot product produces the following quadratic equation:

$$\mu^2 + 2\mu(\mathbf{d} \cdot \Delta\mathbf{p}) + |\Delta\mathbf{p}|^2 - r^2 = 0$$

Intersection calculations: Spheres


- The quadratic equation has the following solution:

$$\mu = -\mathbf{d} \cdot \Delta\mathbf{p} \pm \sqrt{(\mathbf{d} \cdot \Delta\mathbf{p})^2 - |\Delta\mathbf{p}|^2 + r^2}$$

- Solutions:
 - if the quadratic equation has no solution, the ray does not intersect the sphere
 - if the quadratic equation has two solutions ($\mu_1 < \mu_2$):
 - μ_1 corresponds to the point at which the rays enters the sphere
 - μ_2 corresponds to the point at which the rays leaves the sphere

Precision Problems

- In ray tracing, the origin of (secondary) rays is often on the surface of objects
 - Theoretically, $\mu = 0$ for these rays
 - Practically, calculation imprecision creeps in, and the origin of the new ray is slightly beneath the surface
- Result: the surface area is shadowing itself



Graphics Lecture 11: Slide 13

ε to the rescue ...

- Check if t is within some epsilon tolerance:
 - if $\text{abs}(\mu) < \varepsilon$
 - point is on the sphere
 - else
 - point is inside/outside
 - Choose the ε tolerance empirically
- Move the intersection point by epsilon along the surface normal so it is outside of the object
- Check if point is inside/outside surface by checking the sign of the implicit (sphere etc.) equation

Intersection calculations: Cylinders

- A cylinder can be described by
 - a position vector \mathbf{p}_1 describing the first end point of the long axis of the cylinder
 - a position vector \mathbf{p}_2 describing the second end point of the long axis of the cylinder
 - a radius r
- The axis of the cylinder can be written as $\Delta\mathbf{p} = \mathbf{p}_1 - \mathbf{p}_2$ and can be parameterized by $0 \leq \alpha \leq 1$


Intersection calculations: Cylinders

- To calculate the intersection of the cylinder with the ray:

$$\mathbf{p}_1 + \alpha \Delta \mathbf{p} + \mathbf{q} = \mathbf{p}_0 + \mu \mathbf{d}$$

- Since $\mathbf{q} \cdot \Delta \mathbf{p} = 0$ we can write

$$\alpha(\Delta \mathbf{p} \cdot \Delta \mathbf{p}) = \mathbf{p}_0 \cdot \Delta \mathbf{p} + \mu \mathbf{d} \cdot \Delta \mathbf{p} - \mathbf{p}_1 \cdot \Delta \mathbf{p}$$



Intersection calculations: Cylinders

- Solving for α yields:

$$\alpha = \frac{\mathbf{p}_0 \cdot \Delta \mathbf{p} + \mu \mathbf{d} \cdot \Delta \mathbf{p} - \mathbf{p}_1 \cdot \Delta \mathbf{p}}{\Delta \mathbf{p} \cdot \Delta \mathbf{p}}$$

- Substituting we obtain:

$$\mathbf{q} = \mathbf{p}_0 + \mu \mathbf{d} - \mathbf{p}_1 - \left(\frac{\mathbf{p}_0 \cdot \Delta \mathbf{p} + \mu \mathbf{d} \cdot \Delta \mathbf{p} - \mathbf{p}_1 \cdot \Delta \mathbf{p}}{\Delta \mathbf{p} \cdot \Delta \mathbf{p}} \right) \Delta \mathbf{p}$$

Intersection calculations: Cylinders

- Using the fact that $\mathbf{q} \cdot \mathbf{q} = r^2$ we can use the same approach as before to the quadratic equation for μ :

$$r^2 = \left(\mathbf{p}_0 + \mu \mathbf{d} - \mathbf{p}_1 - \left(\frac{\mathbf{p}_0 \cdot \Delta \mathbf{p} + \mu \mathbf{d} \cdot \Delta \mathbf{p} - \mathbf{p}_1 \cdot \Delta \mathbf{p}}{\Delta \mathbf{p} \cdot \Delta \mathbf{p}} \right) \Delta \mathbf{p} \right)^2$$

- If the quadratic equation has no solution:
no intersection
- If the quadratic equation has two solutions:
intersection

Intersection calculations: Cylinders

- Assuming that $\mu_1 \leq \mu_2$ we can determine two solutions:

$$\alpha_1 = \frac{\mathbf{p}_0 \cdot \Delta \mathbf{p} + \mu_1 \mathbf{d} \cdot \Delta \mathbf{p} - \mathbf{p}_1 \cdot \Delta \mathbf{p}}{\Delta \mathbf{p} \cdot \Delta \mathbf{p}}$$

$$\alpha_2 = \frac{\mathbf{p}_0 \cdot \Delta \mathbf{p} + \mu_2 \mathbf{d} \cdot \Delta \mathbf{p} - \mathbf{p}_1 \cdot \Delta \mathbf{p}}{\Delta \mathbf{p} \cdot \Delta \mathbf{p}}$$

- If the value of α_1 is between 0 and 1 the intersection is on the outside surface of the cylinder
- If the value of α_2 is between 0 and 1 the intersection is on the inside surface of the cylinder

Intersection calculations: Plane

- Objects are often described by geometric primitives such as
 - triangles
 - planar quads
 - planar polygons
- To test intersections of the ray with these primitives we must test whether the ray will intersect the plane defined by the primitive

Intersection calculations: Plane

- The intersection of a ray with a plane is given by


$$\mathbf{p}_1 + \mathbf{q} = \mathbf{p}_0 + \mu \mathbf{d}$$

- where \mathbf{p}_1 is a point in the plane.
Subtracting \mathbf{p}_1 and multiplying with the normal of the plane \mathbf{n} yields:

$$\mathbf{q} \cdot \mathbf{n} = 0 = (\mathbf{p}_0 - \mathbf{p}_1) \cdot \mathbf{n} + \mu \mathbf{d} \cdot \mathbf{n}$$

- Solving for μ yields:


$$\mu = -\frac{(\mathbf{p}_0 - \mathbf{p}_1) \cdot \mathbf{n}}{\mathbf{d} \cdot \mathbf{n}}$$



Intersection calculations: Triangles

- To calculate intersections:
 - test whether triangle is front facing
 - test whether plane of triangle intersects ray
 - test whether intersection point is inside triangle
- If the triangle is front facing:

$$\mathbf{d} \cdot \mathbf{n} < 0$$



Intersection calculations: Triangles

- To test whether plane of triangle intersects ray

- calculate equation of the plane using

$$\mathbf{p}_2 - \mathbf{p}_1 = \mathbf{a}$$


$$\mathbf{p}_3 - \mathbf{p}_1 = \mathbf{b}$$

- calculate intersections with plane as before

$$\mathbf{n} = \mathbf{a} \times \mathbf{b}$$

- To test whether intersection point is inside triangle:

$$\mathbf{q} = \alpha \mathbf{a} + \beta \mathbf{b}$$



Intersection calculations: Triangles

- A point is inside the triangle if

$$0 \leq \alpha \leq 1$$

$$0 \leq \beta \leq 1$$

$$\alpha + \beta \leq 1$$

- Calculate α and β by taking the dot product with \mathbf{a} and \mathbf{b} :

$$\alpha = \frac{(\mathbf{b} \cdot \mathbf{b})(\mathbf{q} \cdot \mathbf{a}) - (\mathbf{a} \cdot \mathbf{b})(\mathbf{q} \cdot \mathbf{b})}{(\mathbf{a} \cdot \mathbf{a})(\mathbf{b} \cdot \mathbf{b}) - (\mathbf{a} \cdot \mathbf{b})^2}$$

$$\beta = \frac{\mathbf{q} \cdot \mathbf{b} - \alpha(\mathbf{a} \cdot \mathbf{b})}{\mathbf{b} \cdot \mathbf{b}}$$

Intersection calculations: Triangles

- algorithm by **Möller and Trumbore**:
- translate the origin of the ray and then change the base of that vector which yields parameter vector (t, u, v)
- t is the distance to the plane in which the triangle lies
- (u, v) are barycentric coordinates inside the triangle
- plane equation need not be computed on the fly nor be stored

Intersection calculations: Triangles

```
1 bool triangle_intersection( vec3 v1,
2                             vec3 v2,
3                             vec3 v3, // Triangle vertices
4                             vec3 origin, //Ray origin
5                             vec3 ray_dir, //Ray direction
6                             float* out )
7
8 //Find vectors for two edges sharing v1
9 vec3 edge1 = v2-v1;
10 vec3 edge2 = v3-v1;
11
12 //Begin calculating determinant - also used to calculate u parameter
13 vec3 p = cross(ray_dir, edge2)
14
15 //if determinant is near zero, ray lies in plane of triangle or ray
16 //is parallel to plane of triangle
17 float det = dot(edge1, p);
18
19 if(det > -EPSILON && det < EPSILON)
20 return false;
21
22 float inv_det = 1.f / det;
23
24 //calculate distance from v1 to ray origin
25 vec3 t = origin-v1;
```

Intersection calculations: Triangles

```
27 //Calculate u parameter and test bound
28 float u = dot(t, p) * inv_det;
29
30 //The intersection lies outside of the triangle
31 if(u < 0.f || u > 1.f)
32 return false;
33
34 //Prepare to test v parameter
35 vec3 q = cross(t, edge1);
36
37 float v = dot(ray_dir, q) * inv_det;
38 //The intersection lies outside of the triangle
39 if(v < 0.f || u + v > 1.f)
40 return false;
41
42 float mu = dot(edge2, q) * inv_det;
43
44 if(t > EPSILON) { //ray intersection
45 *out = mu;
46 return true;
```

Ray tracing: Pros and cons


- Pros:
 - Easy to implement
 - Extends well to global illumination
 - shadows
 - reflections / refractions
 - multiple light bounces
 - atmospheric effects
- Cons:
 - Speed! (seconds per frame, not frames per second)

Speedup Techniques

- Why is ray tracing slow? How to improve?
 - Too many objects, too many rays
 - Reduce ray-object intersection tests
 - Many techniques!

Acceleration of Ray Casting


- Goal: Reduce the number of ray/primitive intersections



Graphics Lecture 11: Slide 30

Conservative Bounding Region

- First check for an intersection with a conservative bounding region
- Early reject




Graphics Lecture 11: Slide 31

Bounding Regions


- What makes a good bounding region?

Conservative Bounding Regions




Graphics Lecture 11: Slide 33

Regular Grid




Create Grid

- Find bounding box of scene
- Choose grid resolution (n_x, n_y, n_z)
- $grid_x$ need not = $grid_y$




Insert Primitives into Grid

- Primitives that overlap multiple cells?
- Insert into multiple cells (use pointers)



For Each Cell Along a Ray


- Does the cell contain an intersection?
 - Yes: return closest intersection
 - No: continue



Graphics Lecture 11: Slide 37

Preventing Repeated Computation


- Perform the computation once, "mark" the object
- Don't re-intersect marked objects



Graphics Lecture 11: Slide 38

Don't Return Distant Intersections


- If intersection t is not within the cell range, continue (there may be something closer)




Graphics Lecture 11: Slide 39

Adaptive Grids

- Subdivide until each cell contains no more than n elements, or maximum depth d is reached



Nested Grids




Octree/(Quadtree)


Graphics Lecture 11: Slide 40

Primitives in an Adaptive Grid

- Can live at intermediate levels, or be pushed to lowest level of grid





Octree/(Quadtree)



Graphics Lecture 11: Slide 41

Binary Space Partition (BSP) Tree


- Recursively partition space by planes
- Every cell is a convex polyhedron



Graphics Lecture 11: Slide 42

Binary Space Partition (BSP) Tree


- Simple recursive algorithms
- Example: point finding



Graphics Lecture 11: Slide 43

Binary Space Partition (BSP) Tree



- Trace rays by recursion on tree
 - BSP construction enables simple front-to-back traversal



Graphics Lecture 11: Slide 44

Grid Discussion

- Regular
 - + easy to construct
 - + easy to traverse
 - may be only sparsely filled
 - geometry may still be clumped
- Adaptive
 - + grid complexity matches geometric density
 - more expensive to traverse (especially BSP tree)



Example

- <https://www.youtube.com/watch?v=aKqxonOrl4Q>
- <https://www.youtube.com/watch?v=qlyzo9ll9Vw>
- <https://www.youtube.com/watch?v=AV279wThmVU>
-