






Direct and Global Illumination

- <u>Direct illumination</u>: A surface point receives light directly from all light sources in the scene.
 - Computed by the direct illumination model.
- <u>Global illumination</u>: A surface point receives light after the light rays interact with other objects in the scene.
 - Points may be in shadow.
 - Rays may refract through transparent material.
 - Computed by reflection and transmission rays.

Albrecht Dürer's Ray Casting Machine

• Albrecht Dürer, 16th century






Graphics

5


Arthur Appel, 1968

- On calculating the illusion of reality, 1968
- Cast one ray per pixel (ray casting).
 - For each intersection, trace one ray to the light to check for shadows
 - Only a local illumination model
- Developed for pen-plotters



Ray casting

```
cast ray
    Intersect all objects
    color = ambient term
    For every light cast shadow ray
        col += local shading term
```




Ray casting




Turner Whitted, 1980

- An Improved Illumination Model for Shaded Display, 1980
- First global illumination model:
 - An object's color is influenced by lights and other objects in the scene
 - Simulates specular reflection and refractive transmission




Turner Whitted, 1980



Recursive ray casting

Does it ever end?


- Stopping criteria:
 - Recursion depth: Stop after a number of bounces
 - Ray contribution: Stop if reflected / transmitted contribution becomes too small



0 recursion


Does it ever end?

- Stopping criteria:
 - Recursion depth: Stop after a number of bounces
 - Ray contribution: Stop if reflected / transmitted contribution becomes too small



Does it ever end?

- Stopping criteria:
 - Recursion depth: Stop after a number of bounces
 - Ray contribution: Stop if reflected / transmitted contribution becomes too small



Ray tracing: Primary rays

- For each ray we need to test which objects are intersecting the ray:
 - If the object has an intersection with the ray we calculate the distance between viewpoint and intersection
 - If the ray has more than one intersection, the smallest distance identifies the visible surface.
- Primary rays are rays from the view point to the nearest intersection point
- Local illumination is computed as before:

$$L = k_a + (k_d(\mathbf{n} \cdot \mathbf{l}) + k_s(\mathbf{v} \cdot \mathbf{r})^q)I_s$$


Ray tracing: Secondary rays

- Secondary rays are rays originating at the intersection points
- Secondary rays are caused by
 - rays reflected off the intersection point in the direction of reflection
 - rays transmitted through transparent materials in the direction of refraction
 - shadow rays


Recursive ray tracing: Putting it all together


• Illumination can be expressed as

$$L = k_a + (k_d(\mathbf{n} \cdot \mathbf{l}) + k_s(\mathbf{v} \cdot \mathbf{r})^q)I_s + k_{reflected}L_{reflected} + k_{refracted}L_{refracted}$$




Recursive Ray Tracing: Ray Tree





Precision Problems




- In ray tracing, the origin of (secondary) rays is often below the surface of objects
 - Theoretically, the intersection point should be on the surface
 - Practically, calculation imprecision creeps in, and the origin of the new ray is slightly beneath the surface
- Result: the surface area is shadowing itself or the ray continues on the wrong side

ε to the rescue ...

- Check if t is within some epsilon tolerance:
 - if $abs(\mu) < \epsilon$
 - · point is on the surface
 - else
 - point is inside/outside
 - Choose the ε tolerance empirically
- Move the intersection point by epsilon along the surface normal so it is outside of the object
- Check if point is inside/outside surface by checking the sign of the implicit (sphere etc.) equation


Mirror reflection

- Compute mirror contribution
- Cast ray in direction symmetric wrt. normal
- Multiply by reflection coefficient (color)



Mirror reflection

Don't forget to add epsilon to the ray



Without epsilon
Graphics Lecture 10: Slide 23

With epsilon

Mirror reflection secondary ray primary ray \mathbf{V} $\phi_{in} \mid \phi_{out}$

24

Mirror reflection


- To calculate illumination as a result of reflections
 - calculate the direction of the secondary ray at the intersection of the primary ray with the object.

given that

- n is the unit surface normal
- $-\mathbf{v}$ is the direction of the primary ray
- $-\mathbf{v}$ ' is the direction of the secondary ray as a result of reflections

$$\mathbf{v'} = \mathbf{v} - (2\mathbf{v} \cdot \mathbf{n})\mathbf{n}$$


Mirror reflection



$$\mathbf{v'} = \mathbf{v} - (2\mathbf{v} \cdot \mathbf{n})\mathbf{n}$$

Transparency


- Compute transmitted contribution
- Cast ray in refracted direction
- Multiply by transparency coefficient



 The angle of the refracted ray can be determined by Snell's law:

$$\eta_1 \sin(\phi_1) = \eta_2 \sin(\phi_2)$$

- η_1 is a constant for medium 1
- η_2 is a constant for medium 2
- φ₁ is the angle between the incident ray and the surface normal
- φ₂ is the angle between the refracted ray and the surface normal



• In vector notation Snell's law can be written:

$$k_1(v \cdot n) = k_2(v' \cdot n)$$

The direction of the refracted ray is


$$\mathbf{v}' = \frac{\eta_1}{\eta_2} \left[\sqrt{(\mathbf{n} \cdot \mathbf{v})^2 + \left(\frac{\eta_2}{\eta_1}\right)^2 - 1} - \mathbf{n} \cdot \mathbf{v} \right] \cdot \mathbf{n} + \mathbf{v}$$


This equation only has a solution if

$$(\mathbf{n} \cdot \mathbf{v})^2 > 1 - \left(\frac{\eta_2}{\eta_1}\right)^2$$

- This illustrates the physical phenomenon of the limiting angle:
 - if light passes from one medium to another medium whose index of refraction is low, the angle of the refracted ray is greater than the angle of the incident ray
 - if the angle of the incident ray is large, the angle of the refracted ray is larger than 90°
 - → the ray is reflected rather than refracted

 Make sure you know whether you are entering or leaving the transmissive material






Amount of reflection and refraction

- Traditional (hacky) ray tracing
 - Constant coefficient reflection
 - Component per component multiplication
- Better: Mix reflected and refracted light according to the Fresnel factor.

$$L = k_{\textit{fresnel}} L_{\textit{reflected}} + (1 - k_{\textit{fresnel}}) L_{\textit{refracted}}$$




Fresnel factor

• More reflection at grazing angle










Schlick's Approximation


Schlick's approximation

$$k_{fresnel}(\theta) = k_{fresnel}(0) + (1 - k_{fresnel}(0))(1 - (\mathbf{n} \cdot \mathbf{l}))^{5}$$


- $k_{fresnel}(\theta)$ = Fresnel factor at zero degrees
- Choose $k_{fresnel}(0) = 0.8$, this will look like stainless steel
- Fresnel factor at zero degrees has low value ~ 0.05 for dielectric materials like plastic.



How do we add shadows?



How do we add shadows?





$$L = k_a + s(k_d(\mathbf{n} \cdot \mathbf{l}) + k_s(\mathbf{v} \cdot \mathbf{r})^q)I_s + k_{reflected}L_{reflected} + k_{refracted}L_{refracted}$$


$$s = \begin{cases} 0 & \text{if light source is obscured} \\ 1 & \text{if light source is not obscured} \end{cases}$$

Shadows: Problems?

Make sure to avoid self-shadowing










Shadows

 One shadow ray per intersection per point light source












Soft shadows

 Multiple shadow rays to sample area light source










Reflection: Conventional ray tracing

• One reflection per intersection




Reflection: Conventional ray tracing

• How can we create effects like this?




Reflection: Monte Carlo ray tracing

• Random reflection rays around mirror direction




Glossy surfaces




Ray tracing


- Cast a ray from the eye through each pixel
- Trace secondary rays (light, reflection, refraction)




- Cast a ray from the eye through each pixel
- Cast random rays from the visible point
 - Accumulate radiance contribution




- Cast a ray from the eye through each pixel
- Cast random rays from the visible point
- Recurse



- Cast a ray from the eye through each pixel
- Cast random rays from the visible point
- Recurse




Send rays to light




Monte-Carlo Path Tracing

- Trace only one secondary ray per recursion
- But send many primary rays per pixel




Example




1 sample per ray

Example



256 samples per ray



"Fukaya House" Waro Kishi




















Graphics Lecture 10: Slide 63

took 4.5 days to render! (10 years ago)