Certificate No.: 3745.01

FCC - TEST REPORT

Report Number	:	**709502502981-00A**	Date of Issue:	April 21,2025

Model	:	T1-3S
Product Type	:	Wi-Fi and Bluetooth Module
Applicant	:	Hangzhou Tuya Information Technology Co.,Ltd
Address	:	Room 301,Building 1,Huace Center,Xihu District, Hangzhou,Zhejiang, China
Manufacturer	:	Hangzhou Tuya Information Technology Co.,Ltd
Address	:	Room 301,Building 1,Huace Center,Xihu District, Hangzhou,Zhejiang, China
Test Result	:	■ **Positive** ☐ **Negative**
Total pages including Appendices	:	84

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1 Table of Contents 2
2 Report Modification Record 3
3 Details about the Test Laboratory 3
4 Description of the Equipment under Test 4
5 Summary of Test Standards 6
6 Summary of Test Results 7
7 General Remarks 8
8 Test Setups 9
9 Systems test configuration 12
10 Technical Requirement 13
10.1 Conducted Emission 13
10.2 Conducted peak output power 18
10.3 6dB bandwidth 19
10.4 spectral density 24
10.5 Spurious RF conducted emissions 29
10.6 Band edge 42
10.7 Spurious radiated emissions for transmitter 51
11 Test Equipment List 81
12 System Measurement Uncertainty 82
13 Photographs of Test Set-ups 83
14 Photographs of EUT 84

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

2 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
709502502981-00A	First Issue	04/21/2025

3 Details about the Test Laboratory

Test Site 1

Company name:	TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch No.16 Lane, 1951 Du Hui Road, Shanghai 201108, P.R. China
Telephone:	+86 21 6141 0123
Fax:	+86 21 6140 8600
FCC Registration No.:	820234
FCC Designation Number:	CN1183
ISED CAB identifier	CN0101
IC Registration No.:	31668

4 Description of the Equipment under Test

Product: Wi-Fi and Bluetooth Module

Model no.: T1-3S

FCC ID: 2ANDL-T1-3S

Rating: 3.0-3.6V DC; Typical:3.3V DC

RF Transmission Frequency: Wi-Fi:2412-2462MHz
Bluetooth LE:2402~2480MHz

No. of Operated Channel: 2.4GHz WIFI: 11 for 802.11b/g/n(HT20)
2.4GHz BLE: 40

Modulation: 802.11b: CCK, DSSS
802.11g/n20: BPSK, QPSK, 16-QAM, 64-QAM
2.4GHz BLE:GFSK

Channel list:

802.11b/g/n(HT20)			
Ch	Fre(MHz)	Ch	Fre(MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Bluetooth Low Energy							
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Hardware Version: V1.0.0

Software Version: V3.5.0

Antenna type: Onboard PCB antenna

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Antenna Gain:	1.68dBi
Description of the EUT:	The Equipment Under Test (EUT) is a Wi-Fi and Bluetooth module which support 2.4GHz Wi-Fi and BLE 5.2(support 1Mbps data rate). We tested it and listed the worst data in this report.
Test sample no.:	SHA-905535-1 (RF radiated); SHA-905535-2 (RF conducted)

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

5 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2023 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 Measurement Guidance and ANSI C63.10-2020.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

6 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207	Conducted emission AC power port	13-17	Site 1	☒	☐	☐
§15.247 (b) (3)	Conducted peak output power	18	Site 1	☒	☐	☐
§15.247(a)(1)	20dB bandwidth and 99% Occupied Bandwidth	---	---	☐	☐	☒
§15.247(a)(1)	Carrier frequency separation	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Number of hopping frequencies	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Dwell Time - Average Time of Occupancy	---	---	☐	☐	☒
§15.247(a)(2)	6dB bandwidth	19-23	Site 1	☒	☐	☐
§15.247(e)	Power spectral density	24-28	Site 1	☒	☐	☐
§15.247(e)	Spurious RF conducted emissions	29-41	Site 1	☒	☐	☐
§15.247(d)	Band edge	42-50	Site 1	☒	☐	☐
§15.247(d) & §15.209 & §15.205	Spurious radiated emissions for transmitter	51-80	Site 1	☒	☐	☐
§15.203	Antenna requirement	See note 1		☒	☐	☐

Remark 1: N/A – Not Applicable.
Note 1: The EUT uses PCB antenna, which gain is 1.68dBi. In accordance to §15.203, it is considered sufficiently to comply with the provisions of this section.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

7 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2ANDL-T1-3S, complies with Section 15.207,15.209,15.205,15.247 of the FCC Part 15, Subpart C Rules.

This report is only for the 2.4GHz Wi-Fi test report, for the 2.4GHz BLE test report please refer to 709502502981-00B.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

☐ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

☐ - **Does not** fulfill the general approval requirements.

Sample Received Date:	March 18, 2025
Testing Start Date:	March 20, 2025
Testing End Date:	April 10, 2025


-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:	Prepared by:	Tested by:
Jiaxi XU	Hui TONG	Chengjie GUO
Review Engineer	Project Engineer	Test Engineer

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600


8 Test Setups

8.1 AC Power Line Conducted Emission test setups




8.2 Radiated test setups

9kHz ~ 30MHz Test Setup:




TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:




TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

18GHz ~ 25GHz Test Setup:




8.3 Conducted RF test setups

For Conducted peak output power



For other test items



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

9 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	E470	PF-OU5TS7 17/09

Test software: Beken Wi-Fi Test Tool V1.7.4

Test Mode Applicability and Tested Channel Detail:

Mode	Tested Channel	Data Rate (Mbps)	Modulation	Index Value (Power level setting)
802.11b	1	1	DSSS	73
	6	1	DSSS	82
	11	1	DSSS	73
802.11b	1	5.5	CCK	71
	6	5.5	CCK	73
	11	5.5	CCK	71
802.11g	1	6	OFDM	82
	6	6	OFDM	81
	11	6	OFDM	81
802.11n HT20	1	MCS0	OFDM	82
	6	MCS0	OFDM	78
	11	MCS0	OFDM	78

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

10 Technical Requirement

10.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

Limit

According to §15.207, conducted emissions limit as below:

Frequency MHz	QP Limit dBµV	AV Limit dBµV
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Conducted Emission

150k-30MHz Conducted Emission Test


EUT Information

EUT Name:	Wi-Fi and Bluetooth Module
Model	T1-3S
Client:	Hangzhou Tuya Information Co., Ltd
Op Cond	Power on and transmitted mode, TX_2437MHz at g mode, AC 120V/60Hz
Operator:	Chengjie Guo
Standard	FCC Part 15.207(a)
Comment:	Phase L
Sample No.:	SHA-905535-1

Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup:	Voltage with 2-Line-LISN
Receiver:	[ESR 3]
Level Unit:	dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.172500	---	25.21	54.84	29.63	1000.0	9.000	L1	19.5
0.172500	44.14	---	64.84	20.70	1000.0	9.000	L1	19.5
0.496500	30.81	---	56.06	25.25	1000.0	9.000	L1	19.5
0.528000	---	26.22	46.00	19.78	1000.0	9.000	L1	19.5
2.098500	---	20.81	46.00	25.19	1000.0	9.000	L1	19.5
2.107500	26.77	---	56.00	29.23	1000.0	9.000	L1	19.5
2.706000	---	24.71	46.00	21.29	1000.0	9.000	L1	19.5
2.751000	30.14	---	56.00	25.86	1000.0	9.000	L1	19.5
11.116500	27.91	---	60.00	32.09	1000.0	9.000	L1	19.8
11.503500	---	22.77	50.00	27.23	1000.0	9.000	L1	19.8
13.920000	33.20	---	60.00	26.80	1000.0	9.000	L1	19.8
27.649500	---	36.56	50.00	13.44	1000.0	9.000	L1	21.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

150k-30MHz Conducted Emission Test


EUT Information

EUT Name:	Wi-Fi and Bluetooth Module
Model	T1-3S
Client:	Hangzhou Tuya Information Co., Ltd
Op Cond	Power on and transmitted mode, TX_2437MHz at g mode, AC 120V/60Hz
Operator:	Chengjie Guo
Standard	FCC Part 15.207(a)
Comment:	Phase N
Sample No.:	SHA-905535-1

Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup:	Voltage with 2-Line-LISN
Receiver:	[ESR 3]
Level Unit:	dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.163500	47.59	---	65.28	17.69	1000.0	9.000	N	19.5
0.177000	---	27.57	54.63	27.06	1000.0	9.000	N	19.5
0.501000	33.58	---	56.00	22.42	1000.0	9.000	N	19.5
0.586500	---	21.88	46.00	24.12	1000.0	9.000	N	19.5
2.035500	---	23.50	46.00	22.50	1000.0	9.000	N	19.5
2.112000	29.40	---	56.00	26.60	1000.0	9.000	N	19.5
2.404500	30.82	---	56.00	25.18	1000.0	9.000	N	19.5
2.647500	---	25.16	46.00	20.84	1000.0	9.000	N	19.5
11.665500	---	19.53	50.00	30.47	1000.0	9.000	N	19.8
11.697000	24.99	---	60.00	35.01	1000.0	9.000	N	19.8
14.658000	32.14	---	60.00	27.86	1000.0	9.000	N	19.9
27.649500	---	34.97	50.00	15.03	1000.0	9.000	N	20.8

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

10.2 Conducted peak output power

Test Method

1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

4) Measure the peak power of the transmitter. This measurement is a peak over both the ON and OFF periods of the transmitter.



Wideband Power Sensor conducted test setup

Limits

According to §15.247 (b) (3) conducted peak output power limit as below:

	Frequency Range	Limit	Limit
	MHz	W	dBm
Conducted peak output power	2400-2483.5	≤1	≤30

Test result as below

Mode	Frequency MHz	Conducted Peak Output Power(dBm) §15.247 (b) (3)	Result
802.11b (DSSS)	2412MHz	18.23	Pass
	2437MHz	18.12	Pass
	2462MHz	17.95	Pass

Mode	Frequency MHz	Conducted Peak Output Power(dBm) §15.247 (b) (3)	Result
802.11b (CCK)	2412MHz	17.94	Pass
	2437MHz	17.79	Pass
	2462MHz	18.02	Pass

Mode	Frequency MHz	Conducted Peak Output Power(dBm) §15.247 (b) (3)	Result
802.11g	2412MHz	19.66	Pass
	2437MHz	20.12	Pass
	2462MHz	19.29	Pass

Mode	Frequency MHz	Conducted Peak Output Power(dBm) §15.247 (b) (3)	Result
802.11n (HT20)	2412MHz	19.11	Pass
	2437MHz	18.56	Pass
	2462MHz	18.99	Pass

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

10.3 6dB bandwidth

Test Method

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
   RBW=1% to 5% of the occupied bandwidth but not less than 100kHz, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Use the automatic bandwidth measurement capability of an instrument, use the X dB bandwidth mode with X set to 6 dB.
5. Allow the trace to stabilize, record the 6 dB Bandwidth value.

Limit

6dB bandwidth Limit [kHz]	≥500


Test result

Test Mode	Frequency MHz	6dB bandwidth (MHz)		Result
		result	limit	verdict
802.11b (DSSS)	2412	8.695	≥0.5	Pass
	2437	8.681	≥0.5	Pass
	2462	8.29	≥0.5	Pass
802.11b (CCK)	2412	8.395	≥0.5	Pass
	2437	8.261	≥0.5	Pass
	2462	8.36	≥0.5	Pass
802.11g	2412	17.206	≥0.5	Pass
	2437	17.068	≥0.5	Pass
	2462	17.222	≥0.5	Pass
802.11n(HT20)	2412	15.435	≥0.5	Pass
	2437	15.373	≥0.5	Pass
	2462	15.895	≥0.5	Pass


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

6 dB Bandwidth


-6dB Bandwidth NVNT b DSSS 2412MHz Ant1



-6dB Bandwidth NVNT b DSSS 2437MHz Ant1




-6dB Bandwidth NVNT b DSSS 2462MHz Ant1




TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600


-6dB Bandwidth NVNT b CCK 2412MHz Ant1



-6dB Bandwidth NVNT b CCK 2437MHz Ant1




-6dB Bandwidth NVNT b CCK 2462MHz Ant1




TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Test Graphs


-6dB Bandwidth NVNT g 2412MHz Ant1



-6dB Bandwidth NVNT g 2437MHz Ant1



-6dB Bandwidth NVNT g 2462MHz Ant1




TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600


-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1



-6dB Bandwidth NVNT n20 2462MHz Ant1



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

10.4 spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
4. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW≥3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
5. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
6. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm/3kHz]
≤8

Test result

802.11 b (DSSS)

Frequency	Power spectral density	Result
MHz	**dBm/3kHz**	
Low channel 2412MHz	-4.93	Pass
Middle channel 2437MHz	-4.81	Pass
High channel 2462MHz	-4.61	Pass

802.11 b (CCK)

Frequency	Power spectral density	Result
MHz	**dBm/3kHz**	
Low channel 2412MHz	-3.44	Pass
Middle channel 2437MHz	-3.38	Pass
High channel 2462MHz	-3.42	Pass

802.11 g

Frequency	Power spectral density	Result
MHz	**dBm/3kHz**	
Low channel 2412MHz	-11.6	Pass
Middle channel 2437MHz	-11.6	Pass
High channel 2462MHz	-11.88	Pass


802.11 n (HT20)

Frequency	Power spectral density	Result
MHz	**dBm/3kHz**	
Low channel 2412MHz	-12.29	Pass
Middle channel 2437MHz	-12.63	Pass
High channel 2462MHz	-12.74	Pass


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Power spectral density


PSD NVNT b DSSS 2412MHz Ant1



PSD NVNT b DSSS 2437MHz Ant1




PSD NVNT b DSSS 2462MHz Ant1




TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600


PSD NVNT b CCK 2412MHz Ant1



PSD NVNT b CCK 2437MHz Ant1




PSD NVNT b CCK 2462MHz Ant1




Test Graphs


PSD NVNT g 2412MHz Ant1




PSD NVNT g 2437MHz Ant1




PSD NVNT g 2462MHz Ant1




PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1



PSD NVNT n20 2462MHz Ant1



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

10.5 Spurious RF conducted emissions

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
   Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
   RBW = 100 kHz, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
5. The level displayed must comply with the limit specified in this Section. Submit these plots.
6. Repeat above procedures until all frequencies measured were complete.

Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600


Spurious RF conducted emissions

802.11 B (DSSS)


Out-of-Band Emissions

Channel 1 (2412MHz)


Reference point




Spurious Emission (30MHz – 1GHz)







Spurious Emission (1GHz –5GHz)







Spurious Emission (5GHz –26.5GHz)



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Out-of-Band Emissions	
Channel 6 (2437MHz)	
Reference point	Spurious Emission (30MHz – 1GHz)
	
Spurious Emission (1GHz –5GHz)	Spurious Emission (5GHz –26.5GHz)
	


Out-of-Band Emissions	
Channel 11 (2462MHz)	
Reference point	Spurious Emission (30MHz – 1GHz)
	
Spurious Emission (1GHz –5GHz)	Spurious Emission (5GHz –26.5GHz)
	

802.11 B (CCK)


Out-of-Band Emissions

Channel 1 (2412MHz)


Reference point




Spurious Emission (30MHz – 1GHz)











Spurious Emission (1GHz –5GHz)







Spurious Emission (5GHz –26.5GHz)











Out-of-Band Emissions	
Channel 6 (2437MHz)	
Reference point	Spurious Emission (30MHz – 1GHz)
	
Spurious Emission (1GHz –5GHz)	Spurious Emission (5GHz –26.5GHz)
	

Out-of-Band Emissions	
Channel 11 (2462MHz)	
Reference point	Spurious Emission (30MHz – 1GHz)
	
Spurious Emission (1GHz –5GHz)	Spurious Emission (5GHz –26.5GHz)
	

802.11 G





Out-of-Band Emissions	
Channel 1 (2412MHz)	
Reference point	Spurious Emission (30MHz – 1GHz)
	
Spurious Emission (1GHz –5GHz)	Spurious Emission (5GHz –26.5GHz)
	

Out-of-Band Emissions	
Channel 6 (2437MHz)	
Reference point	Spurious Emission (30MHz – 1GHz)
	
Spurious Emission (1GHz –5GHz)	Spurious Emission (5GHz –26.5GHz)
	

Out-of-Band Emissions	
Channel 11 (2462MHz)	
Reference point	Spurious Emission (30MHz – 1GHz)
	
Spurious Emission (1GHz –5GHz)	Spurious Emission (5GHz –26.5GHz)
	

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600


802.11 N HT20

Out-of-Band Emissions	
Channel 1 (2412MHz)	
Reference point	Spurious Emission (30MHz – 1GHz)
	
Spurious Emission (1GHz –5GHz)	Spurious Emission (5GHz –26.5GHz)
	


Out-of-Band Emissions

Channel 6 (2437MHz)


Reference point




Spurious Emission (30MHz – 1GHz)







Spurious Emission (1GHz –5GHz)



Spurious Emission (5GHz –26.5GHz)



Out-of-Band Emissions	
Channel 11 (2462MHz)	
Reference point	Spurious Emission (30MHz – 1GHz)
	
Spurious Emission (1GHz –5GHz)	Spurious Emission (5GHz –26.5GHz)
	

10.6 Band edge

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
   Span = wide enough to capture the peak level of the in-band emission and all spurious
   RBW = 100 kHz, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize, use the peak and delta measurement to record the result.
5. The level displayed must comply with the limit specified in this Section.
6. Repeat above procedures until all frequencies measured were complete and submit all the plots.


Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3), the attenuation required shall be 30 dB instead of 20 dB.


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Test result

Band Edge NVNT b DSSS 2412MHz Ant1 Ref




Band Edge NVNT b DSSS 2412MHz Ant1 Emission




	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.410 5 GHz	6.134 dBm			
2	N	1	f	2.400 0 GHz	-36.60 dBm			
3	N	1	f	2.390 0 GHz	-51.36 dBm			
4	N	1	f	2.389 7 GHz	-50.96 dBm			
5								
6								

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Band Edge NVNT b DSSS 2462MHz Ant1 Ref




Band Edge NVNT b DSSS 2462MHz Ant1 Emission




	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.460 5 GHz	5.306 dBm			
2	N	1	f	2.483 5 GHz	-55.48 dBm			
3	N	1	f	2.500 0 GHz	-54.84 dBm			
4	N	1	f	2.487 7 GHz	-52.90 dBm			
5								
6								

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Band Edge NVNT b CCK 2412MHz Ant1 Ref




Band Edge NVNT b CCK 2412MHz Ant1 Emission




	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.412 8 GHz	6.147 dBm			
2	N	1	f	2.400 0 GHz	-38.45 dBm			
3	N	1	f	2.390 0 GHz	-53.27 dBm			
4	N	1	f	2.386 6 GHz	-51.97 dBm			
5								
6								

Band Edge NVNT b CCK 2462MHz Ant1 Ref



Band Edge NVNT b CCK 2462MHz Ant1 Emission




	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.462 8 GHz	6.145 dBm			
2	N	1	f	2.483 5 GHz	-55.19 dBm			
3	N	1	f	2.500 0 GHz	-55.96 dBm			
4	N	1	f	2.483 6 GHz	-51.88 dBm			
5								
6								


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Test Graphs

Band Edge NVNT g 2412MHz Ant1 Ref




Band Edge NVNT g 2412MHz Ant1 Emission




	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.413 3 GHz	1.596 dBm			
2	N	1	f	2.400 0 GHz	-42.14 dBm			
3	N	1	f	2.390 0 GHz	-53.05 dBm			
4	N	1	f	2.388 3 GHz	-50.66 dBm			
5								
6								

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Band Edge NVNT g 2462MHz Ant1 Ref




Band Edge NVNT g 2462MHz Ant1 Emission




	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.462 0 GHz	2.261 dBm			
2	N	1	f	2.483 5 GHz	-48.95 dBm			
3	N	1	f	2.500 0 GHz	-56.63 dBm			
4	N	1	f	2.483 5 GHz	-48.95 dBm			
5								
6								

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Band Edge NVNT n20 2412MHz Ant1 Ref




Band Edge NVNT n20 2412MHz Ant1 Emission




	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.413 3 GHz	1.498 dBm			
2	N	1	f	2.400 0 GHz	-44.20 dBm			
3	N	1	f	2.390 0 GHz	-53.44 dBm			
4	N	1	f	2.386 4 GHz	-52.15 dBm			
5								
6								

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Band Edge NVNT n20 2462MHz Ant1 Ref



Band Edge NVNT n20 2462MHz Ant1 Emission



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.463 3 GHz	1.280 dBm			
2	N	1	f	2.483 5 GHz	-52.64 dBm			
3	N	1	f	2.500 0 GHz	-56.43 dBm			
4	N	1	f	2.483 6 GHz	-52.11 dBm			
5								
6								

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

10.7 Spurious radiated emissions for transmitter

Test Method

1. The EUT was place on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10

   1) Procedure for Unwanted Emissions Measurements Below 1000 MHz

   Span = wide enough to capture the peak level of the in-band emission and all spurious
   RBW = 100 kHz to 120kHz, VBW≥RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

   2) For Peak unwanted emissions Above 1GHz:

   Span = wide enough to capture the peak level of the in-band emission and all spurious
   RBW = 1MHz, VBW≥RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

   Procedures for average unwanted emissions measurements above 1GHz

   a) RBW = 1MHz.
   b) VBW \ [3 × RBW].
   c) Detector = RMS (power averaging), if [span / (# of points in sweep)] \ RBW / 2. Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
   d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
   e) Sweep time = auto.
   f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
   g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
   1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is [10 log (1 / D)], where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is [20 log (1 / D)], where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission (AV) at frequency above 1GHz.

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in§ 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

Frequency MHz	Field Strength μV/m	Field Strength dBμV/m	Detector	Measurement distance meters
0.009-0.490	2400/F(kHz)	48.5-13.8	AV	300
0.490-1.705	24000/F(kHz)	33.8-23.0	QP	30
1.705-30	30	29.5	QP	30
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

Note 1: Limit 3m(dBμV/m)=Limit 300m(dBμV/m)+40Log(300m/3m) (Below 30MHz)
Note 2: Limit 3m(dBμV/m)=Limit 30m(dBμV/m)+40Log(30m/3m) (Below 30MHz)

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Test result

The worst case of Radiated Emission below 30MHz: Only the worst case listed as below.

0.009-30MHz Radiated Emission

EUT Information


EUT Name:	Wi-Fi and Bluetooth Module
Model	T1-3S
Client:	Hangzhou Tuya Information Co., Ltd
Op Cond	DC 3.3V power on and transmitted mode, TX_2437MHz at g mode
Operator:	Chengjie Guo
Standard	FCC Part 15.209(a)
Comment:	Horizontal
Sample No.:	SHA-905535-1

Sweep Setup: RE_Loop E_pre [EMI radiated]

Hardware Setup:	RE_Loop Antenna V
Receiver:	[ESR 3]
Level Unit:	dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
9 kHz - 150 kHz	88.125 Hz	PK+	200 Hz	0.01 s	0 dB
150 kHz - 30 MHz	4.39 kHz	PK+	9 kHz	0.01 s	0 dB

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.010234	47.55	127.40	79.86	100.0	H	261.0	19.6
0.116336	35.34	106.29	70.95	100.0	H	65.0	18.8
0.501177	35.17	73.60	38.43	100.0	H	81.0	18.7
1.352780	35.46	64.98	29.52	100.0	H	1.0	18.8
2.033184	29.28	69.54	40.26	100.0	H	341.0	18.9
12.915265	28.64	69.54	40.90	100.0	H	246.0	18.9

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

0.009-30MHz Radiated Emission

EUT Information


EUT Name:	Wi-Fi and Bluetooth Module
Model	T1-3S
Client:	Hangzhou Tuya Information Co., Ltd
Op Cond	DC 3.3V power on and transmitted mode, TX_2437MHz at g mode
Operator:	Chengjie Guo
Standard	FCC Part 15.209(a)
Comment:	Vertical
Sample No.:	SHA-905535-1

Sweep Setup: RE_Loop E_pre [EMI radiated]

Hardware Setup:	RE_Loop Antenna V
Receiver:	[ESR 3]
Level Unit:	dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
9 kHz - 150 kHz	88.125 Hz	PK+	200 Hz	0.01 s	0 dB
150 kHz - 30 MHz	4.39 kHz	PK+	9 kHz	0.01 s	0 dB

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.030062	35.83	118.04	82.21	100.0	Y	359.0	18.9
0.116601	34.11	106.27	72.16	100.0	Y	25.0	18.8
0.496787	32.33	73.68	41.35	100.0	Y	38.0	18.7
1.352780	33.03	64.98	31.95	100.0	Y	95.0	18.8
2.077081	29.08	69.54	40.46	100.0	Y	149.0	18.9
16.405081	29.97	69.54	39.57	100.0	Y	284.0	18.8

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

The worst case of Radiated Emission below 1GHz: Only the worst case listed as below.

30-1000MHz Radiated Emission


EUT Information

EUT Name:	Wi-Fi and Bluetooth Module
Model:	T1-3S
Client:	Hangzhou Tuya Information Technology Co., Ltd
Op Cond:	DC 3.3V power on and transmitted mode, TX_2437MHz at g mode
Operator:	Chengjie Guo
Test Spec:	FCC Part 15.209(a)
Comment:	Horizontal
Sample No:	SHA-905535-1

Sweep Setup: RE_VULB9168_pre_Cont_30-1000 [EMI radiated]

Hardware Setup:	RE_VULB9168
Receiver:	[ESR 3]
Level Unit:	dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.2 s	20 dB



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)
191.080000	30.8	1000.0	120.000	185.0	H	165.0	18.5	12.7
239.440000	34.6	1000.0	120.000	186.0	H	129.0	19.7	11.4
287.960000	34.7	1000.0	120.000	199.0	H	1.0	21.5	11.3
310.520000	33.7	1000.0	120.000	187.0	H	178.0	22.0	12.3
383.960000	37.8	1000.0	120.000	168.0	H	55.0	24.1	8.2
940.880000	34.4	1000.0	120.000	177.0	H	118.0	34.8	11.6

(continuation of the "Limit and Margin" table from column 16 ...)

Frequency (MHz)	Limit - QPK (dBuV/m)	Comment
191.080000	43.5	
239.440000	46.0	
287.960000	46.0	
310.520000	46.0	
383.960000	46.0	
940.880000	46.0	

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

30-1000MHz Radiated Emission


EUT Information

EUT Name:	Wi-Fi and Bluetooth Module
Model:	T1-3S
Client:	Hangzhou Tuya Information Technology Co., Ltd
Op Cond:	DC 3.3V power on and transmitted mode, TX_2437MHz at g mode
Operator:	Chengjie Guo
Test Spec:	FCC Part 15.209(a)
Comment:	Vertical
Sample No:	SHA-905535-1

Sweep Setup: RE_VULB9168_pre_Cont_30-1000 [EMI radiated]

Hardware Setup:	RE_VULB9168
Receiver:	[ESR 3]
Level Unit:	dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.2 s	20 dB



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)
32.480000	20.0	1000.0	120.000	188.0	V	132.0	18.9	20.0
63.080000	19.9	1000.0	120.000	164.0	V	114.0	20.2	20.1
191.960000	20.9	1000.0	120.000	177.0	V	13.0	18.4	22.6
238.800000	21.7	1000.0	120.000	188.0	V	315.0	19.6	24.3
382.120000	32.2	1000.0	120.000	175.0	V	116.0	24.0	13.9
477.600000	28.9	1000.0	120.000	157.0	V	12.0	26.5	17.1

(continuation of the "Limit and Margin" table from column 16 ...)


Frequency (MHz)	Limit - QPK (dBuV/m)	Comment
32.480000	40.0	
63.080000	40.0	
191.960000	43.5	
238.800000	46.0	
382.120000	46.0	
477.600000	46.0	

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600


Radiated Emission 1-18 GHz

802.11B (DSSS):2412MHz



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m
1607.800000	45.8	42.3	198.0	H	174.0	-13.9	28.2	74.0	11.7	54.0
4824.000000	50.2	48.5	169.0	H	186.0	-2.6	23.8	74.0	5.5	54.0
16725.400000	52.5	48.7	187.0	H	178.0	6.7	21.5	74.0	5.3	54.0



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m
4824.000000	48.7	46.6	199.0	V	4.0	-2.6	25.3	74.0	7.4	54.0
11220.100000	51.0	47.0	189.0	V	259.0	4.5	23.1	74.0	7.0	54.0
17123.500000	52.6	49.2	178.0	V	174.0	6.8	21.4	74.0	4.8	54.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2363.000000	51.9	41.7	186.0	H	178.0	-0.9	22.1	74.0	12.3	54.0
2390.000000	53.6	42.9	174.0	H	145.0	-0.8	20.4	74.0	11.1	54.0
2412.000000	105.3	---	198.0	H	135.0	-0.7	-31.3	74.0	---	---




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m
2386.000000	54.1	42.4	189.0	V	168.0	-0.8	19.9	74.0	11.6	54.0
2390.000000	54.5	44.6	178.0	V	15.0	-0.8	19.5	74.0	9.4	54.0
2412.000000	105.1	---	198.0	V	147.0	-0.7	-31.1	74.0	---	---


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11B (DSSS):2437MHz



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4874.000000	48.5	46.2	189.0	H	147.0	-2.5	25.5	74.0	7.8	54.0
12082.900000	50.4	45.3	177.0	H	178.0	5.2	23.6	74.0	8.7	54.0
17846.500000	51.7	43.5	197.0	H	142.0	7.2	22.3	74.0	10.5	54.0




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4874.000000	49.4	46.7	189.0	V	359.0	-2.5	24.6	74.0	7.3	54.0
12075.400000	50.7	46.4	178.0	V	274.0	5.2	23.3	74.0	7.6	54.0
16719.700000	51.8	47.9	166.0	V	175.0	6.7	22.2	74.0	6.1	54.0


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11B (DSSS):2462MHz



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4924.000000	46.5	42.1	178.0	H	166.0	-2.3	27.5	74.0	12.0	54.0
11935.900000	50.1	45.7	199.0	H	141.0	5.1	23.9	74.0	8.3	54.0
17823.700000	51.9	46.4	198.0	H	78.0	7.2	22.1	74.0	7.6	54.0



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4924.000000	46.9	43.7	189.0	V	25.0	-2.3	27.1	74.0	10.3	54.0
11851.900000	50.5	46.5	168.0	V	114.0	5.1	23.6	74.0	7.5	54.0
17034.700000	52.0	48.8	145.0	V	178.0	6.7	22.0	74.0	5.3	54.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2462.000000	104.3	---	254.0	H	177.0	-0.4	-30.3	74.0	---	---
2483.500000	50.7	42.4	236.0	H	25.0	-0.3	23.3	74.0	11.6	54.0
2499.400000	49.5	39.4	232.0	H	175.0	-0.3	24.5	74.0	14.7	54.0




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2462.000000	103.4	---	158.0	V	154.0	-0.4	-29.4	74.0	---	---
2483.500000	51.7	39.7	166.0	V	178.0	-0.3	22.3	74.0	14.3	54.0
2505.400000	48.8	38.6	187.0	V	136.0	-0.2	25.2	74.0	15.5	54.0


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11B (CCK):2412MHz



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+	Limit - PK+ (dBuV/m)	Margin - AV	Limit - AV (dBuV/m)
4824.000000	47.5	44.6	223.0	H	163.0	-2.6	26.5	74.0	9.4	54.0
11994.100000	50.1	43.8	236.0	H	184.0	5.2	23.9	74.0	10.2	54.0
16696.300000	52.3	44.0	285.0	H	152.0	6.7	21.7	74.0	10.0	54.0



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4824.000000	47.6	44.8	187.0	V	135.0	-2.6	26.4	74.0	9.2	54.0
12108.400000	50.4	45.5	158.0	V	114.0	5.2	23.6	74.0	8.5	54.0
17064.400000	51.6	46.3	177.0	V	24.0	6.7	22.4	74.0	7.7	54.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m	Margin - AV (dB)	Limit - AV (dBuV/m
2319.400000	52.4	41.2	188.0	H	23.0	-1.1	21.7	74.0	12.8	54.0
2390.000000	52.5	43.5	157.0	H	178.0	-0.8	21.5	74.0	10.6	54.0
2412.000000	105.9	---	169.0	H	152.0	-0.7	-31.9	74.0	---	---




Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m	Margin - AV (dB)	Limit - AV (dBuV/m)
2383.500000	53.4	42.3	189.0	V	185.0	-0.8	20.6	74.0	11.8	54.0
2390.000000	53.9	44.4	199.0	V	359.0	-0.8	20.1	74.0	9.6	54.0
2412.000000	108.5	---	187.0	V	135.0	-0.7	-34.5	74.0	---	---

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11B (CCK):2437MHz



Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m
4874.000000	46.2	42.2	189.0	V	159.0	-2.4	27.8	74.0	11.8	54.0
12084.100000	50.2	45.8	177.0	V	201.0	5.2	23.8	74.0	8.2	54.0
16683.700000	51.8	45.9	169.0	V	219.0	6.7	22.2	74.0	8.1	54.0




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4874.000000	46.7	42.7	164.0	V	22.0	-2.5	27.3	74.0	11.3	54.0
12130.300000	50.4	45.0	188.0	V	164.0	5.3	23.6	74.0	9.0	54.0
16632.700000	51.7	46.2	189.0	V	31.0	6.6	22.4	74.0	7.8	54.0


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11BC(CCK):2462MHz



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m	Margin - AV (dB)	Limit - AV (dBuV/m)
4924.000000	46.6	43.9	251.0	H	125.0	-2.3	27.4	74.0	10.1	54.0
12043.000000	50.3	45.2	189.0	H	136.0	5.2	23.7	74.0	8.8	54.0
16656.400000	51.6	46.8	214.0	H	178.0	6.6	22.4	74.0	7.2	54.0



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m	Margin - AV (dB)	Limit - AV (dBuV/m
4924.000000	46.4	40.4	189.0	V	135.0	-2.3	27.6	74.0	13.6	54.0
12072.700000	51.1	46.3	188.0	V	14.0	5.2	22.9	74.0	7.7	54.0
17055.400000	51.3	46.1	168.0	V	178.0	6.7	22.7	74.0	7.9	54.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m	Margin - AV (dB)	Limit - AV (dBuV/m)
2462.000000	105.0	---	178.0	H	8.0	-0.4	-31.0	74.0	---	---
2482.000000	51.5	41.5	174.0	H	66.0	-0.3	22.6	74.0	12.5	54.0
2494.000000	48.8	39.2	199.0	H	78.0	-0.3	25.2	74.0	14.8	54.0




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2462.000000	107.4	---	188.0	V	174.0	-0.4	-33.4	74.0	---	---
2483.500000	52.4	42.9	187.0	V	135.0	-0.3	21.6	74.0	11.1	54.0
2487.100000	51.3	40.9	198.0	V	147.0	-0.3	22.8	74.0	13.1	54.0


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11G:2412MHz



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4824.000000	45.2	40.8	199.0	H	359.0	-2.6	28.8	74.0	13.2	54.0
12012.700000	50.4	44.3	178.0	H	125.0	5.2	23.6	74.0	9.7	54.0
16653.400000	51.3	45.8	169.0	H	196.0	6.6	22.8	74.0	8.2	54.0



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4824.000000	44.0	38.0	142.0	V	164.0	-2.6	30.0	74.0	16.0	54.0
12029.800000	50.5	44.3	125.0	V	113.0	5.2	23.5	74.0	9.8	54.0
16644.100000	51.6	45.7	127.0	V	143.0	6.6	22.4	74.0	8.3	54.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2384.500000	58.3	42.5	185.0	H	31.0	-0.8	15.7	74.0	11.5	54.0
2390.000000	62.6	47.7	168.0	H	359.0	-0.8	11.4	74.0	6.3	54.0
2412.000000	107.0	---	169.0	H	145.0	-0.7	-33.0	74.0	---	---




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2384.500000	59.7	45.4	185.0	V	358.0	-0.8	14.3	74.0	8.6	54.0
2390.000000	63.1	49.3	159.0	V	45.0	-0.8	10.9	74.0	4.8	54.0
2412.000000	106.5	---	187.0	V	14.0	-0.7	-32.5	74.0	---	---


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11G:2437MHz



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4874.000000	45.2	39.1	188.0	H	242.0	-2.4	28.8	74.0	14.9	54.0
12077.200000	50.3	44.3	168.0	H	214.0	5.2	23.7	74.0	9.7	54.0
16714.900000	52.3	46.0	196.0	H	133.0	6.7	21.8	74.0	8.0	54.0




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK (dB)	Limit – PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4874.000000	43.0	35.9	175.0	V	11.0	-2.7	31.0	74.0	18.1	54.0
6498.400000	48.2	43.6	180.0	V	134.0	0.0	25.8	74.0	10.4	54.0
17153.200000	52.0	44.9	188.0	V	132.0	6.8	22.0	74.0	9.1	54.0


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11G:2462MHz



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4924.000000	45.3	41.3	199.0	H	175.0	-2.3	28.8	74.0	12.7	54.0
12112.600000	49.9	43.9	197.0	H	11.0	5.2	24.1	74.0	10.1	54.0
17112.700000	51.9	46.1	187.0	H	324.0	6.8	22.1	74.0	7.9	54.0




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m	Margin - AV (dB)	Limit - AV (dBuV/m
4924.000000	43.9	38.2	241.0	V	142.0	-2.3	30.1	74.0	15.8	54.0
9504.100000	49.2	42.6	175.0	V	17.0	2.9	24.8	74.0	11.4	54.0
16679.200000	52.7	45.1	158.0	V	199.0	6.7	21.3	74.0	8.9	54.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600


RE_HF907_BRF_Pre



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2462.000000	104.2	---	163.0	H	32.0	-0.4	-30.2	74.0	---	---
2483.500000	53.4	41.7	199.0	H	155.0	-0.3	20.6	74.0	12.3	54.0
2490.400000	49.1	39.2	185.0	H	154.0	-0.3	24.9	74.0	14.8	54.0

RE_HF907_BRF_Pre




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2462.000000	104.0	---	187.0	V	225.0	-0.4	-30.0	74.0	---	---
2483.500000	54.6	43.4	165.0	V	178.0	-0.3	19.4	74.0	10.7	54.0
2493.100000	49.9	37.7	174.0	V	12.0	-0.3	24.1	74.0	16.3	54.0


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11N20:2412MHz



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4824.000000	44.0	38.4	185.0	H	22.0	-2.6	30.0	74.0	15.6	54.0
12113.200000	51.1	46.8	169.0	H	175.0	5.2	22.9	74.0	7.2	54.0
16482.100000	52.7	47.6	187.0	H	174.0	6.2	21.3	74.0	6.4	54.0



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4824.000000	42.9	36.3	178.0	V	359.0	-2.3	31.1	74.0	17.7	54.0
11899.600000	51.0	45.1	186.0	V	166.0	5.1	23.0	74.0	8.9	54.0
17093.800000	52.0	46.8	185.0	V	133.0	6.7	22.0	74.0	7.2	54.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/	Margin - AV (dB)	Limit - AV (dBuV/
2387.000000	52.8	41.2	199.0	H	145.0	-0.8	21.2	74.0	12.8	54.0
2390.000000	55.0	42.6	187.0	H	12.0	-0.8	19.0	74.0	11.4	54.0
2412.000000	104.1	---	169.0	H	174.0	-0.7	-30.1	74.0	---	---




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2385.000000	54.4	41.5	178.0	V	23.0	-0.8	19.7	74.0	12.5	54.0
2390.000000	58.4	46.9	198.0	V	178.0	-0.8	15.6	74.0	7.1	54.0
2412.000000	103.5	---	187.0	V	145.0	-0.7	-29.5	74.0	---	---


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11N20:2437MHz



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+	Limit - PK+	Margin - AV	Limit - AV
4874.000000	42.6	36.5	169.0	H	359.0	-2.5	31.4	74.0	17.5	54.0
11851.300000	50.8	44.5	188.0	H	311.0	5.1	23.2	74.0	9.5	54.0
17102.200000	52.2	46.9	178.0	H	152.0	6.8	21.8	74.0	7.1	54.0




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/	Margin - AV (dB)	Limit - AV (dBuV/m
4874.000000	43.7	36.9	178.0	V	2.0	-2.5	30.3	74.0	17.1	54.0
11900.800000	50.9	45.9	188.0	V	158.0	5.1	23.1	74.0	8.1	54.0
17989.300000	53.6	47.6	189.0	V	174.0	7.4	20.4	74.0	6.4	54.0


TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

802.11N20:2462MHz



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4924.000000	43.7	37.7	185.0	H	114.0	-2.3	30.3	74.0	16.3	54.0
11878.300000	50.3	44.5	199.0	H	247.0	5.1	23.7	74.0	9.5	54.0
17761.000000	52.3	46.1	178.0	H	152.0	7.0	21.7	74.0	7.9	54.0



Limit and Margin


Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4924.000000	43.5	37.9	188.0	V	359.0	-1.5	30.5	74.0	16.1	54.0
11847.700000	49.6	44.5	169.0	V	184.0	5.1	24.4	74.0	9.5	54.0
16658.500000	51.8	45.8	178.0	V	165.0	6.6	22.2	74.0	8.2	54.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2462.000000	102.0	---	185.0	H	280.0	-0.4	-28.0	74.0	---	---
2486.500000	50.1	39.9	199.0	H	318.0	-0.3	23.9	74.0	14.1	54.0
2499.400000	49.1	37.9	178.0	H	352.0	-0.3	24.9	74.0	16.1	54.0



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
2462.000000	102.2	---	188.0	V	124.0	-0.4	-28.2	74.0	---	---
2483.500000	53.7	42.6	199.0	V	153.0	-0.3	20.3	74.0	11.4	54.0
2500.000000	48.8	40.1	177.0	V	147.0	-0.3	25.2	74.0	13.9	54.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

The worst case of Radiated Emission 18-25GHz: Only the worst case listed as below.

18-25GHz Radiated Emission


EUT Information

EUT Name:	Wi-Fi and Bluetooth Module
Model	T1-3S
Client:	Hangzhou Tuya Information Co., Ltd
Op Cond	DC 3.3V power on and transmitted mode, TX_2437MHz at g mode
Operator:	Chengjie Guo
Standard	FCC Part 15.209(a)
Comment:	Horizontal
Sample No.:	SHA-905535-1

Sweep Setup: RE_3116C_pre [EMI radiated]

Hardware Setup:	RE_3116C
Receiver:	[FSV 40]
Level Unit:	dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
18 GHz - 25 GHz	500 kHz	PK+	1 MHz	0.05 s	0 dB



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
18485.000000	48.66	74.00	25.34	100.0	H	171.0	8.1
19778.500000	46.31	74.00	27.69	100.0	H	139.0	8.3
20441.000000	45.30	74.00	28.70	100.0	H	235.0	8.4
21447.500000	44.45	74.00	29.55	100.0	H	122.0	8.6
23142.500000	43.69	74.00	30.31	100.0	H	10.0	8.9
24929.500000	45.01	74.00	28.99	100.0	H	337.0	9.0

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

18-25GHz Radiated Emission

EUT Information


EUT Name:	Wi-Fi and Bluetooth Module
Model	T1-3S
Client:	Hangzhou Tuya Information Co., Ltd
Op Cond	DC 3.3V power on and transmitted mode, TX_2437MHz at g mode
Operator:	Chengjie Guo
Standard	FCC Part 15.209(a)
Comment:	Vertical
Sample No.:	SHA-905535-1

Sweep Setup: RE_3116C_pre [EMI radiated]

Hardware Setup:	RE_3116C
Receiver:	[FSV 40]
Level Unit:	dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
18 GHz - 25 GHz	500 kHz	PK+	1 MHz	0.05 s	0 dB

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
18156.500000	47.90	74.00	26.10	100.0	V	172.0	8.1
19443.000000	46.99	74.00	27.01	100.0	V	46.0	8.4
20269.500000	46.31	74.00	27.69	100.0	V	244.0	8.3
22021.500000	44.33	74.00	29.67	100.0	V	267.0	8.8
23576.500000	44.08	74.00	29.92	100.0	V	192.0	8.9
24457.000000	45.18	74.00	28.82	100.0	V	325.0	9.0

Remark:

(1) Emission level= Original Receiver Reading + Correct Factor
(2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
(3) Margin = limit – Corrected Reading

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

11 Test Equipment List

List of Test Instruments
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal spectrum analyzer	Agilent	N9020B	MY59050168	2025-2-19	2026-2-18
	Wideband power sensor	Rohde & Schwarz	NRP-Z81	105903	2025-2-19	2026-2-18
	10dB Attenuator	Aeroflex Weinschel	CG-4689	93459	2025-2-19	2026-2-18
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2024-8-1	2025-7-31
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2024-8-1	2025-7-31
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2024-8-30	2025-8-29
	Double-ridged waveguide horn antenna	Rohde & Schwarz	HF907	102868	2024-4-14	2025-4-13
	Pre-amplifier	Shenzhen HzEMC	HPA-081843	HYPA23026	2024-4-16	2025-4-15
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2024-6-26	2025-6-25
	Double Ridged Horn Antenna	ETS-Lindgren	3116C	00246076	2023-7-7	2026-7-6
	3m Semi-anechoic chamber	TDK	9X6X6	----	2024-5-8	2027-5-7
	Band reject filter	Wainwright	WRCGV10-2382-2402-2480-2500-52SS	38	2024-8-1	2025-7-31
	Coaxial Cable	----	----	RE Cable 01	2024-8-1	2025-7-31
	Coaxial Cable	----	----	RE Cable 02	2024-8-1	2025-7-31
	Coaxial Cable	----	----	RE Cable 03	2024-8-1	2025-7-31
	Coaxial Cable	----	----	RE Cable 04	2024-8-1	2025-7-31
CE	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2024-8-1	2025-7-31
	LISN	Rohde & Schwarz	ENV216	101924	2024-8-1	2025-7-31

Measurement Software Information			
Test Item	Software	Manufacturer	Version
C	MTS 8310	MWRFtest	3.0.0.0
	Power Viewer	Rohde & Schwarz	V 11.0
RE	EMC 32	Rohde & Schwarz	V10.50.40
CE	EMC 32	Rohde & Schwarz	V9.15.03

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density
- Spurious RF conducted emissions
- Band edge

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

12 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB
Carrier power conducted measurement	50MHz~18GHz, 1.238dB
Spurious Emission Conducted Measurement	9kHz ~40GHz, 1.224dB

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2021, clause 4.4.3 and 4.5.1.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

13 Photographs of Test Set-ups

Refer to the < Test Setup photos >.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600

14 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

----------End of Test Report----------

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
3-13, No.151, Heng Tong Road, Shanghai, 200070, P.R. China
Phone: +86 21 61410123, Fax:+86 21 61408600