

Taskwarrior Nautical V2.0 - Systems Manual

1) Philosophy

Life is a highly complex endeavour so the focus should be on managing systems, not just tasks. Taskwarrior has a powerful system and Nautical gives you two complementary engines for describing recurring work:

Chains for period-based recurrence. Give it a duration like `3d` or `28h` - Nautical calculates the next due time from your completion.

Anchors for calendar-position recurrence. Specify patterns like `w:mon,wed` (Mondays and Wednesdays) or `m:2sat` (2nd Saturday) - Nautical walks your local calendar to find exact matches.

Both respect your time, preserve context across iterations, and stop exactly when you tell them to.

2) Reading this manual

Start with the installation and then jump to point 9 at the recipes library and write some test tasks to get a feel for the system. When you want to find out more about the work under the hood and the capabilities then browse the other sections. Nautical is made to be reliable, intuitive and easy to use. **Best of luck and Godspeed.**

Installation

Nautical = `nautical_core.py` + `on-add-nautical.py` + `on-modify-nautical.py`.

- Put the hooks in place:
 - `on-add-nautical.py` → `~/task/hooks/`
 - `on-modify-nautical.py` → `~/task/hooks/`
 - `chain_core.py` → `~/task/` (or next to the hooks; Nautical looks in both locations)
- Make them executable: `chmod +x ~/task/hooks/on-*-nautical.py`.
- Add the UDAs from headline 4 to your `~/taskrc`.
- Open `config-nautical.toml` and set your preferences.

Here's a clean README-ready "Configuration" section you can drop in.

Configuration

Nautical reads an optional TOML file named `config-nautical.toml` that lives **next to** `nautical_core.py`.

If the file is missing, sensible built-in defaults are used. Changes take effect on the next hook run—no restart needed.

Example: `nautical.toml`

```
# TimeZone and salt for rand
wrand_salt = "nautical|wrand|v2"
tz          = "Australia/Sydney"

# Enable deterministic per-chain IDs and fast chain exports
enable_chain_id = true

# Anchor cache & precompute (ACF+timeline hints) - file-based cache
enable_anchor_cache = true # faster on Termux
anchor_cache_path   = "" # default next to core

# Yearly date token format for anchors like y:06-01 or y:20-04:05-15
# MD = MM-DD (default). DM = DD-MM.
anchor_year_fmt = "MD"

# ChainID toggle
enable_chain_id = true # faster on Termux and a more elegant solution to retrieve all tasks in a chain
```

Keys

enable_chain_id (bool, default: true)

Turns on ChainID stamping and chain-scoped exports:

- New nautical task (has `anchor` or `cp`) gets `chainID = short(uuid)`.
- Spawned tasks inherit parent's ChainID.
- Modify won't overwrite an existing ChainID or stamp linked tasks.
- Hooks prefer `task export chainID:<short>` for O(1) chain fetches.

enable_anchor_cache (bool, default: true)

When true, Nautical precomputes and writes **ACF (Anchor Canonical Form) + anchor hints** (e.g., first due, timeline preview) to a cache file for near-instant previews. When false, no cache file is written and ACF (Anchor Canonical Form) is only kept in memory for the session (never stored as a UDA).

anchor_cache_path (string, default: next to core)

Where to write the cache when `enable_anchor_cache=true`. Path can be relative (to the core's folder) or absolute. Make sure it's writable.

anchor_year_fmt (string, default: `MD`)

Controls how yearly date tokens are parsed and linted:

- `MD` → **MM-DD** (e.g., `y:06-01`, `y:04-20:05-15`)
- `DM` → **DD-MM** (e.g., `y:01-06`, `y:20-04:15-05`)

If a token doesn't match, Nautical's linter will explain the expected format and suggest a fix.

3) Notation & conventions

This section is the “grammar” Nautical understands.

3.1 Engines & where they read time from

- **Chains** (`cp`) - Use a **period** (e.g., `3d`, `28h`, `P2W`). Next link is computed from the **completion time** (and may preserve wall-clock; see §3.2).
- **Anchors** (`anchor`) - Use **calendar positions** (weekly / monthly / yearly). Next link is computed by **walking local calendar dates** that match your pattern.

3.2 Dates, times, and time zones

- **Local vs UTC**: All calendar reasoning (anchors) is done on **local dates**; panels display local time. Internally, times persist in UTC.
- **Seed time**: The first link's `due:` time becomes the wall-clock reference.
 - If your period is a **multiple of 24h** (e.g., `2d`, `1w`), Nautical keeps that wall-clock (due time).
 - What if you want a chain period multiple of 24h but want to have an exact add from completion time? The simplest solution is to use "cp:24h+1s"; that extra second is going to cause the engine to respect the completion time.
 - For other periods (e.g., `28h`, `33h`) Nautical does an **exact add from end**.
- **Per-term time**: You can attach time to specific anchor terms with `@t=HH:MM` (e.g., `w:mon@t=09:00,fri@t=15:00`). If omitted, Nautical uses the seed link's `due:` time.
- **Date style for yearly anchors**: `y:DD-MM` vs `y:MM-DD` is **configurable**; Nautical respects your setting.
 - To modify this setting, which has a default of MM-DD, you have to open `config-nautical.toml` and set your preference.

3.3 Anchor tokens you can use (by family)

Weekly

- **Weekdays**: `mon`, `tue`, `wed`, `thu`, `fri`, `sat`, `sun`.
- **Lists**: `w:mon,fri`.
- **Ranges**: `w:mon-wed` (inclusive).
- **Stepped cadence**: `w/2:mon,tue` (every 2 weeks on Mon & Tue), `w/3:fri` (every 3rd week on Fri).

Monthly – by date

- **Specific days**: `m:1`, `m:15`, `m:31`.
- **Last day**: `m:-1`.
- **Lists**: `m:1,15,-1`.
- **Ranges/buckets**: `m:1:7` (days 1–7), `m:22:28`, etc.
- **Business-day ordinals**: `m:5bd` (5th business day), `m:15bd`.
- **Stepped cadence**: `m/2:-1` (every 2 months on last day), `m/3:1` (every 3 months on the 1st).

Monthly – by weekday position

- **Nth weekday**: `m:1mon` ... `m:5sun` (1st–5th).
- **Last weekday**: `m:last-fri`, `m:last-mon`, etc.
- **Lists**: `m:2mon,4thu`.
- **Stepped cadence**: `m/2:2sat` (every 2 months, 2nd Saturday), `m/4:last-fri`.

Yearly

- **Specific dates**: `y:05-20` (or `y:05-20` / `y:20-05` per your setting).
- **Lists**: `y:01-15,04-15,07-15,10-15`.
- **Ranges (inclusive)**: `y:20-01:27-01` (Jan 20–27), `y:20-04:15-05` (Apr 20–May 15).
- **Random month pick**: `y:rand-10` (one random day in October, deterministic per chain).
- **Leap day**: `y:29-02` (appears only in leap years).
- **Stepped cadence**: `y/3:06-07` (every 3 years on 7 of June)

3.4 Modifiers (`@...`) and what they do

Attach modifiers to **individual terms** (right after them). Multiple modifiers can be chained; order is not important unless noted.

- **Time of day**: `@t=HH:MM` - sets the time for that term only.
 - Example: `w:mon@t=09:00,fri@t=15:00` (Monday at 9, Friday at 15)
- **Business-day rolls** (for date-based terms):
 - `@nbd` - roll to **next business day** if the date falls on weekend.
 - `@pbd` - roll to **previous business day** before the date if the date falls on weekend.
 - `@nw` - **nearest weekday** to that date (Fri if Sat, Mon if Sun).
 - `@bd` - **weekdays only** (filters out Sat/Sun for random/bucket picks).

- **Specific weekday rolls** (apply to a date to find the next/previous named weekday):
 - `@next-mon`, `@prev-fri`, `@next-sat`, `@prev-mon`, etc.
 - For example anchor: "y:12-31@prev-fri" will match the Friday before the end of the year.
- **Scope notes:**
 - Rolls are most meaningful for **monthly day** terms (e.g., `m:1@nbd`).
 - Weekly terms (`w:mon`) already select weekdays; applying `@nbd` is redundant there.
 - Yearly fixed dates pair well with `@t=...`; business-day rolls are typically used through monthly forms.

3.5 Logic & grouping

- **AND:** `+` - both sides must match.
Example: `w:mon + m:1,15` → Mondays that are also the 1st or 15th.
- **OR:** `|` - either side may match.
Example: `m:1sat | m:3fri`.
- **Parentheses:** group sub-expressions.
Example: `(m:1:7 + m:rand@bd) | (m:8:14 + m:rand@bd)`.
- **Precedence:** `+` (AND) binds **tighter** than `|` (OR). Use parentheses to make intent explicit.
- **Whitespace:** optional; ignored inside patterns. When your shell could parse `+` or `|`, **quote** the pattern:
anchor: 'w:mon + m:1,15'

3.6 Modes (anchor backfill semantics)

Attach via UDA: `anchor_mode:skip` (default), `all`, or `flex`.

- **skip** - do **not** backfill missed anchors; jump to the next future match. (training or vitamins)
- **all** - **backfill every** missed anchor before moving forward (useful for bills).
- **flex** - skip backlog **once**, then behave like **all** going forward.
 - Explanation: This is used when the mode of a task is 'all' and you don't want to backfill the overdues but want to continue doing the task going forward; in that instance you modify the anchor_mode to 'flex' and on the next completion of the task, Nautical is going to jump overdues and go to the next anchor match and change the mode to 'all'. This is a one-off convenience mode.

3.7 Caps (hard stops)

- **By count:** `cp_max:N` - stop at the **N-th** link; panels mark second-to-last and last.
- **By date:** `cp_until:YYYY-MM-DD[Tth:mm]` - include anchors **≤ this local moment**; last link is the final anchor on/before that time.
- **Both set:** Nautical stops at **whichever comes first**.
- **Overdue rule:** If a link is overdue, **nothing spawns** until you finish/delete it.

3.7.1 Manual stop of the chain

- Modification of the "chain" UDA to **off**. When this is executed and the task is completed, Nautical isn't going to spawn the next instance.
- Deletion of the task.

3.8 Random behavior (deterministic)

- `w:rand` - one random day per week.
- `m:rand` - one random day each month.
- `m:rand@bd` - one random **weekday** each month.
- `y:rand-MM` - one random day in that month each year.
- check the anchor library for more examples.

3.9 Validation & edge cases

- **Strict parsing:** malformed tokens are rejected (e.g., `m:1,1as5`, non-leap `y:29-02`, out-of-range days).
- **Case-insensitive** tokens (`Mon`, `MON`, `mon` all work); prefer lowercase.
- **Business day definition:** **Mon–Fri**; no holiday calendar... *yet*.
- **Quoting:** Always quote patterns with spaces, `+`, or `|`.
- **One engine per task:** Use either `cp` or `anchor` on the same task.

4) UDAs setup

```
#
# NAUTICAL
#
## Classic Chain Recurrence
uda.cp.type=duration
uda.cp.label=Chain Period
uda.chain.type=string
uda.chain.label=Chain Status
uda.chain.values=on,off
```

```

uda.chain.default=off

## Advanced Anchor Recurrence
uda.anchor.type=string
uda.anchor.label=Anchor
uda.anchor_mode.type=string
uda.anchor_mode.values=flex,all,skip
uda.anchor_mode.default=skip
uda.anchor_mode.label=Anchor Mode

## Limits
uda.chainMax.type=numeric
uda.chainMax.label=Chain Max
uda.chainUntil.type=date
uda.chainUntil.label=Chain Until

## Lineage
uda.prevLink.type=string
uda.prevLink.label=Previous Link
uda.nextLink.type=string
uda.nextLink.label=Next Link
uda.link.type=numeric
uda.link.label=Link Number
uda.chainID.type=string
uda.chainID.label=ChainID
#

```

5) Core behavior

- One pending link.
- Overdue pauses. If a link is overdue, Nautical waits. Complete or delete it to move on.
- Copies your context. Project, tags, UDAs, dependencies, and annotations (timestamps kept) travel to the next link.
- Caps are hard stops. `chainMax` (by count) / `chainUntil` (by date). Panels mark second-to-last and last link.
- Drift-free. Multiples of 24h keep due time; odd spans add exactly.

6) Chains (Classic Chain Recurrence)

6.1 Period syntax you can use

- Short forms: `12d`, `2w`, `28h`, `90m`.
- ISO-8601 works too: `P12D`, `P2W`, `PT28H`.

6.2 Wall-clock vs exact-add

- Multiples of 24h (e.g., `2d`, `1w`) → keep the same local time as the seed task's `due:`.
 - Use your desired chain period +1s or -1s to use exact add. (Example, `cp:3d-1s`)
- Other spans (e.g., `28h`, `33h`) → next due = end + cp (exact add), so odd cadences don't drift.

6.3 Seeding the time

Give the first link a due time; Nautical carries it when appropriate.

```

# Trim the grass every 12 days at 09:00
task add "Trim the grass" due:tomorrow+9h cp:12d

# The next link is going to have a due time of 09:00 regardless if you completed the current one early or late.

```

6.4 Stopping conditions

- By count: `chainMax:5` → stop after 5 links.
 - By date: `chainUntil:2025-12-31` → stop on/at the last link before that date.
 - By manually modifying the chain UDA to off. (task 112 modify chain:off)
 - By deletion of the task.
- Panels show links left and the final date.

```

# 33h cadence, cap by count
task add "Calibration checks" cp:33h chainMax:5 due:today+12h

# Daily at noon, cap by date
task add "Deep work block" cp:1d chainUntil:2025-12-20T12:00 due:today+12h

```

7) Anchors (Real-World Patterns)

7.1 Mental model

Anchors point to **calendar positions** (days, weekdays, nth weekdays) and Nautical walks those exact dates. You can combine rules with AND/OR and adjust to business-day reality.

7.2 Weekly anchors

- **Single weekdays:** `mon`, `tue`, `wed`, `thu`, `fri`, `sat`, `sun`.
- **Lists (comma-separated):** `w:mon,fri`.
- **Ranges:** `w:mon-wed` (equivalent to `w:mon,tue,wed`).
- **Per-term time:** attach `@t=HH:MM` to each weekday if you want **different times per day**, e.g., `w:mon@t=09:00,fri@t=15:00`.
- **Combine with logic:** AND `+` (e.g., `w:mon + m:1,15`), OR `|`.
- **Time tip:** If you omit `@t=`, Nautical uses the **seed task's due time**.

```
# Mon & Fri (skip missed)
task add "Gym sessions" cp_anchor:w:mon,fri anchor_mode:skip due:today

# Range - Mon..Wed
task add "Study block" cp_anchor:w:mon-wed anchor_mode:skip due:today

# Different times per weekday - 09:00 on Mon, 15:00 on Fri
task add "Split training" cp_anchor:w:mon@t=09:00,fri@t=15:00 anchor_mode:skip due:today

# Only Mondays that are also 1st or 15th (AND)
task add "Friends meeting" cp_anchor:'w:mon + m:1,15' due:today

# Either Friday or Sunday (OR)
task add "Weekend wind-down" cp_anchor:'w:fri | w:sun' due:today
```

Tip: You don't have to mention `anchor_mode` in the task addition if you are happy with the default set by the UDA.

7.3 Monthly anchors - by date

- **Specific days:** `m:1`, `m:15`, `m:31`; **last day:** `m:-1`.
- **Lists:** `m:1,15,-1`.
- **Ranges/buckets:** `m:1:7` (days 1–7), `m:22:28`.
- **Business-day ordinals:** `m:5bd` (5th business day), `m:15bd`.
- **Roll modifiers:** `@nbd` (next business day), `@pbd` (previous BD), `@nw` (nearest weekday), `@bd` (weekdays only), and specific weekday rolls `@next-mon`, `@prev-fri`.
- **Per-term time:** attach `@t=HH:MM` to **individual dates for different times per date**, e.g., `m:1@t=09:00,15@t=15:00`.
- **Logic:** AND `+`, OR `|`, and parentheses `(...)`.
- **Time tip:** Without `@t=`, the seed task's `due:` time is used.

```
# 1st and last day (backfill if missed)
task add "Billing sweep" cp_anchor:m:1,-1 anchor_mode:all due:today

# First business day at 09:00
task add "Payroll" cp_anchor:m:1@nbd@t=09:00 anchor_mode:all due:today

# Mid-month on nearest weekday
task add "Mid-month billing" cp_anchor:m:15@nw anchor_mode:skip due:today

# 5th business day
task add "Supplier payments" cp_anchor:m:5bd anchor_mode:all due:today

# Different times per date - 1st at 09:00, 15th at 15:00
task add "Billing windows" cp_anchor:m:1@t=09:00,15@t=15:00 anchor_mode:all due:today

# Buckets (days 1-7) - pair with logic or random
task add "Focus window" cp_anchor:m:1:7 anchor_mode:skip due:today
```

7.4 Monthly anchors - by weekday position

- **Nth weekday:** `m:1mon` ... `m:5sun` (1st–5th).
- **Last weekday:** `m:last-fri`, `m:last-mon`, etc.
- **Lists:** `m:2mon,4thu`.
- **Time:** seed via `due:` or add `@t=HH:MM`.
- **Logic:** AND/OR with other monthly or weekly rules.

```
# 2nd Saturday
task add "Sourdough bake day" cp_anchor:m:2sat anchor_mode:skip due:today

# Last Friday of the month
task add "Design session" cp_anchor:m:last-fri anchor_mode:skip due:today

# 1st Wednesday and 3rd Friday
task add "Parent-teacher meeting" cp_anchor:m:1wed,3fri due:today
```

7.5 Yearly anchors

- **Specific dates:** `y:05-20` (or `y:05-20` / `y:20-05` depending on your configured DD-MM vs MM-DD style).

- **Lists:** `y:01-15,04-15,07-15,10-15`.
- **Ranges** (inclusive): `y:20-01:27-01` (Jan 20–27), `y:20-04:15-05` (Apr 20–May 15).
- **Random month pick:** `y:rand-10` (one day in October, deterministic per chain).
- **Per-term time:** attach `@t=HH:MM` to **individual year-dates** to vary by month, e.g., `y:06-01@t=09:00,12-01@t=15:00`.
- **Logic:** AND/OR with other yearly terms.
- **Note:** Business-day rolls mostly apply to monthly day rules; yearly dates pair well with `@t=` for month-specific times.

```
# Anniversary reminder
task add "Anniversary dinner" cp_anchor:y:05-20 anchor_mode:all due:today

# Quarterly review (simple yearly list)
task add "Quarterly review" cp_anchor:y:01-15,04-15,07-15,10-15 anchor_mode:all due:today

# Different times by month - June 1 at 09:00, Dec 1 at 15:00
task add "Seasonal review" cp_anchor:y:06-01@t=09:00,12-01@t=15:00 anchor_mode:skip due:today

# A random day in October each year
task add "Spooky surprise" cp_anchor:y:rand-10 anchor_mode:skip due:today

# Leap day (appears only in leap years)
task add "Leap-day check" cp_anchor:y:29-02 anchor_mode:skip due:today
```

8) Caps with anchors

Caps stop a chain by **count** (`chainMax`) or by **date** (`chainUntil`). They work with both **Chains** and **Anchors**.

How Nautical counts (Anchors)

- `chainMax` → stops after the **N-th link** (the panel marks *second-to-last* and *last*).
- `chainUntil:YYYY-MM-DD[Thh:mm]` → includes anchors **up to and including** that moment in your **local time**. The final link shown is the last anchor \leq **until**.
- If you set **both**, Nautical stops at the **earliest** of the two limits.

Good to know

- If a link is **overdue**, nothing new spawns until you complete/delete it.
- **Modes** (`skip`/`all`/`flex`) still apply: caps don't override catch-up semantics.
- Panels show **Links left**, **Final (max / until)**, and a timeline that marks (*last link*).

```
# Weekly anchors (Mon/Fri), stop after 6 links
# → exact final date shown in the completion panel
task add "Bootcamp" cp_anchor:w:mon,fri anchor_mode:skip chainMax:6 due:today

# Business-day monthly, stop by date (end of Q4)
task add "AP run" cp_anchor:m:1@nbd due:today chainUntil:2025-12-31T17:00

# Chain (33h cadence), stop after 5 links
task add "Stability checks" cp:33h chainMax:5 due:today+12h
```

9) Recipes library

Chains

```
# Grass trim - every 12 days at 09:00
task add "Trim the grass" due:tomorrow+9h cp:12d

# Vitamins - every 28 hours (exact add)
task add "Take the vitamin" due:today+15h cp:28h

# Two-day sprint - stop after 6 links
task add "Focus sprint" cp:2d chainMax:6 due:today+09:00

# Daily deep work until a deadline (keeps 12:00)
task add "Deep work block" cp:1d chainUntil:2025-12-20T12:00 due:today+12h
```

Anchors

Paste this once and replace `<pattern>` with any of the patterns below:

```
task add "Anchor demo" anchor_mode:skip due:today project:nautical.test anchor:'<pattern>'
```

Tip: attach `@t=HH:MM` **on individual terms** when you need **different times per term** (e.g., 09:00 on Monday, 15:00 on Friday).

Weekly anchors

w:mon	→ Mondays
w:mon,fri	→ Mondays and Fridays
w:mon-wed	→ Monday through Wednesday
w:fri w:sun	→ Fridays or Sundays (OR)
w:mon + m:1,15	→ Mondays that are also the 1st or 15th (AND)
w:mon@t=09:00,fri@t=15:00	→ Mon at 09:00, Fri at 15:00 (per-term times)
w/2:mon,tue	→ every 2 weeks on Monday & Tuesday
w/3:fri	→ every 3 weeks on Friday

Monthly anchors - by date

m:1	→ 1st day of month
m:-1	→ last day of month
m:1,15,-1	→ 1st, 15th, and last day
m:1:7	→ bucket: days 1-7 of month
m:5bd	→ 5th business day of month
m:1@nbd	→ 1st rolled to next business day (if weekend)
m:1@pbd	→ previous business day before the 1st
m:15@nw	→ nearest weekday to the 15th
m:1@t=09:00,15@t=15:00	→ 1st at 09:00, 15th at 15:00 (per-term times)
m/2:-1	→ every 2 months on the last day
m/3:1	→ every 3 months on the 1st
m:1@prev-mon	→ 1st rolled back to previous Monday
m:1@next-sat	→ 1st rolled forward to next Saturday

Monthly anchors - by weekday position

m:2sat	→ 2nd Saturday of each month
m:last-fri	→ last Friday of each month
m:1wed,3fri	→ 1st Wednesday and 3rd Friday
m/2:2sat	→ every 2 months, 2nd Saturday
m/4:last-fri	→ every 4 months, last Friday

Yearly anchors

y:05-20	→ May 20th (DD-MM or MM-DD per your setting)
y:01-15,04-15,07-15,10-15	→ Quarterly markers
y:20-04:15-05	→ Apr 20 - May 15 (inclusive range)
y:rand-10	→ one random day in October (deterministic per chain)
y:29-02	→ Feb 29 (appears only in leap years)
y:06-01@t=09:00,12-01@t=15:00	→ June 1 at 09:00; Dec 1 at 15:00 (per-term times)

Random gallery

w:rand	→ one random day each ISO week
(w:rand w:wed)	→ one random day per week or Wednesday (two days per week)
(w:sat,sun + m:rand)	→ one random Sat/Sun for each month.
(m:rand + y:04-20:05-15)	→ one random day each month and within Apr 20-May 15 each year
m:rand	→ one random day each month
m:rand@bd	→ one random **weekday** each month
(m:1:7 + m:rand@bd)	→ one random weekday chosen from the 1-7 bucket
(m:8:14 + m:rand@bd)	→ one random weekday from 8-14 (use with OR buckets)
y:rand-10@t=12:00	→ one random October date at 12:00

Rolls gallery (quick reference)

@nbd	→ next business day if weekend
@pbd	→ previous business day before a date
@nw	→ nearest weekday to a date
@bd	→ weekdays only (filter)
@next-mon	→ roll forward to the next Monday
@prev-mon	→ roll backward to the previous Monday
@next-sat	→ roll forward to the next Saturday

Anchor combinations (use **+** for AND, **|** for OR, parentheses to group)

'w:mon + m:1,15'	→ Mondays that are also the 1st or 15th
'm:1sat m:3fri'	→ either 1st Saturday or 3rd Friday
'(m:1:7 + m:rand@bd) (m:8:14 + m:rand@bd)'	→ one random BD in days 1-7 OR 8-14
'w:mon-wed w:fri'	→ Mon-Wed or Friday
'w:mon@t=09:00 + m:1:21'	→ Mondays within days 1-21 at 09:00
'm:1@nbd + w:fri'	→ 1st business day that is also a Friday

Modes reminder: `anchor_mode: skip` (skip missed), `all` (backfill all), `flex` (skip backlog once, then be strict).

12) FAQ (short)

Q: How do you change from DD-MM to MM-DD for yearly patterns?

A: Use the config file (config-nautical.toml). The default is MD (MM-DD).

Q: Can you disable caching of the anchors?

A: Use the config file (config-nautical.toml) for the related toggle.

Q: Can you mix `cp` and `anchor` on the same task?

A: Use one engine per task. You can keep separate tasks for each behavior.

Q: Is random really random?

A: No, it's **deterministic per chain** (seeded by the root). Every task gets a fair, stable draw.

Q: Why didn't the link keep the same time?

A: Only multiples of 24h preserve wall-clock. Odd spans add exactly from **end** (completion time).

Q: You forgot to mark as done a classic recurrence task on the day when you completed it?

A: Use the command 'task ID done end:[date-of-completion]'. Nautical is going to calculate the new link from the 'end' variable.

Q: Why not keep the chain as completion time + chain period regardless if it is a multiple of 24h?

A: This way a schedule can be maintained with ease regardless of early/late completions in the day. Small discrepancies will otherwise cause drift. You can't manage a system (effectively) without routines.

Q: Can I backfill missed anchors only once, then go strict?

A: Yes - that's `flex` mode.

13) Performance tips

- **Keep it simple:** prefer concise patterns over massive OR lists.
 - **Termux speed:** Nautical has been designed to run fast on mobile (especially with the file caching enabled).
 - **Quote complex patterns** to avoid shell parsing: `anchor: '(m:1:7 + m:rand) | m:last-fri'`.
-

14) Project status & bug reporting

Nautical is a complex system handling intricate calendar logic, time zone calculations, and state transitions across hundreds of edge cases. While it's been tested rigorously across various scenarios, the surface area for bugs remains significant.

If you encounter unexpected behavior:

- Check your pattern syntax against the reference sections above
- Verify your UDA configuration matches the expected setup
- Review the panel output for clues about what Nautical computed

When something breaks: Open a GitHub issue with:

- Your pattern or chain configuration
- The unexpected behavior (what you expected vs. what happened)
- Relevant panel output or task details
- Your Taskwarrior version and environment (desktop/Termux/etc.)

The more context you provide, the faster we can isolate and fix the issue.

[Repository](#)

Support the project

I've been working on this project through the darkest time of my life, where I'm still at when I'm typing this.

The only thing kept me going was the promise I've made to my-self to never give up.

If Nautical has improved your workflow and you'd like to support continued development:

[Buy me a coffee](#)

Your support helps sustain the time invested in building, testing, and maintaining systems like this. Every contribution is greatly appreciated.