

Taskwarrior Nautical v4.7.0 - Systems Manual

1) Philosophy

Life is a highly complex endeavour so the focus should be on managing systems, not just tasks. Taskwarrior has a powerful system and Nautical gives you two complementary engines for describing recurring work:

Chains for period-based recurrence. Give it a duration like `3d` or `28h` - Nautical calculates the next due time from your completion.

Anchors for calendar-position recurrence. Specify patterns like `w:mon,wed` (Mondays and Wednesdays) or `m:2sat` (2nd Saturday) - Nautical walks your local calendar to find exact matches.

Both respect your time, preserve context across iterations, and stop exactly when you tell them to.

2) Reading this manual

Start with the installation and then jump to point 9 at the recipes library and write some test tasks to get a feel for the system.

When you want to find out more about the work under the hood and the capabilities then browse the other sections. Nautical is made to be reliable, intuitive and easy to use.

Best of luck and Godspeed.

Installation

Nautical = `nautical_core/` + `on-add-nautical.py` + `on-modify-nautical.py` + `on-exit-nautical.py`.

- Put the hooks in place:
 - `on-add-nautical.py` → `~/.task/hooks/`
 - `on-modify-nautical.py` → `~/.task/hooks/`
 - `on-exit-nautical.py` → `~/.task/hooks/`
 - `nautical_core/` → `~/.task/` (package directory; override with `NAUTICAL_CORE_PATH` for dev/tests)

Final setup

- Make them executable: `chmod +x ~/.task/hooks/on-*-nautical.py`.
- Add the UDAs from headline 4 to your `~/.taskrc`.
- Open `config-nautical.toml` and set your preferences.

Here’s a clean README-ready “Configuration” section you can drop in.

Configuration

Nautical reads an optional TOML file named `config-nautical.toml` that lives **next to the** `nautical_core/` package directory.

If the file is missing, sensible built-in defaults are used. Changes take effect on the next hook run.

Config precedence is: `config-nautical.toml` overrides built-in defaults.

Example: `config-nautical.toml`

```
# TimeZone and salt for rand

wrand_salt = "nautical|wrand|v4"

tz = "Australia/Sydney"

# trusted directory for anchor_file and omit_file basenames, check 3.7
anchor_file_dir = ""
omit_file_dir  = ""

# Anchor cache & precompute (ACF+timeline hints) – file-based cache
enable_anchor_cache = true # faster on Termux

anchor_cache_dir = "" # default next to core
anchor_file_dir = "" # trusted directory for anchor_file basenames
omit_file_dir = "" # trusted directory for anchor omit_file basenames

#
# on-modify hook toggles
#

chain_color_per_chain = true
show_timeline_gaps = true
show_analytics = true # set to false to disable analytics panel
analytics_style = "clinical" # "coach" or "clinical" (no "off" mode here)
```

```
analytics_ontime_tol_secs = 14400
verify_import = true
debug_wait_sched = false
recurrence_update_udas = [] # optional date UDAs to carry (example: ["rappel","next_review"])
panel_mode = "rich"
fast_color = true
spawn_queue_max_bytes = 524288
max_chain_walk = 500
max_anchor_iterations = 128
max_link_number = 10000
sanitize_uda = false
sanitize_uda_max_len = 1024
max_json_bytes = 10485760


# Optional anchor aliases. Use with anchor:"@name".
# TOML tables stay active until the next table, so keep top-level settings above this point.
# Examples:
[anchor_presets]
payday = "m:15,-1bd"
workout = "w:mon,wed,fri"


[omit_presets]
holidays = "y:12-24..12-31"
april = "y:apr"
```

Keys

chainID (mandatory in v3+)

- New nautical task (has anchor or cp) gets chainID = short(uuid) .
- Spawned tasks inherit parent’s ChainID.
- Modify won’t overwrite an existing ChainID or stamp linked tasks.
- Hooks use task export chainID:<short> for O(1) chain fetches.
- If your existing chains are missing ChainID, run tools/nautical_backfill_chainid.py .

enable_anchor_cache (bool, default: true)

When true, Nautical precomputes and writes **ACF (Anchor Canonical Form)** + **anchor hints** (e.g., first due, timeline preview) to a cache file for near-instant previews. When false, no cache file is written and ACF (Anchor Canonical Form) is only kept in memory for the session (never stored as a UDA).

anchor_cache_dir (string, default: next to core)

Where to write the cache when enable_anchor_cache=true . Path can be relative (to the core’s folder) or absolute. Make sure it’s writable.

anchor_file_dir (string, default: empty)

Trusted directory for task-level anchor_file: basenames. Nautical resolves anchor_file only inside this directory and rejects paths like ../calendar.csv or /tmp/x.csv .

omit_file_dir (string, default: empty)

Trusted directory for task-level omit_file: basenames. Nautical resolves omit_file only inside this directory and rejects paths like ../holidays.csv or /tmp/x.csv .

NAUTICAL_DNF_DISK_CACHE (env, default: enabled)

On-add JSONL cache for parsed anchors. Set NAUTICAL_DNF_DISK_CACHE=0 to disable.

max_anchor_iterations (int, default: 128)

Upper bound on anchor iteration scans before using a fallback date.

max_link_number (int, default: 10000)

Upper bound for auto-incremented chain link numbers.

sanitize_uda (bool, default: false)

When true, sanitize string fields by removing control characters and clamping length.

sanitize_uda_max_len (int, default: 1024)

Maximum length for sanitized string values.

max_json_bytes (int, default: 10485760)

Maximum size accepted from hook stdin.

NAUTICAL_CLEAR_CACHES (env, default: disabled)

When set to 1 , clear in-process LRU caches after anchor parsing.

DST policy

When Nautical converts a local wall-clock time to UTC (e.g., anchor @t times), it applies a deterministic DST policy:

- Ambiguous times (fall back) choose the earlier occurrence.

- Nonexistent times (spring forward) shift forward to the next valid local time.

on-modify toggles (config)

Hook behavior can be tuned via `config-nautical.toml`:

- **chain_color_per_chain** (bool, default: false)
- **show_timeline_gaps** (bool, default: true)
- **show_analytics** (bool, default: true)
 - Set `show_analytics = false` to disable analytics output.
- **analytics_style** ("coach" or "clinical", default: clinical)
 - `analytics_style` has no "off" value; disable via `show_analytics = false`.
- **analytics_ontime_tol_secs** (int seconds, default: 14400)
- **verify_import** (bool, default: true)
- **debug_wait_sched** (bool, default: false)
- **recurrence_update_udas** (list or CSV string, default: empty)
 - Date-type UDA fields to carry to the next link using the same wall-clock delta rule as `wait` / `scheduled`.
 - Example: `recurrence_update_udas = ["rappel", "next_review"]`
 - Also accepted: `recurrence_update_udas = "rappel,next_review"`
- **panel_mode** ("rich", "fast", or "line", default: rich)
- **fast_color** (bool, default: true)
- **spawn_queue_max_bytes** (int bytes, default: 524288)
- **max_chain_walk** (int, default: 500)

3) Notation and Conventions

This section is the “grammar” Nautical understands.

3.1 Engines & where they read time from

- **Chains** (`cp`) - Use one **period** (e.g., `3d`, `28h`, `P2W`) or a sequence of periods (e.g., `3d,20d,7d`). Next link is computed from the **completion time** (and may preserve wall-clock; see §3.2).
- **Anchors** (`anchor`, `anchor_file`) - Use **calendar positions** and/or **file-backed dates**. Nautical builds one local recurrence stream from:
 - `anchor` expressions
 - `anchor_file` explicit datesand then applies omission rules from `omit` / `omit_file`.

3.2 Dates, times, and time zones

- **Local vs UTC**: All calendar reasoning (anchors) is done on **local dates**; panels display local time. Internally, times persist in UTC.
- **Seed time**: The **first link’s due: time** becomes the wall-clock reference.
- If your period is a **multiple of 24h** (e.g., `2d`, `1w`), Nautical keeps that wall-clock (due time).
- What if you want a chain period multiple of 24h but want to have an exact add from completion time? The simplest solution is to use "cp:24h+1s"; that extra second is going to cause the engine to respect the completion time.
- For other periods (e.g., `28h`, `33h`) Nautical does an **exact add from end**.
- **Per-term time**: You can attach time to specific anchor terms with `@t=HH:MM` (e.g., `w:mon@t=09:00,fri@t=15:00`). If omitted, Nautical uses the seed link’s `due:` time.
- **Date style for yearly anchors**: `y:MM-DD` only (same MM-DD style as Taskwarrior dates).

3.3 Anchor tokens you can use (by family)

Weekly

- **Weekdays**: `mon`, `tue`, `wed`, `thu`, `fri`, `sat`, `sun`.
- **Lists**: `w:mon,fri`.
- **Ranges**: `w:mon..wed` (inclusive).
- **Stepped cadence**: `w/2:mon,tue` (every 2 weeks on Mon & Tue), `w/3:fri` (every 3rd week on Fri).
- **Random**: `w:rand` (one random day each week)

Monthly – by date

- **Specific days**: `m:1`, `m:15`, `m:31`.
- **Last day**: `m:-1`.
- **Lists**: `m:1,15,-1`.
- **Ranges/buckets**: `m:1..7` (days 1–7), `m:22..28`, etc.
- **Business-day ordinals**: `m:5bd` (5th business day), `m:15bd`.
- **Stepped cadence**: `m/2:-1` (every 2 months on last day), `m/3:1` (every 3 months on the 1st).
- **Random**: `m:rand` (one random day each month)

Monthly – by weekday position

- **Nth weekday**: `m:1mon` ... `m:5sun` (1st–5th).
- **Last weekday**: `m:last-fri`, `m:last-mon`, etc.
- **Lists**: `m:2mon,4thu`. (2nd Monday, 4th Thursday)
- **Stepped cadence**: `m/2:2sat` (every 2 months, 2nd Saturday), `m/4:last-fri`.

Yearly

- **Specific dates:** `y:05-20`.
- **Lists:** `y:01-15,04-15,07-15,10-15`.
- **Ranges (inclusive):** `y:20-01..27-01` (Jan 20–27), `y:20-04..15-05` (Apr 20–May 15).
- **Random month pick:** `y:10-rand` (one random day in October, deterministic per chain).
- **Leap day:** `y:02-29` (appears only in leap years).
- **Stepped cadence:** `y/3:06-07` (every 3 years on 7 of June)

3.4 Modifiers (@...) and what they do

Attach modifiers to **individual terms** (right after them). Multiple modifiers can be chained; order is not important unless noted.

- **Time of day:** `@t=HH:MM` - sets the time for that term only.
 - Example: `w:mon@t=09:00,fri@t=15:00` (Monday at 9, Friday at 15)
- **Business-day rolls** (for date-based terms):
 - `@nbd` - roll to **next business day** if the date falls on weekend.
 - `@pbd` - roll to **previous business day** before the date if the date falls on weekend.
 - `@nw` - **nearest weekday** to that date (Fri if Sat, Mon if Sun).
 - `@bd` - **weekdays only** (filters out Sat/Sun for random/bucket picks).
- **Day offsets:**
 - `@+Nd` - shift the matched date **forward by N days** after any roll/filter is applied.
 - `@-Nd` - shift the matched date **backward by N days** after any roll/filter is applied.
 - Examples: `y:04-25@+2d` (Apr 25 each year, 2 days later), `y:04-25@-2d` (Apr 25 each year, 2 days earlier), `m:1@nbd@+1d` (1st rolled to next business day, then moved one day later).
- **Specific weekday rolls** (apply to a date to find the next/previous named weekday):
 - `@next-mon`, `@prev-fri`, `@next-sat`, `@prev-mon`, etc.
 - For example anchor:"y:12-31@prev-fri" will match the Friday before the end of the year (even if 12-31 is a Friday).

Scope notes:

- Rolls are most meaningful for **monthly and yearly day** terms (e.g., `m:1@nbd`, `y:02-28@nw`, `y:03-05@-10d`).
- Weekly terms (`w:mon`) already select weekdays; applying `@nbd` is redundant there.
- Day offsets apply to the final matched date, so they compose naturally with `@t=...` and with rolls such as `@nbd`, `@pbd`, `@nw`, `@next-mon`, and `@prev-fri`.

3.5 Logic & grouping

- **AND:** `+` - both sides must match.

Example: `w:mon + m:1,15` → Mondays that are also the 1st or 15th.

- **OR:** `|` - either side may match.

Example: `m:1sat | m:3fri`.

- **Parentheses:** group sub-expressions.

Example: `(m:1..7 + m:rand@bd) | (m:8..14 + m:rand@bd)`.

- **Precedence:** `+` (AND) binds **tighter** than `|` (OR). Use parentheses to make intent explicit.
- **Whitespace:** optional; ignored inside patterns. When your shell could parse `+` or `|`, **quote** the pattern:

3.6 Modes (anchor backfill semantics)

Attach via UDA: `anchor_mode:skip` (default), `all`, or `flex`.

- **skip** - do **not** backfill missed anchors; jump to the next future match. (training or vitamins)
- **all** - **backfill every** missed anchor before moving forward (useful for bills).
- **flex** - skip backlog **once**, then behave like **all** going forward.
- Explanation: This is used when the mode of a task is 'all' and you don't want to backfill the overdues but want to continue doing the task going forward; in that instance you modify the `anchor_mode` to 'flex' and on the next completion of the task, Nautical is going to jump overdues and go to the next anchor match and change the mode to 'all'. This is a one-off convenience mode.

3.7 Unified anchor recurrence (anchor, anchor_file, omit, omit_file)

Anchor recurrence now has two inclusion sources and two exclusion sources:

- inclusion:
 - `anchor`
 - `anchor_file`
- exclusion:
 - `omit`
 - `omit_file`

Nautical evaluates them as:

- `(anchor U anchor_file) - (omit U omit_file)`

This means:

- `anchor` and `anchor_file` can be used **together** on the same task.
- `omit` and `omit_file` are applied **after** both inclusion sources are merged.
- omitted dates stay visible in timeline-style feedback as explicit skipped rows.

Inclusion sources

- `anchor` uses the full anchor grammar described above.
- `anchor_file` loads explicit dates from a file in `anchor_file_dir`.
- If both are present, Nautical takes the **union** of both occurrence streams.
- If both sources produce the same local datetime, Nautical deduplicates it.

Anchor presets

Reusable anchor expressions can be defined in `config-nautical.toml`:

```
[anchor_presets]
payday = "m:15,-1bd"
workout = "w:mon,wed,fri"

[omit_presets]
holidays = "y:12-24..12-31"
april = "y:apr"
```

Use them with `@name`:

```
task add "Pay bills" anchor:"@payday"
task add "April workouts" anchor:"@workout + y:apr"
task add "Workout except April" anchor:"@workout" omit:"@april"
```

Simple preset panels show the expansion:

```
Preset @payday → m:15,-1bd
```

`[anchor_presets]` and `[omit_presets]` are intentionally separate namespaces. The same `@name` can be defined differently for inclusion and omission.

Accepted `anchor_file` formats:

- Plain text lines:
 - `YYYY-MM-DD`
 - `YYYY-MM-DD..YYYY-MM-DD`
 - blank lines and `#` comments are ignored
- CSV with a `date` column:
 - column order does not matter
 - extra columns are ignored
 - repeated dates are deduplicated

`anchor_file` is basename-only. Nautical resolves it only inside `anchor_file_dir`.

Exclusion sources

- `omit` and `omit_file` apply to **anchor recurrence only**.
- `omit` uses the **same anchor grammar** as `anchor`.
- `omit_file` loads explicit blocked dates from a file in `omit_file_dir`.
- Omitted dates are **skipped, not rolled**. Nautical keeps searching until it finds the next valid anchor date.
- `omit` is **date-based only**. Time modifiers like `@t=09:00` are rejected.
- If `omit` or `omit_file` removes every future match, Nautical fails cleanly instead of looping.

Accepted `omit_file` formats:

- Plain text lines:
 - `YYYY-MM-DD`
 - `YYYY-MM-DD..YYYY-MM-DD`
 - blank lines and `#` comments are ignored
- CSV with a `date` column (and additionally a "description" column):
 - column order does not matter
 - extra columns are ignored
 - repeated dates are deduplicated

Examples:

- Skip all Wednesdays from a weekly pattern:
 - `anchor:w:mon,wed,fri omit:w:wed`
- Merge expression and file-backed dates:
 - `anchor:w:tue,fri anchor_file:2026.csv@-1d@t=12:00,18:00`
- Skip one yearly date window from a monthly random Saturday pattern:
 - `anchor:'m:rand + w:sat' omit:'y:12-24..12-31'`
- Skip a recurring monthly anchor on a specific yearly date:
 - `anchor:m:1 omit:y:01-01`
- Skip dates from a file in `omit_file_dir` :
 - `anchor:'m:rand + w:sat' omit_file:2025.csv`
- Use all four sources together:
 - `anchor:'w:tue,fri | y:05-05' anchor_file:'2026.csv@-1d@t=12:00,18:00' omit:'y:04-28..05-05' omit_file:2026.csv`

3.8 Caps (hard stops)

- **By count:** `chainMax:N` - stop at the **N-th** link; panels mark second-to-last and last.
- **By date:** `chainUntil:YYYY-MM-DD[Thh:mm]` - include anchors $\leq$ **this local moment**; last link is the final anchor on/before that time.
- **Both set:** Nautical stops at **whichever comes first**.
- **Overdue rule:** If a link is overdue, **nothing spawns** until you finish/delete it.

3.8.1 Manual stop of the chain

- Modification of the "chain" UDA to **off**. When this is executed and the task is completed, Nautical isn't going to spawn the next instance.
- **Deletion** of the task.

3.8 Random behavior (deterministic)

- `w:rand` - one random day per ISO week.
- `m:rand` - one random day each month.
- `m:rand@bd` - one random **weekday** each month.
- `y:MM-rand` - one random day in that month each year.
- `y:rand` - one random day in the year.

Random anchors behave like independent dice rolls, but the result is reproducible. Each draw is derived from the random algorithm version, `wrand_salt`, `chainID`, normalized expression, and recurrence period.

- Two tasks using the same random anchor can pick different dates in the same period because their `chainID` values differ.
- The same chain and period always produce the same date. Preview, completion spawning, timeline reconstruction, omit evaluation, retries, and sync therefore agree without storing mutable random state.
- Changing `wrand_salt` deliberately produces a new sequence of future random dates. Keep it stable if existing chains must retain their current sequence.
- Constrained random anchors choose uniformly from all matching dates. For example, `y:rand + y:apr,jul,oct` rolls among every valid date in those three months.
- Repeats and streaks are valid random outcomes. Nautical does not force balancing or shuffle eligible dates into a visible cycle.
- check the anchor library for more examples.

3.9 Validation & edge cases

- **Strict parsing:** malformed tokens are rejected (e.g., `m:1,1a5`, non-leap `y:02-29`, out-of-range days).
- **Case-insensitive** tokens (`Mon`, `MON`, `mon` all work); prefer lowercase.
- **Business day definition:** `Mon..Fri`; if you need to skip dates use "omit" or "omit_file" functionality.
- **Quoting:** Always quote patterns with spaces, `+`, or `|`.
- **One recurrence engine per task:** Use either `cp` **or anchor recurrence** on the same task.
 - Anchor recurrence may use any combination of:
 - `anchor`
 - `anchor_file`
 - `omit`
 - `omit_file`

4) UDAs setup

```
# #####TTFRI
# #####TFRI
# #####TFRI

## Classic Chain Recurrence

uda.cp.type=string
uda.cp.label=Chain Period
uda.chain.type=string
uda.chain.label=Chain Status
```



```
uda.chain.values=on,off
uda.chain.default=off


## Advanced Anchor Recurrence


uda.anchor.type=string
uda.anchor.label=Anchor
uda.anchor_file.type=string
uda.anchor_file.label=Anchor File
uda.anchor_mode.type=string
uda.anchor_mode.values=flex,all,skip
uda.anchor_mode.default=skip
uda.anchor_mode.label=Anchor Mode


uda.omit.type=string
uda.omit.label=Omit
uda.omit_file.type=string
uda.omit_file.label=Omit File


## Limits


uda.chainMax.type=numeric
uda.chainMax.label=Chain Max
uda.chainUntil.type=date
uda.chainUntil.label=Chain Until


## Lineage


uda.prevLink.type=string
uda.prevLink.label=Previous Link
uda.nextLink.type=string
uda.nextLink.label=Next Link
uda.link.type=numeric
uda.link.label=Link Number
uda.chainID.type=string
uda.chainID.label=ChainID


#
```

5) Core behavior

- **One pending link.**
- **Completion does not create duplicates on sync.**
- **Overdue pauses.** If a link is overdue, Nautical waits. Complete or delete it to move on.
- **Copies your context.** Project, tags, UDAs, dependencies, and **annotations (timestamps kept)** travel to the next link.
- **Caps are hard stops.** `chainMax` (by count) / `chainUntil` (by date). Panels mark second-to-last and last link.
- **Drift-free.** Multiples of 24h keep due time; odd spans add exactly.

6) Chains (Classic Chain Recurrence)

6.1 Period syntax you can use

The simplest chain uses one period in `cp`.

```
task add "Trim the grass" cp:12d due:tomorrow+9h
```

This means:

```
#1 is due tomorrow at 09:00
# When #1 is completed, Nautical creates #2 due 12 days later
# When #2 is completed, Nautical creates #3 due 12 days later
```

For a single period, every link uses the same interval. This is the classic Nautical chain: completion advances the chain by one configured period.

Common period forms:

- Short forms: `12d`, `2w`, `28h`, `90m`.
- ISO-8601 works too: `P12D`, `P2W`, `PT28H`.

Advanced period forms:

- Sequence forms: `3d,20d,7d,10d,3d`.
- Random range forms: `rand(3d..7d)`.

6.2 Sequential periods

Once the single-period model is clear, `cp` can also hold a comma-separated sequence of periods:

```
task add "Insect treatment" cp:"3d,20d,7d,10d,3d" due:today
```

Nautical uses one period per completed link:

```
#1 -> #2: 3d
#2 -> #3: 20d
#3 -> #4: 7d
#4 -> #5: 10d
#5 -> #6: 3d
#6 -> #7: 3d  # sequence repeats from the start
```

The active step is derived from the task's `link` number. Nautical does not store a separate sequence index, so the sequence cannot drift out of sync with the chain.

Panels show the active sequence step and period:

```
Step 3/5 (7d)
```

Upcoming cp sequence rows also show the period used for each row.

6.3 Random periods

`cp` can use a bounded random period:

```
task add "Check trap" cp:"rand(3d..7d)" due:today
```

Each link gets one deterministic pick inside the range. The same chain link will resolve to the same period again if Nautical has to recompute it.

Random periods can also be mixed into a sequence:

```
task add "Follow-up cycle" cp:"3d,rand(10d..20d),7d"
```

For “roughly every N days”, use jitter shorthand:

```
task add "Routine inspection" cp:"14d~2d"
```

This means Nautical will pick a deterministic period between `12d` and `16d` for each link. It is equivalent in behavior to a bounded random range, but easier to read for “base period plus/minus spread” schedules.

Nautical shows the selected interval in panels and timelines:

```
Step 2/3 (14d)
```

Use `rand(<duration>..<duration>)` with two dots between the lower and upper bound. For example, `rand(3d..7d)` is valid; `rand(3d-7d)` is not.

This is useful for staged real-world cycles:

- farming or insect lifecycle schedules,

- follow-ups that start close together and then spread out,
- equipment checks after installation or repair,
- training, recovery, or inspection stages.

If you use cp sequences or random cp ranges, `cp` must be configured as a string UDA:

```
uda.cp.type=string
```

If it remains `duration`, Taskwarrior will reject comma-separated or random values before Nautical sees them.

6.4 Wall-clock vs exact-add

- **Multiples of 24h** (e.g., `2d`, `1w`) → keep the same local time as the seed task’s `due:`.
- Use your desired chain period +1s or -1s to use exact add. (Example, cp:3d-1s)
- **Other spans** (e.g., `28h`, `33h`) → next due = **end** + **cp** (exact add), so odd cadences don’t drift.

6.5 Seeding the time

Give the first link a due time; Nautical carries it when appropriate.

```
# Trim the grass every 12 days at 09:00

task add "Trim the grass" due:tomorrow+9h cp:12d


# The next link is going to have a due time of 09:00 regardless if you completed the current one early or late.
```

6.6 Stopping conditions

- **By count:** `chainMax:5` → stop after 5 links.
- **By date:** `chainUntil:2025-12-31` → stop on/at the last link before that date.
- By manually modifying the chain UDA to **off**. (task 112 modify chain:off)
- By deletion of the task.

Panels show **links left** and the **final date**.

```
# 33h cadence, cap by count

task add "Calibration checks" cp:33h chainMax:5 due:today+12h


# Daily at noon, cap by date

task add "Deep work block" cp:1d chainUntil:2025-12-20T12:00 due:today+12h
```

7) Anchors (Real-World Patterns)

7.1 Mental model

Anchors point to **calendar positions** (days, weekdays, nth weekdays) and Nautical walks those exact dates. You can combine rules with AND/OR and adjust to business-day reality.

7.2 Weekly anchors

- **Single weekdays:** `mon`, `tue`, `wed`, `thu`, `fri`, `sat`, `sun`.
- **Lists** (comma-separated): `w:mon,fri`.
- **Ranges:** `w:mon..wed` (equivalent to `w:mon,tue,wed`).
- **Shortcuts:** `w:wk` (Mon–Fri), `w:we` (Sat–Sun).
- **Shortcut:** `w:wd` (Mon–Fri).
- **Per-term time:** attach `@t=HH:MM` to **each weekday** if you want **different times per day**, e.g., `w:mon@t=09:00,fri@t=15:00`.
- **Combine** with logic: AND `+` (e.g., `w:mon + m:1,15`), OR `|`.
- **Time tip:** If you omit `@t=`, Nautical uses the **seed task’s due time**.

```
# Mon & Fri (skip missed)
```

```
task add "Gym sessions" anchor:w:mon,fri

# Mon/Wed/Fri, but skip every Wednesday in April, July and October

task add "Strength training" anchor:w:mon,wed,fri omit:"w:wed + y:apr,jul,oct"

# Monthly date night, but skip dates listed in 2025.csv inside omit_file_dir

task add "Date night" anchor:'m:rand + w:sat' omit_file:2025.csv

# Range - Mon..Wed

task add "Study block" anchor:w:mon..wed

# Different times per weekday - 09:00 on Mon, 15:00 on Fri

task add "Split training" anchor:w:mon@t=09:00,fri@t=15:00

# Only Mondays that are also 1st or 15th (AND)

task add "Friends meeting" anchor:'w:mon + m:1,15' due:today

# Either Friday or Sunday (OR)

task add "Weekend celebration" anchor:'w:fri | w:sun' due:today
```

Tip: You don't have to mention anchor_mode in the task addition if you are happy with the default set by the UDA.

7.3 Monthly anchors - by date

- **Specific days:** `m:1`, `m:15`, `m:31`; **last day:** `m:-1`.
- **Lists:** `m:1,15,-1`.
- **Ranges/buckets:** `m:1..7` (days 1–7), `m:22..28`.
- **Shortcuts:** `m:ld` (last day), `m:lbd` (last business day).
- **Business-day ordinals:** `m:5bd` (5th business day), `m:15bd`.
- **Roll modifiers:** `@nbd` (next business day), `@pbd` (previous BD), `@nw` (nearest weekday), `@bd` (weekdays only), and specific weekday rolls `@next-mon`, `@prev-fri`.
- **Per-term time:** attach `@t=HH:MM` to **individual dates** for **different times per date**, e.g., `m:1@t=09:00,15@t=15:00`.
- **Logic:** AND `+`, OR `|`, and parentheses `( ... )`.
- **Time tip:** Without `@t=`, the seed task’s `due:` time is used.

```
# 1st and last day (backfill if missed)

task add "Billing sweep" anchor:m:1,-1 anchor_mode:all due:today

# First business day at 09:00

task add "Payroll" anchor:m:1@nbd@t=09:00 anchor_mode:all due:today

# Mid-month on nearest weekday

task add "Mid-month billing" anchor:m:15@nw

# 5th business day

task add "Supplier payments" anchor:m:5bd anchor_mode:all due:today

# Different times per date - 1st at 09:00, 15th at 15:00

task add "Billing windows" anchor:m:1@t=09:00,15@t=15:00 anchor_mode:all due:today

# Buckets (days 1-7) - pair with logic or random

task add "Focus window" anchor:m:1..7
```

7.4 Monthly anchors - by weekday position

- **Nth weekday:** `m:1mon` ... `m:5sun` (1st–5th).
- **Last weekday:** `m:last-fri`, `m:last-mon`, etc.
- **Lists:** `m:2mon,4thu`.
- **Time:** seed via `due:` or add `@t=HH:MM`.
- **Logic:** AND/OR with other monthly or weekly rules.

```
# 2nd Saturday

task add "Sourdough bake day" anchor:m:2sat


# Last Friday of the month

task add "Design session" anchor:m:last-fri anchor_mode:all due:today


# 1st Wednesday and 3rd Friday

task add "Parent-teacher meeting" anchor:m:1wed,3fri
```

7.5 Yearly anchors

- **Specific dates:** `y:05-20` (or `y:05-20` / `y:20-05` depending on your configured DD-MM vs MM-DD style).
- **Lists:** `y:01-15,04-15,07-15,10-15`.
- **Ranges** (inclusive): `y:01-20..01-27` (Jan 20–27), `y:04-20..05-15` (Apr 20–May 15).
- **Random month pick:** `y:10-rand` (one day in October, deterministic per chain).
- **Quarter aliases:** `y:q1..q4` (quarter window), `y:q1s` (start month), `y:q1m` (mid month), `y:q1e` (end month).
- **Quarter ranges:** `y:q1s..q2s` (start months of Q1–Q2), `y:q1m..q3m` (mid months), `y:q2e..q4e` (end months).
- **Per-term time:** attach `@t=HH:MM` to **individual year-dates** to vary **by month**, e.g., `y:06-01@t=09:00,12-01@t=15:00`.
- **Logic:** AND/OR with other yearly terms.
- **Note:** Business-day rolls mostly apply to monthly day rules; yearly dates pair well with `@t=` for month-specific times.

```
# Anniversary reminder

task add "Anniversary dinner" anchor:y:05-20 anchor_mode:all due:today


# Quarterly review (simple yearly list)

task add "Quarterly review" anchor:y:01-15,04-15,07-15,10-15 anchor_mode:all due:today


# Different times by month - June 1 at 09:00, Dec 1 at 15:00

task add "Seasonal review" anchor:y:06-01@t=09:00,12-01@t=15:00


# A random day in October each year

task add "Spooky surprise" anchor:y:10-rand


# Leap day (appears only in leap years)

task add "Leap-day check" anchor:y:02-29 *****


# Quarter-based anchors (advanced)

task add "Quarter start kickoff" anchor:'y:q1s..q4s + m:1'

task add "Quarter end closeout" anchor:'y:q1e..q4e + m:lbd' anchor_mode:all due:today

task add "Mid-quarter check-in" anchor:'y:q1m..q4m + m:15'
```

8) Caps with anchors

Caps stop a chain **by count** (`chainMax`) or **by date** (`chainUntil`). They work with both **Chains** and **Anchors**.

How Nautical counts (Anchors)

- `chainMax` → stops after the **N-th link** (the panel marks *second-to-last* and *last*).
- `chainUntil:YYYY-MM-DD[Thh:mm]` → includes anchors **up to and including** that moment in your **local time**. The final link shown is the last anchor $\leq$ **until**.
- If you set **both**, Nautical stops at the **earliest** of the two limits.

Good to know

- If a link is **overdue**, nothing new spawns until you complete/delete it.
- **Modes** (`skip` / `all` / `flex`) still apply: caps don’t override catch-up semantics.
- Panels show **Links left**, **Final (max / until)**, and a timeline that marks (*last link*).

```
# Weekly anchors (Mon/Fri), stop after 6 links

# → exact final date shown in the completion panel

task add "Bootcamp" anchor:w:mon,fri anchor_mode:skip chainMax:6 due:today


# Business-day monthly, stop by date (end of Q4)

task add "AP run" anchor:m:1@nbd due:today chainUntil:2025-12-31T17:00


# Chain (33h cadence), stop after 5 links

task add "Stability checks" cp:33h chainMax:5 due:today+12h
```

9) Recipes library

Chains

```
# Grass trim - every 12 days at 09:00

task add "Trim the grass" due:tomorrow+9h cp:12d


# Vitamins - every 28 hours (exact add)

task add "Take the vitamin" due:today+15h cp:28h


# Insect treatment cycle - staged intervals, then repeat

task add "Insect treatment" cp:"3d,20d,7d,10d,3d" due:today


# Check a trap every 3 to 7 days, deterministic per chain link

task add "Check trap" cp:"rand(3d..7d)" due:today


# Routine inspection roughly every two weeks, plus or minus two days

task add "Routine inspection" cp:"14d~2d" due:today


# Follow-up cycle with a flexible middle interval

task add "Follow-up cycle" cp:"3d,rand(10d..20d),7d" due:today


# Follow-up schedule - close first, then wider gaps and ends after a full cycle

task add "Client follow-up" cp:"1d,3d,7d,14d,30d" chainMax:5 due:today


# Two-day sprint - stop after 6 links
```

```
task add "Focus sprint" cp:2d chainMax:6 due:today+09:00

# Daily deep work until a deadline (keeps 12:00)

task add "Deep work block" cp:1d chainUntil:2025-12-20T12:00 due:today+12h
```

Anchors

Paste this once and replace `<pattern>` with any of the patterns below:

```
task add "Anchor demo"  project:nautical.test anchor:'<pattern>'
```

Tip: attach `@t=HH:MM` **on individual terms** when you need **different times per term** (e.g., 09:00 on Monday, 15:00 on Friday).

Weekly anchors

```
w:mon → Mondays

w:mon,fri → Mondays and Fridays

w:mon..wed → Monday through Wednesday

w:wk → Mon-Fri (weekday shortcut)

w:wd → Mon-Fri (weekday shortcut)

w:we → Sat-Sun (weekend shortcut)

"w:wd@t=09:00 | w:we@t=11:00" → Mon-Fri @ 09:00 and Sat-Sun @ 11:00

w:fri|w:sun → Fridays or Sundays (OR)

w:mon + m:1,15 → Mondays that are also the 1st or 15th (AND)

w:mon@t=09:00,fri@t=15:00 → Mon at 09:00, Fri at 15:00 (per-term times)

w/2:mon,tue → every 2 weeks on Monday & Tuesday

w/3:fri → every 3 weeks on Friday

w:mon..fri@t=09:00,17:30 → Mon-Fri with two times per day
```

Monthly anchors - by date

```
m:1 → 1st day of month

m:-1 → last day of month

m:ld → last day of month (shortcut)

m:1,15,-1 → 1st, 15th, and last day

m:1..7 → bucket: days 1-7 of month

m:5bd → 5th business day of month

m:lbd → last business day of month (shortcut)

m:1@nbd → 1st rolled to next business day (if weekend)

m:1@pbd → previous business day before the 1st

m:15@nw → nearest weekday to the 15th

m:1@t=09:00,15@t=15:00 → 1st at 09:00, 15th at 15:00 (per-term times)
```

m/2:-1 → every 2 months on the last day

m/3:1 → every 3 months on the 1st

m:1@prev-mon → 1st rolled back to previous Monday

m:1@next-sat → 1st rolled forward to next Saturday

m:1 + y:01..06,12 → 1st of month except Jul–Nov (via inclusion)

Monthly anchors - by weekday position

m:2sat → 2nd Saturday of each month

m:last-fri → last Friday of each month

m:1wed,3fri → 1st Wednesday and 3rd Friday

m/2:2sat → every 2 months, 2nd Saturday

m/4:last-fri → every 4 months, last Friday

Yearly anchors

y:05-20 → May 20th (DD-MM or MM-DD per your setting)

y:01-15,04-15,07-15,10-15 → Quarterly markers

y:04-20..05-15 → Apr 20 – May 15 (inclusive range)

y:10-rand → one random day in October (deterministic per chain)

y:02-29 → Feb 29 (appears only in leap years)

y:06-01@t=09:00,12-01@t=15:00 → June 1 at 09:00; Dec 1 at 15:00 (per-term times)

y:q1 → Q1 window (Jan–Mar)

y:q1s → Q1 start month (Jan)

y:q1m → Q1 mid month (Feb)

y:q1e → Q1 end month (Mar)

Random gallery

w:rand → one random day each ISO week

(w:rand | w:wed) → one random day per week or Wednesday (two days per week)

(w:sat,sun + m:rand) → one random Sat/Sun for each month.

"w:sun + y:rand" → one random Sunday every year.

(m:rand + y:04-20..05-15) → one random day each month and within Apr 20–May 15 each year

m:rand → one random day each month.

m:rand@bd → one random **weekday** each month

(m:1..7 + m:rand@bd) → one random weekday chosen from the 1–7 bucket

(m:8..14 + m:rand@bd) → one random weekday from 8–14 (use with OR buckets)

y:10-rand@t=12:00 → one random October date at 12:00

y:rand → one random day in the Year

"(y:rand + y:01-01..06-30) | (y:rand + y:07-01..12-31)" → One random day in Jan..Jun and another in Jul..Dec.

"y:rand + y:apr,jul,oct" → One random day a year selected from the months Apr, Jul, Oct.

Rolls gallery (quick reference)

- @nbd → next business day if weekend
- @pbd → previous business day before a date
- @nw → nearest weekday to a date
- @bd → weekdays only (filter)
- @next-mon → roll forward to the next Monday
- @prev-mon → roll backward to the previous Monday
- @next-sat → roll forward to the next Saturday

Anchor combinations (use + for AND, | for OR, parentheses to group)

- 'w:mon + m:1,15' → Mondays that are also the 1st or 15th
- 'm:1sat | m:3fri' → either 1st Saturday or 3rd Friday
- '(m:1..7 + m:rand@bd) | (m:8..14 + m:rand@bd)' → one random BD in days 1-7 OR 8-14
- 'w:mon..wed | w:fri' → Mon-Wed or Friday
- 'w:mon@t=09:00 + m:1..21' → Mondays within days 1-21 at 09:00
- 'm:1@nbd + w:fri' → 1st business day that is also a Friday

Modes reminder: anchor_mode:skip (skip missed), all (backfill all), flex (skip backlog once, then be strict).

12) FAQ (short)

Q: How do you change the yearly date format?

A: You don't in v3+. Yearly anchors use MM-DD only.

Q: Can you disable caching of the anchors?

A: Use the config file (config-nautical.toml) for the related toggle.

Q: Can you mix cp and anchor on the same task?

A: Use one engine per task. You can keep separate tasks for each behavior.

Q: Is random really random?

A: No, it's deterministic per chain (seeded by the root). Every task gets a fair, stable draw.

Q: Why didn't the link keep the same time?

A: Only multiples of 24h preserve wall-clock. Odd spans add exactly from end (completion time).

Q: You forgot to mark as done a classic recurrence task on the day when you completed it?

A: Use the command 'task ID done end:[date-of-completion]'. Nautical is going to calculate the new link from the 'end' variable.

Q: Why not keep the chain as completion time + chain period regardless if it is a multiple of 24h?

A: This way a schedule can be mentained with ease regardless of early/late completions in the day. Small discrapancies will otherwise cause drift. You can't manage a system (effectively) without routines.

Q: Can I backfill missed anchors only once, then go strict?

A: Yes - that's flex mode.

13) Practical Usage Tips

- **Keep it simple:** prefer concise patterns over massive OR lists.
- **Termux speed:** Nautical has been designed to run fast on mobile (especially with the file caching enabled).
- **Quote complex patterns** to avoid shell parsing: `anchor: '(m:1..7 + m:rand) | m:last-fri'`.

14) Redundancy and Recovery

This section is focused on production hardening for busy systems (1000+ task/hour) .
For most personal setups, Nautical works well without enabling every item below.

Operational Knobs

Common knobs:

- `NAUTICAL_DNF_DISK_CACHE=0` disables the on-add JSONL cache (default: enabled).
- `NAUTICAL_EXIT_STRICT=1` makes on-exit return 1 when spawns are dead-lettered or errored (for scripting).
- `NAUTICAL_DIAG=1` prints diagnostics and config search paths.
- `NAUTICAL_DIAG_LOG=1` persists structured diagnostics to `TASKDATA/.nautical_diag.jsonl`.
- `NAUTICAL_DIAG_LOG_MAX_BYTES=262144` caps the diagnostic log before rotation.
- `NAUTICAL_DURABLE_QUEUE=1` enables fsync for queue/dead-letter writes (safer, slower).
- `NAUTICAL_PROFILE=1` emits lightweight timing (stderr).
- `panel_mode="fast"` forces plain panel rendering (skip Rich).
- `panel_mode="line"` shows a single summary line inside a compact panel.
- `fast_color=false` disables ANSI in fast panels.
- `spawn_queue_max_bytes` caps deferred spawn queue size.
- `spawn_queue_drain_max_items` caps items drained per batch.
- `max_chain_walk` caps how far chain summaries/analytics run.

Data directory resolution:

- Hooks resolve Taskwarrior data dir from `TASKDATA` or hook argv (`data:` / `data.location:` in Hooks v2).
- `rc.data.location=...` is only injected for hook-spawned `task` calls when that data dir is explicit.

Durable Queue Mode

Set `NAUTICAL_DURABLE_QUEUE=1` to force `fsync` on queue/dead-letter writes and queue staging replaces.
This improves crash/power-loss durability but adds IO latency.

Diagnostic Log Mode

Set `NAUTICAL_DIAG_LOG=1` to write structured hook diagnostics to `TASKDATA/.nautical_diag.jsonl`.
Use `NAUTICAL_DIAG_LOG_MAX_BYTES` (default `262144`) to cap file size before automatic rotation.

Spawn Queue + Recovery Model

When a chain link is completed, Nautical queues a spawn intent and the on-exit hook imports the child task and then updates the parent `nextLink`. This avoids re-entering Taskwarrior while it holds its datastore lock.

Queue storage is SQLite-first in `TASKDATA/.nautical_queue.db`. Legacy JSONL queue files are still read for mixed-version compatibility and manual recovery workflows.

If a crash happens between queuing and import, the intent remains in the queue (`.nautical_queue.db` or legacy JSONL compatibility files) and will be picked up on the next Taskwarrior command. Permanent failures are written to `.nautical_dead_letter.jsonl`.

For synced multi-device setups, Nautical treats the next child as a stable chain slot rather than a purely local spawn event:

- The queued child UUID is deterministic for that slot, based on the parent task UUID, `chainID`, recurrence kind, and next link number.
- If two systems complete the same parent before sync converges, both systems derive the same child UUID, so they target the same next task instead of creating two different children.
- During queue drain, on-exit also checks for an already-existing equivalent child by `chainID` + `link` + `prevLink` before importing. If one is found, Nautical links the parent to that task instead of importing another copy.

This prevents future duplicate next links after the updated hooks are installed on all devices that share the database. It does not automatically clean up duplicates that already exist.

On-exit returns 0 by default. Set `NAUTICAL_EXIT_STRICT=1` to return 1 when any spawn was dead-lettered or errored.

Health Check and Alerting

Use the local health checker to watch queue/dead-letter pressure and lock contention (JSONL + SQLite queue metrics):

```
python3 tools/nautical_health_check.py --taskdata ~/.task --json
```

Exit codes:

- `0` healthy

- `1` warning
- `2` critical

Recommended rollout:

- Enable `NAUTICAL_DIAG_LOG=1` first.
- Keep `NAUTICAL_EXIT_STRICT=0` during bake-in.
- Monitor dead-letter and queue metrics.
- Flip `NAUTICAL_EXIT_STRICT=1` once stable.

Periodic alert example:

```
python3 tools/nautical_health_check.py --taskdata ~/.task --queue-crit-bytes 524288
python3 tools/nautical_health_check.py --taskdata ~/.task --queue-db-crit-rows 200
```

Automation templates in `tools/ops/`:

- `nautical-health-check.crontab`
- `nautical-health-check.service`
- `nautical-health-check.timer`
- `nautical_health_check_cron.sh`
- `README.md` (install steps)

Performance Checklist

- Enable disk cache: default on (disable only if debugging).
- Use `panel_mode="fast"` on slow terminals or mobile.
- If you see slowdowns, run `NAUTICAL_PROFILE=1` for a short session.
- For heavy workloads, raise `spawn_queue_max_bytes` and `spawn_queue_drain_max_items`.

Load Testing

```
python3 tools/load_test_nautical.py --tasks 2000 --concurrency 4
python3 tools/load_test_nautical.py --ramp --ramp-start 200 --ramp-step 500 --ramp-max 10000 --concurrency 16
python3 tools/load_test_nautical.py --ramp --done-only --ramp-start 200 --ramp-step 500 --ramp-max 10000 --concurrency 16
python3 tools/load_test_nautical.py --rate-ramp --rate-secs 30 --rate-start 5 --rate-step 5 --rate-max 100
```

Mode summary:

- Batch: fixed number of adds (and optional dones), report latency stats.
- Ramp: increase task count per stage until thresholds are hit.
- Done-only: measure on-modify performance by completing tasks created in the stage.
- Rate-ramp: increase target ops/sec and report throughput and latency limits.

Self-check and diagnostics

```
python3 nautical_navigator.py --self-check
NAUTICAL_DIAG=1 python3 nautical_navigator.py --self-check
```

Anchor explain / validate

```
python3 nautical_navigator.py --explain "m:last-fri"
python3 nautical_navigator.py --validate "w:mon..fri@t=09:00,17:00"
```

Dead-letter recovery (manual)

- Ensure no Taskwarrior command is running.
- Inspect `.nautical_dead_letter.jsonl` in `TASKDATA` and identify entries to retry.
- Preferred: use navigator recovery commands (below) so entries are queued safely.
- Compatibility path: append selected JSON lines back into `.nautical_spawn_queue.jsonl` unchanged (on-exit drains legacy JSONL before SQLite when legacy backlog exists).
- Optionally remove retried lines from `.nautical_dead_letter.jsonl`.
- Run any Taskwarrior command to trigger on-exit drain.

Dead-letter recovery (navigator)

```
python3 nautical_navigator.py --recover-dead-letter --recover-dry-run
python3 nautical_navigator.py --recover-dead-letter --recover-prune
python3 nautical_navigator.py --recover-dead-letter --recover-limit 10
```

- `--recover-dry-run` reports recoverable entries without writing files.
- `--recover-prune` removes recovered lines from dead-letter after requeue.
- `--recover-limit` caps recoveries per run.

Break-glass Mode

If hooks misbehave or Taskwarrior input format changes, bypass hooks temporarily:

```
task rc.hooks=off <command>
```

Environment and Files

- `TASKDATA` points to the Taskwarrior data directory; Nautical reads/writes queues and locks there.
- `NAUTICAL_CORE_PATH` overrides the core load path (dev/tests); it can point to either a directory containing `nautical_core/` or directly to `nautical_core/__init__.py`.
- Hooks also read Hooks v2 argv tokens (`data:` / `data.location:`) to resolve Taskwarrior data dir when `TASKDATA` is not set.
- Hook-spawned `task` subprocesses only force `rc.data.location=...` when data dir is explicit (env/argv), avoiding bad fallbacks on split config/data setups.
- Hook files create these in `TASKDATA` :
 - `.nautical_queue.db` (primary deferred-spawn queue; SQLite, WAL mode)
 - `.nautical_spawn_queue.jsonl` and `.nautical_spawn_queue.lock`
 - `.nautical_spawn_queue.processing.jsonl` (legacy in-flight compatibility file)
 - `.nautical_dead_letter.jsonl` and `.nautical_dead_letter.lock`
 - `.nautical_spawn_queue.lock_failed` (last failure marker only; overwritten each time)
 - `.nautical_spawn_queue.lock_failed.count` (counter for lock contention)

15) Troubleshooting

Nautical is a complex system handling intricate calendar logic, time zone calculations, and state transitions across hundreds of edge cases. While it's been tested rigorously across various scenarios, the surface area for bugs remains significant.

If you encounter unexpected behavior:

- Check your pattern syntax against the reference sections above
- Verify your UDA configuration matches the expected setup
- Review the panel output for clues about what Nautical computed

When something breaks:

Open a GitHub issue with:

- Your pattern or chain configuration
- The unexpected behavior (what you expected vs. what happened)
- Relevant panel output or task details
- Your Taskwarrior version and environment (desktop/Termux/etc.)

The more context you provide, the faster we can isolate and fix the issue.

[Repository](#)

16) Support the project

I've been working on this project through the darkest time of my life, where I'm still at when I'm typing this.

The only thing kept me going was the promise I've made to my-self to never give up.

If Nautical has improved your workflow and you'd like to support continued development:

[Buy me a book](#) , [PayPal](#) or [GitHub](#)

Your support helps sustain the time invested in building, testing, and maintaining systems like this. Every contribution is greatly appreciated.