Catarina Leandro / November 2026

Which comments should a moderator see first?

I built an AI-assisted review prototype and labelled 260 archived TikTok comments using a rubric based on TikTok's public guidelines. I tested whether surrounding text helps identify violations and whether a different queue order helps reviewers reach them in time.

A blind test with 16 comments and two review slots

1	Affectionate joke about a corgi	In review
2	Reassurance about someone's appearance	In review
5	Comment about one person striking another	Outside budget

The context model flagged the only comment I labelled a violation, but ranked it fifth. A reviewer with two slots would have missed it. The examples above are paraphrased.

Two product decisions

1. Keep the context model in offline testing.

On ten validation comments, the comment-only model flagged four of eight harmless comments. Adding the caption and available parent comment reduced this to one. Both models caught the two violations. Those same two cases helped set the alert threshold.

2. Keep the existing queue order.

A rule could move one physical-harm alert to the front. It moved the known case from fifth to first on replay. On two fresh batches of 40, both methods selected the same five comments per batch. The change showed no gain at that review capacity.

What I would test next

I would ask independent reviewers to label fresh English comments for violation, severity and missing context before seeing model scores. At equal staffing and review capacity, I would count serious cases gained and displaced by each order. Reviewer handling times would show whether the simulated budget reflects an actual shift.

One reviewer supplied the original labels. The archived sample is small and partly selected for challenging wording. Operational and multilingual performance still need independent evaluation.