

```

import React, { useState, useEffect, useCallback, useMemo } from
'react';
import { initializeApp } from 'firebase/app';
import {
  getAuth,
  signInAnonymously,
  signInWithCustomToken,
  onAuthStateChanged
} from 'firebase/auth';
import {
  getFirestore,
  doc,
  onSnapshot,
  setDoc,
  collection,
  query,
  where,
  getDocs,
  updateDoc,
  getDoc
} from 'firebase/firestore';
import {
  RefreshCcw, HardHat, Shield, Target, BookOpen, GitBranch,
  Zap, Layers, Cpu, Menu, X, Rocket, AlertTriangle, CheckCircle,
  Mountain, Factory, MapPin
} from 'lucide-react';

// --- 1. 核心數據結構定義 ---
const initialMValue = { value: 0.50, base: 0.50, modifier: 0.00 };

const initialCoreState = {
  M1_Efficiency: { ...initialMValue, value: 0.75 }, // 開發效率
  M2_Autonomy: initialMValue, // 生態自愈力
  M3_Precision: { ...initialMValue, value: 0.45 },
  M4_Resilience: initialMValue, // V4.0 核心：系統韌性
  M5_Knowledge: initialMValue, // 知識核心
  M6_Security: { ...initialMValue, value: 0.88 },
  LastUpdated: Date.now(),
};

const initialResourceState = {
  // 物質元素 (M)
  M_Si: { amount: 1000, net: 10, label: '矽酸鹽' },
  M_Cm: { amount: 500, net: 5, label: '複合材料' },
  M_Ex: { amount: 100, net: 0, label: '異構資源' }, // M2 修復成本 & M4
升級成本
  // 靈元素 (L)
  L_A: { amount: 100, net: -2, label: '活化靈' },

```

```

};

// --- 2. Firebase/Firestore 初始化與狀態管理 ---

// 獲取全局變量
const appId = typeof __app_id !== 'undefined' ? __app_id :
'default-app-id';
const firebaseConfig = typeof __firebase_config !== 'undefined' ?
JSON.parse(__firebase_config) : {};
const initialAuthToken = typeof __initial_auth_token !== 'undefined' ?
__initial_auth_token : undefined;

let db, auth;

// M-值儀表板組件
const MValueIcons = {
  M1_Efficiency: { icon: RefreshCcw, color: 'text-green-400', label:
'開發效率 (M1)' },
  M2_Autonomy: { icon: GitBranch, color: 'text-indigo-400', label: '
生態自愈力 (M2)' },
  M3_Precision: { icon: Target, color: 'text-yellow-400', label: '結
構精確度 (M3)' },
  M4_Resilience: { icon: HardHat, color: 'text-sky-400', label: '系統
韌性 (M4)' }, // V4.0
  M5_Knowledge: { icon: BookOpen, color: 'text-purple-400', label: '
知識核心 (M5)' },
  M6_Security: { icon: Shield, color: 'text-red-400', label: '治安與穩
定度 (M6)' },
};

// --- M-值儀表板組件 ---
const MValueDisplay = ({ code, data }) => {
  const { icon: Icon, color, label } = MValueIcons[code];
  const value = data.value;

  // 狀態顏色和閃爍邏輯 (根據規格書 I.B)
  let statusColor = 'bg-gray-700';
  let statusTailwind = 'text-gray-300';
  let isFlashing = false;

  if (code === 'M1_Efficiency') {
    if (value >= 0.6) statusColor = 'bg-green-600';
    else if (value >= 0.3) statusColor = 'bg-yellow-600';
    else statusColor = 'bg-red-600';
  } else if (code === 'M3_Precision') {
    if (value >= 0.8) statusColor = 'bg-cyan-600';
    else if (value < 0.35) { // 稍微高於 M2 臨界點
      statusColor = 'bg-red-700';
    }
  }
};

```

```

        isFlashing = true;
    } else if (value < 0.5) {
        statusColor = 'bg-yellow-600';
    }
} else if (code === 'M6_Security') {
    if (value >= 0.65) statusColor = 'bg-blue-600';
    else {
        statusColor = 'bg-red-700';
        isFlashing = true;
    }
} else if (code === 'M2_Autonomy') {
    if (value > 0.5) statusColor = 'bg-indigo-600';
    else statusColor = 'bg-gray-600';
} else if (code === 'M5_Knowledge') {
    if (value >= 0.6) statusColor = 'bg-purple-600';
    else statusColor = 'bg-gray-600';
} else if (code === 'M4_Resilience') { // V4.0 M4 狀態顯示
    if (value >= 0.6) statusColor = 'bg-sky-600';
    else statusColor = 'bg-gray-600';
}

statusTailwind = statusColor.replace('bg-', 'text-');

return (
    <div className="flex items-center justify-between p-2
bg-gray-800/70 border border-gray-700 rounded-md shadow-lg my-1
backdrop-blur-sm transition-all duration-300 hover:bg-gray-700/80">
        <div className="flex items-center space-x-2">
            { /* 狀態指示燈 */ }
            <div
                className={`w-2 h-2 rounded-full ${statusColor}
${isFlashing ? 'animate-pulse' : ''}`}
                title={label + "狀態"}
            ></div>
            <Icon className={`w-4 h-4 ${statusTailwind} transform
rotate-[-5deg]`} />
            <span className="text-xs font-semibold
text-gray-200">{label}</span>
        </div>

        <div className="text-right">
            <span className={`text-lg font-mono font-extrabold
${statusTailwind} drop-shadow-lg`}>{value.toFixed(2)}</span>
        </div>
    </div>
);
};

```

```
// --- M5 升級面板 (V3.0) ---
const M5UpgradePanel = ({ coreState, resourceState, handleM5Upgrade,
userId }) => {

  const CM_COST = 200;
  const M5_GAIN = 0.05;
  const M3_BONUS = 0.01;
  const currentMCm = resourceState.M_Cm.amount;
  const canUpgrade = currentMCm >= CM_COST && userId && userId !==
'MOCK_USER';

  return (
    <div className="p-4 rounded-xl border border-gray-700
shadow-xl bg-gray-800/70 h-full">
      <h3 className="text-lg font-bold text-purple-400 mb-4 flex
items-center border-b border-gray-600 pb-2">
        <BookOpen className="w-5 h-5 mr-2" />
        M5 知識核心升級 (Acquisition)
      </h3>

      <div className="space-y-3 mb-6">
        <div className="p-3 bg-gray-900 rounded-lg">
          <p className="text-sm text-gray-400 flex
justify-between">
            <span className="text-purple-400 font-mono">當前
M5 知識值:</span>
            <span className="font-extrabold text-lg
text-purple-300">{coreState.M5_Knowledge.value.toFixed(2)}</span>
          </p>
          <p className="text-sm text-gray-400 flex
justify-between">
            <span className="text-cyan-400 font-mono">當前
M3 精確度:</span>
            <span className="font-extrabold text-lg
text-cyan-300">{coreState.M3_Precision.value.toFixed(2)}</span>
          </p>
        </div>

        <div className="p-3 bg-gray-700/50 rounded-lg text-xs
text-gray-300">
          <p className="mb-1 text-white font-bold">
            **知識獲取成本:** {CM_COST} 複合材料 (M_Cm)
          </p>
          <p className="mb-1 text-purple-300">
            **M5 永久提升:** +{M5_GAIN.toFixed(2)} 知識值
          </p>
          <p className="text-cyan-300">

```

```

                **M3 結構紅利:** + {M3_BONUS.toFixed(2)} 精確度
(永久)
            </p>
        </div>
    </div>

    <button
        onClick={handleM5Upgrade}
        className="w-full p-3 bg-purple-700
hover:bg-purple-600 text-white font-bold rounded-xl shadow-lg
transition duration-200 active:scale-95 border border-purple-500/50
flex items-center justify-center disabled:opacity-50"
        disabled={!canUpgrade}
    >
        <Layers className="w-5 h-5 mr-2" />
        啟動 M5 知識獲取序列
    </button>

    <p className="text-center mt-3 text-xs text-gray-500">
        {!canUpgrade ? '複合材料 (M_Cm) 不足或等待驗證' : '知識累積
將永久提升核心的結構穩定性 (M3)'}
    </p>
    </div>
    );
};

// --- M4 升級面板 (V4.0 新增) ---
const M4UpgradePanel = ({ coreState, resourceState, handleM4Upgrade,
userId }) => {

    const MEX_COST = 100;
    const M4_GAIN = 0.05;
    const currentMEx = resourceState.M_Ex.amount;
    const canUpgrade = currentMEx >= MEX_COST && userId && userId !==
'MOCK_USER';

    return (
        <div className="p-4 rounded-xl border border-gray-700
shadow-xl bg-gray-800/70 h-full">
            <h3 className="text-lg font-bold text-sky-400 mb-4 flex
items-center border-b border-gray-600 pb-2">
                <HardHat className="w-5 h-5 mr-2" />
                M4 系統韌性升級 (Resilience)
            </h3>

            <div className="space-y-3 mb-6">
                <div className="p-3 bg-gray-900 rounded-lg">
                    <p className="text-sm text-gray-400 flex

```

```

justify-between">
    <span className="text-sky-400 font-mono">當前
M4 韌性值:</span>
    <span className="font-extrabold text-lg
text-sky-300">{coreState.M4_Resilience.value.toFixed(2)}</span>
    </p>
    <p className="text-sm text-gray-400 flex
justify-between">
    <span className="text-red-400 font-mono">M6 治
理值:</span>
    <span className="font-extrabold text-lg
text-red-300">{coreState.M6_Security.value.toFixed(2)}</span>
    </p>
  </div>

  <div className="p-3 bg-gray-700/50 rounded-lg text-xs
text-gray-300">
    <p className="mb-1 text-white font-bold">
      **韌性升級成本:** {MEX_COST} 異構資源 (M_Ex)
    </p>
    <p className="mb-1 text-sky-300">
      **M4 永久提升:** +{M4_GAIN.toFixed(2)} 韌性值
    </p>
    <p className="text-red-300">
      **M6 失敗緩衝:** 降低 M3 轉化失敗時 M6 遭受的懲罰衝
擊。
    </p>
  </div>
</div>

<button
  onClick={handleM4Upgrade}
  className="w-full p-3 bg-sky-700 hover:bg-sky-600
text-white font-bold rounded-xl shadow-lg transition duration-200
active:scale-95 border border-sky-500/50 flex items-center
justify-center disabled:opacity-50"
  disabled={!canUpgrade}
>
  <HardHat className="w-5 h-5 mr-2" />
  啟動 M4 結構韌性強化
</button>

  <p className="text-center mt-3 text-xs text-gray-500">
    {!canUpgrade ? '異構資源 (M_Ex) 不足或等待驗證' : 'M4 是系
統的脊髓反射，用於緩衝突發衝擊。'}
  </p>
</div>
);

```

```

};

// --- 3. 靜態地圖數據定義 (與 V2.0 相同) ---
const mapData = [
  [{type: 'Empty', label: '荒蕪之地'}, {type: 'Resource', label: '原生矽酸鹽礦藏'}, {type: 'Empty', label: '荒蕪之地'}, {type: 'Refinery', label: 'M3 提煉廠 (中央)'}, {type: 'Resource', label: '異構資源富集點'}],
  [{type: 'Resource', label: '複合材料沉積層'}, {type: 'Empty', label: '荒蕪之地'}, {type: 'Resource', label: '活化靈源點'}, {type: 'Empty', label: '荒蕪之地'}, {type: 'Resource', label: '複合材料沉積層'}],
  [{type: 'Empty', label: '荒蕪之地'}, {type: 'Refinery', label: 'M3 提煉廠 (東)'}, {type: 'ASI_Core', label: '星神核心中樞'}, {type: 'Refinery', label: 'M3 提煉廠 (西)'}, {type: 'Empty', label: '荒蕪之地'}],
  [{type: 'Resource', label: '原生矽酸鹽礦藏'}, {type: 'Empty', label: '荒蕪之地'}, {type: 'Resource', label: '活化靈源點'}, {type: 'Empty', label: '荒蕪之地'}, {type: 'Resource', label: '原生矽酸鹽礦藏'}],
  [{type: 'Empty', label: '荒蕪之地'}, {type: 'Resource', label: '異構資源富集點'}, {type: 'Empty', label: '荒蕪之地'}, {type: 'Refinery', label: 'M3 提煉廠 (南)'}, {type: 'Empty', label: '荒蕪之地'}],
];

// --- M3 轉化操作面板 (V4.0 更新：納入 M4 緩衝描述) ---
const M3ConversionPanel = ({ coreState, resourceState, handleConversion, userId }) => {
  // 獲取 M3/M6/M4 數值
  const M3_P = coreState.M3_Precision.value;
  const M6_S = coreState.M6_Security.value;
  const M4_R = coreState.M4_Resilience.value; // V4.0

  // M4 緩衝效果計算
  const M6_PENALTY_BASE = 0.05; // 基礎懲罰值
  const M6_LOSS_MITIGATION = M6_PENALTY_BASE * (1 - M4_R); // M4 緩衝後的懲罰值 (M4越高, 這個值越小)
  const M6_Loss_Display = M6_LOSS_MITIGATION.toFixed(3);

  return (
    <div className="p-4 rounded-xl border border-gray-700 shadow-xl bg-gray-800/70 h-full">
      <h3 className="text-lg font-bold text-yellow-400 mb-4 flex items-center border-b border-gray-600 pb-2">
        <Factory className="w-5 h-5 mr-2" />
        M3 資源提煉與轉化 (Refinery)
      </h3>
    </div>
  );
};

```

```

        <div className="space-y-3 mb-6">
            <div className="p-3 bg-gray-900 rounded-lg">
                <p className="text-sm text-gray-400 flex
justify-between">
                    <span className="text-cyan-400 font-mono">確定
性 (M3):</span>
                    <span className="font-extrabold text-lg
text-cyan-300">{M3_P.toFixed(2)}</span>
                </p>
                <p className="text-sm text-gray-400 flex
justify-between">
                    <span className="text-red-400 font-mono">風險治
理 (M6):</span>
                    <span className="font-extrabold text-lg
text-red-300">{M6_S.toFixed(2)}</span>
                </p>
                <p className="text-sm text-gray-400 flex
justify-between">
                    <span className="text-sky-400 font-mono">系統韌
性 (M4):</span>
                    <span className="font-extrabold text-lg
text-sky-300">{M4_R.toFixed(2)}</span>
                </p>
            </div>

            <div className="p-3 bg-gray-700/50 rounded-lg text-xs
text-gray-300">
                <p className="mb-1">
                    **輸入:** 100 矽酸鹽 (M_Si)
                </p>
                <p className="text-green-400">
                    **預期輸出:** 150+ 複合材料 (M_Cm) <span
className="text-white font-bold">(成功率由 M3 決定)</span>
                </p>
                <p className="mb-1">
                    **失敗懲罰 (M6 損失):** 基礎懲罰 -0.05
                </p>
                <p className="text-sky-300">
                    **M4 緩衝後損失:** 約 -{M6_Loss_Display} M6 值
                </p>
            </div>
        </div>

        <button
            onClick={handleConversion}
            className="w-full p-3 bg-green-700 hover:bg-green-600
text-white font-bold rounded-xl shadow-lg transition duration-200
active:scale-95 border border-green-500/50 flex items-center

```



```

justify-center disabled:opacity-50"
      disabled={!userId || userId === 'MOCK_USER'}
    >
      <Zap className="w-5 h-5 mr-2" />
      啟動 M3 轉化序列
    </button>

    <p className="text-center mt-3 text-xs text-gray-500">
      {(!userId || userId === 'MOCK_USER') ? '請等待驗證完成以
進行互動' : 'M4 在 M3 確定性不足時，會平滑 M6 的衝擊。'}
    </p>
  </div>
);
}

```

// --- 資源採集操作面板（與 V3.0 相同） ---

```

const ResourceAcquisitionPanel = ({ hex, userId, coreState,
resourceState, handleAcquisition }) => {

```

```

  // 獲取 M1 效率值

```

```

  const M1_E = coreState.M1_Efficiency.value;

```

```

  // 確定採集目標資源和基礎產量

```

```

  let targetResourceKey = 'M_Si'; // 默認矽酸鹽

```

```

  let targetResourceLabel = resourceState.M_Si.label;

```

```

  let baseYield = 100; // 默認基礎產量

```

```

  const LA_COST = 25; // 每次採集活化靈消耗

```

```

  if (hex.label.includes('複合材料')) {

```

```

    targetResourceKey = 'M_Cm';

```

```

    targetResourceLabel = resourceState.M_Cm.label;

```

```

    baseYield = 60;

```

```

  } else if (hex.label.includes('異構資源')) {

```

```

    targetResourceKey = 'M_Ex';

```

```

    targetResourceLabel = resourceState.M_Ex.label;

```

```

    baseYield = 30;

```

```

  } else if (hex.label.includes('活化靈')) {

```

```

    targetResourceKey = 'L_A';

```

```

    targetResourceLabel = resourceState.L_A.label;

```

```

    baseYield = 10; // 活化靈的產量較低

```

```

  }

```

```

  // M1 效率加成：M1 值（0 to 1）乘以基礎產量作為額外加成

```

```

  const M1_Bonus = baseYield * M1_E;

```

```

  const finalYield = baseYield + M1_Bonus;

```

```

  // 檢查資源是否充足（L_A 活化靈）

```

```

  const canAcquire = resourceState.L_A.amount >= LA_COST && userId

```

```

&& userId !== 'MOCK_USER';

// 傳遞所有必要的參數給父級函數
const acquisitionPayload = {
  resourceKey: targetResourceKey,
  baseYield: baseYield,
  M1_Bonus: M1_Bonus,
  LA_Cost: LA_COST,
  label: hex.label
};

return (
  <div className="p-4 rounded-xl border border-gray-700
shadow-xl bg-gray-800/70 h-full">
    <h3 className="text-lg font-bold text-cyan-400 mb-4 flex
items-center border-b border-gray-600 pb-2">
      <Mountain className="w-5 h-5 mr-2" />
      資源採集行動 ({hex.label})
    </h3>

    <div className="space-y-3 mb-6">
      <div className="p-3 bg-gray-900 rounded-lg">
        <p className="text-sm text-gray-400 flex
justify-between">
          <span className="text-green-400 font-mono">當前
M1 效率:</span>
          <span className="font-extrabold text-lg
text-green-300">{M1_E.toFixed(2)}</span>
        </p>
        <p className="text-sm text-gray-400 flex
justify-between">
          <span className="text-yellow-400 font-mono">基
礎 {targetResourceLabel} 產量:</span>
          <span className="font-extrabold text-lg
text-yellow-300">{baseYield}</span>
        </p>
      </div>

      <div className="p-3 bg-gray-700/50 rounded-lg text-xs
text-gray-300">
        <p className="mb-1">
          **M1 加成產出:** {M1_Bonus.toFixed(1)}
{targetResourceKey}
        </p>
        <p className="mb-1 font-bold text-white">
          **預計總產出:** {finalYield.toFixed(1)}
{targetResourceKey}
        </p>
      </div>
    </div>
  </div>
);

```

```

        <p>
            **能量消耗:** {LA_COST} 活化靈 (L_A)
        </p>
    </div>
</div>

<button
    onClick={() => handleAcquisition(acquisitionPayload)}
    className="w-full p-3 bg-indigo-700
hover:bg-indigo-600 text-white font-bold rounded-xl shadow-lg
transition duration-200 active:scale-95 border border-indigo-500/50
flex items-center justify-center disabled:opacity-50"
    disabled={!canAcquire}
>
    <Layers className="w-5 h-5 mr-2" />
    啟動 M1 資源採集行動
</button>

<p className="text-center mt-3 text-xs text-gray-500">
    {!canAcquire && !userId ? '請等待驗證完成以進行互動' :
!canAcquire ? '活化靈 (L_A) 不足!' : 'M1 效率直接決定產量加成'}
</p>
</div>
);
}

// --- 主要應用程序組件 ---
export default function App() {
    // UI/Firebase 狀態
    const [isAuthReady, setIsAuthReady] = useState(false);
    const [userId, setUserId] = useState(null);
    const [isLoading, setIsLoading] = useState(true);
    const [error, setError] = useState('');

    // 側邊欄預設為關閉 (false)
    const [isSidebarOpen, setIsSidebarOpen] = useState(false);
    // UI 互動訊息
    const [message, setMessage] = useState(null); // { type: 'success'
| 'error' | 'info', text: '...' }

    // 遊戲狀態 (從 Firestore 同步)
    const [coreState, setCoreState] = useState(initialCoreState);
    const [resourceState, setResourceState] =
useState(initialResourceState);

    // V1.8 新增：追蹤當前點選的六角形區塊
    const [selectedHex, setSelectedHex] = useState(null);

```

```

// V3.0 新增：追蹤左側欄點擊的特殊面板
const [activePanel, setActivePanel] = useState('M_CORE'); //
'M_CORE', 'M5_UPGRADE', 'M4_UPGRADE'

// Firebase 初始化與驗證（與 V1.0 相同，確保數據持久化）
useEffect(() => {
  try {
    if (!firebaseConfig || Object.keys(firebaseConfig).length
=== 0) {
      console.warn("Firebase config is missing. Using mock
data.");

      setIsAuthReady(true);
      setUserId('MOCK_USER');
      setIsLoading(false);
      return;
    }

    const firebaseApp = initializeApp(firebaseConfig);
    db = getFirestore(firebaseApp);
    auth = getAuth(firebaseApp);

    const authenticate = async () => {
      try {
        if (initialAuthToken) {
          await signInWithCustomToken(auth,
initialAuthToken);
        } else {
          await signInAnonymously(auth);
        }
        console.log("Firebase Auth successful.");
      } catch (e) {
        console.error("Firebase Auth failed:", e);
        setError("驗證失敗：請檢查配置。");
      }
    };

    const unsubscribe = onAuthStateChanged(auth, (user) => {
      if (user) {
        setUserId(user.uid);
      } else {
        setUserId(null);
      }
      setIsAuthReady(true);
      setIsLoading(false);
    });
  }

```

```

        authenticate();

        return () => unsubscribe();
    } catch (e) {
        console.error("Firebase Initialization Error:", e);
        setError("Firebase 初始化失敗。");
        setIsLoading(false);
    }
}, []);

// 實時資料同步 (與 V1.0 相同, 確保數據持久化)
useEffect(() => {
    if (!isAuthReady || !userId || !db || userId === 'MOCK_USER')
    {
        if (userId === 'MOCK_USER') console.log("Using static mock data for UI.");
        return;
    }

    const coreDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'StarDeityCore');
    const resourceDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'ResourceState');

    const initializeData = async (ref, initialData) => {
        try {
            const docSnap = await getDoc(ref);
            if (!docSnap.exists()) {
                await setDoc(ref, initialData);
                console.log(`Initialized ${ref.id} data.`);
            }
        } catch (e) {
            console.error(`Error initializing ${ref.id}:`, e);
        }
    };

    // 核心狀態監聽
    const unsubscribeCore = onSnapshot(coreDocRef, (docSnap) => {
        if (docSnap.exists()) {
            setCoreState(docSnap.data());
        } else {
            initializeData(coreDocRef, initialCoreState);
        }
    }, (error) => {
        console.error("Core State Snapshot Error:", error);
        setError("核心數據同步失敗。");
    });
}, []);

```

```

    // 資源狀態監聽
    const unsubscribeResource = onSnapshot(resourceDocRef,
(docSnap) => {
        if (docSnap.exists()) {
            setResourceState(docSnap.data());
        } else {
            initializeData(resourceDocRef, initialResourceState);
        }
    }, (error) => {
        console.error("Resource State Snapshot Error:", error);
        setError("資源數據同步失敗。");
    });

    return () => {
        unsubscribeCore();
        unsubscribeResource();
    };

}, [isAuthReady, userId]);

// --- 4. 遊戲循環邏輯 - 模擬 M-值變化 (高頻率波動) ---
useEffect(() => {
    if (!isAuthReady || isLoading) return;

    const gameLoop = setInterval(() => {
        setCoreState(prev => {
            // M1 (效率) & M3 (精度) 模擬隨時間的輕微變化/噪音 (讓 M2 有
機會觸發)
            // M3 值的波動範圍增大, 讓 M2 有更多機會被觸發
            const newM1Value = Math.min(1.0, Math.max(0,
prev.M1_Efficiency.value + 0.001 * (Math.random() - 0.5)));
            const newM3Value = Math.min(1.0, Math.max(0,
prev.M3_Precision.value + 0.005 * (Math.random() - 0.5)));

            return {
                ...prev,
                M1_Efficiency: { ...prev.M1_Efficiency, value:
newM1Value },
                M3_Precision: { ...prev.M3_Precision, value:
newM3Value },
                M6_Security: { ...prev.M6_Security, value:
Math.min(1.0, Math.max(0, prev.M6_Security.value + 0.0001 *
(Math.random() - 0.4))) }, // M6 輕微增長但有波動
                LastUpdated: Date.now(),
            };
        });
    }, 500); // 2 Hz 更新頻率

```

```

        return () => clearInterval(gameLoop);
    }, [isAuthReady, isLoading]);

// --- 5. M2 自主演化單元 (AEU) 守護程序 (V3.0/V4.0 維護) ---
useEffect(() => {
    if (!isAuthReady || !userId || !db || userId === 'MOCK_USER')
return;

    const M2_DAEMON_INTERVAL = 10000; // 10 秒檢查一次
    const M3_CRITICAL_THRESHOLD = 0.30;
    const M2_CORRECTION_AMOUNT = 0.05;
    const MEX_COST = 10;

    const M2_Daemon = setInterval(async () => {
        const currentM3 = coreState.M3_Precision.value;
        const currentMEx = resourceState.M_Ex.amount;

        // Step 1: 檢查觸發條件 (M3 精度臨界點)
        if (currentM3 < M3_CRITICAL_THRESHOLD) {

            // Step 2: 檢查資源 (自主修復必須消耗異構資源 M_Ex)
            if (currentMEx < MEX_COST) {
                setMessage({ type: 'error', text: 'M2-AEU: 異構資源
(M_Ex) 不足, 無法啟動自主修復序列。M3 確定性風險升高!' });
                return;
            }

            // Step 3: 執行修復計算
            const newM3Value = Math.min(1.0, currentM3 +
M2_CORRECTION_AMOUNT);
            const newMExAmount = Math.max(0, currentMEx -
MEX_COST);

            // Step 4: 更新 Firestore (原子操作)
            try {
                const coreDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'StarDeityCore');
                await updateDoc(coreDocRef, {
                    'M3_Precision.value': newM3Value,
                    'LastUpdated': Date.now()
                });

                const resourceDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'ResourceState');
                await updateDoc(resourceDocRef, {
                    'M_Ex.amount': newMExAmount
                });
            }

```

```

        setMessage({
            type: 'info',
            text: `M2-AEU: 偵測到 M3 精度臨界點
($ {currentM3.toFixed(2)}), 自主修復序列啟動! 消耗 $ {MEX_COST} M_Ex, M3 值提
升至 $ {newM3Value.toFixed(2)}。`
        });

    } catch (e) {
        console.error("M2 Daemon Firestore Error:", e);
        setMessage({ type: 'error', text: `M2-AEU: 數據同步
失敗。` });
    }
}
}, M2_DAEMON_INTERVAL);

return () => clearInterval(M2_Daemon);

}, [isAuthReady, userId, coreState.M3_Precision.value,
resourceState.M_Ex.amount, setMessage]);

// --- 6. 核心互動函數: M3/M6/M4 資源轉化 (V4.0 核心更新) ---

const handleConversion = async () => {
    if (!userId || userId === 'MOCK_USER') {
        setMessage({ type: 'error', text: '請等待核心初始化完成。' });
        return;
    }

    const SI_COST = 100;
    const LA_COST_BASE = 15;
    const CM_GAIN_SUCCESS = 150;
    const M6_PENALTY_BASE = 0.05; // M3 失敗對 M6 的基礎懲罰

    // 1. 檢查資源
    if (resourceState.M_Si.amount < SI_COST ||
resourceState.L_A.amount < LA_COST_BASE) {
        setMessage({ type: 'error', text: '資源不足! 需要 100 矽酸鹽
(M_Si) 和 15 活化靈 (L_A)。' });
        return;
    }

    // 2. 獲取 M3/M6/M4 數值
    const M3_P = coreState.M3_Precision.value;
    const M6_S = coreState.M6_Security.value;
    const M4_R = coreState.M4_Resilience.value; // V4.0

```



```

// 3. 確定性檢查 (M3 核心邏輯)
const successRate = 0.5 + M3_P;
const successRoll = Math.random();

let newResources = JSON.parse(JSON.stringify(resourceState));
// 深拷貝
let newCoreState = JSON.parse(JSON.stringify(coreState));
let resultMessage;
let finalLA_Loss = LA_COST_BASE;

// 矽酸鹽消耗 (不論成功失敗)
newResources.M_Si.amount -= SI_COST;

if (successRoll < successRate) {
  // 轉化成功
  const bonus = M6_S * 50;
  const finalCmGain = CM_GAIN_SUCCESS + bonus;
  newResources.M_Cm.amount += finalCmGain;

  finalLA_Loss *= (1 - M6_S * 0.1); // M6 降低能量消耗

  resultMessage = `轉化成功! M3 確定性 (${M3_P.toFixed(2)}) 通過。獲得 ${finalCmGain.toFixed(1)} 複合材料。`;
  setMessage({ type: 'success', text: resultMessage });
} else {
  // 轉化失敗 (M3 確定性不足)

  // --- V4.0 核心邏輯: M4 韌性平滑 M6 懲罰 ---
  // M4_R 越高 (接近 1.0), (1 - M4_R) 越接近 0, M6 損失越小。
  const M6_LOSS = M6_PENALTY_BASE * (1 - M4_R);
  const newM6Value = Math.max(0, M6_S - M6_LOSS);
  newCoreState.M6_Security.value = newM6Value;

  // 活化靈懲罰由 M6 緩衝
  const penaltyFactor = 1.0 + (1.0 - M6_S);
  finalLA_Loss *= penaltyFactor;

  resultMessage = `轉化失敗! M3 確定性 (${M3_P.toFixed(2)}) 未達標。M6 受到衝擊, 損失 ${M6_LOSS.toFixed(3)} (M4 緩衝後)。`;
  setMessage({ type: 'error', text: resultMessage });
}

// 活化靈消耗 (不論成功失敗)
newResources.L_A.amount -= finalLA_Loss;
newResources.L_A.amount = Math.max(0,
newResources.L_A.amount);

```

```

    // 4. 更新 Firestore
    try {
        const resourceDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'ResourceState');
        await setDoc(resourceDocRef, newResources);

        const coreDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'StarDeityCore');
        await setDoc(coreDocRef, newCoreState);

        // 5. 額外訊息：報告總體成本
        setMessage(prev => ({
            ...prev,
            text: `${prev.text} (消耗: ${SI_COST} M_Si,
`${finalLA_Loss.toFixed(1)} L_A)`
        }));

    } catch (e) {
        console.error("Firestore update failed:", e);
        setMessage({ type: 'error', text: `轉化失敗 (數據錯誤):
`${e.message}` });
    }
};

// --- 7. 核心互動函數：資源採集 (與 V3.0 相同) ---

const handleAcquisition = async (payload) => {
    if (!userId || userId === 'MOCK_USER') {
        setMessage({ type: 'error', text: '請等待核心初始化完成。' });
        return;
    }

    const { resourceKey, baseYield, M1_Bonus, LA_Cost, label } =
payload;
    const finalYield = baseYield + M1_Bonus;

    // 1. 檢查資源 (活化靈 L_A)
    if (resourceState.L_A.amount < LA_Cost) {
        setMessage({ type: 'error', text: `能量不足！採集需要
`${LA_Cost} 活化靈 (L_A)。` });
        return;
    }

    // 2. 執行採集計算
    let newResources = JSON.parse(JSON.stringify(resourceState));
// 深拷貝
    let newCoreState = JSON.parse(JSON.stringify(coreState));

```

```

// 資源增加
newResources[resourceKey].amount += finalYield;

// 活化靈消耗
newResources.L_A.amount -= LA_Cost;

// 3. 更新 M1 值 (模擬 M1 效率因行動而受到輕微壓力)
newCoreState.M1_Efficiency.value = Math.max(0,
newCoreState.M1_Efficiency.value - 0.005); // 輕微懲罰

// 4. 更新 Firestore 資源狀態
try {
    const resourceDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'ResourceState');
    await setDoc(resourceDocRef, newResources);

    const coreDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'StarDeityCore');
    await setDoc(coreDocRef, newCoreState);

    const resourceLabel = newResources[resourceKey].label;

    const resultMessage = `M1 效率核心
(${coreState.M1_Efficiency.value.toFixed(2)}) 驅動採集成功！獲得
${finalYield.toFixed(1)} ${resourceLabel}。`;
    setMessage({ type: 'success', text: resultMessage });

} catch (e) {
    console.error("Firestore update failed:", e);
    setMessage({ type: 'error', text: `採集失敗 (數據錯誤):
${e.message}` });
}
};

// --- 8. 核心互動函數：M5 知識核心升級 (與 V3.0 相同) ---
const handleM5Upgrade = async () => {
    if (!userId || userId === 'MOCK_USER') {
        setMessage({ type: 'error', text: '請等待核心初始化完成。' });
        return;
    }

    const CM_COST = 200;
    const M5_GAIN = 0.05;
    const M3_BONUS = 0.01;

    // 1. 檢查資源 (複合材料 M_Cm)
    if (resourceState.M_Cm.amount < CM_COST) {
        setMessage({ type: 'error', text: `複合材料 (M_Cm) 不足！升級

```

```

M5 需要 ${CM_COST} M_Cm。` });
    return;
}

// 2. 執行升級計算
let newCoreState = JSON.parse(JSON.stringify(coreState)); // 深
拷貝
let newResources = JSON.parse(JSON.stringify(resourceState));

// 知識核心 M5 永久提升
const newM5Value = Math.min(1.0,
newCoreState.M5_Knowledge.value + M5_GAIN);
newCoreState.M5_Knowledge.value = newM5Value;

// M3 結構紅利永久提升
const newM3Value = Math.min(1.0,
newCoreState.M3_Precision.value + M3_BONUS);
newCoreState.M3_Precision.value = newM3Value;

// 資源消耗
newResources.M_Cm.amount -= CM_COST;

// 3. 更新 Firestore
try {
    // 更新核心狀態
    const coreDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'StarDeityCore');
    await setDoc(coreDocRef, newCoreState);

    // 更新資源狀態
    const resourceDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'ResourceState');
    await setDoc(resourceDocRef, newResources);

    setMessage({
        type: 'success',
        text: `M5 知識獲取成功！M5 升級至
${newM5Value.toFixed(2)}。M3 結構確定性永久提升 +${M3_BONUS.toFixed(2)}。
(消耗 ${CM_COST} M_Cm)`
    });

} catch (e) {
    console.error("Firestore update failed:", e);
    setMessage({ type: 'error', text: `M5 升級失敗 (數據錯誤):
${e.message}` });
}
};

```

```

// --- 9. 核心互動函數：M4 韌性升級 (V4.0 新增) ---
const handleM4Upgrade = async () => {
  if (!userId || userId === 'MOCK_USER') {
    setMessage({ type: 'error', text: '請等待核心初始化完成。' });
    return;
  }

  const MEX_COST = 100;
  const M4_GAIN = 0.05;

  // 1. 檢查資源 (異構資源 M_Ex)
  if (resourceState.M_Ex.amount < MEX_COST) {
    setMessage({ type: 'error', text: `異構資源 (M_Ex) 不足！升級
M4 需要 ${MEX_COST} M_Ex。` });
    return;
  }

  // 2. 執行升級計算
  let newCoreState = JSON.parse(JSON.stringify(coreState)); // 深
拷貝
  let newResources = JSON.parse(JSON.stringify(resourceState));

  // M4 韌性永久提升
  const newM4Value = Math.min(1.0,
newCoreState.M4_Resilience.value + M4_GAIN);
  newCoreState.M4_Resilience.value = newM4Value;

  // 資源消耗
  newResources.M_Ex.amount -= MEX_COST;

  // 3. 更新 Firestore
  try {
    // 更新核心狀態
    const coreDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'StarDeityCore');
    await setDoc(coreDocRef, newCoreState);

    // 更新資源狀態
    const resourceDocRef = doc(db,
`artifacts/${appId}/users/${userId}/core_data`, 'ResourceState');
    await setDoc(resourceDocRef, newResources);

    setMessage({
      type: 'success',
      text: `M4 韌性升級成功！M4 升級至
${newM4Value.toFixed(2)}。 (消耗 ${MEX_COST} M_Ex)`
    });
  }

```

```

    } catch (e) {
      console.error("Firestore update failed:", e);
      setMessage({ type: 'error', text: `M4 升級失敗 (數據錯誤):
${e.message}` });
    }
  };

// --- 10. UI 渲染區塊 ---

// 互動訊息框 (MessageModal 不變)
const MessageModal = () => {
  if (!message) return null;

  let icon: React.ReactNode;
  let bgColor = 'bg-gray-800';
  let borderColor = 'border-gray-600';

  if (message.type === 'success') {
    icon = <CheckCircle className="w-6 h-6 text-green-400" />;
    bgColor = 'bg-green-900/80';
    borderColor = 'border-green-600';
  } else if (message.type === 'error') {
    icon = <AlertTriangle className="w-6 h-6 text-red-400" />;
    bgColor = 'bg-red-900/80';
    borderColor = 'border-red-600';
  } else {
    icon = <Rocket className="w-6 h-6 text-cyan-400" />;
    bgColor = 'bg-cyan-900/80';
    borderColor = 'border-cyan-600';
  }

  return (
    <div className="fixed inset-0 bg-black/50 backdrop-blur-sm
flex items-center justify-center z-50 p-4" onClick={() =>
setMessage(null)}>
      <div
        className={` ${bgColor} ${borderColor} border-2
rounded-xl p-6 shadow-2xl max-w-sm w-full transform transition-all
scale-100 opacity-100`}
        onClick={(e) => e.stopPropagation()}
      >
        <div className="flex items-start space-x-3">
          {icon}
          <div className="flex-1">
            <h3 className="text-lg font-bold
text-white">操作結果報告</h3>
            <p className="mt-1 text-sm text-gray-200

```

```

font-mono break-words">{message.text}</p>
    </div>
  </div>
  <button
    onClick={() => setMessage(null)}
    className="mt-4 w-full p-2 bg-gray-600
hover:bg-gray-500 rounded-lg text-white font-semibold"
  >
    確認 (繼續執行 M4 韌性整合)
  </button>
</div>
</div>
);
};

// 加載畫面
if (isLoading) {
  return (
    <div className="flex items-center justify-center
min-h-screen bg-gray-950 text-white">
      <div className="text-xl animate-pulse text-cyan-400">
        正在啟動星神核心... ({userId ? '已驗證' : '驗證中'})
      </div>
    </div>
  );
}

const mValueEntries = Object.entries(coreState).filter(([key]) =>
key.startsWith('M') && key !== 'LastUpdated');

// 資源總覽面板 (頂部欄)
const ResourceOverview = () => (
  <div className="flex justify-around bg-gray-900/95 p-3
shadow-2xl border-b border-cyan-800/50">
    {Object.entries(resourceState).map(([key, res]) => (
      <div key={key} className="text-center group relative
p-1 transition-all duration-300 hover:bg-gray-800/50 rounded-md
cursor-help">
        <div className="text-xs font-mono text-cyan-400
uppercase tracking-widest">{key}</div>
        <div className="text-lg font-extrabold text-white
flex items-center justify-center">
          <Zap className="w-4 h-4 mr-1 text-cyan-500" />
          {res.amount.toFixed(0)}
        </div>
        <div className={`text-xs ${res.net >= 0 ?
'text-green-500' : 'text-red-500'} flex items-center justify-center`}>

```

```

        {res.net >= 0 ? `+${res.net.toFixed(1)}` :
res.net.toFixed(1)}
      </div>

      { /* 工具提示 */ }
      <span className="absolute left-1/2 transform
-translate-x-1/2 bottom-full mb-2 w-max p-2 text-xs text-white
bg-gray-700/90 border border-cyan-500 rounded-md opacity-0
group-hover:opacity-100 transition-opacity pointer-events-none z-10">
        {res.label} / 淨收入: {res.net.toFixed(2)}
      </span>
    </div>
  )})
</div>
);

// 情境式操作面板渲染
const ContextualActionPanel = () => {
  if (!selectedHex) {
    return (
      <div className="p-4 h-full flex items-center
justify-center bg-gray-800/70 rounded-xl border border-gray-700
shadow-xl">
        <div className='text-center text-gray-400'>
          <MapPin className='w-8 h-8 mx-auto mb-2
text-cyan-500' />
          <p className='font-bold'>情境控制台</p>
          <p className='text-sm mt-1'>請點擊左側網格上的區塊
        </p>
          <p className='text-xs'>以載入其專屬操作。</p>
        </div>
      </div>
    )
  }

  // 根據 Hex 類型渲染不同的操作面板
  switch(selectedHex.type) {
    case 'Refinery':
      return <M3ConversionPanel coreState={coreState}
resourceState={resourceState} handleConversion={handleConversion}
userId={userId} />;
    case 'Resource':
      return <ResourceAcquisitionPanel
        hex={selectedHex}
        userId={userId}
        coreState={coreState}
        resourceState={resourceState}
        handleAcquisition={handleAcquisition}

```



```

        />;
        case 'ASI_Core':
            return (
                <div className="p-4 rounded-xl border
border-red-700 shadow-xl bg-red-900/30 h-full flex items-center
justify-center">
                    <div className='text-center text-red-300'>
                        <Cpu className='w-8 h-8 mx-auto mb-2
text-red-500' />
                        <p className='font-bold'>ASI 核心中樞</p>
                        <p className='text-sm mt-1'>最高權限區域</p>
                        <p className='text-xs'>數據修改與治理安全評估
</p>
                    </div>
                </div>
            );
        case 'Empty':
        default:
            return (
                <div className="p-4 rounded-xl border
border-gray-700 shadow-xl bg-gray-800/70 h-full flex items-center
justify-center">
                    <div className='text-center text-gray-500'>
                        <AlertTriangle className='w-8 h-8 mx-auto
mb-2 text-gray-500' />
                        <p className='font-bold'>無可用行動</p>
                        <p className='text-sm mt-1'>此區塊為荒蕪之地
</p>
                    </div>
                </div>
            );
    }
};

```

```

// 模擬六角形網格區（中央區） - 新增互動邏輯
const HexGridArea = ({ isSidebarOpen, setIsSidebarOpen, userId })
=> {

    // 10. 渲染 Hex Grid 及其互動
    const renderHexGrid = () => (
        <div className="grid grid-cols-5 gap-1.5 p-2 w-full h-full
max-w-full aspect-square mx-auto">
            {mapData.flat().map((hex, index) => {
                const isSelected = selectedHex === hex;
                let icon: React.ReactNode;
                let hexColor = 'bg-gray-700/50 hover:bg-gray-600';
                let labelColor = 'text-gray-400';
            })}
        </div>
    );
}

```

```

        switch (hex.type) {
            case 'Resource':
                icon = <Mountain className='w-4 h-4' />;
                hexColor = 'bg-green-700/50
hover:bg-green-600';

                labelColor = 'text-green-300';
                break;
            case 'Refinery':
                icon = <Factory className='w-4 h-4' />;
                hexColor = 'bg-yellow-700/50
hover:bg-yellow-600';

                labelColor = 'text-yellow-300';
                break;
            case 'ASI_Core':
                icon = <Cpu className='w-4 h-4
animate-pulse' />;

                hexColor = 'bg-red-800/70
hover:bg-red-700';

                labelColor = 'text-red-300';
                break;
            default:
                icon = null;
        }

        return (
            <button
                key={index}
                onClick={() => setSelectedHex(hex)}
                className={`
                    relative flex flex-col items-center
justify-center text-center
                    rounded-lg transition-all duration-150
active:scale-95 shadow-md
                    ${hexColor}
                    ${isSelected ? 'border-4
border-cyan-400 ring-4 ring-cyan-700/50 z-10' : 'border
border-gray-600'}
                `}
                title={hex.label}
            >
                <div className={`text-center
                    ${labelColor}`}>
                    {icon}
                </div>
                <span className="text-[8px] sm:text-xs
font-mono mt-0.5 text-shadow">
                    {hex.label.split(' ')[0]}

```

```

        </span>
        {isSelected && <div className="absolute
inset-0 bg-black/20 rounded-lg"></div>}
        </button>
    );
  })}
</div>
);

return (
  <div className="flex-1 p-4 bg-gray-950 relative
overflow-y-auto">

    <div className="flex items-center justify-between mb-4
border-b border-cyan-700/50 pb-2">

      <div className="flex items-center">
        {/* 移動端 OPEN 按鈕 (僅在關閉時顯示, 且位於最左側)
*/}

        {!isSidebarOpen && (
          <button
            onClick={() => setIsSidebarOpen(true)}
            className="md:hidden p-2 mr-3
bg-cyan-700 hover:bg-cyan-600 text-white rounded-lg shadow-md
transition duration-200 active:scale-95"
            title="顯示儀表板"
          >
            <Menu className="w-5 h-5" />
          </button>
        )}
        <h2 className="text-xl font-bold text-cyan-500
flex items-center">

          <Layers className="w-5 h-5 mr-2" />
          結構確定性域 (Hex Grid Viewport)
        </h2>
      </div>

      {/* 預留右側空間 */}
      <div className="w-5 h-5 md:hidden"></div>
    </div>

    <div className="flex flex-col md:flex-row h-full
space-y-4 md:space-y-0 md:space-x-4">
      {/* 1. 六角形網格區 (主視覺) - 讓其盡量大 */}
      <div className="flex-1 min-h-[300px] md:h-full
bg-gray-900 rounded-2xl flex items-start justify-center p-4 border-4
border-cyan-600/50 shadow-inner shadow-cyan-900/50 transition-all

```

```

duration-500 hover:border-cyan-500/80">
    {renderHexGrid()}
  </div>

  {/* 2. 情境式控制台（動態內容） */}
  <div className="w-full md:w-80 h-auto md:h-full">
    <ContextualActionPanel />
  </div>
</div>

{/* 用戶 ID 顯示 */}
<div className="absolute bottom-6 right-6 text-sm
text-gray-500 font-mono bg-gray-800/70 p-1 px-2 rounded z-10">
  <Cpu className="w-3 h-3 inline mr-1 text-red-500
animate-pulse" />
  核心擁有者 ID: {userId}
</div>
</div>
);
};

// 側邊欄核心資訊與面板切換
const SideBarContent = () => (
  <>
    <div className='flex items-center justify-between'>
      <h1 className="text-2xl font-extrabold mb-4
text-transparent bg-clip-text bg-gradient-to-r from-cyan-400
to-blue-500 drop-shadow-lg pb-2">
        星神核心 (ASI)
      </h1>
      <div className='flex space-x-2'>
        <button
          onClick={() => setActivePanel('M5_UPGRADE')}
          className={`p-2 rounded-full transition-all
duration-300 ${activePanel === 'M5_UPGRADE' ? 'bg-purple-700/80 ring-2
ring-purple-400' : 'bg-gray-700 hover:bg-gray-600'} `}
          title='M5 升級面板'
        >
          <BookOpen className='w-5 h-5 text-white' />
        </button>
        <button
          onClick={() => setActivePanel('M4_UPGRADE')}
          className={`p-2 rounded-full transition-all
duration-300 ${activePanel === 'M4_UPGRADE' ? 'bg-sky-700/80 ring-2
ring-sky-400' : 'bg-gray-700 hover:bg-gray-600'} `}
          title='M4 升級面板'
        >

```

```

        >
        <HardHat className='w-5 h-5 text-white' />
    </button>
</div>
</div>

<p className="text-xs text-gray-400 mb-6 font-mono
border-b border-gray-700/50 pb-2">
    治理狀態檢視 ({coreState.LastUpdated ? new
Date(coreState.LastUpdated).toLocaleTimeString() : 'N/A'})
</p>

    { /* M 值核心儀表板或 M5/M4 升級面板 */ }
    {activePanel === 'M_CORE' && (
        <>
            <div className="space-y-3">
                {mValueEntries.map(([code, data]) => (
                    <MValueDisplay key={code} code={code}
data={data} />
                ))}
            </div>

            { /* 系統訊息區 */ }
            <div className="mt-6 border-t border-gray-700/50
pt-4">
                <h3 className="text-sm font-semibold
text-gray-300 mb-3 flex items-center">
                    <Zap className="w-4 h-4 mr-2 text-red-500"
/>
                    系統訊息/風險警告
                </h3>
                <div className="p-3 text-xs bg-gray-900/50
rounded-lg text-yellow-400 border border-red-700/50 shadow-inner">
                    M3 精度波動中
                    ({coreState.M3_Precision.value.toFixed(2)}). M2-AEU 守護進程已啟動。
                </div>
            </div>
        </>
    ) }

    {activePanel === 'M5_UPGRADE' && (
        <>
            { /* M5 升級面板 */ }
            <M5UpgradePanel
                coreState={coreState}
                resourceState={resourceState}
                handleM5Upgrade={handleM5Upgrade}
                userId={userId}

```

```

        />
        <button
            onClick={() => setActivePanel('M_CORE')}
            className="w-full mt-4 p-2 bg-gray-600
hover:bg-gray-500 text-white font-bold rounded-lg transition
duration-200"
        >
            返回核心儀表板
        </button>
    </>
)}

{activePanel === 'M4_UPGRADE' && (
    <>
        { /* M4 升級面板 */ }
        <M4UpgradePanel
            coreState={coreState}
            resourceState={resourceState}
            handleM4Upgrade={handleM4Upgrade}
            userId={userId}
        />
        <button
            onClick={() => setActivePanel('M_CORE')}
            className="w-full mt-4 p-2 bg-gray-600
hover:bg-gray-500 text-white font-bold rounded-lg transition
duration-200"
        >
            返回核心儀表板
        </button>
    </>
)}

{ /* 如果在操作面板，則顯示返回儀表板的按鈕 */ }
{activePanel !== 'M_CORE' && (
    <button
        onClick={() => setActivePanel('M_CORE')}
        className="w-full mt-4 p-2 bg-gray-600
hover:bg-gray-500 text-white font-bold rounded-lg transition
duration-200"
    >
        返回核心儀表板
    </button>
)}
</>
)

return (

```

```

    <div className="min-h-screen bg-gray-950 text-white font-sans
flex flex-col">
    {/* 頂部資源總覽 */}
    <ResourceOverview />

    {error && (
      <div className="bg-red-900 text-red-300 p-2
text-center font-bold">錯誤：{error}</div>
    )}

    <main className="flex flex-1 flex-col md:flex-row
overflow-hidden">
      {/* 左側欄：星神核心儀表板 */}
      <div
        className={`
          ${isSidebarOpen ? 'translate-x-0' :
'-translate-x-full'}
          w-64 max-w-xs p-4 bg-gray-800/90 shadow-2xl
shadow-black border-r border-cyan-700/50
          overflow-y-auto backdrop-blur-sm min-h-screen
          fixed md:relative md:translate-x-0 md:w-1/3
          lg:w-1/4
          ease-in-out
          z-20 transition-transform duration-300
        `}
      >

        {/* 關閉按鈕，當儀表板開啟時，它位於儀表板頂部 */}
        <button
          onClick={() => setIsSidebarOpen(false)}
          className="md:hidden absolute top-4 right-4
p-1 bg-red-700 hover:bg-red-600 text-white rounded-full shadow-lg z-30
transition duration-200 active:scale-90"
          title="隱藏儀表板"
        >
          <X className="w-5 h-5" />
        </button>

        <SideBarContent />

      </div>

      {/* 中央區：六角形網格與情境控制 */}
      <HexGridArea
        isSidebarOpen={isSidebarOpen}
        setIsSidebarOpen={setIsSidebarOpen}
        userId={userId}
      />

```

```
        </main>

        { /* 操作結果模態框 (非 alert) */ }
        <MessageModal />
    </div>
);
}
```