

Classes-And-Metrics (CAM): a Collection of Snapshots of GitHub Java Repositories

Yegor Bugayenko

yegor256@huawei.com

Huawei, Russia, Moscow

Abstract

Even though numerous researchers require stable datasets along with source code and basic metrics calculated on them, neither GitHub nor any other code hosting platform provides such a resource. Consequently, each researcher must download their own data, compute the necessary metrics, and then publish the dataset somewhere to ensure it remains accessible indefinitely. Our CAM project addresses this need. CAM is an open-source software capable of cloning Java repositories from GitHub, filtering out unnecessary files, parsing Java classes, and computing metrics such as Cyclomatic Complexity, Halstead Effort and Volume, C&K metrics, Maintainability Metrics, LCOM5 and HND, as well as some Git-based Metrics. At least once a year, we execute the entire script, a process which requires a minimum of ten days on a very powerful server, to generate a new dataset. Subsequently, we publish it on Amazon S3, thereby ensuring its availability as a reference for researchers. The latest archive of 2.2Gb that we published on the 2nd of March, 2024 includes 532K Java classes with 48 metrics for each class.

1 Motivation

First, research projects that analyze Java code usually extract it from repositories where open-source projects store their files, such as GitHub. It is common practice in papers explaining results to fully disclose the coordinates of the open-source code being extracted. However, source code is inherently volatile: repositories change their locations and files are modified, as demonstrated by Robles [8]. To ensure the replicability of their research results, paper authors must somehow guarantee that the source code used at the time of research remains available and intact throughout the paper’s lifetime. One obvious solution would be to make copies of the

repositories being extracted and then host them somewhere they are “forever” available.

Second, research methods typically involve filtering out certain types of files found in repositories, such as plain text documents or graphic images, which are not source code. Additionally, some source code files may need to be excluded because they are auto-generated or contain unparseable Java code, making them unsuitable for most methods of code analysis.

Third, most source code analysis research involves collecting metrics from the files found in extracted repositories, such as lines of code, complexity, cohesion, and so on. Most of these metrics are already known, and their retrieval mechanisms are trivial, as summarized by Nuñez-Varela et al. [7].

Thus, there is an obvious duplication of work among different research projects: (a) they have to “host” extracted data to ensure desirable replicability, as noted by Cosentino et al. [3], (b) they must implement filtering of source code fetched from GitHub, and (c) they have to collect popular metrics. Having a ready-to-use archive of downloaded, filtered, and measured source code files would help many research projects reduce the amount of work required.

2 Methodology

In order to help research projects in all three tasks mentioned above, we created CAM¹ archive: an open-source collection of scripts regularly (at least once a year) being executed in Docker containers in our proprietary computing environment with results published in form of an “immutable” ZIP archive as either a GitHub “asset” attached to the next release of CAM repository or an object in Amazon S3 (depending on the size of the archive). Here, immutability is not technically guaranteed but promised: even though we, being the owners of

¹<https://github.com/yegor256/cam>

CAM repository, are able to replace any previously created assets, we are not going to do so in order to not jeopardize the idea. Instead, new releases will be published retaining previously generated assets unmodified.

At the time of writing, CAM repository consists of scripts written in Makefile, Python, Ruby, and Bash, which do exactly the following:

- Fetch 1024 repositories from GitHub, which have `java` language tag, have more than 1K and less than 10K stars, and are at least as big as 200Kb;
- Remove files without `.java` extension, Java files with syntax errors, `package-info.java` files, files with lines longer than 1024 characters, and unit tests;
- Calculate KLoC, NCSS, Cyclomatic Complexity [6], Cognitive Complexity [2], LCOM5 [5], NHD [4], TCC [1], number of attributes, number of constructors, number of methods, number of static methods, and some other metrics.

The size of the latest archive generated on the 2nd of March, 2024 is 2.2Gb. It includes 532K Java classes with 48 metrics for each class. It took us 10 days on a server with eight vCPU and 32Gb of RAM to generate the data.

Conclusion

We expect CAM archive to be used by research teams analyzing Java source, which want (a) to guarantee replicability of their results and (b) to reduce data pre-processing efforts. We also expect open-source community to contribute to CAM scripts, making filtering more powerful and adding more code metrics to the collection.

References

- [1] James M. Bieman and Byung-Kyoo Kang. 1995. Cohesion and Reuse in an Object-Oriented System. *SIGSOFT Software Engineering Notes* 20, SI (1995), 259–262.
- [2] G. Ann Campbell. 2018. Cognitive Complexity: An Overview and Evaluation. In *Proceedings of the International Conference on Technical Debt*. 57–58.
- [3] Valerio Cosentino, Javier L. Cánovas Izquierdo, and Jordi Cabot. 2017. A Systematic Mapping Study of Software Development With GitHub. *IEEE Access* 5 (2017), 7173–7192. <https://doi.org/10.1109/ACCESS.2017.2682323>
- [4] Steve Counsell, Stephen Swift, and Jason Crampton. 2006. The Interpretation and Utility of Three Cohesion Metrics for Object-Oriented Design. *ACM Transactions on Software Engineering and Methodology (TOSEM)* 15, 2 (2006), 123–149. <https://doi.org/10.1145/1131421.1131422>
- [5] Brian Henderson-Sellers, Larry L. Constantine, and Ian M. Graham. 1996. Coupling and Cohesion (Towards a Valid Metrics Suite for Object-Oriented Analysis and Design). *Object Oriented Systems* 3, 3 (1996), 143–158.
- [6] Thomas J. McCabe. 1976. A Complexity Measure. *IEEE Transactions on Software Engineering* 4 (1976), 308–320.
- [7] Alberto S Nuñez-Varela, Héctor G Pérez-Gonzalez, Francisco E Martínez-Perez, and Carlos Soubervielle-Montalvo. 2017. Source Code Metrics: A Systematic Mapping Study. *Journal of Systems and Software* 128 (2017), 164–197.
- [8] Gregorio Robles. 2010. Replicating MSR: A Study of the Potential Replicability of Papers Published in the Mining Software Repositories Proceedings. In *IEEE Working Conference on Mining Software Repositories*. 171–180. <https://doi.org/10.1109/MSR.2010.5463348>