

Genomic Repeat inference from Depth (GRiD): A Pipeline for Haplotype-Resolved Large VNTR Copy Number Estimation

Zachary Caterer^{1,2,3}, Meng Lin¹, Qiang An⁴, Maizy S. Brasher¹, Elbay Aliyev¹, Harriet Dashnow¹, Joanne B. Cole^{1,3}, Ethan Lange¹, Mariaelisa Graff⁴, Christy L. Avery⁴, Christopher R. Gignoux^{1,3}, and Maggie Stanislawski^{1,3}

¹ Department of Biomedical Informatics, University of Colorado Anschutz, Aurora, CO USA ² Department of Chemical and Biological Engineering, University of Colorado Boulder, Boulder, CO USA ³ Interdisciplinary Quantitative Biology PhD Program, Biofrontiers Institute, University of Colorado Boulder, Boulder, CO USA ⁴ Department of Epidemiology, University of North Carolina Chapel Hill, Chapel Hill, NC USA ^{*} Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Variable number tandem repeats (VNTRs) are genomic regions in which a sequence motif is repeated in tandem a variable number of times across individuals. Large VNTRs, repeat units spanning hundreds to thousands of base pairs, are a substantial source of structural variation in the human genome and have been linked to complex traits and disease (Mukamel et al., 2021). Because repeat units in these VNTRs can be more than 35 times the length of the standard 150-bp short sequencing reads, large VNTRs cannot be genotyped by conventional variant-calling approaches. Furthermore, accurate copy number estimation from short-read whole-genome sequencing (WGS) remains challenging. A well-characterized example is the Kringle IV type-2 (KIV-2) VNTR within the LPA gene, which is the primary genetic determinant of lipoprotein(a) [Lp(a)] concentration (Mukamel et al., 2021; Utermann et al., 1987). Lp(a) is a causal and highly heritable ($h^2 > 70\%$) atherosclerotic cardiovascular disease (ASCVD) risk factor elevated in an estimated 1.5 billion people globally (Reyes-Soffer et al., 2022). Both Lp(a) concentrations and effect of LPA genetic variants vary substantially across ancestry groups, underscoring the importance of ancestry-aware genetic analyses and risk prediction (Kronenberg et al., 2022; Nordestgaard et al., 2010; Tsimikas, 2017). The KIV-2 repeat unit spans ~5.5 kb, with individuals carrying 1–40 copies per haplotype, and KIV-2 copy number is inversely correlated with Lp(a) concentration (Clarke et al., 2009; Kamstrup et al., 2009; Mukamel et al., 2021; Utermann et al., 1987). Accurate estimation of KIV-2 copy number therefore has important implications for genetic studies of Lp(a) and cardiovascular disease, including analyses of ancestry-related variation and genetic risk (Kronenberg et al., 2022; Mukamel et al., 2021). While this VNTR serves as a region of great interest, prior work has been limited to custom pipelines, limiting applications by the broader field.

GRiD (Genomic Repeat inference from Depth) is an open-source Python pipeline that addresses this methodological gap. GRiD estimates diploid and haplotype-resolved VNTR copy number from short-read WGS data. GRiD combines read-depth normalization, read depth profile-matched nearest-neighbor estimation, and identity-by-descent (IBD)-based haplotype inference (Hujoel et al., 2026). Although GRiD was developed and validated for the LPA KIV-2 locus, its core framework is locus-agnostic and applicable to any large VNTR with sufficient sample size. The pipeline is designed to be accessible to researchers without extensive bioinformatics expertise.

44 Statement of need

45 Large VNTRs present a shared set of computational challenges that place them outside the
46 scope of existing repeat genotyping software and standard genomic analysis pipelines. Their
47 repeat units are orders of magnitude larger than the short tandem repeats (STRs) targeted
48 by most available tools (Bakhtiari et al., 2018; Dolzhenko & others, 2019; Mousavi et al.,
49 2019; Willems et al., 2017), and in individuals with high-copy-number alleles the VNTR region
50 can span hundreds of kilobases, making read-pair spanning approaches difficult with standard
51 paired-end reads. Haplotype resolution from short-read data can be important for downstream
52 genomic analyses that depend allele-specific copy number, including analyses of statistical
53 associations, genomic coverage, and haplotype based tract, particularly given the expense
54 and difficulty of obtaining long-read data for large epidemiological cohorts. GRiD is designed
55 to address these challenges directly through three features: (1) a read-depth normalization
56 and nearest-neighbor framework that is locus-agnostic and parameterized entirely through
57 a configuration file, (2) an IBD-based iterative phasing algorithm (Hujoel et al., 2026) that
58 decomposes diploid copy number into haplotype-specific estimates using cohort relatedness,
59 and (3) a single installable pipeline that encapsulates the full workflow from short-read WGS
60 to haplotype-resolved copy number in an intuitive, reproducible, multi-threaded form.

61 Although several software packages address aspects of tandem repeat analysis, no existing
62 open-source tool provides an end-to-end workflow for estimating both diploid and haplotype-
63 resolved copy number from short-read whole-genome sequencing data at modern biobank scales.
64 Consequently, many studies have relied on custom analysis pipelines, limiting reproducibility,
65 portability, and cross-cohort compatibility. GRiD fills this gap by providing a configurable,
66 documented, and openly available implementation of these methods.

67 State of the field

68 Several mature software packages exist for genotyping tandem repeats from short-read
69 sequencing data. ExpansionHunter (Dolzhenko & others, 2019), and HipSTR (Willems
70 et al., 2017) were developed primarily for short tandem repeats (STRs) whereas GangSTR
71 (Mousavi et al., 2019) was developed for short VNTRs (defined by a repeat motif length of up
72 to 20bp). However, these methods are designed for repeat lengths where short reads can still
73 provide sufficient direct evidence about repeat structure. Likewise, TRTools (Mousavi et al.,
74 2021) provides downstream analysis utilities for STR genotypes but does not extend to large
75 VNTR copy number estimation. advNTR (Bakhtiari et al., 2018) supports genome-wide VNTR
76 genotyping using hidden Markov models but is designed for repeat units that are substantially
77 shorter (<150 bp) than loci such as the 5.6 kb LPA KIV-2 repeat. Earlier methods such as
78 VNTRseek (Gelfand et al., 2014) detected shorter VNTRs by comparing read-derived repeat
79 counts to a reference catalog, while GtTR (Ganesamoorthy et al., 2018) estimated absolute
80 target VNTR copy number by scaling short-read depth across locus boundaries against a
81 baseline genotype derived from long reads, though it remains unable to phase individual diploid
82 alleles. More recently, danbing-tk (Lu et al., 2021) introduced repeat-pangenome graphs for
83 genome-wide profiling of VNTR length and motif composition from short-read sequencing
84 data. This approach represents VNTR sequence diversity using haplotype-resolved assemblies
85 and estimates VNTR dosage from graph-specific k-mer counts. Recent advances in long-read
86 sequencing have enabled direct characterization of complex repeat regions (Didericksen &
87 others, 2024). For example, Kivvi (PacificBiosciences, 2026) estimates KIV-2 copy number
88 from PacBio HiFi sequencing data. However, most large population cohorts (eg, 1000G (The
89 1000 Genomes Project Consortium, 2015), TOPMed (Taliun et al., 2021), and the Genotype-
90 Tissue Expression (GTEx) project (GTEx Consortium, 2017)) remain based on short-read
91 whole-genome sequencing, motivating methods that can estimate VNTR copy number without
92 requiring long-read data. KILDA (Molitor & others, 2025) estimates KIV-2 diploid copy
93 number directly from short-read FASTQ files using an alignment-free k-mer-counting approach

normalized against non-repetitive sequences. The proprietary Illumina DRAGEN LPA Caller similarly estimates KIV-2 copy number but requires the FPGA-accelerated DRAGEN platform. vntr-calling-nf (genepi, 2024) provides a Nextflow workflow for VNTR analysis but focuses on coding variant detection rather than large-VNTR copy number quantification and has primarily been validated using whole-exome sequencing data. Collectively, these tools do not provide an end-to-end solution for estimating haplotype-resolved copy number of large VNTRs from short-read whole-genome sequencing data at population scale.

Software design

GRiD integrates approaches from prior work for estimating large VNTR copy number from short-read sequencing (Hujoel et al., 2026; Mukamel et al., 2021). It provides a configurable, end-to-end workflow for estimating both diploid and haplotype-resolved large VNTR copy number from short-read whole-genome sequencing data at cohort scale. The pipeline is designed to be accessible to researchers without extensive bioinformatics expertise.

GRiD is implemented in Python (≥ 3.8) and follows a modular architecture organized into seven sequential pipeline steps, each implemented as an independent utility module under grid/utis/. The pipeline is orchestrated by grid/pipeline.py and driven by a user-supplied YAML configuration file, which specifies file paths, genomic coordinates, per-step parameters, and which steps to execute. The command-line interface is implemented with Click (Ronacher & others, 2024) and provides an entry point: grid wgs for whole-genome sequencing data.

The Whole Genome Sequencing pipeline proceeds as follows:

1. **Index verification / creation:** Ensures CRAM/BAM index files (.crai/.bai) exist for all input samples, creating them with samtools (Li et al., 2009) if needed.
2. **Read counting:** Counts properly paired reads in the target VNTR region using pysam (Heger & others, 2024), filtering by mapping quality and SAM flags.
3. **Coverage estimation:** Runs mosdepth (Brent S. Pedersen & Quinlan, 2018a) across the genome in binned mode to produce per-sample depth profiles.
4. **Coverage normalization:** Normalizes coverage within individuals (by sample mean depth) and across individuals (by a z-score transformation), then filters to high-variance regions enriched for VNTR signal.
5. **Nearest-neighbor identification:** Uses scikit-learn (Pedregosa et al., 2011) to compute Euclidean distances in normalized depth space and identify the top-N genomically similar neighbors per individual, providing a cohort-matched reference for CNV normalization.
6. **Diploid copy number estimation:** Computes per-exon diploid copy number for each individual by normalizing their read counts relative to their nearest neighbors' read counts, accounting for sample-specific sequencing depth.
7. **Haplotype inference:** Applies an IBD-based iterative phasing algorithm (Hujoel et al., 2026) that uses haplotype-matched neighbors to decompose diploid copy number estimates into haplotype-specific contributions.

All multi-sample steps are parallelized using Python's concurrent.futures.ThreadPoolExecutor, and progress is reported via the Rich terminal library (Willison, 2024). Configuration validation at pipeline startup provides early, informative error messages before any compute-intensive steps run.

Research impact statement

GRiD has been applied to >50,000 study participants with whole-genome sequencing data from multiple TOPMed cohorts and 1000G cohorts, comprising tens of thousands of participants across African, European, Hispanic/Latino, and admixed American ancestry groups. These

analyses form the basis of ongoing research manuscripts and demonstrate the applicability of GRiD to population-scale analyses and heterogeneous sequencing datasets.

GRiD provides a reproducible, open-source implementation of a previously custom analysis workflow, enabling large-VNTR copy number estimation from existing short-read whole-genome sequencing datasets. By packaging the complete workflow with documentation, example datasets, and automated installation, GRiD reduces the technical barriers to incorporating large VNTR analyses into population-scale genomic studies.

Mathematics

The mathematical framework implemented in GRiD follows previously published methods. Coverage estimation, normalization, and diploid copy-number estimation follow Mukamel et al. (Mukamel et al., 2021), while haplotype-specific copy-number inference follows Hujoel et al. (Hujoel et al., 2026). The equations below describe their implementation within GRiD; detailed methodological derivations and justification are provided in the original publications.

Coverage estimation. Following Mukamel et al. (Mukamel et al., 2021), weighted mean depth across the VNTR region from mosdepth (Brent S. Pedersen & Quinlan, 2018b) bins is computed as:

$$\text{Coverage} = \left\lceil 100 \cdot \frac{\sum_{i \in R} (\bar{C}_i \cdot (\min(e, r_{i,e}) - \max(s, r_{i,s})))}{\sum_{i \in R} (\min(e, r_{i,e}) - \max(s, r_{i,s}))} \right\rceil$$

where R is the set of bins overlapping the region $[s, e]$, $\bar{C}_i$ is the mean depth of bin i , and $r_{i,s}$ and $r_{i,e}$ are the bin boundaries.

Normalization. Following Mukamel et al. (Mukamel et al., 2021), let $D \in \mathbb{R}^{N \times M}$ be the depth matrix for N individuals across M genomic bins. Within-individual normalization gives $D_{ij}^{(1)} = D_{ij} / \bar{D}_i$, where $\bar{D}_i$ is the individual mean. Across-individual normalization then yields:

$$D_{ij}^{\text{norm}} = \frac{D_{ij}^{(1)} - \mu_j}{\sqrt{\mu_j}}$$

where μ_j is the population mean of $D_{ij}^{(1)}$. Regions are filtered by a variance ratio σ_j^2 / μ_j , and the top fraction of high-variance regions are retained for neighbor computation.

Neighbor-normalized diploid copy number. GRiD uses nearest-neighbor relationships in the normalized depth space to provide a local reference for copy-number estimation. Following the approach of Mukamel et al. (Mukamel et al., 2021), for individual i with read count r_i and depth scale s_i , the diploid copy number estimate is:

$$\widehat{\text{dipCN}}_i = \frac{r_i / s_i}{\frac{1}{|N_i|} \sum_{j \in N_i} r_j / s_j}$$

where N_i is the set of nearest neighbors identified from the normalized depth space using the nearest-neighbor implementation provided by scikit-learn (Pedregosa et al., 2011).

Haplotype inference. Haplotype-specific copy-number inference follows the approach of Hujoel et al. (Hujoel et al., 2026). This step uses identity-by-descent (IBD) relationships between samples to partition the diploid copy-number estimate into haplotype-specific estimates. For each individual, the two haplotype estimates are iteratively updated according to the copy numbers of IBD-matched haplotypes:

$$h_{i,k}^{(t+1)} = \widehat{\text{dipCN}}_i \cdot \frac{\bar{h}_{N_{i,k}}^{(t)}}{\bar{h}_{N_{i,1}}^{(t)} + \bar{h}_{N_{i,2}}^{(t)}}$$

where $\bar{h}_{N_{i,k}}^{(t)}$ is the mean haplotype copy number of IBD neighbors on haplotype k at iteration t . At each iteration, the relative copy numbers of IBD-matched haplotypes determine the allocation of the individual's diploid copy-number estimate between the two haplotypes. The estimates are iteratively updated to incorporate information from IBD-related haplotypes.

AI Usage Disclosure

The authors used GitHub Copilot and Anthropic Claude (Claude Sonnet 4) during the development of this software and the preparation of this manuscript. GitHub Copilot was used as an interactive coding assistant to suggest code completions, refactoring ideas, and boilerplate implementations. Claude was used to assist with code review, debugging, documentation development, and editorial improvements to the manuscript, including suggestions for clarity, organization, and grammar. AI tools were not used to generate scientific conclusions or interpret results. All AI-assisted code and manuscript edits were reviewed, validated, and, where necessary, modified by the authors before inclusion. The authors take full responsibility for the accuracy, correctness, and content of the software and manuscript.

Acknowledgements

We are deeply indebted to Drs. Po-Ru Loh and Margaux Hujoel for sharing code and providing additional technical support. We would additionally like to thank Dr. Akshay Avvaru for his help and support. This work was supported by NIH K01: HL157658, R01: HL172887 and NSF: 2022138 grants. The funders had no role in the design, development, analysis, or preparation of this work.

References

- Bakhtiari, M., Shleizer-Burko, S., Gymrek, M., Bansal, V., & Bafna, V. (2018). Targeted genotyping of variable number tandem repeats with adVNTR. *Genome Research*, 28(11), 1709–1719. <https://doi.org/10.1101/gr.235119.118>
- Clarke, R., Peden, J. F., Hopewell, J. C., & others. (2009). Genetic variants associated with Lp(a) lipoprotein level and coronary disease. *New England Journal of Medicine*, 361(26), 2518–2528. <https://doi.org/10.1056/NEJMoa0902604>
- Didericksen, K., & others. (2024). Long-read sequencing resolves complex repeat structures in the human genome. *Nature Genetics*. <https://doi.org/VERIFY>
- Dolzhenko, E., & others. (2019). ExpansionHunter: A sequence-graph-based tool to analyze variation in short tandem repeat regions. *Bioinformatics*, 35(22), 4754–4756. <https://doi.org/10.1093/bioinformatics/btz431>
- Ganesamoorthy, D., Cao, M. D., Duarte, T. P. S., Chen, W., & Coin, L. J. M. (2018). GtTR: Bayesian estimation of absolute tandem repeat copy number using sequence capture and high throughput sequencing. *BMC Bioinformatics*, 19(1), 267. <https://doi.org/10.1186/s12859-018-2266-9>
- Gelfand, Y., Hernandez, Y., Loving, J., & Benson, G. (2014). VNTRseek—a computational tool to detect tandem repeat variants in high-throughput sequencing data. *Nucleic Acids Research*, 42(14), 8884–8894. <https://doi.org/10.1093/nar/gku642>

- 213 genepi. (2024). *Vntr-calling-nf: A Nextflow pipeline for VNTR variant calling*. <https://github.com/genepi/vntr-calling-nf>
- 214
- 215 GTEx Consortium. (2017). Genetic effects on gene expression across human tissues. *Nature*,
216 550(7675), 204–213. <https://doi.org/10.1038/nature24277>
- 217 Heger, A., & others. (2024). *Pysam: A python module for reading and manipulating*
218 *SAM/BAM/CRAM files*. <https://github.com/pysam-developers/pysam>
- 219 Hujoel, M. L., Handsaker, R. E., Tang, D., Kamitaki, N., Mukamel, R. E., Rubinacci, S.,
220 Palamara, P. F., McCarroll, S. A., & Loh, P.-R. (2026). Insights into DNA repeat expansions
221 among 900,000 biobank participants. *Nature*, 1–10.
- 222 Kamstrup, P. R., Tybjaerg-Hansen, A., Steffensen, R., & Nordestgaard, B. G. (2009). Genetically
223 elevated lipoprotein(a) and increased risk of myocardial infarction. *JAMA*, 301(22),
224 2331–2339. <https://doi.org/10.1001/jama.2009.801>
- 225 Kronenberg, F., Mora, S., Stroes, E. S. G., & others. (2022). Lipoprotein(a) in atherosclerotic
226 cardiovascular disease and aortic stenosis: A European Atherosclerosis Society consensus
227 statement. *European Heart Journal*, 43(39), 3925–3946. <https://doi.org/10.1093/eurheartj/ehac361>
- 228
- 229 Li, H., Handsaker, B., Wysoker, A., & others. (2009). The sequence alignment/map format and
230 SAMtools. *Bioinformatics*, 25(16), 2078–2079. <https://doi.org/10.1093/bioinformatics/btp352>
- 231
- 232 Lu, J.-H., Yang, C.-C., Chou, E. J., Gerasimova, A., Melendez, J., Markello, A., & Chaisson,
233 M. J. P. (2021). Profiling variable-number tandem repeat variation across populations
234 using repeat-pangenome graphs. *Nature Communications*, 12(1), 4250. <https://doi.org/10.1038/s41467-021-24378-0>
- 235
- 236 Molitor, L., & others. (2025). KILDA: K-mer-based inference of LPA diploid copy number
237 from short-read alignment-free data. *NAR Genomics and Bioinformatics*. <https://doi.org/10.1093/nargab/lqaf070>
- 238
- 239 Mousavi, N., Margoliash, J., Pulara, N., & others. (2021). TRTools: A toolkit for genome-
240 wide analysis of tandem repeats. *Bioinformatics*, 37(18), 3062–3064. <https://doi.org/10.1093/bioinformatics/btab358>
- 241
- 242 Mousavi, N., Shleizer-Burko, S., Yanicky, R., & Gymrek, M. (2019). GangSTR: Template-
243 based estimation of short tandem repeats. *Nucleic Acids Research*, 47(15), e90. <https://doi.org/10.1093/nar/gkz501>
- 244
- 245 Mukamel, R. E., Handsaker, R. E., Sherman, M. A., & others. (2021). Protein-coding repeat
246 polymorphisms strongly shape diverse human phenotypes. *Science*, 373(6562), 1499–1505.
247 <https://doi.org/10.1126/science.abg8635>
- 248 Nordestgaard, B. G., Chapman, M. J., Ray, K., Borén, J., Andreotti, F., Watts, G. F.,
249 Ginsberg, H. N., Amarengo, P., Catapano, A., Descamps, O. S., Fisher, E., Kovanen, P. T.,
250 Kuivenhoven, J. A., Lesnik, P., Masana, L., Reiner, Z., Taskinen, M.-R., Tokgözoğlu, L., &
251 Tybjaerg-Hansen, A. (2010). Lipoprotein(a) as a cardiovascular risk factor: Current status.
252 *European Heart Journal*, 31(23), 2844–2853. <https://doi.org/10.1093/eurheartj/ehq386>
- 253 PacificBiosciences. (2026). *Kivvi: KIV-2 and D4Z4 copy number estimation from PacBio HiFi*
254 *whole-genome sequencing*. <https://github.com/PacificBiosciences/Kivvi>
- 255 Pedersen, Brent S., & Quinlan, A. R. (2018a). Mosdepth: Quick coverage calculation
256 for genomes and exomes. *Bioinformatics*, 34(5), 867–868. <https://doi.org/10.1093/bioinformatics/btx699>
- 257
- 258 Pedersen, Brent S., & Quinlan, A. R. (2018b). Mosdepth: quick coverage calculation
259 for genomes and exomes. *Bioinformatics*, 34(5), 867–868. <https://doi.org/10.1093/bioinformatics/btx699>

- 260 [bioinformatics/btx699](https://bioinformatics.btx699)
- 261 Pedregosa, F., Varoquaux, G., Gramfort, A., & others. (2011). Scikit-learn: Machine learning
262 in Python. *Journal of Machine Learning Research*, 12, 2825–2830. [https://jmlr.org/](https://jmlr.org/papers/v12/pedregosa11a.html)
263 [papers/v12/pedregosa11a.html](https://jmlr.org/papers/v12/pedregosa11a.html)
- 264 Reyes-Soffer, G., Ginsberg, H. N., Berglund, L., Duell, P. B., Heffron, S. P., Kamstrup,
265 P. R., Lloyd-Jones, D. M., Marcovina, S. M., Yeang, C., Koschinsky, M. L., & others.
266 (2022). Lipoprotein (a): A genetically determined, causal, and prevalent risk factor for
267 atherosclerotic cardiovascular disease: A scientific statement from the american heart
268 association. *Arteriosclerosis, Thrombosis, and Vascular Biology*, 42(1), e48–e60.
- 269 Ronacher, A., & others. (2024). *Click: Python composable command line interface toolkit*.
270 <https://palletsprojects.com/p/click/>
- 271 Taliun, D., Harris, D. N., Kessler, M. D., Carlson, J., Szpiech, Z. A., Torres, R., Taliun, S. A.
272 G., Corvelo, A., Gogarten, S. M., Kang, H. M., Pitsillides, A. N., LeFaive, J., Lee, S.-B.,
273 Tian, X., Browning, B. L., Das, S., Emde, A.-K., Clarke, W. E., NHLBI Trans-Omics
274 for Precision Medicine (TOPMed) Consortium, & Abecasis, G. R. (2021). Sequencing of
275 53,831 diverse genomes from the NHLBI TOPMed Program. *Nature*, 590(7845), 290–299.
276 <https://doi.org/10.1038/s41586-021-03205-y>
- 277 The 1000 Genomes Project Consortium. (2015). A global reference for human genetic variation.
278 *Nature*, 526(7571), 68–74. <https://doi.org/10.1038/nature15393>
- 279 Tsimikas, S. (2017). A test in context: Lipoprotein(a): Diagnosis, prognosis, controversies,
280 and emerging therapies. *Journal of the American College of Cardiology*, 69(6), 692–711.
281 <https://doi.org/10.1016/j.jacc.2016.11.042>
- 282 Utermann, G., Menzel, H. J., Kraft, H. G., Duba, H. C., Kemmler, H. G., & Seitz, C. (1987).
283 Lp(a) glycoprotein phenotypes: Inheritance and relation to Lp(a)-lipoprotein concentrations
284 in plasma. *Journal of Clinical Investigation*, 80(2), 458–465. [https://doi.org/10.1172/](https://doi.org/10.1172/JCI113093)
285 [JCI113093](https://doi.org/10.1172/JCI113093)
- 286 Willems, T., Zuk, O., Erlich, Y., & Gymrek, M. (2017). Genome-wide profiling of heritable
287 and de novo STR variations. *Nature Methods*, 14, 590–592. [https://doi.org/10.1038/](https://doi.org/10.1038/nmeth.4267)
288 [nmeth.4267](https://doi.org/10.1038/nmeth.4267)
- 289 Willison, W. (2024). *Rich: Rich text and beautiful formatting in the terminal*. [https:](https://github.com/Textualize/rich)
290 [//github.com/Textualize/rich](https://github.com/Textualize/rich)