

MUTABLE DATA STRUCTURES AND DATA ABSTRACTIONS

COMPUTER SCIENCE MENTORS 61A

February 13 to February 17, 2016

1 Lists

1. Draw box-and-pointer diagrams for the following:

```
>>> a = [1, 2, 3]
>>> a
```

Solution:

```
[1, 2, 3]
```

```
>>> a[2]
```

Solution: 3

```
>>> b = a
>>> a = a + [4, 5]
>>> a
```

Solution:

```
[1, 2, 3, 4, 5]
```

```
>>> b
```

Solution:

```
[1, 2, 3]
```

```
>>> c = a
```

```
>>> a = [4, 5]
```

```
>>> a
```

Solution:

```
[4, 5]
```

```
>>> c
```

Solution:

```
[1, 2, 3, 4, 5]
```

```
>>> d = c[0:2]
```

```
>>> c[0] = 9
```

```
>>> d
```

Solution:

```
[1, 2]
```

Solution: [Box and pointer diagram in Python Tutor - tinyurl.com/week5-bap](https://tinyurl.com/week5-bap)

2. Write a function that takes in a list `nums` and returns a new list with only the primes from `nums`. Assume that `is_prime(n)` is defined. You may use a `while` loop, a `for` loop, or a list comprehension.

def all_primes(nums):

Solution:

```
result = []
for i in nums:
    if is_prime(i):
        result = result + [i]
return result
```

List comprehension:

```
return [x for x in nums if is_prime(x)]
```

2 Data Abstraction

3. The following is an **Abstract Data Type (ADT)** for elephants. Each elephant keeps track of its name, age, and whether or not it can fly. Given our provided constructor, fill out the selectors:

```
def elephant(name, age, can_fly):  
    """  
    Takes in a string name, an int age, and a boolean can_fly.  
    Constructs an elephant with these attributes.  
    >>> dumbo = elephant("Dumbo", 10, True)  
    >>> elephant_name(dumbo)  
    "Dumbo"  
    >>> elephant_age(dumbo)  
    10  
    >>> elephant_can_fly(dumbo)  
    True  
    """  
    return [name, age, can_fly]  
def elephant_name(e):
```

Solution:

```
    return e[0]
```

```
def elephant_age(e):
```

Solution:

```
    return e[1]
```

```
def elephant_can_fly(e):
```

Solution:

```
    return e[2]
```

4. This function returns the correct result, but there's something wrong about its implementation. How do we fix it?

```
def elephant_roster(elephants):  
    """  
    Takes in a list of elephants and returns a list of their  
    names.  
    """  
    return [elephant[0] for elephant in elephants]
```

Solution:

elephant[0] is a Data Abstraction Violation (DAV).
We should use a selector instead.

5. Fill out the following constructor for the given selectors.

```
def elephant(name, age, can_fly):
```

Solution:

```
    return [[name, age], can_fly]
```

```
def elephant_name(e):  
    return e[0][0]  
def elephant_age(e):  
    return e[0][1]  
def elephant_can_fly(e):  
    return e[1]
```

6. How can we write the fixed `elephant_roster` function for the constructors and selectors in the previous question?

Solution: No change is necessary to fix `elephant_roster` since using the `elephant` selectors “protects” the roster from constructor definition changes.

7. (Optional) Fill out the following constructor for the given selectors.

```
def elephant(name, age, can_fly):  
    """  
    >>> chris = elephant("Chris Martin", 38, False)  
    >>> elephant_name(chris)  
        "Chris Martin"  
    >>> elephant_age(chris)  
        38  
    >>> elephant_can_fly(chris)  
        False  
    """  
    def select(command)
```

Solution:


```
        if command == "name":  
            return name  
        elif command == "age":  
            return age  
        elif command == "can_fly":  
            return can_fly  
        return "Breaking abstraction barrier!"  
    return select  
def elephant_name(e):  
    return e("name")  
def elephant_age(e):  
    return e("age")  
def elephant_can_fly(e):  
    return e("can_fly")
```

3 Trees**Things to remember**


```
def tree(label, branches=[]):  
    return [label] + list(branches)  
  
def label(t):  
    return t[0]  
  
def branches(t): # Always returns a list of trees  
    return t[1:]
```

8. Draw the tree that is created by the following statement:

```
tree(4,  
    [tree(5, []),  
     tree(2,  
         [tree(2, []),  
          tree(1, [])]),  
     tree(1, []),  
     tree(8,  
         [tree(4, [])])])
```



9. Construct the following tree and save it to the variable `t`.



Solution:

```
t = tree(9, [tree(2, []),
              tree(4, [tree(1, [])]),
              tree(4, [tree(7, []),
                      tree(3, [])])])
```

10. What would this output?

```
>>> label(t)
```

Solution: 9

```
>>> branches(t)[2]
```

Solution:

```
tree(4, [tree(7, []), tree(3, [])])
```

```
>>> branches(branches(t)[2])[0]
```

Solution:

```
tree(7, [])
```

11. Write the Python expression to get the integer 2 from `t`.

Solution:

```
label(branches(t)[0])
```


12. Write the function `sum_of_nodes` which takes in a tree and outputs the sum of all the elements in the tree.

```
def sum_of_nodes(t):  
    """  
    >>> t = Tree(...) # Tree from question 2.  
    >>> sum_of_nodes(t) # 9 + 2 + 4 + 4 + 1 + 7 + 3 = 30  
    30  
    """
```

Solution:

```
total = label(t)  
for branch in branches(t):  
    total += sum_of_nodes(branch)  
return total
```

Alternative solution:

```
return label(t) +\  
    sum([sum_of_nodes(b) for b in branches(t)])
```