

SSN COLLEGE OF ENGINEERING, KALAVAKKAM
DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING
Compiler Design Lab – CS6612

Programming Assignment-2 - Implementation of Lexical Analyzer for the patterns
(identifier, comments, operators, constants)

Due Date: 25.01.17 & 30.01.17

Develop a Lexical analyzer to recognize the patterns namely, identifiers, constants, comments and operators using the following regular expressions.

Regular Expression for Identifier letter → [a-zA-Z] digit → [0-9] id → letter(letter digit)*	Regular Expression for Constant digit → [0-9] digits → digit digits optFrac → .digits optExp → E(+ - ε) digits numberconst → digits optFrac optExp charconst → '(letter)' stringconst → "(letter)*" constant → numberconst charconst stringconst
Regular Expression for Comments start1 → \ end1 → */ multi → start (letter)* end start2 → // single → start (letter)*	Regular Expression for Operators relop → < <= == != > >= arithop → + - * / % logicalop → && ! operator → relop arithop logicalop

Regular Expression for keywords int → int float → float char → char double → double keywords → int float char double	
---	--

Convert the regular expressions into cumulative transition diagram as shown in Figure 1. Each state represents a condition that could occur during the process of scanning the input looking for a lexeme that matches one of the several patterns. Convert each state into a piece of code.




Figure 1. Cumulative Transition diagram

Develop a scanner that will recognize all the above specified tokens. Test your program for all specified tokens. Example input and output specification is given below.

Example input source program

```
main()
{
    int a=10,b=20;
    if(a>b)
        printf("a is greater");
    else
        printf("b is greater");
}
```

Output:

main()	– function call
{	- special character
int	– keyword
a	– identifier
=	- assignment operator
10	– integer constant
,	-special character
b	– identifier
=	- assignment operator
20	– integer constant
;	- special character
if	- keyword
(- special character
a	– identifier
>	- relational operator
b	– identifier
)	- special character
printf("a is greater")	– function call
;	- special character
printf("b is greater")	– function call
;	- special character
}	- special character