
Chapter 6: CPU Scheduling





Chapter 6: CPU Scheduling

- Basic Concepts
- Scheduling Criteria
- Scheduling Algorithms
- Thread Scheduling
- Multiple-Processor Scheduling
- Real-Time CPU Scheduling
- Operating Systems Examples
- Algorithm Evaluation





Objectives


- To introduce CPU scheduling, which is the basis for multiprogrammed operating systems
- To describe various CPU-scheduling algorithms
- To discuss evaluation criteria for selecting a CPU-scheduling algorithm for a particular system
- To examine the scheduling algorithms of several operating systems






Basic Concepts

- Maximum CPU utilization obtained with multiprogramming
- CPU-I/O Burst Cycle Process execution consists of a cycle of CPU execution and I/O wait
- CPU burst followed by I/O burst
- CPU burst distribution is of main concern





Histogram of CPU-burst Times







CPU Scheduler

- Short-term scheduler selects from among the processes in ready queue, and allocates the CPU to one of them
 - Queue may be ordered in various ways
- CPU scheduling decisions may take place when a process:
 - 1. Switches from running to waiting state
 - 2. Switches from running to ready state
 - 3. Switches from waiting to ready
 - 4. Terminates
- Scheduling under 1 and 4 is nonpreemptive
- All other scheduling is preemptive
 - Consider access to shared data inconsistent data
 - Consider preemption while in kernel mode inconsistent kernel data structures
 - Consider interrupts occurring during crucial OS activities disable interrupts at entry and enable at exit.





Dispatcher

- Dispatcher module gives control of the CPU to the process selected by the short-term scheduler; this involves:
 - switching context
 - switching to user mode
 - jumping to the proper location in the user program to restart that program
- Dispatch latency time it takes for the dispatcher to stop one process and start another running





Scheduling Criteria

- CPU utilization keep the CPU as busy as possible
- Throughput # of processes that complete their execution per time unit
- Turnaround time amount of time to execute a particular process
- Waiting time amount of time a process has been waiting in the ready queue
- Response time amount of time it takes from when a request was submitted until the first response is produced, not output (for time-sharing environment)





Scheduling Algorithm Optimization Criteria

- Max CPU utilization
- Max throughput
- Min turnaround time
- Min waiting time
- Min response time





First-Come, First-Served (FCFS) Scheduling

<u>Process</u>	Burst Time
P_1	24
P_2	3
P_3	3

Suppose that the processes arrive in the order: P_1 , P_2 , P_3 The Gantt Chart for the schedule is:

P_{1}	P_2	P_3
0	4 2	27 30

- Waiting time for $P_1 = 0$; $P_2 = 24$; $P_3 = 27$
- Average waiting time: (0 + 24 + 27)/3 = 17






FCFS Scheduling (Cont.)

Suppose that the processes arrive in the order:

$$P_2$$
, P_3 , P_1

The Gantt chart for the schedule is:



- Waiting time for $P_1 = 6$; $P_2 = 0$; $P_3 = 3$
- Average waiting time: (6 + 0 + 3)/3 = 3
- Much better than previous case
- Convoy effect short process behind long process
 - Consider one CPU-bound and many I/O-bound processes





Shortest-Job-First (SJF) Scheduling

- Associate with each process the length of its next CPU burst
 - Use these lengths to schedule the process with the shortest time
- SJF is optimal gives minimum average waiting time for a given set of processes
 - The difficulty is knowing the length of the next CPU request
 - Could ask the user






Example of SJF

<u>Process</u>	Burst Time
P_1	6
P_2	8
P_3	7
P_4	3

SJF scheduling chart



• Average waiting time = (3 + 16 + 9 + 0) / 4 = 7






Determining Length of Next CPU Burst

- Can only estimate the length should be similar to the previous one
 - Then pick process with shortest predicted next CPU burst
- Can be done by using the length of previous CPU bursts, using exponential averaging
 - 1. $t_n = \text{actual length of } n^{th} \text{ CPU burst}$
 - 2. τ_{n+1} = predicted value for the next CPU burst
 - 3. α , $0 \le \alpha \le 1$
 - 4. Define: $\tau_{n=1} = \alpha t_n + (1 \alpha)\tau_n$.
- Commonly, α set to $\frac{1}{2}$
- Preemptive version called **shortest-remaining-time-first**





Prediction of the Length of the Next CPU Burst



CPU burst (t_i) 6 4 6 4 13 13 13 ... "guess" (τ_i) 10 8 6 6 5 9 11 12 ...





Examples of Exponential Averaging

- $\alpha = 0$
 - $\tau_{n+1} = \tau_n$
 - Recent history does not count
- $\alpha = 1$
 - $\tau_{n+1} = \alpha t_n$
 - Only the actual last CPU burst counts
- If we expand the formula, we get:

$$\tau_{n+1} = \alpha t_n + (1 - \alpha)\alpha t_{n-1} + \dots + (1 - \alpha)^j \alpha t_{n-j} + \dots + (1 - \alpha)^{n+1} \tau_0$$

Since both α and $(1 - \alpha)$ are less than or equal to 1, each successive term has less weight than its predecessor






Example of Shortest-remaining-time-first

Now we add the concepts of varying arrival times and preemption to the analysis

<u>Process</u>	<u>Arrival Time</u>	Burst Time
P_1	0	8
P_2	1	4
P_3	2	9
P_4	3	5

Preemptive SJF Gantt Chart



Average waiting time = [(10-1)+(1-1)+(17-2)+5-3)]/4 = 26/4 = 6.5 msec





Priority Scheduling

- A priority number (integer) is associated with each process
- The CPU is allocated to the process with the highest priority (smallest integer ≡ highest priority)
 - Preemptive
 - Nonpreemptive
- SJF is priority scheduling where priority is the inverse of predicted next CPU burst time
- Problem = Starvation low priority processes may never execute
- Solution ≡ Aging as time progresses increase the priority of the process





Example of Priority Scheduling

<u>Process</u>	Burst Time	<u>Priority</u>
P_1	10	3
P_2	1	1
P_3	2	4
P_4	1	5
P_5	5	2

Priority scheduling Gantt Chart

P_2	2	P ₅	P ₁	P ₃	P ₄
0	1	6	5 16	,	18 19

■ Average waiting time = 8.2 msec





Round Robin (RR)

- Each process gets a small unit of CPU time (time quantum q), usually 10-100 milliseconds. After this time has elapsed, the process is preempted and added to the end of the ready queue.
- If there are *n* processes in the ready queue and the time quantum is *q*, then each process gets 1/*n* of the CPU time in chunks of at most *q* time units at once. No process waits more than (*n*-1)*q* time units.
- Timer interrupts every quantum to schedule next process
- Performance
 - q large ⇒ FIFO
 - q small ⇒ q must be large with respect to context switch, otherwise overhead is too high






Example of RR with Time Quantum = 4

<u>Process</u>	Burst Time
P_1	24
P_2	3
P_3	3

The Gantt chart is:




- Typically, higher average turnaround than SJF, but better response
- q should be large compared to context switch time
- q usually 10ms to 100ms, context switch < 10 usec






Time Quantum and Context Switch Time







Turnaround Time Varies With The Time Quantum



process	time
P_1	6
P_2	3
P_3	1
P_4	7

80% of CPU bursts should be shorter than q






Multilevel Queue

- Ready queue is partitioned into separate queues, eg:
 - foreground (interactive)
 - background (batch)
- Process permanently in a given queue
- Each queue has its own scheduling algorithm:
 - foreground RR
 - background FCFS
- Scheduling must be done between the queues:
 - Fixed priority scheduling; (i.e., serve all from foreground then from background). Possibility of starvation.
 - Time slice each queue gets a certain amount of CPU time which it can schedule amongst its processes; i.e., 80% to foreground in RR
 - 20% to background in FCFS





Multilevel Queue Scheduling





Multilevel Feedback Queue

- A process can move between the various queues; aging can be implemented this way
- Multilevel-feedback-queue scheduler defined by the following parameters:
 - number of queues
 - scheduling algorithms for each queue
 - method used to determine when to upgrade a process
 - method used to determine when to demote a process
 - method used to determine which queue a process will enter when that process needs service






Example of Multilevel Feedback Queue

Three queues:

- Q₀ RR with time quantum 8 milliseconds
- Q₁ RR time quantum 16 milliseconds
- Q₂ FCFS

Scheduling

- A new job enters queue Q₀ which is served FCFS
 - When it gains CPU, job receives 8 milliseconds
 - If it does not finish in 8 milliseconds, job is moved to queue Q₁
- At Q₁ job is again served FCFS and receives 16 additional milliseconds
 - If it still does not complete, it is preempted and moved to queue Q₂







Thread Scheduling

- Distinction between user-level and kernel-level threads
- When threads supported, threads scheduled, not processes
- Many-to-one and many-to-many models, thread library schedules user-level threads to run on LWP
 - Known as process-contention scope (PCS) since scheduling competition is within the process
 - Typically done via priority set by programmer
- Kernel thread scheduled onto available CPU is system-contention scope (SCS) – competition among all threads in system





Pthread Scheduling

- API allows specifying either PCS or SCS during thread creation
 - PTHREAD_SCOPE_PROCESS schedules threads using PCS scheduling
 - PTHREAD_SCOPE_SYSTEM schedules threads using SCS scheduling
- Can be limited by OS Linux and Mac OS X only allow PTHREAD_SCOPE_SYSTEM





Pthread Scheduling API

```
#include <pthread.h>
#include <stdio.h>
#define NUM THREADS 5
int main(int argc, char *argv[]) {
   int i, scope;
   pthread_t tid[NUM THREADS];
   pthread attr t attr;
   /* get the default attributes */
   pthread_attr_init(&attr);
   /* first inquire on the current scope */
   if (pthread_attr_getscope(&attr, &scope) != 0)
      fprintf(stderr, "Unable to get scheduling scope\n");
   else {
      if (scope == PTHREAD SCOPE PROCESS)
         printf("PTHREAD_SCOPE_PROCESS");
      else if (scope == PTHREAD_SCOPE_SYSTEM)
         printf("PTHREAD SCOPE SYSTEM");
      else
         fprintf(stderr, "Illegal scope value.\n");
```



Pthread Scheduling API

```
/* set the scheduling algorithm to PCS or SCS */
   pthread_attr_setscope(&attr, PTHREAD_SCOPE_SYSTEM);
   /* create the threads */
   for (i = 0; i < NUM THREADS; i++)
      pthread create(&tid[i],&attr,runner,NULL);
   /* now join on each thread */
   for (i = 0; i < NUM THREADS; i++)
     pthread join(tid[i], NULL);
/* Each thread will begin control in this function */
void *runner(void *param)
   /* do some work ... */
  pthread exit(0);
```

6.31



Multiple-Processor Scheduling

- CPU scheduling more complex when multiple CPUs are available.
- Two approaches:
- Asymmetric multiprocessing has all scheduling decisions, I/O processing, and other system activities handled by a single processor—the master server
 - only one processor accesses the system data structures, alleviating the need for data sharing
- Symmetric multiprocessing (SMP) each processor is selfscheduling, all processes in common ready queue, or each has its own private queue of ready processes
 - Currently, most common




Multiple-Processor Scheduling – contd.,

- If a process migrates from one processor to another, the data it was using(cache memory) has to be cleared in the first processor and populated in the second.
- high cost of invalidating and repopulating caches, most SMP systems try to avoid migration of processes from one processor to another and instead attempt to keep a process running on the same processor. This is known as processor affinity
- Processor affinity process has affinity for processor on which it is currently running
 - soft affinity OS has a policy to attempt to keep a process on the same processor but no guarantee i.e.,process is allowed to migrate
 - hard affinity allowing a process to specify a subset of processors on which it may run
 - Linux implements soft affinity but has sched_setaffinity() to set hard affinity
 - Variations including processor sets



NUMA and CPU Scheduling

- Illustratration: an architecture featuring non-uniform memory access (NUMA), in which a CPU has faster access to some parts of main memorythan to other parts.
- This occurs in systems containing combined CPU and memory boards. The CPUs on a board can access the memory on that board faster than they can access memory on other boards in the system.
- Can use affinity concepts and change this issue.



Note that memory-placement algorithms can also consider affinity



Multiple-Processor Scheduling – Load Balancing

- If SMP, need to keep all CPUs loaded for efficiency. (each processor has its own queue)
- Load balancing attempts to keep workload evenly distributed
- Push migration periodic task checks load on each processor, and if load imbalanced, pushes task from overloaded CPU to other CPUs
- Pull migration idle processors pulls waiting task from busy processor.
- Contradicts Processor affinity concepts.






Multicore Processors

- Recent trend to place multiple processor cores on same physical chip. OS perspective: each core is considered as a separate processor
- Faster and consumes less power
- Multiple threads per core also growing
 - Takes advantage of memory stall to make progress on another thread while memory retrieve happens
- When a processor accesses memory, it spends a significant amount of time waiting for the data to become available. This situation, known as a memory stall
- From an operating-system perspective, each hardware thread appears as a logical processor that is available to run a software thread. Thus, on a dual-threaded, dual-core system, four logical processors are presented to the operating system.






Multithreaded Multicore System



Memory stall on a single threaded processor



Memory stall on a dual threaded processor





Multicore Processors – contd.,

- Multithreaded multicore processor actually requires two different levels of scheduling.
- On one level are the scheduling decisions that must be made by the operating system as it chooses which software thread to run on each hardware thread (logical processor).
- A second level of scheduling specifies how each core decides which hardware thread to run.





Real-Time CPU Scheduling

- Can present obvious challenges
- Soft real-time systems no guarantee as to when critical real-time process will be scheduled but promises that critical processes will be given priority over non-critical ones
- Hard real-time systems task must be serviced within its deadline or no service at all.
- Issues:
 - Minimizing Latency
 - Scheduling





Minimizing Latency

- Two types of latencies affect performance
 - Interrupt latency time from arrival of interrupt to start of Interrupt service routine
 - Dispatch latency time taken for scheduling - to take current process off CPU and switch to the new process





Figure 6.12 Event latency.




Interrupt Latency





(Cont.)

- Conflict phase of dispatch latency:
 - Preemption of any process running in kernel mode
 - 2. Release by lowpriority process of resources needed by highpriority processes








Priority-based Scheduling

- For real-time scheduling, scheduler must support preemptive, prioritybased scheduling
 - But only guarantees soft real-time
- For hard real-time must also provide ability to meet deadlines
- Processes have new characteristics: periodic ones require CPU at constant intervals
 - Has processing time t, deadline d, period p
 - $0 \le t \le d \le p$
 - Rate of periodic task is 1/p





Scheduling Contd.,

Issues in scheduling:

- process may have to announce its deadline requirements to the scheduler. Then, using a technique known as an admission-control algorithm, the scheduler does one of two things.
- It either admits the process, guaranteeing that the process will complete on time, or
- rejects the request as impossible if it cannot guarantee that the task will be serviced by its deadline.





Virtualization and Scheduling

- Virtualization software schedules multiple guests onto CPU(s)
- Each guest doing its own scheduling
 - Not knowing it doesn't own the CPUs
 - Can result in poor response time
 - Can effect time-of-day clocks in guests
- Can undo good scheduling algorithm efforts of guests





Rate Monotonic Scheduling

- Static priorities with preemption
- A priority is assigned based on the inverse of its period
- Shorter periods = higher priority; (means that higher priority for processes that need the CPU more often)
- Longer periods = lower priority

Eg: Two processes,P1 and P2.

The deadline for each process requires that it complete its CPU burst by the start of its next period.

We measure the CPU utilization of a process *Pi as the ratio of its burst to its period—* ti/pi —

the CPU utilization of P1 is 20/50 = 0.40 and

that of P2 is 35/100 = 0.35,

for a total CPU utilization of 75 percent (scheduling is possible within deadlines)





Contd.,

Suppose, P2 is assigned a higher priority than P1.





Figure 6.16 Scheduling of tasks when P_2 has a higher priority than P_1 .




Applying Rate Monotonic with P1 as higher priority that P2

Rate-monotonic scheduling is considered optimal in that if a set of processes cannot be scheduled by this algorithm, it cannot be scheduled by any other algorithm that assigns static priorities.

Missed Deadlines with Rate Monotonic Scheduling

Assume that process P1 has a period of p1 = 50 and a CPU burst of t1 = 25. For P2, the corresponding values are p2 = 80 and t2 = 35.

The total CPU utilization of the two processes is (25/50)+(35/80) = 0.94 (scheduling seems possible but not since it misses deadline)



Limitation:

CPU utilization is bounded, and it is not always possible fully to maximize CPU resources.

Worst case CPU utilization for N processes is given by

$$N(2^{1/N}-1)$$
.





Contd.,

With one process in the system, CPU utilization is 100 percent, but it falls to approximately 69 percent as the number of processes approaches infinity.

With two processes, CPU utilization is bounded at about 83 percent.

In the first example, combined CPU utilization is 75% (so scheduling was possible with deadlines)

In the second example with two processes, the combined CPU utilization is 94% (so cannot guarantee scheduling within deadline)






Earliest Deadline First Scheduling (EDF)

- Dynamic priorities
- Priorities are assigned according to deadlines: the earlier the deadline, the higher the priority; the later the deadline, the lower the priority.
- Under the EDF policy, when a process becomes runnable, it must announce its deadline requirements to the system.

Second example: Assume that process P1 has a period of p1 = 50 and a CPU burst of t1 = 25.

For P2, the corresponding values are p2 = 80 and t2 = 35.



Earliest Deadline First Scheduling (EDF)

- Unlike the rate-monotonic algorithm, EDF scheduling does not require that processes be periodic, nor must a process require a constant amount of CPU time per burst.
- The only requirement is that a process announce its deadline to the scheduler when it becomes runnable.
- The appeal of EDF scheduling is that it is theoretically optimal.
- In practice, however, it is impossible to achieve this level of CPU utilization due to the cost of context switching between processes and interrupt handling





Proportional Share Scheduling

- T shares are allocated among all processes in the system
- \blacksquare An application receives *N* shares where N < T
- This ensures each application will receive N/T of the total processor time.
- Eg:A,B,C processes then A receives 50 shares, B 30 and C 10 shares of the CPU time. Reamining 20% free.
- Must have an admission control algorithm. i.e., If a new process D arrives requesting 30% of the CPU time, it should be denied as it cannot be allocated.





POSIX Real-Time Scheduling

- The POSIX.1b standard
- API provides functions for managing real-time threads
- Defines two scheduling classes for real-time threads:
- SCHED_FIFO threads are scheduled using a FCFS strategy with a FIFO queue. There is no time-slicing for threads of equal priority
- 2. SCHED_RR similar to SCHED_FIFO except time-slicing occurs for threads of equal priority
- Defines two functions for getting and setting scheduling policy:
- 1. pthread_attr_getsched_policy(pthread_attr_t *attr,
 int *policy)
- 2. pthread_attr_setsched_policy(pthread_attr_t *attr,
 int policy)

Where parameter (1) set of attributes for the thread.

Parameter (2) determines the type of scheduling policy that is got/set



POSIX Real-Time Scheduling API

```
#include <pthread.h>
#include <stdio.h>
#define NUM THREADS 5
int main(int argc, char *argv[])
  int i, policy;
  pthread t tid[NUM THREADS];
  pthread attr t attr;
  /* get the default attributes */
  pthread attr init(&attr);
  /* get the current scheduling policy */
  if (pthread attr getschedpolicy(&attr, &policy) != 0)
      fprintf(stderr, "Unable to get policy.\n");
  else {
      if (policy == SCHED OTHER) printf("SCHED OTHER\n");
      else if (policy == SCHED RR) printf("SCHED RR\n");
      else if (policy == SCHED FIFO) printf("SCHED FIFO\n");
```



POSIX Real-Time Scheduling API (Cont.)

```
/* set the scheduling policy - FIFO, RR, or OTHER */
   if (pthread attr setschedpolicy(&attr, SCHED FIFO) != 0)
      fprintf(stderr, "Unable to set policy.\n");
   /* create the threads */
   for (i = 0; i < NUM THREADS; i++)
      pthread create(&tid[i],&attr,runner,NULL);
   /* now join on each thread */
   for (i = 0; i < NUM THREADS; i++)
     pthread join(tid[i], NULL);
/* Each thread will begin control in this function */
void *runner(void *param)
   /* do some work ... */
  pthread exit(0);
```





Operating System Examples

- Linux scheduling
- Windows scheduling
- Solaris scheduling





Linux Scheduling Through Version 2.5

- Prior to kernel version 2.5, ran variation of standard UNIX scheduling algorithm
- Version 2.5 moved to constant order O(1) scheduling time
 - Preemptive, priority based
 - Two priority ranges: time-sharing and real-time
 - **Real-time** range from 0 to 99 and **nice** value from 100 to 140
 - Map into global priority with numerically lower values indicating higher priority
 - Higher priority gets larger q
 - Task run-able as long as time left in time slice (active)
 - If no time left (expired), not run-able until all other tasks use their slices
 - All run-able tasks tracked in per-CPU runqueue data structure
 - Two priority arrays (active, expired)
 - Tasks indexed by priority
 - When no more active, arrays are exchanged
 - Worked well, but poor response times for interactive processes




Linux Scheduling in Version 2.6.23 +

- Completely Fair Scheduler (CFS)
- Scheduling classes
 - Each has specific priority
 - Scheduler picks highest priority task in highest scheduling class
 - Rather than quantum based on fixed time allotments, based on proportion of CPU time
 - 2 scheduling classes included, others can be added
 - 1. default
 - real-time
- Quantum calculated based on nice value from -20 to +19
 - Lower value is higher priority
 - Calculates target latency interval of time during which task should run at least once
 - Target latency can increase if say number of active tasks increases
- CFS scheduler maintains per task virtual run time in variable vruntime
 - Associated with decay factor based on priority of task lower priority is higher decay rate
 - Normal default priority yields virtual run time = actual run time
- To decide next task to run, scheduler picks task with lowest virtual run time



CFS Performance

The Linux CFS scheduler provides an efficient algorithm for selecting which task to run next. Each runnable task is placed in a red-black tree—a balanced binary search tree whose key is based on the value of vruntime. This tree is shown below:



When a task becomes runnable, it is added to the tree. If a task on the tree is not runnable (for example, if it is blocked while waiting for I/O), it is removed. Generally speaking, tasks that have been given less processing time (smaller values of vruntime) are toward the left side of the tree, and tasks that have been given more processing time are on the right side. According to the properties of a binary search tree, the leftmost node has the smallest key value, which for the sake of the CFS scheduler means that it is the task with the highest priority. Because the red-black tree is balanced, navigating it to discover the leftmost node will require O(lgN) operations (where N is the number of nodes in the tree). However, for efficiency reasons, the Linux scheduler caches this value in the variable rb_leftmost, and thus determining which task to run next requires only retrieving the cached value.





Linux Scheduling (Cont.)

- Real-time scheduling according to POSIX.1b
 - Real-time tasks have static priorities
- Real-time plus normal map into global priority scheme
- Nice value of -20 maps to global priority 100
- Nice value of +19 maps to priority 139

	Real-Time		Normal	
0		99	100	139
← Higher				Lower
3		Priority		





Windows Scheduling

- Windows uses priority-based preemptive scheduling
- Highest-priority thread runs next
- Dispatcher is scheduler
- Thread runs until (1) blocks, (2) uses time slice, (3) preempted by higher-priority thread
- Real-time threads can preempt non-real-time
- 32-level priority scheme
- Variable class is 1-15, real-time class is 16-31
- Priority 0 is memory-management thread
- Queue for each priority
- If no run-able thread, runs idle thread





Windows Priority Classes

- Win32 API identifies several priority classes to which a process can belong
 - REALTIME_PRIORITY_CLASS, HIGH_PRIORITY_CLASS, ABOVE_NORMAL_PRIORITY_CLASS,NORMAL_PRIORITY_CLASS, BELOW_NORMAL_PRIORITY_CLASS, IDLE_PRIORITY_CLASS
 - All are variable except REALTIME
- A thread within a given priority class has a relative priority
 - TIME_CRITICAL, HIGHEST, ABOVE_NORMAL, NORMAL, BELOW_NORMAL, LOWEST, IDLE
- Priority class and relative priority combine to give numeric priority
- Base priority is NORMAL within the class
- If quantum expires, priority lowered, but never below base





Windows Priority Classes (Cont.)

- If wait occurs, priority boosted depending on what was waited for
- Foreground window given 3x priority boost
- Windows 7 added user-mode scheduling (UMS)
 - Applications create and manage threads independent of kernel
 - For large number of threads, much more efficient
 - UMS schedulers come from programming language libraries like
 C++ Concurrent Runtime (ConcRT) framework





Windows Priorities

	real- time	high	above normal	normal	below normal	idle priority
below normal	23	12	9	7	5	3
lowest	22	11	8	6	4	2
idle	16	1	1	1	1	1





Solaris

- Priority-based scheduling
- Six classes available
 - Time sharing (default) (TS)
 - Interactive (IA)
 - Real time (RT)
 - System (SYS)
 - Fair Share (FSS)
 - Fixed priority (FP)
- Given thread can be in one class at a time
- Each class has its own scheduling algorithm
- Time sharing is multi-level feedback queue
 - Loadable table configurable by sysadmin






Solaris Dispatch Table

priority	time quantum	time quantum expired	return from sleep
25	120	15	52
30	80	20	53
35	80	25	54
40	40	30	55
45	40	35	56
50	40	40	58
55	40	45	58
59	20	49	59





Solaris Scheduling







Solaris Scheduling (Cont.)

- Scheduler converts class-specific priorities into a per-thread global priority
 - Thread with highest priority runs next
 - Runs until (1) blocks, (2) uses time slice, (3) preempted by higher-priority thread
 - Multiple threads at same priority selected via RR





Algorithm Evaluation

- How to select CPU-scheduling algorithm for an OS?
- Determine criteria, then evaluate algorithms
- Deterministic modeling
 - Type of analytic evaluation
 - Takes a particular predetermined workload and defines the performance of each algorithm for that workload
- Consider 5 processes arriving at time 0:

Process	Burst Time		
P_1	10		
P_2	29		
P_3	3		
P_4	7		
P_5	12		



6.68




Deterministic Evaluation


- For each algorithm, calculate minimum average waiting time
- Simple and fast, but requires exact numbers for input, applies only to those inputs
 - FCS is 28ms:



Non-preemptive SFJ is 13ms:



• RR is 23ms:







Queueing Models

- Describes the arrival of processes, and CPU and I/O bursts probabilistically
 - Commonly exponential, and described by mean
 - Computes average throughput, utilization, waiting time, etc.
- Computer system described as network of servers, each with queue of waiting processes
 - Knowing arrival rates and service rates
 - Computes utilization, average queue length, average wait time, etc





Little's Formula

- = n = average queue length
- \blacksquare W = average waiting time in queue
- λ = average arrival rate into queue
- Little's law in steady state, processes leaving queue must equal processes arriving, thus:

$$n = \lambda \times W$$

- Valid for any scheduling algorithm and arrival distribution
- For example, if on average 7 processes arrive per second, and normally 14 processes in queue, then average wait time per process = 2 seconds






Simulations

- Queueing models limited
- Simulations more accurate
 - Programmed model of computer system
 - Clock is a variable
 - Gather statistics indicating algorithm performance
 - Data to drive simulation gathered via
 - Random number generator according to probabilities
 - Distributions defined mathematically or empirically
 - Trace tapes record sequences of real events in real systems





Evaluation of CPU Schedulers by Simulation





Implementation

- Even simulations have limited accuracy
- Just implement new scheduler and test in real systems
 - High cost, high risk
 - Environments vary
- Most flexible schedulers can be modified per-site or per-system
- Or APIs to modify priorities
- But again environments vary



End of Chapter 6

