

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/329838361>

An extensive experimental survey of regression methods

Article in *Neural Networks* · December 2018

DOI: 10.1016/j.neunet.2018.12.010

CITATION

1

READS

186

6 authors, including:



Manisha Sirsat

6 PUBLICATIONS 14 CITATIONS

[SEE PROFILE](#)



E. Cernadas

University of Santiago de Compostela

47 PUBLICATIONS 1,242 CITATIONS

[SEE PROFILE](#)



Sadi Alawadi

University of Santiago de Compostela

3 PUBLICATIONS 2 CITATIONS

[SEE PROFILE](#)



S. Barro

University of Santiago de Compostela

226 PUBLICATIONS 3,303 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



DETEPRE [View project](#)



Identification [View project](#)

An extensive experimental survey of regression methods

M. Fernández-Delgado^{1,*}, M.S. Sirsat¹, E. Cernadas¹, S. Alawadi¹, S. Barro¹, M. Febrero-Bande²

Abstract

Regression is a very relevant problem in machine learning, with many different available approaches. The current work presents a comparison of a large collection composed by 77 popular regression models which belong to 19 families: linear and generalized linear models, generalized additive models, least squares, projection methods, LASSO and ridge regression, Bayesian models, Gaussian processes, quantile regression, nearest neighbors, regression trees and rules, random forests, bagging and boosting, neural networks, deep learning and support vector regression. These methods are evaluated using all the regression datasets of the UCI machine learning repository (83 datasets), with some exceptions due to technical reasons. The experimental work identifies several outstanding regression models: the M5 rule-based model with corrections based on nearest neighbors (`cubist`), the gradient boosted machine (`gbm`), the boosting ensemble of regression trees (`bstTree`)

*M. Fernández-Delgado

Email address: `manuel.fernandez.delgado@usc.es` (M. Fernández-Delgado)

URL: `http://citius.usc.es` (M. Fernández-Delgado)

¹Centro Singular de Investigación en Tecnoloxías da Información da USC (CiTIUS), University of Santiago de Compostela, Campus Vida, 15782, Santiago de Compostela, Spain.

²Dept. of Statistics, Mathematical Analysis and Optimization, University of Santiago de Compostela, Campus Vida, 15782, Santiago de Compostela, Spain.

and the M5 regression tree. **Cubist** achieves the best squared correlation (R^2) in 15.7% of datasets being very near to it, with difference below 0.2 for 89.1% of datasets, and the median of these differences over the dataset collection is very low (0.0192), compared e.g. to the classical linear regression (0.150). However, **cubist** is slow and fails in several large datasets, while other similar regression models as M5 never fail and its difference to the best R^2 is below 0.2 for 92.8% of datasets. Other well-performing regressors are the committee of neural networks (**avNNet**), extremely randomized regression trees (**extraTrees**, which achieves the best R^2 in 33.7% of datasets), random forest (**rf**) and ε -support vector regression (**svr**), but they are slower and fail in several datasets. The fastest regression model is least angle regression **lars**, which is 70 and 2,115 times faster than M5 and **cubist**, respectively. The model which requires least memory is non-negative least squares (**nnls**), about 2 GB, similarly to **cubist**, while M5 requires about 8 GB. For 97.6% of datasets there is a regression model among the 10 bests which is very near (difference below 0.1) to the best R^2 , which increases to 100% allowing differences of 0.2. Therefore, provided that our dataset and model collection are representative enough, the main conclusion of this study is that, for a new regression problem, some model in our top-10 should achieve R^2 near to the best attainable for that problem.

Keywords: Regression, UCI machine learning repository, cubist, M5, gradient boosted machine, extremely randomized regression tree, support vector regression penalized linear regression.

1. Introduction

The objective of this paper is to provide a “road map” for researchers who want to solve regression problems and need to know how well work the currently available regression methods. In machine learning, regression methods are designed to predict continuous numeric outputs where an order relation is defined. Regression has been widely studied from the statistics field, which provides different approaches to this problem: linear and generalized linear regression, least and partial least squares regression (LS and PLS), least absolute shrinkage and selection operator (LASSO) and ridge regression, multivariate adaptive regression splines (MARS), least angle regression (LARS), among others. Furthermore, several methods arising from the field of machine learning were designed to be universal function approximators, so they can be applied both for classification and regression: neural networks, support vector machines, regression trees and rules, bagging and boosting ensembles, random forests and others. The current work develops an empirical quantitative comparison of a very large collection of regression techniques which is intended to provide the reader: 1) a list of the currently available regression models, grouped by families of related methods; 2) a brief description and list of references about each approach, alongside with technical details about its execution such as software implementation, list of tunable hyperparameters and recommended values; 3) a ranking of the available models according to its performance and speed, identifying the best performing approach and the performance level which can be expected for it; and 4) the code to run all the regression models considered in this study for

25 any regression problem³. In this comparison, we use the whole collection of
 26 regression datasets provided of the UCI machine learning repository (except-
 27 ing some datasets excluded by technical reasons), which a large collection of
 28 regression problems, and it should allow to develop a realistic and significant
 29 evaluation of the regression methods. As we explained in a previous paper
 30 comparing classifiers [1], provided that the size of the model collection used
 31 in the current comparison is large enough, we can assume that the best per-
 32 formance, measured in terms of squared correlation (R^2), achieved by some
 33 regression model for each dataset (denoted as R_{best}^2) is the highest attainable
 34 performance for that dataset. For a model which achieves a given R^2 in that
 35 dataset, the difference $\Delta = R_{best}^2 - R^2$, averaged over the dataset collection,
 36 can be used as an estimation of the expected Δ for that model and a new
 37 dataset D , not included in the collection. For the best model X on the cur-
 38 rent comparison, it is expected that $\Delta \gtrsim 0$, i.e., the R^2 achieved by X should
 39 not be too far from R_{best} in average over the data collection. Thus, although
 40 by the No-Free-Lunch theorem [2] we can not guarantee that X will be the
 41 best model for D , we can expect that X will achieve $R^2 > R_{best}^2 - \Delta$, so that
 42 X will not be very far from R_{best}^2 for dataset D . Consequently, the current
 43 paper may be useful for researchers who want to know how far a given model
 44 (e.g. the best model X) will be from the best available performance (which
 45 is, of course, unknown) for a new dataset. On the other hand, in general the
 46 best models in the current comparison achieve the best, or very near to the
 47 best, performances for most datasets in the collection. Therefore, although

³<https://nextcloud.citius.usc.es/index.php/s/Yb8LZQQFrgckjFk> (visited December 14, 2018).

48 X will not be the best regression model for a new dataset D , we can expect
 49 that some of the best models in our comparison will achieve the best R^2 .
 50 Thus, the current comparison may be also useful to provide to the reader a
 51 reduced list (e.g., the 10 best performing models of the collection) which is
 52 expected to include the one which provides the highest available performance
 53 for a new dataset D .

54 The section 2 describes the materials and methods used for this compar-
 55 ison, which include the list of datasets and regression methods, grouped by
 56 families. The description of regression models and issues related to their ex-
 57 ecution (software implementation, number of tunable hyperparameters and
 58 their values) are included in Appendix B. The section 3 reports the results
 59 of the experimental work and discusses them globally, by families of regres-
 60 sion models and by datasets, best model for each dataset, elapsed time and
 61 memory. Finally, the section 4 compiles the conclusions of this study.

62 2. Materials and methods

63 This section describes the scope of the current work, defined by the collec-
 64 tion of datasets used in this comparison (subsection 2.1) and by the regression
 65 methods that will be compared (subsection 2.2).

Original UCI name	Datasets	#patterns	#inputs
3D Road network	3Droad	434,874	4/3
Airfoil self-noise	airfoil	1,503	5
Air quality	air-quality-CO, air-quality-NMHC air-quality-NO2, air-quality-NOx air-quality-O3	1,230	8
Appliances energy prediction	appliances-energy	19,735	28/26
Auto MPG	auto-MPG	398	8/23
Automobile	automobile	205	26/66

Continued on next page.

Table 2 – *Continued from previous page.*

Original UCI name	Datasets	#patterns	#inputs
Beijing PM2.5	beijing-pm25	41,758	12
Bike sharing	bike-day	731	13/30
	bike-hour	17,379	14/42
Blog feedback	blog-feedback	60,021	280/13
Buzz in social media	buzz-twitter	583,250	77
Combined cycle power plant	combined-cycle	9,568	4
Communities & crime	com-crime	1,994	122
Communities & crime unnormalized	com-crime-unnorm	2,215	124/126
Computer hardware	com-hd	209	7
Concrete compressive strength	compress-stren	1,030	8
Concrete slump test	slump	103	9
	slump-comp, slump-flow		7
Condition based maintenance of naval propulsion plants	cond-turbine	11,934	13
Conventional and Social Media Movies 14/15	csm1415	231	12/11
Cuff-less blood pressure estimation	cuff-less	61,000	3/2
Daily Demand Forecasting Orders	daily-demand	60	13/12
Dynamic features of VirusShare Executables	dynamic-features	107,856	482/265
Energy efficiency	energy-cool, energy-heat	768	8/7
Facebook comment volume	facebook-comment	40,949	54/48
Facebook metrics	facebook-metrics	500	19
Forestfires	forestfires	517	12/39
Gas sensor array under dynamic gas mixtures	gas-dynamic-CO	58	438/57
	gas-dynamic-methane		
Geographical original of music	geo-lat, geo-long	1,059	116/72
	geo-music-lat, geo-music-long		68
GPS trajectories	gps-trajectory	163	10
Greenhouse gas observing network	greenhouse-net	955,167	15
Housing	housing	452	13
Individual household electric power consumption	household-consume	2,049,280	6/5
Istanbul stock exchange	stock-exchange	536	8
KEGG metabolic reaction network (undirected)	KEGG-reaction	65,554	27/25
KEGG metabolic relation network (directed)	KEGG-relation	54,413	22/17
Online news popularity	online-news	39,644	59/55
Online video characteristics and transcoding time dataset	video-transcode	68,784	20/8

Continued on next page.

Table 2 – Continued from previous page.

Original UCI name	Datasets	#patterns	#inputs
Parkinson speech dataset with multiple types of sound recordings	park-speech	1,040	26
Parkinsons telemonitoring	park-motor-UPDRS, park-total-UPDRS	5,875	16
PM2.5 Data 5 Chinese Cities	pm25-beijing-dongsi	24,237	13
	pm25-beijing-dongsihuan	20,166	
	pm25-beijing-nongzhanguan	24,137	
	pm25-beijing-us-post	49,579	
	pm25-chengdu-caotangsi	22,997	
	pm25-chengdu-shahepu	23,142	
	pm25-chengdu-us-post	27,368	
	pm25-guangzhou-city-station	32,351	
	pm25-guangzhou-5th-middle-school	21,095	
	pm25-guangzhou-us-post	32,351	
	pm25-shanghai-jingan	22,099	
	pm25-shanghai-us-post	31,180	
	pm25-shanghai-xuhui	23,128	
	pm25-shenyang-taiyuanji	22,992	
	pm25-shenyang-us-post	20,452	
	pm25-shenyang-xiaoheyan	23,202	
Physicochemical properties of protein tertiary structure	physico-protein	45,730	9
Relative location of CT slices on axial axis	CT-slices	53,500	385/355
Servo	servo	167	4/15
SML2010	SML2010	4,137	20/18
Stock portfolio	stock-abs, stock-annual, stock-excess stock-rel, stock-systematic, stock-total	252	6
Student performance	student-mat	395	32/77
	student-por	649	32/56
UJIIndoorLoc	UJ-lat, UJ-long	21,048	528/373
Yacht hydrodynamics	yacht-hydro	308	6
YearPredictionMSD	year-prediction	2,000	90

Table 2: Collection of 83 datasets from the UCI repository. Each column reports: original name in the UCI repository; datasets created from the original one; number of patterns (or observations) and inputs, before and after preprocessing.

Excluded dataset	Reason
Amazon access samples	Huge number of inputs (20,000)
Breast cancer Wisconsin (Prognostic)	Too few recurrent patterns (47)
Cargo 2000 Freight Tracking and Tracing	Less than 10 different output values (3)
Challenger USA space shuttle O-ring	Too few patterns (23) and inputs (3)
Condition based maintenance of naval propulsion plants (compress output)	Less than 10 different output values (9)
Container crane controller	Too few patterns (15)
DrivFace	Less than 10 different output values (4 subjects)
Early biomarkers of Parkinsons disease based on natural connected speech	Data are not available
Educational process mining	Inputs and output for regression are not clear
ElectricityLoadDiagrams	Huge number of inputs (140,256)
Fertility	Less than 10 different output values (2)
Gas sensor array drift dataset at different concentrations	Less than 10 different output values (7)
Gas sensor array exposed to turbulent gas mixtures	Huge number of inputs (150,000)
Gas sensor array under flow modulation	Less than 10 different output values (4)
Geo-Magnetic field and WLAN	Data format very complex
Improved spiral test using digitized graphics tablet for monitoring parkinsons disease	Data are not available
Insurance Company Benchmark (COIL 2000)	Less than 10 different output values (3)
KDC-4007 dataset Collection	Less than 10 different output values (8)
KDD cup 1998	Format too complex
Las Vegas Strip	Less than 10 different output values (5)
News popularity in multiple social media platforms	Data are text instead of numbers
Noisy office	Format too complex (PNG images)
Open university learning analytics	Format too complex
Paper Reviews	Less than 10 different output values (5)
Parkinson disease spiral drawings using digitized graphics tablet	Less than 10 different output values (3)
Skillcraft1 master table	Less than 10 different output values (7)
Solar flare	Less than 10 different output values
Tamilnadu electricity board hourly readings	Less than 10 different output values (2)
Tennis major tournament match statistics	Format problems
Twin gas sensor arrays	Less than 10 different output values (4)
UJIIndoorLoc-Mag	Output almost constant, format very complex
wiki4HE	Less than 10 different output values (7)
Wine quality (white/red)	Less than 10 different output values (7/6)

Table 1: List of the UCI regression datasets which were excluded from this study with the reason to be discarded. In datasets with discrete outputs the number of different output (or response) values is between parentheses.

2.1. Datasets

In the current research, we selected 48 of the 82 datasets (81 because the *Air Quality* dataset is repeated) listed as regression problems⁴ by the UCI Machine Learning Repository [3]. The remaining 33 datasets were discarded due to the reasons listed in Table 1. The reason which led to discard a larger amount (17) of datasets was the reduced number of output (usually called response in Statistics) values, because the majority of the regression models are designed for datasets with continuous outputs and many different values, where an ordering relation has sense. Therefore, we excluded 17 datasets whose outputs have few values (specifically, less than 10), because including them in the dataset collection might favour some regression models with respect to others, thus biasing the results of the study. These datasets should be considered as ordinal classification instead of pure regression problems. Table 2 reports the collection of 83 datasets which we use in the current work, with their numbers of patterns (usually named observations in Statistics) and inputs (also called features or attributes). Some of the 48 original UCI regression datasets selected for this work generated several regression problems, one for each data column which can be used as output for regression. Thus, some UCI datasets (whose original names are listed in the column 1 of the tables) give several datasets in column 2 (e.g., the *Air quality* dataset gives five datasets named by us *air-quality-CO*, *air-quality-NMHC*, etc.). There are also discrepancies between data in Table 2 with respect to the documentation of the UCI ML repository, which are described in detail in Appendix A.

⁴<http://archive.ics.uci.edu/ml/datasets.html?task=reg> (visited February 5, 2018).

Dataset and details	Dataset and details
3Droad: 4: altitude	geo-long: 118: longitude; same file
airfoil : 6: scaled sound pressure	geo-music-lat : 69: latitude; default file
air-quality-CO : 3: PT08.S1; 1,2,7,9,11,12	geo-music-long : 70: longitude; same file
air-quality-NMHC : 7: PT08.S2; 1,2,4,9,11,12	gps-trajectory* : 2: speed; 1,9,12,13; tracks file
air-quality-NO2 : 10: PT08.S4; 1,2,4,7,9,12	greenhouse-net: 16: synthetic; pasted all files
air-quality-NOx : 9: PT08.S3; 1,2,4,7,11,12	household-consume* : 3: global_active_power
air-quality-O3 : 11: PT08.S5; 1,2,4,7,9,11	housing: 14: MEDV
appliances-energy : 2: appliances; 1	KEGG-reaction* : 29: edgeCount; 1
auto-MPG* : 1: mpg	KEGG-relation : 24: ClusteringCoefficient; 1
automobile : 26: price :	online-news : 60: shares
bike-day : 16: cnf; 1,2; day.csv	park-motor-UPDRS : 5: motor_UPDRS; 1 2, 3, 4, 6
bike-hour : 17: cnf; 1,2; hour.csv	park-speech : 28: UPDRS; train_data.txt
blog-feedback : 281: target; pasted all files	park-total-UPDRS : 6: total_UPDRS; 1, 2, 3, 4, 5
buzz-twitter : 78: discussions : Twitter.data	physico-protein : 1: RMSD
combined-cycle : 5: PE; Folds5x2_pp.csv	servo : 5: class
com-crime* : 128: ViolentCrimesPerPop;1-5	slump : 8: slump
com-crime-unnorm* : 146: ViolentCrimesPerPop; 1-5,130-145,147	slump-comp : 10: comp. strength
com-hd : 10: ERP; 1,2	slump-flow : 9: flow
compress-stren : 9: ccs; Concrete_data.xls	SML2010* : 3: dining-room temperature; 1,2,4; both files
cond-turbine : 18: GT Turbine; 17; data.txt	stock-exchange : 10: EM; 1
CT-slices : 386: reference	student-mat : 33: G3; G1, G2
cuff-less* : 2: ABP	student-por : 33: G3; G1, G2
energy-cool : 10: cool	UJ-lat : 522: latitude; both files
energy-heat : 9: heat	UJ-long : 521: longitude; both files
facebook-comment : 54; Features_Variant_1.csv	
facebook-metrics : 1	
forestfires : 13: area	video-transcode : 21: utime; transcoding_mesurment.tsv
gas-dynamic-CO : 2: CO conc; 1	yacht-hydro : 7: resistance
gas-dynamic-methane : 2: Methane; 1	year-prediction : 1: year
geo-lat : 117: latitude; chromatic file	

Table 3: Information about datasets used in the current work: column number and name (if exists) used as output; removed columns (e.g., time marks or other outputs) where corresponds; files used, in datasets where several files are available; *: means that dataset contains missing patterns, which we replaced by the column mean.

91 Although several datasets in Table 2 contain several ten thousand pat-
 92 terns, and even half (buzz-twitter), one (greenhouse-net) and two million pat-
 93 terns (household-consume), the current study is not oriented to large-scale
 94 datasets because the available implementations of the majority of regression
 95 models would not work on such large datasets due to memory errors or ex-

96 cesive time. Thus, including large-scale datasets on the current study would
 97 bias the results and conclusions, limiting the comparison to those models
 98 with implementations that could be run on large data and favouring them
 99 over the remaining ones. Such a study for large-scale datasets would require
 100 a separate and completely different work which falls outside the scope of
 101 the current paper. Even discarding large-scale datasets, some models in our
 102 study are not able to train and test with some large datasets of our col-
 103 lection due to the limited RAM memory, although we set a maximum size
 104 of 128 GB. Besides, some other models spend a long time to finish, so we
 105 fixed a maximum run-time of 48 hours and labeled any model that could
 106 not finish within this time lapse as failing for this dataset. As usual, the
 107 output was pre-processed using the Box-Cox transformation [4] in order to
 108 make it more similar to a symmetric uni-modal distribution, with the `boxcox`
 109 function (`MASS` package) of the R statistical computing language [5]. In the
 110 *greenhouse-net* and *com-crime-unnorm* datasets, the decimal logarithm of
 111 the inputs are used, due to the wide range of many inputs. The constant, re-
 112 peated and collinear inputs⁵ are removed from all the datasets. Specifically,
 113 the `lm` function in the `stats` R package is used to calculate the coefficients of
 114 the linear model trained on the whole dataset, and the inputs with NA (not
 115 available) coefficients in the linear model are removed. This reason leads e.g.
 116 the *Blog feedback* dataset to reduce its inputs from 280 to 13. The rationale
 117 behind this is that constant, repeated or collinear inputs lead many models
 118 to develop calculations with singular matrices, so it is useful to remove these

⁵An input is considered collinear when it can be calculated as a linear combination of other inputs.

119 inputs in order to avoid the subsequent errors. On the other hand, the inputs
 120 with discrete values are replaced by dummy (also named indicator) inputs.
 121 For each discrete input (often named nominal variables in Statistics) with n
 122 values, it is replaced by $n - 1$ dummy binary inputs. The first value of the
 123 original discrete input is codified as zero values for the $n - 1$ dummy inputs;
 124 the second value is codified as 1 in the first dummy variable and zero in the
 125 remaining ones, and so on. Therefore, those datasets with discrete inputs
 126 increase the number of inputs, so that e.g. the *student-mat* dataset (Table
 127 2, second column) increases its inputs from 32 to 77 due to the presence of
 128 discrete inputs. In Table 2 the datasets whose “#inputs” column shows two
 129 numbers (i.e. 8/23), the first is the number of inputs of the original UCI
 130 dataset, and the second is the number of inputs used effectively in our exper-
 131 iments, after removing those inputs which are constant, repeated or collinear,
 132 and after replacing discrete inputs by their corresponding dummy variables.
 133 Those datasets with only one number in the #inputs column means that no
 134 input was removed nor added. Table 3 reports the name and number of the
 135 attribute used as output for each dataset. It also specifies the numbers of the
 136 columns that were discarded (if any), due to being useless (e.g., times, dates,
 137 names, etc.) or because they are alternative outputs (in datases with several
 138 outputs to be predicted) which can not be used as inputs (e.g., **latitude** can
 139 not be used as input for *UJ-long* dataset in Table 2). In those datasets with
 140 more than one file, the table specifies the files used. An asterisk (*) iden-
 141 tifies datasets with missing values, which are replaced by the mean of the
 142 non-missing values of that column. Note that applying further sophisticated
 143 management techniques to inputs with missing values might allow to extract

144 some information out of them in order to raise the prediction accuracy.

145 2.2. Regression models

146 We apply a wide collection of 77 models which belong to several families.
147 All the files (data, programs and results) are publicly available⁶. The major-
148 ity of them (74 models) are selected from the list of models⁷ included in the
149 Classification and Regression Training (**caret**) R package [6]. We discarded
150 52 **caret** models listed in Table 4, either because they are equivalent to other
151 models already included in our study (which are listed in the “Equivalence”
152 columns of the upper part of the table), due to run-time errors or because
153 they can not be used for regression (listed in the lower part of the table).
154 Instead of using the **train** function of the **caret** package, we ran the models
155 directly using the corresponding R packages (see the detailed list of mod-
156 els below), in order to control the execution of each single model. Besides,
157 the direct execution allows us to use the same configuration (e.g., the same
158 training and test patterns) as other four popular models, implemented in
159 other platforms, that we included in our study although they do not belong
160 to the **caret** model list (see the link in the above footnote). These models
161 are the deep learning neural network (named **dlkeras** in our study), using
162 the module **Keras**, configured for Theano [7], in the Python programming
163 language [8]; the ε -support vector regression (named **svr**), implemented by
164 the **LibSVM** library [9] and accessed via the C++ interface; the generalized re-
165 gression neural network and extreme learning machine with Gaussian kernel

⁶<https://nextcloud.citius.usc.es/index.php/s/Yb8LZQQFrgckjFk> (visited December 14, 2018).

⁷<http://topepo.github.io/caret/available-models.html> (visited April 27, 2017).

166 (named `grnn` and `kelm`, respectively) in Matlab [10].

Equivalence	Equivalence	Equivalence	Equivalence
bagEarthGCV → bagEarth	ctree → ctree2	gamLoess, gamSpline → gam	enpls → enpls.fs
gcvEarth → earth	glm.nb → bayesglm	glmnet_h2o → glmnet	knn → kknn
lars2 → lars	lmStepAIC → glmSAIC	M5Rules → M5	pls → simpls
nnet,mlpWD, mlpSGD, neuralnet → mlpWDml		RRFglobal → RRF	rbfDDA → rbf
parRF, ranger, Rborist, rfRules → rf		rpart1SE, rpart2 → rpart	xyf → bdk
Regression model not used		Reason	
bam		Version of gam for very large datasets	
krlsPoly		Polynomial kernel is not implemented	
ordinalNet		It requires a discrete output	
blasso, blassoAveraged, bridge		Not valid for regression	
leapBackward, leapForward, leapSeq		Run-time errors	
logicBag, logreg		Only for logic regression (binary outputs)	
svmLinear, svmPoly, rvmLinear, rvmPoly		Replaced by their versions with radial kernel	
svmBoundrangeString, svmExpoString		Only for text classification	
ANFIS, DENFIS, FIR.DM, GFS.LT.RS,HYFIS		Run-time errors	
GFS.FR.MOGUL, GFS.THRIFT, WM, FS.HGD			

Table 4: Upper part: Regression models of the `caret` model list which are not used because an equivalent model is already included in our study (`mlpWD` and `mlpWDml` refer to `mlpWeightDecay` and `mlpWeightDecayML`, respectively, in the `caret` model list). Lower part: models of the `caret` list excluded from this study due to run-time errors and other reasons.

167 The model operation is optimized by tuning the set of hyperparameters
168 specified in the `caret` model list. Almost all the models that we used have
169 from one to four tunable hyperparameters. We specify the number of values
170 tried for each hyperparameter (defined in the file `values.txt`, placed in the
171 folder `programs/R` of the file `regression.tar.gz`), which are listed in the
172 model description below. However, the specific hyperparameter values are
173 calculated by the `getModelInfo` function of the `caret` package, being in some
174 cases different for each dataset. Note that for some models (e.g. `gprRad`)
175 and datasets, this function returns a value list with less items than the num-
176 ber specified in `values.txt`, and even sometimes just one value is used. In

Family	Regression models	Family	Regression models
Linear regression (LR)	1. lm [11]	Least absolute shrinkage and selection operator (LASSO)	21. lasso [12]
	2. rlm [13]		22. relaxo [14]
Generalized linear regression (PLM)	3. penalized [15]		Ridge
	4. enet [12]	24. ridge [12]	
	5. glmnet [17]	25. spikeslab [18]	
	6. glmSAIC [19]	26. foba [20]	
Additive models (AM)	7. gam [21]	Bayesian models (BYM)	27. bayesglm [22]
	8. earth [23]		28. brnn [24]
Least squares (LS)	9. nnls [25]		Gaussian processes (SGP)
	10. krlsRadial [27]	30. gprLin [28]	
Projection methods (PRJ)	11. spls [29]	Quantile regression (QTR)	
	12. simpls [30]		32. gprPol [28]
	13. kpls [31]		33. rqlasso [32]
	14. wkpls [33]	Quantile regression (QTR)	34. rqnc [34]
	15. enpls.fs [35]		35. qrnn [36]
	16. plsRglm [37]	Nearest neighbors (NN)	36. kknns [38]
	17. ppr [39]	Regression trees (RGT)	37. rpart [40]
	18. pcr [41]		38. nodeHarvest [42]
	19. icr [43]		39. ctree2 [44]
	20. superpc [45]		40. partDSA [46]
			41. evtree [47]

Table 5: List of regression models and references grouped by families (see Appendix B for a brief description of each model).

177 these cases, although the `caret` model list specifies that hyperparameter as
 178 tunable, in the practice only one value is used. The list of hyperparameter
 179 values which are used in our experiments for a model and dataset is included
 180 in the file `results_model_dataset.dat`, where `model` and `dataset` stand for
 181 the names of the regression model and dataset, respectively, which is placed
 182 in the directory `results/dataset/model_implem`, where `implem` may be R,
 183 C, Python or Matlab. For some models (`ridge`, `rlm`, `mlpWD`, `mlpWDml`, `dnn`,
 184 `krlsRad` and `icr`), the value list provided by the `getModelInfo` function was
 185 not valid due to several reasons, so we directly specify the hyperparameter
 186 values used for tuning in the file `programs/R/initialize.R`. The models
 187 in Matlab, C++ and Python use pre-specified values, listed in the script

Family	Regression models	Family	Regression models
Regression rules (RGR)	42. M5 [48]	Boosting (BST) (continued)	60. gbm [49]
	43. cubist [50]		61. blackboost [51]
	44. SBC [52]		62. xgbTree [53]
Random forests (RF)	45. rf [54]	Neural networks (NET)	63. xgbLinear [53]
	46. Boruta [55]		64. mlWD [56]
	47. RRF [57]		65. mlWDml [56]
	48. cforest [58]		66. avNNet [6]
	49. qrf [59]		67. rbf [56]
	50. extraTrees [60]		68. grnn [61]
Bagging (BAG)	51. bag [62]		69. elm [63]
	52. bagEarth [6]		70. kelm [63]
	53. treebag [64]		71. pcaNNet [6]
Boosting (BST)	54. rndGLM [65]		72. bdk [66]
	55. BstLm [53]	Deep learning (DL)	73. dlkeras [67]
	56. bstSm [53]		74. dnn [68]
	57. bstTree [53]	Support vector regression (SVR)	75. svr [9]
	58. glmboost [69]		76. svmRad [70]
	59. gamboost [69]		77. rvmRad [71]

Table 6: Continuation of Table 5.

run_model_dataset.sh, which are the same for all datasets. Tables 5 and 6 list the the collection of 77 regression models used in this work, grouped by families, which are described in the Appendix B, specifying the software implementation (R package or other platforms), their tunable hyperparameters and the values used.

3. Results and discussion

The experimental work [72] uses the following methodology: for each dataset with less than 10,000 patterns, $N = 500$ random partitions are generated, using the 50% of the patterns for training, 25% for validation (in hyperparameter tuning) and 25% for test. For each dataset with more than 10,000 patterns, a 10-fold cross validation is developed, so there are $N = 10$ training, validation and test percentages. The rationale is to limit the compu-

200 tational overhead of 500 trials to smaller datasets, using a lighter methodol-
 201 ogy (10-fold), although statistically less significant, for larger datasets. Each
 202 regression model is trained on the training partitions for each combination
 203 of its hyperparameter values, and it is tested on its corresponding validation
 204 partition. The performance measures used are the root mean square error
 205 (RMSE), the squared correlation (R^2) and the mean absolute error (MAE).
 206 We use these three different measures in order to give more significance to
 207 the results, which in this way can be observed from three different points of
 208 view, and also in order to evaluate whether they are coherent suggesting sim-
 209 ilar conclusions. For each combination of hyperparameter values, the average
 210 RMSE over the validation partitions is calculated, and the combination with
 211 the lowest average RMSE is selected for testing (quantile regression models
 212 as `rqlasso`, `rqnc` and `qrnn` are designed to optimize the quantile error, which
 213 is used instead of RMSE). Finally, the model is trained on the training parti-
 214 tions using the selected combination of its hyperparameter value and tested
 215 on the test partitions. The performance measurements are the RMSE, R^2
 216 and MAE between the true and predicted output values concatenated for the
 217 N test sets. Note that the R^2 is calculated using the predicted and true out-
 218 puts for the test patterns, while it is often used to measure the percentage of
 219 variance explained by the model on the training patterns. Those regression
 220 models which lack tunable hyperparameters are trained on the training parti-
 221 tions and tested on the corresponding test partitions, and the average RMSE,
 222 R^2 and MAE over the test partitions are the quality measurements. Some
 223 models which are specially sensitive to collinear inputs are trained, for each
 224 partition, using only those inputs which are not collinear. Although collinear

inputs have been removed from the dataset in the initial preprocessing, for certain partitions some inputs in the training set may be collinear despite of being not collinear considering the whole dataset. To avoid the subsequent errors, these inputs are discarded for these models. All the continuous inputs and the output are standardized to have zero mean and standard deviation one, using the mean and deviation calculated in each training partition.

We run this collection of 77 regression models over 83 datasets, developing a total of 6,391 experiments, which were developed on a cluster whose nodes are equipped with 64 Intel Xeon E5-2650L processors and 4 GB of RAM memory each processor, although those regression models which required more memory with large data sets were run using several processors and up to 128 GB of RAM memory. Since certain models failed for some datasets, we developed a preliminar study to evaluate the datasets according to their size, given by its population, and “difficulty”, estimated by the R^2 achieved by the linear regression model (`lm`). We selected `lm` because it is a classical approach which can be considered as a baseline reference for other models and it does not require large time nor memory, so it does not fail in any dataset. The Figure 1 plots R_{lm}^2 for all the datasets vs. their populations N_p . According this plot, we divided the datasets into four groups: group SD includes 20 datasets with $N_p < 5,000$ and $R_{lm}^2 < 0.6$, i.e., small-difficult datasets; group SE includes 23 datasets with $R_{lm}^2 \geq 0.6$ and $N_p < 5,000$ (small-easy datasets); group LD with 33 datasets where $R_{lm}^2 < 0.6$ and $N_p \geq 5,000$ (large-difficult datasets); and group LE with 7 datasets where $R_{lm}^2 \geq 0.6$ and $N_p \geq 5,000$ (large-easy datasets). Table 7 lists the datasets of each group.




Figure 1: Values of R^2 achieved by $1m$ for all the datasets plotted against their populations (in logarithmic scale), dividing datasets in groups small-difficult (SD, lower left quarter of the figure), small-easy (SE, upper left), large-difficult (LD, lower right) and large-easy (LE, upper right).

250 In order to compare the R^2 values achieved by the regression models over
251 all the datasets, averaging would weight more those datasets with high R^2 ,
252 favouring models which perform well in easy datasets and biasing the results.
253 In order to do a neutral comparison, the solution is to average over all the
254 datasets the model positions in a ranking sorted by decreasing R^2 , instead of
255 directly averaging R^2 values, because the model positions belong to the same
256 range for all the datasets. This is done using the Friedman ranking [73] of
257 the R^2 coefficient, which evaluates the position where each regression model
258 is placed, in average over all the datasets, when R^2 is sorted by decreasing
259 values. The R^2 Friedman ranking of the $M = 77$ models over the $D = 83$
260 datasets can be calculated as follows. For each dataset $d = 1, \dots, D$, the R^2
261 values of all the models are sorted decreasingly. For each model $m = 1, \dots, M$
262 let be p_{md} its position in dataset d . The Friedman rank F_m of model m is

263 defined as $F_m = \frac{1}{D} \sum_{d=1}^D p_{md}$, i.e., the average position of model m over all
 264 the sortings of R^2 for the different datasets. For example, a model with rank
 265 5 achieves the 5th highest R^2 coefficient in average over all the datasets.

266 A number of run-time errors happened for certain models and datasets.
 267 There are more errors in large datasets, because some model implementations
 268 may not be designed to process large amounts of data. When a model fails
 269 for a dataset (because it overcomes the maximum allowed time of 48 hours,
 270 because it requires more than 128 GB of RAM, or due to other reasons), and
 271 in order to calculate the Friedman ranking, its R^2 is intended to be zero,
 272 while its RMSE and MAE are assigned as:

$$RMSE = \max \left\{ \max_{m \in \mathcal{R}} [RMSE_m], \sqrt{\frac{1}{N} \sum_{i=1}^N (t_i - \bar{t}_i)^2} \right\} \quad (1)$$

$$MAE = \max \left\{ \max_{m \in \mathcal{R}} [MAE_m], \frac{1}{N} \sum_{i=1}^N |t_i - \bar{t}| \right\} \quad (2)$$

273 where $\mathcal{R}$ is the set of models which did not fail in that dataset, t_i is the
 274 true output for test pattern i and N is the number of test patterns. Besides,
 275 denoting by k the test partition to which pattern i belongs, $\bar{t}_i$ is the mean of
 276 the true output values over the patterns in the k -th training partition. The
 277 rationale behind this is that a regression model which fails behaves as if it
 278 would predict the mean of the true output values for all the test patterns, so it
 279 should be the last of the list. For some models, the errors happen only during
 280 tuning for some partitions, which are not considered to calculate the average
 281 RMSE corresponding to that combination of hyper-parameter values. When

a model fails for a given combination of hyper-parameter values and all the partitions, that combination is not selected for testing. When a model fails for all the combinations of hyper-parameter values, or when it fails for some test partition, the model is considered that fails for that dataset. Overall, the number of experiments where the model failed is 1,205 and represents 18.85% of the 6,391 experiments.

Group (#datasets)	Datasets
SD (20): small-difficult	airfoil com-crime-unnorm csm1415 forestfires geo-lat geo-long geo-music-lat geo-music-long gps-trajectory park-speech slump slump-flow stock-abs stock-annual stock-excess stock-rel stock-systematic stock-total student-mat student-por
SE (23): small-easy	air-quality-CO air-quality-NMHC air-quality-NO2 air-quality-NOx air-quality-O3 automobile auto-mpg bike-day com-crime com-hd compress-stren daily-demand energy-cool energy-heat facebook-metrics gas-dynamic-CO gas-dynamic-methane housing servo slump-comp SML2010 stock-exchange yacht-hydro
LD (33): large-difficult	3Droad appliances-energy beijing-pm25 blog-feedback buzz-twitter cuff-less dynamic-features facebook-comment greenhouse-net household-consume KEGG-relation online-news park-motor-UPDRS park-total-UPDRS physico-protein pm25-beijing-dongsi pm25-beijing-dongsihuan pm25-beijing-nongzhanguan pm25-beijing-us-post pm25-chengdu-caotangsi pm25-chengdu-shahepu pm25-chengdu-us-post pm25-guangzhou-5th-middle-school pm25-guangzhou-city-station pm25-guangzhou-us-post pm25-shanghai-jingan pm25-shanghai-us-post pm25-shanghai-xuhui pm25-shenyang-taiyuanji pm25-shenyang-us-post pm25-shenyang-xiaoheyan video-transcode year-prediction
LE (7): large-easy	bike-hour combined-cycle cond-turbine CT-slices KEGG-reaction UJ-lat UJ-long

Table 7: Groups of datasets according to its size (small/large) and complexity (easy/difficult).

3.1. Discussion by dataset group

Table 8 reports the 20 best regression models according to the Friedman ranking of R^2 , RMSE and MAE for the datasets of **group SD**, which includes 20 **small-difficult** datasets. For each model in the R^2 ranking, the percentage of datasets where it failed is also reported (column %Error). The last two columns report the models which achieved the best R^2 for some

dataset and the percentage of datasets where this happened. First of all, **penalized** achieves the first positions in the three rankings, being the best R^2 for 25% of datasets. **ExtraTrees**, **rf** and **kelm** are the following in the R^2 ranking, although the former achieves much lower positions in RMSE and MAE rankings. Specifically, **extraTrees** achieves the best R^2 in 40% of the datasets, although it fails in 5% of them, so it can be considered less regular as **penalized**. Other good positions in the R^2 ranking are for **qrf** and **bstTree**, followed by **avNNet**, **svr** and **svmRad**, Gaussian process (**gprRad** and **gprPol**), **bagEarth** and **cubist**, which achieves the best R^2 for 10% of datasets.

	R^2			RMSE		MAE		Best R^2	
Pos.	Model	Rank	%Error	Model	Rank	Model	Rank	Model	%Best
1	penalized	8.45	0.0	penalized	9.65	penalized	13.40	extraTrees	40.0
2	extraTrees	13.05	5.0	kelm	13.15	svmRad	13.90	penalized	25.0
3	rf	15.35	5.0	gprPol	14.45	svr	15.70	cubist	10.0
4	kelm	19.15	5.0	bagEarth	17.55	kelm	16.25	brnn	10.0
5	qrf	20.75	0.0	svmRad	18.00	bstTree	19.15	rbf	5.0
6	bstTree	21.00	0.0	cforest	18.65	gprPol	19.25	qrf	5.0
7	avNNet	21.25	5.0	bstTree	19.10	cubist	19.65	bagEarth	5.0
8	svr	22.20	10.0	svr	19.35	bagEarth	19.75	—	—
9	svmRad	23.15	5.0	enet	21.50	cforest	21.45	—	—
10	gprRad	23.20	0.0	BstLm	22.75	qrf	23.35	—	—
11	RRF	24.10	20.0	glmboost	23.80	avNNet	23.85	—	—
12	bagEarth	24.10	0.0	gbm	24.20	gbm	24.35	—	—
13	gprPol	24.35	0.0	foba	24.70	grnn	27.00	—	—
14	gbm	24.60	0.0	bMachine	25.30	gprRad	28.35	—	—
15	cubist	26.20	5.0	grnn	26.25	extraTrees	29.05	—	—
16	ridge	27.85	0.0	spls	27.25	rf	29.15	—	—
17	treebag	29.45	0.0	spikeslab	27.25	BstLm	29.45	—	—
18	foba	29.55	0.0	rf	27.90	treebag	29.50	—	—
19	spls	29.85	0.0	lars	28.35	rqlasso	29.75	—	—
20	lars	30.25	0.0	avNNet	28.90	glmboost	29.95	—	—

Table 8: List of the 20 best regression models according to the Friedman rank of R^2 , RMSE and MAE for dataset group SD, with 20 **small-difficult** datasets. The last two columns list the models which achieve the best R^2 for some dataset, sorted by decreasing number of datasets.

Since this group includes only small datasets, most models exhibit low

error percentages (i.e., most models never or rarely fail on datasets of this group), although some models with errors achieve good positions, e.g. **svr** (10% of errors), **RRF** (20%), **extraTrees** and **cubist** (5% each one). Besides, **qrnm** and **nodeHarvest** are very slow and they were shutdown after 48 h. for the 20 datasets of this group. Considering memory errors, **rndGLM** is the model which requires more memory, overcoming the memory and time limits in 1 and 5 datasets of this group, respectively.

Pos.	R^2			RMSE		MAE		Best R^2	
	Model	Rank	%Error	Model	Rank	Model	Rank	Model	%Best
1	cubist	6.48	0.0	cubist	6.26	cubist	5.65	cubist	21.7
2	avNNet	10.13	4.3	avNNet	10.04	avNNet	10.96	avNNet	13.0
3	bstTree	12.57	0.0	bstTree	12.39	bstTree	13.70	extraTrees	13.0
4	gbm	12.87	0.0	gbm	12.74	ppr	13.91	gbm	8.7
5	bagEarth	14.57	0.0	bagEarth	14.30	gbm	13.96	penalized	8.7
6	ppr	14.65	0.0	ppr	14.52	bagEarth	15.96	bMachine	8.7
7	bMachine	14.96	4.3	bMachine	15.22	bMachine	16.70	kelm	4.3
8	extraTrees	17.13	8.7	earth	18.35	M5	16.83	M5	4.3
9	earth	18.57	0.0	kelm	18.65	qrf	17.43	rf	4.3
10	kelm	18.70	17.4	extraTrees	18.87	extraTrees	18.00	brnn	4.3
11	rf	19.26	4.3	rf	19.65	kelm	18.74	bagEarth	4.3
12	M5	20.30	0.0	M5	19.87	rf	19.70	bstTree	4.3
13	RRF	22.43	8.7	RRF	22.61	earth	21.00	—	—
14	qrf	22.48	0.0	qrf	23.43	brnn	22.48	—	—
15	brnn	23.65	21.7	brnn	23.61	RRF	22.83	—	—
16	gprPol	24.00	4.3	gprPol	24.22	pcaNNet	24.17	—	—
17	pcaNNet	25.04	0.0	pcaNNet	25.09	gprPol	25.78	—	—
18	dlkeras	27.35	0.0	dlkeras	27.61	rqlasso	26.52	—	—
19	Boruta	27.43	17.4	Boruta	27.78	cforest	27.13	—	—
20	enet	28.52	0.0	enet	28.09	Boruta	27.70	—	—

Table 9: List of the 20 best regression models according to the Friedman rank of R^2 , RMSE and MAE over 23 datasets of group SE (**small-easy**).

Considering **small-easy** datasets (group **SE**, 23 datasets, table 9), the three rankings are even more coherent than for group SD, sharing the first three positions: **cubist**, which achieves the best R^2 for 21.7% of datasets, **avNNet** (the best R^2 for 13% of datasets) and **bstTree**. **Penalized** is not present in this list (although it is the best in 8.7% of datasets), but **gbm**

and **bMachine** (which are the bests in 8.7% of datasets), **bagEarth**, **ppr**,
extraTrees (the best in 13% of datasets), **earth** and **kelm** are in positions 4-
10. Other models with good results are **rf**, **M5** (the best for 4.3% of datasets),
RRF and **qrf**.

Pos.	R^2			RMSE		MAE		Best R^2	
	Model	Rank	%Error	Model	Rank	Model	Rank	Model	%Best
1	M5	9.48	0.0	M5	9.39	M5	9.55	extraTrees	48.5
2	cubist	12.39	15.2	gbm	12.61	kknn	12.55	bstTree	12.1
3	gbm	12.48	3.0	cubist	12.70	cubist	12.61	cubist	9.1
4	xgbTree	14.24	6.1	xgbTree	14.15	gbm	13.42	dlkeras	6.1
5	kknn	14.48	12.1	kknn	14.48	xgbTree	14.82	xgbTree	6.1
6	bstTree	15.12	12.1	bstTree	15.27	bstTree	16.00	ppr	3.0
7	blackboost	16.79	0.0	blackboost	17.27	grnn	17.33	kknn	3.0
8	dlkeras	18.36	15.2	pcaNNet	18.33	blackboost	17.70	M5	3.0
9	svr	18.58	27.3	svr	18.45	svr	18.76	rf	3.0
10	pcaNNet	18.76	0.0	dlkeras	18.67	pcaNNet	18.82	qrf	3.0
11	grnn	19.70	18.2	ppr	19.48	dlkeras	19.18	bMachine	3.0
12	ppr	19.73	3.0	grnn	19.52	ppr	19.58	—	—
13	qrf	21.33	27.3	qrf	21.27	qrf	20.30	—	—
14	svmRad	21.88	24.2	svmRad	21.79	svmRad	20.58	—	—
15	earth	22.52	0.0	earth	22.21	extraTrees	22.33	—	—
16	extraTrees	23.03	27.3	bag	22.91	bag	22.61	—	—
17	bag	23.03	15.2	avNNet	23.42	earth	22.88	—	—
18	avNNet	23.52	21.2	extraTrees	23.91	avNNet	23.64	—	—
19	bMachine	24.76	24.2	bMachine	24.64	bMachine	25.24	—	—
20	cforest	25.79	27.3	cforest	25.91	rpart	26.00	—	—

Table 10: List of the 20 best regression models according to the Friedman rank of R^2 , RMSE and MAE for the 33 datasets of group LD (**large-difficult**).

In **large-difficult** datasets (group **LD**, 33 datasets, table 10), the **M5**
achieves the first positions in the three rankings (although it achieves the best
 R^2 only in 3% of datasets), followed by **cubist** (which achieves the best R^2
and errors in 9.1% and 15.2% of datasets, respectively) and **gbm**. Other mod-
els with good performance are **xgbTree**, **knn**, **bstTree**, **blackboost**, **dlkeras**
(15.2% of errors), **svr** (with errors in 27.3% of datasets) and **pcaNNet**. The
high error frequency of several models (either by overcoming limits on mem-
ory or time) is due to the large size of datasets in this group. **ExtraTrees** also

overcomes the maximum time in 27.3% of datasets and, as in groups SD and SE, it achieves the best R^2 for more datasets (48.5%). Specifically, it achieves the highest R^2 for 13 of the 16 datasets created from the original *PM2.5 Data 5 Chinese Cities* dataset in the UCI repository. In these datasets **svr** and **keIm** were run with a lower number of hyperparameter values ($\{ 0.125, 0.5, 1, 4, 16 \}$ and $\{ 0.00391 \ 0.01562 \ 0.125 \ 1 \ 4 \}$ for C and γ , respectively), in order to avoid overcoming the maximum run time. The models **wkpls**, **gprPol**, **krlsRad**, **rvmRad**, **SBC** and **qrnn** failed for the 33 datasets of this group.

Pos.	Model	Rank	Pos.	Model	Rank	Pos.	Model	Rank	Pos.	Model	Rank
1	M5	8.1	6	pcaNNet	15.4	11	rpart	23.5	16	avNNet	26.6
2	gbm	9.8	7	earth	18.6	12	treebag	24.1	17	svmRad	26.8
3	blackboost	10.9	8	kknn	19.4	13	ctree2	25.1	18	enet	26.8
4	xgbTree	14.6	9	bstTree	19.8	14	elm	26.2	19	bag	26.9
5	ppr	14.8	10	cubist	20.4	15	svr	26.2	20	dlkeras	27.9

Table 11: Friedman rank of R^2 (first 20 models) of group LD (**large-difficult** datasets) discarding PM2.5 Data Chinese Cities datasets.

The PM2.5 Data 5 Chinese Cities datasets represent almost the half of the 33 datasets in this group. Since this fact might bias the results, we calculated the R^2 Friedman rank discarding these 16 datasets (Table 11). In this case, the best model is M5 again, **cubist** descends to the 10th position, replaced by **gbm** and followed by **blackboost**, **xgbTree** and **ppr**, while **extraTrees** leaves the top-20.

The rankings of group LE (**large-easy**) is very similar to group LD: the M5 achieves again the best position in the rankings of R^2 , RMSE and MAE, followed by the same models as the previous group: **cubist** (which achieves the best R^2 in 42.9%, and errors in 14.3%, of the datasets), **gbm**, **bag**, **bstTree**, **blackboost** and **pcaNNet**. In this group, **extraTrees** only achieves

Pos.	R^2			RMSE		MAE		Best R^2	
	Model	Rank	%Error	Model	Rank	Model	Rank	Model	%Best
1	M5	6.57	0.0	M5	6.57	M5	5.14	cubist	42.9
2	cubist	10.43	14.3	cubist	10.43	cubist	10.29	extraTrees	14.3
3	gbm	11.43	0.0	gbm	11.43	gbm	12.43	rf	14.3
4	bag	14.57	0.0	bag	14.57	bag	13.43	brnn	14.3
5	bstTree	15.29	14.3	bstTree	15.29	blackboost	15.86	dlkeras	14.3
6	blackboost	15.43	0.0	blackboost	15.43	pcaNNet	17.00	—	—
7	pcaNNet	16.00	0.0	pcaNNet	15.71	bstTree	17.29	—	—
8	xgbTree	19.57	14.3	xgbTree	19.43	rlm	20.00	—	—
9	lm	21.43	0.0	earth	21.29	xgbTree	21.00	—	—
10	earth	21.86	0.0	kknn	22.14	kknn	21.57	—	—
11	bayesglm	21.86	0.0	lm	22.57	dlkeras	22.14	—	—
12	kknn	22.14	14.3	bayesglm	22.57	earth	23.00	—	—
13	avNNet	23.14	42.9	avNNet	23.14	avNNet	23.43	—	—
14	dlkeras	23.43	14.3	dlkeras	23.71	lm	23.71	—	—
15	svr	24.43	42.9	lasso	24.43	svr	25.29	—	—
16	lasso	24.71	0.0	svr	24.71	gam	25.43	—	—
17	spikeslab	25.29	0.0	enet	25.00	bayesglm	25.43	—	—
18	bagEarth	25.57	14.3	spikeslab	25.29	spikeslab	25.43	—	—
19	enet	26.14	14.3	bagEarth	25.43	lasso	25.71	—	—
20	gam	26.14	0.0	gam	25.86	lars	26.14	—	—

Table 12: List of the 20 best regression models according to the Friedman rank of R^2 , RMSE and MAE for the 7 **large-easy** datasets (group LE).

the best R^2 in 1 dataset, which represents 14.3%, and achieves errors in 57.1% of datasets. Since the datasets are easy, the `lm` also achieves a good position (9th). The models which fail in the 7 datasets of this group are `keIm`, `wkpls`, `gprPol`, `krlsRad`, `rvmRadial`, `SBC`, `nodeHarvest` and `qrnn`.

3.2. Global discussion

We also developed an analysis considering all the datasets together. Table 13 reports the 20 best models according to the Friedman rankings for R^2 , RMSE and MAE over all the datasets, alongside with the percentage of datasets with errors for the 20 best models according to R^2 (column %Error) and the percentage of datasets where each model achieves the best R^2 (column %Best). The global results confirm the conclusions over the four dataset groups: `cubist` is globally the best regression model on the three

Pos.	R^2			RMSE		MAE		Best R^2	
	Model	Rank	%Error	Model	Rank	Model	Rank	Model	%Best
1	cubist	13.92	8.4	cubist	14.96	cubist	12.18	extraTrees	33.7
2	gbm	15.42	1.2	gbm	15.34	gbm	16.12	cubist	15.7
3	bstTree	15.84	6.0	bstTree	15.40	bstTree	16.23	penalized	8.4
4	M5	18.20	0.0	M5	17.20	M5	16.36	bstTree	6.0
5	avNNet	19.23	14.5	avNNet	21.01	avNNet	20.16	brnn	4.8
6	extraTrees	19.61	19.3	bagEarth	22.46	qrf	21.11	avNNet	3.6
7	qrf	22.41	14.5	bMachine	22.48	svr	23.08	rf	3.6
8	pcaNNet	23.49	0.0	svr	23.54	extraTrees	23.41	bMachine	3.6
9	rf	23.82	24.1	earth	23.99	bagEarth	23.57	dlkeras	3.6
10	bMachine	23.83	15.7	blackboost	24.39	pcaNNet	24.29	gbm	2.4
11	bagEarth	24.14	7.2	extraTrees	24.71	bMachine	24.45	M5	2.4
12	svr	24.17	27.7	pcaNNet	24.83	ppr	24.76	qrf	2.4
13	ppr	24.57	4.8	ppr	26.06	kknn	25.07	bagEarth	2.4
14	earth	25.52	0.0	kknn	26.46	earth	25.40	xgbTree	2.4
15	blackboost	25.69	0.0	qrf	26.84	grnn	25.92	kelm	1.2
16	kknn	26.24	6.0	rf	27.01	svmRad	26.28	ppr	1.2
17	penalized	27.70	12.0	grnn	27.37	blackboost	26.92	kknn	1.2
18	dlkeras	28.07	7.2	enet	27.41	bag	27.27	rbf	1.2
19	svmRad	29.14	28.9	cforest	27.53	cforest	27.28	—	—
20	grnn	29.61	9.6	bag	27.64	rf	27.57	—	—

Table 13: List of the 20 best models according to the Friedman rank of R^2 , RMSE and MAE over all the datasets.

rankings (although it achieves errors for 8.4% of datasets), followed by **gbm** and **bstTree**. The difference is higher in terms of MAE (ranks 12.18 and 16.12 for **cubist** and **gbm**, respectively) than in terms of R^2 or RMSE. **Cubist** is also the second model which achieves more often the best R^2 (in 15.7% of datasets) after **extraTrees** (33.7%), whose position is however much lower (6, 11 and 8 in the R^2 , RMSE and MAE rankings, respectively), achieving errors for 19.3% of datasets. The **M5** achieves position 4 in the three rankings, but it never fails, so its difference with **cubist** is caused by lower performance in datasets where **cubist** does not fail. Globally, the best neural network is **avNNet** (position 5). Other models in the top-10 of some rankings are **qrf**, **pcaNNet**, **rf** (with 24.1% of errors), **bMachine**, **bagEarth**, **svr** (27.7% of errors), **earth** and **blackboost**. Penalized, which is the best model for

372 8.4% of datasets, achieves position 17 in the R^2 ranking, with 12% of errors.

373 The **lm** falls outside this table (positions 33–34).

Pos.	Model	Rank	Pos.	Model	Rank	Pos.	Model	Rank	Pos.	Model	Rank
1	cubist	11.1	6	ppr	19.5	11	qrf	22.1	16	kknn	24.8
2	gbm	12.6	7	pcaNNet	20.4	12	bMachine	23.0	17	rf	26.0
3	M5	13.5	8	earth	20.6	13	bagEarth	23.6	18	bag	26.7
4	bstTree	14.1	9	blackboost	21.0	14	dlkeras	23.9	19	grnn	28.0
5	avNNet	18.8	10	extraTrees	21.1	15	svr	24.6	20	cforest	29.0

Table 14: List of the 20 best regression models according to the Friedman rank of R^2 over all the datasets excepting PM2.5 Data 5 Chinese Cities.

374 Despite its high number of errors, **extraTrees** achieves a good position
375 because it achieves the best R^2 for the majority of the thirteen PM2.5 Data 5
376 Chinese Cities datasets. In order to confirm that this fact does not bias the
377 global results, we created an alternative ranking discarding these datasets
378 (see Table 14). This alternative rank is rather similar to the previous one,
379 being **cubist**, **gbm**, **M5** and **bstTree** the first models, but **extraTrees** and
380 **rf** move from positions 6 and 9 to 10 and 17, respectively.

381 We evaluated the statistical significance of the differences in R^2 among
382 models with several tests. A Friedman test [74], implemented using the **stats**
383 package, comparing all the models gives a p -value of $1.8 \cdot 10^{-45} < 0.05$, which
384 means that the difference among them is statistically significant. Table 15
385 reports the results of several statistical tests [75] developed to compare the
386 globally best model (**cubist**) and the remaining 19 best models in terms
387 of R^2 . We used: 1) the paired-sample T-test, with the Matlab **ttest(x,y)**
388 function: according to [75], since the number of datasets (83) is higher than
389 30, the requirement of normal distributions for the R^2 values is not necessary;

Pos.	Model	Paired T	Dunnett	2-Sample T	Wilcoxon	Sign	Post-Hoc
2	gbm	0.825	1.000	0.921	0.593	0.001*	0.160
3	bstTree	0.215	1.000	0.789	0.409	0.000*	0.974
4	M5	0.781	1.000	0.902	0.658	0.000*	0.007*
5	avNNet	0.000*	0.451	0.068	0.075	0.000*	0.001*
6	extraTrees	0.001*	0.474	0.083	0.124	0.909	0.671
7	qrf	0.034*	0.995	0.383	0.285	0.006*	0.000*
8	pcaNNet	0.034*	0.984	0.294	0.273	0.000*	0.042*
9	rf	0.001*	0.375	0.064	0.048*	0.002*	0.000*
10	bMachine	0.000*	0.624	0.109	0.051	0.000*	0.000*
11	bagEarth	0.000*	0.518	0.074	0.086	0.000*	0.000*
12	svr	0.000*	0.031*	0.005*	0.002*	0.000*	0.116
13	ppr	0.004*	0.737	0.125	0.143	0.000*	0.000*
14	earth	0.013*	0.919	0.204	0.188	0.000*	0.000*
15	blackboost	0.045*	0.988	0.303	0.194	0.000*	0.000*
16	kknn	0.003*	1.000	0.452	0.097	0.000*	0.000*
17	penalized	0.000*	0.006*	0.000*	0.001*	0.000*	0.000*
18	dlkeras	0.019*	0.992	0.343	0.133	0.000*	0.000*
19	svmRad	0.000*	0.001*	0.000*	0.000*	0.000*	0.000*
20	grnn	0.000*	0.897	0.196	0.037*	0.000*	0.000*

Table 15: p -values achieved by the paired-sample T-test, Dunnett test, two-sample T-test, Wilcoxon ranksum test, sign test and Post-Hoc Friedman-Nemenyi test comparing the R^2 of the globally best model (**cubist**) and the remaining models in the top-20. The asterisks label models where the comparison is statistically significant ($p < 0.05$).

2) the Dunnett’s test [76] of multiple comparison, using the **dunnett**⁸ Matlab function; 3) the two-sample T-test, with the Matlab **ttest2** function; 4) the Wilcoxon rank sum test [77], with the Matlab **ranksum** function; 5) the sign test, using the Matlab **signtest** function [77]; and 6) the Post-Hoc Friedman-Nemenyi test (**PMCMR** [78] R package). The paired T-test gives significant differences, labeled as an asterisk (*), except for the first three models, while the Dunnett, two-sample T and Wilcoxon tests only label few models as statistically different, including **svr**, **penalized** and **svmRad** (the Wilcoxon

⁸<https://es.mathworks.com/matlabcentral/fileexchange/38157-dunnett-m>

test also labels `rf` and `grnn` as different). The sign test, which counts the number of datasets where each regressor achieves the best R^2 , labels all the models as statistically different to `cubist` excepting `extraTrees`. Finally, the Post-Hoc Friedman-Nemenyi test, which develops a comparison of multiple models, identifies as statistically significant the differences with all the models excepting `gbm`, `bstTree` `extraTrees` and `svr`.




Figure 2: Value of R^2_{best} against R^2 for all the datasets.

Figures 2a and 2b plot R^2_{best} against R^2_{cubist} and R^2_{M5} , respectively, for all the datasets (M5 is the first regression model in the ranking which never fails). Cubist is near the best R^2 for all the points above 0.6, but its R^2 is almost zero for more than 10 points, due mainly to errors, which are on the vertical axis. However, all the points are near the red line for M5, which never fails, whose R^2 is near zero only for those datasets whose best R^2 is already almost zero, so the probability that M5 achieves R^2 near R^2_{best} is much higher.

Left panel of Figure 3 plots the percentage of datasets where the difference $\Delta = R^2_{best} - R^2$ overcomes a threshold θ , where R^2 is the value achieved by the first 4 models in Table 13: `cubist`, `gbm`, `bstTree` and M5. The model is




Figure 3: Left panel: percentage of datasets where the difference $\Delta = R^2_{best} - R^2$, with R^2 achieved by **cubist**, **gbm**, **bstTree** and **M5**, overcomes a given threshold θ . Right panel: boxplots of the differences $R^2_{best} - R^2$ for the 10 best regressors.

414 better when the line is lower, because the percentage of datasets where $\Delta > \theta$
 415 is lower. For low θ values, the lines follow the order **cubist** < **bstTree** <
 416 **gbm** < **M5**, but the high error frequency of **cubist** and **bstTree** (7 and 5,
 417 respectively) cause that blue and black lines fall to zero for $\theta > 0.4$ (outside
 418 the plot), while green and red lines (**gbm** and **M5**, respectively) fall to zero
 419 at 0.322 and 0.338. Note that **gbm** fails (achieving $R^2 = 0$) only for dataset
 420 *year-prediction*, for which by chance R^2_{best} is low (0.338), so $\Delta = 0.338$ for
 421 this dataset and the green curve falls to zero at $\theta = 0.338$. If the R^2_{best} were
 422 higher, the green line would continue to the right without falling to zero,
 423 similarly to blue and black lines. The right panel of Figure 3 shows the
 424 boxplots of the differences $R^2_{best} - R^2$ for the first 10 models in the global
 425 ranking. The blue boxes report the 25% and 75% quantiles, while the red
 426 line inside the box is the median, and the blue points outside the box are the
 427 outliers. Although **cubist**, **gbm**, **bstTree**, **extraTrees** and **rf** exhibit low
 428 medians, all the models have several outliers (caused by datasets where they

fail) with high Δ values, excepting M5, the only one which guarantees low Δ values (below 0.322) for all the datasets.




Figure 4: Left panel: R^2_{gbm} (blue), R^2_{M5} (red) and R^2_{best} (green) for each dataset, sorted by decreasing values of R^2_{gbm} values. Right panel: histogram of the difference $R^2_{M5} - R^2_{gbm}$.

Figure 4 (left panel) plots R^2_{best} and the R^2 achieved by M5 and gbm. M5 is near R^2_{best} more often than gbm, and in several cases gbm is clearly below M5, but the former rarely outperforms the latter, and in these cases with lower difference. The right panel shows the histogram of the difference $R^2_{M5} - R^2_{gbm}$: its values are positive (i.e., M5 outperforms gbm) for 52.4% of the datasets, and when they are positive, they are higher (in absolute value) than when they are negative, so the sum of positive Δ values (2.3) outperforms the sum of negative values (-1.3). This shows that overall M5 outperforms gbm, although the latter is higher in the global ranking (Table 13). Remember that cubist, gbm and bstTree fail for some datasets, while M5 never fails.

In the left panel of Figure 4 above, the maximum difference $R^2_{best} - R^2_{M5}$ is 0.322 in dataset *student-mat*, whose output is discrete with more than 10 values (see the left panel of Figure 5), so the dataset was not excluded. The low $R^2_{best} = 0.3673$ for this dataset means that no model, and not only M5,




Figure 5: Left panel: true against predicted output for M5 (blue points) and the best regression model (**penalized**) for dataset *student-mat*. Right panel: difference $R^2_{best} - R^2_{M5}$ against R^2_{best} for all the datasets.

445 fits accurately the true output, and both blue and green points fit equally
 446 bad the red line. The right panel of the same figure plots the difference
 447 $R^2_{best} - R^2_{M5}$ against R^2_{best} . This difference is low for all the datasets (note
 448 that the vertical scale is 0–0.4), being below 0.2 (resp. 0.1) for 92.8% (resp.
 449 60.2%) of the datasets.




Figure 6: Left: values of R^2_{lm} , R^2_{rlm} and R^2_{best} , sorted by decreasing R^2_{lm} . Right: R^2_{M5} and R^2_{best} against $1 - R^2_{lm}$.

450 The left panel of Figure 6 compares R^2_{lm} , R^2_{rlm} and R^2_{best} in all datasets.

451 Since both models only differ in the robustness against outliers, the dif-
 452 ference between them identifies those datasets with outliers. This difference
 453 overcomes 0.05 only in 6 datasets and its highest value is 0.31, so that dataset
 454 outliers are few and not very relevant. In order to study the behavior of M5
 455 with the dataset complexity, the right panel shows R_{best}^2 and R_{M5}^2 against
 456 $1 - R_{lm}^2$, which measures the difficulty of the regression problem. The differ-
 457 ence $R_{best}^2 - R_{M5}^2$, instead of raising with $1 - R_{lm}^2$, achieves the highest values
 458 for $0.65 < 1 - R_{lm}^2 < 0.9$. However, in the most difficult datasets, where
 459 $1 - R_{lm}^2 > 0.9$, the R_{M5}^2 follows very well R_{best}^2 , so M5 performs well even for
 460 hard datasets.




Figure 7: Left: values of R^2 achieved by **dlkeras**, **M5** and **cubist** (datasets sorted by decreasing R^2_{max}). Right: boxplots of R_{best}^2 and R^2 achieved by **cubist**, **M5** and **dlkeras** over all the datasets.

461 Figure 7 (left panel) compares **dlkeras** to **M5** and **cubist** over all the
 462 datasets (points with $R^2 = 0$ correspond to datasets where **cubist** or **dlkeras**
 463 fail). The **cubist** model (green line) achieves almost always the highest per-
 464 formance (in 61 of 83 datasets), while **M5** overcomes **cubist** and **dlkeras**
 465 in 18 datasets, and **dlkeras** only in 4 datasets. In fact, **cubist** outper-

466 forms `dlkeras` in 71 datasets, while `dlkeras` outperforms `cubist` only in 8
 467 datasets. The difference between `dlkeras` and `M5` is lower (44 and 39 datasets
 468 favouring `M5` and `dlkeras`, respectively. The right panel of Figure 7 shows
 469 the boxplots of R_{best}^2 and R^2 of `cubist`, `M5` and `dlkeras`: this last box is
 470 clearly below `cubist` and `M5`, but its median is similar to `M5` and lower than
 471 `cubist`. The upper box ends of `cubist` and `M5` are near to R_{best}^2 , and the
 472 median of `cubist` is also very near to R_{best}^2 , but the lower box ends of `cubist`
 473 and `dlkeras` are much below R_{best}^2 and `M5` due to errors. Analyzing the pa-
 474 rameter tuning of `dlkeras`, the largest available size ($75^3 = 421,875$ neurons
 475 in three hidden layers) was selected only in 17 of 83 datasets. Therefore,
 476 in the remaining 66 datasets R^2 did not increase with larger networks, so
 477 they are not expected to provide better performances. However, they would
 478 spend higher computation times, overcoming the maximum allowed time (48
 479 h.) more frequently, so `dlkeras` would achieve more errors than `cubist`
 480 and `M5`, which never fails.

Small-difficult		Small-easy		Large-difficult		Large-easy	
Family-model	Pos.	Family-model	Pos.	Family-model	Pos.	Family-model	Pos.
PLM-penalized	1	RGR-cubist	1	RGR-M5	1	RGR-M5	1
RF-extraTrees	2	NET-avNNet	2	BST-gbm	3	BST-gbm	3
NET-kelm	4	BST-bstTree	3	NN-kknn	5	BAG-bag	4
BST-bstTree	6	BAG-bagEarth	5	DL-dlkeras	8	NET-pcaNNet	7
SVR-svr	8	PRJ-ppr	6	SVR-svr	9	LR-lm	9
SGP-gprRad	10	BYM-bMachine	7	NET-pcaNNet	10	AM-earth	10
		RF-extraTrees	8				
		AM-earth	9				

Table 16: Best model of each family within the 10 best positions in the R^2 Friedman ranking for each dataset group.


3.3. Discussion by family of regression model

It is interesting to analyze the behavior of the best model of each family. Table 16 reports the families with models in the top-10 of the R^2 ranking for each dataset group. The boosting family (BST, with models `bstTree` and `gbm`) and neural networks (NET, models `ke1m`, `avNNet` and `pcaNNet`) families, are present in all the groups, while regression rules (RGR), with models `cubist` and `M5`, achieves the first position in three of four groups (small-easy, large-difficult, large-easy), and penalized linear regression (PLM) achieves the first position (`penalized`) in small-difficult datasets. Bagging (BAG, with models `bag` and `bagEarth`) and support vector regression (SVR, `svr`) are present in two groups, while RF (`extraTrees`), projection methods (PRJ, `ppr`), Gaussian processes (SGP, `gprRad`), nearest neighbors (NN, `kknn`), deep learning (DL, `dlkeras`) and linear regression (LR, `lm` and `rlm`) are only present in just one group.


Family	Best	Pos.	Family	Best	Pos.
Regression rules	cubist	1	Nearest neighbors	kknn	16
Boosting	gbm	2	Penalized linear models	penalized	17
Neural networks	avNNet	5	Deep learning	dlkeras	18
Random forests	extraTrees	6	Ridge	foba	27
Bayesian models	bMachine	10	Lasso	lars	28
Bagging	bagEarth	11	Linear regresion	lm	33
Support vector regression	svr	12	Regression trees	ctree2	37
Projection methods	ppr	13	Gaussian processes	gprPol	50
Generalized additive models	earth	14	Quantile regression	rqlasso	56

Table 17: Best regression model of each family and position in the global ranking.


Considering the global ranking, Table 17 reports the families, sorted by the position of their best models in Table 13. Only regression rules, boosting and neural networks are in the top-5, followed by random forests and




(a) Small-difficult (SD).



(b) Small-easy (SE).



(c) Large-difficult (LD).



(d) Large-easy (LE).

Figure 8: Best R^2 (in green), R^2 achieved by the model with the best R^2 Friedman rank (in blue), and R^2 achieved by 1m (in red) for each group.

Bayesian models with positions below 10. Most of the remaining families have best models which outperform 1m (position 33), while regression trees, Gaussian processes and quantile regression achieve positions even higher.

3.4. Best result for each dataset

The green line of Figure 4 above shows R^2_{best} for the 83 datasets. For 41 of them (which represents 49.39%) the $R^2_{best} > 0.8$, so that at least one model was able to predict the output with an acceptable accuracy (alternatively,

505 these datasets might be considered as “easy” to learn). Besides, for other
 506 20 datasets (24.09% of the total) the R_{best}^2 is between 0.6 and 0.8, which
 507 is still an acceptable accuracy (datasets with middle difficulty). However,
 508 R_{best}^2 is between 0.2 and 0.6 for 13 datasets, which represents 15.66% (hard
 509 datasets), while $R_{best}^2 < 0.2$ for 9 datasets (10.84%), where the models could
 510 not learn the regression problem at all. Some datasets are really hard, e.g.
 511 *stock-abs*, where $R_{best}^2 = 0.059$. Figure 8 plots the best R^2 , alongside with
 512 R^2 achieved by the best model and by **1m** for each dataset group. In group
 513 SD (Figure 8a), the best model (**penalized**) is near to the best R^2 except
 514 for datasets *airfoil*, *gps-trajectory*, *slump-flow* and *slump*. Since this group
 515 includes small-difficult datasets, the R^2 of **1m** is always below 0.6, but for the
 516 first five datasets some model achieves higher R^2 values. The **penalized** is
 517 also better than **1m** for all datasets, although the difference is low for datasets
 518 after *geo-music-long*. For group small-easy (SE, Figure 8b), the R^2 values of
 519 **1m** are higher, but the best model (**cubist**) is always very near to the best
 520 R^2 with some difference with respect to **1m**. In the large-difficult group (LD,
 521 Figure 8c), the **1m** values are very low and the best model (**M5**) is far from
 522 **1m**, following the best R^2 very closely for 12 of 33 datasets with a margin
 523 of 0.2-0.4 for the remaining 21 datasets. Finally, in group LE (large-easy
 524 datasets, Figure 8d) the **1m** is already near the best R^2 , although the best
 525 model (**M5** again) always achieves the best R^2 .

526 3.5. Discussion by elapsed times and memory consumption

527 We studied the memory and time required by each regression model over
 528 all the datasets. Table 18 reports the information of the 20 best models ac-
 529 cording to the R^2 Friedman rank in each column: %Best reports the percent-

age of datasets where they achieve the best R^2 ; %Error reports the percentage
of datasets where they failed; %ME reports the percentage of memory errors
caused by overcoming the largest allowed memory (128 GB); Datasets/mem
reports the number of datasets run on the memory queues with $\{2^i\}_{i=1}^6$ GB.

						#Datasets/mem(GB)		
Pos.	Model	Rank	%Best	%Error	%ME	2-4-8-16-32-64-128	%TE	Time
1	cubist	13.92	15.7	8.4		68-6-8-1-0-0-0	8.4	2.47
2	gbm	15.42	2.4	1.2		78-3-2-0-0-0-0	1.2	1.46
3	bstTree	15.84	6.0	6.0		74-5-3-1-0-0-0	6.0	3.84
4	M5	18.20	2.4			0-36-29-18-0-0-0		1.32
5	avNNet	19.23	3.6	14.5		77-3-2-0-0-1-0	14.5	3.20
6	extraTrees	19.61	33.7	19.3		72-9-2-0-0-0-0	20.5	3.62
7	qrf	22.41	2.4	14.5		62-12-4-1-3-1-0	14.5	3.99
8	pcaNNet	23.49				77-3-3-0-0-0-0		1.36
9	rf	23.82	3.6	24.1		69-6-2-0-5-1-0	24.1	3.05
10	bMachine	23.83	3.6	15.7		54-27-2-0-0-0-0	16.8	12.10
11	bagEarth	24.14	2.4	7.2		76-1-4-1-1-0-0	7.2	2.21
12	svr	24.17		27.7		78-5-0-0-0-0-0	27.7	172800
13	ppr	24.57	1.2	4.8		78-3-2-0-0-0-0	4.8	1.24
14	earth	25.52				77-4-2-0-0-0-0		1.46
15	blackboost	25.69				75-1-3-0-3-0-1		1.48
16	kknn	26.24	1.2	6.0		80-2-1-0-0-0-0	6.0	2.41
17	penalized	27.70	8.4	12.0		77-4-2-0-0-0-0	12.0	1.54
18	dlkeras	28.07	3.6	7.2		83-0-0-0-0-0-0	7.2	6.17
19	svmRad	29.14		28.9		77-2-3-0-0-1-0	28.9	172800
20	grnn	29.61		9.6	6.0	47-13-6-5-5-1-1	3.6	0.22
28	lars	33.16				79-2-2-0-0-0-0		0.03
77	qrnn	77.00		100.0		77-4-2-0-0-0-0	100.0	172800
63	rndGLM	51.80		51.8	44.6	0-0-0-12-22-10-2	7.2	2.54

Table 18: List of the 20 first regression models sorted by increasing R^2 Friedman rank, with the percentage of datasets where each model achieves the best R^2 (column %Best), percentage datasets with of errors (column %Error), percentage of memory errors (column %ME), number of datasets for each memory size (column #Datasets/mem), percentage of time errors (%TE) and training+test time (in sec.) spent for dataset *compress-stren* (column Time). Empty cells correspond to zero values.

In order to measure the time required by each model, the time spent in
hyper-parameter tuning is discarded to avoid biasing caused by differences

among models in the number of hyper-parameters and hyper-parameter values. The column `%TE` reports the percentage of time errors, i.e., datasets where the model overcomes the maximum allowed time (48 h.). Although it may surprise that some models are not able to finish within 48 h., we must consider the size of some datasets (more than 2 millions of patterns, up to 640 inputs) and the high number of trials (500) for some datasets. Generally, high values in the `%TE` column happen with slow models, specially for large datasets. Since some models fail but do not overcome the allowed memory nor time, the sum of columns `%ME` and `%TE` is not always equal to column `%Error`, e.g. `nnls` has no memory nor time errors, but `%Error` is 4.8%. The column `Time` reports the time (in sec.) spent by the model for a training+testing trial on dataset *compress-stren*, whose size might be considered “standard”: 1,030 patterns and 8 inputs. The time is set to the maximum allowed time for models with errors in this dataset.

Comparing `cubist`, `gbm`, `bstTree` and `M5` in terms of column `%Best`, `cubist` achieves often the best R^2 (15.7% of datasets) followed by `bstTree` (6%) while `gbm` and `M5` tie (2.4%). `Cubist` and `bstTree` fail in 8.4% and 6% of datasets, respectively, while `gbm` fails less (the three overcome the allowed time) and `M5` never fails. None of them overcomes the memory limits, but `M5` requires more memory (4-16 GB), while the others require 2-8 GB. Finally, `M5` and `gbm` are faster (1.32 and 1.46 s./trial, respectively), while `bstTree` and `cubist` spend about 2-4 s. The `avNNet` and `extraTrees` spend about 3-4 s. but the former requires less memory (2 GB for 77 of 83 datasets)⁹. Among

⁹Both `extraTrees` and `bartMachine` use Java and by technical reasons their memory was limited to 8 GB.

559 the remaining models, **pcaNNet** never fails, is very fast (1.36 s.) and requires
 560 few memory (2 GB for 77 datasets), while **bMachine** is slower (12.1 s.) and
 561 requires more memory (4 GB for 27 datasets). The **rf** is faster (3.05 s.) with
 562 memory very variable with the dataset size (69 datasets with 2 GB but 1
 563 with 64 GB). On the other hand, **svr** and **svmRad** are very slow with time
 564 errors in 28.9% of datasets, while **grnn**, **ppr**, **earth** and **blackboost** are fast
 565 (between 0.22 to 1.48 s.). However, **grnn** has time errors in 3.6% of datasets,
 566 requiring memory from 2 to 64 GB depending on the dataset with memory
 567 errors in 6% of datasets. Most models in positions 10–20 require few memory,
 568 and **dlkeras** requires the lowest memory (2 GB for all datasets), similar to
 569 **kknn**, although with time errors in 7.2% and 6% of datasets. To have time
 570 and memory references, the last three lines report the fastest and slowest
 571 models (**lars** and **qrnn**, respectively) in the *compress-stren* dataset, and the
 572 model which requires the largest memory (**rndGLM**). Considering times, **lars**
 573 spends 0.03 s. being 26 times faster than **M5** (the fastest model in the top-5),
 574 while **qrnn** is shutdown after 48 h. in all the datasets, being 130,910 times
 575 slower than **M5**. With respect to memory, **gbm** and **bstTree** require only
 576 slightly more memory than **dlkeras** (2 GB for more than 74 datasets), while
 577 **rndGLM** always requires more than 16 GB with memory errors in 45.8% of
 578 the datasets.

579 Figure 9 (left panel) plots, in logarithmic scale, the times spent for each
 580 dataset by **cubist** and **M5**, alongside with **lars** and **bstSm**, which are fastest
 581 and slowest models, respectively, for comparative purposes (**qrnn** is even
 582 slower than **bstSm**, but the former overcomes the allowed time in all the
 583 datasets so it is replaced by **bstSm**). The times are plotted against the




Figure 9: Left: times (in sec.) per trial spent by the best-performing (`cubist` and `M5`) and by the fastest and slowest regression models (`lars` and `bstSm`, respectively). Right: memory (in GB) required by `cubist` and `M5`, and by the models with least and most memory requirements (`dlkeras` and `rndGLM`, respectively). Both plotted against the product `#patterns·#inputs`.

584 product `#patterns·#inputs` of the dataset, which measures its size. `Lars`
 585 is one order of magnitude below `M5` and `cubist`, which are similar for small
 586 datasets, but the difference grows with the dataset size. In largest datasets,
 587 `cubist` is almost two orders of magnitude slower than `M5`, overcoming the
 588 allowed time (48 h. or 172,800 s. $\sim 2 \cdot 10^5$ s.). Finally, `bstSm` is 2-3 orders
 589 slower than `lars` for small datasets, but it already overcomes the time limit
 590 for some small, most medium and all large datasets (overall, for the 78.5%
 591 of datasets). Other slow models are `xgbTree` and `xgbLinear`, `nodeHarvest`,
 592 `krlsRad` and `SBC`, with average times between 20,000 and 300,000 s. and
 593 time errors for 50-85% of datasets.

594 Considering memory, the right panel of Figure 9 plots `cubist` and `M5`,
 595 with `dlkeras` and `rndGLM`, which exhibit the lowest and highest memory re-
 596 quirements, against the product `#patterns·#inputs`. The `dlkeras` spends 2
 597 GB for all the datasets, while `cubist` uses 2 GB excepting some medium and

the 9 largest datasets. However, **M5** requires more memory: 4, 8 and 16 GB for 36, 29 and 18 datasets, respectively. Comparatively, **rndGLM** requires 16, 32, 64 and 128 GB in 12, 22, 10 and 1 datasets, respectively, overcoming 128 GB in 39 datasets (45.8%). Other models with high memory requirements are **gprLin**, **gprPol** and **gprRad**, **rvmRad**, **krlsRad**, **wkpls**, **kelm** and **grnn**, with memory errors in 6-10% of datasets.




Figure 10: Friedman rank of the time (vertical axis) against the Friedman rank of R^2 (horizontal axis) for the 20 best models in Table 18.

Figure 10 plots the Friedman ranks of R^2 and time (horizontal and vertical axis, respectively) for the best 20 models. **Cubist** and **pcaNNet** achieve the lowest R^2 and time ranks, respectively, but the best trade-off between R^2 and time is achieved by **gbM** and **M5**. In fact, **cubist** is only slightly better than **gbM** according R^2 , but it is much slower. Other models with good R^2 are **bstTree** (R^2 similar to **gbM**, but much slower), **avNNet** and **extraTrees**, but they are also slow. The following models according R^2 rank are **rf**, **qrf**, **bMachine** and **bagEarth**, whose R^2 rank is comparable to **pcaNNet** but they

612 are much slower. According to time, the models after `pcaNNet` are `grnn` and
613 `earth`, almost so fast as `gbm` but with much lower R^2 .

614 4. Conclusion

615 The current work develops an exhaustive comparison of 77 regression
616 methods, 73 implemented in R and other 4 in C++, Matlab and Python,
617 over the whole collection of 83 regression datasets of the UCI machine learn-
618 ing repository, including large datasets up to 2 millions of patterns and 640
619 inputs. The collection of regression models, that belong to 19 different fami-
620 lies, aims to be a representative sample of the most popular and well-known
621 methods currently available for regression tasks. The results have been evalu-
622 ated in terms of R^2 , RMSE and MAE, being similar with the three measure-
623 ments, and depending on the dataset properties (size and difficulty, mea-
624 sured by the performance achieved by the classical linear regression). For
625 small-difficult datasets, the `penalized` linear regression achieves the best re-
626 sults, followed by random forest (`rf`) and extremely randomized regression
627 trees (`extraTrees`). For small-easy datasets, the M5 rule-based model with
628 corrections based on nearest neighbors (`cubist`) achieves the best results,
629 followed by the committee of back-propagation neural networks (`avNNet`)
630 and the boosting ensemble of regression trees (`bstTree`). Finally, for both
631 large-difficult and large-easy datasets the M5 regression tree is the best, fol-
632 lowed the gradient boosted machine (`gbm`) and `cubist`. Considering globally
633 all the datasets, `cubist`, `gbm`, `bstTree` and M5 achieve the best positions,
634 and the differences between them are related mainly with: 1) the number of
635 cases where they overcome the memory and time limits (128 GB and 48 h.,

636 respectively): **cubist** and **bstTree** fail in 8% and 6% of datasets, respec-
 637 tively, **gbm** only for 1% and **M5** never fails; and 2) the speed (**gbm**, **M5** and
 638 **bstTree** are 70, 30 and 10 times faster than **cubist**). In terms of R^2 , **gbm**
 639 and **M5** never decrease more than 0.35 below the best R^2 for any dataset, and
 640 $R_{best}^2 - R_{M5}^2 > 0.25$ only in 2.4% of datasets. Other models with good results
 641 are extremely randomized regression trees (**extraTrees**), which achieves the
 642 best R^2 in 33.7% of datasets, support vector regression (**svr**) and random for-
 643 est (**rf**), but they are very slow, overcoming the maximum allowed time (48
 644 h.) for more than 20% of the datasets. A post-hoc Friedman-Nemenyi test
 645 comparing **cubist** and the remaining models gives $p < 0.05$ (i.e., difference
 646 statistically significant) excepting **gbm**, **bstTree** and **extraTrees**.

647 According to the position of their best regression models in the R^2 rank-
 648 ing, the best families are regression rules (whose best models are **cubist**
 649 and **M5**), boosting ensembles (**gbm** and **bstTree**), neural networks (**avNNet**),
 650 random forests (**extraTrees** and **rf**), projection methods (projection pur-
 651 suit, **ppr**) and support vector regression (**svr**). Other families with models
 652 included in the top-20 are bagging ensembles (bagging ensemble of MARS
 653 models, **bagEarth**), generalized additive models (MARS, **earth**), nearest
 654 neighbors (**kknn**), generalized linear models (**penalized**) and deep learning
 655 (**dlkeras**). The remaining families exhibit poorer performances: ridge and
 656 LASSO, Bayesian models, linear regression, regression trees, Gaussian pro-
 657 cesses and quantile regression. The R_{best}^2 overcomes 0.5625, considered the
 658 threshold for very good to excellent R^2 according the Colton scale [79], for
 659 76.2% of the datasets. Considering the elapsed time, the fastest model is
 660 least angle regression (**lars**), while **M5** and **cubist** are 30 and 2,000 times

661 slower, respectively. With respect to memory, the non-negative least squares
662 regression (`nnls`) never requires more than 2 GB, while `cubist` and `M5` re-
663 quire in average about 3 and 8 GB, respectively, and the boosting ensemble
664 of generalized linear models (`rndGLM`) requires about 78 GB, overcoming 128
665 GB in about half datasets. The future work includes to study the relations
666 between the regression problem and the best models in order to predict the
667 best model and its performance for a given dataset.

668 **Acknowledgment**

669 This work has received financial support from the Erasmus Mundus Eu-
670 phrates programme [project number 2013-2540/001-001-EMA2], from the
671 Xunta de Galicia (Centro singular de investigación de Galicia, accreditation
672 2016-2019) and the European Union (European Regional Development Fund
673 - ERDF), Project MTM2016-76969-P (Spanish State Research Agency, AEI)
674 co-funded by the European Regional Development Fund (ERDF) and IAP
675 network from Belgian Science Policy.

676 **Appendix A. Dataset discrepancies with the UCI repository**

677 There are some discrepancies in Table 2 with respect to the original doc-
678 umentation of the UCI ML repository. Specifically, the *beijing-pm25* dataset
679 has 41,757 patterns, despite its description in the UCI documentation spec-
680 ifies 43,824 because 2067 patterns whose output is missing, so it can not
681 be predicted, were removed. The *cuff-less* dataset has 73,200,000 patterns,
682 while its description specifies 12,000. Instead of discarding it, we used the
683 first 61,000 patterns. The *greenhouse-net* dataset has 2,921 files with 327

684 patterns per file, which gives 955,167 patterns instead of 2,921 in the dataset
685 description. The *household-consume* dataset has 2,049,280 patterns instead
686 of 2,075,259 as listed in the UCI documentation, because 25,979 original pat-
687 terns have missing values (labeled as ‘?’) for all the inputs and the output.
688 The *online-news* dataset has 39,644 patterns instead of 39,797 as listed in
689 the UCI documentacion. For the *UJIIndoorLoc* datasets, output `floor` was
690 discarded and did not give a separate regression dataset because it has only
691 three different values.

692 **Appendix B. Listing of regression methods**

693 This appendix describes the regression model used in the current work,
694 grouped by families, alongside with their software implementations and val-
695 ues of their tunable hyper-parameters. Default values are assumed for all the
696 model parameters not cited explicitly.

697 **1. *Linear regression (LR)***

698 1. **lm** is the linear regression model implemented by the **stats** package
699 [11]. Collinear inputs exhibit undefined coefficients in the linear regres-
700 sion model returned by `lm`, being discarded by it and by other models
701 in the list, as we told above.

702 2. **rlm** implements the robust linear model (**MASS** package), fitted using
703 iteratively re-weighted least squares with maximum likelihood type es-
704 timation, which is robust to outliers in the output although not in
705 inputs [13]. The only hyperparameter is the Ψ function, which can be
706 **huber** (Huber function, which leads to a convex optimization problem),

707 `hampel` and Tukey `bisquare`, both with local minima. In our experi-
708 ments, these functions are selected as the best Ψ for 16%, 82% and 2%,
709 respectively, of the datasets.

710 **II. *Penalized linear regression (PLM)***

711 3. **penalized** is the penalized linear regression (`penalized` package), which
712 fits generalized linear models with a combination of L1 and L2 penal-
713 ties. The L1 penalty, also named LASSO, penalizes the sum of absolute
714 values of the coefficients, thus reducing the coefficients of inputs which
715 are not relevant, similarly to input selection. The L2 penalty (also
716 named ridge) penalizes the sum of squared coefficients, reducing the
717 effects of input collinearity. The regression is regularized by weighting
718 both penalties [15], whose weights are given by hyperparameters λ_1 ,
719 tuned with values 1, 2, 4, 8 and 16, and λ_2 , with values 1, 2, 4 and 8.
720 In our experiments, $\lambda_1 = \lambda_2 = 1$ in the 87.9% of the datasets, and only
721 in 10 of 83 datasets $\lambda_1 \neq 1$ or $\lambda_2 \neq 1$.

722 4. **enet** is the elastic-net regression model (`elasticnet` package), com-
723 puted using the least angle regression - elasticnet (LARS-EN) algorithm
724 [12]. Elastic-net provides a model for regularization and input selec-
725 tion, grouping together the inputs which are strongly correlated. This
726 model is specially useful when the number of inputs is higher than
727 the number of patterns, as opposed to LASSO models. There are two
728 hyperparameters (5 values each one): the quadratic penalty, or regular-
729 ization, hyperparameter (λ , with values $0, \{10^{-i}\}_1^3$) and the fraction **s**
730 of the L1 norm of the coefficient vector relative to the norm at the full
731 least squares solution (the **fraction** mode is used in the `predict.enet`

function, with values 0.05, 0.28, 0.52, 0.76, 1).

5. **glmnet** is the LASSO and elastic-net regularization for generalized linear models (GLM) implemented in the **glmnet** package [17]. The **glmnet** model uses penalized maximum likelihood to fit a GLM for the LASSO and elastic-net non-convex penalties. The mixing percentage α is tuned with 5 values from 0.1 to 1: the value $\alpha=1$ (resp. < 1) corresponds to the LASSO (resp. elastic-net) penalty. The selected value for α during hyperparameter tuning was 0.1 in 41.7% of the datasets. The regularization hyperparameter λ is also tuned with values 0.00092, 0.0092 and 0.092.

6. **glmSAIC** is the generalized linear model with stepwise feature selection [19] using the Akaike information criterion and the **stepAIC** function in the **MASS** package (model **glmStepAIC** in the **caret** model list).

746 **III. Additive models (AM)**

7. **gam** is the generalized additive model (GAM) using splines (**mgcv** package). This model [21] is a GLM whose linear predictor is a sum of smooth functions (penalized regression splines) of the covariates. The estimation of the spline parameters uses the generalized cross validation criterion. The only hyperparameter is **select**, a boolean flag that adds an extra penalty term to each function penalizing its wiggleness (waving).

8. **earth** is the multivariate adaptive regression spline (MARS) in the **earth** package. This method [23] is a hybrid of GAM and regression trees (see family XII) which uses a expansion of product spline func-

tions to model non-linear data and interactions among inputs. The spline number and parameters are automatically determined from the data using recursive partitioning, and distinguishing between additive contributions of each input and interactions among them. The functions are added iteratively to reduce maximally the residual, until its change is too small or a number of iterations is reached. The maximum number of terms in the model (`nprune`) is tuned with 15 values (less for some datasets) between 2 and 24.

IV. *Least squares (LS)*

9. **nnls** is the non-negative least squares regression (`nnls` package), which uses the Lawson-Hanson NNLS method [25] to solve for $\mathbf{x}$ the optimization problem $\min_{\mathbf{x}} \|\mathbf{Ax} - \mathbf{b}\|$ subject to $\mathbf{x} \geq 0$, where $\mathbf{A}$ is the input data matrix, $\mathbf{b}$ is the true output and $\mathbf{x}$ is the linear predictor.
10. **krlsRad** is the radial basis function kernel regularized least squares regression (KRLS package), which uses Gaussian radial basis functions to learn the best fitting function which minimizes the squared loss of a Tikhonov regularization problem [27]. The KRLS method, which corresponds to the `krlsRadial` in the `caret` model list, learns a closed form function which is so interpretable as ordinary regression models. The only hyperparameter is the kernel spread (σ), with 10 values in the set $\{10^i\}_{-7}^2$. By default, this method determines the trade-off between model fit and complexity, which is defined by the λ parameter, by minimizing the sum of squared leave-one-out errors. The `getModelInfo` function only lists one value for λ , despite being listed as a tunable hyperparameter in the `caret` model list.

782 **V. *Projection methods (PRJ)***

- 783 11. **spls** is the sparse partial least squares regression (**spls** package). This
784 method [29] uses sparse linear combinations of the inputs in the dimen-
785 sionality reduction of PLS in order to avoid lack of consistency of PLS
786 with high dimensional patterns. The hyperparameters are the number
787 of latent components (**K**), with values 1, 2 and 3, and the threshold (η),
788 with 7 values from 0.1 to 0.9.
- 789 12. **simpls** fits a PLS regression model with the **simpls** method [30], imple-
790 mented by the **pls** function in the **pls** package, with **method=simpls**.
791 The PLS method projects the inputs and the output to a new space and
792 it searches the direction in the input space which explains the maxi-
793 mum output variance. **Simpls** is particularly useful when there are
794 more inputs than patterns and inputs are collinear. It directly calcu-
795 lates the PLS factors as linear combinations of the inputs maximizing a
796 covariance criterion with orthogonality and normalization constraints.
797 The only hyperparameter is the number of components (**ncomp**) used
798 by the **simpls** model, with values from 1 to **min(10,#inputs-1)**.
- 799 13. **kpls** is the PLS regression with **method=kernelpls** [31] in the same
800 function and package as **simpls**, using the same hyperparameter setting
801 as **simpls** with 6 values. This is the model named **kernelpls** in the
802 **caret** model list.
- 803 14. **wkpls** uses **method=widekernelpls** [33] for PLS, tuning the number of
804 components (**ncomp**) as **simpls** also with 10 values (model **widekernelpls**
805 in the **caret** model list).
- 806 15. **enpls.fs** is an ensemble of sparse partial least squares (**spls**, see model

807 #12) regression models implemented by the `enpls` package [35]. The
808 `getModelInfo` function lists only one value for the number of com-
809 ponents (`maxcomp`), while the `threshold` argument, specified as a hy-
810 perparameter by the `caret` model list, is missing in the `enpls.fit`
811 function.

812 16. **plsRglm** is the partial least squares generalized linear model (`plsRglm`
813 package) with `modele=pls-glm-gaussian` [37]. The hyperparameters
814 are the number of extracted components (`nt`), tuned with values 1, 2,
815 3 and 4, and the input significance level (`alpha.pvals.expli`), with
816 values in the set $\{10^i\}_{-2}^2$.

817 17. **ppr** performs the projection pursuit regression (`stats` package), which
818 models the output as a sum of averaging functions (mean, median,
819 etc.) of linear combinations of the inputs [39]. The coefficients are
820 iteratively calculated to minimize a projection pursuit (fitting criterion,
821 given by the fraction of unexplained variance which is explained by each
822 function) until it falls below a predefined threshold. The only tunable
823 hyperparameter is the number of terms of the final model (`nterms`),
824 with values from 1 to 10.

825 18. **pcr** develops principal component regression (`pls` package), which mod-
826 els the output using classical linear regression with coefficients esti-
827 mated with principal component analysis (PCA), i.e., using the prin-
828 cipal components as inputs [41]. It works in three stages: 1) performs
829 PCA and selects a subset of the principal components; 2) uses ordinary
830 least squares to model the output vector using linear regression on the
831 selected components; 3) uses the eigenvectors corresponding to the se-

832 lected components in order to calculate the final `pcr` estimator trans-
 833 forming the modeled output vector to the original space, and estimates
 834 the regression coefficients for the original outputs. The number of com-
 835 ponents (`ncomp`) is tuned with values from 1 to `min(10,#inputs-1)`.
 836 19. **icr** is the independent component regression (`caret` package). The
 837 **icr** fits a linear regression model using independent component analy-
 838 sis (ICA), implemented by the **fastICA** package, instead of the original
 839 inputs [43]. The input data are considered a linear combination of a
 840 number of independent and non-Gaussian components (sources), so the
 841 training set matrix is written as the product of the source matrix and a
 842 linear mixed matrix, which contains the coefficients of the linear com-
 843 bination. The ICA estimates a “separating” matrix, which multiplied
 844 by the original data, provides the sources. This matrix must maxi-
 845 mize the non-gaussianity of the sources, measured by the neg-entropy.
 846 The only hyperparameter is the number of independent components
 847 `n.comp`, with values from 1 to `min(10,#inputs-1)`.
 848 20. **superpc** is the supervised PCA (**superpc** package). This method [45]
 849 retains only a subset of the principal components which are correlated
 850 to the output. The tunable hyperparameters are the number of princi-
 851 pal components (`n.components`), tuned with values 1, 2 and 3 (in all
 852 the datasets the value 1 is selected), and the **threshold** for retaining
 853 the input scores, with values 0.1 and 0.9.

854 **VI. *Least absolute shrinkage and selection operator (LASSO)***¹⁰

¹⁰Due to the high number of models, LASSO models are included in a specific family and not in the penalized linear regression family.

- 855 21. **lasso** performs LASSO regression, using the **enet** function in the **elas-**
856 **ticnet** package with $\lambda = 0$ to obtain the LASSO solution.
- 857 22. **relaxo** develops relaxed LASSO (**relaxo** package), which generalizes
858 the LASSO shrinkage method for linear regression [14]. This method
859 is designed to overcome the trade-off between speed and convergence
860 in the L2-loss function of the regular LASSO, specially for sparse high-
861 dimensional patterns. It provides solutions sparser than LASSO with
862 better prediction error. The relaxation hyperparameter (ϕ) is tuned
863 with 7 values from 0.1 to 0.9, while the penalty hyperparameter (λ) is
864 tuned with 3 data-dependent values.
- 865 23. **lars** is the least angle regression (**lars** package), a model selection
866 method [16] which is less greedy than the typical forward selection
867 methods. It starts with zero coefficients for all the inputs and finds
868 the input i most correlated with the output, increasing step-by-step its
869 coefficient until another input j has high correlation with the current
870 residual (i.e., the error, or difference between the true and predicted
871 outputs). The coefficients of inputs i and j are increased in the equi-
872 angular direction between inputs i and j until some other input k is so
873 correlated with the residual as input j . Then, it proceeds in the equi-
874 angular direction among i , j and k , which is the “least angle direction”,
875 and so on until all the coefficients are non-zero (i.e., all the inputs are in
876 the model). The **lasso** and **fraction** options are specified for training
877 and prediction respectively, and the **fraction** hyperparameter (ratio
878 between the L1 norm of the coefficient vector and the norm at the full
879 LS solution) is tuned with 10 values between 0.05 and 1 (for 46.7% of

880 datasets the selected value of `fraction` was 1).

881 VII. *Ridge regression (RIDGE)*¹¹

882 24. **ridge** develops ridge regression (**elasticnet** package), which introduces
883 a regularization term, alongside with the squared difference between
884 the desired and true outputs, in the function to optimize. This term,
885 which evaluates the model complexity (e.g., the matrix norm for linear
886 models), is weighted by the penalty or regularization hyperparameter
887 (λ). We use the **enet** function in the **elasticnet** package, already used
888 for model **enet**, tuning λ with 5 values between 0.01 and 0.1 (these two
889 values are selected for 50% and 30% of the datasets, respectively).

890 25. **spikeslab** implements the spike and slab regression (**spikeslab** pack-
891 age), which computes weighted generalized ridge regression estimators
892 using Bayesian spike and slab models [18]. The **spikeslab** method
893 combines filtering for dimensionality reduction, model averaging using
894 Bayesian model averaging, and variable selection using the **gnet** estima-
895 tor. The only tunable hyperparameter is the number of selected inputs
896 (**vars**), with the two values listed by the **getModelInfo** function: 2
897 and the number of inputs (both selected with similar frequencies).

898 26. **foba** is the ridge regression with forward, backward and sparse input
899 selection [20], implemented in the **foba** package. We use the adap-
900 tive forward-backward greedy version of the method (with the default
901 value **foba** for the **type** argument of the **foba** function), which does a
902 backward step when the ridge penalized risk increases in less than the

¹¹Similarly to LASSO, ridge regression models are grouped in a separate family instead of the penalized linear regression family.

parameter ν (with value 0.5 by default) multiplied by the ridge penalized risk reduction in the previous forward step. The hyperparameters are regularization for ridge regression (λ), with 10 values between 10^{-5} and 0.1, and the number of selected inputs or sparsity (k) for the prediction, with two values: 2 and the number of inputs.

VIII. *Bayesian models (BYM)*

27. **bayesglm** is the Bayesian GLM, implemented by the **arm** package. It uses expectation maximization to update the β coefficients of the GLM at each iteration, using an augmented regression to represent the prior information [22]. The coefficients are calculated using a Student-t prior distribution.

28. **brnn** is the Bayesian regularized neural network (**brnn** package), a network with one hidden layer trained using Gauss-Newton optimization. The training minimizes a combination of squared error and a regularization term which uses the squared network weights [24]. The Bayesian regularization [80] determines the weights of both terms based on inference techniques. This requires an iterative computation of the Hessian matrix (or its Gauss-Newton approximation) of the performance with respect to the weights and biases until a goal is met or a maximum number of iterations is reached. The weights are not normalized, and the number of hidden neurons (**neurons**) is a hyperparameter tuned with values between 1 and 15, selecting **neurons**=1 in 31.6% of the datasets.

29. **bMachine** is the Bayesian additive regression tree (**bartMachine** package), which consists of a sum of regression trees and a regularization

process developed on the parameters of the tree set [26]. It corresponds to `bartMachine` in the `caret` model list. We use the default number of trees (`num_trees=50`, the unique value listed by the `getModelInfo` function), and the tunable hyperparameters are the prior boundary (`k`), with values 2, 3 and 4, and α (base value in tree prior to decide if a node is terminal or not), with 3 values between 0.9 and 0.99.

IX. *Space Gaussian processes (SGP, also known as kriging)*

30. `gprLin` implements Gaussian process regression (`gaussprLinear` in the `caret` model list), which interpolates values for the output using a sum of Gaussians, each specified by a mean and a covariance (or kernel) function that measures the similarity between inputs. This model uses linear (`vanilladot`) kernel in the `gausspr` function of the `kernlab` package.

31. `gprRad` (named `gaussprRadial` in the `caret` model list) uses the same function with Gaussian (`rbfdot`) kernel and automatically calculated kernel spread (default option `kpar=1`).

32. `gprPol` is the same method with polynomial (`polydot`) kernel (`gaussprPoly` in the `caret` model list), tuning the kernel hyperparameters `degree`, with values 1, 2 and 3, and `scale`, with values $\{10^{-i}\}_1^3$.

X. *Quantile regression (QTR)*

33. `rqlasso` develops quantile regression with LASSO penalty, using the `rq.lasso.fit` function in the `rqPen` package. The quantile regression models optimize the so-called quantile regression error, which uses the tilted absolute value instead of the root mean squared error. This tilted function applies asymmetric weights to positive/negative errors,

953 computing conditional quantiles of the predictive distribution. This
954 method fits a quantile regression model with the LASSO penalty [32],
955 tuning the regularization hyperparameter λ , with 10 values between 0.1
956 and 10^{-4} (for 76.7% of datasets the selected value was less than 0.01).

957 34. **rqnc** performs non-convex penalized quantile regression, with the **rq.**
958 **nc.fit** function in the **rqPen** package. This model performs penalized
959 quantile regression using local linear approximation [34] to maximize
960 the penalized likelihood for non-convex penalties. The two hyperpa-
961 rameters are λ , with the same values as **rqlasso**, and **penalty**, which
962 can be **MCP** (minimax concave penalty) or **SCAD** (smoothly clipped ab-
963 solute deviation).

964 35. **qrnn** is the quantile regression neural network (**qrnn** package), a neu-
965 ral network which uses ramp transfer and quantile regression error
966 functions [36]. The hyperparameters are number of hidden neurons
967 (**n.hidden**), with 7 values from 1 to 13, and the **penalty** for weight
968 decay regularization, with values 0, 0.1 and 0.0001.

969 **XI. *Nearest neighbors (NN)***

970 36. **kknn** performs weighted k-nearest neighbors regression [38], imple-
971 mented by the **kknn** package. The neighbors are weighted using a
972 kernel function according to their distances to the test pattern. The
973 only hyperparameter is the number of neighbors (**kmax**, with 10 odd
974 values between 5 and 23).

975 **XII. *Regression trees (RGT)***

976 37. **rpart** is the classical regression tree trained using the recursive parti-
977 tioning algorithm [40], implemented in the **rpart** package. Only the

978 complexity hyperparameter (`cp`) is tuned (10 values).

979 38. **nodeHarvest** is a simple interpretable tree-based ensemble for high-
980 dimensional regression with sparse results [42] implemented in the **node-**
981 **Harvest** package. A starting tree of few thousand nodes is randomly
982 generated. For a test pattern assigned to a node, the output is the
983 mean of its training outputs; when the test pattern is assigned to several
984 nodes, the output is the weighted average of their means. The selection
985 of the nodes and their weights requires to solve a quadratic program-
986 ming problem with linear inequality constraints. Only few nodes with
987 non-zero weights are selected, so the solution is sparse. The hyperpa-
988 rameters are the maximal interaction depth (`maxinter`, with 10 values
989 between 1 and 10, the most selected were 6-8) and the `mode` (2 values),
990 which can be `mean` (weighted group means) or `outbag` (zero values in
991 the smoothing matrix diagonal). This model is very slow, requiring
992 huge times (more than 6 days) for high `maxinter` values and some
993 datasets.

994 39. **ctree2** is the conditional inference tree (`party` package), which esti-
995 mates the output using inference after a recursive partitioning of the
996 input space [44]. The method tests the null hypothesis of statistical
997 independence between any input and the output, and it stops when
998 the hypothesis can not be rejected. Otherwise, it selects the input
999 most related to the output, measured by the p -value of the partial test
1000 of independence between the output and that input. Then, it does a
1001 binary splitting of the selected input, and the two previous steps are
1002 recursively repeated. The hyperparameters are the threshold for $1 - p$

1003 in order to do a split (`mincriterion`), with 4 linearly spaced values
1004 between 0.01 and 0.99, and the maximum tree depth (`maxdepth`), with
1005 integer values from 1 to 5, selecting `maxdepth=5` for 68.3% of datasets.

1006 40. **partDSA** develops partitioning using deletion, substitution, and ad-
1007 dition, implemented in the **partDSA** package [46]. This method re-
1008 cursively partitions the space considering that multiple inputs jointly
1009 influence the output, predicting a piecewise constant estimation though
1010 a parsimonious model of AND/OR conjunctions. The only hyperparam-
1011 eter is the maximum number of terminal partitions (`cut.off.grow`),
1012 tuned with integer values between 1 and 10, although the value 1 is
1013 selected for all the datasets. The parameter `vfold` is set to 1 in order
1014 to reduce the computational cost for large datasets.

1015 41. **evtree** is the tree model from genetic algorithms [47] which uses evo-
1016 lutionary algorithms to learn globally optimal regression trees (**evtree**
1017 package). It chooses splits for the recursive partitioning in the forward
1018 stepwise search in order to optimize a global cost function. The only
1019 hyperparameter is the complexity (α) of the cost function, tuned with
1020 10 linearly spaced values between 1 and 3, which weights negatively
1021 large tree sizes.

1022 **XIII. Regression rules (RGR)**

1023 42. **M5** is the model tree/rules [48] implemented in the **RWeka** package,
1024 tuning the flags `pruned` and `smoothed` (values `yes/no` each one), and
1025 `rules/trees` (to create a tree or a rule set) of the Weka M5 implemen-
1026 tation.

1027 43. **cubist** learns a M5 rule-based model with corrections based on nearest

1028 neighbors in the training set [50], implemented by the `Cubist` package.
 1029 A tree structure is created and translated to a collection of rules, which
 1030 are pruned and combined, and each rule gives a regression model, ap-
 1031 plied to the patterns which accomplish that rule. `Cubist` extends M5
 1032 with boosting when the hyperparameter `committees` > 1 , and using
 1033 nearest neighbor based to correct the rule-based prediction. The tun-
 1034 able hyperparameters are the number of training `committees` (with 3
 1035 data-dependent odd values) and the number of `neighbors` (with values
 1036 0, 5 and 9) for prediction.

1037 44. **SBC** is the subtractive clustering and fuzzy C-means rules (`frbs` pack-
 1038 age), which uses subtractive clustering to get the cluster centers of a
 1039 fuzzy rule-based system for classification or regression [52]. Initially,
 1040 each training pattern is weighted by a potential function which de-
 1041 creases with its distances to the remaining centers, and then it opti-
 1042 mizes the centers using fuzzy C-means. The center with the highest
 1043 potential is selected as a cluster center, and the potential of the remain-
 1044 ing centers are updated. The only hyperparameter is the neighborhood
 1045 radius (`r.a`), tuned with 7 linearly spaced values between 0 and 1 (this
 1046 value is selected for nearly 50% of the 31 datasets where SBC does
 1047 not fail). The selection of new cluster centers and potential updating
 1048 is repeated until the potentials of the remaining patterns are below a
 1049 pre-specified fraction of the potential of the first cluster center. Once
 1050 all the centers are selected, they are optimized using fuzzy C-means.
 1051 As we report in last rows of Table 4, we also tried the remaining 8
 1052 regression methods implemented in the `frbs` package and included in

1053 the `caret` model list (ANFIS, DENFIS, FIR.DM, GFS.FR.MOGUL,
1054 GFS.LT.RS, GFS.THRIFT, HYFIS and WM), but run-time errors hap-
1055 pened for most or all the datasets.

1056 **XIV. *Random forests (RF)***

1057 45. **rf** is the random forest ensemble of random regression trees imple-
1058 mented by the `randomForest` package [54]. The outputs of the base
1059 regression models are averaged to get the model output. Its only hy-
1060 perparameter is the number of randomly selected inputs (`mtry`) with
1061 10 linearly spaced values from 2 until the number of inputs, or less than
1062 10 values when the number of dataset inputs is less than 11 (the lowest
1063 value `mtry=2` was selected in 18% of the 64 datasets where **rf** does not
1064 fail).

1065 46. **Boruta** combines RF with feature selection (`Boruta` package). An
1066 input is removed when a statistical test proves that it is less relevant
1067 than a shadow random input, created by shuffling the original ones [55].
1068 Conversely, inputs that are significantly better than shadowed ones are
1069 confirmed. The iterative search stops when only confirmed inputs are
1070 retained, or after a maximum number of iterations (`maxRuns=100` by
1071 default), in which case non-confirmed inputs remain unless the iter-
1072 ations or the test p -value (0.01 by default) are increased. The only
1073 hyperparameter is `mtry`, tuned as in **rf**.

1074 47. **RRF** is the regularized random forest (`RRF` package), which uses reg-
1075 ularization for input selection in **rf**, penalizing the selection of a new
1076 input for splitting when its Gini information gain is similar to the in-
1077 puts included in the previous splits [57]. The hyperparameters are

1078 `mtry`, with 3 linearly spaced values between 2 and the number of in-
1079 puts, and the regularization coefficient (`coefReg`), with values 0.01 and
1080 1, both selected with similar frequencies.

1081 48. **cforest** is a forest ensemble of conditional inference trees [54], each one
1082 fitting one bootstrap sample (`party` package [58]). The only hyperpa-
1083 rameter is the number of selected inputs (`mtry`, with values 2 and the
1084 number of inputs) of the conditional trees.

1085 49. **qrf** is the quantile regression forest (`quantregForest` package [59]),
1086 a tree-based ensemble which generalizes RF in order to estimate con-
1087 ditional quantile functions. This regression model grows several RFs,
1088 storing all the training patterns associated to each node in each tree.
1089 For each test pattern, the weight of each training pattern is the average
1090 of the weights of all the training patterns in the leaves activated by that
1091 pattern in the different trees of the forest. Using these weights, the dis-
1092 tribution function of each output value, and the conditional quantiles,
1093 are estimated. The only hyperparameter is `mtry` (tuned with 2 values
1094 as `cforest`). The quantile prediction threshold (argument `what` in the
1095 `predict.quantregForest` function) is set to 0.5.

1096 50. **extraTrees** is the ensemble of extremely randomized regression trees
1097 [60] implemented by the `extraTrees` package. It randomizes the input
1098 and cut-point of each split (or node in the tree), using a parameter
1099 which tunes the randomization strength. The full training set is used
1100 instead of a bootstrap replica. It is expected that explicit randomiza-
1101 tion of input and cut-point splittings combined with ensemble averaging
1102 should reduce the variance more than other methods. Its hyperparam-

eters are the number of inputs randomly selected at each node (`mtry`,
tuned with 2 values as `cforest`) and the minimum sample size to split
a node (`numRandomCuts`), tuned with integer values from 1 to 10 (the
selected value was 1 for 48.3% of the datasets).

XV. *Bagging ensembles (BAG)*

51. **bag** [62] is the bagging ensemble of conditional inference regression
trees (see model #39) implemented by the `caret` package. The output
for a test pattern is the average of the outputs over the base regression
trees.

52. **bagEarth** is the bagged MARS (`caret` package), a bagging ensemble
of MARS base regression models implemented in the `earth` package
(see model #9), which learns a MARS model with `degree=1` for each
bootstrap sample. The only hyperparameter is the maximum number
of terms (`nprune`) in the pruned regression model (10 values).

53. **treebag** is the bagged CART, a bagging ensemble of `rpart` regression
base trees (see model #37), implemented by the `ipredbag` function
in the `ipred` package [64].

XVI. *Boosting ensembles (BST)*

54. **rndGLM** is a boosting ensemble of GLMs [65] implemented by the
`randomGLM` package (also named `randomGLM` in the `caret` model list).
It uses several bootstrap samples (`nBags=100` by default) of the train-
ing set, randomly selecting inputs and interaction terms among them
depending on the `maxInteractionOrder` hyperparameter, tuned with
values 1, 2 and 3 (selected with frequencies 53.3%, 40% and 6.7%, re-
spectively). For each sample, inputs are ranked by its correlation with

the output, and a predefined number of them are selected, using forward selection, to create a multivariate GLM. For a test pattern, the predicted value is the average of the GLM outputs. This regression model has very high memory requirements, overcoming the largest available memory (128GB) in 38 datasets, and requiring 128, 64, 32 and 16GB in 2, 10, 22 and 12 datasets, respectively.

55. **BstLm** is the gradient boosting machine with linear base models, implemented in the **bst** package. Gradient boosting optimizes arbitrary differentiable loss functions defining the fitting criteria [53]. Boosting combines weak base regression models into a strong ensemble by iteratively adding base models, and in each iteration the new model is trained to fit the error (residual) of the previous ensemble. Since the error can be viewed as the negative gradient of the squared error loss function, boosting can be considered a gradient descent method. **BstLm** uses the **bst** function with linear base models (argument **learner=lm**) and Gaussian family, since squared error loss is used. The only hyperparameter is the number of boosting iterations (**mstop**), with 10 values from 50 to 500.

56. **bstSm** is the gradient boosting with smoothing spline base regression models (**learner=sm** in the **bst** function of the same package). The number of boosting iterations (**mstop**) is tuned with 10 values as **BstLm**.

57. **bstTree** is the gradient boosting with regression base trees (**learner=tree**, same function and package as **BstLm**). The hyperparameters are the number of boosting iterations (**mstop**, 4 values from 40 to 200) and the maximum depth of nodes in the final tree (**maxdepth** item in the list

1153 of the `control.tree` argument of the `bst` function), with integer values
 1154 between 1 and 5 (this last value is selected in 55% of the datasets).
 1155 58. **glmboost** is the gradient boosting ensemble with GLM base regression
 1156 models (`glmboost` function in the `mboost` package), tuning the number
 1157 of boosting iterations (`mstop`, 10 values).
 1158 59. **gamboost** is the boosted generalized additive model (`mboost` package),
 1159 a gradient boosting ensemble of GAM base regression models [69]. The
 1160 ensemble minimizes a weighted sum of the loss function evaluated at
 1161 the training patterns by computing its negative gradient. The base re-
 1162 gression models are component-wise models (P-splines with a B-spline
 1163 base, by default). The only hyperparameter is the number of initial
 1164 boosting iterations (`mstop`), with 10 values from 50 to 500, selecting
 1165 500 as the best value for 56.7% of the datasets.
 1166 60. **gbm** is the generalized boosting regression model (`gbm` package [49]),
 1167 named stochastic gradient boosting in the `caret` model list. The hyper-
 1168 parameters are the maximum depth of input interactions (`interaction.`
 1169 `depth`), with integer values from 1 to 5 (the last value was selected in
 1170 48.3% of the datasets), and number of trees for prediction (`n.trees`),
 1171 with values from 50 to 250 with step 50 (the value 250 was selected in
 1172 45% of the datasets). We use a Gaussian distribution and `shrinkage=`
 1173 `0.1` (default values).
 1174 61. **blackboost** is the gradient boosting (`blackboost` function in the `mboost`
 1175 package) with conditional inference regression base trees (`ctree` in the
 1176 `party` package, see model #40) and arbitrary loss functions [51]. The
 1177 only hyperparameter is the maximum tree depth (`maxdepth` argument

1178 in the `party::ctree_control` function, used as `tree_controls` argu-
1179 ment of the `blackboost` function), with integer values from 1 to 5,
1180 value selected in 79% of the datasets.

1181 62. **xgbTree** is the extreme gradient boosting [53], using the `xgb.train`
1182 function in the `xgboost` package with `booster=gbtree`, root mean
1183 squared error as evaluation metric and linear regression as objective
1184 function. The hyperparameters are the maximum tree depth (`max_depth`),
1185 with values 1, 2 and 3 (`max_depth=3` for 53.3% of the datasets); maxi-
1186 mum number of boosting iterations (`nrounds`), with values 50, 100 and
1187 150; and learning rate (η), with values 0.3 and 0.4.

1188 63. **xgbLinear** is the extreme gradient boosting with `booster=gblinear`
1189 and linear regression as objective function (`xgboost` package). Its hy-
1190 perparameters are the L2 (square loss) regularization term on weights
1191 (λ , with values 0, 0.1 and 0.0001), bias (α , with values 0 and 0.1), and
1192 number of boosting iterations (`nrounds`, tuned as **xgbTree**).

1193 **XVII. Neural networks (NET)**

1194 64. **mlpWD** is the classical multi-layer perceptron with one hidden layer
1195 and weight decay (named `mlpWeightDecay` in the `caret` model list).
1196 It uses the `mlp` function in the `RSNNS` package, with `learnFunc =`
1197 `BackpropWeightDecay`. The tunable hyperparameters are the `size`
1198 of the hidden layers (5 odd values between 1 and 5) and the weight
1199 decay (values 0, 0.1, 0.042, 0.01778 and 0.007498).

1200 65. **mlpWDml** is the same network with three hidden layers (`RSNNS` pack-
1201 age, named `mlpWeightDecayML` in the `caret` model list), tuning four
1202 hyperparameters: the sizes of the three hidden layers (`layer1`, `layer2`

and `layer3`, tuned with values 1, 3 and 5 each one) and the weight `decay` (same values as `mlpWD`).

66. **avNNet** is the model averaged neural network (`caret` package). A committee of 5 (argument `repeats`) multi-layer perceptron neural networks of the same size trained using different random seeds, being averaged to give an output [81]. The boolean argument `linout` is set to have linear output neurons for regression, and `MaxNWts` is adjusted to allow the number of weights required by the dataset inputs. The hyperparameters are the network `size`, tuned with 7 odd values between 1 and 13, and the weight `decay` (with values 0, 0.1 and 0.0001).

67. **rbf** is the radial basis function network (`RSNNS` package) which does a linear combination of basis functions, each centered around a prototype [56]. The information is locally codified (opposed to globally in the MLP), the training should be faster and the network is more interpretable, although the output might be undefined if a test pattern does not activate any prototype. The only hyperparameter is the `size` of the hidden layer (10 odd values from 1 to 19).

68. **grnn** is the generalized regression neural network [61], a special type of RBF network implemented by the Matlab neural network toolbox. After a clustering of the training set, the nodes of the hidden layer store the cluster centers, although the Matlab implementation uses so many clusters as training patterns. The output for a test pattern is a weighted sum of the Gaussian functions centered in the cluster centers, scaled by the cluster populations. During training, whenever a pattern is assigned to a cluster, the weight of the Gaussian function corresponding

1228 to that cluster is updated using the desired output. The Gaussian
1229 **spread** is the only hyperparameter (13 values between 0.01 and 2):
1230 large (resp. small) values lead to smooth (resp. close) approximations.

1231 69. **elm** is the extreme learning machine [63] implemented by the **elmNN**
1232 package. The only hyperparameters are the number of hidden neurons
1233 (**nhid**), with 40 odd values between 1 and 79 (the last value was se-
1234 lected in 11.7% of the datasets), and the activation function (**actfun**),
1235 with 4 values: **sin**, **radbas**, **purelin** and **tansig**, selected with similar
1236 frequencies.

1237 70. **kelm** is the ELM neural network with Gaussian kernel [63] using the
1238 publicly available Matlab code¹². The hyperparameters are regulariza-
1239 tion C and kernel spread σ , tuned with values $\{2^i\}_{-5}^{14}$ and $\{2^i\}_{-16}^8$, with
1240 20 and 25 values, respectively.

1241 71. **pcaNNet** is a multi-layer perceptron neural network with one hidden
1242 layer trained on the PCA-mapped training patterns, implemented by
1243 the **caret** and **nnet** packages. The principal components which account
1244 for more than 95% of the data variance are used for training. Each test
1245 pattern is mapped to the principal component space and the trained
1246 **pcaNNet** model gives an output. The tunable hyperparameters are the
1247 **size** of the hidden layer, with 7 values between 1 and 13, and the
1248 **weight decay** of the network, with values 0, 0.1 and 0.0001.

1249 72. **bdk** is the supervised bi-directional Kohonen network, implemented
1250 in the **kohonen** package [66]. The **bdk** combines Kohonen maps and
1251 counterpropagation networks using two maps, for inputs and output

¹²<http://www.ntu.edu.sg/home/egbhuang/elm.kernel.html> (visited March 29, 2017).

1252 respectively. In each iteration, the direct (resp. inverse) pass updates
 1253 only the weights of the input (resp. output) map, using a weighted sim-
 1254 ilarity measurement (Euclidean distance for regression) which involves
 1255 both maps, leading to a bi-directional updating. The test output is the
 1256 weight of the winner node of the output map. The hyperparameters
 1257 are the sizes of both maps (`xdim` and `ydim`, with 3 values from 3 to
 1258 17) and the initial weight (`xweight`) given to the input map during the
 1259 distance calculation for the output map, and to the output map for
 1260 updating the input map, tuned with values 0.5, 0.75 and 0.9).

1261 XVIII. *Deep learning (DL)*

1262 73. **dlkeras** is the deep learning neural network implemented by the **Keras**
 1263 module [67] of the Python programming language, with three hidden
 1264 layers tuned with 50 and 75 neurons for each layer (`nh1`, `nh2` and `nh3`,
 1265 with 8 combinations). The deep learning methods [82, 83] are very
 1266 popular, specially for image classification, and they are included in this
 1267 comparison for regression tasks.

1268 74. **dnn** is the deep belief network implemented in R by the **DeepNet** pack-
 1269 age [68]. It uses three hidden layers, tuning their number of neurons
 1270 using 3 values for each layer (27 combinations). The weights are ini-
 1271 tialized using stacked autoencoder (SAE), which in our experiments
 1272 gave better results than deep belief network (DBN). Hidden and out-
 1273 put neurons have hyperbolic tangent and linear activation functions,
 1274 respectively.

1275 XIX. *Support vector regression (SVR)*

1276 75. **svr** is the ε -support vector regression with Gaussian, accessed via the

1277 C++ interface of the `LibSVM` library [9]. We tuned the regularization
 1278 hyperparameter C and the kernel spread γ with values $\{2^i\}_{-5}^{14}$ and
 1279 $\{2^i\}_{-16}^8$, with 20 and 25 values, respectively.

1280 76. **svmRad** is another implementation of SVR (named `svmRadial` in the
 1281 `caret` model list) with Gaussian kernel (`ksvm` function in the `kernlab`
 1282 package [70] for regression (argument `type=eps-svr`). This implemen-
 1283 tation also uses `LibSVM`, and it tunes the regularization hyperparameter
 1284 C , with 20 values in the set $\{2^i\}_{-4}^{15}$, and the kernel spread σ . Although
 1285 we specify 25 values for σ , the `getModelInfo` function only lists 6 values
 1286 in the set $\{2^{-i}\}_5^7$.

1287 77. **rvmRad** is the relevance vector machine [71] with Gaussian kernel
 1288 (`kernlab` package), named `rvmRadial` in the `caret` model list. The
 1289 RVM has the same functional form as the SVM, but it uses a Bayesian
 1290 learning framework which reduces the number of basis functions, com-
 1291 pared to the SVM, while keeping an accurate prediction. This regres-
 1292 sion model avoids the tunable regularization hyperparameter (C) of
 1293 the SVM, but it uses a method similar to expectation-maximization
 1294 which, unlike SMO, may fall in local minima. The value of the Gaus-
 1295 sian spread σ is estimated by the `getModelInfo` function, which only
 1296 lists one value.

1297 References

1298 [1] M. Fernández-Delgado, E. Cernadas, S. Barro, D. Amorim, Do we need
 1299 hundreds of classifiers to solve real classification problems?, *J. Mach.*
 1300 *Learn. Res.* 15 (2014) 3133–3181.

- 1301 [2] D. H. Wolpert, The lack of a priori distinctions between learning algo-
1302 rithms, *Neural Computation* 9 (1996) 1341–1390.
- 1303 [3] K. Bache, M. Lichman, UCI machine learning repository (2013).
1304 URL <http://archive.ics.uci.edu/ml>
- 1305 [4] G. E. P. Box, D. R. Cox, An analysis of transformations, *J. Royal Stat.*
1306 *Soc. Series B (Methodological)* 26 (2) (1964) 211–252.
- 1307 [5] R Team, R: A language and environment for statistical computing, Vi-
1308 enna, Austria, ISBN 3-900051-07-0 (2008).
1309 URL <https://www.R-project.org>
- 1310 [6] M. Kuhn, Caret: classification and regression training, R package
1311 (2016).
1312 URL <http://topepo.github.io/caret/train-models-by-tag.html>
- 1313 [7] Theano Team, Theano: A Python framework for fast computation of
1314 mathematical expressions, arXiv e-prints.
- 1315 [8] Python Software Foundation, Python Language (2017).
1316 URL <https://www.python.org>
- 1317 [9] C. Chang, C. Lin, LIBSVM: a library for support vector machines, *ACM*
1318 *Trans. on Intel. Syst. and Technol.* 2 (2011) 27:1–27:27.
- 1319 [10] Matlab, version 9.2 (R2017a), Natick (MA) (2011).
- 1320 [11] J. Chambers, Linear models, J. M. Chambers and T. J. Hastie,
1321 Wadsworth & Brooks/Cole, 1992, Ch. 4, pp. 96–138.

- 1322 [12] H. Zou, T. Hastie, Regularization and variable selection via the elastic
1323 net, *J. R. Stat. Soc.* 67 (2005) 301–320.
- 1324 [13] P. Huber, *Robust statistics*, Wiley, 1981.
- 1325 [14] N. Meinshausen, Relaxed lasso, *Comput. Stat. Data An.* (2007) 374–393.
- 1326 [15] J. Goeman, L-1 penalized estimation in the Cox proportional hazards
1327 model, *Biometrical J.* 52 (2010) 70–84.
- 1328 [16] B. Efron, T. Hastie, I. Johnstone, R. Tibshirani, Least angle regression,
1329 *Ann. Stat.* 32 (2004) 407–499.
- 1330 [17] N. Simon, J. Friedman, T. Hastie, R. Tibshirani, Regularization paths
1331 for Cox’s proportional hazards model via coordinate descent, *J. Stat.*
1332 *Softw.* 39 (5) (2011) 1–13.
- 1333 [18] H. Ishwaran, J. Rao, U. Kogalur, Spikeslab : prediction and variable
1334 selection using spike and slab regression, *The R Journal* 2 (2010) 68–73.
- 1335 [19] B. Ripley, *Modern applied statistics with S*, Springer, 2002.
- 1336 [20] T. Zhang, Adaptive forward-backward greedy algorithm for learning
1337 sparse representations, *IEEE Trans. Inf. Theor.* 57 (7) (2011) 4689–4708.
- 1338 [21] S. Wood, Fast stable restricted maximum likelihood and marginal like-
1339 lihood estimation of semiparametric generalized linear models, *J. Royal*
1340 *Stat. Soc.* 1 (73) (2011) 3–36.

- 1341 [22] A. Gelman, A. Jakulin, M. Pittau, Y. Su, A weakly informative default
1342 prior distribution for logistic and other regression models, *Ann. Appl.*
1343 *Stat.* 2 (4) (2009) 1360–1383.
- 1344 [23] J. Friedman, Multivariate adaptive regression splines, *Ann. Stat.* 19 (1)
1345 (1991) 1–141.
- 1346 [24] F. Foresee, M. T. Hagan, Gauss-Newton approximation to Bayesian
1347 regularization, in: *Intl. Joint Conf. on Neural Netw.*, 1997, pp. 1930–
1348 1935.
- 1349 [25] C. Lawson, R. Hanson, Solving least squares problems, Vol. 15 of *Class-*
1350 *ics in Appl. Math.*, Soc. Ind. Appl. Math. (SIAM), 1995.
- 1351 [26] A. Kapelner, J. Bleich, BartMachine: machine learning with Bayesian
1352 additive regression trees, *J. Stat. Softw.* 70 (4) (2016) 1–40.
- 1353 [27] J. Hainmueller, C. Hazlett, Kernel regularized least squares: reducing
1354 misspecification bias with a flexible and interpretable machine learning
1355 approach, *Polit. Anal.* 22 (2013) 143–168.
- 1356 [28] C. Williams, D. Barber, Ibayesian classification with gaussian processes,
1357 *IEEE Trans. Pat. Anal. Mach. Intel.* 20 (12) (1998) 1342–1351.
- 1358 [29] H. Chun, S. Keles, Sparse partial least squares for simultaneous dimen-
1359 sion reduction and variable selection, *J. of the Royal Stat. Soc.* 72 (2010)
1360 3–25.
- 1361 [30] S. Jong, SIMPLS: an alternative approach to partial least squares re-
1362 gression, *Chemometr. intel. lab.* 18 (1993) 251–263.

- [31] S. Jong, Comment on the PLS kernel algorithm, *J. Chemometr.* 8 (1994) 169–174.
- [32] I. Mizera, R. Koenker, Convex optimization in R, *J. Stat. Softw.* 60 (5) (2014) 1–23.
- [33] S. Rännar, F. Lindgren, P. Geladi, S. Wold, A PLS kernel algorithm for data sets with many variables and fewer objects. part 1: theory and algorithm, *J. Chemometr.* 8 (1994) 111–125.
- [34] H. Zou, R. Li, One-step sparse estimates in nonconcave penalized likelihood models, *Ann. Stat.* 36 (4) (2008) 1509–1533.
- [35] N. Xiao, D. Cao, M. Li, Q. Xu, Enpls: an R package for ensemble partial least squares regression, arXiv preprint.
- [36] A. Cannon, Quantile regression neural networks: implementation in R and application to precipitation downscaling, *Comput. & Geosci.* 37 (2011) 1277–1284.
- [37] F. Bertrand, M. Maumy-Bertrand, N. Meyer, Partial least squares regression for generalized linear models, *r* package version 1.1.1 (2014).
URL <http://www-irma.u-strasbg.fr/~fbertran>
- [38] K. Hechenbichler, K. Schliep, Weighted k -nearest-neighbor techniques and ordinal classification, Tech. rep., Ludwig-Maximilians University Munich (2004).
- [39] J. Friedman, W. Stuetzle, Projection pursuit regression, *J. Am. Stat. Assoc.* 76 (1981) 817–823.

- 1385 [40] L. Breiman, J. Friedman, R. Olshen, C. Stone, Classification and regres-
1386 sion trees, Wadsworth and Brooks, 1984.
- 1387 [41] B. Mevik, H. Cederkvist, Mean squared error of prediction (MSEP)
1388 estimates for principal component regression (PCR) and partial least
1389 squares regression (PLSR), J. Chemometr. 18 (9) (2004) 422–429.
- 1390 [42] N. Meinshausen, Node harvest, Ann. Appl. Stat. 4 (4) (2010) 2049–2072.
- 1391 [43] A. Hyvarinen, E. Oja, Independent component analysis: algorithms and
1392 applications, Neural networks 13 (2000) 411–430.
- 1393 [44] T. Hothorn, K. Hornik, A. Zeileis, Unbiased recursive partitioning: a
1394 conditional inference framework, J. Comput. Graph. Stat. 15 (3) (2006)
1395 651–674.
- 1396 [45] E. Bair, R. Tibshirani, Semi-supervised methods to predict patient sur-
1397 vival from gene expression data, PLoS Biol 2 (4) (2004) 511–522.
- 1398 [46] A. Molinaro, K. Lostritto, M. van der Laan, PartDSA: dele-
1399 tion/substitution/ addition algorithm for partitioning the covariate
1400 space in prediction, Bioinformatics 26 (10) (2010) 1357–63.
- 1401 [47] T. Grubinger, A. Zeileis, K. Pfeiffer, Evtree: evolutionary learning of
1402 globally optimal classification and regression trees in R, J. Stat. Softw.
1403 61 (1) (2014) 1–29.
- 1404 [48] R. Quinlan, Learning with continuous classes, in: 5th Australian J.
1405 Conf. on Artif. Intel., 1992, pp. 343–348.

- 1406 [49] G. Ridgeway, Gbm package, <https://cran.r-project.org/package=gbm>
1407 (2017).
- 1408 [50] R. Quinlan, Combining instance-based and model-based learning, in:
1409 Proc. Intl. Conf. on Mach. Learn., 1993, pp. 236–243.
- 1410 [51] P. Buehlmann, T. Hothorn, Boosting algorithms: regularization, predic-
1411 tion and model fitting (with discussion), Stat. Sci. 22 (4) (2007) 477–505.
- 1412 [52] S. Chiu, Method and software for extracting fuzzy classification rules
1413 by subtractive clustering, in: Fuzzy Inf. Proc. Soc., NAFIPS, 1996, pp.
1414 461–465.
- 1415 [53] J. Friedman, Greedy function approximation: a gradient boosting ma-
1416 chine, Ann. Stat. 29 (2001) 1189–1232.
- 1417 [54] L. Breiman, Random forests, Mach. Learn. 45 (2001) 5–32.
- 1418 [55] M. Kursa, W. Rudnicki, Feature selection with the Boruta package, J.
1419 Stat. Softw. 36 (11) (2010) 1–13.
- 1420 [56] A. Zell *et al.*, SNNS: Stuttgart Neural Network Simulator User Man-
1421 ual, Version 4.2, Tech. rep., IPVR, University of Stuttgart and WSI,
1422 University of Tbingen (1998).
- 1423 [57] H. Deng, G. Runger, Gene selection with guided regularized random
1424 forest, Pat. Recog. 46 (12) (2013) 3483–3489.
- 1425 [58] T. Hothorn, Party package, <http://cran.r-project.org/package=party>
1426 (2018).

- 1427 [59] N. Meinshausen, Quantile regression forests, *J. Mach. Learn. Res.* 7
1428 (2006) 983–999.
- 1429 [60] P. Geurts, D. Ernst, L. Wehenkel, Extremely randomized trees, *Mach.*
1430 *Learn.* 63 (1) (2006) 3–42.
- 1431 [61] D. Specht, A general regression neural network, *IEEE T. Neural Netw.*
1432 2 (1991) 568–576.
- 1433 [62] L. Breiman, Bagging predictors, *Mach. Learn.* 24 (1996) 123–140.
- 1434 [63] G.-B. Huang, H. Zhou, X. Ding, R. Zhang, Extreme learning machine
1435 for regression and multiclass classification, *IEEE Trans. Sysys., Man,*
1436 *and Cybern.-Part B: Cybern.* 42(2) (2012) 513–529.
- 1437 [64] A. Peters, Ipred package (2015).
1438 URL <http://cran.r-project.org/package=ipred>
- 1439 [65] L. Song, P. Langfelder, S. Horvath, Random generalized linear model:
1440 a highly accurate and interpretable ensemble predictor, *BMC Bioinform-*
1441 *atics* 14 (1) (2013) 1–22.
- 1442 [66] W. Melssen, R. Wehrens, L. Buydens, Supervised Kohonen networks for
1443 classification problems, *Chemom. Intell. Lab. Syst.* 83 (2006) 99–113.
- 1444 [67] F. Chollet, Keras: The Python Deep Learning library (2015).
1445 URL <https://keras.io>
- 1446 [68] X. Ron, Deepnet package (2015).
1447 URL <https://cran.r-project.org/package=deepnet>

- 1448 [69] P. Buehlmann, B. Yu, Boosting with the L2 loss: regression and classi-
1449 fication, *J. Am. Stat. Assoc.* 98 (2003) 324–339.
- 1450 [70] A. Karatzoglou, Kernlab package (2015).
1451 URL <https://cran.r-project.org/package=kernlab>
- 1452 [71] M. Tipping, Sparse Bayesian learning and the relevance vector machine,
1453 *J. Mach. Learn. Res.* 1 (2001) 211–244.
- 1454 [72] T. Hothorn, F. Leish, A. Zeileis, K. Hornik, The design and analysis
1455 of benchmark experiments, *J. Comput. and Graph. Stat.* 13 (3) (2005)
1456 675–699.
- 1457 [73] S. García, A. Fernández, A. Benítez, F. Herrera, Statistical comparisons
1458 by means of non-parametric tests: a case study on genetic based machine
1459 learning, in: *Proc. II Congreso Español de Informática (CEDI 2007)*,
1460 2007, pp. 95–104.
- 1461 [74] M. Hollander, D. Wolfe, *Nonparametric Statistical Methods*, John Wiley
1462 & Sons, 1973.
- 1463 [75] J. Demšar, Statistical comparisons of classifiers over multiple data sets,
1464 *J. Mach. Learn. Res.* 7 (2006) 1–30.
- 1465 [76] C. Dunnett, A multiple comparison procedure for comparing several
1466 treatments with a control, *J. Am. Stat. Assoc.* 50 (1955) 1096–1121.
- 1467 [77] J. D. Gibbons, S. Chakraborti, *Nonparametric Statistical Inference*,
1468 CRC Press, 2011.

- 1469 [78] T. Pohlert, The pairwise multiple comparison of mean ranks package
1470 (PMCMR), r package (2014).
1471 URL <http://CRAN.R-project.org/package=PMCMR>
- 1472 [79] T. Colton, Statistical in medicine, Little Brown and Co., New York, NJ,
1473 1974.
- 1474 [80] D. MacKay, Bayesian interpolation, Neural Computation 4 (1992) 415–
1475 447.
- 1476 [81] B. Ripley, Pattern recognition and neural networks, Cambridge Univ.
1477 Press, 1996.
- 1478 [82] G. E. Hinton, S. Osindero, Y.-W. Teh, A fast learning algorithm for
1479 deep belief nets, Neural Comput. 18 (7) (2006) 1527–1554.
- 1480 [83] W. Liu, Z. Wang, X. Liu, N. Zeng, Y. Liu, F. Alsaadi, A survey of deep
1481 neural network architectures and their applications, Neurocomputing
1482 234 (2017) 11–26.