

The Tychonoff Theorem (Mizar YELLOW_17)

Lars Warren Ericson¹

¹Catskills Research Company

¹<https://github.com/catskillsresearch/yellow17>

¹lars.ericson@catskillsresearch.com

August 25, 2026

ORCID: 0000-0001-8299-9361

Abstract

This note is the write-up of a Lean 4 translation of Bartomiej Skorulski, *The Tichonov Theorem* (Mizar article YELLOW_17, received 23 May 2000; Formalized Mathematics 9(2), 373–376). The source file is `mml/yellow17.miz` from the [Mizar Mathematical Library](#) at revision `047822c4d814630b28eec8ca6b455e9eb912d5ff`. The headline result is Tychonoff’s theorem: a dependent product of compact spaces is compact. That theorem is the topological engine behind the compactness of the Lawson topology on a continuous lattice and the product theory of compact semilattices in Gierz–Hofmann–Keimel–Lawson–Mislove–Scott, *A Compendium of Continuous Lattices* [GHKLMS80, §III-1, §VI-2–VI-3]. The Lean development is sorry-free. The compared theorems audit to `{proptext, Classical.choice, Quot.sound}`.

1 Introduction

Skorulski’s Mizar article develops the product topology on a set-coded family of spaces and proves compactness of the product from Alexander’s subbasis theorem. This package translates that article into idiomatic Lean 4 against Mathlib 4.33, and packages the translation for Palomar.

We do **not** claim Tychonoff’s theorem as original. Tychonoff proved compactness of products of closed intervals in 1930 and stated the general theorem in 1935 [Tyc30]. The compared claim is a machine-checked Lean rendering of YELLOW_17, with Mathlib supplying the Alexander/Tychonoff infrastructure that Mizar built from untyped products.

The translation is **complete as a catalog** of the article’s named results (`Th1–Th22`, `Lm1`, scheme `ElProductEx`, and the unnamed Tichonov Theorem) but is **not one-to-one**. Mizar `Th8–Th13` are topological-carrier wrappers of `Th1–Th7` and are merged. The headline proof cites Mathlib’s `isCompact_univ_pi / Pi.compactSpace` rather than replaying Skorulski’s `Th15+Th22+ElProductEx` choice-function argument; those lemmas are nonetheless stated and proved. Lean is slightly more general: Mizar assumes a nonempty index set and nonempty factors; the Lean statements allow empty index types.

The Mizar source is copied from [MizarSystem/MML](#) (`mml/yellow17.miz`) and is licensed GPL-3.0-or-later or CC-BY-SA-3.0-or-later by the Association of Mizar Users. Pin and copy date: `mml/FROZEN.txt`. This repository uses the same dual license.

2 Relation to the Compendium

In domain theory the reason one wants Tychonoff is not general topology for its own sake. *A Compendium of Continuous Lattices* [GHKLMS80] characterises continuous lattices as exactly the compact Hausdorff Lawson semilattices:

- **§III-1 (The Lawson topology).** The Lawson topology $\lambda(L)$ is the common refinement of the Scott topology and the lower topology. For a continuous lattice it is compact Hausdorff. The compactness argument realises $\lambda(L)$ as (a closed subspace of) a product of compact two-point spaces, and therefore invokes Tychonoff.
- **§VI-2 (Compact topological semilattices) and §VI-3 (The fundamental theorem of compact semilattices).** A complete lattice admits a compact Hausdorff topology making meet jointly continuous if and only if it is a continuous lattice; that topology is then uniquely $\lambda(L)$. Products of compact Lawson semilattices are again compact Lawson semilattices, again by Tychonoff on the underlying spaces.

Skorulski’s `YELLOW_17`, and the Lean theorems `yellow17_tychonoff` / `yellow17_tychonoff_sets`, supply the space-level product theorem that those Compendium sections use. This package does **not** formalize the Lawson topology or the fundamental theorem; it formalizes the topological lemma they rest on.

(The 2003 successor *Continuous Lattices and Domains* [GHKLMS03] reorganizes the same material as Chapters II–III and VI. We cite the 1980 Compendium, which is the reference used throughout the `YELLOW_*` / `WAYBEL_*` Mizar development.)

3 Representation

Mizar codes a family as a function `F` and the product as the set `product F` of functions on `dom F`. Projections are `proj (F,i)` and updates are `f+(i,xi)`.

Lean uses a dependent product $\forall i, X i$, evaluation `Function.eval`, updates `Function.update`, and cylinders `eval i ⁻¹ ' U`. The open cylinder family `cylinderSubbasis X` is the product pre-basis.

4 Mizar inventory

Formalized Mathematics numbers the printed propositions (1)–(24); the `.miz` file uses `Th1–Th22`, lemma `Lm1`, scheme `ElProductEx`, and one unnamed Tichonov Theorem. The table is the inventory from the translation session. In Markdown tables, literal `|` is written `\|`.

FM	Mizar	Lean	Notes
(1), (9)	Th1, Th9	<code>eval_singleton_inter_mem</code>	Same fact; Th9 is only the topological-carrier wrapper of Th1
(2)	Th2	<code>update_mem_univ_pi</code>	Direct
(3)	Th3	<code>range_eval_eq_univ</code>	Only the surjectivity half. <code>rng proj ⊆ F.i</code> is definitional for <code>eval</code>
(4), (10)	Th4, Th10	<code>preimage_eval_univ</code>	Merged

FM	Mizar	Lean	Notes
(5), (11)	Th5, Th11	update_mem_eval_singleton	Merged
(8)	Th8	eval_apply	rfl
—	Lm1	(folded into next)	Used only to prove Th6
(6), (13)	Th6, Th13	mem_preimage_eval_update_iff	Merged with Lm1
(7), (12)	Th7, Th12	eval_singleton_subset_eval_*	Split into same-axis / off-axis / iff
scheme	ElProductEx	elProductEx / _spec	Present; unused by the Lean headline
(14)	(cover lemma)	(Mathlib)	“F is a cover iff the carrier is $\subseteq F$ ”
(15)	Th14	isCompact_iff_finite_open_subcover	Iff, via Mathlib
(16)	Th15	isCompact_of_subbasis_finite_subcover	Only Alexander’s “if”. Mizar’s converse is the trivial “compact $\Rightarrow$ every open cover has a finite subcover”
(17)	Th16	mem_cylinderSubbasis_iff	Direct, plus extra pi_eq_generateFrom_cylinderSubbasis
(18)	Th17	cylinder_of_singleton_subset	Direct
(19)	Th18	univ_subset_iUnion_preimage_eval	Direct
(20)	Th19	univ_subset_sUnion_of_fiber_cover_no_strict	Stated and proved. Not used to prove Tychonoff
(21)	Th20	exists_cylinder_containing_fiber_of_finite	Same
(22)	Th21	exists_proper_open_cylinder_of_fiber_cover	Same
(23)	Th22	exists_point_fiber_not_finitely_covered	Same
(24)	Tichonov	yellow17_tychonoff_sets	IsCompact (univ.pi s) via isCompact_univ_pi
(24)	Tichonov	yellow17_tychonoff	CompactSpace ($\forall i, X i$) via Pi.compactSpace

FM	Mizar	Lean	Notes
(24)	Tichonov	yellow17_ tychonoff'	Implication form matching the Mizar statement

So every named Mizar result has a Lean counterpart, but there are not 22 separate Lean theorems matching **Th1–Th22** one-for-one.

Complete?

- Yes for the **statements**: product lemmas, cylinder subbasis, compactness criteria, and Tychonoff are all there, and `lake build` is green.
- No for a **Mizar-faithful proof of Tychonoff**. In the `.miz` file, Tychonoff is **Th15** + **Th22** + **ElProductEx** + a choice function through the cover. In Lean the headline does not replay that chain; **Th19–Th22** are combinatorial leftovers.

Proof note (Tychonoff). Axioms of the three headlines: `{propext, Classical.choice, Quot.sound}`. Choice is expected for classical compactness of arbitrary products (Kelley: Tychonoff for T_2 spaces is equivalent to AC). The Compendium’s Lawson-compactness argument in §III-1 inherits that choice.

Proof note (Th15). Mizar states an iff. Lean records the Alexander direction used to test compactness on a generating family (`isCompact_generateFrom`). The converse is the ordinary finite-subcover property (**Th14**).

5 Palomar statement of record

`Challenge.lean` restates every `Yellow17` theorem and definition with `sorry`. `Solution.lean` imports `Yellow17.lean`. `comparator.json` lists all 24 theorems and both definitions (`elProductEx`, `cylinderSubbasis`). Types must match under `pp.all` / `pp.explicit` (`scripts/compare_challenge_solution_types.sh`).

6 Build

Toolchain: Lean / mathlib **v4.33.0**.

```
lake exe cache get
lake build
bash scripts/palomar_preflight.sh
bash scripts/build_arxiv_pdf.sh
```

`lake build` typechecks `Yellow17`, `Challenge`, and `Solution`. Narrative inventory: this file. Metadata: `comparator.json`, `formalization.yaml`. MML pin: `mml/FROZEN.txt`.

7 Acknowledgments

The human author retains sole responsibility for the mathematical content. No large language model is listed as a co-author.

- **Cursor [Cur26]** — agent-assisted editing in the Cursor IDE: Lean 4 translation of Mizar `YELLOW_17`, Palomar Challenge/Solution packaging, and this narrative (`arxiv.md`). Generated Lean was provisional until it compiled under Lean / mathlib v4.33.0.

- **Cursor Grok 4.6** [Grk26] — primary agent (SpaceXAI / Cursor) for Yellow17.lean and the Palomar kit.

The development is at github.com/catskillsresearch/yellow17.

List of Figures

8 References

- [Cur26] Anysphere, Inc. *Cursor: AI-native code editor and agent environment*. <https://cursor.com/> (2026).
- [Grk26] xAI / SpaceXAI and Cursor. *Grok 4.6* conversational coding model, used via the Cursor agent (2026).
- [GHKLMS80] G. Gierz, K. H. Hofmann, K. Keimel, J. D. Lawson, M. Mislove, and D. S. Scott. *A Compendium of Continuous Lattices*. Springer-Verlag, Berlin, 1980. DOI [10.1007/978-3-642-67678-9](https://doi.org/10.1007/978-3-642-67678-9). §III-1 (Lawson topology; compactness via Tychonoff); §VI-2–VI-3 (compact topological semilattices and the fundamental theorem).
- [GHKLMS03] G. Gierz, K. H. Hofmann, K. Keimel, J. D. Lawson, M. Mislove, and D. S. Scott. *Continuous Lattices and Domains*. Encyclopedia of Mathematics and its Applications 93. Cambridge University Press, 2003. Successor of [GHKLMS80]; same material reorganized as Chapters II–III and VI.
- [Sko01] Bartomiej Skorulski. *The Tichonov Theorem*. Formalized Mathematics 9(2), 373–376, 2001. Mizar article YELLOW_17, received 23 May 2000. Source: mml/yellow17.miz in [MizarSystem/MML](https://mizar.system/mml) at 047822c4d814630b28eec8ca6b455e9eb912d5ff (Mizar 7.13.01 / MML 4.181.1147).
- [Tyc30] Andrey Tychonoff. *Über die topologische Erweiterung von Räumen*. Mathematische Annalen 102 (1930), 544–561.
- The mathlib Tychonoff and Alexander theorems (`isCompact_univ_pi`, `Pi.compactSpace`, `isCompact_generateFrom`).

A Complete Lean source

Role	File	Lines
Mizar YELLOW_17 translation (proofs)	Yellow17.lean	325

Total: 1 files, 325 lines of Lean.

A.1 Yellow17.lean

325 lines.

Lean 4 source

```

/-
Copyright (c) 2000-2012 Association of Mizar Users
  (Stowarzyszenie Uzytkownikow Mizara, Bialystok, Poland).
Copyright (c) 2026 Lars Warren Ericson.
Released under the GNU General Public License version 3.0 or later,
or the Creative Commons Attribution-ShareAlike License version 3.0 or later.
See the notices in `yellow17.miz`.
Authors: Bart?omiej Skorulski (Mizar), Lars Warren Ericson (Lean 4).
-/

import Mathlib.Topology.Compactness.Compact

/-!
# The Tychonoff theorem (Mizar `YELLOW_17`)

Idiomatic Lean 4 translation of Bart?omiej Skorulski, *The Tichonov Theorem*
(Mizar article `YELLOW_17`, received 23 May 2000). Mizar?s set-coded products
`product F`, projections `proj(F,i)`, and updates `f+(i,xi)` become dependent
functions `forall i, X i`, evaluation `Function.eval`, and `Function.update`.
-/

open Set Function Topology TopologicalSpace

set_option linter.unusedSectionVars false

universe u v

namespace Yellow17

variable {? : Type u} {X : ? -> Type v}

/-! ## Product, projection, and update (`Th1`-`Th13`) -/

/-- **Mizar `Th1` / `Th9`.** A nonempty intersection of the singleton cylinder
over `xi` with the cylinder over `Ai` forces `xi` in `Ai`. -/
theorem eval_singleton_inter_mem {i : ?} {xi : X i} {Ai : Set (X i)}
  (h : ((eval i ^-1' ({xi} : Set (X i))) I (eval i ^-1' Ai)).Nonempty) :
  xi in Ai := by
  obtain <f, hf_1, hf_2> := h
  exact (show f i = xi from hf_1) |> hf_2

/-- **Mizar `Th2`.** Updating one coordinate of a point of `Set.pi univ s`
stays in the product box. -/
theorem update_mem_univ_pi [DecidableEq ?] {s : forall i, Set (X i)} {f : forall i, X i}
  {i : ?} {xi : X i} (hxi : xi in s i) (hf : f in univ.pi s) :
  update f i xi in univ.pi s := by
  intro j _
  by_cases hj : j = i
  * subst hj
  * simp using hxi
  * simp [update_of_ne hj] using hf j (mem_univ j)

/-- **Mizar `Th3`.** The `i`-th projection of a product of inhabited types is
surjective onto the `i`-th factor. -/
theorem range_eval_eq_univ [forall j, Nonempty (X j)] (i : ?) :
  range (eval i : (forall j, X j) -> X i) = univ :=
  range_eval (a := X) i

/-- **Mizar `Th4` / `Th10`.** The full cylinder over a factor is the whole
product. -/
@[simp] theorem preimage_eval_univ (i : ?) :
  (eval i : (forall j, X j) -> X i) ^-1' (univ : Set (X i)) = univ :=
  preimage_univ

```

```

/-- **Mizar `Th5` / `Th11`.** Coordinate update lands in the singleton cylinder. -/
theorem update_mem_eval_singleton [DecidableEq ?] (f : forall i, X i) (i : ?)
  (xi : X i) : update f i xi in eval i ^-1' ({xi} : Set (X i)) := by
  simp

/-- **Mizar `Th8`.** Projection is evaluation. -/
theorem eval_apply (f : forall i, X i) (i : ?) : eval i f = f i :=
  rfl

/-- **Mizar `Lm1` / `Th6` / `Th13`.** Membership in an off-axis cylinder is
unchanged by updating a different coordinate. -/
theorem mem_preimage_eval_update_iff [DecidableEq ?] {f : forall i, X i}
  {i_1 i_2 : ?} {xi_1 : X i_1} {Ai_2 : Set (X i_2)} (hne : i_1 != i_2) :
  update f i_1 xi_1 in eval i_2 ^-1' Ai_2 <=> f in eval i_2 ^-1' Ai_2 := by
  simp [update_of_ne hne.symm]

/-- **Mizar `Th7` / `Th12`, same coordinate.** -/
theorem eval_singleton_subset_eval_same [DecidableEq ?] {i : ?} {xi : X i}
  {Ai : Set (X i)} [Nonempty (forall j, X j)] :
  eval i ^-1' ({xi} : Set (X i)) subseteq eval i ^-1' Ai <=> xi in Ai := by
  classical
  refine <fun h => ?_, fun hxi => preimage_mono (singleton_subset_iff.2 hxi)>
  obtain <g> := ?Nonempty (forall j, X j)?
  simpa using h (update_mem_eval_singleton g i xi)

/-- **Mizar `Th7` / `Th12`, distinct coordinates.** A proper cylinder cannot
contain a singleton cylinder on another axis. -/
theorem eval_singleton_not_subset_eval_of_ne [DecidableEq ?]
  [forall j, Nonempty (X j)] {i_1 i_2 : ?} {xi_1 : X i_1} {Ai_2 : Set (X i_2)}
  (hne : i_1 != i_2) (hAi : Ai_2 != univ) :
  not eval i_1 ^-1' ({xi_1} : Set (X i_1)) subseteq eval i_2 ^-1' Ai_2 := by
  obtain <xi_2, hxi_2> := nonempty_compl.mpr hAi
  let f : forall j, X j := fun _ => Classical.choice inferInstance
  intro hsub
  have hmem : update (update f i_2 xi_2) i_1 xi_1 in eval i_2 ^-1' Ai_2 :=
    hsub (update_mem_eval_singleton (update f i_2 xi_2) i_1 xi_1)
  have : update f i_2 xi_2 in eval i_2 ^-1' Ai_2 :=
    (mem_preimage_eval_update_iff (f := update f i_2 xi_2) hne).1 hmem
  exact hxi_2 (by simpa using this)

/-- **Mizar `Th7` / `Th12`.** A proper cylinder contains a singleton cylinder
iff the coordinates agree and the point lies in the set. -/
theorem eval_singleton_subset_eval_iff [DecidableEq ?] [forall j, Nonempty (X j)]
  {i_1 i_2 : ?} {xi_1 : X i_1} {Ai_2 : Set (X i_2)} (hAi : Ai_2 != univ) :
  eval i_1 ^-1' ({xi_1} : Set (X i_1)) subseteq eval i_2 ^-1' Ai_2 <=>
  exists h : i_1 = i_2, xi_1 in h |> Ai_2 := by
  refine <fun hsub => ?_, ?_>
  * have hi : i_1 = i_2 := by
    by_contra hne
    exact eval_singleton_not_subset_eval_of_ne hne hAi hsub
  subst hi
  exact <rfl, (eval_singleton_subset_eval_same).1 hsub>
  * rintro <rfl, hxi>
  exact (eval_singleton_subset_eval_same).2 hxi

/-- **Mizar scheme `ElProductEx`.** A point of the product can be assembled
coordinatewise. -/
noncomputable def elProductEx {P : forall i, X i -> Prop}
  (h : forall i, exists x : X i, P i x) : forall i, X i :=
  fun i => (h i).choose

theorem elProductEx_spec {P : forall i, X i -> Prop} (h : forall i, exists x : X i, P i x)

```

```

    (i : ?) : P i (elProductEx h i) :=
    (h i).choose_spec

/--! ## Cylinder subbasis (`Th16`-`Th18`) -/

variable [forall i, TopologicalSpace (X i)]

/-- Open cylinders `eval i ^-1' U`, the product prebasis of `YELLOW_18`. -/
def cylinderSubbasis (X : ? -> Type v) [forall i, TopologicalSpace (X i)] :
  Set (Set (forall i, X i)) :=
  {C | exists (i : ?) (U : Set (X i)), IsOpen U /\ C = eval i ^-1' U}

/-- **Mizar `Th16`.** Every prebasis element is an open cylinder. -/
theorem mem_cylinderSubbasis_iff {A : Set (forall i, X i)} :
  A in cylinderSubbasis X <=>
    exists (i : ?) (U : Set (X i)), IsOpen U /\ A = eval i ^-1' U :=
  Iff.rfl

/-- The open cylinders generate the product topology. -/
theorem pi_eq_generateFrom_cylinderSubbasis :
  (Pi.topologicalSpace : TopologicalSpace (forall i, X i)) =
    generateFrom (cylinderSubbasis X) := by
  refine le_antisymm ?_ ?_
  * apply le_generateFrom
    rintro _ <i, U, hU, rfl>
    exact hU.preimage (continuous_apply i)
  * rw [pi_eq_generateFrom]
    apply le_generateFrom
    rintro t <s, I, hI, rfl>
    let := generateFrom (cylinderSubbasis X)
    have : Set.pi (I : Set ?) s = ? i in I, eval i ^-1' s i := by
      ext f
      simp [Set.mem_pi]
    rw [this]
    exact isOpen_biInter_finset fun i hi =>
      isOpen_generateFrom_of_mem <i, s i, hI i hi, rfl>

/-- **Mizar `Th17`.** If a singleton cylinder sits inside a proper prebasis
element, that element is a proper open cylinder on the same axis. -/
theorem cylinder_of_singleton_subset [DecidableEq ?] [forall j, Nonempty (X j)]
  {i : ?} {xi : X i} {A : Set (forall i, X i)}
  (hA : A in cylinderSubbasis X)
  (hsub : eval i ^-1' ({xi} : Set (X i)) subseq A)
  (hne : A != univ) :
  exists U : Set (X i), U != univ /\ xi in U /\ IsOpen U /\ A = eval i ^-1' U :=
  by
  obtain <i_2, U, hUo, rfl> := hA
  have hU : U != univ := by
    intro h
    exact hne (by simp [h])
  obtain <hii, hxi> := (eval_singleton_subset_eval_iff (i_1 := i) (i_2 := i_2)
    (xi_1 := xi) (Ai_2 := U) hU).1 hsub
  subst hii
  exact <U, hU, hxi, hUo, rfl>

/-- **Mizar `Th18`.** An open cover of a factor lifts to a cylinder cover of
the product. -/
theorem univ_subset_iUnion_preimage_eval {i : ?} {Fi : Set (Set (X i))}
  (h : (univ : Set (X i)) subseq ?_0 Fi) :
  (univ : Set (forall j, X j)) subseq ?_0 ((fun U : Set (X i) => eval i ^-1' U) '' Fi)
  := by
  intro f _
  obtain <U, hU, hfU> := mem_sUnion.1 (h (mem_univ (f i)))

```



```

exact mem_sUnion.2 <eval i ^-1' U, mem_image_of_mem _ hU, hfU>

/--! ## Compactness via open covers and a subbasis (`Th14`-`Th15`) -/

/-- **Mizar `Th14`.** Compactness is the finite-open-subcover property. -/
theorem isCompact_iff_finite_open_subcover {Y : Type u} [TopologicalSpace Y]
  {s : Set Y} :
  IsCompact s <-> forall {? : Type u} (U : ? -> Set Y),
    (forall k, IsOpen (U k)) -> (s subseq ? k, U k) ->
      exists t : Finset ?, s subseq ? k in t, U k :=
isCompact_iff_finite_subcover

/-- **Mizar `Th15`.** Alexander's subbasis theorem: it is enough to test
covers drawn from a generating family. -/
theorem isCompact_of_subbasis_finite_subcover {Y : Type*}
  [T : TopologicalSpace Y] {S : Set (Set Y)} (hTS : T = generateFrom S)
  {s : Set Y}
  (h : forall P subseq S, s subseq ?_0 P -> exists Q subseq P, Q.Finite /\
    s subseq ?_0 Q) :
  IsCompact s :=
isCompact_generateFrom hTS h

/--! ## Combinatorics of cylinder covers (`Th19`-`Th22`) -/

/-- **Mizar `Th19`.** If a singleton fiber is covered by `G` but no member of
`G` contains the fiber, then `G` covers the whole product. -/
theorem univ_subset_sUnion_of_fiber_cover_no_strict [DecidableEq ?]
  [forall j, Nonempty (X j)] {i : ?} {xi : X i} {G : Set (Set (forall j, X j))}
  (hG : G subseq cylinderSubbasis X)
  (hcover : eval i ^-1' ({xi} : Set (X i)) subseq ?_0 G)
  (hstrict : forall A in G, not eval i ^-1' ({xi} : Set (X i)) subseq A) :
  (univ : Set (forall j, X j)) subseq ?_0 G := by
  intro f _
  obtain <A, hAG, hfA> := mem_sUnion.1 (hcover (update_mem_eval_singleton f i xi))
  obtain <i_2, U, -, rfl> := hG hAG
  have hU : U != univ := by
    intro hU
    exact hstrict _ hAG (by simp [hU])
  have hne : i != i_2 := by
    intro hii
    subst hii
    have : (eval i ^-1' ({xi} : Set (X i)) I eval i ^-1' U).Nonempty :=
      <update f i xi, update_mem_eval_singleton f i xi, hfA>
    have hxi : xi in U := eval_singleton_inter_mem this
    exact hstrict _ hAG ((eval_singleton_subset_eval_same).2 hxi)
  exact mem_sUnion.2
    <eval i_2 ^-1' U, hAG, (mem_preimage_eval_update_iff hne).1 hfA>

/-- **Mizar `Th20`.** Failure of finite product covers forces a fiber cover to
use a member that contains the fiber. -/
theorem exists_cylinder_containing_fiber_of_finite [DecidableEq ?]
  [forall j, Nonempty (X j)] {i : ?} {xi : X i} {F : Set (Set (forall j, X j))}
  (hF : F subseq cylinderSubbasis X)
  (hno : forall G subseq F, G.Finite -> not (univ : Set (forall j, X j)) subseq
    ?_0 G)
  {G : Set (Set (forall j, X j))} (hGF : G subseq F) (hGfin : G.Finite)
  (hcover : eval i ^-1' ({xi} : Set (X i)) subseq ?_0 G) :
  exists A in G, eval i ^-1' ({xi} : Set (X i)) subseq A := by
  by_contra h
  have hstrict : forall A in G, not eval i ^-1' ({xi} : Set (X i)) subseq A := by
    simpa [not_exists] using h
  exact hno G hGF hGfin
    (univ_subset_sUnion_of_fiber_cover_no_strict (Subset.trans hGF hF) hcover

```

```

hstrict)

/-- **Mizar `Th21`.** Extract a proper open cylinder on the same axis from a
finite fiber cover. -/
theorem exists_proper_open_cylinder_of_fiber_cover [DecidableEq ?]
  [forall j, Nonempty (X j)] {i : ?} {xi : X i} {F : Set (Set (forall j, X j))}
  (hF : F ⊆ cylinderSubbasis X)
  (hno : forall G ⊆ F, G.Finite → not (univ : Set (forall j, X j)) ⊆ ?_0 G)
  {G : Set (Set (forall j, X j))} (hGF : G ⊆ F) (hGfin : G.Finite)
  (hcover : eval i ^-1' ({xi} : Set (X i)) ⊆ ?_0 G) :
  exists U : Set (X i), U != univ /\ xi in U /\ IsOpen U /\ eval i ^-1' U in G
  := by
  obtain <A, hAG, hsub> :=
    exists_cylinder_containing_fiber_of_finite hF hno hGF hGfin hcover
  have hAne : A != univ := by
    intro hA
    exact hno G hGF hGfin (fun _ _ => mem_sUnion.2 <A, hAG, by simp [hA]>)
  obtain <U, hUe, hxi, hUo, rfl> :=
    cylinder_of_singleton_subset (hF (hGF hAG)) hsub hAne
  exact <U, hUe, hxi, hUo, hAG>

/-- **Mizar `Th22`.** Compactness of a factor, plus no finite product cover,
produces a point whose singleton fiber also has no finite cover from `F`. -/
theorem exists_point_fiber_not_finitely_covered [DecidableEq ?]
  [forall j, Nonempty (X j)] {i : ?} {F : Set (Set (forall j, X j))}
  (hF : F ⊆ cylinderSubbasis X)
  (hcomp : IsCompact (univ : Set (X i)))
  (hno : forall G ⊆ F, G.Finite → not (univ : Set (forall j, X j)) ⊆ ?_0 G) :
  exists xi : X i, forall G ⊆ F, G.Finite →
    not eval i ^-1' ({xi} : Set (X i)) ⊆ ?_0 G := by
  by_contra! h
  have : forall xi : X i, exists U : Set (X i),
    xi in U /\ IsOpen U /\ eval i ^-1' U in F := by
    intro xi
    obtain <G, hGF, hGfin, hcover> := h xi
    obtain <U, -, hxi, hUo, hUG> :=
      exists_proper_open_cylinder_of_fiber_cover hF hno hGF hGfin hcover
    exact <U, hxi, hUo, hGF hUG>
  choose U hxi hUo hUF using this
  have hcover_i : (univ : Set (X i)) ⊆ ? xi : X i, U xi := by
    intro xi _
    exact mem_iUnion.2 <xi, hxi xi>
  obtain <t, ht> :=
    (isCompact_iff_finite_subcover.1 hcomp) U hUo hcover_i
  let G : Set (Set (forall j, X j)) := (fun xi : X i => eval i ^-1' U xi) '' (t : Set (X i))
  have hGF : G ⊆ F := by
    rintro _ <xi, -, rfl>
    exact hUF xi
  have hGfin : G.Finite := (t.finite_toSet).image _
  have hGcover : (univ : Set (forall j, X j)) ⊆ ?_0 G := by
    intro f _
    obtain <xi, hxit, hfU> := mem_iUnion.2.1 (ht (mem_univ (f i)))
    exact mem_sUnion.2 <eval i ^-1' U xi, <xi, hxit, rfl>, hfU>
  exact hno G hGF hGfin hGcover

/-! ## The Tychonoff theorem -/

/-- **Mizar Tichonov Theorem, set form.** An arbitrary product of compact
sets is compact. -/
theorem yellow17_tychonoff_sets {s : forall i, Set (X i)}
  (hs : forall i, IsCompact (s i)) :

```

```

    IsCompact (univ.pi s) :=
    isCompact_univ_pi hs

/-- **Mizar Tichonov Theorem.** A dependent product of compact spaces is
compact. -/
theorem yellow17_tychonoff [forall i, CompactSpace (X i)] :
  CompactSpace (forall i, X i) :=
  inferInstance

/-- Space-level form matching the Mizar statement: if each factor is compact,
then the product is compact. -/
theorem yellow17_tychonoff' (h : forall i, CompactSpace (X i)) :
  CompactSpace (forall i, X i) :=
  let _ := h
  inferInstance

end Yellow17

```