



Finite-Valuation Approximable Structures, Quantum λ -Calculus, and the Jung–Tix Problem: Semantics and Formal Verification in Lean 4

Abstract

We develop a Lean 4 framework toward denotational semantics for an untyped λ -calculus with probabilistic, internal, and external choice, controlled by finite quantum instruments. Inspired by Chen, Kou, and Lyu’s finite-valuation approximable structures, we define $\omega\mathbf{QVA}$ by requiring its approximate identity to factor through finite products of sub-normalized density-operator spaces with the Loewner order. The finite spectrahedra are approximation factors; they are not themselves a quantum powerdomain $\mathcal{Q}(D)$. We prove a parameterized inverse-limit theorem and instantiate its hypotheses with the fixed-register continuation power $\mathcal{Q}_n(D) = [[D \rightarrow R_n] \rightarrow R_n]$. Finite trace-nonincreasing CP instruments embed into this carrier through Scott-continuous token-local aggregation. The embedding preserves deterministic return exactly and agrees with finite map and bind on finitely presented continuations. Embedding order recovers every rational TT test having an explicit Scott representation; a global order equivalence would require an additional density theorem. We also isolate the obstruction to a finite-image Scott retract: any such retract would force the finite image to be closed under nonempty directed suprema. Thus the semantic domain and its physical finite fragment are constructed, while computation-valued term interpretation, the operational semantics and adequacy theorem, and the three choice algebras remain future semantic layers.

1. Introduction and Background

The Scott–Strachey programme for denotational semantics models computation in untyped λ -calculus by solving reflexive domain equations of the form $D \cong [D \rightarrow D]$. In concurrent and

non-deterministic computation, powerdomains (Plotkin, Smyth, Hoare) model internal non-determinism ($\sqcap$) and external interactive choice ($\sqbox$). In probabilistic extensions (pCSP) and higher-order probabilistic programming, randomized branching is quantified via the subprobability valuation powerdomain $\mathcal{V}_{\leq 1}$.

Giving a rigorous denotational semantics to untyped higher-order languages with probabilistic choice requires solving recursive domain equations of the form:

$$D \cong [D \rightarrow \mathcal{P}(\mathcal{V}_{\leq 1}(D))]$$

This requires a category that is simultaneously **Cartesian closed** (to interpret function spaces $[D \rightarrow \dots]$) and **closed under $\mathcal{V}_{\leq 1}$** . In 1998, Achim Jung and Regina Tix identified a persistent obstruction: standard Cartesian closed categories of continuous domains (such as bifinite domains, RB-domains, and FS-domains) were not known to be preserved by $\mathcal{V}_{\leq 1}$.

In August 2026, Chen, Kou, and Lyu resolved the Jung–Tix problem by introducing the category $\omega\mathbf{FVA}$ (Finite-Valuation Approximable domains), establishing the first full Cartesian closed subcategory of continuous domains closed under $\mathcal{V}_{\leq 1}$ and $\mathcal{V}_1$.

2. Syntactic Extension: Untyped λ -Calculus with Choice Operators

We extend the untyped λ -calculus with the three canonical choice operators from concurrent and probabilistic process calculi:

$$M, N ::= x \mid \lambda x.M \mid M N \mid M \oplus_p N \mid M \sqcap N \mid M \sqbox N$$

```
graph TD
    A["Computational Divergence & Choice"] --> B["Probabilistic Choice (M ⊕_p N)"]
    A --> C["Internal Choice (M ⊔ N)"]
    A --> D["External Choice (M ⊓ N)"]
    B --> B1["Resolved by coin of weight p ∈ [0,1]"]
    C --> C1["Resolved by internal demonic scheduler"]
    D --> D1["Resolved by environment / communication trigger"]
```

The Three Choice Operators

1. Probabilistic Choice ($M \oplus_p N$):

- **Behavior:** A coin weighted by $p \in [0, 1]$ is flipped at reduction time; the term reduces to M with probability p and to N with probability $1 - p$.
- **Found in:** Probabilistic λ -calculus, Probabilistic PCF (Plotkin 1989, Jones 1990, Dal Lago, Ehrhard et al.).

2. Internal Nondeterministic Choice ($M \sqcap N$ or $M \oplus N$):

- **Behavior:** Unpredictable, unobservable scheduling or arbitrary choice between two functions/expressions.
- **Found in:** De'Liguoro–Piperno's non-deterministic λ -calculus, Boudol's concurrent λ -calculus.

3. External / Interactive Choice ($M \sqcap N$ or Guarded Selection):

- **Behavior:** Waiting for the environment (e.g., awaiting a message on a communication channel or waiting for an argument/input event).
- **Canonical functional equivalent:** The `select` construct in Concurrent ML (CML) or guarded alternative evaluation:

$$\text{sync}(\text{receive}(c_1) \Rightarrow \lambda x.M \sqcap \text{receive}(c_2) \Rightarrow \lambda y.N)$$

To give this calculus a denotational semantics, one must solve:

$$D \cong [D \rightarrow \mathcal{P}(\mathcal{V}_{\leq 1}(D))]$$

where $[D \rightarrow \dots]$ models higher-order functions, $\mathcal{P}$ models internal choice ($\sqcap$), and $\mathcal{V}_{\leq 1}$ models probabilistic choice ($\oplus_p$).

3. Solving Recursive Domain Equations in $\omega\mathbf{FVA}$

The category $\omega\mathbf{FVA}$ consists of continuous domains D whose identity map is the directed supremum of an increasing sequence of maps factoring through subprobability valuation spaces over finite posets P_n :

$$D \xrightarrow{p_n} \mathcal{V}_{\leq 1}(P_n) \xrightarrow{e_n} D, \quad \sup_{n \in \mathbb{N}} (e_n \circ p_n) = \text{id}_D$$

The Smyth–Plotkin embedding-projection (e - p) method proceeds in five steps:

sequenceDiagram participant D0 as $D_0 = \{\perp\}$ participant Dn as $D_n \in \omega\mathbf{FVA}$ participant Dinf as $D_\infty = \text{colim } D_n$ participant Funct as $F(D_\infty) = [D_\infty \rightarrow \mathcal{V}_{\leq 1}(D_\infty)]$ D0->>Dn: Inductive Functor Application $F(D_n)$ Dn->>Dinf: Bilimit / Inverse Limit Formation Note over Dinf: Saturation Theorem (Thm 6.7(ii)) Dinf->>Dinf: Proves $D_\infty \in \omega\mathbf{FVA}$ Dinf->>Funct: Isomorphism $D_\infty \cong F(D_\infty)$

Step 1: Establish the Ambient Cartesian Closed Category ($\omega\mathbf{FVA}$)

By Theorem 10.4 of Chen–Kou–Lyu (2026):

- **Initial / Pointed Object:** $\perp \in D$ exists for all $D \in \omega\mathbf{FVA}$, and the terminal domain $\mathbb{I} = \{\perp\} = \mathcal{V}_{\leq 1}(\emptyset)$ is in $\omega\mathbf{FVA}$.
- **Cartesian Closure:** If $X, Y \in \omega\mathbf{FVA}$, then $[X \rightarrow Y] \in \omega\mathbf{FVA}$.
- **Probabilistic Closure:** If $X \in \omega\mathbf{FVA}$, then $\mathcal{V}_{\leq 1}(X) \in \omega\mathbf{FVA}$ and $\mathcal{V}_1(X) \in \omega\mathbf{FVA}$.

Therefore, the mixed-variance endofunctor $F(X) = [X \rightarrow \mathcal{V}_{\leq 1}(X)]$ is well-defined internally on $\omega\mathbf{FVA}$.

Step 2: Build the Approximation Chain via Embedding-Projection Pairs

An embedding-projection pair (e, p) satisfies $p \circ e = \text{id}_X$ and $e \circ p \leq \text{id}_Y$.

- **Base stage:** $D_0 = \{\perp\}$.
- **Inductive stages:** $D_{n+1} = F(D_n) = [D_n \rightarrow \mathcal{V}_{\leq 1}(D_n)] \in \omega\mathbf{FVA}$.
- **Lifting:**

$$e_{n+1} = F(e_n, p_n) = [p_n \rightarrow \mathcal{V}_{\leq 1}(e_n)] : D_{n+1} \rightarrow D_{n+2}$$

$$p_{n+1} = F(p_n, e_n) = [e_n \rightarrow \mathcal{V}_{\leq 1}(p_n)] : D_{n+2} \rightarrow D_{n+1}$$

yielding the expanding chain: $D_0 \hookrightarrow D_1 \hookrightarrow D_2 \hookrightarrow \dots \hookrightarrow D_n \hookrightarrow \dots$

Step 3: Take the Bilimit / Colimit D_∞

In **DCPO**, the bilimit is the standard inverse limit:

$$D_\infty = \left\{ (x_n)_{n \in \mathbb{N}} \in \prod_{n \in \mathbb{N}} D_n \mid \forall n, x_n = p_n(x_{n+1}) \right\}$$

equipped with canonical limiting pairs $(e_n^\infty : D_n \rightarrow D_\infty, p_n^\infty : D_\infty \rightarrow D_n)$ satisfying $p_n^\infty \circ e_n^\infty = \text{id}_{D_n}$, $e_n^\infty \circ p_n^\infty \leq e_{n+1}^\infty \circ p_{n+1}^\infty \leq \text{id}_{D_\infty}$, and $\sup_{n \in \mathbb{N}} (e_n^\infty \circ p_n^\infty) = \text{id}_{D_\infty}$.

Step 4: Proving $D_\infty \in \omega\mathbf{FVA}$ (The Saturation Theorem)

By Theorem 6.7(ii) (Unified Kernel-Lifting / Saturation Theorem):

If D is a domain with an increasing sequence $a_n = e_n p_n \leq \text{id}_D$ such that $\sup_n a_n = \text{id}_D$ factoring through $B_n \in \omega\mathbf{FVA}$, then $D \in \omega\mathbf{FVA}$.

Setting $B_n = D_n \in \omega\mathbf{FVA}$ and $a_n = e_n^\infty \circ p_n^\infty$, Theorem 6.7(ii) guarantees $D_\infty \in \omega\mathbf{FVA}$.

Step 5: Establish the Isomorphism $D_\infty \cong [D_\infty \rightarrow \mathcal{V}_{\leq 1}(D_\infty)]$

Because F preserves directed suprema of embedding-projection pairs:

$$F(D_\infty) = F(\text{colim}_n D_n) \cong \text{colim}_n F(D_n) = \text{colim}_n D_{n+1} \cong D_\infty$$

Thus, $D_\infty \cong [D_\infty \rightarrow \mathcal{V}_{\leq 1}(D_\infty)]$ in $\omega\mathbf{FVA}$.

4. Comparison: $\omega\mathbf{FVA}$ vs. Equillogical Spaces ($\mathbf{Equ}$)

In the late 1990s, semanticists recognized that continuous domains (**CONT**) failed Cartesian closure and that standard CCC subclasses were not closed under probabilistic valuations. This led to two historical pathways:

graph TD
 A["The 1990s Dilemma: Higher-Order + Probability"] --> B["Strategy A: Categorical Escape"]
 A --> C["Strategy B: Domain Repair from Within"]
 B --> B1["Equillogical Spaces (Equ) - Bauer, Scott"]
 B1 --> B2["Enlarge universe to Quasitoposes via PERs"]
 C --> C1[" $\omega\mathbf{FVA}$ - Chen, Kou, Lyu (2026)"]
 C1 --> C2["Finite-valuation factorizations within continuous dcpos"]

- 1. **Strategy A — Equillogical Spaces ($\mathbf{Equ}$):** Formed by pairs $(X, \sim)$ of T_0 spaces with equivalence relations. $\mathbf{Equ}$ is a quasitopos (locally Cartesian closed, handles quotients and sheaves). The trade-off is losing concrete order-theoretic approximations and working with realizers.
- 2. **Strategy B — $\omega\mathbf{FVA}$:** Retains pure continuous dcpos with Scott topologies and the way-below relation ($\ll$). It resolves the obstruction by replacing finite-image deflations with finite-valuation factorizations $(D \rightarrow \mathcal{V}_{\leq 1}(P_n) \rightarrow D)$.
- 3. **Categorical Embedding:** Every countably based domain in $\omega\mathbf{FVA}$ embeds fully and faithfully into $\mathbf{Equ}$ as $(D, =_D)$:

$$\omega\mathbf{FVA} \hookrightarrow \omega\mathbf{FS}_{\perp} \hookrightarrow \mathbf{Equ}$$

Comparison Table

Feature	Equillogical Spaces ($\mathbf{Equ}$)	Finite-Valuation Domains ($\omega\mathbf{FVA}$)
Mathematical Nature	Topological spaces + Equivalence relations (Quasitopos)	Partially ordered sets (Continuous DCPOs / FS-domains)
Cartesian Closed?	Yes (by categorical design)	Yes (Theorem 10.4)
Probabilistic Monads?	Yes (via realizability/sheaves)	Yes ($\mathcal{V}_{\leq 1}, \mathcal{V}_1$ are internal functors)

Feature	Equilogical Spaces (Equ)	Finite-Valuation Domains ($\omega\mathbf{FVA}$)
Approximation Theory	Realizers / Moduli of continuity	Way-below relation ($\ll$) & finite posets P_n
Philosophical Role	Higher-order probability in topological/categorical logic	Higher-order probability in classical domain theory

5. The Quantum Extension: From Classical Probability to $\omega\mathbf{QVA}$

In quantum mechanics, unitary evolution creates coherent superposition, while measurement turns that coherence into a classical distribution of outcomes. For a computational-basis measurement,

$$\alpha|0\rangle + \beta|1\rangle \xrightarrow{\{\rho \mapsto P_i \rho P_i\}_{i=0,1}} \begin{cases} 0 & \text{with probability } |\alpha|^2, \\ 1 & \text{with probability } |\beta|^2. \end{cases}$$

The superposition before measurement is not the probabilistic term $M \oplus_p N$: the latter denotes classical randomized control. Internal scheduler choice $M \sqcap N$ and external guarded choice $M \sqcap N$ are two further, independent effects. They do not occur as successive stages after measurement.

The No-Cloning Barrier and the LNL Architecture

Because the **No-Cloning Theorem** ($|\psi\rangle \not\rightarrow |\psi\rangle \otimes |\psi\rangle$) forbids diagonal copy maps $\Delta = \langle \text{id}, \text{id} \rangle$, pure quantum states cannot live directly in a Cartesian Closed Category. Instead, following Selinger and Valiron (2006/2009), we employ a **Linear-Nonlinear (LNL) / Monadic architecture**:

```
graph LR
    subgraph "Higher-Order Control Layer (Cartesian Closed Category:  $\omega\mathbf{QVA}$ )"
        CC["Functions, Recursion, Closures, Post-Measurement  $\oplus_p$ "]
    end
    subgraph "Quantum Computation Monad Q"
        QD["Finite registers, CP trace-nonincreasing maps, instruments"]
    end
    CC --> |Monad Q| QD
```

Generalizing to $\omega\mathbf{QVA}$

We generalize the Chen–Kou–Lyu construction from commutative probability simplices to non-commutative density operator spaces:

graph LR A["Classical $\omega\mathbf{FVA}$ "] -->|Generalization| B["Quantum $\omega\mathbf{QVA}$ "] A1["Finite Posets P "] --> B1["Finite-dim C^* -Algebras $A = \oplus M_d(\mathbb{C})$ "] A2["Simplex $\Delta_{\leq 1}(P)$ "] --> B2["Density Matrices $S_{\leq 1}(A)$ "] A3["Stochastic Order $\leq_{st}$ "] --> B3["Loewner Order $\leq_L$ ($A \leq_L B \leftrightarrow B - A \geq 0$)"] A4["Convex Polytopes"] --> B4["Convex Spectrahedra"] A5["Frontier Erosion Φ^t "] --> B5["Spectral Projection Depletion Φ^t "]

1. **Finite State Spaces:** Let $A = \bigoplus_{k=1}^m M_{d_k}(\mathbb{C})$. Its sub-normalized density operator space is $\mathcal{S}_{\leq 1}(A) = \{\rho \in A_+^* \mid \text{Tr}(\rho) \leq 1\}$ equipped with the Loewner partial order $\rho \leq_L \sigma \iff \sigma - \rho \geq 0$.
2. **Spectral Depletion Semigroup:** For $\rho = \sum \lambda_i E_i$, $\Phi_t(\rho)$ scales down maximal eigenspace projections, preserving the Loewner order ($\rho \leq_L \sigma \implies \Phi_t(\rho) \leq_L \Phi_t(\sigma)$) and establishing that $\mathcal{S}_{\leq 1}(A)$ is an FS-domain.
3. **Definition ($\omega\mathbf{QVA}$):** A domain D is in $\omega\mathbf{QVA}$ if $\text{id}_D = \sup_n a_n$ where each a_n factors through $\mathcal{S}_{\leq 1}(A_n)$ for finite-dimensional C^* -algebras A_n .
4. **Saturation:** The 2-level flattening lemma (Lemma 6.6) depends only on way-below interpolation ($\ll$) and finite separation, so the bilimit $D_\infty = \text{colim}_n D_n$ lies in $\omega\mathbf{QVA}$. The isomorphism $D_\infty \cong [D_\infty \rightarrow \mathcal{Q}(D_\infty)]$ additionally requires a locally continuous endofunctor $\mathcal{Q}$ on $\omega\mathbf{QVA}$.

The surviving roadmap

The development separates the construction of the semantic domain from the semantics of a language. The broad roadmap that survived formal proof is:

1. **Ambient domain theory — complete.** Define $\omega\mathbf{QVA}$, prove Cartesian closure, prove closure of countable rounded theories, and solve the parameterized inverse-limit equation.
2. **Concrete quantum effect — complete for a fixed register.** Construct the continuation power

$$\mathcal{Q}_n(D) = [[D \rightarrow R_n] \rightarrow R_n]$$

and prove the functor, local-continuity, $\omega\mathbf{QVA}$ -closure, and monad laws required by

`IsQuantumPowerModel` and `IsQuantumMonad` .

3. **Finite physical fragment — complete with explicit boundaries.** Embed finite TNI CP instruments into $\mathcal{Q}_n(D)$; prove exact return and finitely presented map/bind compatibility; prove the represented-test direction of refinement correspondence; and replace the unsupported finite-retract claim by a directed-supremum obstruction theorem.
4. **Language semantics — still open.** Interpret computation-valued terms, define the operational semantics, prove adequacy, and construct probabilistic, internal, and external choice operations compatible with finite instruments.

The word “complete” in items 1–3 refers to the stated Lean interfaces and theorems, not to a complete quantum programming language.

Mini-roadmaps followed during domain construction

From finite CP maps to a countable result domain

The first route through Scott-open indicator observations failed to characterize weakest-precondition refinement. `QLambda/RefinementCounterexample.lean` exhibits a rational qubit counterexample over the four-element Boolean diamond: every cumulative Scott-open Choi observation refines, but a monotone Kraus-valued postcondition separates the instruments.

The replacement roadmap was:

1. restrict rational step-postcondition codes to trace-nonincreasing CP maps;
2. test weakest-precondition Choi matrices by finite conjunctions of strict Gaussian-rational quadratic inequalities;
3. identify finitary TT refinement with preservation of all such atoms and tokens;
4. saturate tokens under semantic entailment and strict strengthening;
5. prove the resulting rounded theory is a continuous lattice and an ω **QVA**.

Strict inequalities are essential: they provide rational interpolation and allow a finite observation at a directed supremum to be witnessed at a finite stage.

From exact pullback to rational local approximation

Exact pullback of a rational Choi test through an arbitrary Kraus family need not remain rational. The successful route therefore used local approximation rather than exact syntactic closure:

1. normalize a `PUnit`-valued finite computation to its total TNI Kraus map;
2. prove uniform bounds for pulled-back Choi functionals on the compact TNI region;
3. approximate each strict functional test by a finite rational quadratic neighbourhood;
4. lift atomwise approximation to finite tokens;
5. use token derivations to extend finite physical operations Scott-continuously to all rounded result theories.

This is implemented across `QLambda/TTResultAlgebra.lean`,
`QLambda/TTResultApproximation.lean`, and `QLambda/TTResultOperations.lean`.

From a failed compactness shortcut to token-local aggregation

An attempted shortcut treated an entire finitely satisfied result theory as compact. That statement is false in general: a finite instrument can satisfy infinitely many increasingly precise rational observations. The corrected proof works one output token at a time. A bind observation yields finitely many branch-local source tokens; directedness supplies one common continuation stage because the instrument has finitely many outcomes. `AggregateDerives`, `aggregateResult`, `aggregateResult_sSup`, and `bindResultScott` then give the required Scott-continuous aggregation without whole-theory compactness.

From an intended order equivalence and retract to the valid boundary

The continuation carrier contains arbitrary Scott-continuous higher-order maps, while the embedding only produces finite-instrument aggregators. Consequently, neither a global order equivalence nor a finite-image retract follows merely from operational agreement on finite presentations.

The proved boundary is explicit:

1. if a source rational TT test is represented by a Scott result postcondition and a finite result continuation, then `embed  $\mu$  ≤ embed  $\nu$` implies preservation of that test;
2. if every test in an output code has such a representation, embedding order implies `FinitaryTTRefines` for that code;
3. any Scott projection fixing and landing in the finite image forces that image to be closed under every nonempty directed supremum;
4. therefore any concrete directed family of finite embeddings with a non-finite supremum rules out such a retraction.

The development does **not** assert the missing density theorem or manufacture a non-closure witness. It records these hypotheses rather than claiming an unconditional equivalence or retract.

Definitions produced by the construction

- `RatTNICPMatrix n` is a Gaussian-rational Choi matrix with positivity and trace-nonincreasing certificates.
- `FiniteInstrumentComp n D` is a finite family of TNI CP branches returning values in `D`.
- `FinitaryTTRefines C μ v` quantifies weakest-precondition refinement over rational finite-step postconditions.
- `TTTokenTheory n C` is the saturated rounded completion of finite strict TT tokens.
- `TTResult n` is the fixed result theory at output type `PUnit`.
- `TTContinuationPower n D` is `ScottMap (ScottMap D (TTResult n)) (TTResult n)`.
- `TTPhysicalEmbedding.embed μ` is the Scott-continuous aggregation transformer induced by the finite instrument `μ`.
- `CodedTestRepresentation C c` packages the Scott representation needed to recover a source test `c` from a result continuation.
- `FiniteImageScottRetraction n D` states precisely what a Scott-continuous projection onto the finite embedded image would require.

Principal theorems and proof ideas

Finitary refinement. `finitaryTTRefines_iff_atom_holds` and `finitaryTTRefines_iff_token_holds` reduce matrix refinement to strict rational quadratic separation. `satisfiedTTTheory_le_iff_finitaryTTRefines` then identifies theory inclusion with the finitary preorder. The forward direction uses Choi monotonicity; the reverse direction separates a failed Loewner inequality by a rational quadratic witness.

Rounded completion and ω QVA. `ttTokenTheory_isContinuousLattice` follows from rounded ideal completion. `RoundedTheory.is0megaQVA` uses finite-prefix membership gates, each factoring through finite products of one-dimensional sub-normalized density spaces, to approximate the identity.

Concrete continuation model. `TTContinuation.model n` satisfies `IsQuantumPowerModel`; the same carrier satisfies `IsQuantumMonad`. Evaluation and precomposition are Scott-continuous, and pointwise directed suprema prove local continuity. Therefore the parameterized theorem

`omegaQVA_quantum_domain_equation_solved` applies and yields

$$D_\infty \cong [D_\infty \rightarrow \mathcal{Q}_n(D_\infty)].$$

Physical embedding. `bindResultScott_satisfied` proves that on a continuation represented by finite result instruments,

$$\text{embed}(\mu)(k) = (\mu \text{ bind } \nu). \text{satisfiedTTTheory}.$$

The proof extracts finitely many branch-local source tokens and extends their semantic derivation to the rounded completion.

Finite monad compatibility. `embed_unit` is exact as an equality of Scott maps.

`embed_bind_unit` and `embed_unit_bind` inherit the continuation monad unit laws.

`embed_map_satisfied` and `embed_bind_satisfied` prove map and Kleisli compatibility on finitely presented result continuations, where physical finite bind has an exact meaning.

Order boundary. `finitaryTTRefines_test_of_embed_le` and

`finitaryTTRefines_of_embed_le` recover represented rational tests from embedding order.

Their proofs evaluate the pointwise Scott-map inequality at the representing continuation and use `satisfiedTTTheory_le_iff_finitaryTTRefines`.

Retract boundary. `finiteImage_directedSupClosed_of_retraction` applies preservation of directed suprema by the proposed Scott projection and its fixed-point law.

`no_finiteImageScottRetraction_of_directedSup_not_finite` turns any future non-closure witness into a contradiction.

Examples and separating cases

1. **Deterministic return.** A one-outcome identity instrument returning `d` embeds exactly as continuation evaluation at `d`: `embed (unit d) = TTContinuation.unit d`.
2. **Finite sequential composition.** When `k e` is the satisfied result theory of a finite continuation at each returned value, evaluating `embed μ` at `k` equals the satisfied theory of physical instrument bind. The map and bind compatibility theorems are obtained by weakest-precondition semantic equivalence.
3. **Why indicator observations are insufficient.** The Boolean-diamond qubit example proves `ObservationRefines μ ν` while `Refines μ ν` fails. Rational CP-valued step

postconditions retain the missing value-dependent quantum information.

4. **Why finite presentations are not assumed compact.** Increasing rational thresholds can approximate a boundary observation indefinitely; token-local witnesses, not a single compact satisfied theory, establish Scott continuity.

Abstract specification and solved domain equation

The finite spectrahedron $\mathcal{S}_{\leq 1}(A)$ is an approximation factor in $\omega\mathbf{QVA}$, not the computation type $\mathcal{Q}(D)$. A quantum power model is instead an assignment Q such that:

1. $Q(D)$ is a complete lattice whenever D is;
2. Q is functorial on Scott maps;
3. Q is order-enriched and locally continuous on monotone $\mathbb{N}$ -families;
4. $D \in \omega\mathbf{QVA}$ implies $Q(D) \in \omega\mathbf{QVA}$.

Let $D_0 \in \omega\mathbf{QVA}$ and let $j_0 : [D_0 \rightarrow Q(D_0)] \rightarrow D_0$ be a continuous-lattice projection. For the inverse limit of $D_{m+1} = [D_m \rightarrow Q(D_m)]$, `omegaQVA_quantum_domain_equation_solved` proves

$$D_\infty \in \omega\mathbf{QVA} \quad \text{and} \quad D_\infty \cong [D_\infty \rightarrow Q(D_\infty)].$$

The mixed tower maps and inverse identities are proved from the specification and instantiate with `TTContinuation.model n`.

Roadmap from the domain to a complete language semantics

The domain construction supplies the space in which a fixed-register untyped quantum language can be interpreted. A complete semantics still requires the following layers, in this order:

1. **Computation-valued term interpretation.** Define environments and compositional denotations for variables, abstraction, application, quantum primitives, measurement, and recursion into the solved domain. Prove substitution, weakening, and Scott continuity of every clause.
2. **Operational semantics.** Give a small-step or evaluation semantics carrying classical outcomes and sub-normalized quantum states, including divergence and dynamic

measurement branches. Prove preservation of trace bounds and compatibility with finite-instrument composition.

3. **Probabilistic, internal, and external choice.** Construct the three operations on `TTContinuationPower`; prove Scott continuity, their algebraic laws, and agreement with the corresponding finite-instrument operations. These are distinct effects and must not be conflated with quantum superposition.
4. **Adequacy.** Relate operational probabilities and conditional post-measurement states to denotational observations. Prove soundness first, then computational adequacy; only after this step should the development claim a complete quantum λ -calculus semantics.

6. Back-and-Forth Operational Correspondence with Qiskit

The tables in this section ground the denotational semantics by relating two operational presentations. They are not intended as a literal compiler specification. Each row is a commuting correspondence

$q\lambda$ construct $\longrightarrow$ CP channel or instrument $\longleftarrow$ Qiskit execution pattern.

For a fixed initial quantum state, the desired equivalence is observational: both sides have the same classical outcome probabilities and, conditioned on an outcome, the same post-measurement quantum state. The quantum forms below are intended primitives extending the classical control syntax of §2; they are not Church encodings. Church booleans remain useful classical data, but they are duplicable and therefore cannot stand for qubits.

Table 1: Quantum primitives with a shared denotation

Concept	Intended $q\lambda$ operational form	Qiskit execution pattern	Shared CP denotation
Prepare $ 0\rangle$	<code>new0(q); M</code>	<code>qc.reset(q)</code> (or a fresh circuit qubit)	Preparation channel with output $ 0\rangle\langle 0 $
Pauli-X	<code>$X(q)$; M</code>	<code>qc.x(q)</code>	$\rho \mapsto X\rho X^\dagger$

Concept	Intended $q\lambda$ operational form	Qiskit execution pattern	Shared CP denotation
Prepare $ 1\rangle$	$\text{new0}(q); X(q); M$	fresh/reset <code>q</code> ; <code>qc.x(q)</code>	Preparation channel with output $ 1\rangle\langle 1 $
Hadamard	$H(q); M$	<code>qc.h(q)</code>	$\rho \mapsto H\rho H^\dagger$; on $ 0\rangle$ the output is coherent $ +\rangle$, not a probabilistic mixture
CNOT	$CX(q, r); M$	<code>qc.cx(q, r)</code>	$\rho \mapsto CX \rho CX^\dagger$
Measurement	measure q with $0 \Rightarrow M \mid 1 \Rightarrow N$	<code>qc.measure(q, c)</code> followed by <code>if_test</code> branches	Instrument $\Phi_i(\rho) = P_i \rho P_i$; probability $\text{Tr}(\Phi_i(\rho))$
Classical probabilistic choice	$M \oplus_p N$	host RNG, or an ancilla rotation followed by measurement and <code>if_test</code>	Branches $p \text{ id}$ and $(1 - p) \text{ id}$ followed by the denotations of M, N

Table 2: Higher-order control and choice

Concept	$q\lambda$ operational role	Qiskit / host-language counterpart	Denotational correspondence
Variable	x is classical data or an opaque register handle	Python parameter, classical value, or register index	Environment lookup; a quantum register is threaded by the instrument semantics rather than copied as a Church value
Abstraction	$\lambda x.M$ packages higher-order	circuit factory, closure, or parameterized	Scott-continuous function producing a computation; not necessarily a unitary

Concept	$q\lambda$ operational role	Qiskit / host- language counterpart	Denotational correspondence
	classical control	subroutine	
Application	$M\ N$ invokes higher-order control	call a factory/ subroutine and compose its result	Evaluation followed by Kleisli/ instrument composition
Probabilistic choice	$M \oplus_p N$ resolves by a classical coin	host RNG or measured ancilla controlling dynamic branches	Convex combination of the two computation denotations
Internal choice	$M \sqcap N$ is selected by an unobservable scheduler	host/runtime scheduler chooses a branch	Nondeterministic powerdomain layer; no fixed 50/50 probability is implied
External choice	$M \sqcap N$ waits for an environment- selected guard/ event	runtime input, callback, or guarded <code>if_test</code>	Environment-indexed family of computations; not inherently a controlled unitary

Thus the “back-and-forth” is between operational realizations at matching semantic layers. Quantum gates and measurements meet as channels and instruments. Untyped λ abstraction and application meet Qiskit through the surrounding classical host language as circuit-producing higher-order control. Some terms require dynamic circuits or runtime interaction rather than one static circuit, but the common denotation still supplies the mental bijection used to guide the formal semantics.

7. Formal Verification in Lean 4 & Capstone Theorem

The formalization is constructed in Lean 4 on top of the `Scott1972` continuous lattice library (<https://github.com/catskillsresearch/scott1972>). Chen–Kou–Lyu-style finite-separation and saturation lemmas are mechanized in `QLambda/Saturation.lean` , and `omegaQVA_closed_under_functionSpace` proves Cartesian closure by finite-separator step-map sampling. `QLambda/QuantumInstrument.lean` develops finite Kraus instruments and proves residual CP refinement equivalent to Choi order. `QLambda/RefinementCounterexample.lean` proves indicator observations too weak for TT refinement. `QLambda/RationalCP.lean` , `QLambda/TT0bservationBasis.lean` , and `QLambda/TTRefinement.lean` replace them by countable physical finitary CP-valued postconditions and prove exact satisfied-theory order correspondence. `QLambda/TTRoundedTheory.lean` forms their saturated continuous completion. `QLambda/RoundedTheory0mega.lean` proves generically that every encodable rounded basis is an $\omega\mathbf{QVA}$ by explicit one-dimensional density factorizations. `QLambda/TTResultAlgebra.lean` , `QLambda/TTResultApproximation.lean` , and `QLambda/TTResult0perations.lean` establish TNI result normalization, rational local approximation, and Scott-continuous token-local aggregation. `QLambda/TTContinuationMonad.lean` defines $\mathcal{Q}_n(D) = [[D \rightarrow R_n] \rightarrow R_n]$, proves every `IsQuantumPowerModel` and `IsQuantumMonad` field, and bundles `TTContinuation.model n` . Finally, `QLambda/TTPhysicalEmbedding.lean` embeds finite physical instruments, proves finite monad compatibility on the precisely stated fragment, proves represented-test refinement recovery, and formalizes the directed-supremum obstruction to a finite-image Scott retract. The remaining work is computation-valued syntax interpretation, operational semantics and adequacy, and the three choice algebras.

```

class IsQuantumPowerModel (Q : (D : Type u) → [CompleteLattice D] → Type u) where
  str : ∀ D [CompleteLattice D], CompleteLattice (Q D)
  map : ∀ {D E} [CompleteLattice D] [CompleteLattice E], ScottMap D E → ScottMap (Q D) (Q E)
  map_id : ...
  map_comp : ...
  map_mono : ...
  map_iSup : ...
  closed : ∀ {D} [CompleteLattice D], IsOmegaQVA D → IsOmegaQVA (Q D)

theorem omegaQVA_quantum_domain_equation_solved
  (M : QuantumPowerModel) (D₀ : QDomain.{u})
  (j₀ : IsContinuousLatticeProjection D₀.carrier (QuantumFunctor M D₀.carrier)) :
  Nonempty (IsOmegaQVA (QDInf M D₀ j₀)) ∧
  ... ∧
  Nonempty (QDInf M D₀ j₀ ≈₀ ScottMap (QDInf M D₀ j₀) (QuantumPower M (QDInf M D₀ j₀)))

structure QuantumOperation (n m : ℕ) where
  kraus : List (Matrix (Fin m) (Fin n) ℂ)
  trace_nonincreasing : ...

structure QuantumInstrument (n m outcomes : ℕ) where
  branch : Fin outcomes → List (Matrix (Fin m) (Fin n) ℂ)
  trace_nonincreasing : ...

structure FiniteInstrumentComp (n : ℕ) (D : Type*) where
  Outcome : Type
  [outcomeFintype : Fintype Outcome]
  branch : Outcome → List (Matrix (Fin n) (Fin n) ℂ)
  value : Outcome → D
  trace_nonincreasing : ...

noncomputable def TTPhysicalEmbedding.embed
  (μ : FiniteInstrumentComp n D) :
  TTContinuationPower n D :=
  TTTOKENTheory.bindResultScott μ

theorem TTPhysicalEmbedding.embed_unit (d : D) :
  embed (FiniteInstrumentComp.unit (n := n) d) =
  TTContinuation.unit (n := n) d

```

8. Acknowledgments & Provenance

- **Software & AI Tooling:** The formalization was mechanized using **Lean 4** and **Mathlib**. The author utilized the **Cursor** development environment, **Grok 4.6 High Fast**, **Gemini 3.7 Flash**, and **GPT-5.6 Sol Medium** as assistive tools for code scaffolding, proof exploration, semantic review, redesign planning, and document drafting.
 - **Integrity Statement:** All formal definitions, proofs, and synthesized results were verified under the Lean 4 compiler. Authors retain full and exclusive responsibility for the mathematical correctness of the mechanized proofs and the contents of this manuscript.
-

References

1. S. Abramsky and B. Coecke. *A categorical semantics of quantum protocols*. In *Proceedings of the 19th Annual IEEE Symposium on Logic in Computer Science (LICS)*, pages 415–425, 2004.
2. P. N. Benton. *A mixed linear and non-linear logic: Proofs, terms and models*. In *Computer Science Logic (CSL)*, LNCS 933, pages 121–135. Springer, 1995.
3. Y. Chen, H. Kou, and Z. Lyu. *Finite-valuation approximable structures: a solution to the Jung–Tix problem of probabilistic powerdomains*. arXiv:2608.03073, 2026.
4. G. Gierz, K. H. Hofmann, K. Keimel, J. D. Lawson, M. Mislove, and D. S. Scott. *Continuous Lattices and Domains*. Cambridge University Press, Cambridge, 2003.
5. C. Jones and G. D. Plotkin. *A probabilistic powerdomain of evaluations*. In *Proceedings of the 4th Annual IEEE Symposium on Logic in Computer Science (LICS)*, pages 186–195, 1989.
6. A. Jung and R. Tix. *The troublesome probabilistic powerdomain*. *Electronic Notes in Theoretical Computer Science*, 13:70–91, 1998.
7. D. S. Scott. *Continuous lattices*. In *Toposes, Algebraic Geometry and Logic*, Lecture Notes in Mathematics, vol. 274, pages 97–136. Springer, Berlin, 1972.
8. P. Selinger and B. Valiron. *A linear-non-linear model for a quantum lambda calculus*. *Information and Computation*, 207(5):603–629, 2009.
9. M. B. Smyth and G. D. Plotkin. *The category-theoretic solution of recursive domain equations*. *SIAM Journal on Computing*, 11(4):761–783, 1982.

10. M. Ying. *Foundations of Quantum Programming*. Morgan Kaufmann / Elsevier, 2016.