

Domain Semantics and Circuit Completeness for a Typed Linear Quantum λ -Calculus Formalized in Lean

4

Lars Warren Ericson¹

¹Catskills Research Company

¹<https://github.com/catskillsresearch/qlambda>

¹lars.ericson@catskillsresearch.com

September 22, 2026

ORCID: 0000-0001-8299-9361

Primary Category: cs.LO (Logic in Computer Science)

Secondary Categories: math.LO (Logic); quant-ph (Quantum Physics)

Abstract

We present a Lean 4 formalization of a typed linear/nonlinear quantum λ -calculus. Separate unrestricted and linear contexts enforce that quantum data cannot be copied or discarded implicitly. The language has linear and unrestricted functions, tensor products, classical bits, qubits, strictly positive recursive types, allocation, unitary gates, reset, and measurement. Probability is not a source-language choice operator: it arises only from quantum measurement.

The semantic target is a type-indexed linear/nonlinear model based on quantum sets, quantum relations, and quantum CPOs. Finite completely positive maps and instruments provide the first-order meanings of gates and measurement, while recursive types are represented by compatible chains of finite unfoldings. A separate finite fragment stages deterministically to a typed circuit normal form and then to a versioned IBM Composer/OpenQASM subset.

The mechanization required detailed proofs for which we found no reusable machine-checked development in the cited quantum-relation and qCPO literature. In particular, we give new Lean proofs that the relevant quantum-relation homs are complete lattices, that relational composition preserves countable joins in both arguments, that daggers reverse composition, that quantum functions compose, and that discrete quantum posets satisfy the quantum-CPO completeness condition. To our knowledge, this is also the first machine-checked construction of the compact-closed quantum-relation structure together with the concrete ordinary adjunction $\mathbf{Set} \rightleftarrows \mathbf{qRel}$ in this representation, and the first certified typed lambda quotation theorem for the declared two-wire Composer fragment. These are novel formal proofs, not claims that every underlying mathematical statement is new; the priority wording is limited by the literature audit described below.

The present theorem boundary is explicit. Source typing, substitution, preservation, runtime progress, measurement normalization, deterministic staging, the quantum-relation enrichment, and structured OpenQASM parse/render round trips are kernel checked. So are the concrete quantum LNL instance, the Scott-function qCPO category, continuous projection-chain fold/unfold maps, and canonical two-wire lambda/circuit completeness. The generic compositional denotation interface and exact operational quotient do not amount to full abstraction or unrestricted computational adequacy for arbitrary recursive programs; we make neither claim. Full sources are at <https://github.com/catskillsresearch/qlambda>.

1 Introduction

Quantum programming combines two incompatible structural regimes. Classical data may be weakened and contracted; unknown quantum data may not be copied, and its disposal must be represented by a physical operation. A semantics that puts both kinds of values in an ordinary Cartesian context obscures this distinction. We instead use a linear/nonlinear judgment

$$\Gamma; \Delta \vdash M : A,$$

where Γ contains unrestricted assumptions and Δ contains exactly-once assumptions. A derivation is intended to denote a morphism

$$F[\Gamma] \otimes [\Delta] \longrightarrow [A]$$

in an ω CPO-enriched LNL model.

This is a typed, type-indexed account. It does not use a universal untyped reflexive object, and it does not put all effects into a central continuation monad. Each admissible recursive type has its own approximation chain. Quantum evolution is represented by linear morphisms; measurement is the source of probabilistic branching.

1.1 Contributions

The development has four connected parts.

1. It gives a Church-style linear/nonlinear quantum λ -calculus with de Bruijn syntax, verified formation predicates for recursive types, substitution, preservation, and a finite-register operational semantics.
2. It formalizes quantum-set and quantum-relation algebra, including complete hom orders, ω -continuous composition, compact closure, the concrete **Set** $\dashv$ **qRel** LNL model, and a separate category of quantum CPOs and Scott-continuous quantum functions.
3. It constructs a deterministic, resource-certified staging procedure from a closed terminating first-order fragment to circuit normal form.
4. It gives canonical typed lambda quotation for a two-wire circuit fragment and a structured Composer/OpenQASM interchange with ideal classical-quantum denotation and canonical parse/render theorems.

The first substantial formalization obligation not available as an off-the-shelf machine-checked library was the enriched algebra of quantum relations. Weaver, Kornell, Jenča–Lindenhovius, and Kornell–Lindenhovius–Mislove prove stronger paper-level categorical results, but provide no Lean implementation of the chosen matrix/subspace representation. We prove the complete hom lattice, bilateral join-continuity of composition, closure of functions under composition, and the discrete-qCPO instance directly. The higher-order development further proves explicit tensor, evaluation/currying, unitors, associator, braiding, and the ordinary strong monoidal adjunction. In particular it does not use the false route from pointwise-ordered continuous maps to graph relations: graph is used from a discretely ordered ordinary set category.

1.2 Scope

“Circuit completeness” means that every circuit in the declared finite target fragment has a canonical well-typed lambda representative. It does not mean that every unitary has an exact

finite decomposition. OpenQASM is an interchange format here, not the denotational semantics, and no result concerns calibration, noise, transpiler heuristics, or arbitrary Python/Qiskit programs.

2 The Typed Linear Language

Types are

$$A, B ::= \alpha \mid 1 \mid \text{Bit} \mid \text{Qubit} \mid A \otimes B \mid A \multimap B \mid A \rightarrow B \mid \mu\alpha.A.$$

The two arrows correspond to linear and unrestricted binders. The term syntax uses lambda as its only binder. Tensor and measurement elimination are continuation based, which avoids adding ad hoc binding constructs.

The physical primitives are fresh- $|0\rangle$ allocation, X , H , T , rational-angle RY , saturated CX , reset, and measurement. Measurement consumes a linear qubit and passes both the classical result and the post-measurement qubit to its continuation. There is no `emit`, source sequencing primitive, probabilistic choice, internal choice, or external choice.

2.1 Contexts and typing

Unrestricted variables may be weakened and contracted. A linear context is a list of optional type cells; context splitting partitions occupied cells while preserving de Bruijn positions. Linear application and tensor introduction split the linear context. An unrestricted closure may not capture live linear resources.

Lean declarations are concentrated in:

- `QLambda/Linear/Syntax.lean`;
- `QLambda/Linear/Context.lean`;
- `QLambda/Linear/Typing.lean`;
- `QLambda/Linear/TypeFormation.lean`.

The executable type checker is connected to the proof-level typing relation. Negative examples include cloning a qubit and capturing a live qubit in an unrestricted function.

2.2 Substitution and source safety

The formal substitution proof distinguishes used and unused linear variables. It includes split rotation, all-`none` transport, linear substitution, and unrestricted substitution with empty linear support. These results imply preservation for deterministic source reduction and for measurement-labelled transitions.

For closed nonrecursive terms, progress yields either a value, a classical step, or a genuine quantum blocking point. It is not the vacuous statement that a primitive is “stuck.”

3 Finite Quantum Runtime

A runtime configuration contains a finite register state, allocated-wire information, an environment, and a typed control stack. Gates act by their canonical matrices. Reset discards and reinitializes one wire. Measurement has two labelled branches whose weights are obtained from the Born rule.

The runtime proves:

- internal-transition preservation;
- measurement-transition preservation;
- nonnegativity and upper bounds of branch probabilities;
- normalization of the two measurement outcomes;
- progress modulo finite-wire exhaustion.

The runtime does not add source-level probability. Probabilities label physical measurement transitions only.

4 Quantum Sets, Relations, and qCPOs

A quantum set X is a family of finite-dimensional Hilbert spaces $(X_x)_{x \in \text{At}(X)}$. A quantum relation $R : X \rightarrow Y$ assigns to each pair (x, y) a complex linear subspace

$$R(x, y) \subseteq \mathcal{L}(X_x, Y_y).$$

Relations are ordered pointwise by inclusion. Composition takes the span of operator products over intermediate atoms, and dagger takes adjoints while reversing atom pairs.

4.1 Formalized relation algebra

`QLambda/Domain/QuantumRel.lean` proves:

$$(T \circ S) \circ R = T \circ (S \circ R), \quad R \circ 1 = R = 1 \circ R,$$

$$(S \circ R)^\dagger = R^\dagger \circ S^\dagger,$$

and

$$\left(\bigvee_n S_n \right) \circ R = \bigvee_n (S_n \circ R), \quad S \circ \left(\bigvee_n R_n \right) = \bigvee_n (S \circ R_n).$$

Each hom is a complete lattice. Consequently quantum sets and quantum relations form an ω CPO-enriched category `qRelCategory`.

A relation is a quantum function when it satisfies the usual dagger inequalities. Comparable quantum functions are equal, and quantum functions are closed under composition. Unitary matrices yield quantum functions, and the formalized H , X , T , RY , and CX matrices agree with their completed-CP presentations.

4.2 Quantum posets and completeness

A quantum poset is a quantum set with a reflexive, transitive, antisymmetric quantum relation. The qCPO condition is stated using increasing sequences of functions from atomic probes. Discrete quantum posets are qCPOs because comparability forces equality, so every such chain is constant. This gives the qubit, classical bit, and tensor-unit objects used by the finite fragment.

`QuantumMonoidal.lean` supplies tensor on homs, internal hom, evaluation, currying, unitors, associator, and braiding, and proves the required ω -supremum laws. `QuantumLNL.lean` packages the resulting concrete model. Its nonlinear category consists of sets and functions with discrete hom orders; classical inclusion is the graph functor and its right adjoint is the set of relations from the tensor unit. This deliberately avoids the non-monotone graph map from pointwise-ordered continuous-function homs.

Separately, `QuantumCPOCategory.lean` packages quantum CPOs and Scott-continuous quantum functions as an ω CPO-enriched category. The formalization does not identify that category with the linear category of the concrete `Set-qRel` adjunction. The published recursive LNL route instead uses the quantum lift monad and its Kleisli category; that construction is not yet present here.

5 Type-Indexed Denotation and Recursive Types

The semantic interface assigns:

$$\llbracket \Gamma; \Delta \rrbracket = F \llbracket \Gamma \rrbracket \otimes \llbracket \Delta \rrbracket.$$

Tensor and arrows are interpreted by the monoidal and closed structure. Primitives carry presentation-independent finite CP classes. Measurement is a finite instrument into a classical sum.

For a strictly positive recursive body $A(\alpha)$, the intended object $\llbracket \mu\alpha.A \rrbracket$ is the bilimit of its finite unfolding chain. `QLambda/Domain/RecursiveTypes.lean` constructs the carrier of compatible approximants and its complete-lattice structure. Dropping and restoring the zeroth approximation define inverse ω -continuous maps, packaged as `ProjectionChain.shiftIso`.

`QLambda/Linear/Denotation.lean` records the exact operations needed by every typing rule, its constructor equations, and presentation-independent finite CP meanings for physical primitives. Classical beta, fix unfolding, and fold/unfold are exact in the operational quotient. We do not conflate that interface with a fully instantiated qCPO denotation or claim unrestricted adequacy: connecting every admissible source-type functor and every primitive to one higher-order qCPO model remains outside the theorem boundary.

6 Deterministic Staging to Circuits

The circuit-normal fragment has statically bounded qubit and classical registers. A prefix allocator produces `Fin q` wire indices and proves freshness, distinctness, and bounds. Fresh-qubit allocation lowers to reset on a fresh physical wire.

Staging is a fuelled call-by-value evaluator. Lambdas, including higher-order gate combinators, execute at staging time. A successful result contains first-order data only. Recursive types and general recursion remain in the language semantics but are excluded from this finite compilation fragment.

Lean proves successful staging is deterministic and preserves source type, resource typing, circuit well-formedness, and allocation bounds. Regression examples include Bell preparation, measurement-controlled gates, reset/reuse, and higher-order gate composition.

7 Circuit Reflection and Completeness

`QLambda/Linear/Circuit.lean` translates between the circuit normal form and the supported Composer block fragment. Compilation preserves ideal CQ denotation. Reflection is total on a proof-carrying supported block, and compilation after reflection returns the original block.

A canonical lambda quotation uses unrestricted binders for classical slots and linear binders for wires. `QuotationGeneral.lean` covers two qubit and two classical registers, including distinct-wire CX , measurement, reset/reuse, store, sequencing, conditionals, and bounded repeat. It excludes the unsupported coin command by an explicit `Quotable` predicate.

The checked capstones have the following meanings:

- `denote_compile`: staging and compilation preserve source denotation;
 - `denote_reflect`: quotation preserves circuit denotation;
 - `compile_reflect`: compiling a canonical representative returns the canonical circuit;
 - `quotation_capstone`: every `Quotable` command has a well-typed canonical lambda representative whose compilation is the original command and whose inherited CQ denotation is equal to the circuit denotation.
-

8 Composer and OpenQASM Interchange

The target is a frozen, versioned AST with finite registers. The supported structured subset includes gates, measurement, reset, classical assignment, conditionals, switches, bounded loops, boxes, and structured loop control where the ideal semantics is defined.

Rendering produces canonical OpenQASM text. Parsing accepts exactly the declared canonical presentation and proves render/parse round trips under the `ParserCanonical` boundary. This is deliberately not a parser for arbitrary OpenQASM 3 text.

Circuit denotation is an ideal classical–quantum instrument. Sequencing is instrument bind; measurement updates a classical slot; structured control is interpreted compositionally. Barriers and delays remain syntax but are identities in the ideal semantics.

9 Mechanized Claims and Release Boundary

The following components are kernel checked without semantic axioms:

- source scope, typing, substitution, preservation, and progress;
- finite-register gate/reset/measurement runtime and normalization;
- pointed ω CPO maps, products, evaluation, currying, and least fixed points;
- complete quantum-relation hom lattices and enriched composition;

- tensor/internal-hom closure and the concrete **Set-qRel** LNL model;
- the category of qCPOs and Scott-continuous quantum functions;
- inverse continuous shift maps for projection-chain bilimits;
- discrete qCPO instances and finite CP/gate presentations;
- deterministic staging with resource certificates;
- circuit/Composer correspondence on the supported block fragment;
- typed lambda quotation and circuit completeness for the declared two-wire fragment;
- structured canonical OpenQASM round trips.

The theorem boundary does not include an equivalence between the checked LNL and qCPO categories, a fully instantiated denotation of every admissible recursive source type, full abstraction, or unrestricted adequacy. It also does not include noisy-device behavior or exact finite synthesis of every unitary. Missing semantic structure is not introduced as an axiom or hidden as a theorem parameter.

10 Related Work and Novelty Qualification

Weaver introduced quantum relations as operator subspaces. Kornell, Lindenhovius, and Mislove developed quantum posets and quantum CPOs and used them for recursive quantum programming. Selinger and Valiron established linear/nonlinear semantic methods for higher-order quantum computation. Pagani, Selinger, and Valiron gave quantitative semantics, and Tsukada and Asada developed enriched presheaf models with strong recursion and full-abstraction results.

Those works are the semantic foundation and prove stronger paper-level results than claimed here: complete relation homs, arbitrary-join-preserving composition, dagger compactness, quantum-function order, qCPO enrichment, and the lifted recursive LNL model all have explicit literature support. Our novelty claim is therefore limited to Lean formalization of the selected representation and its integration with the typed source and finite circuit pipeline. We list exact declarations. Absence of another proof-assistant implementation from the sources checked is not itself a mathematical priority proof.

List of Figures

11 References

- A. Kornell, B. Lindenhovius, and M. Mislove, *Quantum CPOs*, 2021, arXiv:2109.02196.
- N. Weaver, *Quantum relations*, Memoirs of the American Mathematical Society 215(1010), 2012.
- A. Jenča and B. Lindenhovius, *Monoidal Quantaloids*, 2025.
- A. Kornell et al., *A Category of Quantum Posets*, 2023.
- A. Kornell et al., *Categories of Quantum CPOs*, arXiv:2406.01816.
- P. Selinger and B. Valiron, *A lambda calculus for quantum computation with classical control*, Mathematical Structures in Computer Science 16(3), 2006.
- M. Pagani, P. Selinger, and B. Valiron, *Applying quantitative semantics to higher-order quantum computing*, POPL, 2014.
- T. Tsukada and K. Asada, *Enriched presheaf model of quantum FPC*, 2024.

Lean was produced with AI-agent assistance under the author’s direction and review. The trusted proof object is the Lean kernel output, not generated prose or tests.

A Lean module index

Checked by lake build. Repository: <https://github.com/catskillsresearch/qlambda>. Vendored vendor/scott1972 is pinned in vendor/FROZEN.txt.

A.1 QLambda project and Palomar

Role	File
QLambda root import graph	QLambda.lean
QLambda development	QLambda/CQ/Basic.lean
QLambda development	QLambda/CQ/Domain.lean
QLambda development	QLambda/CQ/FiniteSemantics.lean
Composer/OpenQASM interchange	QLambda/Composer/Denotation.lean
Composer/OpenQASM interchange	QLambda/Composer/Fixtures.lean
Composer/OpenQASM interchange	QLambda/Composer/MatrixSemantics.lean
Composer/OpenQASM interchange	QLambda/Composer/Model.lean
Composer/OpenQASM interchange	QLambda/Composer/OpenQASM.lean
Composer/OpenQASM interchange	QLambda/Composer/OpenQASMParser.lean
Composer/OpenQASM interchange	QLambda/Composer/Syntax.lean
Composer/OpenQASM interchange	QLambda/Composer/WellFormed.lean

Role	File
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/DiscreteSet.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/Enriched.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/LinearNonlinear.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/OmegaCPO.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/QuantumCPO.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/QuantumCPOCategory.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/QuantumCategory.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/QuantumClassical.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/QuantumLNL.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/QuantumMonoidal.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/QuantumRel.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/QuantumRelational.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/QuantumSet.lean
Quantum relation, qCPO, and LNL semantics	QLambda/Domain/RecursiveTypes.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Circuit.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Context.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Denotation.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Elaboration.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Examples.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Metatheory.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Operational.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Quotation.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/QuotationGeneral.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/RegFile.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Runtime.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Substitution.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Syntax.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/TypeFormation.lean
Typed linear language, runtime, and circuit correspondence	QLambda/Linear/Typing.lean
QLambda development	QLambda/QuantumInstrument.lean
QLambda development	QLambda/QuantumRuntimeState.lean
QLambda development	QLambda/QuantumStateSpace.lean
Palomar challenge statements	Challenge.lean
Palomar compared solutions	Solution.lean

A.2 Vendored Scott1972 (subset of rows; full tree under vendor/scott1972/)

Role	File
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/Constructions.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/FunctionSpaceTower.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/FunctionSpaces.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/Injective.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/InverseLimits.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/MilnerCorrection.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/ScottMaps.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/Specialization.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/Theorem212.lean
Vendored Scott 1972 foundation	vendor/scott1972/Scott1972/ContinuousLattice/WayBelow.lean

Primary OCR source: [sources/ScottContinLatt1972.md](#) — transcription of [Sco72].

Total indexed: 57 files (46 project + 11 vendor), 18355 lines of Lean.