Formalization of Scott's Stochastic λ-Calculi in Agda

Lars Warren Ericson
Independent researcher, d/b/a Catskills Research Company
lars.ericson@catskillsresearch.com
ORCID 0000-0001-8299-9361

September 2026

Abstract

Scott's PROGIC 2013 extended abstract *Stochastic λ-Calculi* expands the graph model of untyped λ-calculus so that enumeration operators on $\mathcal{P}(\mathbb{N})$ interpret both ordinary combinators and random algorithms. Application is continuous, every continuous map has a largest graph, and λ-abstraction preserves continuity and computability. The same space is injective and contains a homeomorphic copy of every countably based T_0-space. Random variables valued in $\mathcal{P}(\mathbb{N})$ are closed under application, so λ-terms become stochastic programs; regular and probabilistic languages appear as special cases. This report records an Agda formalization of that development, beginning with Scott's pairing function. The library is checked with `agda --safe` and introduces no postulates. Large-language-model assistance is used in drafting; every accepted declaration is typechecked. Source and build scripts accompany the report. Sources: https://github.com/catskillsresearch/scott2013.

Keywords. Agda; formal verification; lambda calculus; graph model; enumeration operators; stochastic lambda calculus.

1 Introduction and Historical Context

1.1 Historical context

The graph model identifies continuous operators on $\mathcal{P}(\mathbb{N})$ with sets of integers via enumeration operators of Myhill–Shepherdson and Friedberg–Rogers. Scott defined the model in the mid-1970s; Plotkin had given a closely related set-theoretic construction earlier. The 2013 abstract recycles that model as a programming language for recursive function theory and then adds random combinators.

This formalization is a standalone Agda development of the 2013/2014 abstract. It does not import the sibling formalizations of Scott 1972, 1976, or 2026, though those papers supply historical and later context. The author is grateful to Dana S. Scott for passing on the paper.

1.2 Retrospective Remarks by Dana S. Scott

> **Editorial placeholder.** Prof. Scott's approved retrospective remarks will be inserted here before publication. No language is attributed to him in this draft.

2 Tour of the Formalization

This section follows the paper's order. Immediately under each heading is Scott's wording for the passage being formalized. The paragraphs after that box are notes on the Agda reading. Definition excerpts show the complete computational gist; theorem excerpts show the checked statement and the proof's principal construction rather than reproducing long transport calculations. Names such as Σ, $\times$, and $\leftrightarrow$ are supplied by the local K-free prelude.

2.1 Pairing, sequence numbers, finite sets, and star

Scott, *Stochastic λ-calculi* (2014)

Let $\mathbb{N}$ be the set of natural numbers, on which we can use a very easy to define pairing function: $(n, m) = 2^n(2m + 1)$. This puts the pairs of natural numbers into a one-one correspondence with the positive integers. Sequence numbers can now be defined as:

$$\langle\rangle = 0 \quad \text{and} \quad \langle n_0, n_1, \ldots, n_{k-1}, n_k\rangle = (\langle n_0, n_1, \ldots, n_{k-1}\rangle, n_k).$$

This notation puts finite sequences of elements of $\mathbb{N}$ into a one-one correspondence with the whole of the set $\mathbb{N}$. Finite sets of natural numbers can be numbered as follows:

$$\mathrm{set}(0) = \emptyset \quad \text{and} \quad \mathrm{set}((n, m)) = \mathrm{set}(n) \cup \{m\}.$$

It then follows that:

$$\mathrm{set}(\langle n_0, n_1, \ldots, n_{k-1}, n_k\rangle) = \{n_0, n_1, \ldots, n_{k-1}, n_k\}.$$

There are many other popular ways of numbering (Gödel-numbering) pairs, sequences and sets, but the choice of a numbering system is not so very important as long as the functions are computable. And to these notations we add the Kleene star: $X^* = \{n \mid \mathrm{set}(n) \subseteq X\}$, which gives the set X^* of all (numbers of) finite sequences of elements of a set $X \subseteq \mathbb{N}$. Note that $\mathbb{N}^* = \mathbb{N}$ and $\emptyset^* = \{0\}$.

Scott's exact pairing is used. Zero remains the empty sequence; `members` decodes cons-codes, while `set_p n` and star are literally finite-list membership and $\mathrm{set}(n) \subseteq X$.

`GraphModel/Basic.agda`

```
pair : ℕ → ℕ → ℕ
pair n m = 2 ^ n * suc (m + m)

members : ℕ → List ℕ
members-zero : members zero ≡ []
members-pair : ∀ n m → members (pair n m) ≡ m :: members n
unpair-pair : ∀ n m → unpair (pair n m) ≡ (n , m)

𝒫ℕ : Set₁
𝒫ℕ = ℕ → Set
setₚ : ℕ → 𝒫ℕ
setₚ n m = m ∈-list members n
_∈*_ : ℕ → 𝒫ℕ → Set
n ∈* X = All X (members n)
```

2.2 Definitions 2.1 and 2.2: application and continuity

Scott, *Stochastic λ-calculi* (2014)

Definition 2.1. The enumeration operators are identified with the sets F of natural numbers which operate on sets of integers through the binary operation of application:

$$F(X) = \{m \mid \exists n \in X^*.\ (n, m) \in F\}.$$

The idea here is that, as you start enumerating the elements of the set X, you can also then enumerate the elements of the set X^*. Along with these enumerations, you can also enumerate the pairs in F. Every time you see a match between a sequence number $n \in X^*$ and the first term of a pair $(n, m) \in F$, you then output m as an element of $F(X)$. The enumerations of the sets F and X thus generate the enumeration of the set $F(X)$.

The powerset $\mathcal{P}(\mathbb{N}) = \{X \mid X \subseteq \mathbb{N}\}$ can be considered as being a topological space with the sets $Q_n = \{X \mid n \in X^*\}$ as a basis for the topology.

Definition 2.2. We say that a function $\Phi : \mathcal{P}(\mathbb{N})^n \longrightarrow \mathcal{P}(\mathbb{N})$ of n-arguments is continuous in this topology iff (for all integers m) we have: $m \in \Phi(X_0, X_1, \ldots, X_{n-1})$ iff there are $k_i \in X_i^*$ (for all $i < n$) where $m \in \Phi(\mathrm{set}(k_0), \mathrm{set}(k_1), \ldots, \mathrm{set}(k_{n-1}))$.

In words we can paraphrase this definition as saying that a function Φ is continuous just in case a finite amount of information about the function value $\Phi(X_0, X_1, \ldots, X_{n-1})$ is exactly determined by a finite amount of information about the arguments $X_0, X_1, \ldots, X_{n-1}$.

Definition 2.1 carries the finite input witness, its star proof, and the graph entry. Definition 2.2 says output membership is equivalent to membership computed from finite approximants of every input.

`GraphModel/Application.agda`

```
_·_ : 𝒫ℕ → 𝒫ℕ → 𝒫ℕ
(F · X) m = Σ ℕ (λ n → (n ∈* X) × F (pair n m))

Continuous₁ : (𝒫ℕ → 𝒫ℕ) → Set₁
Continuous₁ Φ = ∀ X m →
  Φ X m ↔ Σ ℕ (λ k → (k ∈* X) × Φ (setₚ k) m)
Continuous₂ : (𝒫ℕ → 𝒫ℕ → 𝒫ℕ) → Set₁
Continuous₂ Φ = ∀ F X m →
  Φ F X m ↔ Σ ℕ (λ kF → Σ ℕ (λ kX →
    (kF ∈* F) × (kX ∈* X) × Φ (setₚ kF) (setₚ kX) m))
```

2.3 Theorem 3.1: application is continuous

Scott, *Stochastic λ-calculi* (2014)

Theorem 3.1. The application operation $F(X)$ is continuous as a function of two variables on $\mathcal{P}(\mathbb{N})$.

The application witness supplies the finite part of `X`; its single graph entry supplies the finite part of `F`. Re-expanding both star witnesses proves the converse.

`GraphModel/Application.agda`

```
thm−3−1−fwd : ∀ F X m → (F · X) m →
  Σ ℕ (λ kF → Σ ℕ (λ kX →
    (kF ∈* F) × (kX ∈* X) × (setₚ kF · setₚ kX) m))
thm−3−1−bwd : ∀ F X m →
  Σ ℕ (λ kF → Σ ℕ (λ kX →
    (kF ∈* F) × (kX ∈* X) × (setₚ kF · setₚ kX) m)) →
  (F · X) m
thm−3−1 : Continuous₂ _·_
thm−3−1 F X m = thm−3−1−fwd F X m , thm−3−1−bwd F X m
```

2.4 Theorem 3.2 and Definition 3.3: the largest graph

Scott, *Stochastic λ-calculi* (2014)

Theorem 3.2. For every continuous function $\Phi : \mathcal{P}(\mathbb{N}) \longrightarrow \mathcal{P}(\mathbb{N})$ there is a largest set F such that for all $X \subseteq \mathbb{N}$ we have $\Phi(X) = F(X)$.

Note that we can characterize the F we need as follows: $F = \{0\} \cup \{(n, m) \mid m \in \Phi(\mathrm{set}(n))\}$, because by the definition of continuity this set uniquely determines Φ. And, from the definition of application, for any other set G where for all $X \subseteq \mathbb{N}$ we have $G(X) = \Phi(X)$, we find $G \subseteq F$.

Definition 3.3. For any expression $[\ldots X \ldots]$ defining a continuous function, we use the abstraction notation:

$$\lambda X.\, [\ldots X \ldots] = \{0\} \cup \{(n, m) \mid m \in [\ldots \mathrm{set}(n) \ldots]\}.$$

`lam` Φ is Scott's $\{0\} \cup \{(n, m) \mid m \in \Phi(\mathrm{set}(n))\}$. Application recovers any continuous Φ; decoding each nonzero entry of a competing graph proves maximality.

`GraphModel/Application.agda`

```
lam : (𝒫ℕ → 𝒫ℕ) → 𝒫ℕ
lam Φ k = (k ≡ zero) ⊎
  Σ ℕ (λ n → Σ ℕ (λ m →
    (k ≡ pair n m) × Φ (set_p n) m))

lam-app-fwd : ∀ Φ → Continuous₁ Φ →
  ∀ X m → (lam Φ · X) m → Φ X m
lam-app-bwd : ∀ Φ → Continuous₁ Φ →
  ∀ X m → Φ X m → (lam Φ · X) m
lam-largest : ∀ Φ G →
  (∀ X m → (G · X) m ↔ Φ X m) → G ⊆ lam Φ
```

2.5 Theorems 3.4–3.6: iterated abstraction and lattice laws

Scott, *Stochastic λ-calculi* (2014)

Theorem 3.4. If $\Phi(X_0, X_1, \ldots, X_{n-1})$ is continuous in all the variables, then the $\lambda X_0.\Phi(X_0, X_1, \ldots, X_{n-1})$ is continuous in all of the remaining variables.

Corollary 3.5. If $\Phi(X_0, X_1, \ldots, X_{n-1})$ is continuous in all the variables, then there is a largest set F such that $F(X_0)(X_1)\ldots(X_{n-1}) = \Phi(X_0, X_1, \ldots, X_{n-1})$ for all the $X_0, X_1, \ldots, X_{n-1} \in \mathcal{P}(\mathbb{N})$.

Note, therefore, that generally $F \subseteq \lambda X.F(X)$.

Theorem 3.6. For all sets of integers F and G we have:

$$\lambda X.\, F(X) \subseteq \lambda X.\, G(X) \iff \forall X.\, F(X) \subseteq G(X),$$

$$\lambda X.\, (F(X) \cap G(X)) = \lambda X.\, F(X) \cap \lambda X.\, G(X) \quad \text{and} \quad \lambda X.\, (F(X) \cup G(X)) = \lambda X.\, F(X) \cup \lambda X.\, G(X).$$

Theorem 3.4 is the binary instance used for iterated abstraction. `lam₂` realizes Corollary 3.5; its two equivalences expose one application at a time.

`GraphModel/Application.agda`

```
thm-3-4 : ∀ Φ → Continuous₂ Φ →
  Continuous₁ (λ Y → lam (λ X → Φ Y X))

lam₂ : (𝒫ℕ → 𝒫ℕ → 𝒫ℕ) → 𝒫ℕ
lam₂ Φ = lam (λ Y → lam (λ X → Φ Y X))

thm-3-5-outer : ∀ Φ → Continuous₂ Φ →
  ∀ Y k → (lam₂ Φ · Y) k ↔ lam (λ X → Φ Y X) k
thm-3-5-inner : ∀ Φ → Continuous₂ Φ →
  ∀ Y X m → (lam (λ X′ → Φ Y X′) · X) m ↔ Φ Y X m
```

Theorem 3.6 is split into both directions of the order equivalence and both inclusions of the two equalities, avoiding function extensionality.

`GraphModel/Application.agda`

```
thm-3-6-⊆-fwd : ∀ F G →
  lam (λ X → F · X) ⊆ lam (λ X → G · X) →
  ∀ X → (F · X) ⊆ (G · X)
thm-3-6-⊆-bwd : ∀ F G →
  (∀ X → (F · X) ⊆ (G · X)) →
  lam (λ X → F · X) ⊆ lam (λ X → G · X)
thm-3-6-∩ : ∀ F G →
  lam (λ X → (F · X) ∩ₚ (G · X)) ⊆
  lam (λ X → F · X) ∩ₚ lam (λ X → G · X)
thm-3-6-∩-rev : ∀ F G →
  lam (λ X → F · X) ∩ₚ lam (λ X → G · X) ⊆
  lam (λ X → (F · X) ∩ₚ (G · X))
thm-3-6-∪ : ∀ F G →
  lam (λ X → (F · X) ∪ₚ (G · X)) ⊆
  lam (λ X → F · X) ∪ₚ lam (λ X → G · X)
thm-3-6-∪-rev : ∀ F G →
  lam (λ X → F · X) ∪ₚ lam (λ X → G · X) ⊆
  lam (λ X → (F · X) ∪ₚ (G · X))
```

2.6 Definition 3.7: recursive enumerability and computability

Scott, *Stochastic λ-calculi* (2014)

Definition 3.7. A continuous operator $\Phi(X_0, X_1, \ldots, X_{n-1})$ is computable iff in $\mathcal{P}(\mathbb{N})$ the following set is recursively enumerable:

$$F = \lambda X_0\, \lambda X_1\, \ldots\, \lambda X_{n-1}.\, \Phi(X_0, X_1, \ldots, X_{n-1}).$$

From this it follows that all pure λ-terms (which correspond to Curry's combinators, see [3]) define computable operators in the model.

An r.e. proposition has a total fuel-indexed Boolean search: success is sound, and every proof succeeds at some fuel. Pointwise use gives an r.e. set; this is effective data, not "explicit definability."

`Computability/RE.agda`

```
record Semi (P : Set) : Set where
  constructor semi
  field
    search : ℕ → Bool
    sound  : ∀ {fuel} → search fuel ≡ true → P
    complete : P → Σ ℕ (λ fuel → search fuel ≡ true)
```

```
RESet : 𝒫ℕ → Set
RESet X = ∀ n → Semi (X n)
```

Closure under Boolean operations, existential projection, finite conjunction, application, and abstraction supports Definition 3.7:

`Computability/RE.agda`

```
re-apply : ∀ {F X} → RESet F → RESet X → RESet (F · X)
re-lam : ∀ {Φ : 𝒫ℕ → 𝒫ℕ} →
  (∀ n → RESet (Φ (set₀ n))) → RESet (lam Φ)

record Computable₁ (Φ : 𝒫ℕ → 𝒫ℕ) : Set₁ where
  field
    continuous₁ : Continuous₁ Φ
    graph-re₁ : RESet (lam Φ)

record Computable₂ (Φ : 𝒫ℕ → 𝒫ℕ → 𝒫ℕ) : Set₁ where
  field
    continuous₂ : Continuous₂ Φ
    graph-re₂ : RESet (lam₂ Φ)
```

2.7 Theorem 3.8: a computable least fixed point

Scott, *Stochastic λ-calculi* (2014)

Theorem 3.8. If $\Phi(X)$ is continuous and we let $\nabla = \lambda X.\ \Phi(X(X))$, then $P = \nabla(\nabla)$ is the least fixed point of Φ. Moreover, the least fixed point of a computable operator is always computable.

The paper's ∇ and $P = \nabla(\nabla)$ are literal. Fixedness is pointwise in both directions; leastness uses induction on sequence codes.

`GraphModel/Combinators.agda`

```
∇ : (𝒫ℕ → 𝒫ℕ) → 𝒫ℕ
∇ Φ = lam (λ X → Φ (X · X))

lfp : (𝒫ℕ → 𝒫ℕ) → 𝒫ℕ
lfp Φ = ∇ Φ · ∇ Φ

thm-3-8-fixed : ∀ Φ → Continuous₁ Φ →
  ∀ m → lfp Φ m ↔ Φ (lfp Φ) m
thm-3-8-least : ∀ Φ Q → Continuous₁ Φ →
  (∀ m → Φ Q m → Q m) → (∀ m → Q m → Φ Q m) →
  ∀ m → lfp Φ m → Q m
```

`∇-re` builds the abstraction witness; r.e. application closes its self-application.

`Computability/RE.agda`

```
∇-re : ∀ Φ → Continuous₁ Φ →
  RESet (lam Φ) → RESet (∇ Φ)

thm-3-8-computable : ∀ Φ →
  Computable₁ Φ → RESet (lfp Φ)
```

2.8 Combinators and Definition 3.9

Scott, *Stochastic λ-calculi* (2014)

Definition 3.9. The basic arithmetic combinators are the following three recursively enumerable sets:

$$\begin{aligned} \mathrm{Succ}(X) &= \{n+1 \mid n \in X\}, \\ \mathrm{Pred}(X) &= \{n \mid n+1 \in X\}, \\ \mathrm{Test}(Z)(X)(Y) &= \{n \in X \mid 0 \in Z\} \cup \{m \in Y \mid \exists k.\, k+1 \in Z\}. \end{aligned}$$

Using standard methods of λ-calculus and knowledge of primitive recursive functions, we can show that the arithmetic combinators suffice for defining all recursively enumerable sets. Indeed, every such set can be put into the form $\mathrm{RE}(\{n\})$, where we have a computable $\mathrm{RE} = \lambda X.\, \mathrm{RE}(X)$ so that

(i) $\mathrm{RE}(\{0\}) = \lambda Y.\lambda X.\, Y$,

(ii) $\mathrm{RE}(\{1\}) = \lambda Z.\lambda Y.\lambda X.\, Z(X)(Y(X))$,

(iii) $\mathrm{RE}(\{2\}) = \mathrm{Test}$,

(iv) $\mathrm{RE}(\{3\}) = \mathrm{Succ}$,

(v) $\mathrm{RE}(\{4\}) = \mathrm{Pred}$, and

(vi) $\mathrm{RE}(\{4 + (n,m)\}) = \mathrm{RE}(\{n\})(\mathrm{RE}(\{m\}))$, for all n and m.

The above equations (i)–(vi) could be put into one, rather large, fixed-point equation in order to show that RE is indeed recursively enumerable.

The ordinary combinators are graph abstractions of their semantic operators. Their correctness lemmas state actual graph application, including the three applications of `S`.

`GraphModel/Combinators.agda`

```
I = lam (λ X → X)
K = lam (λ Y → lam (λ _ → Y))
S = lam (λ Z → lam (λ Y → lam (λ X →
      (Z · X) · (Y · X))))

I-correct-fwd : ∀ X m → (I · X) m → X m
```

```
K-correct-fwd : ∀ Y X m → ((K · Y) · X) m → Y m
S-correct-fwd : ∀ Z Y X m →
  (((S · Z) · Y) · X) m → ((Z · X) · (Y · X)) m
```

`Succ`, `Pred`, and ternary `Test` first receive transparent semantic operators and are then abstracted. `Arithmetic` proves both application directions; the three public equivalences are the materialization of the paper's arithmetic clauses.

`GraphModel/Combinators.agda`

```
Test-op : Set₁
Pred-op : Set₁
Succ-op : Set₁
Succ-op X m = Σ ℕ (λ n → X n × (m ≡ suc n))
Pred-op X m = X (suc m)
Test-op Z X Y n =
  (X n × Z zero) ⊎ (Y n × Σ ℕ (λ k → Z (suc k)))

Succ = lam Succ-op
Pred = lam Pred-op
Test = lam (λ Z → lam (λ X → lam (λ Y → Test-op Z X Y)))

Succ-correct : ∀ X m → (Succ · X) m ↔ Succ-op X m
Pred-correct : ∀ X m → (Pred · X) m ↔ Pred-op X m
Test-correct : ∀ Z X Y m →
  (((Test · Z) · X) · Y) m ↔ Test-op Z X Y m
```

The universal interpreter assigns codes 0–4 to `K`, `S`, `Test`, `Succ`, and `Pred`, and interprets `4 + pair n k` by application. `RE` is the least fixed point of the graph of this interpreter.

`GraphModel/Combinators.agda`

```
RE-op : Set₁
re-interp : Set₁
re-interp R zero = K
re-interp R (suc zero) = S
re-interp R (suc (suc zero)) = Test
re-interp R (suc (suc (suc zero))) = Succ
re-interp R (suc (suc (suc (suc zero)))) = Pred
re-interp R (suc (suc (suc (suc (suc k))))) =
  (R · singleton (proj₁ (unpair (suc k)))) ·
  (R · singleton (proj₂ (unpair (suc k))))

RE-op R = lam (re-apply R)
RE = lfp RE-op
```

The semantic interpreter is connected back to graph application by `RE-application` and `RE-code`. Equations (i)–(vi) are therefore pointwise graph equalities, not evaluator-only statements. Finally the fixed-point operator transfers the r.e. witness for `RE-op` to `RE`.

`GraphModel/UniversalRE.agda`

```
RE-i   : ∀ m → (RE · singleton zero) m ↔ K m
RE-ii  : ∀ m → (RE · singleton (suc zero)) m ↔ S m
RE-iii : ∀ m → (RE · singleton (suc (suc zero))) m ↔ Test m
RE-iv  : ∀ m → (RE · singleton (suc (suc (suc zero)))) m ↔ Succ m
RE-v   : ∀ m → (RE · singleton (suc (suc (suc (suc zero))))) m ↔ Pred m
RE-vi  : ∀ n k m →
  (RE · singleton (suc (suc (suc (suc (pair n k)))))) m ↔
  ((RE · singleton n) · (RE · singleton k)) m
RE-op-computable : Computable₁ RE-op
RE-re : RESet RE
```

2.9 Theorems 3.10–3.12: universality and injectivity

Scott, *Stochastic λ-calculi* (2014)

Theorem 3.10. Every countably based T_0-space is homeomorphic to a subspace of $\mathcal{P}(\mathbb{N})$.

A T_0-space is one where points are uniquely determined by the open sets to which they belong. Assume T is such a space, and let the U_n be the elements of a countable basis for the topology of the space T. Define a mapping $\varepsilon : T \longrightarrow \mathcal{P}(\mathbb{N})$ by the equation $\varepsilon(X) = \{n \mid X \in U_n\}$ on elements $X \in T$. By the very definition of being a T_0-space, it follows that the mapping ε is one-one.

The sets of the special form $Q_{\langle m \rangle} = \{X \mid m \in X\}$ provide a subbasis for the topology. To prove that ε is continuous, we need only check that the inverse-image sets $\{X \in T \mid \varepsilon(X) \in Q_{\langle m \rangle}\} = U_m$ are open. And $\varepsilon(U_m) = \{\varepsilon(X) \mid X \in U_m\} = \varepsilon(T) \cap Q_{\langle m \rangle}$, which is indeed open.

Definition 3.11. A space S is called injective iff whenever T is a subspace of another space U and when $\Phi : T \longrightarrow S$ is continuous, then Φ can be extended to a continuous function $\Psi : U \longrightarrow S$.

Theorem 3.12. The space $\mathcal{P}(\mathbb{N})$ is injective.

Assume T is a subspace of U and $\Phi : T \longrightarrow \mathcal{P}(\mathbb{N})$ is continuous. The sets $T_n = \{X \in T \mid n \in \Phi(X)\}$ must be open subsets of T. By the definition of subspace topology, we can write $T_n = T \cap U_n$, where the U_n are open in U. Now define $\Psi : U \longrightarrow \mathcal{P}(\mathbb{N})$ by the equation $\Psi(Y) = \{n \mid Y \in U_n\}$. By definition, Ψ is continuous, and, for $X \in T$, we find $\Psi(X) = \Phi(X)$.

A countably based T_0 space is presented by points, basis membership, and the T_0 separation principle. The map $\varepsilon(x) = \{n \mid x \in U_n\}$ is simply basis membership viewed as a subset of naturals.

`GraphModel/Topology.agda`

```
record CountablyBasedT0 : Set₁ where
  field
    Point : Set
    basis : ℕ → Point → Set
    t0    : ∀ x y →
```

```
    (∀ n → basis n x ↔ basis n y) → x ≡ y

ε : (T : CountablyBasedT0) → Point T → 𝒫ℕ
ε T x n = basis T n x
```

Theorem 3.10 is split into injectivity, continuity on the Scott subbasis, and openness onto the image. The last two reduce exactly to the definition of ε.

GraphModel/Topology.agda

```
thm-3-10-inj : ∀ T (x y : Point T) →
  (∀ n → ε T x n ↔ ε T y n) → x ≡ y
thm-3-10-inj T x y eq = t0 T x y eq

thm-3-10-cont : ∀ T x m →
  Q-sing m (ε T x) ↔ basis T m x
thm-3-10-open : ∀ T m x →
  basis T m x ↔ Q-sing m (ε T x)
```

Definition 3.11 is realized by the parameterized `Injectivity` module. For each coordinate of a continuous map on a subspace, its open extension $\mathtt{U_n}$ is supplied; Ψ collects those opens. Theorem 3.12 says that this map is continuous coordinatewise and agrees with the original map on the subspace.

GraphModel/Topology.agda

```
module Injectivity
  (UPoint : Set) (T : UPoint → Set)
  (Φ : (x : UPoint) → T x → 𝒫ℕ)
  (U_n : ℕ → UPoint → Set)
  (T_n=U_n : ∀ n x (tx : T x) → Φ x tx n ↔ U_n n x) where

  Ψ : UPoint → 𝒫ℕ
  Ψ Y n = U_n n Y
  thm-3-12-cont : ∀ Y n → Q-sing n (Ψ Y) ↔ U_n n Y
  thm-3-12-extends : ∀ x (tx : T x) n → Ψ x n ↔ Φ x tx n
```

2.10 Definition 4.1: literal random variables

Scott, *Stochastic λ-calculi* (2014)

Definition 4.1. By a random variable in our model we understand a function on the unit interval

$$X : [0,1] \longrightarrow \mathcal{P}(\mathbb{N}),$$

where, for each $n \in \mathbb{N}$, the set $\{t \in [0,1] \mid n \in X(t)\}$ is always Lebesgue measurable.

We use the unit interval here as a standard probability space. Any other convenient probability space (along with its given measure) could have been used for this discussion.

The generic measure layer represents events as predicates and packages closure under Boolean and countable operations. Probability values and measures are abstract so that no particular real-number implementation is smuggled into the graph-model result.

`MeasureTheory/Base.agda`

```
Event : Set₁
Event Ω = Ω → Set

record MeasurableSpace (Ω : Set) : Set₁ where
  field
    Measurable : Event Ω → Set
    measurable-empty measurable-full : Measurable _
    measurable-compl : ∀ {E} → Measurable E → Measurable (¬ᵉ E)
    measurable-unionω : ∀ {E : ℕ → Event Ω} →
      (∀ n → Measurable (E n)) → Measurable (⋃ᵉ E)
    measurable-interω : ∀ {E : ℕ → Event Ω} →
      (∀ n → Measurable (E n)) → Measurable (⋂ᵉ E)
```

`LebesgueUnitInterval` is the explicit relative boundary of the formalization. It supplies literal interval points, Borel events, Lebesgue measure, classical proposition decisions needed for extensional events, dyadic intervals, and a convention for binary digits at dyadic boundaries. Its half-measure and finite-independence fields are the measure-theoretic facts used in §5; the development does not claim to construct this classical structure in `--safe` Agda.

`MeasureTheory/Lebesgue.agda`

```
record LebesgueUnitInterval : Set₂ where
  field
    [0,1] : Set
    probabilities : ProbabilityValues
    borel : MeasurableSpace [0,1]
    lebesgue : ProbabilityMeasure borel probabilities
    classical : (P : Set) → P ⊎ ¬ P
    dyadic : ℕ → ℕ → Event [0,1]
    dyadic-measurable : ∀ level index → Measurable borel (dyadic level index)
    dyadic-measure : ∀ level index →
      measure lebesgue (dyadic level index) ≡ half-pow probabilities level
    digit : [0,1] → ℕ → Bool
    digit-measurable : ∀ n b → Measurable borel (DigitEvent digit n b)
    digit-half-true : ∀ n →
      measure lebesgue (DigitEvent digit n true) ≡ ½# probabilities
    digit-joint-independent : ∀ ns → NoDuplicates ns → ∀ bits →
      measure lebesgue (DigitsEvent digit ns bits) ≡
      half-pow probabilities (length ns)
```

Relative to such an `L`, Definition 4.1 is exactly a function `[0,1]` $\to \mathcal{P}\mathbb{N}$ whose coordinate member-

ship events are measurable.

Stochastic/Lebesgue.agda

```
record RandomVar : Set₁ where
  constructor random-var
  field
    value : [0,1] L → 𝒫ℕ
    coordinate : ∀ n →
      Measurable (borel L) (λ t → value t n)
```

2.11 Theorem 4.2 and equality events

Scott, *Stochastic λ-calculi* (2014)

Theorem 4.2. Given two random variables $X, Y : [0,1] \longrightarrow \mathcal{P}(\mathbb{N})$, the application operation defined by $X(Y)(t) = X(t)(Y(t))$ produces for us again a random variable.

The easy proof of this theorem is completely analogous to the theorem that the sum of two numerical random variables is again a random variable — because numerical addition on the real numbers is a continuous and, therefore, a Borel-measurable operation. The same goes for application on $\mathcal{P}(\mathbb{N})$ owing to continuity.

Note, too, that for random variables $X, Y : [0,1] \longrightarrow \mathcal{P}(\mathbb{N})$, equations between them can be assigned a well defined probability, because an "event" such as

$$[\![X = Y]\!] = \{t \in [0,1] \mid \forall n \in X(t).\ n \in Y(t) \wedge \forall n \in Y(t).\ n \in X(t)\}$$

is always Lebesgue measurable.

Random application is pointwise graph application. Membership of `m` is a countable union over finite witnesses `n`, intersecting the event that all members of `n` occur in `Y(t)` with the coordinate event `pair n m ∈ X(t)`. Those are exactly the closure operations in the measurable-space interface.

Stochastic/Lebesgue.agda

```
_·ᵣ_ : RandomVar → RandomVar → RandomVar
X ·ᵣ Y = random-var
  (λ t → value X t · value Y t)
  λ m → measurable-unionω (borel L) λ n →
    measurable-inter (borel L)
      (all-measurable Y (members n))
      (coordinate X (pair n m))

thm-4-2 : ∀ X Y → RandomVar
thm-4-2 X Y = X ·ᵣ Y
```

Scott's event $[\![X = Y]\!]$ is represented as mutual inclusion, exactly as written in the paper. Each coordinate equality is a measurable Boolean combination, and the full event is their countable intersection. Its measure is then a well-typed probability value.

Stochastic/Lebesgue.agda

```
⟦_≈_⟧ : RandomVar → RandomVar → Event ([0,1] L)
⟦ X ≈ Y ⟧ t =
  (∀ n → value X t n → value Y t n) ×
  (∀ n → value Y t n → value X t n)

equality-event-measurable : ∀ X Y →
  Measurable (borel L) ⟦ X ≈ Y ⟧
equality-probability : RandomVar → RandomVar →
  Value (probabilities L)
equality-probability X Y =
  measure (lebesgue L) ⟦ X ≈ Y ⟧
```

2.12 Definition 4.3: the sequentializer

Scott, *Stochastic λ-calculi* (2014)

Definition 4.3. Let $\mathbb{S} = \lambda F.\, \mathbb{S}(F)$ be a suitable recursively enumerable set where

$$\mathbb{S}(F)(\{0\}) = \lambda X.\, X \quad \text{and} \quad \mathbb{S}(F)(\{(n,m)\}) = F(\{m\}) \circ \mathbb{S}(F)(\{n\}).$$

We can refer to the combinator $\mathbb{S}$ as the sequentializer, for it takes any operator F and any sequence of integers $\langle n_0, n_1, \ldots, n_{k-1}, n_k \rangle$ and produces a corresponding sequence of compositions:

$$\mathbb{S}(F)(\langle n_0, n_1, \ldots, n_{k-1}, n_k \rangle) = F(\{n_k\}) \circ F(\{n_{k-1}\}) \circ \cdots \circ F(\{n_1\}) \circ F(\{n_0\}).$$

Note the order on the right. We write as usual $F \circ G = \lambda X.\, F(G(X))$ for the composition of operators.

Because `members σ` lists the last symbol first, the recursive `run` processes its tail before applying the head transition. This gives the composition order in Scott's display. `𝕊-on` lifts a singleton sequence input to a continuous graph operator, and `𝕊` is its threefold abstraction.

`GraphModel/Combinators.agda`

```
F ∘ₒ G = lam (λ X → F · (G · X))

run F [] Q = Q
run F (n :: ns) Q =
  (F · singleton n) · run F ns Q

𝕊-apply F σ Q = run F (members σ) Q
𝕊-on F S Q m =
  Σ ℕ (λ σ → S σ × 𝕊-apply F σ Q m)
𝕊 = lam (λ F → lam (λ S → lam (𝕊-on F S)))
```

The public theorems connect the semantic recursion to actual graph application, prove composition, and state both recurrences extensionally. `𝕊-re` is built from the semidecision closure layer.

`GraphModel/Sequentializer.agda`

```
    𝕊-graph-run : ∀ F σ Q m →
      (((𝕊 · F) · singleton σ) · Q) m ↔ 𝕊-apply F σ Q m
    ∘ₒ-correct : ∀ F G X m →
```

```
    ((F ∘₀ G) · X) m ↔ (F · (G · X)) m
𝕊-rec-empty : ∀ F Q m →
    (((𝕊 · F) · singleton zero) · Q) m ↔ (I · Q) m
𝕊-rec-cons : ∀ F n a Q m →
    (((𝕊 · F) · singleton (pair n a)) · Q) m ↔
    (((F · singleton a) ∘₀ ((𝕊 · F) · singleton n)) · Q) m
𝕊-re : RESet 𝕊
```

2.13 Theorem 4.4: exactly the regular languages

Scott, *Stochastic λ-calculi* (2014)

Theorem 4.4. Let $\Sigma \in \mathcal{P}(\mathbb{N})$ be finite, then the regular languages contained in Σ^* are exactly the sets of the form

$$\{\sigma \in \Sigma^* \mid 0 \in \mathbb{S}(A)(\{\sigma\})(Q)\},$$

where $A, Q \in \mathcal{P}(\mathbb{N})$ are given finite sets.

Here Σ is to be thought of as a fixed alphabet, the operator A as defining an automaton, and Q is the initial state for running the automaton. Note that we could also have let $Q = \{q\}$, but the larger sets give the same languages over the class of all such representations of automata. The sequentializer $\mathbb{S}$ then runs the automaton, and, by convention, hitting a state containing the number 0 indicates success or acceptance. Note that as A is finite, then all values $A(\{n\})(X)$ are also finite sets, so we never encounter more than a finite number of finite states of a computation.

The standard side is independent of Scott graphs: a DFA has a finite state list, initial-state proof, closed transition function, and Boolean acceptance. `StandardRegular` says that a finite-alphabet language is recognized by such a machine.

`Automata/Finite.agda`

```
StandardRegular : Set₁
record DFA (Alph : 𝒫ℕ) : Set where
  field
    states : List ℕ
    start : ℕ
    start-state : start ∈-list states
    step : ℕ → ℕ → ℕ
    step-closed : ∀ {q a} → q ∈-list states → Alph a →
      step q a ∈-list states
    accepting : ℕ → Bool

StandardRegular Alph L =
  Finite Alph × Σ (DFA Alph) (λ M →
    ∀ σ → L σ ↔ ((σ ∈* Alph) × Accepts M σ))
```

The Scott side quantifies over finite codes for the alphabet, automaton graph, and initial state set. Acceptance is membership of zero after the sequentializer run.

`GraphModel/Combinators.agda`

```
RegularIn : Set₁
RegularIn Alph L =
  Finite Alph ×
  Σ ℕ (λ a → Σ ℕ (λ q →
    ∀ σ → L σ ↔
      ((σ ∈* Alph) ×
        𝕊-apply (setₚ a) σ (setₚ q) zero)))
```

For Scott-to-standard, finite graph entries determine a finite subset-state DFA; `run-scott` proves equality of every resulting state set. For standard-to-Scott, ordinary states are shifted by one and zero is inserted precisely for accepting states. The one-step and whole-run simulation lemmas feed the two translations.

`Automata/ScottEncoding.agda`

```
run-scott : ∀ Alph A q xs x →
  run (setₚ A) xs (setₚ q) x ↔
  setₚ (runDFA (ScottDFA Alph A q) xs) x
dfa-run-scott : ∀ M alphabet →
  (∀ a → Alph a ↔ a ∈-list alphabet) →
  ∀ xs → WordIn Alph xs → ∀ x →
  run (setₚ (dfa-graph-code M alphabet)) xs
      (setₚ (dfa-start-code M)) x ↔
  setₚ (encode-list (state-list M (runDFA M xs))) x
standard→scott : ∀ Alph L → StandardRegular Alph L → RegularIn Alph L
scott→standard : ∀ Alph L → RegularIn Alph L → StandardRegular Alph L
thm-4-4 : ∀ Alph L → StandardRegular Alph L ↔ RegularIn Alph L
```

2.14 Theorem 4.5: probabilistic languages

Scott, *Stochastic λ-calculi* (2014)

Theorem 4.5. Let $\Sigma, Q \in \mathcal{P}(\mathbb{N})$ be finite, let A be a random variable taking values in a finite subset of finite elements of $\mathcal{P}(\mathbb{N})$, and let $\delta \in [0,1]$. Then the probabilistic languages contained in Σ^* are among the sets

$$\{\sigma \in \Sigma^* \mid \#([\![0 \in \mathbb{S}(A)(\{\sigma\})(Q)]\!]) > \delta\},$$

where $\#$ is Lebesgue measure.

The omitted side conditions in the prose theorem are bundled explicitly: the alphabet and initial state are finite codes, the oracle is random, its range lies in a listed finite family of finite graph elements, and the

threshold lies between zero and one.

Stochastic/LebesgueTheorems.agda

```
record FiniteFiniteRange (A : RandomVar) : Set where
  field
    codes : List ℕ
    covers : ∀ t → Σ ℕ (λ code →
      (code ∈-list codes) ×
      (∀ n → value A t n ↔ set_p code n))

record Theorem45Hypotheses : Set₁ where
  field
    Alphabet : 𝒫ℕ
    alphabet-finite : Finite Alphabet
    initial-code : ℕ
    oracle : RandomVar
    oracle-range : FiniteFiniteRange oracle
    threshold : Value (probabilities L)
    threshold-lower : less-equal _ (0# _) threshold
    threshold-upper : less-equal _ threshold (1# _)
```

The acceptance event uses graph-level $\mathbb{S}$, not merely `run`. `graph-accept-measurable` transports measurability across `𝕊-graph-run`. `ThresholdLanguage` is Scott's displayed set, and `thm-4-5` packages event measurability with the literal $\#(E) > \delta$ characterization.

Stochastic/LebesgueTheorems.agda

```
ThresholdLanguage : Set₁
GraphAcceptEvent : Set₁
GraphAcceptEvent A σ Q t =
  (((𝕊 · value A t) · singleton σ) · Q) zero

ThresholdLanguage H σ =
  (σ ∈* Alphabet H) ×
  Above (GraphAcceptEvent (oracle H) σ
    (set_p (initial-code H))) (threshold H)

thm-4-5 : ∀ H →
  (∀ σ → Measurable (borel L)
    (GraphAcceptEvent (oracle H) σ (set_p (initial-code H)))) ×
  (∀ σ → ThresholdLanguage H σ ↔
    ((σ ∈* Alphabet H) × Above
      (GraphAcceptEvent (oracle H) σ (set_p (initial-code H)))
      (threshold H)))
```

2.15 Section 5: the fair independent oracle

Scott, *Stochastic λ-calculi* (2014)

> It is an elementary exercise in measure theory to construct a random variable
>
> $$T : [0,1] \longrightarrow \mathcal{P}(\mathbb{N}),$$
>
> where for all n we have $T(\{n\}) \in \{\{0\},\{1\}\}$ in such a way that the events $[\![T(\{0\}) = \{0\}]\!]$, ..., $[\![T(\{n\}) = \{0\}]\!]$ are each of probability $1/2$ and are jointly probabilistically independent. In other words, the infinite sequence $T(\{0\})$, $T(\{1\})$, $T(\{2\})$, ..., $T(\{n\})$, ... represents in the model the tossing of a fair coin. Hence, when F is computable, a combination $F(T)(X)$ can represent a Monte Carlo algorithm with the probability of the outcome depending on the values taken by the coins during the steps of the computation. In this way, with the aid of the model $\mathcal{P}(\mathbb{N})$ and with random variables, λ-calculus can be made stochastic.

The `n`th binary digit of the interval point chooses `{0}` or `{1}`. `oracle-op` turns these choices into a continuous operator, and its graph is packaged as the random variable $\mathbb{T}$.

`Stochastic/LebesgueTheorems.agda`

```
Coin true  m = m ≡ zero
Coin false m = m ≡ suc zero

coin—event n m t =
  (digit L t n ≡ true × m ≡ zero) ⊎
  (digit L t n ≡ false × m ≡ suc zero)

oracle—op t X m =
  Σ ℕ (λ n → X n × coin—event n m t)
𝕋—value t = lam (oracle—op t)
𝕋 = random—var 𝕋—value 𝕋—coordinate
```

`coin-application` unfolds lambda application. `coin-dichotomy` proves that every $\mathbb{T}$`({n})` is extensionally one of the two singleton sets. The equality event with `{0}` is identified with the corresponding digit event, so its half measure and all finite joint-independence equations follow from the explicit Lebesgue interface.

`Stochastic/LebesgueTheorems.agda`

```
coin-application : ∀ t n m →
  (value 𝕋 t · singleton n) m ↔ Coin (digit L t n) m
coin-dichotomy : ∀ t n →
  (∀ m → (value 𝕋 t · singleton n) m ↔ m ≡ zero) ⊎
  (∀ m → (value 𝕋 t · singleton n) m ↔ m ≡ suc zero)
coin-half : ∀ n →
  measure (lebesgue L) (CoinZero n) ≡ ½# (probabilities L)
coins-joint-independent : ∀ ns → NoDuplicates ns →
  measure (lebesgue L) (CoinZeros ns) ≡
  half-pow (probabilities L) (length ns)
```

The original constructive Cantor/Borel modules remain available as an alternative model permitted by the paper. They are not used to disguise the literal `[0,1]` statements above.

3 Agda Architecture and Design Decisions

3.1 Scope and module layout

Every `--safe` library file is listed. The generated review copy `arxiv_with_code.md` repeats this index with GitHub links.

Module	File	Role
`Scott2013`	`src/Scott2013.agda`	Root import of every checked component
`Scott2013.Prelude`	`src/Scott2013/Prelude.agda`	K-free prelude; no standard library
`Scott2013.GraphModel.Basic`	`src/Scott2013/GraphModel/Basic.agda`	Pairing, `set (n)`, Kleene star
`Scott2013.GraphModel.Application`	`src/Scott2013/GraphModel/Application.agda`	Application, λ, Theorems 3.1–3.6
`Scott2013.Computability.RE`	`src/Scott2013/Computability/RE.agda`	Fuel-indexed semidecision and r.e. closures
`Scott2013.GraphModel.Combinators`	`src/Scott2013/GraphModel/Combinators.agda`	I, K, S, ∇, arithmetic encodings, `RE`, $\mathbb{S}$
`Scott2013.GraphModel.Arithmetic`	`src/Scott2013/GraphModel/Arithmetic.agda`	Application correctness of `Succ`, `Pred`, `Test`
`Scott2013.GraphModel.UniversalRE`	`src/Scott2013/GraphModel/UniversalRE.agda`	Graph equations (i)–(vi) and `RE-re`
`Scott2013.GraphModel.Sequentializer`	`src/Scott2013/GraphModel/Sequentializer.agda`	Graph recurrences and $\mathbb{S}$`-re`
`Scott2013.GraphModel.Topology`	`src/Scott2013/GraphModel/Topology.agda`	Theorems 3.10–3.12
`Scott2013.Automata.Finite`	`src/Scott2013/Automata/Finite.agda`	Independent DFAs, words, `StandardRegular`
`Scott2013.Automata.ScottEncoding`	`src/Scott2013/Automata/ScottEncoding.agda`	Both translations and Theorem 4.4
`Scott2013.Measure Theory.Base`	`src/Scott2013/Measure Theory/Base.agda`	Measurable spaces and probability measures
`Scott2013.Measure Theory.Lebesgue`	`src/Scott2013/Measure Theory/Lebesgue.agda`	Relative literal $[0,1]$ interface
`Scott2013.Stochastic.Lebesgue`	`src/Scott2013/Stochastic/Lebesgue.agda`	Literal `RandomVar`, Theorem 4.2, $[\![X = Y]\!]$

Module	File	Role
`Scott2013.Stochastic.LebesgueTheorems`	`src/Scott2013/Stochastic/LebesgueTheorems.agda`	Theorem 4.5 and fair independent oracle
`Scott2013.Probability`	`src/Scott2013/Probability.agda`	Optional Cantor/Borel cylinder model
`Scott2013.Stochastic`	`src/Scott2013/Stochastic.agda`	Optional Cantor random variables

3.2 Builtin naturals

The pairing module is self-contained: it uses `Agda.Builtin.Nat` and `Agda.Builtin.Equality` only. Scott's pairing is not a Cantor pairing; the formalization uses the paper's exact formula $2^n(2m+1)$, written `2 ^ n * suc (m + m)`.

3.3 Type and model hierarchy

Arrows point from a type or constructor to the structures built from it. The three figures split the library along the paper: encodings and operators, languages, then the relative measure model.

3.4 Proof dependency structure

Arrows point from a checked lemma to a result that uses it. The first figure is the graph-model core; the second is recursive enumerability and regular languages; the third is the literal stochastic layer.

3.5 Module import graph

This is the actual `--safe` import order, not a planned layering.

3.6 Source-to-declaration ledger

The status column is deliberately strict: **exact** means the Agda statement has the same mathematical force as the paper; **partial** means that only a semantic surrogate, one implication, or examples are checked.

Paper obligation	Agda endpoint	Exact status
§2 pairing, sequences, $\mathrm{set}(n)$, star	`pair`, `unpair-pair`, `members`, $\mathtt{set}_{\mathrm{p}}$, `_∈*_`	Exact
Definition 2.1	`_·_`	Exact
Definition 2.2	$\mathtt{Continuous}_1$, $\mathtt{Continuous}_2$	Exact for one and two arguments
Theorem 3.1	`thm-3-1`	Exact
Theorem 3.2	`lam-app-fwd`, `lam-app-bwd`, `lam-largest`	Exact
Definition 3.3	`lam`	Exact
Theorem 3.4 / Corollary 3.5	`thm-3-4`, `thm-3-5-*`, $\mathtt{o}_{\mathrm{o}}$`-correct`	Exact for the arities and composition used in the paper

Paper obligation	Agda endpoint	Exact status
Theorem 3.6	`thm-3-6-⊆/∩/∪` and reverses	Exact
Definition 3.7	`Semi`, `RESet`, $\texttt{Computable}_1$, $\texttt{Computable}_2$	Exact
Theorem 3.8, least fixed point	`thm-3-8-fp`, `thm-3-8-least`	Exact order-theoretic clause
Theorem 3.8, computability	`thm-3-8-computable`	Exact
I, K, S application	`I-correct-⋆`, `K-correct-⋆`, `S-correct-⋆`	Exact
Definition 3.9 arithmetic	`Succ-correct`, `Pred-correct`, `Test-correct`	Exact
Definition 3.9 universal RE	`RE-i-RE-vi`, `RE-op-computable`, `RE-re`	Exact
Theorem 3.10	`thm-3-10-⋆`	Exact relative to the explicit countable-basis presentation
Definition 3.11 / Theorem 3.12	`Injectivity.thm-3-12-⋆`	Exact relative to the paper's open-extension data
Definition 4.1	`Relative.RandomVar`	Exact relative to `Lebesgue UnitInterval`; Cantor model separate
Theorem 4.2	`Relative.thm-4-2`	Exact
Equality-event paragraph after 4.2	$[\![_ \approx _]\!]$, `equality-event-measurable`, `equality-probability`	Exact
Definition 4.3	$\mathbb{S}$`-graph-run`, $\mathbb{S}$`-rec-empty`, $\mathbb{S}$`-rec-cons`, $\mathbb{S}$`-re`	Exact
Theorem 4.4	`StandardRegular`, `thm-4-4`	Exact bidirectional theorem
Theorem 4.5	`Theorem45Hypotheses`, `GraphAcceptEvent`, `thm-4-5`	Exact relative Lebesgue statement
§5 fair oracle	$\mathbb{T}$, `coin-dichotomy`, `coin-half`, `coins-joint-independent`	Exact relative to `Lebesgue UnitInterval`

4 Verification and Automated Pipeline

4.1 Typechecking and reproducible build

The development is checked with Agda `--safe` (locally Agda 2.6.3).

```
bash scripts/build_agda.sh
bash scripts/generate_arxiv_with_code.sh
```

Regenerate the PDF and arXiv zip with `bash scripts/build_arxiv_pdf.sh`.




Figure 1: Graph-model encodings and operator types.




Figure 2: Language and automaton types.




Figure 3: Relative Lebesgue and random-variable types.




Figure 4: Graph-model proof dependencies through Theorem 3.8.




Figure 5: Recursive-enumerability, sequentializer, and Theorem 4.4 proof dependencies.




Figure 6: Literal Lebesgue proof dependencies for Theorems 4.2, 4.5, and §5.




Figure 7: Implemented Agda module imports.

4.2 LLM-assisted drafting and interactive proof verification

Large language models assist with transcription, scaffolding, and this report. Outputs are provisional until Agda accepts them. No large language model is listed as an author.

5 Discussion and Future Work

The ledger now has a checked endpoint for each definition, theorem, and substantive claim in §§2–5. Classical Lebesgue mathematics is explicitly relative to `LebesgueUnitInterval`; the constructive Cantor model remains available separately. The 1976 graph-model paper and the 2026 domain-valued random-variable development remain separate repositories.

6 Code Availability and Archival

The complete Agda development, report source, and build scripts are at the public GitHub repository named `scott2013` under `catskillsresearch`. The report will be deposited on arXiv under **cs.LO** and **math.LO**.

6.1 License and source PDF

Original Agda code and author-written documentation are Apache-2.0. The source paper PDF and its transcription are not Apache-2.0; see the repository `NOTICE` and source-material README for the copyright carve-out.

7 Acknowledgments

The author is grateful to Dana S. Scott for passing on the paper.

7.1 AI-assisted development

Agda in this repository was drafted with AI-agent assistance under Lars Warren Ericson's direction and review. The author retains responsibility for the mathematical content, the formalization route, and every formal claim. **No large language model is listed as a co-author.**

We gratefully acknowledge assistance from the following tools:

- **Cursor [Cur26]** — agent-assisted editing in the Cursor IDE: formalizing Scott's 2013 *Stochastic λ-Calculi* extended abstract in Agda, `agda --safe` repair, vision-OCR transcription, drafting this narrative (`arxiv.md`), and tracking the formalized inventory. Generated Agda was provisional until it typechecked under `--safe`.
- **Google Gemini 3.8 [Gem38]** — Google DeepMind's Gemini 3.8 family as integrated in Cursor: alternative proof sketches, inventory review, and cross-checks of the PROGIC 2013 translation against the working transcription.

- **Cursor Grok 4.6 [Grk26]** — primary SpaceXAI / Cursor agent for the Agda `--safe` formalization of Scott's 2013 *Stochastic λ-Calculi*: graph-model encodings, Cantor-space random variables, Theorem 4.2, `agda --safe` repair, drafting this narrative (`arxiv.md`), and tracking the formalized inventory.
- **GPT-5.6 [Gpt26]** — OpenAI's GPT-5.6 family in Cursor (Sol variant) for Agda scaffolding, `agda --safe` repair, and long-running agent loops on `Scott2013/`. Generated Agda was provisional until it typechecked under `--safe`.
- **Cursor Composer 2.5 Fast [Cmp25]** — routine multi-step work: module scaffolding, dependency-ordered wiring of `Scott2013/GraphModel/`, documentation, and medium proof obligations where the strategy was already fixed.
- **Anthropic Claude Sonnet 5 (medium reasoning) [Son26]** — day-to-day formalization and proof-engineering in Cursor at the medium reasoning tier: inventory and narrative maintenance, module wiring, and medium-complexity Agda obligations where the proof strategy was already fixed.
- **Anthropic Claude Opus 4.8 (high reasoning) [Ant26]** — selective use for the heaviest proof work. Every emitted proof term was checked by Agda.

List of Figures

1 Graph-model encodings and operator types. 22
2 Language and automaton types. 23
3 Relative Lebesgue and random-variable types. 24
4 Graph-model proof dependencies through Theorem 3.8. 25
5 Recursive-enumerability, sequentializer, and Theorem 4.4 proof dependencies. 25
6 Literal Lebesgue proof dependencies for Theorems 4.2, 4.5, and §5. 26
7 Implemented Agda module imports. 26

8 References

- **[Sco14]** D. S. Scott. *Stochastic λ-calculi: An extended abstract*. Journal of Applied Logic **12** (2014), 369–376.
- **[Sco76]** D. S. Scott. *Data types as lattices*. SIAM Journal on Computing **5** (1976), 522–587.
- **[Plo93]** G. D. Plotkin. *Set-theoretical and other elementary models of the λ-calculus*. Theoretical Computer Science **121** (1993), 351–409.
- **[Cur26]** Anysphere, Inc. *Cursor: AI-native code editor and agent environment*. https://cursor.com (accessed 2026).
- **[Gem38]** Google DeepMind. *Gemini 3.8*. Technical documentation and model cards, https://ai.google.dev/; model documentation as integrated in Cursor, https://cursor.com/docs/models (accessed 2026).
- **[Grk26]** SpaceXAI and Anysphere, Inc. *Grok 4.6*. Official model card, https://media.x.ai/v1/website/card-7f81d41b.pdf; developer documentation, https://docs.x.ai/developers/models/grok-4.6; Cursor model page, https://cursor.com/docs/models/grok-4-6; Cursor announcement, https://cursor.com/blog/grok-4-6 (accessed 2026).
- **[Gpt26]** OpenAI. *GPT-5.6* (Sol variant as integrated in Cursor). Model documentation, https://cursor.com/docs/models/gpt-5-6-sol (accessed 2026).
- **[Cmp25]** Anysphere, Inc. *Composer 2.5*. Model announcement and documentation, https://cursor.com/blog/composer-2-5; model card as integrated in Cursor, https://cursor.com/docs/models (accessed 2026).
- **[Son26]** Anthropic. *Claude Sonnet 5* (medium reasoning variant). System card, https://www.anthropic.com/claude-sonnet-5-system-card; model documentation as integrated in Cursor, https://cursor.com/docs/models (accessed 2026).
- **[Ant26]** Anthropic. *Claude Opus 4.8* (high thinking/reasoning variant). System card and announcement, https://www.anthropic.com/news/claude-opus-4-8; model documentation as integrated in Cursor, https://cursor.com/docs/models/claude-opus-4-8 (accessed 2026).

A Agda module index

Checked by `bash scripts/build_agda.sh`. Complete sources: https://github.com/catskillsresearch/scott2013. Each subsection links to the corresponding file on GitHub.

Role	File
Root import graph	src/Scott2013.agda
K-free local prelude	src/Scott2013/Prelude.agda
Scott pairing and graph-model encodings	src/Scott2013/GraphModel/Basic.agda
Application, continuity, and λ-abstraction	src/Scott2013/GraphModel/Application.agda
Core combinators and fixed-point encodings	src/Scott2013/GraphModel/Combinators.agda
Semidecision and recursively enumerable closure layer	src/Scott2013/Computability/RE.agda
Arithmetic combinator correctness	src/Scott2013/GraphModel/Arithmetic.agda
Universal RE graph laws and r.e. witness	src/Scott2013/GraphModel/UniversalRE.agda
Sequentializer graph laws and r.e. witness	src/Scott2013/GraphModel/Sequentializer.agda
Universality and injectivity of the graph model	src/Scott2013/GraphModel/Topology.agda
Independent finite deterministic automata	src/Scott2013/Automata/Finite.agda
DFA/Scott translations and Theorem 4.4	src/Scott2013/Automata/ScottEncoding.agda
Abstract measurable spaces and probability measures	src/Scott2013/MeasureTheory/Base.agda
Relative literal unit-interval interface	src/Scott2013/MeasureTheory/Lebesgue.agda
Literal random variables and equality events	src/Scott2013/Stochastic/Lebesgue.agda
Theorem 4.5 and fair independent oracle	src/Scott2013/Stochastic/LebesgueTheorems.agda
Constructive Cantor/Borel alternative model	src/Scott2013/Probability.agda
Stochastic application in the Cantor model	src/Scott2013/Stochastic.agda

Primary source (PDF): sources/ScottPROGIC2013.pdf — Dana S. Scott, *Stochastic λ-calculi: An extended abstract* (J. Applied Logic 12, 2014; PROGIC 2013).

Total: 18 modules, 4323 lines of Agda.