

lista6

Caue

```
library(DBI)
library(RSQLite)
#conexão com SQL
con <- dbConnect(SQLite(), "me315.sqlite")
```

```
SELECT * FROM PRESERVE
```

Table 1: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0

1.

```
SELECT state, MIN(acres) AS acres FROM preserve
GROUP BY state
```

Table 2: 3 records

STATE	acres
AZ	380
MA	4
MT	121

2.

```
SELECT state, MAX(acres) AS acres
FROM preserve
WHERE acres > 10000
GROUP BY state
```

Table 3: 2 records

STATE	acres
AZ	49120
MT	15000

3.

```
SELECT STATE, MAX(ACRES) AS ACRES FROM PRESERVE
WHERE ACRES > 10000
GROUP BY STATE
ORDER BY ACRES DESC
```

Table 4: 2 records

STATE	ACRES
AZ	49120
MT	15000

4.

```
SELECT STATE, PNAME, ACRES
FROM PRESERVE p1
WHERE ACRES = (SELECT MAX(p2.ACRES) FROM PRESERVE p2 WHERE p2.STATE = p1.STATE)
AND ACRES < 25000
```

Table 5: 2 records

STATE	PNAME	ACRES
MA	DAVID H. SMITH	830
MT	PINE BUTTE SWAMP	15000

5.

```
SELECT STATE, MIN(ACRES) AS ACRES
FROM PRESERVE
GROUP BY STATE
HAVING MIN(ACRES) < 100
```

Table 6: 1 records

STATE	ACRES
MA	4

6.

```
SELECT STATE, PNAME, ACRES
FROM PRESERVE p1
WHERE ACRES > 1000
AND ACRES = (SELECT MAX(p2.ACRES) FROM PRESERVE p2 WHERE p2.STATE = p1.STATE AND p2.ACRES > 1000)
AND ACRES < 25000
```

Table 7: 1 records

STATE	PNAME	ACRES
MT	PINE BUTTE SWAMP	15000

7.

```
SELECT STATE, SUM(ACRES) AS TOTAL_ACRES
FROM PRESERVE
GROUP BY STATE
HAVING SUM(ACRES) >= 10000 AND SUM(ACRES) <= 50000
```

Table 8: 1 records

STATE	TOTAL_ACRES
MT	16931

8.

```
SELECT STATE, AVG(ACRES) AS MEDIA_ACRES
FROM PRESERVE
GROUP BY STATE
ORDER BY MEDIA_ACRES DESC
LIMIT 1
```

Table 9: 1 records

STATE	MEDIA_ACRES
AZ	12840

9.

```
SELECT DNO, AVG(SALARY) AS SALARIO_MEDIO
FROM EMPLOYEE
GROUP BY DNO
```

Table 10: 3 records

DNO	SALARIO_MEDIO
10	1200.000
20	4666.667
40	500.000

10.

```
SELECT DNO, SUM(SALARY) AS SOMA_SALARIOS, MAX(SALARY) AS MAIOR_SALARIO, MIN(SALARY) AS MENOR_SALARIO
FROM EMPLOYEE
GROUP BY DNO
```

Table 11: 3 records

DNO	SOMA_SALARIOS	MAIOR_SALARIO	MENOR_SALARIO
10	2400	2000	400
20	14000	9000	2000
40	500	500	500

11.

```
SELECT DNO, COUNT(*) AS QUANTIDADE_FUNCIONARIOS
FROM EMPLOYEE
WHERE DNO <> 40
GROUP BY DNO
```

Table 12: 2 records

DNO	QUANTIDADE_FUNCIONARIOS
10	2
20	3

12.

```
SELECT DNO, COUNT(*) AS QUANTIDADE_FUNCIONARIOS
FROM EMPLOYEE
GROUP BY DNO
HAVING COUNT(*) > 2
```

Table 13: 1 records

DNO	QUANTIDADE_FUNCIONARIOS
20	3

13.

```
SELECT STATE, SUM(ACRES) AS "sum(acres)"
FROM PRESERVE
WHERE STATE IN ('AZ', 'MA', 'MT')
GROUP BY STATE
```

```

UNION ALL

SELECT 'Total', SUM(ACRES)
FROM PRESERVE
WHERE STATE IN ('AZ', 'MA', 'MT')

```

Table 14: 4 records

STATE	sum(acres)
AZ	51360
MA	1760
MT	16931
Total	70051

```

Sys.setenv(TZ = "America/Sao_Paulo")
Sys.time()

```

```
[1] "2026-09-28 19:35:14 -03"
```