

ChimeraLM: a language model enables accurate structural variant detection in whole-genome amplified long-read sequencing

Yangyang Li^{1†}, Qingxiang Guo^{1†}, Rendong Yang^{1,2*}

¹Department of Urology, Northwestern University Feinberg School of Medicine, 303 E Superior St, Chicago, 60611, IL, USA.

²Robert H. Lurie Comprehensive Cancer Center, Northwestern University Feinberg School of Medicine, 675 N St Clair St, Chicago, 60611, IL, USA.

*Corresponding author(s). E-mail(s): rendong.yang@northwestern.edu;

Contributing authors: yangyang.li@northwestern.edu;

qingxiang.guo@northwestern.edu;

[†]These authors contributed equally to this work.

Abstract

Single-cell genomic analysis relies on whole genome amplification (WGA) to generate sufficient DNA for sequencing, yet this process introduces chimera artifacts that manifest as false-positive structural variation (SV) and compromise downstream analyses. Here we present ChimeraLM, an interpretable genomic language model (GLM) that identifies WGA-induced chimera artifacts directly from sequence information. ChimeraLM is trained on matched WGA and bulk long-read sequencing from the same sample, using bulk support to label chimeric reads as amplification-induced artifacts or genuine genomic events. To capture long-range dependencies in variable-length reads, the model integrates Hyena operators with attention pooling. Evaluated on matched WGA and bulk nanopore datasets, ChimeraLM eliminated ~90% of chimeric reads from WGA data, restoring chimeric read proportion to near-bulk levels, whereas existing approaches achieved at most an 8% reduction. Using high-confidence SV call sets derived from matched bulk data as a reference, ChimeraLM removed 92-93% of unsupported SV calls from WGA datasets while retaining 72-92% of bulk-supported SVs. ChimeraLM further normalized SV type distributions toward bulk profiles by suppressing the characteristic inversion bias observed in unprocessed WGA data. Attention-based interpretation indicates that ChimeraLM

concentrates classification evidence at chimeric junctions, demonstrating its ability to learn biologically interpretable features. ChimeraLM provides a general approach for suppressing amplification-induced artifacts, enabling more reliable single-cell SV analysis across long-read platforms.

Keywords: Whole Genome Amplification, Single Cell, Genomic Language Model, Structural Variation

Main

Single-cell and low-input genomics have transformed our ability to resolve biological heterogeneity, enabling the discovery of rare cell states and the reconstruction of clonal evolution in cancer and development [1–3]. However, the limited DNA input (on the order of picograms per cell) makes comprehensive genome-wide profiling technically challenging [4, 5]. Whole genome amplification (WGA) therefore remains a prerequisite for high-coverage sequencing [6–8], yet it introduces systematic errors that compromise genomic fidelity, particularly for structural variation (SV) detection [9–11].

A major source of error in WGA is amplification-induced chimera formation. During this process, highly processive polymerases such as phi29, which is used in multiple displacement amplification (MDA), can switch templates and join discontinuous genomic loci into a single molecule [9–13]. As a result, WGA-based sequencing often produces chimeric reads that constitute a substantial fraction of the data [9]. These artificial sequences frequently create alignment patterns that closely resemble those generated by genuine SVs, including translocations and inversions [10]. Consequently, SV callers that rely on alignment-based signals (e.g., split-read and supplementary alignments) and coverage-derived evidence often misinterpret these amplification artifacts as true rearrangements, inflating false positives and distorting SV spectra [14–22]. This problem is particularly consequential for WGA-based long-read sequencing, which is otherwise well suited for resolving complex SVs at single-cell resolution [23, 24].

Distinguishing genuine genomic rearrangements from WGA-induced chimera artifacts remains a major computational challenge. Existing quality-control approaches typically rely on handcrafted rules or alignment-derived features, such as read orientation signatures or local coverage deviations [11, 13, 25]. However, these heuristics are often sensitive to platform- and protocol-specific variation. Moreover, they cannot capture sequence-level patterns or long-range dependencies within reads. As a result, low-input long-read sequencing remains difficult to deploy in settings where high precision is essential, including somatic mosaicism profiling [26] and validation of CRISPR off-target effects [27].

To address this challenge, we present ChimeraLM, an interpretable genomic language model (GLM) for identifying and filtering WGA-induced artifacts at the single-read level. Unlike existing approaches that rely on handcrafted rules derived from read alignments or sequence-level [11, 13, 25], ChimeraLM formulates artifact detection as a sequence-modeling task and learns discriminative features directly from raw reads [28]. Building on advances in DNA foundation models [29–32], it captures

latent motifs and structural dependencies that generalize across long-read sequencing platforms provided by [Oxford Nanopore Technologies \(ONT\)](#). On [ONT WGA](#) datasets, ChimeraLM reduces chimeric reads by $\sim 90\%$ while preserving 72–92% of bulk-supported [SVs](#), improving [SV](#) validation rates by 8.5- to 11.0-fold and mitigating [WGA](#)-induced biases in [SV](#) type distributions. Together, ChimeraLM provides an effective and interpretable filter for [WGA](#) long-read data, enabling robust [SV](#) discovery in single-cell and low-input genomics.

Results

Overview of ChimeraLM workflow and model architecture

ChimeraLM operates as a post-alignment filtering module within the single-cell long-read sequencing pipeline (Fig. 1a). After base calling and alignment to the reference genome, the resulting read set typically contains a mixture of true chimeric reads that arise from authentic genomic rearrangements and artificial chimeras introduced during [WGA](#). ChimeraLM evaluates all reads with chimeric alignments before variant calling. For each read, the model determines whether the observed chimera reflects a genuine genomic event or a [WGA](#)-induced artifact. This binary classification enables selective removal of artificial chimeric reads while preserving true rearrangements, which improves the accuracy and sensitivity of downstream [SV](#) analyses.

To construct a robust supervised training set, we generated [WGA](#) long-read sequencing data from the human prostate cancer cell line PC3 using the [ONT PromethION](#) platform. For ground-truth calibration, we acquired three matched bulk long-read datasets from unamplified genomic DNA across diverse technologies: [ONT PromethION](#), [ONT MinION](#), and [Pacific Biosciences \(PacBio\) Sequel II](#). Leveraging these references, we established a bulk-supported labeling framework by cross-referencing each [WGA](#) chimeric read against the chimeric alignment structures identified in the unamplified bulk data (Methods; Fig. 1b; Extended Data Fig. 1a). Under this classification scheme, [WGA](#) reads with alignment architectures corroborated by bulk evidence were labeled as genuine genomic events, while those lacking bulk support were classified as [WGA](#)-induced artifacts. To evaluate the model’s ability to generalize across sequencing hardware, we generated an independent [WGA](#) dataset on the [MinION](#) platform, which was reserved exclusively for testing (Extended Data Fig. 1a).

This labeling procedure classified 12,963,576 chimeric reads from the [WGA PromethION](#) dataset into two groups (genuine events and [WGA](#)-induced artifacts) based on bulk support (Extended Data Fig. 1b). Among these, 12,670,396 reads (97.7%) showed no matching alignment structures in any bulk dataset and were labeled as [WGA](#)-induced artifacts. The remaining 293,180 reads (2.3%) had matching structures in at least one bulk dataset, indicating they represent genuine genomic events rather than amplification artifacts, and were labeled as genuine chimeric reads. To construct a balanced training dataset, we retained all 293,180 genuine chimeric reads and randomly subsampled an equal number of [WGA](#)-induced artifacts. We further added 178,748 chimeric reads sampled from the bulk datasets to the genuine-event set, expanding the diversity of bulk-supported chimeric alignment structures used for training. The final




Fig. 1 ChimeraLM workflow and architecture for detecting WGA artifacts. (a) Single-cell genomic workflow and ChimeraLM integration. Single cells are isolated, followed by DNA extraction and WGA. During amplification, WGA-induced chimeric artifacts (red) are generated alongside genuine chimeric reads (green). After base calling and mapping, ChimeraLM classifies reads with chimeric alignments as genuine events or WGA-induced artifacts, enabling downstream SV detection on filtered data. (b) Bulk-supported label generation. Chimeric reads from WGA data are compared against bulk sequencing from the same cell line. Reads with bulk-supported alignment structures are labeled as genuine events (green); reads with no bulk match are labeled as WGA-induced artifacts (red). (c) ChimeraLM architecture. Input DNA sequences (batch size B , sequence length L) are tokenized at single-nucleotide resolution and encoded into hidden states $H \in \mathbb{R}^{L \times 256}$ through DNA encoder (HyenaDNA [29]). Hyena operators capture long-range dependencies. Attention pooling aggregates position-specific features, and multilayer perceptron (MLP) layers with residual connections process pooled representations for binary classification of genuine events and WGA-induced artifacts. (d) Attention pooling mechanism. Attention weights $\alpha \in \mathbb{R}^{L \times 1}$ are computed through linear layers with GELU activation and softmax normalization, assigning importance scores to each position. The weighted sum produces a fixed-dimensional representation $h_{\text{pooled}} \in \mathbb{R}^{256}$. Created with BioRender.com.

labeled dataset comprised 765,108 reads and was split into training (70%), validation (20%), and test (10%) sets using stratified sampling (Extended Data Fig. 1a).

To model these labeled reads, ChimeraLM needs to process long, variable-length DNA sequences at single-nucleotide resolution (Fig. 1c). We therefore built ChimeraLM on HyenaDNA [29], a genomic foundation model pre-trained on diverse DNA sequences. Each read is tokenized at nucleotide resolution and encoded by Hyena operators [33], which capture long-range sequence context without splitting the input. The encoder produces a sequence of hidden states across the full read. To obtain a fixed-length representation for classification, ChimeraLM uses an attention-pooling module that learns position-specific weights and computes a weighted sum over the hidden states (Fig. 1d). The pooled representation is then passed through residual MLP blocks, and a final softmax outputs the probability that a read reflects a genuine event versus a WGA-induced artifact.




Fig. 2 ChimeraLM accurately identifies and removes WGA-induced chimeric artifacts. (a) Classification performance on held-out test data. ChimeraLM achieves recall of 0.95, precision of 0.70, and F1 score of 0.81. (b) Chimeric read reduction across sequencing platforms. Stacked bars show proportions of chimeric (dark teal) and non-chimeric (light teal) reads in bulk, WGA, and ChimeraLM-filtered samples. ChimeraLM reduces chimeric read frequencies from 46.0% to 4.9% (PromethION) and from 23.0% to 1.5% (MinION), approaching bulk levels (2.3% and 2.5%, respectively). (c,d) Benchmarking against existing methods on PromethION (c) and MinION (d). The gray bar indicates the total number of chimeric read on unfiltered WGA data. The blue bar represents the total number of chimeric reads remaining after filtering by each method. ChimeraLM achieves approximately 90% reduction in chimeric reads on both platforms, while 3rd-ChimeraMiner shows no detectable reduction and CADECT shows 8.3% and 4.6% reduction on PromethION and MinION, respectively. SACRA failed to complete due to memory exhaustion (> 500 GB RAM required).

ChimeraLM achieves high accuracy and reduces artifacts to near-bulk levels across platforms

We first benchmarked ChimeraLM using the held-out test split (10%) derived from the bulk-supported labeled dataset (Extended Data Fig. 1a). This test set consists of chimeric reads labeled as genuine events or WGA-induced artifacts based on whether their chimeric alignment structures are supported by matched bulk sequencing. ChimeraLM achieved an F1 score of 0.81, with 0.95 recall and 0.70 precision (Fig. 2a). The high recall indicates that most WGA-induced artifacts are correctly identified for removal, which is important for limiting downstream false-positive SV calls, while the precision confirms that most reads flagged as artifacts are true amplification-induced chimeras rather than genuine genomic events.

We next examined whether applying ChimeraLM filtering would restore chimeric read rates in full PC3 WGA datasets toward the levels observed in bulk sequencing across both PromethION and MinION platforms (Fig. 2b). Bulk sequencing established low baseline chimeric read rates of 2.3% (PromethION) and 2.5% (MinION). In contrast, WGA increased the chimeric read fraction to 46.0% and 23.0%, respectively. After ChimeraLM filtering, chimeric content dropped to 4.9% on PromethION and 1.5% on MinION, corresponding to 10- to 15-fold reductions, while retaining 15.8 million and 5.6 million reads. These post-filtering rates approach the corresponding bulk baselines, indicating effective removal of WGA-induced artifacts while preserving genuine signal.

We compared ChimeraLM against SACRA [25], 3rd-ChimeraMiner [13], and CADECT [11], existing tools for detecting amplification-induced chimeras (Fig. 2c,d). ChimeraLM reduced chimeric reads by ~90% on both platforms, outperforming CADECT (8.3% and 4.6% reduction on PromethION and MinION, respectively), while 3rd-ChimeraMiner showed no detectable reduction. SACRA could not be evaluated due to out-of-memory errors even with 500 GB RAM.

The MinION results further provide an independent test of model generalization, as this MinION WGA dataset was not used during training. ChimeraLM was trained exclusively on PromethION WGA data, yet achieved comparable chimeric read reduction on MinION. This cross-platform generalization indicates that ChimeraLM captures sequence-level features intrinsic to WGA-induced artifacts rather than platform-specific signatures, supporting its potential applicability to additional long-read and potentially short-read sequencing technologies.




Fig. 3 ChimeraLM improves structural variant detection accuracy. (a) Construction of a high-confidence SV reference dataset from bulk PC3 sequencing. Four bulk datasets were integrated: ONT MinION Mk1C, ONT PromethION P2, the CCLE Illumina whole genome sequencing (WGS) dataset, and the PRJNA361315 Illumina WGS dataset. SVs were called independently within each dataset using multiple callers, and events supported by ≥ 2 callers per dataset were retained. SVs were then compared across datasets, and events observed in ≥ 2 of the four bulk datasets were designated as gold-standard SVs. (b,c) SV validation against the gold-standard reference for PromethION (b) and MinION (c). Bars show SV calls supported by the gold standard (dark teal) or unsupported (light teal). (d,e) SV validation against platform-matched long-read bulk sequencing for PromethION (d) and MinION (e), capturing true long-read SVs that may not be represented in the multi-platform reference. Bars show SV calls supported by the platform-matched long-read bulk data (dark teal) or unsupported (light teal). (f) Distribution of SV types for PromethION and MinION datasets across bulk samples, unfiltered WGA, and WGA with ChimeraLM filtering. Unfiltered WGA exhibits an excess of inversion (INV) events, which is substantially reduced following ChimeraLM filtering. Other SV classes, including translocation (TRA), deletion (DEL), duplication (DUP), and insertion (INS), are also shown.

ChimeraLM reduces unsupported structural variant calls

Accurate SV detection from single cells is essential for characterizing genomic diversity and disease mechanisms. However, WGA-induced chimeric artifacts can be misinterpreted as genuine SVs, potentially leading to incorrect biological inferences. To assess the impact of ChimeraLM on SV calling, we compared SV callsets generated from unfiltered WGA reads with those obtained after applying ChimeraLM filtering (WGA + ChimeraLM). Both callsets were evaluated against two complementary bulk-derived references: (i) a stringent gold-standard SV set derived from bulk PC3 DNA through cross-dataset consensus, and (ii) platform-matched long-read bulk SV callsets used as platform-specific references.

We first constructed a high-confidence gold-standard SV set from bulk PC3 DNA by integrating four independent sequencing datasets: ONT PromethION, ONT MinION, and two Illumina short-read WGS datasets from the Cancer Cell Line Encyclopedia (CCLE Illumina WGS [34]) and from a previously published study (PRJNA361315 Illumina WGS [35]) (Fig. 3a; Extended Data Table 1). SVs were called separately within each dataset using multiple SV callers. Events supported by at least two callers within a dataset were retained, and only SVs observed in at least two of the four datasets were designated as gold-standard events.

Relative to this stringent gold standard, unfiltered WGA produced a large number of unsupported SVs. On PromethION, WGA yielded 3,601,099 SV calls, of which only 8,815 (0.24%) overlapped gold-standard events. After ChimeraLM filtering, total calls decreased to 305,570 (a 91.5% reduction) while retaining 8,067 gold-standard events (91.5% retention), increasing the validation rate to 2.64% (11-fold) (Fig. 3b). On MinION, total calls decreased from 451,390 to 38,432 (a 91.5% reduction), while gold-standard-supported events decreased from 7,193 to 6,269, corresponding to 87.2% retention. The validation rate increased from 1.59% to 16.3% (10-fold) (Fig. 3c).

Because the gold standard is intentionally stringent and may exclude true SVs detectable only in long-read data, we next performed platform-matched validation using long-read bulk sequencing from the same platform (Fig. 3d,e). This analysis provides a platform-specific estimate of recall and reduces bias introduced by the strict gold-standard definition. ChimeraLM increased validation rates from 0.38% to 3.24% on PromethION (8.5-fold) and from 1.25% to 12.79% on MinION (10-fold), while retaining 71.9% and 87.1% of bulk-supported events, respectively. Together, these results show that ChimeraLM removes the vast majority of unsupported SV calls while preserving the majority of bulk-supported variants across platforms.

ChimeraLM mitigates WGA-induced SV type biases

Amplification artifacts can profoundly distort the apparent spectrum of SVs, complicating biological interpretation. To quantify these effects, we compared SV-type compositions across bulk, unfiltered WGA, and ChimeraLM-filtered datasets generated on both ONT PromethION and MinION platforms (Fig. 3f). Bulk datasets displayed SV profiles dominated by deletions and insertions, whereas WGA datasets exhibited a striking inflation of inversions, reaching 83.0% on PromethION and 88.3% on MinION. This inversion-heavy signature mirrors previous observations from

single-cell long-read sequencing using PacBio and droplet-based MDA [22], suggesting that many of these events arise from amplification-induced chimeras rather than genuine genomic rearrangements.

To directly assess which SV types are preferentially associated with amplification artifacts, we examined SV calls supported exclusively by reads classified as WGA-derived chimeras. These artifact-supported events were overwhelmingly enriched for inversions, comprising 88.4% on PromethION and 92.4% on MinION (Extended Data Fig. 2). Smaller fractions of deletions, duplications, and insertions were also present, indicating that WGA artifacts inflate not only inversion calls but generate false positives across multiple SV categories.

Applying ChimeraLM substantially reduced these biases. The inversion fraction decreased from 83.0% to 60.7% on PromethION and from 88.3% to 46.2% on MinION, while the relative abundance of deletions and insertions increased toward bulk-like levels (Fig. 3f). By selectively removing artifact-supported events, ChimeraLM suppresses the dominant inversion inflation and reduces spurious calls across SV types, shifting SV-type distributions toward bulk profiles and improving the accuracy and interpretability of single-cell SV analyses [22].




Fig. 4 ChimeraLM attention weights are enriched at chimeric junction regions. (a,b) Attention weight profiles for two representative chimeric reads exhibiting distinct junction configurations. Upper panels show per-position attention weights (blue) with the mean attention across the read indicated by a dashed line. Red vertical lines mark inferred chimeric junction positions, and pink shading denotes the junction-centered region (± 50 bp). Lower panels display read-level alignments, highlighting orientation transitions at the junctions (green, forward orientation; red, reverse-complemented orientation). (c,d) Quantitative comparison of attention weights between junction and non-junction regions. Junction-centered windows show significantly elevated attention weights relative to non-junction regions ($P = 5.3 \times 10^{-14}$ and $P = 6.8 \times 10^{-15}$; Wilcoxon rank-sum test). (e,f) Schematic illustration of WGA-induced chimera formation. During amplification, DNA fragments originating from distant genomic loci can be amplified in either orientation, joining them into a single molecule with discordant orientations, producing inversion-like alignment signatures. The two examples illustrate forward-to-reverse and reverse-to-forward orientation transitions.

Attention visualization reveals interpretable classification features

We examined whether ChimeraLM’s attention weights provide an interpretable signal by focusing on mechanistically relevant regions of chimeric reads, particularly the junctions during WGA (Fig. 4). We inspected two representative chimeric reads exhibiting distinct junction configurations (Fig. 4a,b). In both cases, attention remained relatively flat across most positions but formed sharp, concentrated peaks at the inferred junction regions. These peaks aligned with the read-level breakpoint separating two genomic loci and coincided with an orientation transition between adjacent alignment segments.

To quantify this effect, we compared attention weights within junction-centered windows (± 50 bp) against weights from non-junction regions (Fig. 4c,d). Junction windows showed significantly higher attention weights (Wilcoxon rank-sum test, $P = 5.3 \times 10^{-14}$ and $P = 6.8 \times 10^{-15}$), indicating that ChimeraLM preferentially emphasizes sequence context proximal to chimeric junctions.

This attention enrichment is consistent with the expected structure of WGA-induced chimeras (Fig. 4e,f): DNA fragments from distant loci can be amplified in either orientation and subsequently joined, generating junctions with discordant orientations. Together, these results suggest that ChimeraLM’s attention peaks provide a mechanistically interpretable signal that concentrates classification evidence to junction-proximal sequence positions within individual reads.

Discussion

WGA enables genomic analysis from single cells and other low-input samples, but it also introduces chimeric artifacts that compromise SV detection. ChimeraLM addresses this challenge by classifying chimeric reads as genuine events or WGA-induced artifacts directly from read information, and removing artifacts before variant calling, rather than attempting to correct artifact-driven calls post hoc. Across ONT platforms, ChimeraLM improved data quality at the read and variant levels: it reduced chimeric reads by $\sim 90\%$ while retaining 72–92% of bulk-supported SVs, and it increased the ratio of supported SV calls by 8.5–11.0-fold. Notably, performance generalized from PromethION (used for training) to MinION without platform-specific retraining, suggesting that ChimeraLM captures properties shared by WGA-induced artifacts rather than instrument-specific signatures.

In comparison, existing methods showed limited effectiveness on our ONT WGA datasets. Two tools originally developed and primarily evaluated on PacBio data (SACRA and 3rd-ChimeraMiner) [13, 25] either failed to complete under our evaluation setting (SACRA, > 500 GB RAM) or showed no detectable reduction (3rd-ChimeraMiner), highlighting poor cross-platform generalization. CADECT [11], which was designed for ONT data, achieved only 8.3% and 4.6% reduction on PromethION and MinION, respectively. CADECT detects concatemers via sliding-window self-alignment, an effective strategy for repeat-like structures with internal sequence similarity, but it is not designed to capture the broader diversity of WGA-induced chimeras. Together, these comparisons suggest that rule-based or subtype-specific

heuristics do not comprehensively address amplification-induced chimeras and motivate learning-based models that can extract discriminative sequence signatures without imposing predefined structural assumptions.

ChimeraLM also illustrates the value of deep learning for quality-control problems where conventional alignment- and coverage-derived criteria provide limited resolution. [11, 13, 25, 28]. By learning directly from sequence, ChimeraLM discovers subtle compositional and structural features that separate genuine events from amplification artifacts. The model also offers interpretability through attention visualization: attention weights concentrate at junction regions where template switching joins discordant loci, validating the biological relevance of the learned features. These methodological advances have direct implications for single-cell genomics, where high false-positive rates in WGA data have constrained robust characterization of chromosomal instability, clonal evolution, and SV burden [20, 22, 36]. By improving the signal-to-noise ratio and clarifying SV-type spectra that are otherwise distorted by amplification artifacts, ChimeraLM enables more confident identification of genuine SVs, supporting studies of cancer evolution, developmental biology, and somatic mosaicism where single-cell resolution is essential [26, 27].

Several limitations warrant consideration. First, the current model processes reads independently; integrating contextual features such as coverage or phasing information may further enhance accuracy. Second, regarding computational resources, while central processing unit (CPU) inference is feasible, graphics processing unit (GPU) acceleration is recommended for processing large-scale datasets. Finally, future work should extend validation to diverse cell types, sequencing platforms (e.g., PacBio HiFi), and alternative WGA protocols, including multiple annealing and looping-based amplification cycles (MALBAC) [37], linear amplification via transposon insertion (LIANTI) [5], primary template-directed amplification (PTA) [19], and droplet-based MDA (dMDA) [38]. While the sequence-based approach suggests broad applicability, systematic validation across amplification chemistries is needed to assess generalization limits and optimize performance for specific protocols.

More broadly, ChimeraLM illustrates the potential of GLMs for data quality control. As long-context architectures continue to advance [29], extending the model’s context window to handle megabase-scale inputs could enable artifact detection in more complex genomic structures. This framework could extend to other amplification-dependent technologies, such as cell-free DNA analysis, ancient DNA studies, and low-biomass metagenomics. Furthermore, attention-based interpretability opens opportunities for studying template-switching dynamics, potentially guiding the development of improved amplification protocols. In summary, ChimeraLM provides a practical and interpretable framework for enhancing long-read single-cell genomic fidelity, ensuring that downstream biological insights are derived from genuine SVs rather than technical artifacts.

Methods	553
Cell culture, single-clone preparation, and nanopore sequencing	554
<i>Cell culture and single-clone establishment</i>	555
PC3 prostate cancer cells (ATCC® CRL-1435™) were cultured in RPMI-1640 medium supplemented with 10% fetal bovine serum and 1% penicillin–streptomycin at 37 °C with 5% CO ₂ . To minimize biological heterogeneity, a monoclonal population was established by serial dilution in 96-well plates, ensuring that each culture originated from a single cell. Mycoplasma contamination was routinely tested and confirmed negative prior to DNA extraction.	556
<i>DNA extraction and whole-genome amplification</i>	557
From the monoclonal population, two types of DNA samples were prepared: a bulk (non-amplified) control and ten single-cell MDA-amplified genomes. Bulk high-molecular-weight DNA was extracted using the Monarch® HMW DNA Extraction Kit for Cells & Blood (New England Biolabs). Individual cells were isolated using 1CellDish-60 mm (iBiochips) and amplified using the REPLI-g Advanced DNA Single Cell Kit (Qiagen) following the manufacturer’s protocol. DNA concentration and fragment integrity were assessed with a Qubit 4 fluorometer and Agilent TapeStation (DNA 1000/5000 ScreenTape). Only samples meeting quality standards were used for library construction.	558
<i>Nanopore library preparation and sequencing</i>	559
Libraries were prepared using the ONT Ligation Sequencing Kit V14 (SQK-LSK114) and sequenced on MinION Mk1C or PromethION P2 Solo devices with R10.4.1 flow cells following the manufacturer’s genomic DNA workflow. Because all single-cell samples originated from the same monoclonal lineage, differences between amplified and bulk datasets primarily reflect MDA-induced artifacts rather than biological variation.	560
<i>Basecalling and read processing</i>	561
POD5 files were basecalled using Dorado v0.5.0 with the high-accuracy model <code>dna_r10.4.1_e8.2_400bps_hac@v4.3.0</code> [39]. Reads with mean quality < 10 or length < 500 bp were removed. Adapters and concatemers were trimmed using Cutadapt v4.0 [40] in a two-pass, error-tolerant procedure. Filtered reads were aligned to the GRCh38.p13 reference genome using minimap2 v2.26 (<code>map-ont</code> preset) [41]. BAM files were sorted and indexed using SAMtools v1.16 [42]. Read-length and mapping statistics were computed using NanoPlot v1.46.1 [43]. All samples were processed using identical parameters.	562
<i>Chimeric read identification</i>	563
Chimeric reads were identified from BAM files using supplementary alignment (SA) tags. Reads were classified as chimeric if they (i) were mapped, (ii) contained an SA tag, (iii) were primary alignments (not secondary), and (iv) were not supplementary alignments themselves. This definition counts each chimeric read once using its primary	564

alignment while excluding secondary/supplementary records, thereby avoiding double-counting and reducing ambiguity from low-confidence alignments. Reads lacking SA tags were classified as non-chimeric.

Training data construction

Data generation and sources

To construct the training dataset, we generated WGA and bulk sequencing data from PC3 cells. The WGA sample was amplified and sequenced on the PromethION P2 platform (ONT), while three independent bulk datasets were produced from non-amplified genomic DNA: bulk PromethION P2, bulk MinION Mk1c (ONT), and bulk PacBio. These bulk datasets represent authentic biological sequences free from amplification-induced artifacts. In contrast, WGA sequencing includes both genuine genomic reads and artificial chimeras introduced during the amplification process.

Ground truth annotation and class definition

Ground truth labels were established by systematically comparing chimeric reads from the WGA PromethION P2 dataset against those from the three bulk datasets. For each WGA chimeric read, all alignment segments—defined by their genomic start and end coordinates—were compared to the corresponding segments of bulk chimeric reads. A WGA read was labeled as biological if every segment matched at least one bulk chimeric read within a 1 kb positional tolerance, indicating that the structural configuration is also present in non-amplified DNA. Reads lacking any matching pattern across all bulk datasets were labeled as artificial chimeras, presumed to arise from the amplification process. Additional chimeric reads were randomly sampled from the bulk datasets and labeled as biological, as these reads originate from genuine genomic rearrangements such as true SVs. The final labeled dataset combined the annotated WGA PromethION P2 reads with the subsampled bulk chimeric reads and was subsequently partitioned into training, validation, and test sets as described below.

Dataset partitioning and cross-platform validation

The combined labeled dataset, derived from WGA PromethION P2 and bulk sequencing data, was divided into training (70%), validation (20%), and test (10%) sets using stratified random sampling. These subsets were used respectively for model training, hyperparameter tuning, and performance evaluation on data from the same sequencing platform.

To evaluate cross-platform generalization, the complete WGA MinION Mk1c dataset was reserved. This dataset, generated on a different nanopore platform, was never used during model training or internal testing. This two-level evaluation design allowed us to test whether ChimeraLM captures general sequence features of amplification-induced chimeras rather than platform-specific artifacts.

Model architecture

DNA encoder

ChimeraLM employs the pre-trained HyenaDNA model [29] as its DNA encoder. This model was pre-trained on large-scale genomic data and provides robust sequence representations. DNA sequences are tokenized at single-nucleotide resolution, with each base (A, C, G, T, N) mapped to a unique integer token (7, 8, 9, 10, 11, respectively). Special tokens include [CLS]=0, [PAD]=4, and others for sequence processing. Input sequences are truncated at 32,768 bp or padded to enable batch processing.

For a tokenized input sequence $\mathbf{x} \in \mathbb{Z}^L$, the HyenaDNA generates contextualized hidden representations:

$$\mathbf{H} = \text{HyenaDNA}(\mathbf{x}) \in \mathbb{R}^{L \times 256}$$

where $\mathbf{H} = (\mathbf{h}_1, \mathbf{h}_2, \dots, \mathbf{h}_L)$ represents position-wise hidden states with dimension 256. The Hyena operators [33] efficiently capture both local sequence motifs and long-range dependencies essential for distinguishing biological sequences from chimeric artifacts.

Attention pooling

To aggregate variable-length sequence representations into fixed-size vectors, ChimeraLM implements attention-based pooling. For hidden states $\mathbf{H} \in \mathbb{R}^{L \times 256}$, attention weights are computed through a two-layer network:

$$\mathbf{e} = \text{GELU}(\text{Linear}_{256 \rightarrow 256}(\mathbf{H})) \in \mathbb{R}^{L \times 256}$$

$$\mathbf{s} = \text{Linear}_{256 \rightarrow 1}(\mathbf{e}) \in \mathbb{R}^{L \times 1}$$

$$\boldsymbol{\alpha} = \text{softmax}(\mathbf{s}) \in \mathbb{R}^{L \times 1}$$

The pooled representation is the weighted sum of hidden states:

$$\mathbf{h}_{\text{pooled}} = \sum_{i=1}^L \alpha_i \mathbf{h}_i \in \mathbb{R}^{256}$$

This mechanism assigns learned importance weights to each sequence position, enabling the model to focus on informative regions while accommodating natural variability in read lengths.

Classification head

The pooled representation is processed through a MLP with residual connections. The first layer expands dimensionality:

$$\mathbf{f}_1 = \text{Dropout}_{0.1}(\text{GELU}(\text{Linear}_{256 \rightarrow 512}(\mathbf{h}_{\text{pooled}}))) \in \mathbb{R}^{512}$$

Subsequent residual blocks with input $\mathbf{f}_{\text{in}} \in \mathbb{R}^{512}$ compute:

$$\mathbf{f}_{\text{out}} = \text{Dropout}_{0.1}(\text{Linear}_{512 \rightarrow 512}(\text{GELU}(\text{Linear}_{512 \rightarrow 512}(\mathbf{f}_{\text{in}})))) + \mathbf{f}_{\text{in}}$$

where the skip connection enables stable gradient flow during training. The final layer produces binary classification logits:

$$\mathbf{z} = [z_0, z_1] = \text{Linear}_{512 \rightarrow 2}(\mathbf{f}_{\text{final}}) \in \mathbb{R}^2$$

where z_0 and z_1 represent logits for biological and artificial chimeric classes, respectively. During inference, the predicted class is $\hat{y} = \text{argmax}_{i \in \{0,1\}} z_i$.

Model summary

The complete ChimeraLM pipeline processes DNA sequences through: (1) single-nucleotide tokenization, (2) HyenaDNA backbone encoding to generate contextualized representations, (3) attention pooling to aggregate position-specific features, (4) MLP layers with residual connections to learn classification features, and (5) binary classification output. The entire model with $\sim 4.2\text{M}$ trainable parameters is trained end-to-end using labeled data.

Model training and optimization

Training configuration

ChimeraLM was trained using PyTorch [44] and PyTorch Lightning [45] frameworks. Input sequences were tokenized using the tokenizer with maximum sequence length of 32,768 bp. Sequences longer than this threshold were truncated; shorter sequences were padded to enable batch processing. Training employed mixed-precision computation (bf16) to accelerate training while maintaining numerical stability.

Optimization procedure

We used the AdamW optimizer [46] with learning rate $\eta = 1 \times 10^{-4}$ and weight decay $\lambda = 0.01$. AdamW implements adaptive learning rates with decoupled weight decay, combining the benefits of Adam optimization with proper L2 regularization. A ReduceLROnPlateau scheduler dynamically adjusted the learning rate based on validation loss, reducing it by a factor of 0.1 when no improvement occurred for 10 consecutive epochs. Early stopping with patience of 10 epochs prevented overfitting by terminating training when validation performance plateaued. A fixed random seed (12345) ensured reproducibility across training runs.

The training objective used cross-entropy loss for binary classification. For a training example with class label $y \in \{0, 1\}$ and model logits $\mathbf{z} = [z_0, z_1]$, the loss is:

$$\mathcal{L}(\mathbf{z}, y) = -\log \left(\frac{\exp(z_y)}{\exp(z_0) + \exp(z_1)} \right) = -z_y + \log(\exp(z_0) + \exp(z_1))$$

where z_0 and z_1 represent logits for biological and artificial chimeric classes, respectively.

Training implementation

Training used batch size of 16 sequences with 30 parallel data loading workers. GPU acceleration was employed for efficient processing, with training typically requiring

55 hours. Model checkpointing saved the best-performing model based on validation metrics. Configuration management used Hydra [47] to enable reproducible experimentation.

Model evaluation

Performance was monitored using precision, recall, and F1 score on the validation set after each epoch:

$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}}, \quad \text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}}$$

$$\text{F1} = \frac{2 \times \text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$$

where TP (true positives) are chimeric reads correctly classified as artificial, TN (true negatives) are biological reads correctly classified as biological, FP (false positives) are biological reads misclassified as artificial, and FN (false negatives) are artificial reads misclassified as biological. Final model selection was based on best validation performance as determined by early stopping.

Model inference and application

Inference pipeline

To apply ChimeraLM to new WGA sequencing data, the model takes a BAM file as input. Chimeric reads are identified using SA tags and filtered to exclude unmapped, secondary, or supplementary alignments. Each chimeric read sequence is tokenized using the tokenizer (maximum length 32,768 bp, with truncation or padding as needed). The trained model processes sequences in batches, generating two logits $[z_0, z_1]$ for each read corresponding to biological and artificial chimeric classes. Classification is determined by $\hat{y} = \text{argmax}(z_0, z_1)$. ChimeraLM outputs a filtered BAM file containing only reads classified as biological, which can be directly used for downstream analyses including SV calling.

Performance evaluation

Test set evaluation

Final model performance was evaluated on the held-out test set and the independent MinION Mk1c dataset. Metrics (precision, recall, and F1 score) were computed as described in the training section, where true positives represent chimeric reads correctly classified as artificial and true negatives represent biological reads correctly classified as biological.

SV calling

SVs were called using multiple tools to ensure comprehensive detection. For long-read data (ONT PromethION P2 and MinION Mk1c), we used Sniffles v2.5 [14, 15], DeBreak v1.2 [16], SVIM v2.0.0 [17], and cuteSV v2.1.1 [18]. For short-read data of the PC3 cell line, we used both the CCLE Illumina WGS dataset and the PRJNA361315

783 Illumina [WGS](#) dataset, processed with Manta v1.6.0 [48], DELLY v1.5.0 [49], and
784 SvABA v1.1.0 [50]. All tools were executed with default recommended parameters.

785

786 *Gold standard SV dataset construction*

787 To evaluate the impact of ChimeraLM on [SV](#) detection accuracy, we generated a high-
788 confidence gold-standard [SV](#) set from bulk PC3 sequencing data. All [SV](#) comparisons
789 and breakpoint corrections were performed using OctopusSV v0.2.3 [51]. Four bulk
790 datasets were integrated: [ONT](#) MinION Mk1c, [ONT](#) PromethION P2, the CCLE Illu-
791 mina [WGS](#) dataset, and the PRJNA361315 Illumina [WGS](#) dataset. [SVs](#) were called
792 independently within each dataset, and events supported by at least two [SV](#) callers
793 were retained. The remaining calls were then compared across datasets, and [SVs](#)
794 observed in at least two of the four datasets were designated as gold-standard events
795 for benchmarking.

796

797 *SV benchmarking analysis*

798 To assess the impact of ChimeraLM on [SV](#) calling accuracy, we compared [SV](#) calls from
799 unfiltered [WGA](#) data and ChimeraLM-filtered [WGA](#) data against two references: (1)
800 the stringent multi-platform gold standard dataset, and (2) platform-matched long-
801 read bulk sequencing data. Benchmarking was performed using Truvari v4.2.2 [52]
802 with default parameters. [SVs](#) were considered supported if they matched reference
803 variants within the defined breakpoint tolerance. Validation rates were calculated as
804 the proportion of called [SVs](#) supported by the reference. This dual benchmarking
805 strategy quantifies both improvements in detecting high-confidence multi-platform
806 [SVs](#) and the retention of platform-specific true variants.

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

Benchmarking against existing methods

ChimeraLM was compared to existing computational methods for detecting
amplification-induced chimeric artifacts: SACRA [25] (GitHub commit 9a2607e), 3rd-
ChimeraMiner [13] (GitHub commit 04b5233), and CADECT v1.2 [11]. Both tools
were applied to [WGA](#) data from PromethION P2 and MinION Mk1c platforms using
default parameters as recommended in their documentation. Performance was evalu-
ated by measuring the percentage reduction in chimeric reads relative to unprocessed
[WGA](#) data. Chimeric reads were identified using [WGA](#) tag-based alignment criteria
(reads with [SA](#) tags indicating split alignments), and reduction rates were calculated
as the proportion of chimeric reads removed by each method.

Attention weight analysis

To investigate ChimeraLM’s interpretability, we analyzed attention weights from
the pooling mechanism for representative chimeric reads. Attention weights indicate
the relative importance assigned to each sequence position during classification. For
selected reads, we extracted per-position attention weights and visualized them along-
side read alignments to identify whether the model focuses on mechanistically relevant
regions.

Chimeric junction positions were identified from alignment data (defined by break-points in [SA](#) tags). A region of ± 50 bp surrounding each junction was designated as the junction region. Attention weights within junction region were compared to non-junction regions using the Wilcoxon rank-sum test [53], with statistical significance assessed at $p < 0.001$.

Data visualization

Figures were generated using Python with Matplotlib [54] and Seaborn [55].


Computing resources

Computations were performed on a [high performance computing \(HPC\)](#) server with 64-core Intel Xeon Gold 6338 CPU, 256 GB RAM, and two NVIDIA A100 [GPUs](#) (80 GB memory each).


Extended Data Table 1 Sequencing and alignment statistics of PC3

Sample	Platform	Reads ($\times 10^6$)	Total bases (Gb)	Total bases aligned (Gb)	Fraction aligned	Mean length (bp)	Mean quality (Q)	Average identity (%)
WGA	MinION	9.11	14.6	10.4	0.7	1,603	14.3	97.6
WGA	PromethION	44.69	128.2	69.2	0.5	2,869	14.5	96.1
Bulk	MinION	0.97	8.1	7.1	0.9	8,310	17.2	97.3
Bulk	PromethION	8.00	69.9	62.4	0.9	8,732	18.5	97.7

Supplementary information.



Extended Data Fig. 1 Training dataset construction and bulk-supported labeling strategy. (a) Workflow for generating labeled training data. WGA PromethION data is compared against three independent bulk sequencing datasets (PromethION, MinION, and PacBio). Reads with no bulk matches (Match 0) are labeled artificial; reads matching one or more bulk datasets (Match 1–3) are labeled biological, along with chimeric reads sampled directly from bulk data. The labeled dataset is split into training (70%), validation (20%), and test (10%) sets. The WGA MinION dataset is reserved for independent cross-platform evaluation. (b) Distribution of chimeric read matches. Bar chart shows the number of WGA PromethION chimeric reads (log scale) by bulk dataset matches. Match 0 reads ($\sim 10^7$) lacking bulk validation are classified as artificial; Match 1–3 reads with bulk support are classified as biological. The substantial imbalance reflects high prevalence of WGA-induced artifacts.



Extended Data Fig. 2 Composition of artifact-supported SVs for PromethION (a) and MinION (b). Donut charts summarize the distribution of SV types including [translocation \(TRA\)](#), [deletion \(DEL\)](#), [inversion \(INV\)](#), [duplication \(DUP\)](#), and [insertion \(INS\)](#) among events supported exclusively by chimera artifacts, representing artificial SVs preferentially removed by ChimeraLM.

Acknowledgements. We thank Tingyou Wang for guidance on figure preparation. This project was supported in part by NIH grants R35GM142441 and R01CA259388 awarded to RY.

970

971 **Declarations**

972

Author Contributions. YL, QG and RY designed the study. YL and QG performed the analysis. QG performed the experiments. YL and QG designed and implemented the model. YL built the command-line tool and documentation. YL, QG and RY wrote the manuscript. RY supervised this work.

977

Data Availability. The raw sequencing data generated in this study have been deposited in the NCBI Sequence Read Archive (SRA) under BioProject accession PRJNA1354861. The dataset includes Oxford Nanopore long-read whole-genome sequencing of PC3 prostate cancer cells and MDA-amplified single-cell derivatives. The individual SRA accessions are as follows: PC3 bulk (MinION Mk1C), SRR35904028; PC3 bulk (PromethION P2), SRR35904029; PC3 10-cell WGA (MinION Mk1C), SRR35904026; PC3 10-cell WGA (PromethION P2), SRR35904027. We can access the data at the following link: <https://dataview.ncbi.nlm.nih.gov/object/PRJNA1354861?reviewer=viej6cv6mgbli3n7a9a5k1bsb3>

986

Code Availability. ChimeraLM, implemented in Python, is open source and available on GitHub (<https://github.com/ylab-hi/ChimeraLM>) under the Apache License, Version 2.0. The package can be installed via PyPI (<https://pypi.org/project/chimeralm>) using pip, with wheel distributions provided for Windows, Linux, and macOS to ensure easy cross-platform installation. An interactive demo is available on Hugging Face (<https://huggingface.co/spaces/yangliz5/ChimeraLM>), allowing users to test ChimeraLM’s functionality without local installation. For large-scale analyses, we recommend using ChimeraLM on systems with GPU acceleration. Detailed system requirements and optimization guidelines are available in the repository’s documentation (<https://ylab-hi.github.io/ChimeraLM/>).

997

Conflict of interest. The authors declare no competing interests.

998

999

1000 **Acronyms**

1001

CPU central processing unit 12

1002

DEL deletion 7, 21

1003

dMDA droplet-based MDA 12

1004

DUP duplication 7, 21

1005

1006

1007

1008

1009

1010

1011

1012

GLM genomic language model 1, 2, 12

1007

1008

1009

1010

1011

1012

1013

1014

1015

1016

1017

1018

1019

1020

1021

1022

1023

1024

1025

1026

1027

1028

1029

1030

1031

1032

1033

1034

1035

1036

1037

1038

1039

1040

1041

1042

1043

1044

1045

1046

1047

1048

1049

1050

1051

1052

1053

1054

1055

1056

1057

1058

1059

1060

1061

1062

1063

1064

1065

1066

1067

1068

1069

1070

1071

1072

1073

1074

1075

1076

1077

1078

1079

1080

1081

1082

1083

1084

1085

1086

1087

1088

1089

1090

1091

1092

1093

1094

1095

1096

1097

1098

1099

1100

1101

1102

1103

1104

1105

1106

1107

1108

1109

1110

1111

1112

1113

1114

1115

1116

1117

1118

1119

1120

1121

1122

1123

1124

1125

1126

1127

1128

1129

1130

1131

1132

1133

1134

1135

1136

1137

1138

1139

1140

1141

1142

1143

1144

1145

1146

1147

1148

1149

1150

1151

1152

1153

1154

1155

1156

1157

1158

1159

1160

1161

1162

1163

1164

1165

1166

1167

1168

1169

1170

1171

1172

1173

1174

1175

1176

1177

1178

1179

1180

1181

1182

1183

1184

1185

1186

1187

1188

1189

1190

1191

1192

1193

1194

1195

1196

1197

1198

1199

1200

1201

1202

1203

1204

1205

1206

1207

1208

1209

1210

1211

1212

1213

1214

1215

1216

1217

1218

1219

1220

1221

1222

1223

1224

1225

1226

1227

1228

1229

1230

1231

1232

1233

1234

1235

1236

1237

1238

1239

1240

1241

1242

1243

1244

1245

1246

1247

1248

1249

1250

1251

1252

1253

1254

1255

1256

1257

1258

1259

1260

1261

1262

1263

1264

1265

1266

1267

1268

1269

1270

1271

1272

1273

1274

1275

1276

INV inversion	7, 21	1013
LIANTI linear amplification via transposon insertion	12	1014
MALBAC multiple annealing and looping-based amplification cycles	12	1015
MDA multiple displacement amplification	2, 9	1016
MLP multilayer perceptron	4, 5, 15, 16	1017
ONT Oxford Nanopore Technologies	3, 7, 8, 11, 13, 14, 17, 18	1018
PacBio Pacific Biosciences	3, 14	1019
PTA primary template-directed amplification	12	1020
SA supplementary alignment	13, 14, 17–19	1021
SV structural variation	1–4, 6–9, 11, 12, 14, 17, 18, 21	1022
TRA translocation	7, 21	1023
WGA whole genome amplification	1–12, 14, 17–20	1024
WGS whole genome sequencing	7, 8, 17, 18	1025
References		1026
[1] Kalef-Ezra, E. <i>et al.</i> Single-cell somatic copy number variants in brain using different amplification methods and reference genomes. <i>Communications Biology</i> 1288 (2024).		1027
[2] Navin, N. <i>et al.</i> Tumour evolution inferred by single-cell sequencing. <i>Nature</i> 472 , 90–94 (2011).		1028
[3] Sun, C. <i>et al.</i> Mapping recurrent mosaic copy number variation in human neurons. <i>Nature Communications</i> 4220 (2024).		1029
[4] Gawad, C., Koh, W. & Quake, S. R. Single-cell genome sequencing: current state of the science. <i>Nature Reviews Genetics</i> 175–188 (2016).		1030
[5] Chen, C. <i>et al.</i> Single-cell whole-genome analyses by linear amplification via transposon insertion (LIANTI). <i>Science (new York, N.Y.)</i> 356 , 189–194 (2017).		1031
[6] Macaulay, I. C. & Voet, T. Single cell genomics: Advances and future perspectives. <i>PLOS Genetics</i> 10 , e1004126 (2014).		1032
[7] de Bourcy, C. F. A. <i>et al.</i> A quantitative comparison of single-cell whole genome amplification methods. <i>PLoS ONE</i> e105585 (2014).		1033
[8] Biezuner, T. <i>et al.</i> Comparison of seven single cell whole genome amplification commercial kits using targeted sequencing. <i>Scientific Reports</i> 17171 (2021).		1034

1059 [9] Lu, N., Qiao, Y., Lu, Z. & Tu, J. Chimera: The spoiler in multiple displacement
1060 amplification. *Computational and Structural Biotechnology Journal* 1688–1696
1061 (2023).
1062
1063 [10] Lasken, R. S. & Stockwell, T. B. Mechanism of chimera formation during the
1064 multiple displacement amplification reaction. *BMC Biotechnology* **7**, 19 (2007).
1065
1066 [11] Agyabeng-Dadzie, F. *et al.* Evaluating the benefits and limits of multiple displace-
1067 ment amplification with whole-genome oxford nanopore sequencing. *Molecular*
1068 *Ecology Resources* e14094 (2025).
1069
1070 [12] Dean, F. B. *et al.* Comprehensive human genome amplification using multiple
1071 displacement amplification. *Proceedings of the National Academy of Sciences* **99**,
1072 5261–5266 (2002).
1073
1074 [13] Lu, N. *et al.* Exploration of whole genome amplification generated chimeric
1075 sequences in long-read sequencing data. *Briefings in Bioinformatics* **24**, bbad275
1076 (2023).
1077
1078 [14] Sedlazeck, F. J. *et al.* Accurate detection of complex structural variations using
1079 single-molecule sequencing. *Nature Methods* 461–468 (2018).
1080
1081 [15] Smolka, M. *et al.* Detection of mosaic and population-level structural variants
1082 with sniffles2. *Nature Biotechnology* 1571–1580 (2024).
1083
1084 [16] Chen, Y. *et al.* Deciphering the exact breakpoints of structural variations using
1085 long sequencing reads with DeBreak. *Nature Communications* 283 (2023).
1086
1087 [17] Heller, D. & Vingron, M. SVIM: Structural variant identification using mapped
1088 long reads. *Bioinformatics* 2907–2915 (2019).
1089
1090 [18] Jiang, T. *et al.* Long-read-based human genomic structural variation detection
1091 with cuteSV. *Genome Biology* 189 (2020).
1092
1093 [19] Gonzalez-Pena, V. *et al.* Accurate genomic variant detection in single cells with
1094 primary template-directed amplification. *Proceedings of the National Academy of*
1095 *Sciences* **118**, e2024176118 (2021).
1096
1097 [20] Kosugi, S. *et al.* Comprehensive evaluation of structural variation detection
1098 algorithms for whole genome sequencing. *Genome Biology* **20**, 117 (2019).
1099
1100 [21] Alkan, C., Coe, B. P. & Eichler, E. E. Genome structural variation discovery and
1101 genotyping. *Nature Reviews Genetics* **12**, 363–376 (2011).
1102
1103 [22] Hård, J. *et al.* Long-read whole-genome analysis of human single cells. *Nature*
1104 *Communications* **14**, 5164 (2023).

[23]	Gupta, P., O'Neill, H., Wolvetang, E. J., Chatterjee, A. & Gupta, I. Advances in single-cell long-read sequencing technologies. <i>NAR Genomics and Bioinformatics</i> 6 , lqae047 (2024).	1105 1106 1107 1108
[24]	Wen, L. & Tang, F. Single-cell omics sequencing technologies: The long-read generation. <i>Trends in Genetics</i> 0 (2025).	1109 1110 1111
[25]	Kiguchi, Y., Nishijima, S., Kumar, N., Hattori, M. & Suda, W. Long-read metagenomics of multiple displacement amplified DNA of low-biomass human gut phageomes by SACRA pre-processing chimeric reads. <i>DNA Research</i> 28 , dsab019 (2021).	1112 1113 1114 1115
[26]	Ha, Y.-J. <i>et al.</i> Comprehensive benchmarking and guidelines of mosaic variant calling strategies. <i>Nature Methods</i> 20 , 2058–2067 (2023).	1116 1117 1118
[27]	Höijer, I. <i>et al.</i> Amplification-free long-read sequencing reveals unforeseen CRISPR-Cas9 off-target activity. <i>Genome Biology</i> 21 , 290 (2020).	1119 1120 1121
[28]	Li, Y. <i>et al.</i> A genomic language model for chimera artifact detection in nanopore direct rna sequencing. <i>bioRxiv</i> (2024). URL https://www.biorxiv.org/content/early/2024/10/25/2024.10.23.619929 .	1122 1123 1124 1125
[29]	Nguyen, E. <i>et al.</i> <i>HyenaDNA: Long-range genomic sequence modeling at single nucleotide resolution</i> , Vol. 36, 43177–43201 (Curran Associates, Inc., 2023).	1126 1127 1128
[30]	Dalla-Torre, H. <i>et al.</i> Nucleotide transformer: building and evaluating robust foundation models for human genomics. <i>Nature Methods</i> 287–297 (2025).	1129 1130 1131
[31]	Zhou, Z. <i>et al.</i> <i>DNABERT-2: Efficient foundation model and benchmark for multi-species genomes</i> , 1–24 (OpenReview.net, 2024).	1132 1133
[32]	Consens, M. E. <i>et al.</i> To transformers and beyond: Large language models for the genome (2023). arXiv:2311.07621 .	1134 1135 1136
[33]	Poli, M. <i>et al.</i> <i>Hyena hierarchy: Towards larger convolutional language models</i> , Vol. 202, 28043–28078 (PMLR, 2023).	1137 1138 1139
[34]	Barretina, J. <i>et al.</i> The Cancer Cell Line Encyclopedia enables predictive modelling of anticancer drug sensitivity. <i>Nature</i> 483 , 603–607 (2012).	1140 1141 1142
[35]	Seim, I., Jeffery, P. L., Thomas, P. B., Nelson, C. C. & Chopin, L. K. Whole-Genome Sequence of the Metastatic PC3 and LNCaP Human Prostate Cancer Cell Lines. <i>G3 (Bethesda, Md.)</i> 7 , 1731–1741 (2017).	1143 1144 1145 1146
[36]	Mahmoud, M. <i>et al.</i> Structural variant calling: The long and the short of it. <i>Genome Biology</i> 20 , 246 (2019).	1147 1148 1149 1150

1151 [37] Zong, C., Lu, S., Chapman, A. R. & Xie, X. S. Genome-wide detection of single-
1152 nucleotide and copy-number variations of a single human cell. *Science* 1622–1626
1153 (2012).
1154
1155 [38] Dippenaar, A. *et al.* Droplet based whole genome amplification for sequencing
1156 minute amounts of purified mycobacterium tuberculosis DNA. *Scientific Reports*
1157 **14**, 9931 (2024).
1158
1159 [39] PLC., O. N. Dorado. <https://github.com/nanoporetech/dorado> (2023).
1160
1161 [40] Martin, M. Cutadapt removes adapter sequences from high-throughput sequenc-
1162 ing reads. *Embnet.journal* **17**, 10–12 (2011).
1163
1164 [41] Li, H. Minimap2: Pairwise alignment for nucleotide sequences. *Bioinformatics*
1165 3094–3100 (2018).
1166
1167 [42] Danecek, P. *et al.* Twelve years of SAMtools and BCFtools. *GigaScience* giab008
1168 (2021).
1169
1170 [43] De Coster, W. & Rademakers, R. NanoPack2: Population-scale evaluation of
1171 long-read sequencing data. *Bioinformatics* **39**, btad311 (2023).
1172
1173 [44] Paszke, A. *et al.* *PyTorch: An imperative style, high-performance deep learning*
1174 *library*, Vol. 32, 8024–8035 (Curran Associates, Inc., 2019).
1175
1176 [45] Falcon, W. & The PyTorch Lightning team. PyTorch Lightning. GitHub
1177 repository (2019). URL <https://github.com/Lightning-AI/lightning>.
1178
1179 [46] Loshchilov, I. & Hutter, F. *Decoupled weight decay regularization* (2019).
1180
1181 [47] Yadan, O. Hydra - a framework for elegantly configuring complex applications.
1182 GitHub repository (2019). URL <https://github.com/facebookresearch/hydra>.
1183
1184 [48] Chen, X. *et al.* Manta: Rapid detection of structural variants and indels for
1185 germline and cancer sequencing applications. *Bioinformatics* 1220–1222 (2016).
1186
1187 [49] Rausch, T. *et al.* DELLY: Structural variant discovery by integrated paired-end
1188 and split-read analysis. *Bioinformatics* i333–i339 (2012).
1189
1190 [50] Wala, J. A. *et al.* SvABA: Genome-wide detection of structural variants and
1191 indels by local assembly. *Genome Research* 581–591 (2018).
1192
1193 [51] Guo, Q., Li, Y., Wang, T.-Y., Ramakrishnan, A. & Yang, R. OctopusSV and
1194 TentacleSV: A one-stop toolkit for multi-sample, cross-platform structural variant
1195 comparison and analysis. *Bioinformatics* btaf599 (2025).
1196
1197 [52] English, A. C., Menon, V. K., Gibbs, R. A., Metcalf, G. A. & Sedlazeck, F. J.
Truvari: Refined structural variant comparison preserves allelic diversity. *Genome*

<i>Biology</i> 23 , 271 (2022).	1197
	1198
[53] Virtanen, P. <i>et al.</i> SciPy 1.0: Fundamental algorithms for scientific computing in python. <i>Nature Methods</i> 261–272 (2020).	1199
	1200
	1201
[54] Hunter, J. D. Matplotlib: A 2d graphics environment. <i>Computing in Science & Engineering</i> 90–95 (2007).	1202
	1203
	1204
[55] Waskom, M. L. seaborn: statistical data visualization. <i>Journal of Open Source Software</i> 3021 (2021).	1205
	1206
	1207
	1208
	1209
	1210
	1211
	1212
	1213
	1214
	1215
	1216
	1217
	1218
	1219
	1220
	1221
	1222
	1223
	1224
	1225
	1226
	1227
	1228
	1229
	1230
	1231
	1232
	1233
	1234
	1235
	1236
	1237
	1238
	1239
	1240
	1241
	1242