

**SECTION –IV**  
**KEYSPECIFICATIONS(CONTD....)**

| <b>Item Number</b> | <b>Item Title</b>                              | <b>Item Description</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <b>Consignee</b> |
|--------------------|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <b>1</b>           | <b>ALMIRAH SMALL STEEL (1/2H 1/2S) FD 1034</b> | <p><b>ALMIRAH SMALL STEEL 1/2H X 1/2S</b><br/> <b>DIMENSION:-</b>The Overall size of almirah small steel shall be 1270mm high, 765mm wide and 440mm deep.<br/> <b>DESCRIPTION:-</b><br/> a) It shall be made of 1mm thick CRCA steel sheet. All joints shall be riveted and welded thoroughly.<br/> b) The almirah shall have one 120mm long chrome plated handle as approved by GE/Engineer-in-Charge with built in 3 way locking arrangement with proper workmanship.<br/> c) The almirah shall have Two half shelves and one full shelves made of 1mm thick CRCA steel sheet. One x 20 mm dia conduit pipe shall be chrome plated with wall thickness of 1.6 mm shall be fixed with side sockets.<br/> d) Rest all specifications and dimensions are as per drg<br/> <b>FINISH:-</b> The almirah shall be dry powder coated in double shade (shutter in off white and outer frame in steel grey) after preparation of surface through 7 Tank Anti rust Treatment Unit with Hostile Facilities and Powder Coating unit.</p>                                                                                                                                                                                                                                                                                                                                          | <b>GE BABINA</b> |
| <b>2</b>           | <b>BED HARD STEEL FD/E6/MAP/08R</b>            | <p><b>BED HARD STEEL</b><br/> <b>DIMENSION:</b> The Overall size shall be 2050mm long, 900mm wide and 400mm high (upto Plywood top).<br/> <b>DESCRIPTION:</b><br/> a) The frame of bed shall made of MS pipe of 18 Gauge as per specified sizes mentioned in drg.<br/> b) Irrespective of whatever shown on drawing, Head Board/Foot Board of bed hard shall be provided with 18mm thick Exterior grade I MEDIUM DENSITY FIBRE BOARD (MDF Board), IS 12406 : 2003 Both Side laminated (BSL) one side in super matt finish in approved shade on post form top and other side balancing white with 2mm thick PVC beading. MDF Board shall be cover 18mm square pipe also and Shall be screwed from back side complete<br/> c) The top of bed hard shall be of 12mm thick BWR ply of grade -A; place and fix over the four equidistant stiffener with 12 Nos of flat head bolt of 6 mm dia, 50mm long nylon insert nut and round washer.<br/> d) Each leg of bed hard shall be provided with high quality PVC shoes 40mm high having metal washer fitted inside compatible to insert 38x38mm sq pipe.<br/> e) Rest all specifications and dimensions are as per drg.<br/> <b>FINISH:-</b>The bed hard shall be dry powder coated in black shade after preparation of surface through 7 Tank Anti rust Treatment Unit with Hostile Facilities and Powder Coating unit.</p> | <b>GE BABINA</b> |

## SECTION –IV

### KEYSPECIFICATIONS(CONTD....)

|   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |           |
|---|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| 3 | BIN LINEN<br>MULTIPURPOSE<br>FD/E6/MAP/09 | <p><b>BIN LINEN MULTIPURPOSE</b></p> <p><b>DIMENSION:</b> The overall size of the bin linen multipurpose shall be 1200mm long x 450mm wide x 750mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) It shall be made of exterior grade I Medium Density Fibreboard (MDF) of thickness as specified in drg, conforming to IS 12406:2003 (irrespective of what is shown on the drawing). It shall be laminated on both sides (BSL) – one side in a super matt finish in an approved shade with post-formed edges, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading.</p> <p>b) Top should be projected 25 mm with full round post form finish, Base 120 mm boarder in front fully post form on top and Back side shall be made of exterior grade I Medium Density Fibreboard (MDF) of thickness as specified in drg.</p> <p>c) Irrespective of what is shown on drg, the base of bin linen multipurpose shall be of size 1200mm long x 450mm wide x 75mm high, made of 1st class teak wood scantling 30mm thick. The bottom frame shall have four Nos of 25mmx25mm stiffeners placed and fitted at equidistant positions inside the base frame. All wood to be used shall be 1st class hard teak wood. The base frame shall be fixed with 10 Nos Right Angle Stainless steel claiamp of size 20mm x 20mm with (minimum) fastner screw &amp; screw glue.</p> <p>d) Each drawer shall be provided with 2 x Nos of Soft Close Ball Bearing Sliding Telescopic Drawer Channel of size 13W x 45Th Millimeters x 300L mm with minimum load capacity of 35 Kgs. Drawer and shutter shall be provided with 100mm long 8mm dia chrome plated Oval D Pull handles with screw.</p> <p>e) Shutter shall be provided with magnetic catchers and soft closing concealed Intermate Hinges at inside with fastner screw &amp; screw glue.</p> <p>f) Rest all specifications and dimensions are as per drg.</p> <p><b>FINISH:</b> All unlaminated Medium Density Fibreboard (MDF) surface/wooden surface shall be polished in high gloss melamine polish in approved (by GE/Engr-in-Charge) shade after preparation of surfaces.</p> | GE BABINA |
| 4 | BOOK CASE OPEN<br>SMALL FD 355            | <p><b>BOOK CASE OPEN SMALL</b></p> <p><b>DIMENSION:</b> The overall size of the Book Case shall be 760 mm (H) × 300 mm (D) × 1230 mm (W).</p> <p><b>DESCRIPTION:</b></p> <p>a) The Book Case shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003 (irrespective of what is shown on the drawing). It shall be laminated on both sides (BSL) – one side in a super matt finish in an approved shade with post-formed edges, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading.</p> <p>b) Top should be projected 25 mm with full round post form finish, Base 120 mm boarder in front fully post form on top and Back side shall be made of exterior grade I Medium Density Fibreboard (MDF)</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | GE BABINA |

## SECTION –IV

### KEYSPECIFICATIONS(CONTD....)

|   |                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |           |
|---|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
|   |                     | <p>of thickness as specified in drg.</p> <p>c) The back shall be made of 12 mm thick exterior grade I MDF conforming to IS 12406:2003 (irrespective of what is shown on the drawing). It shall be laminated on both sides (BSL) – one side in a super matt finish in an approved shade with post-formed edges, and the other side with balancing white laminate.</p> <p>d) The bottom frame shall be made of 1st class teak wood, free from cracks, knots, and other blemishes, and shall conform to the size, shape, and finish as shown in the approved drawings and as directed.</p> <p>e) All other specifications and dimensions shall be as per the drawing.</p> <p><b>FINISH:</b> All wooden surfaces shall be polished with high-gloss melamine polish in an approved shade (by GE/Engineer-in-Charge), after proper surface preparation.</p>                                                                                                                                                                                                       |           |
| 5 | CHAIR DINING FD 279 | <p><b>CHAIR – DINING</b></p> <p><b>DIMENSION:-</b> The overall size shall be 440 mm wide × 430 mm deep × 890 mm high, with a seat height of 460 mm.</p> <p><b>DESCRIPTION:-</b></p> <p>a) All wood used shall be 1st class hard teak wood.</p> <p>b) The seat of the chair shall be woven with 2mm wide, 0.6mm thick half round gola type weighing not less than 6 gms in ten running meters with border woven with 4mm thick plastic cane Type I (virgin HDPE) and shall not be recycled type, in true godrej pattern.</p> <p>c) The leg frame shall be fixed with 8 Nos. right-angle stainless steel clamps of minimum size 20 mm × 20 mm, using screws and screw glue.</p> <p>d) Hard nylon buffers of 25 mm diameter shall be provided at the bottom of each leg, fixed with 20 mm long screws.</p> <p>e) All other specifications and dimensions shall be as per the drawing.</p> <p><b>FINISH:-</b>The chair shall be polished with high-gloss melamine polish in an approved shade (by GE/Engineer-in-Charge), after proper surface preparation.</p> | GE BABINA |
| 6 | CHAIR EASY FD 229   | <p><b>CHAIR – EASY</b></p> <p><b>DIMENSION:</b> The overall size shall be 545 mm long × 575 mm wide × 740 mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) All wood used shall be 1st class hard teak wood.</p> <p>b) The seat of the chair shall be woven with 2mm wide, 0.6mm thick half round gola type weighing not less than 6 gms in ten running meters with border woven with 4mm thick plastic cane Type I (virgin HDPE) and shall not be recycled type, in true godrej pattern.</p> <p>c) The leg frame shall be fixed with 8 Nos. right-angle stainless steel clamps of minimum size 20 mm × 20 mm, using screws and screw glue.</p> <p>d) Hard nylon buffers of 25 mm diameter shall be provided at the bottom of each leg, fixed with 20 mm long screws.</p> <p>e) All other specifications and dimensions shall be as per the drawing.</p>                                                                                                                                                                                                        | GE BABINA |

## SECTION –IV

### KEYSPECIFICATIONS(CONTD....)

|   |                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |           |
|---|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
|   |                                          | Finish:- The chair shall be polished with high-gloss melamine polish in an approved shade (by GE/Engineer-in-Charge), after proper surface preparation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |           |
| 7 | CHAIR EASY CUSHIONED<br>FD 358           | <p><b>CHAIR – EASY CUSHIONED</b></p> <p><b>DIMENSION:</b> The overall size shall be 545 mm long × 510 mm wide × 740 mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) All wood used shall be 1st class hard teak wood.</p> <p>b) The seat and back of the chair shall be made of 40-density foam cushion (as approved by GE/Engineer-in-Charge) with a thickness of 75 mm and 50 mm, respectively. The cushions shall be placed and fixed on 12 mm BWR plywood, upholstered with leatherette rexine of approved shade and texture, as directed by BSO/GE.</p> <p>c) The armrests of the chair shall have 40-density foam cushions of 25 mm thickness, upholstered with leatherette rexine of approved shade and texture, as directed by BSO/GE.</p> <p>d) Hard nylon buffers of 25 mm diameter shall be provided at the bottom of each leg, fixed with 20 mm long screws.</p> <p>e) All other specifications and dimensions shall be as per the drawing.</p> <p>Finish:- The chair shall be polished with high-gloss melamine polish in an approved shade (by GE/Engineer-in-Charge), after proper surface preparation.</p> | GE BABINA |
| 8 | CHAIR VERANDAH<br>FD 359                 | <p><b>CHAIR VERANDAH</b></p> <p><b>DIMENSION:</b>The Overall size of the chair shall be 460mm wide, 600mm deep and 355mm high upto seat from ground level and over all height 760 mm.</p> <p><b>DESCRIPTION:</b></p> <p>a) The frame of the chair verandah shall be made up of 20mm dia conduit pipe of wall thickness 1.6mm.</p> <p>b) Seat and back of the chair shall be woven with plastic cane Type I (virgin HDPE) and shall not be recycled type, 4mm wide and 0.6 mm thick half round in Matt pattern as per trade practice.</p> <p>c) Irresepective of whatever shown on drawing 10mm dia MS Rod welded to rear legs all as directed.</p> <p>d) PVC hard rubber toes shall be provided to each leg of chair verandah.</p> <p>e) Rest all specifications and dimensions are as per drg.</p> <p><b>FINISH:-</b> The Chair frame shall be dry powder coated in white shade after preparation of surface through 7 Tank Anti rust Treatment Unit with Hostile Facilities and Powder Coating unit.</p>                                                                                                              | GE BABINA |
| 9 | CHAIR WITH ARMS<br>(VISITOR CHAIR)<br>TP | <p><b>CHAIR WITH ARMS (VISITOR CHAIR)</b></p> <p><b>Model:</b> CHAIR MS -127 VI, Make: Methodex or similar model in Godrej/Nilkamal</p> <p>All as shown in the OEM catalogue of the specified make and model, and as directed by the GE.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | GE BABINA |

## SECTION –IV

### KEYSPECIFICATIONS(CONTD....)

|    |                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |           |
|----|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| 10 | CHARPOY WITH HARD TOP FD/MAP-II/01 | <p><b>CHARPOY WITH HARD TOP</b></p> <p><b>DIMENSION:</b> The Overall size shall be 1980mm long, 900mm wide and 440mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) The frame of charpoy shall be made of MS hollow section pipe of 16 Gauge as per specified sizes mentioned in drg.</p> <p>b) The top of charpoy shall be of 12mm thick BWR ply of grade -A; place and fix over the three equidistant stiffener with 12 Nos of flat head bolt of 6 mm dia, 50mm long nylon insert nut and round washer.</p> <p>c) Each leg of Charpoy shall be provided with high quality PVC shoes 40mm high having metal washer fitted inside compatible to insert 32x32mm sq pipe.</p> <p>d) Irrespective of whatever shown on drawing, 03 Nos x MS TUBE stiffener of size 25X25MMX16 GAUGE, shall be provided at equidistant, perpendicular to long rail.</p> <p>e) Rest all specifications and dimensions are as per drg.</p> <p><b>FINISH:</b> The Charpoy shall be dry powder coated in black shade after preparation of surface through 7 Tank Anti rust Treatment Unit with Hostile Facilities and Powder Coating unit.</p>                                 | GE BABINA |
| 11 | LOCKER BED SIDE STEEL FD-1029      | <p><b>LOCKER BED SIDE STEEL</b></p> <p><b>DIMENSION:</b> The Overall size shall be 1100mm high, 760mm wide and 600mm deep.</p> <p><b>DESCRIPTION:-</b></p> <p>a) It shall be made of 1mm thick CRCA steel sheet. All joints shall be riveted and welded thoroughly.</p> <p>b) 20 mm dia conduit pipe shall be chrome plated with wall thickness of 1.6 mm shall be fixed with side sockets</p> <p>c) Two handles chromium plated 100mm long shall be fixed to shutters with necessary riveting as approved by GE/Engineer-in-Charge.</p> <p>d) One safty type hasp and staple 75mm long x 40mm x 3mm chrome plated shall also be fixed to shutters with riveting as approved by GE/Engineer-in- Charge.</p> <p>e) The left shutters shall be provided with 100mm long tower bolt inside at upper and lower ends.</p> <p>f) Rest all specifications and dimensions are as per drg</p> <p><b>FINISH:-</b> The almirah shall be dry powder coated in double shade (shutter in off white and outer frame in Chocolate brown) after preparation of surface through 7 Tank Anti rust Treatment Unit with Hostile Facilities and Powder Coating unit.</p> | GE BABINA |
| 12 | PEG TABLE FD 384                   | <p><b>PEG - TABLE</b></p> <p><b>DIMENSIONS:</b>The overall size shall be 450 mm long × 300 mm wide × 380 mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) All wood used shall be 1st class hard teak wood.</p> <p>b) The top shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003 (irrespective of what is shown on the drawing). It shall be laminated on both sides (BSL) – one side in a super matt finish in an approved shade with</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |           |

## SECTION –IV

### KEYSPECIFICATIONS(CONTD....)

|    |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |  |
|----|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|    |                                           | <p>post-formed edges, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading.</p> <p>c) The top shall project 25 mm with a full-round post-formed finish. It shall be fixed with 6 Nos. right-angle stainless steel clamps of minimum size 20 mm × 20 mm, using fastener screws and screw glue.</p> <p>d) Irrespective of what is shown on the drawing, one centre stiffener of size 20 × 40 mm shall be provided at the centre of the side bottom rails for extra support.</p> <p>e) PVC hard rubber shoes of 25 mm diameter shall be provided at the bottom of each leg, fixed with 20 mm long screws.</p> <p>f) All other specifications and dimensions shall be as per the drawing.</p> <p><b>FINISH:</b> All wooden surfaces shall be polished with high-gloss melamine polish in an approved shade (by GE/Engineer-in-Charge), after proper surface preparation.</p>                                                                                                                                                |  |
| 13 | TABLE (STEEL)<br>900X900X760MM FD<br>1009 | <p><b>TABLE (STEEL) 900X900X760MM</b></p> <p><b>DIMENSIONS:</b> The overall size shall be 900 mm (L) × 900 mm (W) × 760 mm (H).</p> <p><b>DESCRIPTION:</b></p> <p>a) The top shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003, laminated on both sides (BSL) – one side in a super matt finish in an approved shade with a post-formed edge, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading, irrespective of what is shown on the drawing, all as specified and directed.</p> <p>b) The frame shall be made of 25 mm square MS tube with a wall thickness of 1.6 mm.</p> <p>c) Hard rubber toes shall be provided to each leg. All other specifications and dimensions shall be as per the drawing.</p> <p><b>FINISH:</b> The table shall be dry powder-coated in steel grey shade (as approved by GE/Engineer-in-Charge), after surface preparation through a 7-tank anti-rust treatment process with hostile facilities and a powder-coating unit.</p> |  |
| 14 | TABLE BED SIDE<br>FD/E6/MAP/15 R          | <p><b>TABLE BED SIDE</b></p> <p><b>DIMENSION:</b> The overall size of the table bed side 450mm x 450mm x 500mm.</p> <p><b>DESCRIPTION:</b></p> <p>a) The frame shall be of 18mm square hollow pipe of 18 gauge.</p> <p>b) It shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003, laminated on both sides (BSL) – one side in a super matt finish in an approved shade with a post-formed edge, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading, irrespective of what is shown on the drawing, all as specified and directed.</p> <p>c) Back ply shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003, laminated</p>                                                                                                                                                                                                                                                                                    |  |

## SECTION –IV

### KEYSPECIFICATIONS(CONTD....)

|    |                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |
|----|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|    |                                    | <p>on both sides (BSL) – one side in a super matt finish in an approved shade with a post-formed edge, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading, irrespective of what is shown on the drawing, all as specified and directed.</p> <p>e) Each drawer shall be provided with 2 x Nos of Soft Close Ball Bearing Sliding Telescopic Drawer Channel of size 13W x 45Th Millimeters x 300L mm with minimum load capacity of 35 Kgs. Drawer shall be provided with 100mm long 8mm dia chrome plated Oval D Pull handles with screw.</p> <p>f) Rest all specifications and dimensions are as per drg.</p> <p><b>FINISH:</b> All metal frame/surface shall be dry powder coated in black shade after preparation of surface through 7 Tank Anti rust Treatment Unit with Hostile Facilities and Powder Coating unit and all unlaminated surfaces shall be polished with high gloss melamine polish in approved (by GE/Engr-in- Charge) shade after preparation of surfaces.</p> |  |
| 15 | TABLE CENTRE FD 375                | <p><b>TABLE – CENTRE</b></p> <p><b>DIMENSION:</b> The overall size shall be 1200 mm long × 600 mm wide × 400 mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) Frame shall be made of Brass pipes (anodized finish) of size Legs: 40 mm Ø brass pipe, Horizontal frame: 25 mm Ø brass pipe.</p> <p>b) The top shall be made of 10 mm thick plate tinted glass (smoke colour) of size As per drawing: approx. 1200 × 600 mm with rounded corners.</p> <p>c) Hard rubber/PVC Shoe shall be fixed to the bottom of all legs as per drawing..</p> <p>d) All other specifications and dimensions shall be as per the drawing.</p> <p><b>FINISH:</b> All edges: shall be Machine cut and Polished edges with arris finish. Corners: Smooth rounded (radius as per drawing). Frame shall be satin anodized brass finish, uniform color and coating in an approved shade (by GE/Engineer-in-Charge), after proper surface preparation.</p> <p>All joints: shall be Properly welded / brazed and Smoothly finished without visible marks.</p>                      |  |
| 16 | TABLE DINING 6 PERSON FD/MAP-II/03 | <p><b>TABLE DINING 6 PERSON</b></p> <p><b>DIMENSION:</b> The Overall size shall be 1500mm long, 900mm wide and 750mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) All wood to be used shall be 1st class hard teak wood.</p> <p>b) The top shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003 (irrespective of what is shown on the drawing). It shall be laminated on both sides (BSL) – one side in a super matt finish in an approved shade with post-formed edges, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading.</p> <p>c) Top should be projected 25 mm with full round post form finish.</p>                                                                                                                                                                                                                                                                                                                     |  |

## SECTION –IV

### KEYSPECIFICATIONS(CONTD....)

|    |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  |
|----|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|    |                                         | <p>Top shall be fixed with 12 Nos Right Angle Stainless steel clamp of size 50mm x 25mm (minimum) with fastner screw &amp; screw glue.</p> <p>d) Eight wooden corner brackets made to shape of size 100mm x 100mm x 35mm thick shall also be fixed in between the legs and top rails with adhesive and wooden screws to make the table more strudy.</p> <p>e) 25mm dia hard plastic shoes shall also be provided to bottom of all legs with 20mm screws.</p> <p>f) Rest all specifications and dimensions are as per drg.</p> <p>FINISH: All wooden surfaces/unlaminated surfaces shall be polished with high gloss melamine polish in approved (by GE/Engr-in-Charge) shade after preparation of surfaces.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  |
| 17 | TABLE DINING 8 PERSON FD 273            | <p><b>TABLE DINING 8 PERSON</b></p> <p><b>DIMENSION:</b> The Overall size shall be 1800mm long, 900mm wide and 760mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) All wood to be used shall be 1st class hard teak wood.</p> <p>b) The top shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003 (irrespective of what is shown on the drawing). It shall be laminated on both sides (BSL) – one side in a super matt finish in an approved shade with post-formed edges, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading.</p> <p>c) Top should be projected 25 mm with full round post form finish. Top shall be fixed with 12 Nos Right Angle Stainless steel clamp of size 50mm x 25mm (minimum) with fastner screw &amp; screw glue.</p> <p>d) Eight wooden corner brackets made to shape of size 100mm x 100mm x 35mm thick shall also be fixed in between the legs and top rails with adhesive and wooden screws to make the table more strudy.</p> <p>e) 25mm dia hard plastic shoes shall also be provided to bottom of all legs with 20mm screws.</p> <p>f) Rest all specifications and dimensions are as per drg.</p> <p>FINISH: All wooden surfaces/unlaminated surfaces shall be polished with high gloss melamine polish in approved (by GE/Engr-in-Charge) shade after preparation of surfaces.</p> |  |
| 18 | TABLE DRESSING GENTS WITH MIRROR FD-230 | <p><b>TABLE DRESSING GENTS WITH MIRROR</b></p> <p><b>DIMENSION:</b> The overall size shall be 900 mm long × 300 mm wide × 790 mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) All wood used shall be 1st class hard teak wood.</p> <p>b) The top, sides, and bottom of the dressing table shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003 (irrespective of what is shown on the drawing). It shall be laminated on both sides (BSL) – one side in a super matt finish in an approved shade with post-formed edges, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading.</p> <p>c) Irrespective of what is shown on the drawing, the top shall project</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |



## SECTION –IV

### KEYSPECIFICATIONS(CONTD....)

|    |                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |  |
|----|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|    |                                                          | <p>25 mm with a full-round post-formed finish. It shall be fixed with 08 Nos. right-angle stainless steel clamps of minimum size 20 mm × 20 mm, using screws and screw glue.</p> <p>d) Irrespective of what is shown on the drawing, the drawer shall be provided with 2 Nos. soft-close ball-bearing telescopic drawer channels of size 13W × 45Th mm × 300L mm, with a minimum load capacity of 35 kg. The drawer shall also be provided with 100 mm long, 8 mm dia chrome-plated oval “D” pull handles fixed with screws.</p> <p>e) Looking mirror shall be 5.5 mm thick fixed inside the teak wood frame made out of 35mmx25mm section or 18mm thick post formed top as approved by GE/Engineer-in-Charge. Irrespective of what is shown on the drawing, Back ply should have 0.70 mm white/off white shade laminate.</p> <p>f) All other specifications and dimensions shall be as per the drawing.</p> <p><b>FINISH:</b> All wooden surfaces shall be polished with high-gloss melamine polish in an approved shade (by GE/Engineer-in-Charge), after proper surface preparation.</p>                                                                                                                                                                                                                                                                                                                                                                                            |  |
| 19 | TABLE WITH DRAWER (STEEL)<br>900X600X760MM FD<br>1008    | <p><b>TABLE WITH DRAWER (STEEL) 900X600X760MM</b></p> <p><b>DIMENSIONS:</b> The overall size shall be 900 mm (L) × 600 mm (W) × 760 mm (H).</p> <p><b>DESCRIPTION:</b></p> <p>a) The top shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003, laminated on both sides (BSL) – one side in a super matt finish in an approved shade with a post-formed edge, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading, irrespective of what is shown on the drawing, all as specified and directed.</p> <p>b) The frame shall be made of 25 mm square MS tube with a wall thickness of 1.6 mm.</p> <p>c) The drawer shall be fabricated from 1 mm thick CRCA steel sheet. All joints shall be properly riveted and thoroughly welded.</p> <p>d) The drawer shall be fitted with a standard PVC recessed handle of size 150 × 55 × 35 mm and a 4-lever lock with duplicate keys, make – Godrej / Link / Harrison, as approved by GE/Engineer-in-Charge, with proper workmanship.</p> <p>e) Hard rubber toes shall be provided to each leg. All other specifications and dimensions shall be as per the drawing.</p> <p><b>FINISH:</b> The table shall be dry powder-coated in steel grey shade (as approved by GE/Engineer-in-Charge), after surface preparation through a 7-tank anti-rust treatment process with hostile facilities and a powder-coating unit.</p> |  |
| 20 | TABLE WITHOUT DRAWER (STEEL)<br>900X600X760MM FD<br>1007 | <p><b>TABLE WITHOUT DRAWER (STEEL) 900X600X760MM</b></p> <p><b>DIMENSIONS:</b> The overall size shall be 900 mm (L) × 600 mm (W) × 760 mm (H).</p> <p><b>DESCRIPTION:</b></p> <p>a) The top shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003, laminated</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |

## SECTION –IV

### KEYSPECIFICATIONS(CONTD....)

|    |                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |
|----|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|    |                         | <p>on both sides (BSL) – one side in a super matt finish in an approved shade with a post-formed edge, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading, irrespective of what is shown on the drawing, all as specified and directed.</p> <p>b) The frame shall be made of 25 mm square MS tube with a wall thickness of 1.6 mm.</p> <p>c) Hard rubber toes shall be provided to each leg. All other specifications and dimensions shall be as per the drawing.</p> <p><b>FINISH:</b> The table shall be dry powder-coated in steel grey shade (as approved by GE/Engineer-in-Charge), after surface preparation through a 7-tank anti-rust treatment process with hostile facilities and a powder-coating unit.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |  |
| 21 | TABLE WRITING FD<br>275 | <p><b>TABLE - WRITING</b></p> <p><b>DIMENSION:</b> The overall size shall be 1145 mm long × 600 mm wide × 760 mm high.</p> <p><b>DESCRIPTION:</b></p> <p>a) All wood used shall be 1st class hard teak wood.</p> <p>b) The top, sides, and bottom of the table shall be made of 18 mm thick exterior grade I Medium Density Fibreboard (MDF) conforming to IS 12406:2003 (irrespective of what is shown on the drawing). It shall be laminated on both sides (BSL) – one side in a super matt finish in an approved shade with post-formed edges, and the other side with balancing white laminate. All exposed edges shall be finished with 2 mm thick PVC edge beading.</p> <p>c) The top shall project 25 mm with a full-round post-formed finish. It shall be fixed with 10 Nos. right-angle stainless steel clamps of minimum size 50 mm × 50 mm, using screws and screw glue.</p> <p>d) The drawer shall be provided with 2 Nos. soft-close ball-bearing telescopic drawer channels of size 13W × 45Th mm × 300L mm, with a minimum load capacity of 35 kg. The drawer shall also be provided with 100 mm long, 8 mm dia chrome-plated oval “D” pull handles fixed with screws.</p> <p>e) 25 mm dia hard rubber/PVC rings shall be fixed to the bottom of all legs with 20 mm long screws.</p> <p>f) Irrespective of what is shown on the drawing, 2 Nos. additional legs of size 35 × 55 × 100 mm and one additional bottom rail of size 20 × 50 × 600 mm shall be provided for box support, as directed by the Engineer-in-Charge.</p> <p>g) T Shutter shall be provided with magnetic catchers and soft-closing concealed Intermediate hinges fixed inside with screws and screw glue.</p> <p>h) All other specifications and dimensions shall be as per the drawing.</p> <p><b>FINISH:</b> All wooden surfaces shall be polished with high-gloss melamine polish in an approved shade (by GE/Engineer-in-Charge), after proper surface preparation.</p> |  |

#### **SECTION –IV**

##### **KEYSPECIFICATIONS(CONTD....)**

|           |                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                  |
|-----------|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <b>22</b> | TRESTLE STORE ROOM<br>STEEL FD 1043 | <b>TRESTLE – STORE ROOM (STEEL)</b><br><b>DIMENSIONS:</b> The overall size shall be 2440 mm (L) × 600 mm (W) × 300 mm (H).<br><b>DESCRIPTION:</b><br>a) All dimensions, shapes, and sizes shall be as shown on the drawing and as specified.<br>b) All joints, welding, and fixing shall be carried out as shown on the drawings, with standard workmanship.<br>c) Angle iron of size 40 × 40 × 6 mm (mild steel) and T-iron of size 50 × 50 × 6 mm shall be provided, all as per drawing and as specified.<br>d) All other items, fittings, and fixtures shall be as shown on the drawing.<br><b>FINISH:</b><br>The steel frame shall be dry powder-coated in black shade, after surface preparation through a 7-tank anti-rust treatment process with hostile facilities and a powder coating unit. | <b>GE BABINA</b> |
|-----------|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|

**SECTION-V**

| <b>Ser No.</b> | <b>Description of Item</b>                         | <b>Ref Drawing No.</b> |
|----------------|----------------------------------------------------|------------------------|
| 1              | ALMIRAH SMALL STEEL (1/2H 1/2S) FD 1034            | FD 1034                |
| 2              | BED HARD STEEL FD/E6/MAP/08R                       | FD/E6/MAP/08R          |
| 3              | BIN LINEN MULTIPURPOSE FD/E6/MAP/09                | FD/E6/MAP/09           |
| 4              | BOOK CASE OPEN SMALL FD 355                        | FD 355                 |
| 5              | CHAIR DINING FD 279                                | FD 279                 |
| 6              | CHAIR EASY FD 229                                  | FD 229                 |
| 7              | CHAIR EASY CUSHIONED FD 358                        | FD 358                 |
| 8              | CHAIR VERANDAH FD 359                              | FD 359                 |
| 9              | CHAIR WITH ARMS (VISITOR CHAIR)                    | TP                     |
| 10             | CHARPOY WITH HARD TOP FD/MAP-II/01                 | FD/MAP-II/01           |
| 11             | LOCKER BED SIDE STEEL FD-1029                      | FD-1029                |
| 12             | PEG TABLE FD 384                                   | FD 384                 |
| 13             | TABLE (STEEL) 900X900X760MM FD 1009                | FD 1009                |
| 14             | TABLE BED SIDE FD/E6/MAP/15 R                      | FD/E6/MAP/15 R         |
| 15             | TABLE CENTRE FD 375                                | FD 375                 |
| 16             | TABLE DINING 6 PERSON FD/MAP-II/03                 | FD/MAP-II/03           |
| 17             | TABLE DINING 8 PERSON FD 273                       | FD 273                 |
| 18             | TABLE DRESSING GENTS WITH MIRROR FD-230            | FD-230                 |
| 19             | TABLE WITH DRAWER (STEEL) 900X600X760MM FD 1008    | FD 1008                |
| 20             | TABLE WITHOUT DRAWER (STEEL) 900X600X760MM FD 1007 | FD 1007                |
| 21             | TABLE WRITING FD 275                               | FD 275                 |
| 22             | TRESTLE STORE ROOM STEEL FD 1043                   | FD 1043                |