

SECTION –IV
KEYSPECIFICATIONS(CONTD....)

Item Number	Item Title	Item Description	Consignee
1	Table Pantry FD 1020	Over all size shall be 900mm long, 550mm wide and 840mm high. Size of steel frame shall be 880mmx815mm. Legs shall be four in numbers. Legs shall be of 25mm square mild steel tube of wall thickness. All steel sheet used for drawers and side covering of drawer and for support of drawer shall be of mild steel and 1mm thick. Top of table shall be 25mm thick polished Kotah stone slab in one piece. Legs shall be provided with hard rubber/PVC toes at bottom. All steel surfaces exposed to view when placed in position shall be painted with two coats of silver grey hammer paint internally and externally with spray machine after preparation of surfaces. A mark of MES shall also be provided on top left corner of front shutter with visible colour. Painting shall be done with spray machine. Rest all as per drg.	GE JHANSI
2	Locker Bed side FD 1029	Over all size shall be 760mm long, 600 mm wide and 1100 mm high. 02 numbers base channel of 100 mm high made of mild steel sheet shall be welded at 50mm from each end of 760 mm length. Steel sheet shall be 1 mm thick. All exposed steel surface shall be painted with two coat of light grey coloured enamel paint over a coat of primer. Rest all as per drg.	GE JHANSI
3	Bath Mat PVC FD E6 MAP 07	Over all size 400 mm long 300 mm wide and 250 mm high. 4 nos arc shaped legs of size 10 mm x 100 at corners and one leg of 25 mm dia in center shall be provided. PVC sheet thickness shall be 5 mm. Size of stiffener shall be 3mm x 10 mm. Rest all as per drg.	GE JHANSI
4	Hat Stand With Mirror FD 233	Over all size shall be 1000 mm long and 710 mm high. 4mm thick teak plywood of size 100mmx 710 mm shall be provided in front and 4 mm thick commercial ply of same size shall be provided to the back of frame. 5 mm thick mirror of size 300mm x 440 mm shall be provided. Brass pegs of size 120mm x 75mm shall be fixed with screw. All wood work shall be teak wood. All exposed surface shall be french polished. Rest all as per drg.	GE JHANSI
5	Receptical PVC FD E6 MAP 13	The body of receptacle PVC shall be made up of thick polymer plastic .It shall be of capacity 20 liters, provided with lid and handle as shown in drg.	GE JHANSI

SECTION –IV

KEYSPECIFICATIONS(CONTD....)

6	Charpoy with Hard Top FD MAP II 01	Over all size shall be 1980mm long x 900mm wide and 440 mm high. Frame of charpoy shall be made of 25mm x65mm x 16 Gauge MS rectangular pipe. 03 Nos 25mm x25mm x16 Gauge MS stiffeners shall be provided on equal distance to support the ply even only 02 Nos stiffeners shown on drg. Legs shall be made of 32mmx32mm x 16 gauge MS pipe. MS plate of size 323mm 32mm x 5mm shall be welded at the bottom of the legs under which 3mm thick rubber sheet shall be fixed with adhesive. Top of the charpoy shall be made of 12 mm thick BWR grade plywood. 03 Nos MS cleat shall be welded on every short rail to support the ply. All exposed steel surface shall be painted with two coat of black coloured enamel paint over a coat of primer. Rest all as per drg. Make of plywood: Duro/Greenply/Century	GE JHANSI
7	Charpoy folding with plytop FD 388 R	Overall size shall be 1980mm long, 900mm wide and 450mm high. Frame over which 9mm thick BWR grade plywood shall be fixed over two U-shaped frames 927.5mm long and 900mm wide fixed together in the middle by two gusset plates. The frame shall be of 25mm dia mild steel pipe of wall thickness of 2mm. The open ends of U-shaped frames shall be joined by flat iron gusset pipe place (02Nos.) cut the shape out of 140mmx110mmx3mm mild steel sheet and 8mm dia rivets. 25mmx3mm flat iron 165mm long made to shape shall be welded to 140mmx110mmx3mm flat iron gusset pipe towards inner side of frame. Middle legs, two numbers shall be welded to middle horizontal mild steel conduit of 25mm dia and 2mm wall thickness to form U-shape. Middle legs shall be of 25mm dia and wall thickness as 2mm shall be provided to both short sides of the charpoy frame. 850mmx450mm U-shape legs 25mm dia and wall thickness as 2mm shall be provided to both short sides of the charpoy joined to frame by 20mmx3mm as shown on drawing. 25mmx3mm flat iron 200mm long made to shape out of 60mmx3mm as shown on drawing. 25mmx3mm flat iron 365mm long made to shape shall be welded to pipes. 20mmx3mm flat iron stays riveted to each other and in the middle shall be provided as shown on drawing to facilitate the folding of charpoy. PVC shoes shall be provided to bottom of all legs. Painting shall be done with automotive paint after preparation of surfaces as directed by Engineer-in-charge A Horizontal pipe piece shall be fixed at 125mm below the bottom of top pipe of leg frame. Three pieces of 12mm dia mild steel pipes of wall thickness 2mm shall be welded in head and foot sides with equal spacing. Rest all as per drg. Make of plywood: Duro/Greenply/Century	GE JHANSI
8	Chair verandah officer FD MAP II 06	The overall size of the chair shall be 455mm wide 455mm deep and 940mm high. The frame of the chair shall be of 19mm dia MS tube of wall thickness 1.6mm duly powder coated. The seat and back of the chair shall be of PVC 4mm of weight not less than 1.85 kgs and grooves 90x10mm ten in nos on seat and back. One stiffener 19mm dia MS tube shall be provided in between the front legs as shown in drg. An additional support in	GE JHANSI

SECTION –IV

KEYSPECIFICATIONS(CONTD....)

		seat and back shall be provided at centre between the seat and back duly welded for rest of PVC seat irrespective of what is shown on drg. Rubber shoes of best quality shall be provided to each end of legs. Rest all as per drg.	
9	Almirah med steel 1/2H X 1/2 S FD 1034	Overall size shall be 765mm long, 440mm wide and 1270mm high. The base shall be made of two numbers mild steel channels shape with ends covered and welded to bottom of almirah. Mild steel sheet for channel base shall be 1mm thick. The base channel shall be welded at 50mm from each end of 765mm length. Top, sides, back bottom and front of almirah shall be of 1mm thick mild steel sheet. A partition in the centre of almirah shall be provided vertically with 1mm thick mild steel sheet. Three shelves, equally spaced, of 1mm thick mild steel sheet shall be provided in one half towards left hand side. One top shelf on right hand side shall be provided matching with top shelf shall be provided with 20mm dia chromium plated steel conduit pipe of wall thickness 1.25mm and shall have sockets at both ends. Front shutter shall have two leaves. A steel chromium plated handle 100mm long shall be provided to shutter. A three way locking device shall be provided to front shutters. Each leaf of front shutter shall have two hinges of 75mm long butt hinged and shutters shall be side hung. All joints, welding and fixing shall be done in accordance with standard workmanship. All exposed steel surface shall be painted with two coat of green coloured spray paint on doors and light grey colour on rest of surface over a coat of primer. Rest all as per drg.	GE JHANSI
10	Couch examination with footstep HFD 2019	Over all size 1895mm long x 510 mm wide x 830 mm high. Top of the couch shall be upholstered in two piece in which one shall be in size of 450 mm long x 510 mm wide with provision of 0-80 degree adjustable. Frame shall be made of tubular stainless steel frame duly provisioned of two cabinet and three drawers. All exposed surface shall be painted with epoxy powder coated paint in ivory white colour. Rest all as per drg.	GE JHANSI
11	Ladder Aluminium FD 1025	Over all size shall be 2310 mm long and 363.50 mm wide. Two aluminium stringers 60 x 31.75 mm made in 'C' shape and 3.18 mm thick aluminium shall be 2310 mm long and joined together with 8 Nos aluminium conduit fluted pipe which wall thickness shall not be less than 2.43 mm. .	GE JHANSI
12	Bed Fowler steel HFD 2002	Over all size shall be 2250 mm long x 985 mm wide x 600-1006 mm high. Main frame shall be made of 50mm x 30 mm rectangular pipe of 16 SWG (1.63 mm) with perforated Mild steel sheet top of 18 SWG (1.25 mm) thickness provided with 4 corners buffers. Head and foot bows shall be made of both side prelaminated particle board of 19 mm thick. Panels framed in 31 mm dia detachable 350 mm high stainless steel head and foot bows. Head raise range shall be 0-80 degree and Knee raise range 0-45 degree. All exposed steel surface shall be ivory	GE JHANSI

SECTION –IV

KEYSPECIFICATIONS(CONTD....)

		coloured epoxy powder coated over a coat of primer. Rest all as per drg.	
--	--	--	--

SECTION-V

Ser No.	Description of Item	Ref Drawing No.
1	Table Pantry FD 1020	FD 1020
2	Locker Bed side FD 1029	FD 1029
3	Bath Mat PVC FD E6 MAP 07	FD E6 MAP 07
4	Hat Stand With Mirror FD 233	FD 233
5	Receptical PVC FD E6 MAP 13	FD E6 MAP 13
6	Charpoy with Hard Top FD MAP II 01	FD MAP II 01
7	Charpoy folding with plytop FD 388 R	FD 388 R
8	Chair verandah officer FD MAP II 06	FD MAP II 06
9	Almirah med steel 1/2H X 1/2 S FD 1034	FD 1034
10	Couch examination with footstep HFD 2019	HFD 2019
11	Ladder Aluminium FD 1025	FD 1025
12	Bed Fowler steel HFD 2002	HFD 2002