

TECHNICAL SPECIFICATION FOR DHP COPPER SEAMLESS FINISHED TUBES OF VARIOUS SIZES, C.NO. 37, SYSTEMS DEPARTMENT

Sl No.	Item Description	Qty. (In Meter)
1	DHP Copper Seamless Finished Tube OD = 8 X 1 mm Thick	1000
2	DHP Copper Seamless Finished Tube OD = 10 X 1.6 mm Thick	200
3	DHP Copper Seamless Finished Tube OD = 10 X 2.5 mm Thick	200
4	DHP Copper Seamless Finished Tube OD = 14 X 1.6 mm Thick	200
5	DHP Copper Seamless Finished Tube OD = 14 X 3 mm Thick	200
6	DHP Copper Seamless Finished Tube OD = 20 X 2 mm Thick	100
7	DHP Copper Seamless Finished Tube OD = 20 X 4.5 mm Thick	100
8	DHP Copper Seamless Finished Tube OD = 25 X 3 mm Thick	100
9	DHP Copper Seamless Finished Tube OD = 25 X 5.5 mm Thick	100
10	DHP Copper Seamless Finished Tube OD = 30 X 2 mm Thick	200
11	DHP Copper Seamless Finished Tube OD = 30 X 3.5 mm Thick	100
12	DHP Copper Seamless Finished Tube OD = 30 X 6.5 mm Thick	100
13	DHP Copper Seamless Finished Tube OD = 36 X 2 mm Thick	200
14	DHP Copper Seamless Finished Tube OD = 36 X 8 mm Thick	100
15	DHP Copper Seamless Finished Tube OD = 41.5 X 9 mm Thick	60
16	DHP Copper Seamless Finished Tube OD = 42 X 2.5 mm Thick	200
17	DHP Copper Seamless Finished Tube OD = 48 X 11 mm Thick	60
18	DHP Copper Seamless Finished Tube OD = 57 X 2.5 mm Thick	100

TECHNICAL SPECIFICATION- BS 2871, Grade C 106, (DHP)

Element	Ni	Fe	Sn	Pb	P	Cu	Impurity
Value in %	0.10 max	0.03 max	0.010 max	0.010 max	0.013 max	99.85 minimum	< 0.06, Bismuth, Arsenic, Antimony

Note-1

- > All pipes are in seamless mode.
- > Minimum acceptable length ≥ 3.5 Mtr
- > Maximum acceptable curvature $\pm \leq 1.15$ % of original size.
- > Permissible variation in thickness is $\pm \leq 2.5$ % of original Thickness.
- > Outer Diameter permissible variation $\leq 1.0\%$ for up to 25mm Dia, & $\leq 1.5\%$ up to 100mm
- > RA of internal surface < 45 micron
- > Product must be free from any strain.
- > All products should be clean smooth and free from any defects.

Note-2

Test certificate must be provided by the firm from any NABL/Government approved laboratory, as per technical specification and along with 02 year Guarantee/Warranty Certificate. **All inspections and testing charges should be paid by the firm/Vendors.**