

DRAFT COST SCHEDULE

Name of work:- PROW OF CENTRAL MI ROOM IN SECT 'A' PATIALA MIL STATION THROUGH AMWP 2024-25.

Station: Patiala Mil Station

Job No: 113TN HQ/AMWP/2024-25/Q3W dated 07 Jun 2024

Auth: Station Headquarters Patiala letter No 1019/6/AA/AMWP/2024-25/Q

Ser No	Drq No	Nomenclature
1	FD-TP	Board notice 6' x 5' The overall size shall be 6 Feet x 5 Feet. 25mm x 75mm particle board frame of commercial face with 06mm thick teak wood edging around shall be provided as shown on drawing. 19mm thick soft wood board shall be fixed inside the frame over which best quality green baize cloth shall be fixed as shown on drawing. Aluminium flat of 63mm x 3.25mm shall be provided around at the back of the board. On front side 22mm x 10mm aluminium channel shall be provided in side of particle board frame to house 05mm thick glass shutter. All wooden surfaces exposed to view when placed in position shall be french polished with high gloss finish.
2	FD/E6/MAP/12	Chair writing MAP All as shown on drg. The frame shall be made of 25mmx10mm in section MS tubular frame cantilever type and shall be black powder coated. The Seat and back shall be made of 12mm thick hot pressed plywood upholstered with fabric and moulded polyurethane foam (50mm thick) having density 50-55 Kg per Cu Mtr and hardness 20+/-2 Kg on Hampden machine and having PVC lipping all round the seat and back. The back shall be designed with contoured lumber support for extra comfort. Two Nos of one piece arm rest made of black integral skin polyurethane with 75-85 shore 'A' hardness & reinforced with MS insert and shall be scratch and weather resistant. 04 Nos of rubber stopper shall be provided at the bottom of chair as shown on drg. The quality and colour of fabric shall be as approved by the GE.
3	FD-229	Chair Easy Overall size shall be 510 mm long, 575 mm wide, and 720 mm high, all wood shall be first class teak wood (MP), well seasoned free from cracks and knots. Caning shall be done with plastic cane of 2 mm side and 0.40 mm thick half round gola type weighing not less than 06 gms per 10 running meters. Caning shall be done in Godrej pattern. PVC shoes 25x25 mm shall be provided at bottom of all legs. Finishes:- All wood surfaces, exposed to view when placed in position shall be given high gloss French polish with lacquer finish after preparation of surface. Rest all as shown on drawing.
4	FD-277	Peg Table All as shown on drawing. All work shall be of first class hard wood teak (MP). The overall size of Peg table shall be 450mm long, 300mm wide and 380mm high. Top of table shall be made of 18mm thick exterior grade teak faced pre-laminated particle board. 04mm thick teak wood beading shall be provided all around the top of the table. Legs shall be of teak wood of section 30mmx50mm. Top long and short rails connecting the legs at top shall be of 20x40mm in section of teak wood. Two Nos of short stiffeners each between the legs at 100mm from bottom shall be provided to the Peg Table. All wooden surfaces exposed to view when placed in position shall be french polished with high gloss finish after preparation of the surfaces. Hard rubber/PVC shoes shall be fixed to the bottom of legs of the Peg Table.
5	FD-274	Table center All timber work shall be first class hard (Teak Wood) well seasoned. All dimension shape and size shall be as per drawing. Table top shall be made with 18 mm thick pre-laminated particle board exterior grade with teak veneer shade and standard PVC edging around the top of the table. The particle board shall be of Make "NOVAPAN AND ARCHID LAM" respectively as approved by GE. All exposed surfaces of wood work shall be french polished except bottoms to table top and bottom of leg and PVC toes shall be provided to the bottom of legs. Rest all as per specified and shown of Metal waiting chair three seater
6	FD-TP	Overall size (in mm) 1765(L) x 710(D) x 775(H). Visitor sofa three seater with powder coated Arms & legs, perforated powder coated seat & back.
8	FD-1032	Almirah Medium Steel All as shown on drawing. Overall size shall be 760 mm long, 440mm wide and 1270mm high. Top, sides, bottom, back, front and shelves of almirah shall be of 01mm thick MS sheet. Front shutters shall have two leaves. Three shelves equally spaced making four compartments shall be provided to Almirah. A steel chromium plated handle 100mm long with three way locking device shall be provided to front shutters with 75mm long, 06 lever, ISI marked brass lock. Each leaf of front shutter shall be hinged with two numbers butt hinges 75mm long and shutters shall be side hung. All joints and welding, fixing shall be done in accordance with standard workmanship. All steel members/surfaces exposed to view when placed in position shall be painted with two coats of synthetic enamel paint internally and externally over a coat of red oxide primer after preparation of surface with spray machine. The colour and shade of the Paint shall be as approved by the GE.

9	HFD/2019	Cough examination Overall size shall be 1900 mm long x 600 mm wide x 800/810 mm high and designed for maximum patient comfort, hygiene, and versatility, featuring durable metal frames (Often CRCA steel) with high density foam mattress covered in easy to clean, fire-resistant, and waterproof leatherette. Adjustability motorized the headrest, backrest upto 85 degree and overall height to ensure ergonomic positions for both patients and practitioners, Storage integration come with built in cabinets and drawers, optimizing space for medical supplies. Hard rubber/PVC toes shall be provided to bottom of legs. The colour and shade of the paint shall be as approved by the GE.
10	FD/MAP-II/01	Charpoy IP ply top All as shown on drawing. The overall size of the chimney shall be 900 mm long, 600mm wide and 400mm high. The frame of chimney shall be made of 25mm x 5mm rectangular spike (18 gauge) and equal distance shall be made of 25mm x 25mm square MS pipe (18 gauge) as shown on drawing. The legs of chimney shall be made of 25 x 25 x 2 mm MS square pipe and bottom frame of chimney shall be fabricated by using MS angle of 25mm x 25mm x 5mm. No. of strips shall be provided on bottom side of chimney suitable as per ISI marked BWR phenol bonded exterior grade commercial board of 12mm thickness shall be provided in bottom of chimney for making it leak proof, on top of this 3mm thick rubber sheet shall be fixed with adhesive. All steel surface exposed to view when placed in position shall be black powder coated.
11	FD-1026	Stool revolving adjustable steel All as shown on drawing. Overall size shall be 510mm diameter at bottom and 750mm high when in lowest position of adjustable. Use 25 mm square mild steel pipe with 1.6mm thickness. Padded seat covered with rexine in olive green color Hard rubber/PVC toes shall be provided to bottom of legs. All steel surfaces exposed to view when placed in position shall be given two coats of enamel paint over a coat of primer with spray machine after preparation of steel surfaces.
14	FD-1003	Table office officer steel All as shown on drg. Overall size shall be 1680mm long, 870mm wide and 760 mm high. Steel frame of overall size shall be of 1600mm long, 565mm wide and 740mm high. Four legs of 25mm mild steel tube of 1.6mm wall thickness shall be provided as shown on drg. Top of legs shall be joined together with U-shaped frame of 25mmx40mm of 1mm thick sheet. Three drawers shall be provided on right hand sides of table. A cupboard with front openable door shall be provided on the left hand side of the table as shown in front elevation of drg. A shelf be provided in the middle of cupboard. All sheet for drawer, shelf and cupboard and back covering shall be of 1mm thick MS black sheet. Irrespective of what is shown on drawing the top of table shall be made of 18mm thick exterior grade pre-laminated particle board both side teak faced with 04mm thick teak wood beading all around the top duly melamine polished. Hard rubber/ PVC shoes shall be provided to all legs. Locking device shall be provided to drawers and shutters of cupboard. All steel surfaces exposed to view when placed in position shall be painted with two coats of synthetic enamel paint over a coat of primer after preparation of surfaces with spray machine. The colour and shade of the paint shall be as approved by the GE.
17	FD-1038	Rack adj 6 tier steel All as shown on drawing. Overall size shall be 915mm long, 610mm wide and 1905mm high. (The width is variable and shall be considered for procurement as per the requirement of users. However this specification has been considered with 610mm width.) four vertical angle iron of 40mmx40mmx4mm shall be provided at four corners. Top, bottom, sides, back, shelves shall be of 1 mm thick mild steel sheet. The bottom sheet shall be at 100mm from bottom. Five shelves equally spaced to make six equal compartments shall be provided of 1 mm thick mild steel sheet. Four 75mmx75mmx3mm flat iron cut to shape to form angular brackets shall be provided on front side as shown on drawing. All steel surfaces exposed to view when placed in position shall be given two coats of enamel paint over a coat of primer with spray machine after preparation of steel surfaces.
20	FD/IE6/MAP/13	Receptacle PVC Receptacle shall be made of thick polymer plastic and of capacity 20 Ltrs with pendulum type lid and steel handles on both sides all as shown on drawing. The colour shall only be Red, Green or Blue. The Contractor may also provide the readymade Receptacle PVC of Make :- Milton, Cello or Britte with same specifications.
21	FD-1023	Side rack with tray steel All as shown on drg. Overall size shall be 840mm long, 355mm wide and 810mm high. Four MS angle iron 40x40x3mm shall be provided as legs and shall be 810mm high. Mild steel sheet shelves made to shape shall be welded to angle iron legs at 100mm from bottom and 50mm from top. The middle shelf shall be equally spaced between top and bottom shelves. The thickness of sheet shall be 1mm. Top shelf shall have three compartments or spaces equally spaced with 50mm high partition and back covering with 1mm thick MS sheet. All steel surfaces exposed to view when placed in position shall be given two coats of synthetic enamel paint over a coat of primer after preparation of surfaces. Painting shall be done with spray machine. The colour and shade of the paint shall be as approved by the GE.

22	FD-83 (M)	Screen Moveable steel All as shown drawing Screen moveable shall be of three fold middle span shall be 1200mm wide and the sides shall be equally spaced. Overall size shall be 1650mm high and 2400mm wide. Frame shall be made out of 25mm dia conduit with all thickness 1.6mm, six number ball bearing rubber castors of 50mm dia shall be provided at bottom as shown on drawing. The springs for curtains. Curtains shall not be provided by contractor. All steel and iron surfaces exposed to view when placed in position shall be given two coats of enamel paint, white color, over a coat of primer after preparation of surfaces as directed by GE. Painting shall be done with spray machine.
23	FD-81 (M)	Stool steel 305x305x760mm All as shown on drg. The overall size shall be 305mm long, 305mm wide and 760mm high. The whole stool frame including stiffeners shall be made of 01mm thick MS sheet. All steel surfaces exposed to view when placed in position shall be given two coats of synthetic enamel paint over a coat of primer after preparation of surfaces. Painting shall be done with spray machine. The colour and shade of the paint shall be as approved by the GE.
24	FD-1013	Table tubular stainless steel (2100 x 900 x 760 mm) All as shown on drawing. Overall size shall be 2100mm long, 900mm wide and 760mm high. 100 mm Nominal thickness stainless steel sheet on top. Four legs shall be of 25mm square mild steel tube of wall thickness 1.6mm. Legs shall be joined together with top rails of 25mm square mild steel tube of wall thickness 1.6mm. Hard rubber/PVC toes shall be provided to bottom of legs. All steel surfaces exposed to view when placed in position shall be given two coats of enamel paint over a coat of primer with spray machine after preparation of steel surfaces.
25	FD-TP	Bed Fowler steel Overall size shall be 2200 mm long x 900mm wide x 600 mm high and with high density foam mattress covered in easy to clean, fire-resistant, and waterproof leatherette. Material primarily Mild steel (MS) or cold rolled close annealed (CRCA) steel for the main frame and mattress base. Finishing pretreated and epoxy powder coated to resist and ensure easy cleaning. Frame structure strong MS tubular frame 60mm x 30 mm x 1.6 mm ERW Tube. Thickness 16 to 18 gauge steel is commonly used for tubing and sheets. Load capacity frequently rated for 150 kgs or more. Main frame 60mm x 30 mm x 1.6 (16/18G) ERW Tube, Support section 25mm x 1.6 mm and linkage 40 mm x 20 mm x 1.6mm tube. Hard rubber/PVC toes shall be provided to bottom of legs. The colour and shade of the paint shall be as approved by the GE.

IC Furniture

DRAFT COSTED SCHEDULE (FURNITURE PORTIO

Name of work: Provn of Gua
items)

Unit: GE (N) Pattala

oliet & bathroom for Bn Main Gate at 601 Erme Bn at old Cantt

Sr No.	Drq No.	Description of Items
1	2	3
1	FD/E6/MAPI3	Reci Reci type Gre... :- Milton, Cello or Brite with same specifications.
2	FD-1007	Table 900x600x760mm without drawer steel All as shown on drg. The overall size shall be 900mm long, 600mm wide and 760mm high. The frame shall be made up of 25mm Sq MS pipe having 1.6mm wall thickness. The top of the Table shall be made up of 18mm thick teak faced exterior grade pre-laminated particle board with 04mm thick teak wood beading all around the top duly french polished. All steel surfaces exposed to view when placed in position shall be given two coats of synthetic enamel grey paint over a coat of primer after preparation of surfaces. Painting shall be done with spray machine. Hard rubber/PVC shoes shall be fixed to the bottom of legs of the Table.
3	FD/MAPI-II/01	Charpoy with Hard Top All as shown on drawing. The overall size of the Charpoy shall be 1980mm long, 900mm wide and 440mm high. The frame of the Charpoy shall be made of 25mmx65mm rectangular MS pipe (16 gauge). The Charpoy shall have 02 Nos of stiffners of 25mmx25mm square MS pipe (16 gauge) at equal distance and fixed to charpoy as shown on drawing. The legs of the charpoy shall be made of 32x32 x16 gauge MS Sq tube. 01 No. of stiffner of 25mmx25mm square MS pipe (16 gauge) shall be provided between the legs at 150mm from bottom along short side. 12 mm thick ISI marked, BWR phenol bonded exterior grade commercial plywood of suitable size shall be fixed on the top of charpoy. MS plate of 32x32x5mm shall be welded at bottom of legs and under which 03mm thick rubber sheet shall be fixed with adhesive. All steel surfaces exposed to view when placed in position shall be black powder coated.

4	FD/E6/MAPI/12	Chair Writing (MAP) All as shown on drg. The frame shall be made of 25mmx10mm in section MS tubular frame cantilever type and shall be black powder coated. The Seat and back shall be made of 12mm thick hot pressed plywood upholstered with fabric and moulded polyurethane foam (50mm thick) having density 50-55 Kg per Cu Mtr and hardness 20+/-2 Kg on Hampden machine and having PVC lipping all round the seat and back. The back shall be designed with contoured lumber support for extra comfort. Two Nos of one piece arm rest made of black integral skin polyurethane with 75-85 shore 'A' hardness & reinforced with MS insert and shall be scratch and weather resistant. 04 Nos of rubber stopper shall be provided at the bottom of chair as shown on drg. The quality and colour of fabric shall be as approved by the GE.
5	FD-TP	Metal waiting chair Q3 seater All as per make and model. A 03 seater metal perforated waiting chair in single piece with arms and legs made of steel and duly chrome plated and powder coated in glossy silver finish of Make :- Geeken, Model :- Spacio or equivalent with similar specifications of make Godrej, Neelkamal.
6	FD TP	Rifle Rack for Ten Rifles The overall size of the rifle rack shall be 48 inch long, 15 inch wide and 36 inch high single fire including ammunition box and mounting fixtures. The rifle shall be thief proof and single fire to accommodate ten numbers of rifles. Make: KAYPEE & CO., Model: RIFLOK. The contractor may supply the equivalent other approved make rifle rack with the same specifications and similar price.
		Total Amount


Offg BSO (N) Patiala

Scourtinged with APPR

copy BSO