

		5	6
1	Taking down copper/aluminium point wiring (light, fan, socket or power) complete, including fixture and fittings such as switches, ceiling roses, pendants, regulators, sockets, light fitting etc. removing materials to store for keeping in safe custody or for taking credit (credit for above items should be made as per conditions separately) and making good disturbed surfaces of walls, floors, etc.	Point	375
2	M&L for concealed conduit for one light point wiring with 1.5 Sqmm (nominal cross-sectional area) PVC insulated unsheathed single core copper cable working voltage 1100 volts grade conforming to IS-694 with stranded copper conductor in and including PVC conduit of adequate size with all accessories (including cutting chases & making good the disturbed surface to its original specification) including MS sunk box, 3mm thick hylum sheet top cover fixed by means of brass machine screw and cap washer including size 1.5 sq mm (nominal cross sectional area) PVC insulated unsheathed single core multistranded copper conductor cable as earth continuity conductor connected to main switches/DB's or common earth dolly complete all as specified and directed for the following :	Point	90
3	All as per item No 2 here in before but for one Ceiling Fan / exhaust fan point controlled by one, one way switch and regulator	Point	20
4	all as per item No 2 here in before but for one 3 point 5 Amps switch socket outlet point controlled by one switch on the same board.	Point	10
5	All as per item No 2 here in before but for one 3 pin 5 Amps switch socket outlet point controlled by one switch on independent board .	Point	30
6	All as per item No 2 here in before but for one bell point controlled by one, bell switch 5 Amps	Point	8
7	All as per item No 2 here in before but using 2.5 sq mm single core copper conductor cable of multistranded FRLSH PVC insulated unsheathed 1100 volts grade for 5/15 amps switch socket combination point	Point	20
8	All as per item No. 2.00 here -in- before but wiring with 4.0 Sq mm single core copper conductor cable of multistranded FRLSH PVC insulated unsheathed 1100 volts grade for power point metal plug earth socket	Point	6
9	M&L point wiring using approved colour coding as per IS by using FRLS PVC insulated 1.5 Sqmm multistranded, 1100 volt grade copper conductor cable unsheathed type, alongwith 1.5 Sqmm FRLS PVC insulated stranded copper conductor cable for continuous earthing in & incl PVC casing & capping with accessories having ISI mark fixed on wall surfaces / ceiling including concealed of suitable sunken box and hylum sheet for fixing switches, sockets, regulators, etc. for one light point controlled by one switch complete all as specified and directed.	Point	90

10	All as per item 9.00 here in before but for one Ceiling Fan / exhaust fan point controlled by one, one way switch and regulator	Point	20
11	All as per item 9.00 here in before but for one 3 point 5 Amps switch socket outlet point controlled by one switch on the same board.	Point	10
12	All as per item 9.00 here in before but for one 3 pin 5 Amps switch socket outlet point controlled by one switch on independent board.	Point	30
13	All as per item 9.00 here in before but for one bell point controlled by one, bell switch 5 Amps	Point	15
14	All as per item No 9 here in before but using 2.5 sq mm single core copper conductor cable of multistranded FRLSH PVC insulated unsheathed 1100 volts grade for 5/15 amps switch socket combination point	Point	20
15	All as per item No. 9 here -in- before but wiring with 4.0 Sq mm single core copper conductor cable of multistranded FRLSH PVC insulated unsheathed 1100 volts grade for power point metal plug earth socket	Point	6
16	S & F switch piano single pole flush type 5 amps, 230 volts. complete all as specified and directed.	Each	220
17	S & F bell push flush type 5 amps, 230 volts. complete all as specified and directed.	Each	23
18	S & F socket combination flush type multipurpose 2/3 pin 5 amps 2 in 1, 230 Volts all as specified.	Each	20
19	S & F switch socket combination flush type multipurpose 2/3 pin 5 amps 2 in 1 230 Volts complete all as specified and directed.	Each	60
20	S & F switch socket combination 2 in 1 multipurpose 3/5 pin 5/15 amps flush type complete all as specified	Each	40
21	S & F ceiling rose three terminal surface bakelite type AC 50 Hz 230 volts of size 65 x 50 mm complete all as specified and directed.	Each	395
22	S & F ceiling fan regulator step type, flush type heavy duty suitable to work on 230 volts Ac supply complete all as specified and directed.	Each	20
23	S & F lamp holder insulated body surface bakelite with back plate suitable for angle / batten fittings fixed with PVC round/square blocks complete all as specified and directed.	Each	20
24	S&F in repair switch piano single pole flush type 5 amps, 230 volts including removal old existing unsv one complete all as specified and directed.	Each	300
25	S&F in repair switch socket combination flush type multipurpose 2/3 pin 5/15 amps 2 in 1 230 Volts all as specified including removal old existing unsv one complete all as specified and directed.	Each	100
26	S&F in repair switch socket combination 2 in 1 multipurpose 3/5 pin 5/15 amps flush type including removal old existing unsv one complete all as specified and directed.	Each	50
27	S&F in repair ceiling rose three terminal surface bakelite type AC 50 Hz 230 volts of size 65 x 50 mm including removal old existing unsv one complete all as specified and directed.	Each	300
28	S&F in repair ceiling fan regulator step type, flush type heavy duty suitable to work on 230 volts Ac supply including removal old existing unsv one complete all as specified and directed.	Each	50
29	S&F in repair lamp holder insulated body surface bakelite with back plate suitable for angle / batten fittings fixed with wooden round blocks including removal old existing unsv one complete all as specified and directed.	Each	30

30	S&F in repair call bell suitable to work on 230 volts Ac supply including removal of old unsv call bell complete all as specified.	Each	20
31	S & F LED Lamp 9/10 Watt with B 22 base complete all as specified.	Each	50
32	S & F new energy saving rechargeable LED bulb 9 Watt, Base-22, 240 V , CCT- 6500K polycarbonate body , Lamp life 15000 Working Hours complete all as specified and directed.	Each	50
33	M&L Sheet metal enclosure with Single pole and neutral enclosure with a two pin and earth plug and socket complete with one two pole MCB 20 Amp, 10 KA complete all as specified and directed.	Each	12
34	M&L in repair Sheet metal enclosure with Single pole and neutral enclosure with a two pin and earth plug and socket complete with one two pole MCB 20 Amp, 10 KA complete all as specified and directed.	Each	15
35	Taking down the existing unserviceable main switch/ cut out/ DBs of any type/ capacity/ description as existing at site including making good the disturbed surfaces to match with the existing finishes all as specified.	Each	40
36	S&F sheet metal enclosure for VT DB,TPN, MCB DB TPN 4 way (with provision for MCCB as INCOMER and MCB as out going). Confirming to IS as per IEC 61439-3, IP 43, double door including 63 Amp, 25 KA, TP MCCB as incomer (Vertical type double door, 63 Amps MCCB rate inclusive) including fixing the DB box flush in wall of any type and making good the disturbed surface to match as the existing complete all as specified and directed by Engr-in-Charge.	Each	2
37	S & F sheet metal enclosure for MCB, DB, TPN 415 Volts, IP 43, 100 amps rated copper busbar 4 way Double door (Vertical DB with prov of MCB as incomer) Confirming to IS as per IEC 61439-3 including fixing the DB box flush in wall of any type and making good the disturbed surface to match as the existing complete all as specified and directed by Engr-in-Charge.	Each	20
38	S & F sheet metal enclosure for MCB, DB, SPN, 240 Volts, 100 Amps rated busbar, Confirming to IS as per IEC 61439-3, 8 way Double door enclosure made up of CRCA sheet steel, RAL 9003 powder coated, IP 43 , IK 09 including fixing the DB box flush in wall of any type and making good the disturbed surface to match as the existing with all as specified and directed by Engr-in-Charge.	Each	12
39	All as per item No 38 but of 4 Way Double door.	Each	6
40	S & F MCB TPN 63 to 100 Amps, 415 volts, 10KA , C Series suitable for fixing in MCB DB incl taking down old Unsv complete all as specified.	Each	40
41	S & F MCB SPN, 32 - 63 Amps , 230 volts 10 KA, C Series suitable for fixing on MCB DB incl taking down old Unsv complete all as specified.	Each	20
42	S & F MCB SP 6 to 30 Amps 240 volts C Series for fixing on MCB DB's incl taking down old Unsv complete all as specified.	Each	250
43	Supply and fixing of moulded case circuit breaker (MCCB) four pole Adjustable type 415 volt, 50 Cycles, 63 Amps of breaking capacity 25 KA after and including taking down / dismantling of old existing unserviceable one complete all as specified and as directed.	Each	4
44	Supply and fixing of moulded case circuit breaker (MCCB) four pole Adjustable type 415 volt, 50 Cycles, 125 Amps of breaking capacity 25 KA after and including taking down / dismantling of old existing unserviceable one complete all as specified and as directed.	Each	4

45	Supply & fixing in repair sheet metal enclosures triple pole and earth plug with socket, as per IEC 61439-3 complete with one four pole MCB of capacity 63 A (3P+N+E-FP), 415 V, with neutral links including taking down unserviceable one all as specified and directed by Engineer in charge.	Each	2
46	Taking down the existing unserviceable sub main wiring of any type / description as existing at site including making good the disturbed surfaces to match with the existing finishes all as specified.	RM	480
47	S&F for Sub main wiring with Four run of single core (3 phase) PVC insulated unsheathed cable 1100 volts grade, 6.0 Sqmm size with multistranded copper conductor, FRLSH cable drawn in with and including PVC casing capping not less than 32 mm ISI marked including all accessories of casing capping including one run of PVC insulated unsheathed 6.0 Sqmm cable with multistranded copper conductor green PVC insulated as continuous earth conductor cable connected to earth dolly complete all as specified and directed by EIC. (4 x 6.0 sqmm + 1 x 6.0 Sqmm earth wire).	RM	120
48	All as per Item No 46 here in before but of size 6 Sqmm 3 core for single phase phase, Neutral and Earth. (2 x 6.0 sqmm + 1 x 6.0 Sqmm earth wire).	RM	180
49	All as per Item No 46 here in before but of size 4 Sqmm 3 core for single phase phase, Neutral and Earth. (2 x 4.0 sqmm + 1 x 4.0 Sqmm earth wire).	RM	150
50	All as per Item No 46 here in before but of size 10 Sqmm 5 core for three phase, Neutral and Earth. (4 x 10.0 sqmm + 1 x 10.0 Sqmm earth wire).	RM	30
51	S&F LED light fitting 20W, 4ft, 220 volt AC, having colour temperature day light (6500K), Decorative ultra slim square profile LED lighting fixture with extruded polycarbonate incl taking down old unsv complete all as specified and directed. Make : Havells/Crompton/Philips/Orient/HPL	Each	300
52	Supply & fixing in repair Ultra bright LED tube rod 18 Watt (G-13 Lamp Holder) 240 V, PF > 0.90, colour Temp 6500 K, System Luminous efficacy > 110lumen per watt, to be fixed in existing or new batten/ patti including changing the wiring suitable for T8 LED retrofit lamp in existing tube light fitting complete	Each	80
53	S&F LED light fitting 9/10W, 2ft, 220 volt AC, having colour temperature day light (6500K), Decorative ultra slim square profile LED lighting fixture with extruded polycarbonate incl taking down old unsv complete all as specified and directed. Make : Havells/Crompton/Philips/Orient/HPL	Each	80
54	S & F Energy saving new generation environmental friendly long life versatile pressure die cast aluminium IP 66 security light fitting luminaire with high power LEDs as light source and electronic driver of capacity 25 watts with pre wired and necessary mounting arrangements, provision of new 3 core multistranded copper conductor of size 23/0.193 from ceiling rose to fitting and GI pipe bracket made out of GI pipe medium grade 32 mm dia 1.5 mtr long bend to required shape complete incl removal of old unsv fitting all as directed by	Each	15
55	S&F LED light fitting 1x9W/1X10W/bulkhead luminaires including LED light driver holder connecting up with three core flexible copper conductor cable of suitable size and taking down old Unsv light complete all as specified and directed. Make : Havells/Crompton/Philips/Orient/HPL	Each	15
56	S&F in replacement of LED 25 W Post Top Lantern, energy saving, environmental friendly, long life aesthetically designed with symmetrical light distribution, spun aluminium landscape luminaire with IP66 protection high power LED as light source incl taking down old Unsv complete all as specified and directed.	Each	6

57	Taking down existing panel light fitting any type and S&F in replacement LED luminaire 600 mm x 600 mm, 35/36 watt, 220 V AC, having colour temperature day light (6500K), Ultra modern recess mounting luminaire with high performance LEDs, suitable for mounting with Armstrong/Grid ceiling incl taking down old unsv light fitting complete all as specified and directed. Make : Havells/Crompton/Philips/Orient/HPL	Each	30
58	S & F LED downlight recess/Surface mounted nominal power 12 Watt, frequency of 50 Hz, lumen output of minimum 1080, lumen efficacy of minimum 90 lumens per watt, isolated electronic LED driver with output short circuit protection, surge voltage protection upto 2 KVs, complete all as specified and as directed. Make : Havells/Crompton/Philips/Orient/HPL	Each	10
59	Supply and fix Round highway LED light 100 watt operational voltage of 170 volts to 270 volts, frequency of 50 Hz, lumen efficacy of minimum 100 lumens per watt, isolated electronic LED driver incl taking down light fittings from any height up to 18 mtrs complete all as specified and as directed. Make : Havells/ Crompton/ Philips/ Orient	Each	8
60	Taking down old unserviceable light fitting and Supply & fixing in replacement of LED 8 W landscape lighting bollard type pressure die cast powder coated housing with PC diffuser, efficient light output LED using 2 core PVC insulated cable aluminium conductor 2.5 Sqmm approx 2 m length complete all as specified and directed. Make : Havells/Crompton/Philips/Orient/HPL	Each	8
61	Supply and fix of LED Aviation Obstruction light (Red Colour) incl taking out old u/s fitting complete all as specified and directed as per Engg-in-charge . CAT No - GLN-703 of make crompton or equivalent to Balaj/Philips/Havells.	Each	4
62	S&F in repair hylam sheet 3 mm thick white in colour of size 130 mm x 180 mm including taking down existing unserviceable complete all as specified and directed.	Each	30
63	S&F in repair hylam sheet 3 mm thick white in colour of size 120 mm x 170 mm including taking down existing unserviceable complete all as specified and directed.	Each	30
64	S&F in repair hylam sheet 3 mm thick white in colour of size 230 mm x 280 mm including taking down existing unserviceable complete all as specified and directed.	Each	30
65	S&F in repair hylam sheet 3 mm thick white in colour round type of size 80 mm dia including taking down existing unserviceable complete all as specified and directed.	Each	20
66	S&F in repair modular switch 1 way 6A, 1 Module complete all as specified and directed	Each	100
67	S&F in repair modular switch 1 way 16A, 1 Module complete all as specified and directed	Each	40
68	S&F in repair modular bell switch 1 way , 1 Module complete all as specified and directed	Each	10
69	S&F in repair modular socket 6A 2/3 Pin combined -2 module including repairing/replacement of whole modular fittings and frame with new one as per existing fittings complete all as specified and directed by EIC	Each	50
70	S&F in repair modular switch socket combination 16A , 6 Pin combined -3 module including repairing/replacement of whole modular fittings and frame with new one as per existing fittings complete all as specified and directed by EIC	Each	50
71	Supply and fixing in repair of stepped type Modular electronic fan regulator 1- module , 100 watt flush type , on the existing hylam laminated sheet etc as required, complete all as specified and directed by EIC . including taking down old u/s Make: Anchor (Roma) cat No :- 289510 or equivalent of make : Legrand/	Each	20

72	S&F in repair Modular metal flush box of 1/2 module with white cover plate including make good to match with existing surface complete all as specified and directed by EIC.	Each	20
73	S&F in repair Modular metal flush box of 3 module with white cover plate including make good to match with existing surface complete all as specified and directed by EIC.	Each	20
74	S&F in repair Modular metal flush box of 4 module with white cover plate including taking out u/s including make good to match with existing surface complete all as specified and directed by EIC.	Each	20
75	S&F in repair Modular metal flush box of 6 module with white cover plate including taking out u/s including make good to match with existing surface complete all as specified and directed by EIC.	Each	20
76	Material and labour for earthing complete with galvanized steel plate electrodes of size 600x600x6mm thick buried directly in ground with earth pit not less than 2.25 meter deep below normal ground level with top edge of plate not less than 1.5 meter below normal ground level connected to galvanised wire 4.00 mm earth lead by means of nuts, bolts, checknuts and washers including 15 mm bore galvanized iron pipe, medium grade for protection of earth lead upto the length of 7.5 meter towards test terminal and 20 mm bore galvanized iron pipe, medium grade for watering, and providing of charcoal and common salt in alternate layers, including necessary earth work if any type of soil and including PCC pit in PCC 1:2:4 with provision of wire mesh and funnel, complete all as shown in electrical plate No 5 of SSR Part-1 including testing on	Each	8
77	S&F LED wall light (Bed side light) fitting for study table including 3 watt LED, aluminium body, including LED driver with on /off button switch ,flexible pipe with lamp head 360 degree rotating type, 220 Volts mounted on wall as per sample including connecting with PVC insulated multistranded copper flexible cable 0.5 sqmm three core, in casing capping and including taking connection from nearest socket/ light point and light to be fixed/ mounted on PVC rectangular box white colour complete all as specified & directed.	Each	50
78	Attending complaints of Geyser of any capacity any type from exiting position for checking of heating element, thermostat, and all accessories incl electrical connection etc, removing defected parts and re-assembling the same and refixing to its existing location with testing for its proper functioning complete all as specified and directed by Engr-in-charge. NOTE: (i) Complaints should attend within 24 hrs after receipt of complaints from Complaint cell . (ii) If any spares required then spares shall be measured and paid separately under relevant items of the schedule . (iii). One	Each Job	100
79	M& L for dismantling Geyser of any capacity any type from exiting position for descaling, removing its accessories removing the scale (white presipated) deposited in it, cleaning the inner tank properly, painting with spray gun and re-assembling the same and refixing to its existing location with testing for its proper functioning complete all as specified and directed by Engr-in-charge. NOTE: (i) If any spares required then spares shall be measured and paid separately under relevant items of the schedule . (ii) The said job shall be done in MES workshop after dismantling from its original /existing location and	Each Job	50
80	Supply only inner container SS or as per sample suitable for vertical type geyser 50 ltrs storage capacity including taking down of defective container as per OEMs specifications complete all as specified and directed	Each	10
81	All as per item No above here in before but 25 Ltr Capacity complete all as specified and directed.	Each	20

82	Supply only in repair Thermostat 0-75 Degree as per existing size as per OEMs specifications complete all as specified and directed	Each	100
83	Supply only in repair Heating element 1.5 KW, as per OEMs specifications all as specified and directed	Each	50
84	Supply only in repair Heating element 2 KW, as per OEMs specifications all as specified and directed	Each	50
85	Supply only Indicator lamp with flexible copper wire of suitable size Red/Green including taking down of defective indicator lamp complete all as specified and directed.	Each set of two	20
86	Supply & fixing PVC Connection with steel reinforced pipe for hot water connection of Size 18" x 1/2" including rubber washers including taking down of defective blade complete all as specified and directed	Each	40
87	Supply only Apperture plate SS suitable for 25/50 ltrs geyser along with rubber gasket, nuts, bolts, etc as per OEMs specifications complete all as specified and directed	Each	40
88	Supply and fixing in repairs plug top 15/16 Amps suitable for geyser socket outlet complete all as specified and as directed.	Each	40
89	S&F in repair stop valve but fancy type, chromium plated, screwed down (CP) of size 15 mm fancy type complete all as specified and directed.	Each	60
90	M&L in repair bib taps, cast copper alloy with butterfly handle, screwed down, screwed for iron pipe or for brass ferrule and fixed for bib tap 15 mm dia fancy type all as specified and as directed.	Each	60
91	M&L for complete servicing of solar hot water system (solar water heater, flat plate collector type), with cleaning of sludge deposited in pipe line of solar panel by using cleaning regent, check and repair of pipe line for any leakage, including carrying out brazing of copper pipe for leakage, cleaning of glass shell, cleaning of hot water tank, replacement of u/s clamps, adapter, hose pipe including filling of distilled water and coolant in reservoir including complete servicing to keep the plant functional of capacity up to 200 LPD.	Each	40
NOTES:- (i) Servicing shall be carried out through authorised technicians or as approved by GE.			
92	M&L in repair for replacement of thermostat, long body, ISI marked of solar water heater of cap up to 200 LPD including taking down of defective thermostat complete all as specified and directed	Each	60
93	M&L in repair for replacement of electrical heating element of 1.5/2.0 KW ISI marked (long thread type, as per existing), ISI marked, of solar water heater of cap up to 200 LPD including taking down of defective element complete all as specified and directed. Make: Solar Element or equivalent make as approved by GE	Each	60
94	M&L for replacement in repair hot water pipe insulation with glass wool and aluminium cladding 20 mm bore including all material complete all as specified and directed	RM	20
95	M&L for replacement in repair hot water pipe insulation with glass wool and aluminium cladding 40 mm bore including all material complete all as specified and directed	RM	20
96	S&F in repair to solar collector plate panel as per existing size, specification and make of capacity up to 200 LPD incl all accessories complete all as specified and as directed by Eng-in-charge.	Each	4

97	S&F in repair to solar water heater tank as per existing size , specification and make of capacity upto 300 LPD incl all accessories complete all as specified and as directed by Engineer-in-charge .	Each	4
98	S&F CIMFR certified LED flame proof batten suitable for single T8 tube of 20 Watt , IP 65 protected , including 1 x 20 W LED tube 240 Volt, recommended for Gas / Vapour group of IIA & IIB and Zone 1&2, complete including connecting with PVC insulated multi stranded copper flexible cable 0.5 sqmm three core, Make: Crompton /Sudhir / Shyam Switchgears Pvt ltd	Each	20
99	S&F CIMFR certified LED flame proof bay light, 60 watt, Well glass in die cast Al housing with heat resistant toughened glass, IP 65 protected. 240 Volt, PF> 0.90 , System Luminous efficacy> 100Lm/W, Recommended for Gas / Vapour group of IIA & IIB and Zone 1&2 complete including connecting with PVC insulated multi stranded copper flexible cable 0.5 sqmm three core, Make: Crompton /Sudhir / Shyam Switchgears Pvt ltd.	Each	8
100	S&F Flame proof weather proof rotary switch with cable termination box in LM 6 aluminium alloy housing single Pole 16 Amp, 250 volts complete all as specified and as directed. Make : Make : Sudhir / Shyam Switchgears Pvt ltd.	Each	24
101	S&F Flame proof - weather proof switch socket & plug combined 16 A, 250 V(2P+Earth) with cable termination in LM 6 aluminium alloy housing with plug complete all as directed. Make : Sudhir / Shyam Switchgears Pvt ltd	Each	10
102	S&F Flame proof - weather proof switch socket & plug combined 32 A, 500 V(4P+Earth) with cable termination in LM 6 aluminium alloy housing with plug complete all as directed .Make : Sudhir / Shyam	Each	5
103	S&F flame proof weather proof metallic hose conduit 3/4 " dia , M20 /3/4" conduit MxM / FM x M / Fx F 3/4 " dia 300 mm long incl complete all as specified and as directed.. Make : Sudhir / Shyam Switchgears Pvt ltd	Each	5
104	S&F flame proof weather proof metallic hose conduit 3/4 " dia , M20 /3/4" conduit MxM / FM x M / Fx F 3/4 " dia 500 mm long incl complete all as specified and as directed. Make : Sudhir / Shyam Switchgears Pvt ltd	Each	5