

TECHNICAL SPECIFICATION FOR CONSTRUCTION OF SYNTHETIC SURFACE VOLLEYBALL COURT

S No	Device	Description	Qty
1.	<u>Material and Labour for asphalt 30x19Mt</u>		570 sqmt
	(a)	Soil Treatment and spray of weed control chemicals	
	(b)	Laying of WBM hard stone soiling course 6"	
	(c)	Laying of asphalt BM in 80/100 grade bitumen for 40mm thickness in 19mm stone aggregate	
	(d)	Laying of asphalt BM in 80/100 grade bitumen for 25mm thickness in 6-8mm stone aggregate	
	(e)	Providing storm water drain	
	(f)	Providing the toe wall	
2.	<u>Synthetic all weather acrylic surface-ultra cushion system (8 layer)</u>		570 sqmt
	(a)	One layer ultra resurface/filter	
	(b)	Two layers of heavy cushion	
	(c)	Three layers of fine cushion	
	(d)	Two layers of colour	
	(e)	Court line markings	
3.	<u>Volleyball court Accessories complete supply and fixing</u>		01 Set
	(a)	Volleyball Poles of Iron Pipe adjustable Height 3"x4" in Pipe Provision of tightener for net	
	(b)	Net made of heavy synthetic cord with synthetic tape all four sides	
	(c)	Volleyball antenna made of fiber with red and white markings and synthetic tape for tightening in net and Velcro.	
	(d)	Volleyball referee chair made of 30mm round pipe with 25mm structure with stairs and provision for referee for standing.	01 Nos
	(e)	Volleyball scoreboard electric 4' x 3' with LED Display portable and movable on wheels	01 Nos
	(f)	Water removing roller more than 80 cm wide, adequate for all playing surface. It removes water when pushed forward or backward.	01 Nos
4.	<u>Chain link fencing</u>		300 Sqmt
	(a)	Proving to fabricate and creating of GI chain link fencing with 75mm x 75mm 10 gauge hexagonal shape on toe wall	
	(b)	Height of chain link fencing is 10 supported by 2" dia pipe space 10 apart.	
	(c)	Top and Bottom supported by 2 x 2 pipe with the provision of One/Two Gates complete with primer and enamel paints.	