

Sr No	Item	Qty	Specification
1	Table for Court staff	8	Supplying & Placing Modular table in completely knock down conditions with an overall size 1500mm X 750mm X 750mm that is to be assembled at site. The construction of the main table shall be free standing structure constructed with the help of minifix dowels and pins. The worktop shall be made up of 25mm thick particle board with approved laminate and finish as per approved shade. The top profile shall be in rectangle shape with front and back full round post form and other edges shall be sealed with 2mm thick thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. A pullout keyboard tray shall be provided of 18mm thick Pre-laminated particle board having size 550mm X 280mm. The tray shall be operated on keyboard channel. The top shall be supported over particle board base gable end. The end wall of the table on the side shall be topped by gable end. It should be made up of 25mm thick particle board and profile shall be in linear shape with front and back full round post form and other edge with appropriate PVC edge banding. The table shall be clad with 18mm thick modesty panel which provide structural support for the table. It should be 18mm thick pre-laminated particle board with appropriate PVC edge banding connected with both end. There shall be buffers provided at the base to avoid scratches on the floor. A mobile pedestal shall be provided with an overall size 400mm X 450mm X 650mm. The pedestal shall be made up of Pre-laminated particle board of grade II of IS 12823. Pedestal side, back, top, fascia shall be 18mm thick and drawer base shall be 9mm thick. The pedestal shall have 3 nos. of drawer i.e. 2 box drawer and 1 filing drawer. The drawer shall be operated with SS handle and easily close & open with the assistance of roller channel and ball bearing channel to enable smooth operation. The drawer shall have central locking mechanism in which all the drawer shall be synchronized locked with one single key. The pedestal shall be mounted over 50mm injection moulded nylon castor. A movable type CPU unit shall be provided with an overall size 468mm X 284mm. The CPU unit shall be made up of 18mm thick Pre-laminated particle board. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The board used should meet International Standard of quality, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of rupture and modulus of elasticity bending tested as per IS 2380..
2	Table for Authorized Representatives	8	Supplying & Placing Modular table in completely knock down conditions with an overall size 1500mm X 750mm X 750mm that is to be assembled at site. The construction of the main table shall be free standing structure constructed with the help of minifix dowels and pins. The worktop shall be made up of 25mm thick particle board with approved laminate and finish as per approved shade. The top profile shall be in rectangle shape with front and back full round post form and other edges shall be sealed with 2mm thick thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. A pullout keyboard tray shall be provided of 18mm thick Pre-laminated particle board having size 550mm X 280mm. The tray shall be operated on keyboard channel. The top shall be supported over particle board base gable end. The end wall of the table on the side shall be topped by gable end. It should be made up of 25mm thick particle board and profile shall be in linear shape with front and back full round post form and other edge with appropriate PVC edge banding. The table shall be clad with 18mm thick modesty panel which provide structural support for the table. It should be 18mm thick pre-laminated particle board with appropriate PVC edge banding connected with both end. There shall be buffers provided at the base to avoid scratches on the floor. A mobile pedestal shall be provided with an overall size 400mm X 450mm X 650mm. The pedestal shall be made up of Pre-laminated particle board of grade II of IS 12823. Pedestal side, back, top, fascia shall be 18mm thick and drawer base shall be 9mm thick. The pedestal shall have 3 nos. of drawer i.e. 2 box drawer and 1 filing drawer. The drawer shall be operated with SS handle and easily close & open with the assistance of roller channel and ball bearing channel to enable smooth operation. The drawer shall have central locking mechanism in which all the drawer shall be synchronized locked with one single key. The pedestal shall be mounted over 50mm injection moulded nylon castor. A movable type CPU unit shall be provided with an overall size 468mm X 284mm. The CPU unit shall be made up of 18mm thick Pre-laminated particle board. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The board used should meet International Standard of quality, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of rupture and modulus of elasticity bending tested as per IS 2380..
3	Chair for Court Staff	8	Supplying and placing ergonomically designed, comfortable & aesthetically appealing High back chair. The seat shall be made of metal insert MS CRCA chrome plated upholstered with high resilience polyurethane foam (30+19)mm thick having density 60kg/m ³ & 40kg/m ³ with black leatherite tapestry 0.8mm thick and 535 GSM and the back shall be supported by MS CRCA chrome finish upholstered with high resilience polyurethane foam 19mm thick having density 23kg/m ³ with black leatherite tapestry 0.8mm thick and 535 GSM with contoured lumbar support which helps to provide full back support and maintain the natural curvature of the spine. The seat and back shall be fixed with metal frame and the armrest shall be used PU arm completely joint with seat and back. The chair shall have swivel tilt 360 degree revolving mechanism with upright position locking and tilt tension adjustment. The pneumatic seat height adjustment for healthy seating, user can adjust seat height upto 120mm with BIFMA standard class-3 gaslift to suit them using the lever under the seat. The gas-lift mechanism should be tested as per ANSI/BIFMA X5.1-2011 standards. The Pedestal shall be made up of injection moulded black nylon having pitch circle Dia 700 mm fitted with 5 nos. 50mm twin wheel castors which shall be made of injection moulded black nylon 30% glass filled having self lubricating property for friction free movemen with BIFMA standards. The Seat size shall be 510±10 mm(W)X450±10 mm(D) and back size shall be 690±10 mm(H) from seat & overall height = 1110±10 mm.
4	Chair for Ars	16	Supplying and placing ergonomically designed, comfortable & aesthetically appealing Medium back chair. The seat shall be made of metal insert MS CRCA chrome plated upholstered with high resilience polyurethane foam (30+19)mm thick having density 60kg/m ³ & 40kg/m ³ with black leatherite tapestry 0.8mm thick and 535 GSM and the back shall be supported by MS CRCA chrome finish upholstered with high resilience polyurethane foam 19mm thick having density 23kg/m ³ with black leatherite tapestry 0.8mm thick and 535 GSM with contoured lumbar support which helps to provide full back support and maintain the natural curvature of the spine. The seat and back shall be fixed with metal frame and the armrest shall be used PU arm completely joint with seat and back. The chair shall have swivel tilt 360 degree revolving mechanism with upright position locking and tilt tension adjustment. The Hydraulic seat height adjustment for healthy seating, user can adjust seat height upto 120mm with BIFMA standard class-3 gaslift to suit them using the lever under the seat. The gas-lift mechanism should be tested as per ANSI/BIFMA X5.1-2011 standards. The Pedestal shall be made up of injection moulded black nylon having pitch circle Dia 650 mm fitted with 5 nos. 50mm twin wheel castors which shall be made of injection moulded black nylon 30% glass filled having self lubricating property for friction free movemen with BIFMA standards. The Seat size shall be 495±10 mm(W)X470±10 mm(D) and back size shall be 460±10 mm(H) from seat & overall height = 870±10 mm.
5	Chairs for Visitors Courts	75	Providing and supplying visitor chair with ergonomic design for user comfort. The seat and back shall be made of metal insert pipe frame padded with high resilience polyurethane foam (30+19)mm thick having density (60+40) kg/m ³ in seat 19mm thick having density 23kg/m ³ in back. The same shall be upholstered with leatherite tapestry 0.8mm thick and 535 GSM. The backrest of the chair shall be made by keeping the natural curvature of the spine with lumbar support. The armrest shall be used polyurethane arm completely joint with seat and back. The frame structure shall be cantilever support type made up of MS/CRCA chrome plated round pipe of Dia. 25.4mm with 2mm thick. There shall be co-polymer polypropylene shoe provided at the base to avoid scratches on the floor. The seat size shall be 480±10 mm(W) X 470±10 mm(D) and back size shall be 460±10 mm(H) from seat & overall height = 870±10 mm.
6	Cabinets	8	Supplying & placing storage unit with an overall size 900mm X 450mm X 2000mm. Storage shall be made up of Pre-laminated particle board of grade II of IS 12823 with approved laminate and finish as per approved shade. All profile i.e. side, back, top, shutter, skirting shall be 18mm thick and the edges shall be sealed with thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. The storage shall have 3 nos. of adjustable shelf and 1 fixed shelf. 2 normal shutter and 2 glass shutter shall be provided for closing and opening the shutter. The glass shutter shall be made 4mm clear glass insert within aluminium profile. The shutter shall be operated with concealed crank hinge with SS handle as well as MP lock mechanism. To protect the wall from kicks, abrasion and serve as a decorative moulding, skirting shall be provided at bottom. There shall be buffers provided at the base to avoid scratches on the floor. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The boards used should meet international standards of quality and safety, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of elasticity bending tested as per IS 2380.
7	L Shape Table with Attached Pedestrial and Drawers	4	Supplying & Placing Modular table in completely knock down conditions with an overall size 2100mm X 2100mm X 750mm that is to be assembled at site. The worktop shall have the size 2000mm X 1000mm x 76mm thick made up of Medium Density Fibre-board with approved veneer laminate and PU polish accordingly. The table top profile shall be in rectangle shape with round corners and full round post forming edges. The table top shall be supported on MDF board based gable end. The end wall of the table on the side shall be topped by gable end. It should be made up of 76mm thick medium density fibre-board and profile shall be in moulded construction with full round post forming edges and duly deco painted. The table shall be clad with 18mm thick modesty panel which provide structural support for the table. It should be 18mm thick medium density fibre-board in linear shape with appropriate PVC edge banding and veneer laminate. There shall be buffers provided at the base to avoid scratches on the floor. The table shall have side unit for storage purpose with an overall size 2100mm x 600mm X 600mm. It shall have 2 nos. of drawer, 1 nos. of filling space with door and 1 nos of open space . The drawer shall be operated with profile handle and easily close & open with the assistance of sliding channels to enable smooth operation and sliding rail track and concealed crank hinge. Drawer facai, sides and all other shall be made in 18mm thick and drawer base shall be 9mm thick. To protect the wall from kicks, abrasion and serve as a decorative moulding, skirting shall be provided at bottom. The complete structure shall be supplied with approved veneer laminate, PU polish and deco painted. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification.
8	Table Back Unit	4	Supplying & Placing back storage unit in completely knock down conditions with an overall size 2100mm X 450mm X 750 mm that is to be assembled at site. The top shall be made up of Medium Density Fibre-board with approved veneer laminate and PU polish accordingly. The panel shall be in rectangle shape and should be 25mm thick. Veneered portion of work surface shall be finish with PU polish. The complete unit shall be made up of medium density fibre-board duly veneer laminate and PU polish. It shall have 4 nos. of door shutter operated with the assistance of soft-close concealed crank hinge and 4 nos. of drawer operated on soft-close ball bearing sliding channel.. All the size shall have the tolerance of upper and lower deviation of ±10mm for board & ±0.2mm for metal. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification.

9	High Back Chair	9	Providing and Placing High Back Chair with overall size of 770 mm W x 770 mm D x 1280 – 1370 mm H x 499 – 598 mm Seat Height. The seat and back shall be made of 15mm thick hot pressed commercial plywood padded with high resilience polyurethane foam 50mm thick having density 40kg/m ³ and 25mm thick having density 32kg/m ³ in back. The same shall be upholstered with leatherite tapestry 0.8mm thick and 535 GSM. Seat Size is 520 W mm x 480 D mm. The back is cushioned made of PU foam, upholstered with leatherette. The back size is 530 W mm x 954 H mm. The armrest top is molded from polyurethane and mounted on to a drop lift fixed type tubular armrest support made of Ø25±0.03mm x 1.6±0.01mm thick M.S. ERW tube having chrome plated finish. The Synchro Knee Tilt mechanism is designed with following features : 360° revolving type. The mechanism housing is made up of HPDC aluminium black powder coated. Seat depth adjustment is integrated in the seat through a sliding mechanism. Seat depth adjustment range is of 60±0.5mm. The pneumatic height adjustment has an adjustment stroke of 100±0.3mm. The pedestal is high pressure die cast polished aluminium & fitted with 5 nos. of twin wheel castors. The pedestal is 650±0.5mm pitch centre dia. (750±1.0mm with castors). 5 nos. of twin wheel castors are injection moulded in plastic having 60±0.1mm wheel diameter and assembled to pedestal.
10	Mid Back Chair for Visitors	12	Supplying and placing ergonomically designed, comfortable & aesthetically appealing Medium back chair. The seat shall be made of metal insert MS CRCA chrome plated upholstered with high resilience polyurethane foam (30+19)mm thick having density 60kg/m ³ & 40kg/m ³ with black leatherite tapestry 0.8mm thick and 535 GSM and the back shall be supported by MS CRCA chrome finish upholstered with high resilience polyurethane foam 19mm thick having density 23kg/m ³ with black leatherite tapestry 0.8mm thick and 535 GSM with contoured lumbar support which helps to provide full back support and maintain the natural curvature of the spine. The seat and back shall be fixed with metal frame and the armrest shall be used PU arm completely joint with seat and back. The chair shall have swivel tilt 360 degree revolving mechanism with upright position locking and tilt tension adjustment. The Hydraulic seat height adjustment for healthy seating, user can adjust seat height upto 120mm with BIFMA standard class-3 gaslift to suit them using the lever under the seat. The gas-lift mechanism should be tested as per ANSI/BIFMA X5.1-2011 standards. The Pedestal shall be made up of injection moulded black nylon having pitch circle Dia 650 mm fitted with 5 nos. 50mm twin wheel castors which shall be made of injection moulded black nylon 30% glass filled having self lubricating property for friction free movemen with BIFMA standards. The Seat size shall be 495±10 mm(W)X470±10 mm(D) and back size shall be 460±10 mm(H) from seat & overall height = 870±10 mm.
11	Officers L shape table with drawers	2	Supplying & Placing Modular table in completely knock down conditions with an overall size 1800mm X 1730mm X 750mm that is to be assembled at site. The work top shall have the combination of 18mm PLPB and 25mm MDF board. The top shall have the size 1800mm X 830mm made up of 18mm thick Pre-laminated particle board of grade II of IS 12823 with approved laminate and finish as per approved shade. The base top shall be made up of 25mm thick Medium density fibre-board with deco painted. The top profile shall be in rectangle shape with front half round shape and particle board edges shall be sealed with 2mm thick thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius and MDF board with half round post form. The table top shall be supported on 75mm MS powder coated U-clamp. The end wall of the table on the side shall be topped by gable end. The gable end shall be made up of 36mm thick Pre-laminated particle board and profile shall be in linear shape with appropriate PVC edge banding. The table shall be clad with 18mm thick modesty panel which provide structural support for the table. It shall be 18mm thick pre-laminated particle board in linear shape with appropriate PVC edge banding connected with both end. There shall be buffers provided at the base to avoid scratches on the floor. The side top shall be provided with an overall size 900mm X 450mm X 750mm. It should have the combination of 18mm PLPB and 25mm MDF board. Side top shall be supported on 75mm Peg which mounted over side pedestal unit. The table shall have side unit for storage purpose with an overall size 850mm X 400mm X 645mm. The side unit shall be made up of Pre-laminated particle board of grade II of IS 12823 with base 9mm thick and other parts 18mm thick like shutter, back, fascia, side panel etc. It shall have 3 drawer having same size and 1 nos. of shutter. The drawer shall be operated with SS handle and easily close & open with the assistance of roller channel and ball bearing channel to enable smooth operation. The drawer shall have central locking mechanism in which all the drawer shall be synchronized locked with one single key. The shutter shall be operated by SS handle and concealed crank hinge. To protect the wall from kicks, abrasion and serve as a decorative moulding, skirting shall be provided at bottom. A pedestal shall be provided with an overall size 400mm X 450mm X 645mm. The pedestal shall be made up of Pre-laminated particle board of grade II of IS 12823. Pedestal side, back, top, fascia shall be 18mm thick and drawer base shall be 9mm thick. The pedestal shall have 3 nos. of drawer i.e. 2 box drawer and 1 filing drawer. The drawer shall be operated with SS handle and easily close & open with the assistance of sliding channel to enable smooth operation. The drawer shall have central locking mechanism in which all the drawer shall be locked with one single key. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The board used should meet International Standard of quality, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of rupture and modulus of elasticity bending tested as per IS 2380.
12	Officers Table with Drawers	9	Supplying & Placing Modular table in completely knock down conditions with an overall size 1500mm X 750mm X 750mm that is to be assembled at site. The construction of the main table shall be free standing structure constructed with the help of minifix dowels and pins. The worktop shall be made up of 25mm thick particle board with approved laminate and finish as per approved shade. The top profile shall be in rectangle shape with front and back full round post form and other edges shall be sealed with 2mm thick thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. A pullout keyboard tray shall be provided of 18mm thick Pre-laminated particle board having size 550mm X 280mm. The tray shall be operated on keyboard channel. The top shall be supported over particle board base gable end. The end wall of the table on the side shall be topped by gable end. It should be made up of 25mm thick particle board and profile shall be in linear shape with front and back full round post form and other edge with appropriate PVC edge banding. The table shall be clad with 18mm thick modesty panel which provide structural support for the table. It should be 18mm thick pre-laminated particle board with appropriate PVC edge banding connected with both end. There shall be buffers provided at the base to avoid scratches on the floor. A mobile pedestal shall be provided with an overall size 400mm X 450mm X 650mm. The pedestal shall be made up of Pre-laminated particle board of grade II of IS 12823. Pedestal side, back, top, fascia shall be 18mm thick and drawer base shall be 9mm thick. The pedestal shall have 3 nos. of drawer i.e. 2 box drawer and 1 filing drawer. The drawer shall be operated with SS handle and easily close & open with the assistance of roller channel and ball bearing channel to enable smooth operation. The drawer shall have central locking mechanism in which all the drawer shall be synchronized locked with one single key. The pedestal shall be mounted over 50mm injection moulded nylon castor. A movable type CPU unit shall be provided with an overall size 468mm X 284mm. The CPU unit shall be made up of 18mm thick Pre-laminated particle board. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The board used should meet International Standard of quality, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of rupture and modulus of elasticity bending tested as per IS 2380..
13	Side Table	11	Supplying & placing computer desk of size 800mm(W) X 500mm(D) X 750mm(H). It should have work top made up of 18mm thick Pre-laminated particle board of grade II of IS 12823 with approved laminate and finish as per approved shade. The top profile shall be in rectangle shape and the edges shall be sealed with 2mm thick thin strip of impermeable PVC that is cut to fit the board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. The top board shall be supported on gable end at one end and fixed CPU unit at another end. Keyboard tray shall be provided 18mm thick pre-laminated particle board with an overall size 740mm X 400mm. The tray shall be operated by sliding channel runs on nylon roller to smooth operation. Open spaces shall be provided at one. Complete understructure made in 18mm thick Pre-laminated particle board with appropriate edge banding. To protect the wall from kicks, abrasion and serve as a decorative moulding skirting shall be provided at bottom. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The board used should meet international standards of quality and safety, Indian standard IS12823 grade II should meet long time loadbending, screw-withdrawal strength, modulus of rupture and modulus of elasticity bending tested as per IS 2380.
14	Officers Chair	27	Supplying and placing ergonomically designed, comfortable & aesthetically appealing High back chair. The seat shall be made of metal insert MS CRCA chrome plated upholstered with high resilience polyurethane foam (30+19)mm thick having density 60kg/m ³ & 40kg/m ³ with black leatherite tapestry 0.8mm thick and 535 GSM and the back shall be supported by MS CRCA chrome finish upholstered with high resilience polyurethane foam 19mm thick having density 23kg/m ³ with black leatherite tapestry 0.8mm thick and 535 GSM with contoured lumbar support which helps to provide full back support and maintain the natural curvature of the spine. The seat and back shall be fixed with metal frame and the armrest shall be used PU arm completely joint with seat and back. The chair shall have swivel tilt 360 degree revolving mechanism with upright position locking and tilt tension adjustment. The pneumatic seat height adjustment for healthy seating, user can adjust seat height upto 120mm with BIFMA standard class-3 gaslift to suit them using the lever under the seat. The gas-lift mechanism should be tested as per ANSI/BIFMA X5.1-2011 standards. The Pedestal shall be made up of injection moulded black nylon having pitch circle Dia 700 mm fitted with 5 nos. 50mm twin wheel castors which shall be made of injection moulded black nylon 30% glass filled having self lubricating property for friction free movemen with BIFMA standards. The Seat size shall be 510±10 mm(W)X450±10 mm(D) and back size shall be 690±10 mm(H) from seat & overall height = 1110±10 mm.
15	Chair for Visitors	41	Providing and supplying visitor chair with ergonomic design for user comfort. The seat and back shall be made of metal insert pipe frame padded with high resilience polyurethane foam (30+19)mm thick having density (60+40) kg/m ³ in seat 19mm thick having density 23kg/m ³ in back. The same shall be upholstered with leatherite tapestry 0.8mm thick and 535 GSM. The backrest of the chair shall be made by keeping the natural curvature of the spine with lumbar support. The armrest shall be used polyurethane arm completely joint with seat and back. The frame structure shall be cantilever support type made up of MS/CRCA chrome plated round pipe of Dia. 25.4mm with 2mm thick. There shall be co-polymer polypropylene shoe provided at the base to avoid scratches on the floor. The seat size shall be 480±10 mm(W) X 470±10 mm(D) and back size shall be 460±10 mm(H) from seat & overall height = 870±10 mm.
16	Staff Chair	87	Providing and supplying medium back chair with ergonomic design, comfortable & aesthetically appealing. The seat shall be made of 15mm thick hot pressed plywood upholstered with high resilience moulded polyurethane foam 40mm thick having density 40kg/m ³ with leatherite tapestry 0.8mm thick and 535 GSM and the back shall be made of metal bright bar upholstered with breathable mesh and leatherite tapestry 0.8mm thick and 535GSM. The chair shall be supplied with polyurethane arm mounted on metal pipe loop frame. For seating durability the chair shall have swivel tilt 360 degree revolving mechanism with upright position locking and tilt tension adjustment. The hydraulic seat height adjustment for healthy seating, user can adjust seat height up to 100mm with BIFMA standard class-3 gas-lift to suit them using the lever under the seat. The gas-lift mechanism should be tested as per ANSI/BIFMA X5.1-2011 standards. The pedestal should have five legged MS/CRCA chrome plated having pitch circle Dia. 650 mm fitted with 5 nos. twin wheel castors. The castors of the chair should be injection moulded in black nylon 30% glass filled, confirming to ANSI/BIFMA standard X5.1-2011 tested to perform 98,000 cycles with 250lbs load. The seat size shall be 470±10 mm(W) X 475±10 mm(D) and back size shall be 550±10 mm(H) from seat & overall height = 960±10 mm.

17	Almirah Big	16	Providing, supplying and placing steel almirah in perfectly upright and straight position. The overall size of the Almirah shall be 915mm (W) X 485mm (D) X 1980mm (H) including legs. It should be supplied with 4 nos. of adjustable shelves i.e. 5 loading compartments. All components shall be made of 0.8mm thick high yield strength CRCA sheet of grade 'D' conforming to IS: 513. Stiffeners shall be provided in shelf & door. The steel hinged door shall be provided with locking mechanism which is assembled with bolt arrangement. The shelves shall have folded constructions which have intrinsic rigidity and high load carrying capacity. Uniformly distributed load capacity per each shelf shall be 40kg maximum. The complete steel structure shall be constructed by welding and provide finishing with epoxy polyester powder coated to be thickness 50-60µ.
18	Almirah Small	12	Providing, supplying and placing steel almirah in perfectly upright and straight position. The overall size of the almirah shall be 915mm (W) X 485mm (D) X 1200mm (H) including legs. The Almirah shall be supplied with 2 nos. of adjustable shelves i.e. 3 loading compartments. All components shall be made of 0.8mm thick high yield strength CRCA sheet of grade 'D' conforming to IS: 513. Stiffeners shall be provided in shelf. The steel hinged door shall be provided with mazak handle and one way locking mechanism which is assembled with bolt arrangement. The shelves shall have folded constructions which have intrinsic rigidity and high load carrying capacity. Uniformly distributed load capacity per each shelf shall be 40kg maximum. The complete steel structure shall be constructed by welding and provide finishing with epoxy polyester powder coated to the thickness 40-60µ.
19	Sofa 3 Seater with 2 Arms	16	Supplying and placing Three seater sofa that shall be constructed from natural hard wood and commercial plywood having inner frame. The thickness of the wood should allow for the heavy tension webbing. The sofa shall have spring attached and also be padded separately. The frame shall be padded with high resilience polyurethane foam having density 45Kg/m³ in seat and 32Kg/m³ in back. Cushion arm shall be supplied with backrest frame and padded with high resilience polyurethane foam having density 32Kg/m³. The complete structure shall be upholstered with leatherite tapestry 0.8±0.1 mm thick and 535 GSM. The legs shall be 40mm thick round & 150mm height wooden leg with 3mm thick MS gold plating sheet . Overall width = 2155±10 mm, overall depth = 840±10 mm & overall height = 760±10
20	Sofa 2 seater with 2 Arms	7	Supplying and placing Two seater sofa that shall be constructed from natural hard wood and commercial plywood having inner frame. The thickness of the wood should allow for the heavy tension webbing. The sofa shall have spring attached and also be padded separately. The frame shall be padded with high resilience polyurethane foam having density 45Kg/m³ in seat and 32Kg/m³ in back. Cushion arm shall be supplied with backrest frame and padded with high resilience polyurethane foam having density 32Kg/m³. The complete structure shall be upholstered with leatherite tapestry 0.8±0.1 mm thick and 535 GSM. The legs shall be 40mm thick round & 150mm height wooden leg with 3mm thick MS gold plating sheet . Overall width = 2155±10 mm, overall depth = 840±10 mm & overall height = 760±10
21	Sofa 1 Seater with 2 Arms	7	Supplying and placing single seater sofa that shall be constructed from natural hard wood and commercial plywood having inner frame. The thickness of the wood should allow for the heavy tension webbing. The sofa shall have spring attached and also be padded separately. The frame shall be padded with high resilience polyurethane foam having density 45Kg/m³ in seat and 32Kg/m³ in back. Cushion arm shall be supplied with backrest frame and padded with high resilience polyurethane foam having density 32Kg/m³. The complete structure shall be upholstered with leatherite tapestry 0.8±0.1 mm thick and 535 GSM. The legs shall be 40mm thick round & 150mm height wooden leg with 3mm thick MS gold plating sheet . Overall width = 890±10 mm, overall depth = 840±10 mm & overall height = 760±10
22	Coffee Table	10	Supplying & placing center table with an overall size 1400mm X 720mm X 450mm. The top shall be made up of 30mm thick Pre-laminated particle board of grade II of IS 12823. The profile shall be in rectangle shape and the edges shall be sealed with 2mm thick thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. The lower shelf shall be made up of 18mm thick Pre-laminated particle board. The under structure shall consist of SS 202 grade shiny chrome finish pipe frame having cross-section area 30mm X 15mm. There shall be shoe provided at the bottom to avoid scratches on the floor.
23	Book Shelf Big	10	Supplying & placing storage unit with an overall size 900mm X 450mm X 2000mm. Storage shall be made up of Pre-laminated particle board of grade II of IS 12823 with approved laminate and finish as per approved shade. All profile i.e. side, back, top, shutter, skirting shall be 18mm thick and the edges shall be sealed with thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. The storage shall have 3 nos. of adjustable shelf and 1 fixed shelf. 2 normal shutter and 2 glass shutter shall be provided for closing and opening the shutter. The glass shutter shall be made 4mm clear glass insert within aluminium profile. The shutter shall be operated with concealed crank hinge with SS handle as well as MP lock mechanism. To protect the wall from kicks, abrasion and serve as a decorative moulding, skirting shall be provided at bottom. There shall be buffers provided at the base to avoid scratches on the floor. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The boards used should meet international standards of quality and safety, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of elasticity bending tested as per IS 2380.
24	Oval Shape Table Big	1	Supplying & Placing Conference table in completely knock down conditions with an overall size 4880mm X 1800mm X 750mm that is to be assembled at site. The construction of the main table shall be with minifix dowels, pins and MS brackets. The top shall be made up of back to back 25mm thick pre-laminated particle board of grade II of IS 12823 with approved laminate and finish as per approved shade. The top profile shall be in racetrack oval shape and the edges shall be sealed with 2mm thick thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. The table top shall be supported on particle board base gable end. The end wall of the table on the side shall be topped by gable end. It should be made up of 25mm thick Pre-laminated particle board and the profile shall be in linear shape with appropriate PVC edge banding. The table shall be clad with 18mm thick modesty panel which provide structural support for the table. The modesty panel shall be 18mm thick pre-laminated particle board with appropriate PVC edge banding connected with both end. Wire carrier shall be provided below the table top for power connection having size 60mm X 125mm made of 0.8mm thick high yield strength of CRCA sheet of grade 'D' conforming to IS:513 with duly powder coated. There shall be buffers provided at the base to avoid scratches on the floor. The table connections have to be made in such a way that no gap should be seen in between. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The board used should meet International Standard of quality, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of rupture and modulus of elasticity bending tested as per IS 2380.
25	Movable Compactor	6	Providing and placing mechanically assisted drive mechanism Mobile compactor. The structure shall be made out of 0.8 thick high yield strength CRCA sheet of grade 'D' conforming to IS:513. Each unit have 5 loading levels formed by 4 nos. of adjustable shelves. Body units are bolted to undercarriage. Compactor height from ground should be 2190 mm (2025 body + 120 undercarriage + 22 mm rail). The body including shelves shall be given antirust surface treatment & powder coated with epoxy polyester powder. It involves an 7 step treatment, Final finish consists of epoxy polyester powder coating of approved color & shade with a Dry Film Thickness of minimum 40 microns. It shall have max. load bearing capacity of 60 Kg uniformly distributed per shelf. Shelves shall be mounted on support brackets & shelf level can be adjusted. The Undercarriage shall be welded frame made of HR sheet minimum 2.5 mm thick suitably fabricated to take the loads based on configuration. A Centralized locking arrangement shall be provided through Locking Stiffener mounted onto back of Single Last unit so that it gets locked on channels when all the units are brought together. This arrangement occupies a space of 100 mm. Each Drive type units have Locking Knob near the Drive wheel for manual locking of individual units when a person is using those units. End stoppers are provided at the end of channels to prevent derailment. The nuts & bolts are galvanized / Zn Plated. Movement of units shall be achieved mechanically through a Drive wheel and 'Sprocket-Chain-Tensioner' arrangement mounted rigidly onto body side. 1 Bay Single static Fixed 915 X 455 X 2190. 1 Bay Double movable 915 X 910 X 2190. 1 Bay Single Last Movable (Lockable) 915 X 455 X 2190.
26	Racks for UPS	6	Providing, placing and installing a slotted angle rack with an overall size 900mm (W) X 450mm (D) X 1800mm (H). The panel shall have 5 nos. of shelves made up of 0.8mm thick high yield strength CRCA sheet of grade 'D' conforming to IS: 513. CRCA slotted angle shall be supplied with 2mm thick having size 40mm X 40mm. All steel components shall be 40-60µ thick (DFT) powder coated after 7 tank pre-treatment process flow. Corner plate (gussets) and fasteners shall be provided for complete assembly.
27	Workstation Table	14	Providing and placing workstation table in completely knock down conditions with an overall size 1320mm X 660mm X 1200mm that is to be assembled at site. The work top shall have the size 1200mm X 600mm made up of 25mm thick Pre-laminated particle board of grade II of IS 12823 with approved laminate and finish as per approved shade. The profile of the top shall be in rectangle shape and the edges shall be sealed with 2mm thick thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. A pullout keyboard tray shall be provided of 18mm thick Pre-laminated particle board having size 525mm X 350mm. The tray shall be operated on keyboard channel. The workstation shall have panel based partition of 60 mm thick with overall height 1200mm. The partition shall be linear in profile and provided in the front side of user as well as on the both sides of the user. The top trim, top bar, mid bar, vertical bar, raceway, skirting shall be made up of aluminium extrusions (pre-treated) and duly powder coated with 40µ-60µ thick. The trims shall have the size 60mm X 19mm with 1.5mm thick covered with Die cast end caps on joints 2 ways, 3 ways & 4 ways (L-cover for corner, T-cover for middle section wherever required). The aluminium raceway shall be situated below the worktop with an overall size 116mm(H) X 60mm(D) with 1.4 mm cover thickness and 2mm back thickness as per requirement of inlaying the electrical management and carrying the wire horizontally. The exposed vertical and horizontal faces of the frames shall be snap fitted with trims. There shall be soft-board (with fabric) and marker board provided at front of the user. Laminated top tile and bottom tile shall be situated at both sides of the user and below the work top respectively. The Partition shall have concealed wire management capabilities and should be engaged for responsive and safe operations of power, telecommunications and data (LAN) and has separate components for electrical, data and telephone cables having adequate capability of both the vertical and horizontal wire movements. Slots/cut-outs should be given on raceways to fix all electrical and data points. Zinc coated small top support brackets shall be fixed on the partition for table top support. To protect the wall from kicks, abrasion and serve as a decorative moulding, skirting shall be situated at bottom. Adjustable leveller shoe shall be provided at bottom of the partition to avoid scratches on the floor. Fixed type pedestal shall be provided with an overall size 400mm X 450mm X 725mm. The pedestal shall be made up of Pre-laminated particle board of grade II of IS 12823. Pedestal side, back, top, fascia shall be 18mm thick and drawer base shall be 9mm thick. The pedestal shall have 3 nos. of drawer i.e. 2 box drawer and 1 filing drawer. The drawer shall be operated with SS handle and easily close & open with the assistance of roller channel and ball bearing channel to enable smooth operation. The drawer shall have central locking mechanism in which all the drawer shall be synchronized lock with one single key. To protect the wall from kicks, abrasion and serve as a decorative moulding, skirting shall be provided at bottom. A nylon castor based CPU unit shall be provided with an overall size 468mm X 284mm with 18mm thick Pre-laminated particle board. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The board used should meet International Standard of quality, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of rupture and modulus of elasticity bending tested as per IS 2380.

28	Table	19	Supplying & Placing Modular table in completely knock down conditions with an overall size 1500mm X 750mm X 750mm that is to be assembled at site. The construction of the main table shall be free standing structure constructed with the help of minifix dowels and pins. The worktop shall be made up of 25mm thick particle board with approved laminate and finish as per approved shade. The top profile shall be in rectangle shape with front and back full round post form and other edges shall be sealed with 2mm thick thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. A pullout keyboard tray shall be provided of 18mm thick Pre-laminated particle board having size 550mm X 280mm. The tray shall be operated on keyboard channel. The top shall be supported over particle board base gable end. The end wall of the table on the side shall be topped by gable end. It should be made up of 25mm thick particle board and profile shall be in linear shape with front and back full round post form and other edge with appropriate PVC edge banding. The table shall be clad with 18mm thick modesty panel which provide structural support for the table. It should be 18mm thick pre-laminated particle board with appropriate PVC edge banding connected with both end. There shall be buffers provided at the base to avoid scratches on the floor. A mobile pedestal shall be provided with an overall size 400mm X 450mm X 650mm. The pedestal shall be made up of Pre-laminated particle board of grade II of IS 12823. Pedestal side, back, top, fascia shall be 18mm thick and drawer base shall be 9mm thick. The pedestal shall have 3 nos. of drawer i.e. 2 box drawer and 1 filing drawer. The drawer shall be operated with SS handle and easily close & open with the assistance of roller channel and ball bearing channel to enable smooth operation. The drawer shall have central locking mechanism in which all the drawer shall be synchronized locked with one single key. The pedestal shall be mounted over 50mm injection moulded nylon castor. A movable type CPU unit shall be provided with an overall size 468mm X 284mm. The CPU unit shall be made up of 18mm thick Pre-laminated particle board. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The board used should meet International Standard of quality, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of rupture and modulus of elasticity bending tested as per IS 2380..
29	Side table with drawer	1	Supplying & placing storage unit with an overall size 900mm X 450mm X 750mm. The storage shall be made up of Pre-laminated particle board of grade II of IS 12823 with approved laminate and finish as per approved shade. The top shall be 25mm thick and all other profile i.e. side, back, shutter, shelf, skirting shall be 18mm thick. The edges shall be sealed with thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. The storage shall have 1 nos. of adjustable shelf and 2 nos. of door shutters shall be provided for opening and closing the storage. The shutter shall be operated with concealed crank hinge with Al die cast handle as well as MP lock mechanism. To protect the wall from kicks, abrasion and serve as a decorative moulding, skirting shall be provided at bottom. There shall be buffers provided at the bottom to avoid scratches on the floor. The manufacturer shall have quality and safety assurance like ISO-9001:2015, ISO-14001:2015 and ISO-18001:2007, BIFMA membership and AIOTA certification. The boards used should meet international standards of quality and safety, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of elasticity bending tested as per IS 2380.
30	Sofa 3 Seater with 2 Arms MS	3	Supplying & Placing three seater bench. The seat and back shall be made up of high quality cold rolled MS perforated sheet of 1.2mm thick, pressed and welded to form the shape. The seat and back electrostatically coated with epoxy powder and then cured under heat to allow it to form a skin. The seat and back shall be upholstered with Latherite Tapestry. The armrest shall be made up of mild steel powder coated tube with 1.2mm thick. The base structure shall be supported by MS powder coated with 40-50µ (DFT). There shall be PPCP shoe provided at the base to avoid scratches on the floor. The seat size shall be 450±10 mm(D) X 430±10 mm(H) from ground. Overall height shall be = 755±10 mm, overall depth = 710±10 mm & overall width = 1750±10 mm.
31	Sofa 2-seater with 2 Arms MS	3	Supplying & Placing two seater bench. The seat and back shall be made up of high quality cold rolled MS perforated sheet of 1.2mm thick, pressed and welded to form the shape. The seat and back electrostatically coated with epoxy powder and then cured under heat to allow it to form a skin. The seat and back shall be upholstered with Latherite Tapestry. The armrest shall be made up of mild steel powder coated tube with 1.2mm thick. The base structure shall be supported by MS powder coated with 40-50µ (DFT). There shall be PPCP shoe provided at the base to avoid scratches on the floor. The seat size shall be 450±10 mm(D) X 430±10 mm(H) from ground. Overall height shall be = 755±10 mm, overall depth = 710±10 mm & overall width = 1200±10 mm.
32	Front Table	1	Supplying & Placing Reception table in completely knock down conditions with an overall size 2400mm X 820mm X 1000mm that is to be assembled at site. The top shall have the size 2300mm X 695mm made up of 49mm thick Pre-laminated particle board of grade II of IS 12823 with approved laminate and finish as per approved shade. The upper top shall have the size 1400mm X 300mm with 49mm thick. The top profile shall be in rectangle shape with 2mm thick thin strip of impermeable PVC that is cut to fit the size of board panel and duly pasted with the assistance of edge banding machine at 200 degree Celsius. The side edges shall be covered with die casted aluminium profile. The table top and upper top shall be supported on particle board base strip. The table shall have a front panel having size 1390mm X 750mm with 49mm thick Pre-laminated particle board. A wire manager cap shall be provided on the top of the table for power connection. The end wall of the table on the side shall be topped by gable end. It shall be made up of 49mm thick Pre-laminated particle board and profile shall be in linear shape with one clipped corner and covered by Aluminium profile. There shall be buffers provided to avoid the scratches on the floor. The table shall be clad with 49mm thick modesty panel which provide structural support for the table. It should be 49mm thick pre-laminated particle board in linear shape with appropriate PVC edge banding and covered by aluminum profile connected with both end. The manufacturer shall have basic quality and safety certifications like ISO-9001:2015, ISO-14001: 2015, ISO-18001:2007, BIFMA Membership & AIOTA certification. The board used should meet International Standard of quality, Indian standard IS 12823 grade II should meet long time load bending, screw-withdrawal strength, modulus of rupture and modulus of elasticity bending tested as per IS 2380.