

TECHNICAL SPECIFICATIONS

1. Indoor Data Wall (Size 12.7 ft x 10.6ft)

Number	Item	Item Index	Technology Requirements
1	Pixel	Pitch	2.5mm
		Pixel Configuration	1R1G1B
		Pixel Density	1,60,000 dot/m ²
		Module Resolution	128dot*64dot
		Module Size	320*160mm
		Module Pixel	128*64=8192dot
		View Angle	Horizontal 150°, Vertical 120°
		Best View Distance	2.5m–25m
		Work Temperature	-10°C – 75°C
2	Module	Environment Humidity	10% – 90% RH
		Storage Temperature	-30°C – +90°C
		Protection Grade	IP43
		System Guard	Moistureproof, Dustproof, Heat resistant, Corrosion prevention, Shock resistant
3	Power Supply	Supply Voltage	AC110V–220V ±15%, 40–65Hz
		Average Power	350W/m ²
		Max Power	600W/m ²
4.	Control System	Control Host	Lenovo or above
		Control system	WIN 98/2000/XP
		Control Method	Computer control
		GPU	DVI GPU
		Driving Method	Constant Current
		Refresh Rate	≥3840 Hz
		Frame Frequency	≥60Hz
		Grayscale	Single Color 16384 level
		Color	10.7 Hundred Million
		Brightness	≥800CD/m ²
		Luminousness	0
		Brightness Adjustment	Manual & Automatic
		Video Signal	RF, S-Video, RGB, RGBHV, YUV
		Control System	PCTV + DVI GPU + Master card + Network Cable
		Mean Time Between Failure	10000 hours
		Lifetime	1,00,000 hours
		Flatness	Between adjacent pixels ≤0.5mm
		Brightness Uniformity	Pixel light intensity, MODULE brightness is balance ≤0.1
		Malfunction dot rate	<0.0001
		Wire - Air Power Supply Plug	INTERNAL
		Wire - Navigation Signal Plug	Network CAT6 Cable
		software - synchronous control	HD PLAYER

2. Interactive Panel 98”

Specification	Details
Screen Size	98 Inch
Resolution	4K UHD (3840 × 2160)
Touch Technology	Infrared Multi-Touch
Touch Points	Minimum 20 Touch Points
Brightness	Minimum 450 Nits
RAM	Minimum 4 GB
Storage	Minimum 32 GB
Operating System	Android 11 or Higher
Audio	Inbuilt Speakers
Connectivity	HDMI, USB, LAN, Wi-Fi, Bluetooth
Accessories	Stylus, Remote, Wall Mount Kit
Warranty	Minimum 3 Years OEM Warranty
Installation	Supply, Installation, Testing & Commissioning Included