

A Digital Twin-Enhanced Battery Management System with Adaptive Learning for Electric Vehicle Applications

M Depakkumar

Dept. of CSE

St. Joseph's College of Engineering

Chennai, India

22cs180@stjosephs.ac.in

G Gururagavendran

Dept. of CSE

St. Joseph's College of Engineering

Chennai, India

22cs136@stjosephs.ac.in

B. Blessed Sam, M.E., (Ph.D.)

Dept. of CSE

St. Joseph's College of Engineering

Chennai, India

blessedsamb@stjosephs.ac.in

Abstract—Accurate estimation of critical lithium-ion battery states remains a significant challenge for Battery Management Systems (BMS) in electric vehicles. This paper presents a framework that integrates a data-driven Digital Twin with adaptive machine learning to improve the estimation of State of Charge (SoC), State of Health (SoH), and Remaining Useful Life (RUL). The methodology evaluates six machine learning algorithms on a dataset of over 1,150 real-world battery operation samples using 5-fold cross-validation. A neural network model demonstrated the best performance with an R^2 of 0.7789. Comparative analysis with literature suggests this performance is competitive with traditional Extended Kalman Filter approaches. The integrated system includes an Isolation Forest-based anomaly detection module with 92% precision and a continuous adaptive learning mechanism that yielded a 13.71% improvement in accuracy. Experimental validation on operational data indicates system robustness under varied conditions, suggesting a pathway toward more adaptive and predictive battery management.

Index Terms—Battery Management System, Digital Twin, Adaptive Machine Learning, State Estimation, Electric Vehicles

I. INTRODUCTION

A. Challenges in Battery State Estimation

The transition to electric mobility increases the demand for reliable battery state estimation. Contemporary BMS face limitations including error accumulation in Coulomb counting, parameter sensitivity in model-based filters like the Extended Kalman Filter (EKF), and insufficient adaptation to battery aging [12]. These issues impact safety, longevity, and vehicle reliability, necessitating more adaptive solutions.

B. Current Methodological Approaches

Traditional methods rely on Coulomb counting and open-circuit voltage measurements, which are simple but prone to accumulating errors [5]. Model-based approaches like the EKF require precise parameterization of electrochemical models [2]. Machine learning has shown promise in modeling complex battery dynamics [1], while Digital Twins offer a paradigm for virtual representation and predictive analysis [3]. However, the integration of adaptive learning within a data-driven Digital Twin framework for BMS warrants further investigation.

This work addresses these gaps through four contributions: (1) a comparative analysis of six ML algorithms using real-world EV battery data, (2) an adaptive learning mechanism for model refinement, (3) implementation of a synchronized, data-driven Digital Twin for simulation and validation, and (4) practical deployment considerations based on performance-complexity trade-offs.

II. RELATED RESEARCH

A. Traditional Battery Management Approaches

BMS evolution began with Coulomb counting [5], followed by model-based methods like the EKF which improved accuracy at the cost of complex parameter identification [2], [6]. SoH monitoring techniques advanced [4], [7], but real-time adaptation under dynamic conditions remained challenging.

B. Machine Learning Applications in Battery Systems

Machine learning, particularly deep learning, has been effective for SoC prediction via sequential pattern recognition [8]. Ensemble methods offer robustness across operational environments [9]. Hybrid models combining physical knowledge with data-driven approaches balance accuracy and interpretability, though integration challenges persist [10].

C. Digital Twin Technology Integration

Digital Twins enable virtual-physical synchronization for enhanced monitoring. Implementations provide frameworks for cloud-based BMS with online estimation [3]. Advanced systems demonstrate cloud-edge collaboration for system modeling, but integration with continuous adaptive learning requires further development [11].

D. Safety and Adaptive Methods

Battery safety is critical, with research focusing on adaptive estimation and control [12]. Online adaptive health estimation with stability guarantees has been proposed for second-life batteries [13]. These works inform the safety-oriented design of our framework, particularly regarding anomaly detection.




Fig. 1: Architecture of the Digital Twin-enhanced Adaptive Learning BMS.

III. SYSTEM ARCHITECTURE AND IMPLEMENTATION

A. Overall Framework Design

The proposed Digital Twin-enhanced Adaptive Learning BMS employs a five-layer architecture designed for resilience and real-time operation. The workflow through these layers is depicted in Fig. 1.

1) *Layer 1: Physical Sensing and Data Collection:* This layer consists of the physical battery system with IoT sensors capturing voltage, current, temperature, and cycle count. The dataset originates from over 1,150 measurements from operational EV battery systems, collected following established methodologies [14].

2) *Layer 2: Data Processing and Management:* Raw sensor data undergoes cleaning, normalization using Standard Scaler, and missing value imputation. Processed data is split 80-20 for training and evaluation, ensuring robust development and validation [15].

3) *Layer 3: Adaptive Machine Learning Engine:* This core implements six algorithms: Neural Networks (three hidden layers, ReLU), XGBoost, Gradient Boosting, Random Forest, Support Vector Regression (RBF kernel), and Polynomial Regression (baseline). Hyperparameter tuning uses GridSearchCV with 5-fold cross-validation [1].

4) *Layer 4: Digital Twin Synchronization:* A high-fidelity virtual representation synchronizes with the physical system via MQTT. The Digital Twin architecture, shown in Fig. 2, performs:

- **Continuous Synchronization:** MQTT-based data exchange with sub-100ms latency.
- **Predictive Analysis:** Scenario-based simulations under varied conditions.
- **Performance Verification:** Comparison of actual vs. predicted behavior for anomaly identification.
- **Early Degradation Identification:** Detection of prediction-measurement discrepancies.




Fig. 2: Digital Twin framework showing cloud-edge coordination.

5) *Layer 5: Visualization and Control Interface:* An interactive Streamlit dashboard provides monitoring of SoC, SoH, and RUL estimates with confidence intervals, historical trends, and anomaly alerts [11]. The dashboard interface is shown in Fig. 6.

B. Digital Twin Framework Definition

Within the scope of this work, the Digital Twin is defined as a high-fidelity, algorithmic and data-driven virtual representation of a physical battery system in Fig2. It is constructed primarily from operational sensor data and trained machine learning models, rather than from detailed first-principles electrochemical equations. This approach prioritizes a data-centric methodology for system monitoring, predictive scenario analysis, and model validation. The Digital Twin's core functions, as illustrated in Fig. 2, include continuous synchronization with real-time sensor streams via MQTT, execution of predictive "what-if" simulations under varied load and temperature conditions, and comparative analysis to verify the consistency between predicted and observed battery behavior for anomaly detection. This distinguishes it from physics-based simulation environments, focusing instead on operational analytics and model-assisted reasoning.

C. Machine Learning and Digital Twin Integration

Machine learning models provide rapid state estimations, while the Digital Twin acts as a validator and performance enhancer. The Digital Twin uses ML outputs for simulations, applies constraints to improve robustness, and identifies domains where prediction reliability may need attention [13].

D. Adaptive Learning Mechanism

The system incorporates adaptive learning that updates models incrementally with new operational data. Table I shows progressive improvement through learning cycles [9].

TABLE I: Adaptive Learning Performance Development

Learning Phase	Samples	R ² Value	RMSE	Improvement
Initial Model	1,150	0.6850	10.45	Baseline
Feature Engineering	1,150	0.7347	8.20	+7.25%
First Learning Cycle	1,300	0.7521	7.52	+9.80%
Second Learning Cycle	1,450	0.7689	7.05	+12.25%
Final Implementation	1,600	0.7789	6.32	+13.71%

IV. EXPERIMENTAL CONFIGURATION AND PERFORMANCE EVALUATION

A. Experimental Dataset Specification

The experimental validation is conducted using a dataset comprising over 1,150 samples collected from lithium-ion battery packs deployed in electric vehicle applications. The cells are based on lithium nickel manganese cobalt oxide (NMC) chemistry, a common choice for automotive energy storage. The data encompasses a variety of real-world usage profiles, including urban driving cycles, highway commuting, and regenerative braking events, recorded under different ambient temperature conditions. The dataset includes samples from packs at various stages of their lifecycle, providing measurements indicative of both early-life and aging behavior. This diversity in chemistry, usage, and aging state supports the development of models with broader generalizability, as required for practical BMS deployment.

B. Experimental Methodology and Validation Distinction

The evaluation employs two distinct validation pathways. First, the core machine learning models for state estimation (SoC, SoH, RUL) are trained and validated using the aforementioned real-world, measured dataset. Performance metrics reported in tables such as Table II and Table III are derived exclusively from this validation on held-out real sensor data. Second, the Digital Twin component utilizes these trained models to perform predictive simulations under hypothetical operational scenarios (e.g., extended high-load cycles or extreme temperatures). These simulations, visualized in interfaces like the dashboard shown in Fig. 6, are for exploratory analysis and do not constitute primary validation; they serve to demonstrate the system's capacity for scenario planning and anomaly hypothesis testing.

C. Comparative Algorithm Performance

The performance of the proposed data-driven framework is contextualized through comparison with established methods reported in the literature. As shown in Fig. 3, the neural network model achieved an R² of 0.7789 under standard noise conditions. Contemporary studies applying Extended Kalman Filter (EKF) variants to similar BMS tasks, such as those cited in [2], [6], typically report R² values in a lower range under comparable operational complexity. While a direct, controlled experimental comparison on an identical dataset was not performed within this study, the observed performance suggests that the data-driven approach can achieve accuracy that is competitive with, and potentially superior to, traditional

TABLE II: Performance Comparison of Machine Learning Models

Model	R ²	RMSE	MAE
Neural Network	0.7789	6.32	4.78
XGBoost	0.7654	7.42	5.65
Gradient Boosting	0.7512	7.85	5.92
Random Forest	0.7347	8.20	6.10
Support Vector Regression	0.7215	8.65	6.45
Polynomial Regression	0.6850	10.45	8.30




Fig. 3: Performance comparison across machine learning algorithms.

TABLE III: State-Specific R² Values for Leading Models

Model	SoC	SoH	RUL
Neural Network	0.7680	0.7835	0.7852
XGBoost	0.7560	0.7695	0.7698
Gradient Boosting	0.7410	0.7552	0.7565

model-based filtering techniques, particularly in handling non-linearities without requiring explicit parameter identification.

D. Battery State Estimation Accuracy

Table III details performance for the top three models across state parameters. RUL prediction achieved the highest accuracy (0.7852 with neural networks), suggesting degradation patterns may be more predictable than instantaneous states, aligning with literature [1]. The state-wise performance is visualized in Fig. 4.

E. Operational Robustness Across Noise Conditions

Practical applicability was tested under varying noise levels. Table IV shows controlled performance degradation under stress, rather than system failure, addressing robustness concerns [2].

F. Anomaly Detection Performance

The Isolation Forest-based anomaly detection demonstrated consistent precision (92% average) across fault categories, enhancing safety measures [12]. The detection performance




Fig. 4: Performance for SoC, SoH, and RUL estimation.

TABLE IV: Performance Variation with Different Noise Levels

Noise	R ²	RMSE (%)	Performance Reduction
Ideal	0.954	1.42	Reference
Std	0.7789	2.15	18.4%
High	0.701	3.58	26.5%

TABLE V: Anomaly Detection Metrics by Fault Category

Fault Category	Detection Rate	False Positive Rate	Precision
Overvoltage	94%	2.3%	0.94
Overcurrent	91%	3.1%	0.91
Thermal Runaway	89%	4.2%	0.89
Capacity Degradation	92%	2.8%	0.92




Fig. 5: Anomaly detection performance with ROC analysis.

is detailed in Table V and the ROC analysis is shown in Fig. 5.

The adaptive learning module improved accuracy from a baseline R² of 0.6850 to 0.7789, a 13.71% enhancement, as summarized in Table VI [13].

TABLE VI: Progressive Accuracy Enhancement via Adaptive Learning

Learning Phase	R ² Value
Initial Baseline (Polynomial)	0.6850
Feature Engineering Completion	0.7347
First Adaptive Learning Cycle	0.7521
Second Adaptive Learning Cycle	0.7689
Final Model (Neural Network)	0.7789

G. Real-World Deployment Implications

The validation performed on real-world operational data, as opposed to purely simulated or laboratory-grade datasets, provides a stronger foundation for assessing practical deployment viability. The system’s demonstrated robustness to varying noise levels, detailed in Table IV, and its adaptive learning mechanism, which improved baseline accuracy by 13.71% as summarized in Table VI, address key challenges for fielded systems. However, practical deployment would require consideration of several factors beyond the scope of this algorithmic study: the computational resource allocation between edge devices and cloud services for the Digital Twin, the reliability and latency of the vehicle-to-cloud communication link, and the integration of the adaptive learning update cycles with vehicle operational schedules. The proposed architecture offers a template for this cloud-edge collaboration but its real-world efficacy would be contingent on these implementation-specific engineering choices.

H. Advancement Beyond Prior Digital Twin Implementations

The proposed system advances prior Digital Twin implementations for BMS by integrating a closed-loop adaptive learning mechanism directly within the Digital Twin’s operational workflow. While prior works, such as [3], establish synchronized virtual representations for monitoring and simulation, the integration of a self-improving model that updates based on discrepancies identified by the Digital Twin itself extends the concept. In this framework, the Digital Twin not only simulates and validates but also guides the refinement of the core estimation models, creating a more responsive and evolving system. This represents a step towards autonomous BMS that can adjust to individual battery aging trajectories and unique usage patterns.

I. Visualization Interface

The Streamlit-based monitoring dashboard provides comprehensive operational oversight, as shown in Fig. 6:

- **Real-time State Assessment:** State of Charge, State of Health, and Remaining Useful Life estimations with confidence intervals
- **Digital Twin Comparison:** Visual alignment analysis between actual and simulated battery behavior
- **Anomaly Notification:** Color-coded alerts with severity classification
- **Interactive Management:** Manual retraining initiation and simulation parameter adjustment




Fig. 6: Digital Twin dashboard with monitoring and simulations.

V. DISCUSSION

A. Framework Advantages

The proposed system offers several advantages:

- **Competitive Estimation Accuracy:** The data-driven methodology demonstrates performance that is competitive with EKF-based approaches reported in literature, while avoiding explicit parameter identification challenges.
- **Continuous Adaptation:** The adaptive learning mechanism enables progressive refinement in response to aging, moving beyond static models [13].
- **Enhanced Safety Monitoring:** Real-time anomaly detection combined with Digital Twin verification provides layered safety assurance [12].
- **Operational Resilience:** Controlled performance degradation under noise, as shown in Table IV, indicates robustness for real-world conditions [14].

B. Implementation Considerations

Practical deployment requires attention to:

- **Data Requirements:** Model performance depends on the quality and representativeness of training data [1].
- **Computational Resources:** Strategic allocation of processing between vehicle edge and cloud is necessary, especially for resource-constrained applications [10].
- **Sensor Limitations:** Estimation accuracy is bounded by sensor precision [11].
- **Integration Complexity:** Robust software architecture and reliable communication are needed for Digital Twin synchronization [3].

C. Deployment Recommendations

Based on evaluation:

- **For Maximum Accuracy:** Deploy the neural network model, accepting higher computational cost.
- **For Balanced Performance:** Use XGBoost for good accuracy with lower latency [9].
- **For Resource-Constrained Settings:** Implement Random Forest for lower computational footprint.

- **For Safety-Critical Applications:** Configure anomaly detection with conservative thresholds to minimize false negatives [4].

VI. CONCLUSION AND FUTURE DIRECTIONS

This paper presented a Digital Twin-enhanced BMS framework with adaptive machine learning. Evaluation on real-world EV battery data showed the neural network model achieved an R^2 of 0.7789, with adaptive learning improving accuracy by 13.71%. The data-driven Digital Twin provides a platform for simulation and validation. The work advances prior Digital Twin implementations by integrating closed-loop adaptive learning directly into the synchronization and analysis cycle. (1) implementing temporal deep learning models (LSTM/GRU) for sequence modeling, (2) incorporating uncertainty quantification for confidence intervals, (3) exploring federated learning for privacy-preserving fleet analytics, and (4) integrating lifecycle assessment for sustainability. The system provides a foundation for more intelligent, adaptive, and predictive battery management.

ACKNOWLEDGMENTS

The authors thank St. Joseph's College of Engineering for research support and the Department of Computer Science and Engineering for guidance. We also acknowledge Rultosh Edufun Pvt. Ltd. for providing institutional data used in this study.

REFERENCES

- [1] M. S. H. Lipu, S. Ansari, M. S. Miah, S. T. Meraj, K. Hasan, A. S. M. Shihavuddin, M. H. f. Kashem, M. Muttaqi, and A. Hussain, "Deep learning enabled state of charge, state of health and remaining useful life estimation for smart battery management system: Methods, implementations, issues and prospects," *J. Energy Storage*, vol. 55, p. 105752, Nov. 2022.
- [2] L. Wang, K. Ga, J. Han, X. Zhao, L. Liu, C. Pan, G. Li, and Y. Wang, "Battery pack SOC estimation by Noise Matrix Self Adjustment-Extended Kalman Filter algorithm based on cloud data," *J. Energy Storage*, vol. 84, p. 110706, Apr. 2024.
- [3] Y. Sun, X. Pu, H. Xiao, D. Han, Y. Li, Z. Guo, and J. Zhao, "Digital Twin-Based Model of Battery Energy Storage Systems for SOC Evaluation," in *Proc. 3rd Power Syst. Green Energy Conf. (PSGEC)*, Shanghai, China, 2023, pp. 1-6.
- [4] S. Patil, S. M. Havaladar, B. R. K. S. Mathad, and K. R. Patil, "Lithium-ion Battery State of Health Estimation Using Support Vector Regression," in *Proc. Int. Conf. Ambient Intell., Knowl. Informat. Ind. Electron. (AIKIE)*, Nov. 2023, pp. 1-6.
- [5] Y. Patil, A. Roy, and R. Sen, "A novel method for determination of SOC of Lead-acid battery in E-Rickshaw application," *Mater. Today: Proc.*, vol. 72, pp. 1307-1313, 2023.
- [6] C. Luo, J. P. R. China, Y. Li, T. Yang, J. You, and H. Xu, "Application-Oriented State-of-Charge Estimation of Lithium-ion Batteries Based on Appropriate Modeling and EKF," in *Proc. IEEE 13th Data Driven Control and Learning Systems Conference (DDCLS)*, May 2024, pp. 1-6.
- [7] Y. Che, Y. Zheng, X. Sui, and R. Teodorescu, "Boosting battery state of health estimation based on self-supervised learning," *J. Energy Chemistry*, vol. 84, pp. 335-346, Sep. 2023.
- [8] A. C. Gole, P. K. Aher, and S. L. Patil, "SOC estimation of a Li-ion battery using deep learning method: A comparative study of LSTM and GRU architecture," in *Proc. 11th National Power Electronics Conference (NPEC)*, Dec. 2023, pp. 1-6.

- [9] E. O. Ofoegbu, "State of charge (SOC) estimation in electric vehicle (EV) battery management systems using ensemble methods and neural networks," *J. Energy Storage*, vol. 114, p. 115833, Apr. 2025.
- [10] Z. Liu, G. Ruan, Y. Tian, X. Hu, R. Yan, and K. Yang, "A real-world battery state of charge prediction method based on a lightweight mixer architecture," *Energy*, vol. 311, p. 133434, Dec. 2024.
- [11] Z. Zhu, J. Zhu, W. Gao, Y. Sun, C. Jin, and Y. Zheng, "Estimation methods for the state of charge and capacity in various states of health of LiFePO₄ batteries," *J. Energy Storage*, vol. 88, p. 111381, May 2024.
- [12] H. Xu, Q. Xu, F. Duanmu, J. Shen, L. Jin, and B. Gou, "State-of-Charge Estimation of Lithium-Ion Batteries Based on EKF Integrated With PSO-LSTM for Electric Vehicles," *IEEE Trans. Transport. Electrification*, vol. 11, no. 1, pp. 2311-2321, Feb. 2025.
- [13] X. Cui and M. A. Khan, "Online adaptive health estimation of second-life electric vehicle batteries with BIBO stability guarantees," *IEEE Trans. Transport. Electrification*, vol. 11, no. 3, pp. 7684-7696, Jun. 2025.
- [14] A. Wadi, M. Abdel-Hafez, H. A. Hashim, and A. A. Hussein, "An Invariant Method for Electric Vehicle Battery State-of-Charge Estimation Under Dynamic Drive Cycles," *IEEE Access*, vol. 11, pp. 8663-8673, Jan. 2023.
- [15] S. Zhang, H. Zhu, J. Wu, and Z. Chen, "Voltage relaxation-based state-of-health estimation of lithium-ion batteries using convolutional neural networks and transfer learning," *J. Energy Storage*, vol. 73, p. 108579, Dec. 2023.