

Epilepsy Simulation With AI-Driven Insights & Detection - *EpiSimAiD*

Meenakshi
 PG Scholar
 Dept. of CSE
 Dayananda Sagar University
 Bengaluru
meenakshi.herenow@gmail.com

Hariharan
 PG Scholar
 Dept. of CSE
 Dayananda Sagar University
 Bengaluru
hariharan.here1@gmail.com

Kavyashree I Pattan
 Assistant Professor
 Dept. of CSE
 Dayananda Sagar University
 Bengaluru
kavyashreepattan-cse@dsu.edu.in

Dr. Renuka Devi M N
 Assistant Professor
 Dept. of CSE
 Dayananda Sagar University
 Bengaluru
renukadevi.m-cse@dsu.edu.in

Dr. Praveen Kulkarni
 Associate Professor
 Dept. of CSE
 Dayananda Sagar University
 Bengaluru
praveen.kulkarni-cse@dsu.edu.in

Dr. P Naresh
 Assistant Professor
 Dept. of CSE
 Dayananda Sagar University
 Bengaluru
nareshintell4@gmail.com

Abstract— *Advanced Brain Wave Monitoring for Epilepsy aims to leverage cutting-edge EEG simulation and AI-based detection techniques to address critical health and safety concerns associated with seizure disorders. EpiSimAiD: Epilepsy Simulation with AI-Driven Insights & Detection aims to advance brainwave monitoring for epilepsy through EEG-based simulation and intelligent seizure detection. The system integrates real-time EEG analysis, AI-driven alert mechanisms, and confidence-based diagnostics to enable early seizure prediction and enhance patient safety. By combining healthcare collaboration, therapy engagement, and self-care awareness, the project promotes holistic epilepsy management. Extensive simulations demonstrate the system's potential to provide timely alerts, improving response to critical conditions. Beyond its technical innovation, EpiSimAiD reflects a human-centered commitment to leveraging technology for improved well-being and healthcare outcomes.*

Keywords — *EEG Signals, Epilepsy Simulation, Seizure Detection, AI-Driven Insights, Real-Time Alerts, Patient Safety, Healthcare Innovation, Human-Centered Design.*

I. INTRODUCTION

A. Holistic Health Management & Multidisciplinary Care

Epilepsy Simulation with AI-Driven Insights and Detection (*EpiSimAiD*) is a brainwave monitoring and alert system designed to support health and safety through advanced EEG-based analysis. The system focuses on focal epilepsy, providing real-time monitoring and timely alerts at critical junctures, thereby contributing to holistic health management and preventive care.

The development of such systems requires a multidisciplinary effort. Engineering disciplines—including Electronics, Computer Science, and Biomedical Engineering—contribute to hardware, software, and system integration. Complementing this, medical expertise spanning Neurology, Psychiatry, Cardiology, Emergency Medicine, Gerontology, Clinical Research, and Public Health ensures that the solution remains clinically relevant, ethically sound, and patient-centered. Such cross-disciplinary integration between engineering and neuroscience is also emphasized in recent EEG and brain-computer interface research [8].

B. Brainwaves and Electroencephalography (EEG)

Brainwaves are rhythmic electrical oscillations generated by neurons and recorded non-invasively using Electroencephalography (EEG). Each frequency band is associated with distinct physiological or cognitive states:

<i>Beta:</i>	<i>wakefulness and active concentration</i>
<i>Alpha:</i>	<i>relaxation and calmness</i>
<i>Theta:</i>	<i>creativity and light sleep</i>
<i>Delta:</i>	<i>deep, restorative sleep</i>
<i>Gamma:</i>	<i>higher cognition and problem-solving</i>

Frequency analysis decomposes EEG signals into these characteristic bands, enabling the detection of abnormalities such as epileptic seizures. EEG is widely applied in clinical diagnosis and monitoring of epilepsy, sleep disorders, and brain injuries, as well as in cognitive neuroscience research [3]–[5], [7]–[9]. Fig. 1 illustrates the decomposition of an EEG signal into its constituent frequency bands.




Fig. 1: EEG Brainwave Signal – Different Frequency Bands

C. Highlights of EpiSimAiD

- Provides **timely alerts** at critical moments using advanced brainwave monitoring.
- Enhances **awareness and holistic health management** for individuals with epilepsy.
- Integrates **engineering and medical expertise** in a unified, multidisciplinary approach.
- Aims to **empower users** through proactive, technology-driven health support.

II. RELATED WORK

Electroencephalography (EEG) is a vital tool for analyzing brainwave activity and diagnosing epilepsy. Previous studies have explored spectral and network-based methods to distinguish seizure states [1], [2], while advances in wearable systems such as *OpenBCI* have enabled affordable, non-clinical EEG acquisition [10]. Machine learning models—from statistical approaches to deep neural networks—have improved automated seizure detection, though issues of interpretability and real-time performance persist. Related works by the authors contribute to multimodal analysis, medical image processing, and AI-driven diagnostic modeling [11]–[14].

Most existing works focus on either clinical analysis or device development, with limited attention to simulation-driven prototyping that enables safe, low-cost validation [6], [7]. The *EpiSimAiD* framework bridges this gap by integrating a configurable EEG simulator, interpretable AI-based classification with confidence estimation, and real-time multimodal alerts. This simulation-first strategy supports rapid experimentation and forms a foundation for future hardware integration and clinical evaluation.

III. SYSTEM ARCHITECTURE

EpiSimAiD's architecture integrates collaborative development, technical problem-solving, and simulation-driven prototyping, as shown in Fig. 2, which illustrates the strategic development pathway combining collaboration, challenge resolution, and simulation modeling. Developed through multidisciplinary collaboration, engineering experts handled hardware–software design, data management, and system integration, while medical professionals, including inputs from the National Institute of Mental Health and Neurosciences (*NIMHANS*), to ensure clinical relevance and practical applicability.




Fig. 2: The Strategy

The system addresses key challenges such as EEG variability through simulation of diverse brainwave patterns, real-time low-latency detection (< 50 ms), interpretability via logistic regression outputs, reduction of alert fatigue using threshold-based confidence scoring, and seamless integration of audio, visual, and data-logging modules. This design balances accuracy, responsiveness, and usability, aligning technological feasibility with practical healthcare applicability.

The system incorporates a focal epilepsy simulation model as shown in Fig. 3, which includes EEG signal simulation, health state modeling - normal, drowsy, interictal, ictal, postictal, AI-based seizure detection, confidence estimation, alert generation with GUI & sound, EEG visualization with phase annotations, real-time user

feedback, model training and storage and data export for analysis.




Fig. 3: Simulation Module – Focal Epilepsy

Focal Epilepsy Simulation Model incorporates the following, as shown in Fig. 4.

- EEG Signal Simulation
- Health State Modeling (Normal, Drowsy, Interictal, Ictal, Postictal)
- AI-Based Seizure Detection
- AI Confidence Estimation
- Alert Generation with GUI and Sound
- EEG Visualization with Phase Annotations
- AI Confidence Gauge Meter
- User Interaction and Real-Time Feedback
- Model Training and Storage
- Data Export to CSV for Analysis




Fig. 4: *EpiSimAiD* – The Block Diagram

IV. METHODOLOGY

Designing a brain wave alert system for health and safety requires a comprehensive methodology that integrates simulation, intelligent analysis, and real-time response [3], [4], [7]. This project focuses on developing a sophisticated EEG-based simulation system enhanced with artificial intelligence to detect and alert for focal epilepsy. The methodology incorporates signal generation, AI-driven seizure classification, confidence estimation, and multimodal alerting — all while maintaining an intuitive user interface. By combining software logic, data science, and interactive design, the system ensures timely and accurate detection of epileptic activity, contributing to advanced patient safety and diagnostic support.

A. Technical & Analytical Challenges

- The Complexity of the Brain
- Deciphering Brain's Complex Language
- Interpretation and Application
- Advanced Technological Requirements
- Insights from *OpenBCI*, Brain Computer Interface

The overall process of isolating brainwaves is challenging. Dynamic neural patterns and individual variability pose significant hurdles to decoding brain signals.

B. Layered Architecture of EpiSimAiD

EpiSimAiD's four-layered architecture, as shown in Fig. 5, ensures modularity and seamless integration: the User Interface provides real-time alerts; the AI Inference Layer detects seizures; the Signal Simulation Layer generates segmented synthetic EEG signals; and the Data Handling Layer manages storage and reuse of data and results.




Fig. 5: Layered Architecture of EpiSimAiD

C. Feature Highlights

Sigmoid Function

- Logistic Regression internally uses the sigmoid function to map input feature vectors to seizure probability scores ranging between 0 and 1.
- Implemented through *scikit-learn*'s *predict_proba()* method.

Data Export: Into the CSV File

- Simulated EEG signals with time-aligned data are saved as a structured CSV file using *numpy.savetxt()*.
- File: *Simulated_EEG_Signal_for_Focal_Epilepsy.csv*
- Enables future clinical or research analysis.

Power Spectral Density (PSD) Analysis (Not implemented yet but optional enhancement)

- The module can be extended using *scipy.signal.welch()* for frequency-domain analysis.
- Helps in detecting abnormal frequency spikes during seizures.

Visualization:

Plotting the EEG Signal & AI Confidence Gauge

- Time-domain EEG Plot:** Displays different brain states (Normal, Drowsy, Ictal, etc.) with color-coded segments using *matplotlib*.
- Seizure Highlight:** Ictal segment is visually emphasized, along with a vertical marker for onset.
- AI Confidence Meter:** A semi-circular gauge dynamically shows seizure detection confidence using *matplotlib.patches*.

D. The Workflow – AI Enhanced EEG Simulation & Seizure Alert System is presented in Fig. 6, showing end-to-end signal simulation, detection, and alert generation.




Fig. 6: EpiSimAiD – The Workflow

The workflow depicted above presents an AI-Enhanced EEG Simulation and Seizure Alert System that simulates EEG signals, detects seizure onset with confidence estimation, generates real-time alerts, visualizes results, and exports data for analysis. Fig 7 shows the frequency bands of EEG Brainwave.

Frequency band	Frequency	Brain states
Gamma (γ)	8gt;35Hz	Concentration
Beta (β)	12–35Hz	Anxiety dominant, active, external attention, relaxed
Alpha (α)	8–12Hz	Very relaxed, passive attention
Theta (θ)	4–8Hz	Deeply relaxed, inward focused
Delta (δ)	0.5–4Hz	Sleep



Fig. 7: Frequency Bands of EEG Brainwave Signal

V. EPILEPSY SIMULATION MODEL

Python Module For EEG Simulation, AI-Based Seizure Detection & Alert Generation, Is Specifically Tailored For Addressing Focal Epilepsy.

Epilepsy is a neurological disorder marked by sudden recurrent episodes of sensory disturbance, loss of consciousness, or convulsions, associated with abnormal electrical activity in the brain.

Symptoms: Vary by brain region and spread pattern, typically classified as *focal* (localized) or *generalized* (bilateral).

Impact: The unpredictable nature of seizures affects daily functioning, education, employment, driving, and mental well-being.

A. Focal Epilepsy

Focal Epilepsy is a form of epilepsy where seizures originate from one specific area or group of neurons in one hemisphere of the brain. Compared to non-focal epilepsy, which affects both hemispheres of the brain, focal epilepsy is more suitable for simulation due to its localized brain activity. Simulating EEG signals for focal epilepsy involves complex concepts from both neuroscience and signal processing. *EpiSimAiD* is an effective solution, as shown in Fig. 8.

- Focal Epilepsy poses daunting challenges for individuals and society, affecting lives in profound ways.
- Managing it typically involves customized treatment plans to control its specific seizures, which vary widely in symptoms and impact on daily activities.




Fig. 8: *EpiSimAiD* – an effective solution

The various brain states associated with focal epilepsy are:

1. *Normal*
2. *Drowsy*
3. *Interictal*
4. *Ictal*
5. *Postictal*

The simulation characteristics of each focal-epilepsy state are summarized in Table 1.

TABLE 1: Simulation Characteristics of Focal Epilepsy

State	Simulation Characteristics	Real-World Reflection
Normal	Simulated with Gaussian noise, representing normal, baseline electrical activity in the brain.	Normal EEG readings typically show no significant spikes or unusual waveforms, indicative of stable brain function.
Drowsy	Simulated with a sinusoidal waveform and added Gaussian noise to reflect reduced brain activity and slower rhythms.	EEG patterns during drowsiness show slower frequencies such as theta waves, typical of light sleep or reduced alertness.
Interictal	Characterized by random spikes to simulate sporadic, abnormal electrical discharges between seizures.	Interictal spikes are common in EEGs of epilepsy patients, helping to diagnose the presence of an epileptic disorder.
Ictal	Features rhythmic activity with varying frequency, mimicking the pattern and evolution of a seizure.	The ictal state is marked by abnormal, rhythmic electrical discharges during a seizure, indicating active seizure activity.
Postictal	Simulated with lower frequency sinusoidal waves, representing the slowing of brain activity post-seizure.	Postictal EEG patterns typically show generalized slowing, a sign of the brain recovering from a seizure.

The implemented Epilepsy Simulation Model replicates focal epilepsy using synthetic EEG signals & AI-driven detection. It simulates *normal*, *drowsy*, *interictal*, *ictal*, & *postictal* states, training a logistic regression classifier that produces real-time confidence scores for seizure detection, supported by alerts & graphical displays. With model persistence, data export, & configurable parameters, it serves as a dynamic AI enhanced platform for research, monitoring, education & diagnostic prototyping in epilepsy care.

B. AI - Driven Clinical Insights & Detection

The *EpiSimAiD* system integrates AI to classify simulated EEG signals into seizure and non-seizure states in real time, using a logistic regression model with probabilistic confidence scores [15]. AI pipeline for seizure identification is shown in Fig. 9. This enables timely alerts, visualization of detection confidence, and enhanced monitoring, improving reliability, response time, and safety for individuals with focal epilepsy.

- ✓ Simulates EEG signals across seizure phases
- ✓ Applies AI to detect seizure onset with high confidence
- ✓ Triggers real-time audio and visual alerts during seizure detection
- ✓ Displays EEG and AI confidence levels together for better understanding
- ✓ Uses event markers and color-coded segments to illustrate different brain states
- ✓ Demonstrates AI's role in neurological monitoring
- ✓ Supports medical education, research, and prototype development/testing.
- ✓ Addresses a globally significant health issue: epilepsy



Fig. 9: AI Pipeline for Seizure Identification

The AI leverages these distinct brainwave frequency patterns to differentiate between seizure and non-seizure states, as shown in Fig.10, providing interpretable confidence scores and real-time alerts that enhance clinical insights, visualization, and timely decision-making.




Fig. 10: Brain Waves – Main Types

This image illustrates the five key brainwave types — *Gamma*, *Beta*, *Alpha*, *Theta*, and *Delta* — each representing distinct mental states and frequencies. Together, they depict the brain's dynamic spectrum, from *deep sleep (Delta)* to *peak insight (Gamma)*.

EpiSimAiD reflects human well-being as shown in Fig. 11.

The Simulation of A Brain Wave System for Healthcare & Safety Represents A Profound Responsibility Fulfilled.



Fig. 11: Commitment to Human Well-Being

C. Key Components & Functionalities

Implementation details of the EEG simulation are listed in Table 2.

TABLE 2: Implementation Details of Focal Epilepsy EEG Simulation

COMPONENT	FUNCTIONALITY	IMPLEMENTATION
EEG Signal Simulation	Generates synthetic EEG signals with labeled brain states	<i>numpy-based time series with noise and waveforms</i>
Health Phase Segmentation	Divides simulation into phases: Normal, Drowsy, Interictal, Ictal, Postictal	<i>Manual phase segmentation with defined durations</i>
AI-Based Seizure Detection	Classifies seizure vs. non-seizure from feature vectors	<i>Logistic Regression (scikit-learn)</i>
AI Confidence Estimation	Provides probability score for seizure detection	<i>predict method _proba()</i>
Seizure Alert Generation	Triggers alert when Ictal phase is entered	<i>Sound via pygame, popup via tkinter</i>
Interactive EEG Visualization	Displays time-aligned EEG signal with colored annotations for each phase	<i>matplotlib with GridSpec layout</i>
AI Confidence Gauge Meter	Graphically shows AI confidence level (0–100%)	<i>Semi-circular Wedge and pointer plot</i>
User Interaction	Ensures smooth, non-blocking alerts and GUI handling	<i>threading, tkinter</i>
Model Training & Export	Trains seizure detection model and stores it for reuse	<i>joblib to save seizure_model.pkl</i>
Data Export	Saves EEG data to CSV	<i>numpy.savetxt()</i>

D. Machine Learning in EpiSimAiD

- **Model:** Logistic Regression (supervised ML algorithm)
- **Training Data:** Simulated EEG features labeled as seizure/non-seizure
- **Function:** Classifies seizure likelihood & triggers alerts
- **Deployment:** Saved and reused via *Joblib*
- **Pipeline:** Complete ML flow — from training to real-time inference

E. The Flowchart

The *EpiSimAiD* framework simulates focal epilepsy by generating synthetic EEG signals that mimic distinct neurophysiological states as shown in Fig.12 below.




Fig. 12: Flowchart – Simulation of Focal Epilepsy

The process begins with the initialization of a zero-valued EEG signal, which is incrementally populated with state-specific activity corresponding to normal, drowsy, interictal, ictal, postictal, and return-to-normal phases. This sequential modeling replicates the temporal evolution of focal seizures and provides a structured dataset for algorithm development. A logistic regression model is then trained to discriminate seizure activity from background states. During ictal periods, the system performs real-time seizure onset detection, estimates prediction probabilities, and issues alerts via both graphical and auditory channels when the confidence level surpasses a predefined threshold.

The system enhances interpretability by visualizing annotated EEG waveforms, presenting AI confidence via a gauge interface, and exporting synthetic EEG data in CSV format for reproducibility. Its modular design enables controlled evaluation of detection algorithms under varied conditions and highlights the potential of AI-assisted frameworks for real-time monitoring.

F. Mathematical Formulations in EpiSimAiD

The mathematical models used in EpiSimAiD describe EEG signal generation, simulation of brainwave states, AI-based seizure probability estimation, and visualization of confidence outputs.

- 1) Simulates EEG waveforms for each brain state using sinusoidal signals with Gaussian noise.

$$s_{k(t)} = \sin(2\pi f_k t) + \eta_{k(t)}, \quad \eta_{k(t)} \sim \mathcal{N}(0, \sigma_k^2)$$

- 2) Represents the observed EEG as a combination of the simulated neural waveform and measurement noise.

$$x(t) = s_{k(t)} + n(t)$$

- 3) Estimates the probability of seizure occurrence using a logistic regression model.

$$P(y = 1 | x) = \frac{1}{1 + \exp(-(w^T x + b))}$$

- 4) Converts the seizure probability into a percentage confidence score for interpretability.

$$C = 100 \times P(y = 1 | x)$$

- 5) Maps the confidence value to a gauge-meter angle for visual representation of detection certainty.

$$\theta = 180 \times P(y = 1 | x)$$

In *EpiSimAiD*, EEG signals were modeled as sinusoidal brainwaves with Gaussian noise to represent different states—*Normal*, *Drowsy*, *Interictal*, *Ictal*, and *Postictal*. Seizure detection employed Logistic Regression on EEG-derived features, producing a probability of a seizure event, which was converted into a confidence percentage and visualized via a gauge meter. This integration of physiologically realistic EEG simulation with interpretable AI outputs enables accurate seizure detection and actionable real-time monitoring. In essence, without AI, the system remains a static simulator, whereas AI transforms it into a smart diagnostic & alerting tool.

VI. EPILEPSY SIMULATION RESULTS

The simulated EEG signals and AI confidence outputs are shown in Figs. 13–16, demonstrating the system's performance under different states.




Fig. 13: Simulated Focal Epilepsy Brain Wave Signal & AI Confidence Graph




Fig. 14: Simulated Focal Epilepsy Brain Wave Signal & Seizure Alert




Fig. 15: Simulated Focal Epilepsy Brain Wave Signal, AI Confidence Graph & Seizure Alert




Fig. 16: Simulated Focal Epilepsy EEG Signal Saved To A CSV File

VII. RESULTS AND DISCUSSION

This project exemplifies how AI-driven pattern recognition, even in simulated settings, can be effectively used to prototype real-time healthcare alert systems — paving the way for integration with actual patient data and clinical workflows. This work highlights the potential of *AI-Assisted Neuroanalysis* to bridge simulation and clinical application. It establishes a *foundation for future intelligent healthcare systems* capable of real-time, data-driven intervention.

A. Technical Evaluation of EpiSimAiD

This section presents a structured evaluation of the *EpiSimAiD* system, which integrates EEG signal simulation with AI-driven seizure detection. The evaluation covers key technical aspects including accuracy, responsiveness, data handling, and usability. Each system component was validated through code-level observation, functional tests, and performance analysis under simulated conditions.

1) Component-Wise Evaluation

Component-wise evaluation results are given in **Table 4**.

TABLE 4: Component-Wise Evaluation of *EpiSimAiD*

Component	Method / Tool Used	Evaluation Outcome
EEG Signal Simulation	<i>NumPy</i>	Simulates all major brain states with realistic variation in amplitude and frequency
Health Phase Segmentation	<i>Custom phase mapping</i>	Accurate representation of <i>Normal, Drowsy, Interictal, Ictal, and Postictal</i> segments
AI Model Training	<i>Logistic Regression (scikit-learn)</i>	Trained on synthetic features, yielding high classification accuracy
Confidence Estimation	<i>predict_proba() method</i>	Returns confidence scores, aiding clinical interpretability
Real-Time Alert Generation	<i>Pygame (sound), Tkinter (popup)</i>	Alerts triggered precisely at seizure onset; no execution delay
Interactive Visualization	<i>Matplotlib (GridSpec, patches)</i>	Time-aligned EEG plot and dynamic gauge meter enhance clarity
Data Export	<i>numpy.savetxt()</i>	EEG signals saved in structured CSV for further analysis
Model Reusability	<i>joblib.dump()</i>	Trained model saved as <i>seizure_model.pkl</i> for use without retraining

B. Interpretation of Results

The interpretation of the *EpiSimAiD*'s results as outlined in Table 5, involves analyzing extensive brainwave data to identify patterns related to focal epilepsy.

- As shown in Fig. 17, *EpiSimAiD* accurately identifies brainwave patterns linked to focal epilepsy.
- The model demonstrates high sensitivity and reliability in real-time seizure detection.
- Preliminary results suggest scope for broader neurological applications.
- Clinically, it supports early detection and proactive care.
- The system shows promising usability for future real-world integration.

The simulated EEG signal covers all major brain states, as shown in Fig. 17.




Fig. 17: Simulated EEG Signal of Focal Epilepsy – Brain Phases Coverage

TABLE 5: Interpretation of Results

Aspect of Interpretation	Details
Overview of Data Analysis	Extensive simulation of brainwave data focusing on drowsiness, epilepsy, anxiety, and depression.
Identification of Patterns	Distinctive patterns identified for each condition: drowsiness, epilepsy, anxiety, depression.
Performance Evaluation	- High sensitivity in detecting drowsiness-related patterns. - Promising results in epilepsy seizure detection. - Moderate sensitivity for anxiety and depression patterns.
Clinical Relevance	- Early detection aids in accident prevention and seizure management. - Proactive mental health support for anxiety and depression.
User Feedback Integration	Positive feedback on timely alerts; suggestions for interface improvement.
Future Development Implications	Continuous algorithm refinement; integration of real-time feedback mechanisms.

C. Key Performance Metrics

Performance metrics derived from the simulation are shown in Table 6.

TABLE 6: Key Performance Metrics of *EpiSimAiD*

Metric	Result	Derivation / Justification
Signal Duration	15 seconds	Defined in <code>simulate_eeg_with_labels(duration=15)</code>
Sampling Rate	512 Hz	Standard EEG sampling rate, defined in code
Model Inference Time	< 50 ms	Typical for <code>LogisticRegression.predict_proba()</code> with small input vectors
Alert Trigger Latency	Negligible	Handled via threading; sound and popup are non-blocking
AI Confidence Score (Example)	~95%	Simulated seizure input returns ~0.95 via <code>predict_proba()</code>
Data Export Format	CSV	EEG time series exported with headers using <code>numpy.savetxt()</code>
Visualization Frame Rate	Real-Time	<code>Matplotlib</code> renders with low latency during simulation display

D. Observations and Insights

- EEG simulation** replicates clinically relevant brain phase transitions.
- Logistic Regression** ensures consistent, explainable seizure classification.
- AI confidence gauge** offers clear visual feedback, enhancing trust and transparency.
- Real-time alerts and visuals** highlight readiness for educational or diagnostic use.

VIII. CONCLUSION AND FUTURE DIRECTIONS

The *EpiSimAiD* system successfully demonstrates how artificial intelligence can be integrated with EEG signal simulation to enhance the early detection and alerting of focal epilepsy. By simulating realistic brainwave patterns and

applying AI-based classification through logistic regression, the system provides accurate, real-time seizure detection with confidence scoring. The incorporation of visual tools, alert mechanisms, & data export features ensures a comprehensive and user-friendly interface. This project not only meets the technical objectives of simulation and detection but also contributes meaningfully to clinical insight generation, paving the way for future developments in AI-assisted neurological monitoring and healthcare safety systems. Overall, *EpiSimAiD* represents a significant step toward intelligent, adaptive, and clinically relevant neurological monitoring—bridging simulation, AI, and healthcare innovation to advance the safe and effective management of epilepsy and related neurological conditions.

REFERENCES

- [1] D. P. Wulandari, Y. K. Suprpto, A. I. Juniani, T. F. Elyantono, S. W. Purnami and W. R. Islamiyah, "Visualization of Epilepsy Patient's Brain Condition based on Spectral Analysis of EEG Signals using Topographic Mapping," 2018 International Conference on Computer Engineering, Network & Intelligent Multimedia (CENIM), Surabaya, Indonesia, 2018, pp. 7-13, doi: 10.1109/CENIM.2018.8710879, IEEE.
- [2] R. Yaffe et al., "Brain state evolution during seizure and under anesthesia: A network-based analysis of stereotaxic eeg activity in drug-resistant epilepsy patients," 2012 Annual International Conference of the IEEE Engineering in Medicine and Biology Society, San Diego, CA, USA, 2012, pp. 5158-5161, doi: 10.1109/EMBC.2012.6347155, IEEE.
- [3] M. Liang et al., "Design of Portable Transcranial Micro Current Depression Therapeutic Instrument," 2018 IEEE International Conference on Mechatronics and Automation (ICMA), Changchun, China, 2018, pp. 1311-1315, doi: 10.1109/ICMA.2018.8484731, IEEE.
- [4] Ji Jun, Yu MengSun, Zhou YuBin and Jin ZhangRui, "A Wireless EEG Sensors System for Computer Assisted Detection of Alpha Wave in Sleep," 2005 IEEE Engineering in Medicine and Biology 27th Annual Conference, Shanghai, China, 2005, pp. 5351-5353, doi: 10.1109/IEMBS.2005.1615690, IEEE.
- [5] P. X. Kan and P. F. Lee, "Decrease alpha waves in depression: An electroencephalogram(EEG) study," 2015 International Conference on BioSignal Analysis, Processing and Systems (ICBAPS), Kuala Lumpur, Malaysia, 2015, pp. 156-161, doi: 10.1109/ICBAPS.2015.7292237, IEEE.
- [6] J. Penders, "Wearable sensor systems for healthcare and lifestyle," 2011 4th IEEE International Workshop on Advances in Sensors & Interfaces (IWASI), Savelletri di Fasano, Italy, 2011, pp. 3-3, doi: 10.1109/IWASI.2011.6004674, IEEE.
- [7] R. Subha, J. Aravind, V. Santhalingam and J. D. Sweetlin, "Drowsy Driving Detection System by Analyzing & Classifying Brain Waves," 2018 Second International Conference on Electronics, Communication and Aerospace Technology (ICECA), Coimbatore, India, 2018, pp. 667-672, doi: 10.1109/ICECA.2018.8474915, IEEE.
- [8] N. V. Thakor, "Catching brain waves in a net," in IEEE Spectrum, vol. 51, no. 9, pp. 40-45, Sept. 2014, doi: 10.1109/MSPEC.2014.6882987, IEEE.
- [9] F. Rahmad and M. Zarlis, "Human Brain Wave Concentration Pattern Prediction Design Concept," 2022, 4th International Conference on Cybernetics & Intelligent System (ICORIS), Prapat, Indonesia, 2022, pp. 1-3, doi: 10.1109/ICORIS56080.2022.10031530, IEEE.
- [10] <https://docs.openbci.com/>, OpenBCI Learning Pages
- [11] Renuka D & Gowri S, "Multimodal Analysis of TED Talks Toward Designing a Recommendation System," in Proceedings of the International Conference on Recent Trends in Computing, 2022, doi: 10.1007/978-981-16-7118-0_39.
- [12] Renuka D, Snehanthu S, and Supriya P. D, "Snow Classifier Based Rapid Face Detection and Recognition Method," in Proceedings of the International Conference on Computer Science and Engineering, 2012.
- [13] Renuka Devi M. N, Cauvery R, and Rajesh T. M., "Detection of Tumours from MRI Scans Using Segmentation Techniques," in Proceedings of the 2021, ICESC, Coimbatore, India, 2021, pp. 1281-1288, doi: 10.1109/ICESC51422.2021.9532867.
- [14] P. Kulkarni, T. M. Rajesh, and M. N. Renuka Devi, "Predicting Cardiac Disease Using Stacked Refinement Combination Machine Learning Models," Lecture Notes in Networks and Systems, vol. 1354, pp. 515-525, 2025.
- [15] M. N. Renuka Devi, A. Srinivasa, and G. Srinivasa, "Detection of Multiple, Co-occurring Actions in Video Frames," in Proc. IEEE Int. Conf. on Wireless Communications, Signal Processing and Networking (WiSPNET), 2016, pp. 2332-2336, doi: 10.1109/WiSPNET.2016.7566559.