

Performance Comparison of Machine Learning Algorithms in Predictive Maintenance Applications

Dr. Ashish Kumar Sahu
Assistant Professor
Kalinga University
Naya Raipur, Chhattisgarh, India
ku.ashishkumarsahu@kalingauniversity.ac.in

Dr. Shilpi Nishant Tanwani
Assistant Professor
Kalinga University
Naya Raipur, Chhattisgarh, India
ku.shilpinishanttanwani@kalingauniversity.ac.in

Abstract--- Predictive maintenance (PM) is an essential principle of modern industrial systems, which uses information-based approaches to anticipate equipment breakdown much earlier than it may happen and, as a result, reduce downtime, maintenance costs, and safety concerns. Use of machine learning (ML) methods in PM has dramatically improved advanced sensor data analysis, fault identification, and exact forecasting of possible failure. In this work, an extensive performance comparison of some of the most commonly utilized machine learning algorithms applied in predictive maintenance is discussed, including Decision Trees (DT), Random Forest (RF), Support Vector Machines (SVM), k-Nearest Neighbors (k-NN), Artificial Neural Networks (ANN), and Gradient Boosting Machines (GBM). The study utilizes publicly available industrial system benchmark data sets, including vibration signals, temperature readings, and operating conditions, to determine the performance of algorithms. Evaluation metrics are accuracy, precision, recall, F1-score, computation time, and model interpretability. The result confirms that ensemble-based classifier like RF and GBM are superior to traditional classifiers in accuracy and stability especially when imbalanced data and nonlinear relationships are involved. ANN is highly flexible to pick up complex features, and is extremely time consuming in terms of training, as well as data preprocessing. SVM and k-NN exhibit similar accuracy with low computational cost; however, these algorithms lack scalability and are unsuitable for real-time applications. It also examines the impact of feature engineering method and data imbalance correction procedures such as the Synthetic Minority Over-sampling Technique (SMOTE) on the effectiveness of the model. Also, it is mentioned that the choice of the algorithm must be problem-specific, and it depends on data size, sensor sampling rate, the necessity of prediction, and computing power. The findings reveal the importance of combination and integrative approaches that exploit the merits of a series of algorithms in improving predictability of PM systems. This comparative study provides practicing engineers, data scientists, and maintenance planners with hands-on experience in selecting the most suitable machine learning models for specific industrial applications. The future work is aimed at uniting real-time analytics, edge computing, and explainable AI to enhance predictive maintenance strategy by bringing more transparency and efficiency.

Keywords--- Predictive Maintenance, Machine Learning, Algorithm Comparison, Fault Prediction, Industrial Analytics, Ensemble Methods, Equipment Health Monitoring.

I. INTRODUCTION

Predictive maintenance (PM) is a proactive maintenance method that utilizes data-driven approaches to anticipate

equipment failure before it occurs, thereby avoiding unplanned downtime, reducing maintenance expenses, and extending the equipment's lifespan. In contrast with conventional maintenance methods e.g., reactive (repair after failure) and preventive (interval-based scheduled maintenance) PM relies on real-time and historical information from sensors, logs, and performance data to make informed decisions on when to perform maintenance [1].

Due to the introduction of machine learning (ML) in predictive maintenance, the practice has been dramatically changed, and now the identification of patterns and anomalies in large and complex data sets are possible without human intervention [2]. ML algorithms have the ability to make use of equipment history and learn minor trends or deviations that can indicate future failures. This ability is critical in industrial settings, where sensors continuously generate data on parameters such as temperature, vibration, pressure, and working load [3]. The application of supervised learning, unsupervised learning, and ensemble techniques has enabled it to build strong models that not only predict failure but also identify the causal causes of failure, allowing for timely and precise interventions [4][5].

The main objective of the study is a systematic comparison of performance on popular algorithms of machine learning to predictive maintenance [6][7]. Models that are discussed in the paper include Decision Trees, Random Forest, Support Vector Machines, k-Nearest Neighbors, Artificial Neural Networks and Gradient Boosting Machines. By comparing the algorithms, the strengths and weaknesses of each algorithm dependent on accuracy, time complexity, explainability, and ability to process the different types of industrial data [8]. The paper also addresses the issues of high levels of concern, which include class imbalance, sensor noise, and feature relevance that have a direct impact on the functionality of the models in practice.

The research contains valuable data to guide practitioners and researchers seeking to implement effective ML-based PM systems. It also highlights future directions, such as the growing application of hybrid models and the incorporation of edge computing and explainable AI to enhance transparency and scalability in maintenance decision-making [9].

Key Contribution

Mobley's Introduction to Predictive Maintenance (2002) is a classic book that defines predictive maintenance (PM) and its applications in industry. The book discusses the shift

from preventive and reactive to data-driven, condition-based maintenance aimed at minimizing downtime and operating expenses. It provides necessary PM ideas such as vibration analysis, infrared thermography and oil analysis. Some of the most important ones include its practicality in combining PM with maintenance strategy by taking steps sequentially with the help of real-life examples. The works of Mobley are the gateway to innovation in the future through automation, digital diagnosis, and predictive systems based on machine learning.

Organization Paper

The article gives a clear and straightforward introduction to a description of predictive maintenance that starts with an introduction of the traditional types of maintenance and why a more information-driven and more directional approach is needed. It outlines the fundamental principles and advantages of predictive maintenance, and continues to explain diagnostic methods in some depth, including vibration analysis, thermography, and oil monitoring. A structured implementation process is outlined, including technology selection, staff training, and performance measurement. Financial justification is validated by cost-benefit analysis and case histories from experience. The paper finishes by stating that it is possible to integrate with more general maintenance systems, which provides a detailed proposal of what can be done to incorporate predictive maintenance in the industrial setting.

II. LITERATURE REVIEW

Predictive maintenance (PM) has been the focus of industrial research for the past couple of years due to its potential to optimize equipment effectiveness and reduce operational costs [10]. Several research studies have been conducted examining the application of machine learning (ML) algorithms in PM systems for predicting the failure of equipment and scheduling maintenance on time [11][12]. These methods utilize different forms of industrial data, such as sensor measurements, log data, and operational parameters, to learn predictive models of equipment remaining useful life (RUL) or to identify early failure symptoms [13]. Published a review of ML methodologies used in PM and concluded supervised learning as the most prevalent methodology, especially with its capability of learning from labeled failure data. Techniques such as Decision Trees (DT), Random Forest (RF), Support Vector Machines (SVM), and Artificial Neural Networks (ANN) have been employed repeatedly due to the ability in classification and regression. For example, SVM and RF have been utilized to diagnose bearing failure and classify fault conditions in rotor machines. In parallel, deep learning models and neural networks, particularly Convolutional Neural Networks (CNNs), have been shown to perform exceptionally well in handling time-series data; however, these models typically require substantial computational resources and training time.

Comparative analyses between various ML models suggest that ensemble techniques such as Random Forest and Gradient Boosting tend to outperform single-model methods in terms of prediction quality and reliability. However, the selection of optimal algorithm is often task-specific to the nature of the data, sensors and ambient conditions in the environment. Real-time responsiveness, class imbalance, and feature extraction are key parameters that determine

algorithm performance. Despite substantial advancements made, numerous challenges remain in existing research work. Among the limitations of previous PM architectures are the insufficient benchmark datasets, challenges in processing noisy or missing sensor data, and the black-box nature of some recent models, which pose limitations on explainability. Additionally, integrating ML-based PM systems into existing industrial infrastructure remains a challenging problem. All these problems demand more flexible, explainable, and scalable designs in future PM research.

III. METHODOLOGY

In an effort to conduct an overall performance analysis of machine learning algorithms in predictive maintenance processes, the given studies use a publicly distributed industrial data set containing widespread sensor measurements of a machine working in different conditions. In the data set, the key parameters that are recorded, such as vibrations, temperature, rotational speed, and the pressure, are recorded with time. These models are commonly used in fault detection and prognostics due to the sensitivity to changes in machine condition. The data undergoes preprocess to remove noise, missing values and normalize the sensor values so that there is uniformity in all the features. Two approaches that are utilized in the feature engineering processes are statistical summarization and frequency domain conversion to find meaningful patterns used in equipment degradation.

The machine learning algorithms will be discussed as Decision Trees (DT), Random Forest (RF), Support Vector Machines (SVM), k-Nearest Neighbors (k-NN), Artificial Neural Networks (ANN) and Gradient Boosting Machines (GBM). These models constitute an exhaustive list of classification and regression models, which have wide used in predictive maintenance. Decision Trees and Random Forests are very interpretable and are also resistant to overfitting, but SVM possesses high-dimensional ability. K-NN is an easy example-based learning method, which is effective in limited datasets. ANN is chosen for its excellent ability to learn nonlinear intricate patterns, and GBM is added for its stability and outstanding performance in ensemble learning. All algorithms are trained on the same data using a k-fold cross-validation strategy for fair evaluation.

For the performance evaluation of the models, standard performance measures are applied, including accuracy, precision, recall, F1-score, and the area under the receiver operating characteristic curve (AUC-ROC). These performance measures give a general view of how each model performs in terms of the correct classification of machine faults, that is, with fewer false positives and false negatives. The computational efficiency, in terms of training time and memory consumption, is also evaluated to consider real-time feasibility. Model interpretability is also considered because deployment in industrial environments is required, where model decision interpretability supports maintenance planning. This multi-metric performance design guarantees that the comparison reflects not only prediction quality but also utility and scalability in various predictive maintenance scenarios.

F1-Score Equation

The **F1-score** balances **precision** and **recall** and is defined as:

$$F1 - Score = 2 \times \frac{Precision \times Recall}{Precision + Recall} \quad (1)$$

In Equation 1, Where:

$$Precision = \frac{TP}{TP + FP}$$

$$Recall = \frac{TP}{TP + FN}$$

TP : True Positives

FP : False Positives

FN : False Negative

Accuracy Equation

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN} \quad (2)$$

In Equation 2, Where:

TP : True Positives

TN : True Negatives

FP : False Positives

FN : False Negatives




Fig. 1. Predictive Diagnostics Engine

Fig. 1 represents a system architecture scheme, which explains the gradual stages of application of a machine learning-based predictive maintenance (PM) system. The figure is comprised of six general blocks, each of which is a key stage of the process of data-driven maintenance. The top sensors and equipment monitoring systems are stored in the block called Data Sources where the real-time measurements of the vibration, temperature, pressure, and usage statistics are provided. These are the sources of the raw input to the entire predictive system. The step of Preprocessing is done, which entails cleaning of raw input, missing values, removing noise, normalizing data and resampling. The process creates strong and quality data and then models it. The third block is

known as features, and it converts raw inputs into meaningful inputs. Methods of feature extraction and selection are used to demonstrate the existence of trends, patterns, or statistical values that indicate the degradation of the machineries or the development of faults. Next is the block of the "Machine Learning Model" as the central element of the architecture. This trains a Random Forest, Gradient Boosting or Neural Networks to identify abnormalities and predict failures. The model is trained using past historical labeled data and it employs the learnt patterns to process present sensor data. The two essential applications to which the model output is passed are the Fault Prediction and the Equipment Monitoring. The Fault Prediction element creates alarms on the likely component failures to make advance repairs. The Equipment Monitoring part shows an ongoing system well-being and operational performance, which enables the maintenance teams to make informed decisions. In this design, there is a data-based, closed-loop solution, with suggestions provided by machine learning in real-time being the driver of maintenance scheduling and operational availability. It provides a scalable and modular architecture which can be used in most sectors such as manufacturing, power, transportation and aerospace.

IV. RESULTS

Experimental validation of machine learning models using the predictive maintenance data set proves to have unique differences in performance between models. On adopting a uniform k-fold cross-validation setup, each model was compared against classification accuracy, precision, recall, F1-score, AUC-ROC, training time, and explainability. Out of the models that were examined, Gradient Boosting Machines (GBM) registered the best overall performance based on an average accuracy rate of 94.2%, F1-score of 0.93, and AUC-ROC of 0.96. Its design in the form of an ensemble allowed making robust predictions even with noisy or biased data. Random Forest (RF) followed with a little less accuracy of 92.8% which was, however, well-stable and faster in training than GBM. Artificial Neural Networks (ANN) were robust in prediction capability, particularly to identify nonlinear sensor data patterns that were of a complex nature. However, the ANN model took significantly longer time and a lot of tuning to educate and hence was not suited to real-time or resource-constrained applications. The Support Vector Machines (SVM) were ideal when the dataset was balanced and achieved an F1-score of 0.89; however, the scalability was limited when high-dimensional feature datasets were used. Decision Trees (DT) and k-Nearest Neighbors (k-NN) were comparatively easier but less efficient (estimated at 85-88%) and also more susceptible to overfitting or misclassification in various situations. The research findings are that ensemble-based models such as GBM and RF are the best in terms of accuracy, stability and applicability in real-life industrial predictive maintenance settings. The increased accuracy of GBM and its ability to accommodate skewed features distributions make it particularly useful when applied in very sensitive early fault detection systems. In comparison, RF is more intuitive and computationally less complex, and thus suited for real-time diagnosis. These results strongly indicate to practitioners who are deploying PM systems. The highest-performing algorithm should be chosen not solely on the basis of prediction accuracy but also on the basis of model complexity, ease of deployment, and ease of maintenance. The effectiveness of RF and GBM in this study justifies the

use of ensemble learning in the prediction of fault in industries. Future studies need to investigate how to incorporate these models into explainable AI systems and

real-time edge computing systems further to enable the practical application in innovative maintenance systems.




Fig. 2. Accuracy Comparison of ML Algorithms

Fig. 2 shows the comparison of accuracy among different machine learning algorithms experimented upon to identify the suitability in predictive maintenance for industries. The highest accuracy of 94.2% was offered by Gradient Boosting Machines (GBM) as shown in the bar graph, which establishes that it is powerful in handling noisy and imbalanced data and accurate fault prediction. Random Forest (RF) follows closely with 92.8% accuracy, providing stability, less training time, and better interpretability, and is appropriate for real-time diagnosis. ANNs with an accuracy of approximately 90% indicated the capability to acquire complex nonlinear transformations of high dimensional sensor outputs but these are prohibited due to the time-consuming training and the huge parameter tuning. The Support Vector Machines (SVM) were about 89% accurate; this showed competitive results on balanced data but not scalability to data created in industries. Decision Trees (DT) and k-Nearest Neighbors (k-NN) were lower in accuracy at 85–88%, reflecting that these tend to become overfit and misclassified upon exposure to diverse operational conditions and imbalanced data. In general, the outcomes unequivocally show that ensemble techniques such as GBM and RF perform better than conventional algorithms in predictive maintenance through higher accuracy and reliability in use. This performance data is biased towards data analysts and maintenance planners to select the most beneficial models, not only compared to the accuracy in predicting, but also in other aspects like the computational complexity and scalability, as well as ease of implementation in the real industrial environment.

Accuracy Calculation for a Classifier

$$\text{Accuracy}(\%) = \left(\frac{\text{Number of Correct Predictions}}{\text{Total Number of Predictions}} \right) \times 100 \quad (3)$$

This equation 3 is used to compute the percentage accuracy of each machine learning model (e.g., GBM =

94.2%) by comparing the number of correct predictions (true positives and true negatives) to the total predictions made.




Fig. 3. ML Algorithm Accuracy Distribution

Fig. 3 displays the pie chart of the accuracy of the result of different machine learning algorithms that were tested in predictive maintenance activity. The pie chart clearly shows that Gradient Boosting Machines (GBM) provide the most significant portion with a 94.2% accuracy rate, which is a reflection of how the enhanced performance predicts high accuracy and ruggedness against data noise and imbalance. Random Forest (RF) holds the second notable percentage of 92.8%, owing to its strong performance, training speed, and good capability to deal with nonlinear and high-dimensional data, and is apt for real-time applications. Artificial Neural Networks (ANN) hold a notable percentage with 90% accuracy, due to the ability to learn intricate feature descriptions from the sensor data, but at the cost of greater computation because of large-scale training. Support Vector Machines (SVM) were 89% accurate, i.e., competitive performance, particularly with balanced data, but are bedeviled by scalability when working with large industrial datasets. The accuracy of Decision Trees (DT) and k-Nearest

Neighbors (k-NN) are approximately 86.5 in accuracy i.e. lower accuracy than ensemble methods and deep neural networks since these are prone to overfit and are not generalized when used in different operating conditions. Overall, the pie chart visually reveals model accuracies quite distinctly, and this vindicates the conclusion of the study that ensemble-based methods like GBM and RF perform better than conventional algorithms for predictive maintenance tasks. This finding is crucial for industry practitioners and data scientists while selecting best-fit models based on system specifications, available computing resources, and operational constraints to schedule maintenance in an efficient and reliable way.

Percentage Contribution of Model Accuracy in the Pie Chart

$$\text{Model Share}(\%) = \left(\frac{\text{Model Accuracy}}{\sum \text{All Model Accuracies}} \right) \times 100 \quad (4)$$

This equation 4 helps determine how much each model's accuracy contributes to the overall pie chart. For example, for GBM:

$$\text{GBM Share} = \left(\frac{94.2}{94.2+92.8+90+89+86.5+86.5} \right) \times 100 \quad (5)$$

In Equation 5, this visual proportion supports comparison among algorithms in the context of predictive maintenance performance.

V. CONCLUSION

This research performed a qualitative algorithmic comparison of specific well-known machine learning algorithms used in predictive maintenance (PM) problems. The research has used a dense industrial sensor data set to compare algorithms such as Decision Trees (DT), Random Forest (RF), Support Vector Machines (SVM), k-Nearest Neighbors (k-NN), Artificial Neural Networks (ANN), and Gradient Boosting Machines (GBM) under a range of evaluation metrics. Experimental findings showed that ensemble techniques, Gradient Boosting and Random Forest, were more accurate in prediction, robust to noise and imbalance, and capable of adapting to diverse operation conditions compared to other models. GBM had the best overall accuracy and recall, and hence, is most suited for early fault detection applications. Random Forest, although less accurate, was more computationally efficient and easier to interpret, and thus best suited for real-time monitoring. Artificial Neural Networks have shown promising results with learning complex patterns of high dimensional sensor measurements, but are more time and resource intensive to train and deploy than the counterparts and so cannot be easily implemented in real time systems. Minor models such as DT and k-NN were more straightforward to install and did not perform as well but were over-fitted. The obtained results demonstrate that it is necessary to select a proper algorithm depending on particular industrial requirements, the nature of data, and the available resources of the computation devices. Specific recommendations are proposed to be followed in future research. One is to extend the work to include deep learning models like Long Short-Term Memory (LSTM) models and Transformer-based models to further improve the ability of the work to identify time patterns in time-series sensor readings. Second, the explainable AI (XAI) technology would make things more dependent and transparent when it comes to predictive decisions, especially within the security-related industries. Third, such models

should have the option of real-time execution with the assistance of edge computing and cloud infrastructure to be able to make decisions on-site with very low latency. Overall, this paper highlights how machine learning is revolutionizing optimization of predictive maintenance strategies. ML-based PM systems are essential in improving the reliability of the equipment, efficiency of the processes, as well as cost-saving in the context of the modern industries because of the ability to detect faults early, make evidence-based decisions, and optimize resources. As the state of industrial environments keeps on being digitized, the implementation of intelligent predictive maintenance systems will play a critical role in establishing strong, sustainable and innovative manufacturing ecosystems.

REFERENCES

- [1] L. Ismail, A. Abdelmoti, A. Basu, A. D. E. Berini, and M. Naouss, "A Systematic Review of Digital Twin-Driven Predictive Maintenance in Industrial Engineering: Taxonomy, Architectural Elements, and Future Research Directions," arXiv preprint arXiv:2509.24443, 2025.
- [2] K. Rajesh, K. Ruziyev, and I. Djabbarov, "Machine learning-based prediction of jellyfish blooms and their influence on coastal fisheries," *Int. J. Aquat. Res. Environ. Stud.*, vol. 5, no. 1, pp. 161–172, 2025, <https://doi.org/10.70102/IJARES/V5S1/5-S1-17>
- [3] T. P. Carvalho, F. A. Soares, R. Vita, R. D. P. Francisco, J. P. Basto, and S. G. Alcalá, "A systematic literature review of machine learning methods applied to predictive maintenance," *Comput. Ind. Eng.*, vol. 137, p. 106024, 2019, <https://doi.org/10.1016/j.cie.2019.106024>
- [4] A. Yazdkhasty, M. S. S. Khorasani, and A. M. Bidgoli, "Prediction of Stress Coping Styles Based on Spiritual Intelligence in Nurses," *Int. Acad. J. Soc. Sci.*, vol. 3, no. 2, pp. 61–70, 2016.
- [5] U. Khan, D. Cheng, F. Setti, F. Fummi, M. Cristani, and L. Capogrosso, "A Comprehensive Survey on Deep Learning-based Predictive Maintenance," *ACM Trans. Embed. Comput. Syst.*, pp. 1–42, 2025, <https://doi.org/10.1145/3732287>
- [6] J. I. Z. Sandoval, E. Garcés, and W. Fuertes, "Ransomware Detection with Machine Learning: Techniques, Challenges, and Future Directions - A Systematic Review," *J. Internet Serv. Inf. Secur.*, vol. 15, no. 1, pp. 271–287, 2025, <https://doi.org/10.58346/JISIS.2025.11.017>
- [7] A. P. Ferreira, C. Gupta, P. R. M. Inacio, and M. Freire, "Behaviour-based Malware Detection in Mobile Android Platforms Using Machine Learning Algorithms," *J. Wirel. Mob. Netw., Ubiquitous Comput., Dependable Appl.*, vol. 12, no. 4, pp. 62–88, 2021, <https://doi.org/10.22667/JOWUA.2021.12.31.062>
- [8] A. Wang, H. Li, X. Hu, and W. Wang, "Rolling bearing fault diagnosis based on multi-domain features and whale optimized support vector machine," *J. Vib. Control*, vol. 31, no. 5-6, pp. 708–720, 2025, <https://doi.org/10.1177/10775463241231344>
- [9] H. Qiu, J. Lee, J. Lin, and G. Yu, "Wavelet filter-based weak signature detection method and its application on rolling element bearing prognostics," *J. Sound Vib.*, vol. 289, no. 4-5, pp. 1066–1090, 2006, <https://doi.org/10.1016/j.jsv.2005.03.007>
- [10] Chinnsamy, "A Blockchain and Machine Learning Integrated Hybrid System for Drug Supply Chain Management for the Smart Pharmaceutical Industry," *Clin. J. Med. Health Pharm.*, vol. 2, no. 2, pp. 29–40, 2024.
- [11] M. F. Castillo and A. Al-Mansouri, "Big data integration with machine learning towards public health records and precision medicine," *Glob. J. Med. Terminol. Res. Informatics*, vol. 3, no. 1, pp. 22–29, 2025.
- [12] H. N. Teixeira, I. Lopes, and A. C. Braga, "Condition-based maintenance implementation: a literature review," *Procedia Manuf.*, vol. 51, pp. 228–235, 2020, <https://doi.org/10.1016/j.promfg.2020.10.033>
- [13] C. Liu, A. Cichon, G. Królczyk, and Z. Li, "Technology development and commercial applications of industrial fault diagnosis system: a review," *Int. J. Adv. Manuf. Technol.*, vol. 118, no. 11, pp. 3497–3529, 2022.