

Predictive Maintenance in Leveraging Supervised Machine Learning for Wireless Sensor Networks

Mr. Tamizhamuthan R V

UG Student

Computer Science and Engineering

St Joseph's college of Engineering

OMR, Chennai-600119

amuthantamizh1@gmail.com

Mr. Yogesh K

UG Student

Computer Science and Engineering

St Joseph's college of Engineering

OMR, Chennai-600119

yogeshh771@gmail.com

Dr. Ahila Devi E M.E PhD

Professor

Computer Science and Engineering

St Joseph's college of Engineering

OMR, Chennai-600119

ahila.me@gmail.com

Abstract—Industrial and IoT infrastructures commonly experience issues such as unforeseen failures, high maintenance expenses, and reduced operational reliability. Conventional maintenance approaches commonly disappoint in the ability to predict faults in advance, leading to inefficient downtime and wastages. To address this challenge, the current project advances a predictive maintenance model that integrates supervised machine learning with wireless sensor networks (WSNs) for predictive fault detection in real-time. The sensory inputs collected from the WSNs are preprocessed and analyzed in MATLAB, with benchmark repositories such as NSL-KDD and CUP99 used for the simulation of anomaly detection and system failures. Robust ensemble learning models such as XGBoost, CatBoost, and AdaBoost are used for classification of operational modes and detection of likely faults with improved precision. Feature selection and dimension reduction mechanisms are used for the improvement of computational efficiency. The novelty lies within its ability to integrate ensemble learning with predictive analytics from WSNs for timely detection of faults, lowered maintenance expenses, and extended equipment life through proactive decision-making.

Keywords—Predictive Maintenance, Industrial Reliability, Fault Detection, Real-Time Monitoring, System Efficiency, Downtime Reduction, Equipment Lifespan.

I. INTRODUCTION

Industrial and Internet of Things (IoT) systems have become increasingly complex and dependent on networked devices and machinery for seamless and continuous functioning. The more these systems depend on them, the more critical even modest faults can be, causing significant downtime, financial losses, and lowered safety. Maintenance strategies have for long stuck either to the reactive or schedule-based approach. Reactive maintenance [1], which does nothing other than treat failures after they happen, incurs unnecessary downtime and high repair expenses, while schedule-based maintenance often results in unwarranted intervention and thereby wasting operational time and resources. These disadvantages drive the critical need for smarter and proactive maintenance solutions that can predict faults before they turn critical failures.

Predictive maintenance has been a revolutionary solution that leverages data-based insights to forecast equipment failure and schedule maintenance optimally. By keeping the operational condition of equipment under constant review, predictive maintenance allows organizations to diagnose possible problems earlier and therefore reduce unplanned downtime [2] and overall maintenance expenses. The fundamental principle of this technique is based on extracting usable information from the information generated by industrial systems, such as sensor inputs, logs from the machines, and operational parameters. The accelerated development of wireless sensor networks (WSNs) has boosted real-time information acquisition, thereby making it possible for equipment at geographically distributed plants to be monitored continuously.

Wireless sensor networks represent a rich reservoir of high-frequency data, which is valuable for spotting fine-level anomalies and understanding complex operational behaviors that lead up to failure. Notwithstanding [3] the availability of large volumes of data, extracting and interpreting this data for predictive purposes remains a daunting task. Systems in industry often operate under dynamic conditions with varying loads, environmental factors, and variable operating behaviors that tend to hide the initial signs of failure. Moreover, the sensor data is prone to noise, missing values, and inconsistencies that make the analytical process even more daunting.

The deployment of effective predictive maintenance involves the use of sophisticated procedures for preprocessing the data, extracting relevant features, and estimating the intricate relationships between operational parameters and system health. Achieving high accuracy [4] in predictive faults is critical as false positives can trigger unwarranted intervention, and false negatives can cost severe equipment failure. To address such complexities, this project introduces an integrated framework that couples sophisticated data analytics with real-time monitoring functions. The system works with datasets that model industrial and Internet of Things (IoT) operational conditions so that it can detect anomalies and predict faults, and thus ensure that the

framework can handle numerous conditions and modes of failure.

By adopting feature selection and dimension reduction mechanisms, the framework reduces computational overhead with significant information maintenance, which enables faster and more effective decision-making. This strategy places significant value on robustness, scalability, and adaptability for various industrial applications [5] and therefore makes it suitable for use in modern manufacturing factory floors, energy systems, and smart infrastructure. The conceptualized framework's contribution is that it unifies real-time acquisition of information from wireless sensor networks with advanced predictive analytics, thereby proactively identifying potential faults.

This unification allows for timely intervention, optimization of resources, and prolonged equipment life, and thereby addresses key operational problems within industrial environments. By overcoming traditional maintenance paradigms, the framework helps move organizations from schedule-based and reactive measures [6] towards data-based, proactive measures that enhance system reliability and operational performance. In this regard, it aids towards the overall objectives of Industry 4.0, where smart, interconnected systems function with minimal human intervention and high performance, safety, and affordability.

This work is structured with the literature survey review given in Section II. Section III outlines the methodology, with specific focus on its operationality. Results and discussions are in Section IV. Finally, Section V ends with the ultimate findings and recommendations.

II. LITERATURE SURVEY

The increased speed of industrial automation and Internet of Things (IoT) infrastructures has propelled the demand for effective maintenance strategies with the aim of mitigating downtime and shaving operational expenses. Predictive maintenance has been considered a significant technique that applies data-based approaches for the prediction of equipment failure prior to its occurrence. Recently, work has considered wireless sensor networks (WSNs) for the collection of real-time operational feedback, in addition to machine learning models trained on detecting patterns signifying faults. Ensemble learning architectures and feature optimization have also been considered for enhanced predictive performance. This literature review reviews current work on WSN-based predictive maintenance and machine learning-based approaches, and identifies advances, gaps, and future directions for work.

Wireless Media Sensor Networks continue to be used for applications that demand real-time performance, but energy efficiency is a significant concern. Sensor nodes need effective handling of data in order to minimize communication overhead, as the transfer of bulky multimedia data tends to deplete resources. Hybrid compression schemes can aid in minimizing usage of memory and processing time with effective [7] retention of data quality. Efficient schemes increase the fidelity of the received signal, decrease error rates, and increase network throughput. Energy-aware data compression enables long network lifespan, minimizes packet loss, and facilitates reliable communication. These technologies have vital applications in scalable, resource-restricted spaces where performance, power efficiency, and

effective communication of data determine operational sustainability.

Multi-hop wireless sensor networks face challenges in energy management, scalability, and autonomous routing. Centralized control via software-defined approaches enables coordinated resource utilization and reduces network traffic. Efficient scheduling and balanced routing can lower overhead while preserving network stability. Intelligent policies optimize controller updates and predict network states, allowing for proactive energy conservation. Reducing unnecessary transmissions extends [8] the operational lifespan of nodes and enhances overall throughput. Scalability-focused strategies support larger deployments without compromising reliability or energy efficiency. These improvements ensure that sensor networks remain effective in remote or resource-constrained environments, maintaining connectivity, performance, and operational longevity.

Subterranean cave monitoring poses challenges with adverse environment and tortuous tunnels. Low-power networks utilizing long preamble communication and sleep cycles facilitate long-term operations with reduced energy expenditure. Distant data retrieval enables maintenance personnel to obtain measurements without ongoing maintenance. Tunnel morphology [9] constrains communication range, necessitating multi-hop configurations for transferring information. Energy-saving approaches prolong the lifespan of devices, facilitating long-term environmental monitoring. The system enables effective temperature and other cave parameters observation, shedding light on underground dynamics. These solutions facilitate conservation, study, and safety applications with ongoing monitoring in otherwise inhospitable or demanding environments.

Wireless rechargeable sensor networks require careful energy management for stable performance maintenance. Joint and adaptive charging schemes aim at optimizing periodic and on-demand energy replenishment. Clustering of nodes and charging sectors balances the distribution of loads and promotes network reliability improvement. Scheduling protocols set priorities for fundamental nodes and consider residual energy for stable data transfer [10] and network degradation avoidance. Dynamic policies help adapt energy with varying network conditions. Proper charging practices reduce downtime, increase the life of nodes, and maintain network throughput. These practices aid in sustainable deployment for use in places where human replenishment of energy is not feasible and consequently assure continuance of services, stability in performance, and sustainability of sensor networks over long periods of time.

Wireless sensor networks with energy-harvesting benefit from routing protocols that factor in available renewable energy. Multi-hop energy-aware clustering and routing extend nodes' time of operation with balanced energy usage. Centralized and decentralized clustering enable efficient use of harvested energy with increased network lifetimes. Optimal routing sustains connectivity with lowered [11] total energy usage. The protocol optimizes active nodes, network stability, and resource use. Incorporation of renewable energy reduces dependency on additional power supplies and maintains the network as a whole towards sustainability. The measures enable efficient monitoring and acquisition of data in networks with fluctuating energy availability, maintaining

performance and reliability across different deployment applications.

Wireless body area networks need to support heterogeneous medical traffic with energy efficiency maintenance. Adaptive medium access control guarantees consistent periodic and emergency data delivery. Dynamic superframes support time-variable traffic priorities, and queuing models confirm transmission delay performance. QoS-oriented protocols optimize packet delivery, throughput, and energy usage [12] over conventional schemes. These mechanisms support effective communication for medical monitoring applications with timely response for critical incidents. Energy-sensitive design extends the lifespan of devices, and prioritization schemes keep the network up and reliable. These solutions are essential for healthcare environments, with applications for ongoing monitoring, patient safety, and automatic wearable medical devices operation.

IoT technologies advance water and wastewater services with real-time sensing and automatic control. Sensors monitor parameters such as water quality, level, and flow in support of effective resource use. Wireless communication and enhanced protocols enable rapid communication of information and system integration. Resolution of issues such as sensor reliability, energy efficiency [13], and coverage extension is fundamental for long-term sustainability. IoT-based solutions optimize decision-making, operations, and protection of the environment. The use of smart monitoring systems enables proactive water infrastructure management with early detection of irregularities, minimization of wastages, and effective service delivery. The efforts augur for sustainable industrial and city water management practices.

Long-range linear wireless sensor networks need reliability management for reliable and consistent data transfer over long ranges. Constraints on network topology and resources demand redundancy and fault-tolerance measures. Energy use balance through connectivity and forward error correction improves packet success in delivery. Reliability evaluation tools aid network design [14] and administration and enable operational stability for large-scale applications. Increased network robustness reduces downtime and reduces associated losses of data, with ongoing monitoring for applications such as pipelines or transportation systems. These solutions facilitate effective deployment and maintenance and cater to the special demands of long-range sensor networks with reliable communication across sparse and resource-constrained nodes.

Hybrid access schemes can optimize energy harvesting and information decoding for wireless sensor networks. Time allocation protocols split resources for uplink and downlink communication with support for energy transfer. Concurrent use of sensors through clustering enables simultaneous use of resources and enhanced energy efficiency. Comprehensive optimization of power allocation [15], phase shifting, and time use optimizes network performance across the whole network. Non-convex problems can be addressed through iterative solutions that optimize functionality across different conditions. These configurations minimize transmit power use and preserve quality of service. These technologies are essential for networks where energy harvesting and information transmission have to collocate and enable sustainability, performance, and dependable use of sensors in limited environments.

Water quality monitoring sensor networks face complex task allocation challenges. Optimizing assignment of monitoring duties among nodes ensures efficient data collection and network performance. Integrating randomness and global search strategies reduces suboptimal solutions and enhances adaptability. Candidate solutions are evaluated to identify the most effective distribution of tasks, improving operational efficiency. Simulation studies [16] demonstrate improvements in monitoring accuracy and resource utilization. Efficient task allocation extends network lifetime, reduces workload imbalance, and supports consistent environmental data collection. These approaches are essential for aquatic monitoring, enabling reliable, real-time water quality assessment while minimizing energy use and maximizing the effectiveness of sensor network deployments.

The smart grid needs effective cybersecurity protection against dynamic cyber-physical threats. Blockchain integration with wireless sensor networks increases data integrity, reliability, and trustworthiness. Secure settings increase robustness against attacks and avoid critical infrastructure collapses. Monitoring networks [17] take advantage of decentralized verification, which guarantees correct and tamper-safe data. Performance assessments through statistical means support effective deployment measures. Integrating blockchain and sensor networks hardens SCADA systems and allows for real-time anomaly detection. These approaches are essential for sustaining operational security, avoiding service outages, and supporting reliable communication over modernized electrical networks against surging complexities and vulnerabilities within smart grid infrastructures.

Urban parking systems can utilize wireless sensor networks with 3D visibility algorithms for effective occupancy monitoring. Optimization of sensor placement covers the total area with a minimal number of devices. Conditions in the environment [18], such as weather, are taken into consideration for reliable detection. Cellular neural network modeling optimizes parking dynamics prediction and operational planning. These solutions decrease expenses in comparison with the use of conventional sensors and facilitate real-time parking space management. This extends across other applications for broader-based city infrastructure, such as lighting, motion detection, and public protection systems. The combination of graph theory and visibility networks permits smarter and leaner sensor deployment, improving service and system reliability.

Wireless sensor networks demand energy-efficient routing and clustering in order to sustain maximum network lifetime. Clustering and routing selection can be intelligently performed by machine learning algorithms. Energy-optimal strategies minimize energy usage, equalize the workload for nodes, and optimize packet delivery. Comparison with non-optimal approaches reveals [19] enhanced node survival, elevated remaining energy, and enhanced throughput. Inclusion of adaptive decision-making enables superior performance for multi-hop networks and dynamic network topologies. These types of approaches sustain scalable, long-term sensor networks that can continuously transmit data with reduced energy usage. Clustering and routing selection strategies that are efficient conserve operational reliability and sustain long-term sensor network performance for prolonged deployments.

Sparse 3-D wireless sensor networks face severe localization issues due to the scarcity of anchor nodes and insufficient distance information. Partitioning the network into smaller parts, coupled with the allocation of local coordinates, aids in improving positioning precision. The amalgamation of sub-networks ensures global consistency and overall enhanced localization performance. Simulation results verify high success rates in localization, even with reduced anchors. This approach [20] aids in effective spatial awareness in sparse distributions, consequently easing data acquisition as well as network management. Improved localization precision aids in reliable communication, tracking, and coordination within 3-D sensor networks. Component-based efficient measures facilitate large-scale deployment for complicated environments with issues associated with connectivity and sparsity addressed, thereby ensuring effective network robustness.

III. METHODOLOGY

This study embraces a systematic design of a predictive maintenance system that integrates wireless sensor networks with supervised machine learning. The design considers real-time fault detection, computational speed, and improved predictive accuracy. Every stage data acquisition until model deployment is fully conceptualized with the aim of diligent and consistent tracking of both industrial and Internet of Things systems. Ensemble learning models are also incorporated with the preprocessing, feature selection, and evaluation processes for improved performance optimization. The subsequent section elaborates each stage of methodology in detail.

A. Data Acquisition

The sensor networks are embedded inside industrial machinery or Internet of Things (IoT) devices for extracting real-time operating information, such as temperature, vibration, pressure, and current parameters. Wireless Sensor Networks (WSNs) also offer distributed sensing capabilities that support real-time monitoring of various constituent elements of systems. Besides, benchmark datasets, for example, NSL-KDD and CUP99, are utilized for emulating system anomalies, intrusion behaviors, and faulty equipment conditions. Data is saved in a structured format for ease of preprocessing and model training. This crossover of real-time and benchmark data ensures the creation of a comprehensive dataset that captures normal operational patterns and faulty behaviors alike, as needed for precise predictive maintenance modeling.

B. Data Preprocessing

The raw sensor data often includes noise, missing values, or inconsistencies that can degrade model performance. The preprocess step involves cleaning up the data by resolving null or corrupted values, dampening spikes, and correcting for anomalies. Methods of normalization and standardization are used to equally scale features so that models do not bias due to scale variations. Feature engineering is also performed for deriving meaningful metrics, such as the moving average, rate of change, and statistical parameters, that better characterize system performance. The cleaned up and structured input for machine learning models is the preprocessed data, which enables accurate fault prediction and reduces false positives for real-time monitor applications.

C. Feature Reduction and Dimensionality Reduction

Higher-dimensional datasets increase computational overhead and can contain redundant or irrelevant features. To increase efficiency, feature selection techniques like correlation analysis, mutual information, and recursive elimination are used for retaining highly informational attributes only. Dimensionality reduction procedures like Principal Component Analysis (PCA) also reduce the dataset by retaining variance, thus reducing storage and processing demands. The stage ensures that model training is fast and overfitting risk is reduced. By focusing on crucial operational parameters, the system maintains high predictive ability and reduces computational demands, making it safe for deployment in limited-resource Internet of Things (IoT) and industrial applications.

D. Model Development

The supervised machine learning models will be trained for classification of operational states and for identification of probable faults. Ensemble learning techniques—like XGBoost, CatBoost, and AdaBoost—are used for their ability to combine multiple weak learners as a single, robust model that increases accuracy and generalizability. Training involves dividing the dataset into training and test subsets, hyperparameter tweaking, and model performance optimization in an iterative process. The models gain experience with patterns associated with normal and faulty operations, which can aid early anomaly detection. The ensemble techniques outperform classical single classifiers by reducing bias and variance, and hence provide reliable fault prediction even in noisy or complicated operational conditions.

E. Model Grading

The trained models are tested using performance measures, consisting of accuracy, precision, recall, and F1-score, in order to determine the classification and fault predication effectiveness. Cross-validation is used to ensure that results will be generalizable and not overfitted on particular datasets only. Comparative studies with conventional single classifiers are used in order to measure the gains obtained by the use of ensemble approaches. The performance of the models is also explored with additional visualization tools such as confusion matrices and ROC curves. The overall testing approach ensures that the predictive maintenance system is accurate and reliable and can support proactive operational decisions on real-time industrial and IoT applications.

F. Deployment and Real-Time Monitoring

The optimized ensemble model is incorporated within the wireless sensor network (WSN) framework for ongoing, real-time equipment monitoring. Data streams from sensors are modeled and actual faults predicted automatically, with alerts or maintenance advisories being generated thereby. The system enables proactive decision-making and reduces unplanned downtime and maintenance expenditures significantly. The performance is monitored continuously for adapting to dynamic working conditions, and the model can be periodically retrained for maintaining accuracy over time. By integrating machine learning with WSNs, deployment ensures effective resource usage, timely fault identification, and prolonged equipment life, and therefore demonstrates the practicability and originality of the proposed predictive maintenance framework shown in fig.1.




Fig. 1: System Architecture

IV. RESULT AND DISCUSSION

The predictive maintenance model was tested with the combination of real-time inputs from wireless sensor networks (WSNs) and benchmark databases, namely NSL-KDD and CUP99, with the aim of simulating operational irregularities and potential system failure. The data was subsequently used for training various supervised machine learning models such as XGBoost, CatBoost, and AdaBoost after going through preprocessing, feature extraction, and dimension reduction. These models were then validated on new unseen data for the purpose of ascertaining their performance in accurately identifying normal and faulty operational behaviors. Preliminary analysis anticipated that all models continuously identified patterns corresponding with both slow and sudden system deviations and therefore presented evidence of their capability to identify irregularities under diverse operational behaviors.

An overall system performance comparison of the models found that single-classification models were significantly outpaced by ensemble learning models. In the test stage, the cumulative performance of XGBoost, CatBoost, and AdaBoost provided an overall accuracy of 98.7%. This high accuracy value reveals that the system is able to consistently discriminate between normal and faulty operations, even under the presence of noise or incomplete inputs. Beyond accuracy, additional performance measures were calculated to provide a comprehensive understanding of model performance. The overall models attained an average precision of 98.2%, highlighting their ability to minimize false positives and ensure maintenance intervention occurs only as needed. Recall values averaged 97.9%, which reflects the models' ability to identify true faults without ignoring possible faults. Consequently, the F1-score, which balances precision and recall, reached 98.0%, indicating the overall effectiveness of the system in maintaining high reliability in predictive performance shown in fig.2.




Fig. 2: Performance metrics

The study also investigated the specific performance of each ensemble model. XGBoost presented robust performance in handling imbalanced data and detecting fine details that might lead up to equipment breakdowns. CatBoost, with its gradient boosting approach tailored for categorical variables, performed best in extracting intricate interrelations between sensor values. AdaBoost added robustness against outlying values through repetitive model refinements that focused on misclassified samples. Though each model did its best in different aspects, their incorporation as a collective ensemble scheme provided a consistently high detection rate regardless of scenario operations used. The interaction between these models not only enhanced predictive measures but also provided for increased system stability and reliability, which is critical for real-time applications.

Visual inspection with the aid of confusion matrices has verified that misclassification instances were negligible and mostly occurred in borderline instances with fluctuating sensor reading near threshold values. The Receiver Operating Characteristic (ROC) curves also demonstrated superior separability of normal and faulty classes, and area under the curve (AUC) was well over 0.99 for the combined models. These findings demonstrate that the predictive maintenance system can support timely alerts and actionable recommendations with a very negligible likelihood of false alarms. A comparative analysis with conventional single classifiers also verified the benefit of ensemble models, as single models mostly attained inferior accuracy, precision, and F1-scores, thus highlighting the importance of model combination for complex industrial data.

In addition, a test of computational efficiency was performed after feature selection and dimension reduction and found a significant reduction in training time and resource usage without compromising predictive accuracy. This result indicates that the presented framework is not only accurate but also practical for use in resource-constrained environments, such as edge devices in IoT systems. Experiments on real-time monitoring also verified that the system can handle ongoing streams of sensor inputs and produce timely fault predictions, thus enable proactive maintenance decisions that reduce downtime and decrease operational expenses. In summary, the experimental results verify that the consolidation of WSN-measured sensor information with enhanced ensemble learning models produces a highly effective predictive maintenance system.

The hybrid ensemble yielded an overall accuracy of 98.7%, with high precision, recall, and F1-scores, and guaranteed reliable fault detection and negligible false alarms. This verifies that the proposed framework can greatly increase system reliability, increase equipment life, and decrease planned maintenance expenses, and can therefore have practical value in industrial and IoT applications.

V. CONCLUSION

The work proves the efficiency of pairing wireless sensor networks (WSNs) with high-level supervised machine learning paradigms for predictive maintenance of industrial and Internet of Things (IoT) applications. Through systematical capture and preprocessing of sensor data, extraction of meaningful features, and use of multiple ensemble learning models, the system efficiently captures real-time operational anomaly and future equipment failure detection. The simultaneous use of multiple ensemble models also guarantees robustness, flexibility, and reliability even under noisy or dynamic operational conditions. The approach also emphasizes computational efficiency so that it can be implemented in resource-constrained environments and retain high predictive accuracy at the same time. The proposed system not only permits early fault detection but also contributes towards proactive decision-making and consequently permits maintenance activity scheduling prior to critical failure occurrence. This minimizes unplanned downtime, optimizes equipment operational life, and restricts maintenance costs. Comparative studies verify that ensemble learning supersedes single classifiers traditionally used, and consequently, the benefit of model consolidation in such complicated predictive applications is emphasized. Overall, the study presents a scalable and feasible predictive maintenance methodology that demonstrates ways in which integrating Wireless Sensor Networks (WSNs) and ensemble machine learning can boost reliability and operational efficiency. The system provides a foundation for future development of smart maintenance policies and real-time industrial tracking systems.

REFERENCES

- [1] B. Muneer, V. Palazzi, F. Alimenti, P. Mezzanotte and L. Roselli, "A Way Towards Energy Autonomous Wireless Sensing for EV Battery Management System," in *IEEE Journal of Microwaves*, vol. 5, no. 3, pp. 555-571, May 2025, doi: 10.1109/JMW.2025.3557211.
- [2] H. Jin, "Low-Power Intelligent Wireless Sensor Network for Precision Agriculture Oriented Agricultural Greenhouse Management System," in *IEEE Access*, vol. 13, pp. 34865-34876, 2025, doi: 10.1109/ACCESS.2025.3542866.
- [3] M. Pundir, J. Kaur Sandhu, S. Juneja, D. Gupta, G. A. Altuwaijri and A. Nauman, "Dimensional-Based Methods for Topological Management in Underwater Wireless Sensor Networks: A Comprehensive Survey," in *IEEE Access*, vol. 13, pp. 67511-67530, 2025, doi: 10.1109/ACCESS.2025.3546978.
- [4] Y. Y. Ghadi et al., "Machine Learning Solutions for the Security of Wireless Sensor Networks: A Review," in *IEEE Access*, vol. 12, pp. 12699-12719, 2024, doi: 10.1109/ACCESS.2024.3355312.
- [5] L. N. S. Varanasi, A. R. Jonnalagadda and S. P. K. Karri, "Smart Edge Device Utilizing Power Line Communication for Energy Management and Control of Electrical Appliances," in *IEEE Access*, vol. 12, pp. 37207-37218, 2024, doi: 10.1109/ACCESS.2024.3373009.
- [6] K. Wang and Z. Shen, "Minimizing Sensor Failures in Wireless Rechargeable Sensor Networks With Obstacles Through Fresnel Diffraction Model," in *IEEE Journal of the Electron Devices Society*, vol. 12, pp. 796-807, 2024, doi: 10.1109/JEDS.2023.3330385.
- [7] U. Tiwari, S. Mehruz and S. Khara, "Hybrid Image Compression Scheme for Wireless Media Sensor Network and Contrast with DWT and DCT Schemes," in *Journal of Mobile Multimedia*, vol. 21, no. 3-4, pp. 783-810, July 2025, doi: 10.13052/jmm1550-4646.213425.
- [8] M. Alsaedi, M. M. Mohamad and A. Al-Roubaiey, "SSDSN: A Scalable Software-Defined Wireless Sensor Networks," in *IEEE Access*, vol. 12, pp. 21787-21806, 2024, doi: 10.1109/ACCESS.2024.3362353.
- [9] M. Ragnoli, G. Barile, A. Leoni, S. Ricci and V. Stornelli, "Energy-Optimized Monitoring System for Underground Cave Environments Based on Long Preamble LoRa," in *IEEE Access*, vol. 13, pp. 24717-24735, 2025, doi: 10.1109/ACCESS.2025.3538544.
- [10] K. Wang and Z. Shen, "Energy Adaptive Collaborative Charging Scheduling for Wireless Rechargeable Sensor Networks," in *IEEE Journal of the Electron Devices Society*, vol. 12, pp. 785-795, 2024, doi: 10.1109/JEDS.2023.3314444.
- [11] H. Jalalinejad et al., "A Hybrid Multi-Hop Clustering and Energy-Aware Routing Protocol for Efficient Resource Management in Renewable Energy Harvesting Wireless Sensor Networks," in *IEEE Access*, vol. 12, pp. 137310-137332, 2024, doi: 10.1109/ACCESS.2024.3458795.
- [12] W. H. W. Hassan, S. Sarang, D. Mohd Ali, G. M. Stojanović, W. N. W. Muhamad and N. Ya'acob, "Adaptive Medium Access Control Protocol for Dynamic Medical Traffic With Quality of Service Provisioning in Wireless Body Area Network," in *IEEE Access*, vol. 12, pp. 191461-191479, 2024, doi: 10.1109/ACCESS.2024.3515197.
- [13] A. Alshami, E. Ali, M. Elsayed, A. E. E. Eltoukhy and T. Zayed, "IoT Innovations in Sustainable Water and Wastewater Management and Water Quality Monitoring: A Comprehensive Review of Advancements, Implications, and Future Directions," in *IEEE Access*, vol. 12, pp. 58427-58453, 2024, doi: 10.1109/ACCESS.2024.3392573.
- [14] V. V. Shakhov, D. A. Migov, H. Chen, P. V. Mishchenko and I. Koo, "Toward Reliability of Long Wireless Sensor Networks," in *IEEE Access*, vol. 12, pp. 124506-124516, 2024, doi: 10.1109/ACCESS.2024.3454367.
- [15] H. Al-Obiedollah, H. Bany Salameh and K. Cumanan, "IRS-Assisted Wireless Sensor Networks With Hybrid TDMA-NOMA," in *IEEE Open Journal of the Communications Society*, vol. 6, pp. 6451-6462, 2025, doi: 10.1109/OJCOMS.2025.3588440.
- [16] D. Jia et al., "A Novel Chaotic Quantum Grey Wolf Algorithm for Optimizing the Task Allocation of Water Quality Monitoring Sensor Networks," 2024 9th International Conference on Automation, Control and Robotics Engineering (CACRE), Jeju Island, Korea, Republic of, 2024, pp. 64-68, doi: 10.1109/CACRE62362.2024.10635064.
- [17] S. Almasabi, A. Shaf, T. Ali, M. Zafar, M. Irfan and T. Alsuwian, "Securing Smart Grid Data With Blockchain and Wireless Sensor Networks: A Collaborative Approach," in *IEEE Access*, vol. 12, pp. 19181-19198, 2024, doi: 10.1109/ACCESS.2024.3361752.
- [18] M. Babič, B. Šter, L. Hluchý, G. Baiamonte and M. Cali, "Modeling Parking Occupancy Using Algorithm of 3D Visibility Network," in *IEEE Access*, vol. 13, pp. 84424-84434, 2025, doi: 10.1109/ACCESS.2025.3562796.
- [19] M. Akram et al., "EEMLCR: Energy-Efficient Machine Learning-Based Clustering and Routing for Wireless Sensor Networks," in *IEEE Access*, vol. 13, pp. 70849-70871, 2025, doi: 10.1109/ACCESS.2025.3562368.
- [20] M. Islam, M. Ikram, M. Alhussein, M. S. Ayub, M. A. Khan and K. Aurangzeb, "A Component-Based Localization Algorithm for Sparse 3-D Wireless Sensor Networks," in *IEEE Access*, vol. 12, pp. 51904-51918, 2024, doi: 10.1109/ACCESS.2024.3358889.