



# Comparing and parcellating voxel-scale multimodal human brain connectivity

Christopher Baldassano<sup>1</sup>, Andre Esteva<sup>1</sup>, Diane M. Beck<sup>2</sup>, Li Fei-Fei<sup>1</sup>



<sup>1</sup>Department of Computer Science, Stanford University

<sup>2</sup>Psychology Department and Beckman Institute, University of Illinois Urbana-Champaign

## Summary


- ▶ How is the cortex functionally and structurally organized?
  - ▷ Examine with voxel-level resting-state and tractography connectivity matrices (60,000 by 60,000)
- ▶ **Goal 1:** Parcellate cortex based on connectivity
  - ▷ Use generative model to select best clustering of functional connectivity matrix
  - ▷ Reveals regions related to fine-grain topographic map structure in visual cortex
- ▶ **Goal 2:** Characterize the properties of each parcel
  - ▷ Distributed functional and structural connectivity networks
  - ▷ Functional task and category selectivity

## Data Sources


- ▶ Human Connectome Project
  - ▷ Resting-state fMRI - 468 subjects (2mm, 0.72s)
  - ▷ Diffusion Tractography - 10 subjects (1.25mm)
    - ▷ Sampled 33 billion tracts using FSL
  - ▷ Task fMRI - 20 subjects (2mm, 0.72s)
- ▶ Category Localizers (24 subjects)
- ▶ Probabilistic field map atlas

## Probabilistic Parcellation Model


- ▶ Produces spatially-contiguous “supervoxels”
- ▶ Refines clustering with multiple passes
- ▶ Uses data statistics to help set number of clusters



- ▶ Captures more variance than greedy Ward clustering



## Parcel Properties



- ▶ Early eccentricity parcels, ventral field map parcels
- ▶ Default network comprised of  $\geq 2$  subnetworks
- ▶ PPA bridges retinotopic cluster and posterior default network
- ▶ Functional connectivity in dorsal angular gyrus and inferior temporal sulcus strongly driven by structural connectivity

## Acknowledgments

Thanks to Mike Arcaro, NSF GRFP (DGE-0645962), WU-Minn Human Connectome Project (1U54MH091657)