

Universality of unambiguous register automata

Corentin Barloy - University of Lille
Joint work with Lorenzo Clemente - MIMUW (Warsaw)

STACS 2021


1 Unambiguous register automata

2 Solving the universality problem

Unambiguous register automata


A first (deterministic) register automaton

x is a register that stores values from \mathbb{N}




A first (deterministic) register automaton

x is a register that stores values from \mathbb{N}




A first (deterministic) register automaton

x is a register that stores values from \mathbb{N}




A first (deterministic) register automaton

x is a register that stores values from \mathbb{N}




A first (deterministic) register automaton

x is a register that stores values from \mathbb{N}




A first (deterministic) register automaton

x is a register that stores values from \mathbb{N}




A first (deterministic) register automaton

x is a register that stores values from \mathbb{N}



A second (non-deterministic) one




A third (unambiguous) one

Unambiguity: there is a most one accepting run for each word.

A third (unambiguous) one

Unambiguity: there is a most one accepting run for each word.



Decision problems

The universality problem asks whether a given unambiguous register automaton accepts every word.

Decision problems

The universality problem asks whether a given unambiguous register automaton accepts every word.

Inclusion \iff Equivalence \iff Universality

Decision problems

The universality problem asks whether a given unambiguous register automaton accepts every word.

Inclusion \iff Equivalence \iff Universality

This is quite surprising: for DCFG, Universality is decidable but not Inclusion!

Main result

Theorem [Mottet, Quaas STACS'19]

The universality problem for unambiguous register automata is decidable in 2EXP-SPACE .

Main result

Theorem [Mottet, Quaas STACS'19]

The universality problem for unambiguous register automata is decidable in 2EXP-SPACE .

Theorem [B, Clemente]

The universality problem for unambiguous register automata is decidable in 2EXP-TIME .

Main result

Theorem [Mottet, Quaas STACS'19]

The universality problem for unambiguous register automata is decidable in 2EXP-SPACE.

Theorem [B, Clemente]

The universality problem for unambiguous register automata is decidable in 2EXP-TIME.

Theorem [Bojańczyk, Klin, Moerman]

The universality problem for unambiguous register automata **with guessing**, and over equality or **order**, is decidable in **EXP-TIME**.

Main result

Theorem [Mottet, Quaas STACS'19]

The universality problem for unambiguous register automata is decidable in 2EXP-SPACE .

Theorem [B, Clemente]

The universality problem for unambiguous register automata is decidable in 2EXP-TIME .

Theorem [Bojańczyk, Klin, Moerman]

The universality problem for unambiguous register automata **with guessing**, and over equality or **order**, is decidable in **EXP-TIME**.

- Undecidable in general.

Main result

Theorem [Mottet, Quaas STACS'19]

The universality problem for unambiguous register automata is decidable in 2EXP-SPACE .

Theorem [B, Clemente]

The universality problem for unambiguous register automata is decidable in 2EXP-TIME .

Theorem [Bojańczyk, Klin, Moerman]

The universality problem for unambiguous register automata **with guessing**, and over equality or **order**, is decidable in **EXP-TIME**.

- Undecidable in general.
- Extend Schutzenberger counting approach.

Main result

Theorem [Mottet, Quaas STACS'19]

The universality problem for unambiguous register automata is decidable in 2EXP-SPACE .

Theorem [B, Clemente]

The universality problem for unambiguous register automata is decidable in 2EXP-TIME .

Theorem [Bojańczyk, Klin, Moerman]

The universality problem for unambiguous register automata **with guessing**, and over equality or **order**, is decidable in **EXP-TIME**.

- Undecidable in general.
- Extend Schutzenberger counting approach.
- There is hope for generalisations to other data domains.

Solving the universality problem

For k fixed, \mathbb{N}^k is infinite.

For k fixed, \mathbb{N}^k is infinite.

Let φ be a bijection of \mathbb{N} . The orbit of a word u is the set:

$$o(u) = \{v \mid \exists \varphi \text{ such that } \varphi(u) = v\} \text{ .}$$

For k fixed, \mathbb{N}^k is infinite.

Let φ be a bijection of \mathbb{N} . The orbit of a word u is the set:

$$o(u) = \{v \mid \exists \varphi \text{ such that } \varphi(u) = v\} \text{ .}$$

\mathbb{N}^k has B_k many orbits; where B_k is the k^{th} Bell number.

Ryll-Nardzewski function

$s \in \text{control locations} \times \text{orbit of register values}$

Ryll-Nardzewski function

$s \in \text{control locations} \times \text{orbit of register values}$

$$F_s(\quad) = |\{o(r) \mid r \text{ is a run ending in } s\}|.$$

Ryll-Nardzewski function

$s \in \text{control locations} \times \text{orbit of register values}$

$$F_s(n, \cdot) = |\{o(r) \mid r \text{ is a run ending in } s, \text{ of length } n\}|.$$

Ryll-Nardzewski function


$s \in \text{control locations} \times \text{orbit of register values}$

$F_s(n, k) = |\{o(r) \mid r \text{ is a run ending in } s, \text{ of length } n \text{ and over } k \text{ distinct letters}\}|$.

Ryll-Nardzewski function

$s \in \text{control locations} \times \text{orbit of register values}$


$F_s(n, k) = |\{o(r) \mid r \text{ is a run ending in } s, \text{ of length } n \text{ and over } k \text{ distinct letters}\}|$.



$$F(n+1, k+1) = F(n, k) + (k+1) \cdot F(n, k+1)$$

(Stirling numbers of the second kind)

Counting orbits



n = length of the word, k = number of distinct data values

$$\begin{cases} f_{\bullet}(n+1, k+1) = 0 \\ f_{\bullet}(n+1, k+1) = f_{\bullet}(n, k) + (k+1) \cdot f_{\bullet}(n, k+1) + f_{\bullet}(n, k) + k \cdot f_{\bullet}(n, k+1) \\ f_{\bullet}(n+1, k+1) = f_{\bullet}(n, k) + (k+1) \cdot f_{\bullet}(n, k+1) + f_{\bullet}(n, k+1) \\ f_{\bullet}(n+1, k+1) = f_{\bullet}(n, k+1) + f_{\bullet}(n, k) + k \cdot f_{\bullet}(n, k+1) \end{cases}$$

Zeroneess problem

Universality of register automata reduces to the zeroness problem of linrec sequences:

Given a linrec system, is it the case that the function defined is zero everywhere?

Zeroneess problem

Universality of register automata reduces to the zeroness problem of linrec sequences:

Given a linrec system, is it the case that the function defined is zero everywhere?

- Compute the number $S(n, k)$ of orbits of all words of length n and width k .

$$S(n + 1, k + 1) = (k + 1) \cdot S(n, k + 1) + S(n, k)$$

Zeroneess problem

Universality of register automata reduces to the zeroness problem of linrec sequences:

Given a linrec system, is it the case that the function defined is zero everywhere?

- Compute the number $S(n, k)$ of orbits of all words of length n and width k .

$$S(n + 1, k + 1) = (k + 1) \cdot S(n, k + 1) + S(n, k)$$

- \mathcal{A} universal \Leftrightarrow

$$\forall n, k, f_{\bullet}(n, k) = S(n, k) \Leftrightarrow \forall n, k, f_{\bullet}(n, k) - S(n, k) = 0$$

Zeroneess problem

Universality of register automata reduces to the zeroness problem of linrec sequences:

Given a linrec system, is it the case that the function defined is zero everywhere?

- Compute the number $S(n, k)$ of orbits of all words of length n and width k .

$$S(n + 1, k + 1) = (k + 1) \cdot S(n, k + 1) + S(n, k)$$

- \mathcal{A} universal \Leftrightarrow
 $\forall n, k, f_{\bullet}(n, k) = S(n, k) \Leftrightarrow \forall n, k, f_{\bullet}(n, k) - S(n, k) = 0$
- Linrec is closed by substraction.

$$f(n+1, k+1) - f(n+1, k) - f(n, k) - (k+1) \cdot f(n, k+1) = 0$$

↓

$$\partial_1 \partial_2 \cdot f - \partial_1 \cdot f - f - (k+1) \partial_2 \cdot f = 0$$

↓

$$(\partial_1 \partial_2 - \partial_1 - (k+1) \partial_2 - 1) \cdot f = 0$$

Modelling linrec

$$f(n+1, k+1) - f(n+1, k) - f(n, k) - (k+1) \cdot f(n, k+1) = 0$$

↓

$$\partial_1 \partial_2 \cdot f - \partial_1 \cdot f - f - (k+1) \partial_2 \cdot f = 0$$

↓

$$\underbrace{(\partial_1 \partial_2 - \partial_1 - (k+1) \partial_2 - 1)}_{\text{An example of Ore polynomial}} \cdot f = 0$$

An example of Ore polynomial

Modelling linrec

$$f(n+1, k+1) - f(n+1, k) - f(n, k) - (k+1) \cdot f(n, k+1) = 0$$

↓

$$\partial_1 \partial_2 \cdot f - \partial_1 \cdot f - f - (k+1) \partial_2 \cdot f = 0$$

↓

$$(\partial_1 \partial_2 - \partial_1 - (k+1) \partial_2 - 1) \cdot f = 0$$

An example of Ore polynomial

Note that those operators do not commute:

$$\partial_1 p(n, k) = p(n+1, k) \partial_1 \neq p(n, k) \partial_1 .$$

Modelling linrec

A system of equations with variables f_i , S and g , with coefficients that are operators.

$$\left\{ \begin{array}{llll} (\partial_1 \partial_2) \cdot f_{\bullet} & & & = 0 \\ -\partial_2 \cdot f_{\bullet} & + (\partial_1 \partial_2 - (k+1)\partial_2 - 1) \cdot f_{\bullet} & & = 0 \\ -\partial_2 \cdot f_{\bullet} & & + (\partial_1 \partial_2 - \partial_2) \cdot f_{\bullet} & = 0 \\ & -\partial_2 \cdot f_{\bullet} & + (-(k-1)\partial_2 - 1) \cdot f_{\bullet} & + (\partial_1 \partial_2) \cdot f_{\bullet} = 0 \\ & (\partial_1 \partial_2 - (k+1)\partial_2 - 1) \cdot S & & = 0 \\ & g - S + f_{\bullet} & & = 0 \end{array} \right.$$

Modelling linrec

A system of equations with variables f_i , S and g , with coefficients that are operators.

$$\left\{ \begin{array}{lcl} (\partial_1 \partial_2) \cdot f_{\bullet} & & = 0 \\ -\partial_2 \cdot f_{\bullet} & + (\partial_1 \partial_2 - (k+1)\partial_2 - 1) \cdot f_{\bullet} & = 0 \\ -\partial_2 \cdot f_{\bullet} & & + (\partial_1 \partial_2 - \partial_2) \cdot f_{\bullet} & = 0 \\ & -\partial_2 \cdot f_{\bullet} & + (-(k-1)\partial_2 - 1) \cdot f_{\bullet} & + (\partial_1 \partial_2) \cdot f_{\bullet} & = 0 \\ & (\partial_1 \partial_2 - (k+1)\partial_2 - 1) \cdot S & & = 0 \\ & g - S + f_{\bullet} & & = 0 \end{array} \right.$$

Goal: find an operator L such that $L \cdot g = 0$.

Euclidean properties

Let L_1 and L_2 be two operators.

- It is possible to perform an Euclidean division of L_1 by L_2 .
- There exists a common left multiple of L_1 and L_2 . (Trivial for commutative ring!)

Euclidean properties

Let L_1 and L_2 be two operators.

- It is possible to perform an Euclidean division of L_1 by L_2 .
- There exists a common left multiple of L_1 and L_2 . (Trivial for commutative ring!)

With $L_1 = \partial_2 - (k + 1)$ and $L_2 = \partial_2 - 1$:

$$\begin{aligned}\text{CLM}(L_1, L_2) &= (k\partial_2 - (k + 1)) \cdot L_1 \\ &= (k\partial_2 - (k + 1)^2) \cdot L_2 \\ &= k\partial_2^2 - (k^2 + 3k + 1)\partial_2 + (k + 1)^2\end{aligned}$$

The elimination process

$$\left\{ \begin{array}{llll} (\partial_1 \partial_2) \cdot f_{\bullet} & & & = 0 \\ -\partial_2 \cdot f_{\bullet} & + (\partial_1 \partial_2 - (k+1)\partial_2 - 1) \cdot f_{\bullet} & & = 0 \\ -\partial_2 \cdot f_{\bullet} & & + (\partial_1 \partial_2 - \partial_2) \cdot f_{\bullet} & = 0 \\ & -\partial_2 \cdot f_{\bullet} & + (-(k-1)\partial_2 - 1) \cdot f_{\bullet} & + (\partial_1 \partial_2) \cdot f_{\bullet} = 0 \\ & (\partial_1 \partial_2 - (k+1)\partial_2 - 1) \cdot S & & = 0 \\ & g - S + f_{\bullet} & & = 0 \end{array} \right.$$

⇓ multiply lines 2 and 3 by ∂_1

$$\left\{ \begin{array}{llll} (\partial_1 \partial_2) \cdot f_{\bullet} & & & = 0 \\ -\partial_1 \partial_2 \cdot f_{\bullet} & + (\partial_1^2 \partial_2 - (k+1)\partial_1 \partial_2 - \partial_1) \cdot f_{\bullet} & & = 0 \\ -\partial_1 \partial_2 \cdot f_{\bullet} & & + (\partial_1^2 \partial_2 - \partial_1 \partial_2) \cdot f_{\bullet} & = 0 \\ & -\partial_2 \cdot f_{\bullet} & + (-(k-1)\partial_2 - 1) \cdot f_{\bullet} & + (\partial_1 \partial_2) \cdot f_{\bullet} = 0 \\ & (\partial_1 \partial_2 - (k+1)\partial_2 - 1) \cdot S & & = 0 \\ & g - S + f_{\bullet} & & = 0 \end{array} \right.$$

The elimination process

$$\left\{ \begin{array}{llll} (\partial_1^2 \partial_2 - (k+1) \partial_1 \partial_2 - \partial_1) \cdot f_{\bullet} & & & = 0 \\ & + & (\partial_1^2 \partial_2 - \partial_1 \partial_2) \cdot f_{\bullet} & = 0 \\ & - \partial_2 \cdot f_{\bullet} & + & (- (k-1) \partial_2 - 1) \cdot f_{\bullet} + (\partial_1 \partial_2) \cdot f_{\bullet} = 0 \\ & & (\partial_1 \partial_2 - (k+1) \partial_2 - 1) \cdot S & = 0 \\ & & g - S + f_{\bullet} & = 0 \end{array} \right.$$

↑↑ add first line to second and third lines


$$\left\{ \begin{array}{llll} (\partial_1 \partial_2) \cdot f_{\bullet} & & & = 0 \\ - \partial_1 \partial_2 \cdot f_{\bullet} & + (\partial_1^2 \partial_2 - (k+1) \partial_1 \partial_2 - \partial_1) \cdot f_{\bullet} & & = 0 \\ - \partial_1 \partial_2 \cdot f_{\bullet} & & + & (\partial_1^2 \partial_2 - \partial_1 \partial_2) \cdot f_{\bullet} = 0 \\ & - \partial_2 \cdot f_{\bullet} & + & (- (k-1) \partial_2 - 1) \cdot f_{\bullet} + (\partial_1 \partial_2) \cdot f_{\bullet} = 0 \\ & (\partial_1 \partial_2 - (k+1) \partial_2 - 1) \cdot S & & = 0 \\ & g - S + f_{\bullet} & & = 0 \end{array} \right.$$

The elimination process

$$((k^2 - 5k + 6)\partial_1^3\partial_2^3 + (2k + 2)\partial_1^3\partial_2^2 - 2\partial_1^2\partial_2 + \partial_2^2 - (3k + 3)) \cdot g = 0$$


Deciding zeroness of g

$$((k^2 - 5k + 6)\partial_1^3\partial_2^3 + (2k + 2)\partial_1^3\partial_2^2 - 2\partial_1^2\partial_2 + \partial_2^2 - (3k + 3)) \cdot g = 0$$




Deciding zeroness of g

$$((k^2 - 5k + 6)\partial_1^3\partial_2^3 + (2k + 2)\partial_1^3\partial_2^2 - 2\partial_1^2\partial_2 + \partial_2^2 - (3k + 3)) \cdot g = 0$$



Deciding zeroness of g

$$((k^2 - 5k + 6)\partial_1^3\partial_2^3 + (2k + 2)\partial_1^3\partial_2^2 - 2\partial_1^2\partial_2 + \partial_2^2 - (3k + 3)) \cdot g = 0$$



This yields a 4-EXP-SPACE complexity bound for the universality problem!

$$2^{2^{2^n}}$$

This yields a 4-EXP-SPACE complexity bound for the universality problem!

$$2^{2^{2^{2^n}}}$$

- Lagrange bound on zero of polynomials.
- Zeroness of sections (dimension 1).

Hermite forms

Idea: Instead of removing one variable at a time, invert the matrix using (non-commutative) linear algebra.

Hermite forms

Idea: Instead of removing one variable at a time, invert the matrix using (non-commutative) linear algebra.

- Put matrices of operators in a triangular form (Hermite form):

$$\begin{pmatrix} (\partial_1 - 1)\partial_2 & -\partial_2 \\ -k\partial_2 - 1 & \partial_1\partial_2 \end{pmatrix} \Rightarrow \begin{pmatrix} 1 & (\frac{k}{\partial_1 - 1} - \partial_1)\partial_2 \\ 0 & \partial_2^2 - \frac{1}{\partial_1^2 - \partial_1 - (k+1)}\partial_2 \end{pmatrix}$$

Hermite forms

Idea: Instead of removing one variable at a time, invert the matrix using (non-commutative) linear algebra.

- Put matrices of operators in a triangular form (Hermite form):

$$\begin{pmatrix} (\partial_1 - 1)\partial_2 & -\partial_2 \\ -k\partial_2 - 1 & \partial_1\partial_2 \end{pmatrix} \Rightarrow \begin{pmatrix} 1 & (\frac{k}{\partial_1 - 1} - \partial_1)\partial_2 \\ 0 & \partial_2^2 - \frac{1}{\partial_1^2 - \partial_1 - (k+1)}\partial_2 \end{pmatrix}$$

- Exponential bound on the coefficient of the Hermite form [Giesbrecht, Kim 11].

Hermite forms

Idea: Instead of removing one variable at a time, invert the matrix using (non-commutative) linear algebra.

- Put matrices of operators in a triangular form (Hermite form):

$$\begin{pmatrix} (\partial_1 - 1)\partial_2 & -\partial_2 \\ -k\partial_2 - 1 & \partial_1\partial_2 \end{pmatrix} \Rightarrow \begin{pmatrix} 1 & (\frac{k}{\partial_1 - 1} - \partial_1)\partial_2 \\ 0 & \partial_2^2 - \frac{1}{\partial_1^2 - \partial_1 - (k+1)}\partial_2 \end{pmatrix}$$

- Exponential bound on the coefficient of the Hermite form [Giesbrecht, Kim 11].
- Obtain a bound on the length of a short witness of non-universality.

Main theorems

Theorem [B.,Clemente 20]

The zeroness problem for linrec sequences with univariate polynomial coefficients is decidable in EXP-TIME.

Theorem [B.,Clemente 20]

The universality problem for unambiguous register automata is decidable

- in 2EXP-TIME in general.
- in EXP-TIME (for a fixed number of registers).

Main theorems

Theorem [B.,Clemente 20]

The zeroness problem for linrec sequences with univariate polynomial coefficients is decidable in EXP-TIME.

Theorem [B.,Clemente 20]

The universality problem for unambiguous register automata is decidable

- in 2EXP-TIME in general.
- in EXP-TIME (for a fixed number of registers).

(The complexity becomes EXP-TIME and PTIME if the monicity conjecture holds)

Conclusion

- Improving the complexity. Monicity conjecture: monic cancelling relations suffice:

$$((\cancel{k^2} \rightarrow \cancel{5k} \neq \cancel{6})) \partial_1^3 \partial_2^3 + (2k + 2) \partial_1^3 \partial_2^2 - 2 \partial_1^2 \partial_2 + \partial_2^2 - (3k + 3)) \cdot g = 0$$

This is false for linrec in general, we have to restrict to equations arising from automata. This would give an EXP-TIME bound.

Conclusion

- Improving the complexity. Monicity conjecture: monic cancelling relations suffice:

$$((\cancel{k^2} - \cancel{5k} + \cancel{6})\partial_1^3\partial_2^3 + (2k + 2)\partial_1^3\partial_2^2 - 2\partial_1^2\partial_2 + \partial_2^2 - (3k + 3)) \cdot g = 0$$

This is false for linrec in general, we have to restrict to equations arising from automata. This would give an EXP-TIME bound.

- Extend to other structures: other atoms, timed automata, pushdown automata...

Conclusion

- Improving the complexity. Monicity conjecture: monic cancelling relations suffice:

$$((k^2 - 5k + 6)\partial_1^3\partial_2^3 + (2k + 2)\partial_1^3\partial_2^2 - 2\partial_1^2\partial_2 + \partial_2^2 - (3k + 3)) \cdot g = 0$$

This is false for linrec in general, we have to restrict to equations arising from automata. This would give an EXP-TIME bound.

- Extend to other structures: other atoms, timed automata, pushdown automata...
- Extend to weighted automata.



M. Giesbrecht and M. S. Kim.

Computing the Hermite form of a matrix of Ore polynomials.

Journal of Algebra, 376:341–362, 2013.



A. Mottet and K. Quaas.

The containment problem for unambiguous register automata and unambiguous timed automata.

Theory of Computing Systems, 2020.



O. Ore.

Theory of non-commutative polynomials.

Annals of Mathematics, 34(3):480–508, 1933.



R. Stearns and H. Hunt.

On the equivalence and containment problems for unambiguous regular expressions, grammars, and automata.

In *Proc. of SFCS'81*, pages 74–81, Washington, DC, USA, 1981. IEEE Computer Society.