

FCC200 Report
Affine Cipher and S-DES Implementation

Connor Beardsmore - 15504319

Curtin University
Science and Engineering
Perth, Australia
April 2017

Affine Cipher

Compute Eligible Keys

There are two keys required, a and b . The first is required to be *coprime* with the length of the alphabet, in this scenario 26. The second key representing the linear shift must be both positive and less than the length of the alphabet. To check if the a value is coprime, the following greatest common denominator check was utilized. If the greatest common denominator of a and 26 is 1, the value of a is *coprime* and the key is valid in combination with any valid b value.

```

1 //-----
2 // FUNCTION: gcd
3 // IMPORT: a (int), b (int)
4 // PURPOSE: Find greatest common denominator of 2 numbers
5
6 int gcdFunction( int a, int b )
7 {
8     int quotient, residue, temp, gcd = 1;
9     // SWAP ELEMENTS TO GET THE MAX
10    if ( a < b )
11    {
12        temp = a;
13        a = b;
14        b = temp;
15    }
16    // CHECK IF EITHER NUMBER IS 0
17    if ( a == 0 ) return b;
18    if ( b == 0 ) return a;
19    // SATISFY THE EQUATION: A = B * quotient + residue
20    quotient = a / b;
21    residue = a - ( b * quotient );
22    // RECURSIVELY CALL GCD
23    gcd = gcdFunction( b, residue );
24    return gcd;
25 }
26
27 //-----

```

The results of calling this function on all a values from 1 to 25 are as follows:

- gcdFunction(1, 26) = 1
- gcdFunction(2, 26) = 2
- gcdFunction(3, 26) = 1
- gcdFunction(4, 26) = 2
- gcdFunction(5, 26) = 1
- gcdFunction(6, 26) = 2
- gcdFunction(7, 26) = 1
- gcdFunction(8, 26) = 2
- gcdFunction(9, 26) = 1
- gcdFunction(10, 26) = 2
- gcdFunction(11, 26) = 1
- gcdFunction(12, 26) = 2
- gcdFunction(13, 26) = 13
- gcdFunction(14, 26) = 2
- gcdFunction(15, 26) = 1
- gcdFunction(16, 26) = 2

- `gcdFunction(17, 26) = 1`
- `gcdFunction(18, 26) = 2`
- `gcdFunction(19, 26) = 1`
- `gcdFunction(20, 26) = 2`
- `gcdFunction(21, 26) = 1`
- `gcdFunction(22, 26) = 2`
- `gcdFunction(23, 26) = 1`
- `gcdFunction(24, 26) = 2`
- `gcdFunction(25, 26) = 1`

The full list of valid a values is: **1, 3, 5, 7, 9, 11, 15, 17, 19, 21, 23, 25**

There are a total of 12 possible a values that are coprime with 26. Each of these values can have a shift value (b) of 0 to 25. Thus, the total number of eligible keys is:

$$12 * 26 = 312$$

Of these, 26 keys are trivial Caesar ciphers and 286 are non-trivial.

Recovered Plaintext

```

1 Inthispaperweconsidertheproblemofrobustfacerecognitionusingcolor
2 informationinthiscontextsparserepresentationbasedalgorithmsarethe
3 stateoftheartsolutionsforgrayfacialimageSproposedmodelthecontrolpar
4 ameterizationTechniqueTogetherwiththeconstrainttranscriptionmethodi
5 susedbytransformingtheproposedproblemintoasequenceofoptimalparameter
6 selectionproblemsFinallyapracticalexampleonbeersalesisusedtoshowtheeffectiveness
7 ofproposedmodelandwepresenttheoptimaladvertisingstrategiescorrespondingtodifferent
8 competitionsituations
9

```

Figure 1: Original Plaintext

```

[Connors-MacBook-Pro:affine connor$ make
gcc -c affine.c -Wall -Wextra -std=c99
gcc -c keyEligible.c -Wall -Wextra -std=c99
gcc affine.o keyEligible.o -o affine -Wall -Wextra -std=c99
[Connors-MacBook-Pro:affine connor$ affine -e affine.txt output.txt 11 9

```

Figure 2: Encryption Process

```

1 Twkitzjsborbfhwztqbokibsohuablhmohuvzkmjfbobfhxwtkthwvztwxfhaho
2 twmholjkthwtwkitzfhwkbczsjobobsobzbwkjkthwujzbqjaxhotkilzjobkib
3 zkjkbhmkibjokzhavkthwzmhoxojnmjftjatljxbZsohshzbqlhqbakibfhwkohasjo
4 jlbkbotyjkthwKbfiwtdvbKHxbkibortkikibfhwzkojtwkkojwzfotskthwlbkqhqt
5 zvzbqunkojwzmholtwxkibsohshzbqsohuablwtkhjzbdvbwfbhmhsktljasjojlbkbo
6 zbabfkthwsohuablzMtwjaanjsjofktfjabcljsabhwubbozjabztzvzbqkhzihrkibbmmbfktgbwbzz
7 hmsohshzbqlhqbajwqrsobzbwkibhsktlJajqgboktztwxzkojkbxtbzfhoobzshwqtwxkqhqtmmmbobwk
8 fhlsbktkthwztkvjktwZ
9

```

Figure 3: Encrypted Ciphertext

```
[Connors-MacBook-Pro:affine connor$ affine -d output.txt original.txt 11 9
```

Figure 4: Decryption Process

```
1 |Inthispaperweconsidertheproblemofrobustfacerecognitionusingcolor
2 |informationinthiscontextsparserepresentationbasedalgorithmsarethe
3 |stateoftheartsolutionsforgrayfacialimageSproposedmodelthecontrolpar
4 |ameterizationTechniqueTogetherwiththeconstrainttranscriptionmethodi
5 |susedbytransformingtheproposedproblemintoasequenceofoptimalparameter
6 |selectionproblemsFinallyapracticalexampleonbeersalesisusedtoshowtheeffectiveness
7 |ofproposedmodelandwepresenttheoptimaladvertisingstrategiescorrespondingtodifferent
8 |competitionsituationsS
9
```

d

Figure 5: Recovered Plaintext

Affine Mathematical Proof

The encryption and decryption functions for the affine cipher are as follows:

$$E(x) = (ax + b) \bmod m$$

$$D(x) = a^{-1}(x - b) \bmod m$$

The modular multiplicative inverse of a is defined as:

$$1 = aa^{-1} \bmod m$$

It can be shown that $D(x)$ is the inverse of $E(x)$ via the modular arithmetic laws.

$$\begin{aligned} D(E(x)) &= a^{-1}(E(x) - b) \bmod m \\ &= a^{-1}((ax + b \bmod m) - b) \bmod m \\ &= a^{-1}(ax + b - b) \bmod m \\ &= a^{-1}ax \bmod m \\ &= x \bmod m \end{aligned}$$

Letter Distribution

For the given test file shown in Figure 2, the following table and Figure 7 illustrate the letter distribution and relative frequencies.

• A: 35	• E: 65	• I: 41	• M: 16	• Q: 2	• U: 8	• Y: 3
• B: 7	• F: 14	• J: 0	• N: 35	• R: 39	• V: 2	• Z: 1
• C: 17	• G: 10	• K: 0	• O: 50	• S: 39	• W: 4	
• D: 14	• H: 16	• L: 18	• P: 23	• T: 53	• X: 2	

```

A: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
B: xxxxxxx
C: xxxxxxxxxxxxxxxxxxx
D: xxxxxxxxxxxxxxx
E: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
F: xxxxxxxxxxxxxxx
G: xxxxxxxxx
H: xxxxxxxxxxxxxxxxxxx
I: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
J:
K:
L: xxxxxxxxxxxxxxxxxxx
M: xxxxxxxxxxxxxxxxxxx
N: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
O: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
P: xxxxxxxxxxxxxxxxxxxxxxx
Q: xx
R: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
S: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
T: xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
U: xxxxxxxx
V: xx
W: xxxx
X: xx
Y: xxx
Z: x

```

Figure 6: Letter Distributions

S-DES

S-DES Mathematical Proof

hello

Pseudo Code Structure

The pseudo-code structure of the three key functions utilized in the S-DES implementation is illustrated below.

```
function KEYGENERATION(int key)
    key  $\leftarrow$  PERMUTE( key, P10 )
    LEFTSHIFT( key, 1 )
    subkeys[0]  $\leftarrow$  PERMUTE( key, P8 )
    LEFTSHIFT( key, 2 )
    subkeys[1]  $\leftarrow$  PERMUTE( key, P8 )
    return subkeys
end function
```

```
function SWITCHFUNCTION(int input)
    right  $\leftarrow$  bits && ((1 << 4) - 1)
    left  $\leftarrow$  bits >>> 4
    output  $\leftarrow$  left || (right << 4)
    return output
end function
```

```
function FEISTALKEYROUND(int message, int subkey)
    halves  $\leftarrow$  SPLIT( message )
    fMap  $\leftarrow$  FMAPPING( rightHalf, subkey )
    leftHalf  $\leftarrow$  leftHalf  $\oplus$  fMap
    combined  $\leftarrow$  leftHalf + rightHalf
    return combined
end function
```

Encrypted Test File

```
[Connors-MacBook-Pro:SDES connor$ javac *.java
[Connors-MacBook-Pro:SDES connor$ java SDES -e 130 des.txt output.txt
```

Figure 7: S-DES Encryption Process

```

1  0E03Ehx00+0k0^0a{9h3'
2  E00000000000r0hĩ'0E0
3  0
4  Eh000E00Eh0
5  E0
6  000{{0E0'
7  0Âh0h0
8  f{hI+ 'a^00
9  {9h3'
10 EĞ0'+09000000E0
11 h'\i000
12 EĖ00E
13 f{hE000x00
525 f+00+000+' f
526 00+00
527 EE+x0
528 0h0P0Ğ0h0N0+00+xx0' 'h0xh0+0Ğ0h0+~ã00k00000E0h000h0
529 E0003h900kh00
530 00+00000000k0000q0{+90ks00000k000000h0kh00
531 00+00000
532 Eh0+0Ğ00E0Ğ0h0x+0xh00+0000
533 00+0_E0h'+000E0h000h0
534 EI+{{+E
535 000000000000

```

Figure 8: S-DES Cipher Text

Decrypted Test File

```
[Connors-MacBook-Pro:SDES connor$ java SDES -d 130 output.txt original.txt
```

Figure 9: S-DES Decryption Process

```

1 \subsection{AFS Algebras}
2 ###&&&
3 The Iris dataset is used as an illustrative example for AFS algebras through
4 this paper. It has 150 samples which are evenly distributed in three
5 classes and 4 features of sepal length($f_1$), sepal
6 width($f_2$), petal length($f_3$), and petal width($f_4$). Let a
7 pattern  $x=(x_{\{1\}},x_{\{2\}},x_{\{3\}},x_{\{4\}})$ , where  $x_{\{i\}}$  is the  $i$ th
8 feature value of  $x$ . The following three linguist fuzzy rules have been obtained for Class 1
9 to build the AFS fuzzy classifier in Section 4.
10 \bigskip
11 \textbf{Rule}  $R_1$ : If  $x_{\{1\}}$  is \emph{short sepal}, and  $x_{\{2\}}$ 
12 is \emph{wide sepal}, and  $x_{\{4\}}$  is \emph{narrow petal}, then  $x$ 
13 belongs to Class 1;
258 \subsection{Shannoni's Entropy}
259 Let  $X$  be a discrete random variable with a finite set containing  $N$  symbols
260  $x_{\{0\}}, x_{\{1\}}, \dots, x_{\{N\}}$ . If an output  $x_{\{j\}}$  occurs with probability  $p(x_{\{j\}})$ , then
261 the
262 amount of information associated with the known occurrence of the output  $x_{\{j\}}$  is defined as
263 \begin{equation}
264 I(x_{\{j\}}) = -\log_2 p(x_{\{j\}})
265 \end{equation}
266 Based on this, the concept of Shannoni's entropy is defined as follows:
267 ))))~~~~~

```

Figure 10: S-DES Plain Text

Utilization of an all 1 Key

Performing encryption and decryption with S-DES utilizing a key of all 1's (11111111) does not significantly alter how the algorithm performs. However, during the two feistal key rounds, the subkeys will be equivalent. This leads to both encryption and decryption being the same process. Thus in this situation:

$$x = E(E(x))$$

Modify S-Boxes

The S-BOX values in the SDESConstants.java file were modified to ensure that the S-DES algorithm still performs accurately.

Additional Questions

Threats

hello

Source Coding

Source coding in information transmission aims to compress natural messages for highly efficient message transfer.

Error Coding

Error coding in information transmission attempts to enable a high information rate by the introduction of redundancy to data, as well as via error detection and correction mechanisms.

S-DES Coding

hello

S-DES Confusion and Diffusion

In S-DES, confusion is provided by the S-BOX substitutions performed within the feistel key round. Diffusion in contrast is provided by the permutations applied to the data included the expansion permutation utilized.

Affine Source Code

keyeligible.h

```
1  /*****
2  * FILE: keyEligible.h
3  * AUTHOR: Connor Beardsmore - 15504319
4  * UNIT: FCC200
5  * PURPOSE: Header file for key eligibility checks
6  *   LAST MOD: 24/03/17
7  *   REQUIRES: NONE
8  *****/
9
10 // PROTOTYPES
11 int keyEligible(int, int, int);
12 int gcdFunction(int, int);
13 int extendEuclid(int, int);
14
15 //
```

keyeligible.c

```

1  /*****
2  * FILE: keyEligible.c
3  * AUTHOR: Connor Beardsmore - 15504319
4  * UNIT: FCC200
5  * PURPOSE: Check the eligibility of keys a and b
6  *   LAST MOD: 28/03/17
7  *   REQUIRES: keyEligible.h
8  *****/
9
10 #include "keyEligible.h"
11
12 //-----
13 // FUNCTION: keyEligible
14 // IMPORT: a (int), b (int)
15 // EXPORT: eligible (int)
16 // PURPOSE: Check that the two given keys are eligible via coprime check
17
18 int keyEligible( int a, int b, int alphabet )
19 {
20     int eligible = 1;
21
22     // a must be positive and less than the alphabet (26)
23     if ( ( a < 0 ) || ( b > ( alphabet - 1 ) ) )
24         eligible = 0;
25     // a must be coprime to the alphabet length (26)
26     if ( gcdFunction( a, alphabet ) != 1 )
27         eligible = 0;
28     // b must be positive and less than the alphabet (26)
29     if ( ( b < 0 ) || ( b > ( alphabet - 1 ) ) )
30         eligible = 0;
31     return eligible;
32 }
33
34 //-----
35 // FUNCTION: gcd
36 // IMPORT: a (int), b (int)
37 // PURPOSE: Find greatest common denominator of 2 numbers
38
39 int gcdFunction( int a, int b )
40 {
41     int quotient, residue, temp, gcd = 1;
42     // SWAP ELEMENTS TO GET THE MAX
43     if ( a < b )
44     {
45         temp = a;
46         a = b;
47         b = temp;
48     }
49     // CHECK IF EITHER NUMBER IS 0
50     if ( a == 0 ) return b;
51     if ( b == 0 ) return a;
52     // SATISFY THE EQUATION: A = B * quotient + residue
53     quotient = a / b;
54     residue = a - ( b * quotient );
55     // RECURSIVELY CALL GCD
56     gcd = gcdFunction( b, residue );
57     return gcd;
58 }
59
60 //-----
61 // FUNCTION: extendEuclid
62 // IMPORT: a (int), n (int)
63 // PURPOSE: Extended Euclidean algorithm to find inverse modular

```

```
64
65 int extendEuclid( int a, int n )
66 {
67     int t = 0, newt = 1;
68     int r = n, newr = a;
69     int q = 0, temp = 0;
70
71     // IF GCD IS NOT 1 THEN NO COPRIME EXISTS
72     if ( gcdFunction( a, n ) != 1 )
73         return -1;
74
75     // PERFORM EXTENDED EUCLIDEAN
76     while ( newr != 0 )
77     {
78         q = r / newr;
79         temp = t;
80         t = newt;
81         newt = temp - ( q * newt );
82         temp = r;
83         r = newr;
84         newr = temp - ( q * newr );
85     }
86
87     // MAKE SURE T IS NOT NEGATIVE
88     if ( t < 0 )
89         t = t + n;
90
91     return t;
92 }
93
94 //
```

affine.h

```
1  /*****
2  * FILE: affine.h
3  * AUTHOR: Connor Beardsmore - 15504319
4  * UNIT: FCC200
5  * PURPOSE: Header file for affine cipher
6  *   LAST MOD: 11/03/17
7  *   REQUIRES: stdio.h, ctype.h, stdlib.h, string.h, keyEligible.h
8  *****/
9
10 #include <stdio.h>
11 #include <ctype.h>
12 #include <stdlib.h>
13 #include <string.h>
14 #include "keyEligible.h"
15
16 // PROTOTYPES
17 char encrypt(char, int, int);
18 char decrypt(char, int, int);
19
20 // FUNCTION POINTER
21 typedef char (*FuncPtr)(char, int, int);
22
23 // CONSTANTS
24 #define ARGS 6
25 #define ALPHABET 26
26
27 //
```

affine.c

```

1  /*****
2  * FILE: affine.c
3  * AUTHOR: Connor Beardsmore - 15504319
4  * UNIT: FCC200
5  * PURPOSE: Run Affine cipher given text and key, either encrypt or decrypt
6  *   LAST MOD: 28/03/17
7  *   REQUIRES: affine.h
8  *****/
9
10 #include "affine.h"
11
12 //-----
13 // FUNCTION: main
14
15 int main( int argc, char* argv[] )
16 {
17     if ( argc != ARGS )
18     {
19         printf("\nUSAGE: <FLAG> <INPUT FILE> <OUTPUT FILE> <KEY A> <KEY B>\n");
20         printf("FLAGS ARE: -e for encryption, -d for decryption\n\n");
21         return 1;
22     }
23
24     // CONVERT ARGV NAMES
25     char* flag = argv[1];
26     char* inFile = argv[2];
27     char* outFile = argv[3];
28     int a = atoi( argv[4] );
29     int b = atoi( argv[5] );
30
31     // CHECK THAT THE KEYS ARE ELIGIBLE
32     int validity = keyEligible( a, b, ALPHABET );
33     if ( validity != 1 )
34     {
35         printf("\nKEYS %d AND %d ARE NOT VALID.\n", a, b );
36         return 2;
37     }
38
39     // OPEN INPUT AND OUTPUT FILES
40     FILE* inF = fopen( inFile, "r" );
41     FILE* outF = fopen( outFile, "w" );
42
43     // CHECK OPEN FOR ERRORS
44     if ( ( inF == NULL ) || ( outF == NULL ) )
45     {
46         perror( "\nERROR OPENING INPUT OR OUTPUT FILE\n" );
47         return 3;
48     }
49
50     // FUNCTION POINTER FOR encrypt() OR decrypt()
51     FuncPtr fp;
52
53     // PERFORM ENCRYPTION IF -e FLAG PROVIDED AND VICE VERSA
54     if ( !strcmp( flag, "-e", 2 ) )
55         fp = &encrypt;
56     else if ( !strcmp( flag, "-d", 2 ) )
57         fp = &decrypt;
58     else
59     {
60         printf("\nFLAG IS INCORRECT, MUST BE -e OR -d\n");
61         return 4;
62     }
63

```

```

64 // PERFORM APPROPRIATE FUNCTION
65 while ( ( feof( inF ) == 0 ) && ( ferror( inF ) == 0 ) && ( ferror( inF ) == 0 ) )
66 {
67     // GET THE NEXT CHARACTER FROM FILE
68     char next = fgetc( inF );
69     if ( feof( inF ) == 0 )
70         // WRITE THE CONVERTED CHARACTER TO FILE
71         fputc( ( *fp )( next, a, b ), outF );
72 }
73
74 // CLOSE FILES
75 fclose( inF );
76 fclose( outF );
77
78 return 0;
79 }
80
81 //-----
82 // FUNCTION: encrypt
83 // IMPORT: plain (char), a (int), b (int)
84 // PURPOSE: Convert a plaintext char into the encrypted character
85
86 char encrypt( char plain, int a, int b )
87 {
88     char output = plain;
89     // ENCRYPT BASED ON plain * a + b MODULO 26
90     // IGNORE NON-CHARACTERS
91     if ( isupper(plain) )
92         output = ( ( ( plain - 'A' ) * a + b ) % ALPHABET ) + 'A';
93     else if ( islower(plain) )
94         output = ( ( ( plain - 'a' ) * a + b ) % ALPHABET ) + 'a';
95     return output;
96 }
97
98 //-----
99 // FUNCTION: decrypt
100 // IMPORT: plain (char*), a (int), b (int)
101 // PURPOSE: Convert a ciphertext char into the decrypted character
102
103 char decrypt( char cipher, int a, int b )
104 {
105     // FIND THE MODULO INVERSE USING EUCLIDEAN
106     int inverse = extendEuclid( a, ALPHABET );
107     char output = cipher;
108     // DECRYPT BASED ON inverse * cipher - b MODULO 26
109     // IGNORE NON-CHARACTERS
110     if ( isupper(cipher) )
111         output = ( ( inverse * ( cipher - 'A' - b + ALPHABET ) ) % ALPHABET ) + 'A';
112     else if ( islower(cipher) )
113         output = ( ( inverse * ( cipher - 'a' - b + ALPHABET ) ) % ALPHABET ) + 'a';
114     return output;
115 }
116
117 //-----

```

S-DES Source Code

SDESConstants.java

```

1  /*****
2  * FILE: SDESConstants
3  * AUTHOR: Connor Beardsmore - 15504319
4  * UNIT: FCC200
5  * PURPOSE: Structures to represent the constants in the SDES algorithm
6  * LAST MOD: 21/03/17
7  * REQUIRES: NONE
8  *****/
9
10 public class SDESConstants
11 {
12     // P10 PERMUTATION FOR THE 10-BIT KEY
13     public static final int[] P10 = { 2, 4, 1, 6, 3, 9, 0, 8, 7, 5 };
14
15     //-----
16
17     // P8 PERMUTATION FOR THE 10-BIT KEY
18     public static final int[] P8 = { 5, 2, 6, 3, 7, 4, 9, 8 };
19
20     //-----
21
22     // INITIAL PERMUTATION FOR THE 8-BIT PLAINTEXT
23     public static final int[] IP = { 1, 5, 2, 0, 3, 7, 4, 6 };
24
25     //-----
26
27     // INVERSE PERMUTATION FOR THE 8-BIT PLAINTEXT
28     public static final int[] IPI = { 3, 0, 2, 4, 6, 1, 7, 5 };
29
30     //-----
31
32     // EXPANSION PERMUTATION FOR 4-BITS IN Fk
33     public static final int[] EP = { 3, 0, 1, 2, 1, 2, 3, 0 };
34
35     //-----
36
37     // P4 PERMUTATION AFTER THE S-BOX SELECTION
38     public static final int[] P4 = { 1, 3, 2, 0 };
39
40     //-----
41
42     // SBOX ONE
43     public static final int[][] S0 = { { 1, 0, 3, 2 },
44                                         { 3, 2, 1, 0 },
45                                         { 0, 2, 1, 3 },
46                                         { 3, 1, 3, 2 } };
47
48     //-----
49
50     // SBOX TWO
51     public static final int[][] S1 = { { 0, 1, 2, 3 },
52                                         { 2, 0, 1, 3 },
53                                         { 3, 0, 1, 0 },
54                                         { 2, 1, 0, 3 } };
55
56     //-----
57 }

```


SDESBits.java

```

1  /*****
2  * FILE: SDESBits.java
3  * AUTHOR: Connor Beardsmore - 15504319
4  * UNIT: FCC200
5  * PURPOSE: BitSet alternative using a int
6  *   LAST MOD: 24/03/17
7  *   REQUIRES: NONE
8  *****/
9
10 public class SDESBits
11 {
12     //CONSTANTS
13     public static final int MIN_SIZE = 4;
14     public static final int MAX_SIZE = 10;
15
16     //CLASSFIELDS
17     private int bits;
18     private int size;
19     private int half;
20     // private only applies to different classes, so we can
21     // import an SDESBits and retrieve bits without a getter
22
23     //-----
24     //ALTERNATE CONSTRUCTOR
25
26     public SDESBits( int inBits , int inSize )
27     {
28         // Check inBits and inSize validity
29         if ( inBits < 0 )
30             throw new IllegalArgumentException( "INVALID SDESBits VALUE" );
31         if ( ( inSize < MIN_SIZE ) || ( inSize > MAX_SIZE ) )
32             throw new IllegalArgumentException( "INVALID SDESBits SIZE" );
33         if ( inSize % 2 != 0 )
34             throw new IllegalArgumentException( "INVALID SDESBits SIZE" );
35
36         bits = inBits;
37         size = inSize;
38         half = inSize >>> 1;
39     }
40
41     //-----
42     //COPY CONSTRUCTOR
43
44     public SDESBits( SDESBits inBits )
45     {
46         bits = inBits.bits;
47         size = inBits.size;
48         half = inBits.half;
49     }
50
51     //-----
52     //FUNCTION: switchHalves()
53     //PURPOSE: Switch the left half of bits with the right half
54
55     public void switchHalves()
56     {
57         // Get the right half of the bits
58         int oRight = bits & ( ( 1 << half ) - 1 );
59         // Shift the left half of the bits down
60         bits >>= half;
61         // Combine left half with right half shifted up
62         bits |= ( oRight << half );
63     }

```

```

64
65 //-----
66 //FUNCTION: permute()
67 //IMPORT: permTable (int[])
68 //EXPORT: permuted (SDESBits)
69 //PURPOSE: Create a permutation of this objects bits in a new SDESBits
70
71 public SDESBits permute( int[] permTable )
72 {
73     // Create temporary space the size of the permutation
74     SDESBits permuted = new SDESBits( 0, permTable.length );
75     // Iterate across the permutation, getting and setting bits
76     for ( int ii = 0; ii < permTable.length; ii++ )
77         permuted.setBit( getBit( permTable[ii] ), ii );
78     return permuted;
79 }
80
81 //-----
82 //FUNCTION: leftShift()
83 //IMPORT: shifts (int)
84 //PURPOSE: Perform a circular left shift on the bits of each half
85
86 public void leftShift( int shifts )
87 {
88     //Check shift validity
89     if ( shifts < 1 )
90         throw new IllegalArgumentException( "ILLEGAL SHIFT VALUE" );
91
92     // Temp variable for repeated 1's for a half
93     int ones = ( 1 << half ) - 1;
94     // Avoid shifting more than required
95     if ( half > shifts )
96         shifts %= half;
97
98     // Get the left half and right half
99     int left = bits >>> half;
100    int right = bits & ones;
101
102    // Loop for each shift individually
103    for ( int ii = 0; ii < shifts; ii++ )
104    {
105        // Get the leftmost bit of the left sub-half
106        int leftBit = ( left & ones );
107        leftBit >>>= MIN_SIZE;
108        // Get the rightmost bit of the right sub-half
109        int rightBit = ( right & ones );
110        rightBit >>>= MIN_SIZE;
111
112        // Perform the actual shifting of the bits
113        left = ( left << 1 ) & ones;
114        right = ( right << 1 ) & ones;
115
116        // If the first bits of the halves were one, set final bit
117        if ( leftBit == 1 )    left++;
118        if ( rightBit == 1 )   right++;
119    }
120
121    // Recombine both halves back together
122    bits = ( left << half ) | right;
123 }
124
125 //-----
126 //FUNCTION: split()
127 //EXPORT: halves (SDESBits[])
128 //PURPOSE: Split the bits into two sub-halves and return as objects

```

```

129
130     public SDESBits[] split()
131     {
132         // New container for the halves
133         SDESBits[] halves = new SDESBits[2];
134         // Get the left half and create object
135         int leftInt = bits >>> half;
136         halves[0] = new SDESBits( leftInt , half );
137         // Get the right half and create object
138         int rightInt = ( bits & ( ( 1 << half ) - 1 ) );
139         halves[1] = new SDESBits( rightInt , half );
140
141         return halves;
142     }
143
144 //-----
145 //FUNCTION: xor()
146 //IMPORT: inBits (SDESBits)
147 //PURPOSE: XOR bits with the bits value of inBits
148
149     public void xor( SDESBits inBits )
150     {
151         // Ensure the same size
152         if ( size != inBits.size )
153             throw new IllegalArgumentException( "CANNOT XOR DIFFERENT SIZES" );
154
155         // Call simple exclusive-or on both bits
156         bits ^= inBits.bits;
157     }
158
159 //-----
160 //FUNCTION: setBit()
161 //IMPORT: val (boolean), index (int)
162 //PURPOSE: Set the value at the specified index with the specified value
163
164     public void setBit( boolean val , int index )
165     {
166         // Validity
167         if ( ( index < 0 ) || ( index >= size ) )
168             throw new IllegalArgumentException("SETBIT IMPORTS INVALID");
169
170         // Reset the given bit
171         bits &= ~(1 << ( size - index - 1 ) );
172         // Reset the bits greater than the size we want
173         bits &= (1 << size)-1;
174         // Set the required bit
175         bits |= ((val) ? 1 : 0 ) << ( size - index - 1 );
176     }
177
178 //-----
179 //FUNCTION: getBit()
180 //IMPORT: index (int)
181 //EXPORT: value (boolean)
182 //PURPOSE: Get the value of the bit at the specified index
183
184     public boolean getBit( int index )
185     {
186         if ( ( index < 0 ) || ( index >= size ) )
187             throw new IllegalArgumentException("SETBIT IMPORTS INVALID");
188
189         // Bits are reverse ordered
190         return (bits & 1 << ( size - index - 1 ) ) != 0;
191     }
192
193 //-----

```

```
194
195     public int getBits() { return bits; }
196
197 //-----
198 //FUNCTION: append()
199 //IMPORT: newBits (SDESBits)
200 //PURPOSE: Append new set of bits to the original set
201
202     public void append( SDESBits newBits )
203     {
204         // Increment size
205         size += newBits.size;
206         // Shift original across and add new bits
207         bits = ( bits << newBits.size ) | newBits.bits;
208         // Update half value
209         half = size >>> 1;
210     }
211
212 //-----
213 //FUNCTION: sbbox()
214 //EXPORT: result (int)
215 //PURPOSE: Find the sbbox values for the bits in this object
216
217     public int sbbox()
218     {
219         // Split into halves
220         SDESBits halves[] = this.split();
221
222         // Get row and column of the first four bits
223         int colS0 = ( halves[0].bits & 6 ) >>> 1;
224         int rowS0 = ( ( halves[0].bits & 8 ) >>> 2 ) | ( halves[0].bits & 1 );
225         // Get row and column of the second four bits
226         int colS1 = ( halves[1].bits & 6 ) >>> 1;
227         int rowS1 = ( ( halves[1].bits & 8 ) >>> 2 ) | ( halves[1].bits & 1 );
228
229         // Get the appropriate sbbox value
230         int s0Val = SDESConstants.S0[rowS0][colS0];
231         int s1Val = SDESConstants.S1[rowS1][colS1];
232
233         // Combine the result
234         int result = ( s0Val << 2 ) | s1Val;
235
236         return result;
237     }
238
239 //-----
240 //FUNCTION: toString()
241 //EXPORT: state (String)
242 //PURPOSE: Export bits in a readable binary format
243
244     public String toString()
245     {
246         return Integer.toBinaryString( bits );
247     }
248
249 //-----
250 }
```

SDES.java

```

1  /*****
2  * FILE: SDES.java
3  * AUTHOR: Connor Beardsmore - 15504319
4  * UNIT: FCC200
5  * PURPOSE: Performs SDES encryption or decryption on a given file
6  *   LAST MOD: 21/03/17
7  *   REQUIRES: NONE
8  *****/
9
10 import java.util.*;
11 import java.io.*;
12
13 public class SDES
14 {
15
16     public static final int NUMARGS = 4;
17     public static final int MAXKEY = 1023;
18     public static final int KEY_SIZE = 10;
19     public static final int MESSAGE_SIZE = 8;
20
21     //-----
22
23     public static void main( String[] args )
24     {
25         // Check argument length and output usage
26         if ( args.length != NUMARGS )
27         {
28             System.out.println("USAGE: SDES <mode> <key> <input file> <output file>");
29             System.out.println("modes = -e encryption, -d decryption");
30             System.out.println("keys = int between 0 and 255");
31             System.exit(1);
32         }
33
34         // Rename variables for simplicity
35         String mode = args[0];
36         String key = args[1];
37         String inFile = args[2];
38         String outFile = args[3];
39         SDESBits message, output;
40         int intKey = Integer.parseInt( key );
41
42         try
43         {
44             // Generate subkeys
45             SDESBits subkeys[] = keyGeneration( intKey );
46
47             // Open file streams
48             FileInputStream fis = new FileInputStream( new File( inFile ) );
49             FileOutputStream fos = new FileOutputStream( new File( outFile ) );
50
51             // Read bytes until end of file
52             int next = fis.read();
53             while ( next != -1 )
54             {
55                 message = new SDESBits( next, MESSAGE_SIZE );
56
57                 // Select function based on mode
58                 if ( mode.equals( "-e" ) )
59                     output = encrypt( message, subkeys );
60                 else if ( mode.equals( "-d" ) )
61                     output = decrypt( message, subkeys );
62                 else
63                     throw new IllegalArgumentException("INVALID MODE");

```

```

64
65         // Write converted output to file
66         int outputInt = output.getBits();
67         fos.write( outputInt );
68         next = fis.read();
69     }
70 }
71 catch (Exception e)
72 {
73     System.out.println( e.getMessage() );
74 }
75
76 }
77
78 //-----
79 //FUNCTION: encrypt()
80 //IMPORT: message (SDESBits), subkeys (SDESBits[])
81 //EXPORT: message (SDESBits)
82 //PURPOSE: Encrypt given message with given subkeys
83
84 public static SDSEBits encrypt( SDSEBits message, SDSEBits[] subkeys )
85 {
86     // Initial Permutation
87     message = message.permute( SDESConstants.IP );
88     // First feistal key round with subkey 1
89     message = feistalRound( message, subkeys[0] );
90     // Switch left and right subhalves
91     switchFunction( message );
92     // Second feistal key round with subkey 2
93     message = feistalRound( message, subkeys[1] );
94     // Inverse of Initial Permutation
95     message = message.permute( SDESConstants.IPI );
96     return message;
97 }
98
99 //-----
100 //FUNCTION: decrypt()
101 //IMPORT: message (SDSEBits), subkeys (SDSEBits[])
102 //EXPORT: message (SDSEBits)
103 //PURPOSE: Decrypt given message with given subkeys
104
105 public static SDSEBits decrypt( SDSEBits message, SDSEBits[] subkeys )
106 {
107     // Initial Permutation
108     message = message.permute( SDESConstants.IP );
109     // First feistal key round with subkey 2
110     message = feistalRound( message, subkeys[1] );
111     // Switch left and right subhalves
112     switchFunction( message );
113     // First feistal key round with subkey 1
114     message = feistalRound( message, subkeys[0] );
115     // Inverse of Initial Permutation
116     message = message.permute( SDESConstants.IPI );
117     return message;
118 }
119
120 //-----
121 //FUNCTION: switchFunction()
122 //IMPORT: input (SDSEBitSet)
123 //PURPOSE: Import 8-bit binary and swap the first and last 4 bits
124
125 public static void switchFunction( SDSEBits input )
126 {
127     input.switchHalves();
128 }

```

```

129
130 //-----
131 //FUNCTION: keyGeneration()
132 //IMPORT: keyDec (int)
133 //EXPORT: subkeys (SDESBits[])
134 //PURPOSE: Generate subkeys given the full key
135
136 public static SDESBits[] keyGeneration( int keyDec )
137 {
138     // Check key validity
139     if ( ( keyDec < 0 ) || ( keyDec > MAX_KEY ) )
140         throw new IllegalArgumentException("INVALID KEY");
141
142     // Convert int key into an SDESBits object and create subkey array
143     SDESBits key = new SDESBits( keyDec, KEY_SIZE );
144     SDESBits[] subkeys = new SDESBits[2];
145
146     // P10 permutation, left shift and P8 permutation to form subkey 1
147     key = key.permute( SDESConstants.P10 );
148     key.leftShift(1);
149     subkeys[0] = key.permute( SDESConstants.P8 );
150     // P8 permutation and double left shift to form subkey 2
151     key.leftShift(2);
152     subkeys[1] = key.permute( SDESConstants.P8 );
153
154     return subkeys;
155 }
156
157 //-----
158 //FUNCTION: feistelRound()
159 //IMPORT: message (SDESBits), subkey (SDESBits)
160 //EXPORT: halves (SDESBits)
161 //PURPOSE: Perform feistel key round on message given a subkey
162
163 public static SDESBits feistelRound( SDESBits message, SDESBits subkey )
164 {
165     // Split message in half
166     SDESBits halves[] = message.split();
167     // Perform fMapping function
168     SDESBits fMap = fMapping( halves[1], subkey );
169     // XOR the halves and append
170     halves[0].xor( fMap );
171     halves[0].append(halves[1]);
172     return halves[0];
173 }
174
175 //-----
176 //FUNCTION: fMapping()
177 //IMPORT: message (SDESBits), subkey (SDESBits)
178 //EXPORT: message (SDESBits)
179 //PURPOSE: Perform fMapping function on given message with subkey
180
181 public static SDESBits fMapping( SDESBits message, SDESBits subkey )
182 {
183     // Expansion permutation and XOR with subkey
184     message = message.permute( SDESConstants.EP );
185     message.xor( subkey );
186     // Calculate SBOX values and P4 permutation
187     message = new SDESBits( message.sbox(), MESSAGE_SIZE/2 );
188     message = message.permute( SDESConstants.P4 );
189     return message;
190 }
191
192 //-----
193 }

```