

Deontic Logic

Legal / Normative Reasoning

Deontic Logic

department of mathematics and computer science
FU Berlin

seminar: legal / normative reasoning

docent: Prof. Christoph Benz Müller

speaker: Thomas Harms

Overview

1. Introduction
 1. SDL – Standard Deontic Logic
 2. Weaknesses
 1. CTD Obligations - Chisholm's Paradox
 2. Ross's Paradox
2. Notions of Normative Ideality and Sub-Ideality
 1. Intuitive Idea
 2. SDL Extension – DL
 3. DL Extension – DL*
3. DEON⁺
 1. ALP & CLP
 2. DEON⁺
4. Conclusion

1. Introduction Normative Reasoning

- Norms represent desirable behaviour of members of any society
- Normative systems regulate multi-agent systems.
- While preserving agents autonomy, agents might comply or not
- Problems spawned the very active fields of research of normative multi-agent systems [11]
- Norms are encoded in some logic language
 - Components represent notions of obligation, permission and prohibition
 - One way is by means of modal operators in tradition of Deontic Logic

1. Standard Deontic Logic [1]

- Monadic Modal Logic build around the concepts of obligation, permission, option, impermissibility and omission.
- Basic Deontic Axioms are K, D and TAUT
- SDL is often axiomatized as follows:
 - A1. All tautologous wffs of the language (TAUT)
 - A2. $\mathbf{OB}(p \rightarrow q) \rightarrow (\mathbf{OB}p \rightarrow \mathbf{OB}q)$ (OB-K)
 - A3. $\mathbf{OB}p \rightarrow \sim \mathbf{OB}\sim p$ (OB-D)
 - R1. If $\vdash p$ and $\vdash p \rightarrow q$ then $\vdash q$ (MP)
 - R2. If $\vdash p$ then $\vdash \mathbf{OB}p$ (OB-NEC)

2. Weaknesses of SDL

- Applying Contrary-To-Duty (CTD) norms [10]
- Ross's Paradox [3]
- Paradox of Kant's Law
 - Obligation implies ability. Everything you should do, you must be able to do.
 - 1) If you borrow my car, you are obligated to give it back.
 - 2) You crashed my car.
- Free Choice Permission Paradox

2.1. CTD Norms

- Chisholm's Paradox [8]
- (1) it ought to be that Alice helps her neighbors
- (2) it ought to be that if Alice helps her neighbours, she tells them that she is coming
- (3) if Alice does not help, she ought not to tell them that she is coming
- (4) Alice does not help her neighbours
- Any plausible formalization in SDL turns out to be either inconsistent or not logically independent, which is very undesirable
- Main issue arise from the interpretation of the operator O [12]
 - Semantic intuition of $O(A)$ is that A is true in all normatively ideal worlds

2.1. Ross's Paradox

- Provable schema in SDL is:

$$\mathbf{OA} \rightarrow \mathbf{O(A \vee B)}$$

- **OA**: Bob ought to talk to his wife.
- **O(A \vee B)**: Bob ought to either talk to his wife or kill his wife.
- In a formalization of a normative system the inference is at least difficult to justify.

Notions of Normative Ideality and Sub-Ideality

- Majority of sentences describing propositions true in all normatively ideal circumstances are not normatively relevant.
- Proposal made by Jones, Pörn [12] requires an ‘ought’ sentence to describe a proposition:
 - holds in all normatively ideal circumstances
 - fails in all normatively sub-ideal circumstances
 - fails in those circumstances in which not every prescription is observed
- Alice ought to help the neighbours, then this happens in all normatively ideal scenarios, but fails in some sub-ideal scenario.

SDL Extension - DL

- [12] and [3] extend SDL with an operator O' to distinguish ideal cases
- $O'A$ means: A is true in all normatively sub-ideal worlds.
- Formalization of 'ought'-sentences: **Ought(A)** $=_{\text{def}}$ $OA \wedge \neg O'A$.
- System DL is obtain by adding O' representing bimodal version of SDL supplemented with the axiom-schema: $(OA \wedge \neg O'A) \rightarrow A$. [13]
- Frame to interpret DL are structured as: $\mathbf{F} = \langle \mathbf{W}, \mathbf{R}_O, \mathbf{R}_{O'} \rangle$
 - W – domain of possible worlds
 - R_O and $R_{O'}$ are binary relations over W satisfying the properties:
 - for all $w \in W$, there are $v, u \in W$ s.t. $wR_O v$ and $wR_{O'} u$;
 - for all $w \in W$, $R_O(w) \cap R_{O'}(w) = \emptyset$;
 - for all $w \in W$, either $w \in R_O(w)$ or $w \in R_{O'}(w)$

SDL Extension – DL

- Despite its broader expressive power, DL struggles with some CTD-formalizations.
 - P – Alice helps her neighbours
 - Q – Alice tells her neighbours that she is coming

1. $\text{Ought}(P)$
2. $O(P \rightarrow \text{Ought}(Q)) \wedge O'(P \neg \text{Ought}(Q))$
3. $O(\neg P \rightarrow \text{Ought}(\neg Q)) \wedge O'(\neg P \rightarrow \text{Ought}(\neg Q))$
4. $\neg P$

- Problem is hidden in the fact, that in DL 1-4 entail both OP and $O\neg Q$, meaning Alice helps her neighbors without telling them that she is coming.

SDL Extension – DL

- Certain other paradoxes of deontic reasoning still hold in DL, such as the version of Ross`s paradox [3]:
 - If you neither return my car nor crash it, while you ought to return it, then you ought to return it or crash it.
 - The schema: $(\neg A \wedge \neg B) \rightarrow (\text{Ought}(A) \rightarrow \text{Ought}(A \vee B))$ is provable in DL.
- [13] proposes a system in order to remedy the latter problem by preventing it to be provable.

DL Extension – DL*

- The operator Ought is replaced with an operator **Ought*(A) =_{def} OA ∧ O`¬A**.
- *Ought** will be true at a world only if O`¬A is true there.
- The meaning of O` needs to be altered to: A holds in all *normatively awful* worlds.
- DL* denotes the logic resulting from DL by removing axiom $(OA \wedge \neg O`A) \rightarrow A$ and adding the definition of *Ought**.
- The pragmatic oddity of Chisholm's paradox is still holding in some formalizations.

Abductive Logic Programming (ALP) & Constraint

- Abductive Reasoning – truth value of premises is not bound to truth value of conclusion.
- In an abductive logic program, a distinguished set of predicates, called abducibles, do not have a definition, but their truth value can be assumed.
- A set of formulae, called *Integrity Constraints*, restrict the set of hypotheses in order to avoid unrealistic hypotheses.
- ALP supports hypothetical reasoning and simple, sound implementation of negation by failure.

Deon⁺ - Introduction [2]

- Language where two basic operators (obligation, prohibition) are enriched with quantification over time.
- Syntax is built upon action language, where positive actions are represented by terms, e.g. *answer/2*, *smoke/1*, *use/2*, *drive/2*.
- Terms can contain terms, variables and constants, e.g. *answer(john, me)* stands for the action of answering me, performed by John.
- Negative actions are represented by *not(Action)*, e.g. *not respect(john, speedlimit))*.

Deon⁺ - Obligation [2]

- Obligation are represented as formulas: $obl(A, T)$, where $obl/2$ is an abducible predicate, A is any (positive or negative) action and T is a CLP variable possibly (existentially or universally) quantified.
- “It is mandatory, that John answer me”: $\exists T \text{ } obl(answer(john, me), T)$
- “It is mandatory, John respects the speed limits”: $\forall T \text{ } obl(respect(john, speed\ limit), T)$

Deon⁺ - Prohibition [2]

- Similar to obligation, prohibitions are represented as formulas: $forb(A, T)$, where $forb/2$ is an abducible predicate, A is any (positive or negative) action and T is a CLP variable possibly explicitly (existentially or universally) quantified.
- “A process p cannot consume all the CPU time”: $\exists T forb(use(p, cpu), T)$
- “It is forbidden that John smokes”: $\forall T forb(smoke(john), T)$

Deon⁺ - Variables and Constraints [2]

- Language is not limited to the propositional case, as variables can be included possibly explicitly quantified, e.g. “It is forbidden to smoke”: $\forall X, \forall T, \text{forb}(\text{smoke}(X), T)$.
- Adoption of CLP variables for representing time adds expressiveness to deontic operators, e.g. covering deadlines by constraints over time.
 - “It is forbidden that John leaves the meeting before 10”:

$$\forall T : T < 10 \text{ forb}(\text{leave}(\text{john}, \text{meeting}), T)$$
 - “It is forbidden, that John leaves the meeting before it ends”:

$$\exists T', \forall T : T < T' \text{ forb}(\text{leave}(\text{john}, \text{meeting}), T), \text{end}(\text{meeting}, T')$$

Deon⁺ - Syntax [2]

Definition: A Deon⁺ specification consists of an (abductive) logic programming set of clauses (P), a set of integrity constraints (IC), and a goal (G). A set of meta-level integrity constraints (M) can be added to express or vary the semantics of deontic operators.

- Syntax of deontic literals:
 - $\text{DeonticLiteral} ::= [\text{not}] \text{DeonticAtom}$
 - $\text{DeonticAtom} ::= \text{obl}(\text{Term}, \text{Time})$
 - $\text{DeonticAtom} ::= \text{forb}(\text{Term}, \text{Time})$
 - $\text{Time} ::= \text{Variable} \mid \text{Number}$

Deon⁺ - Syntax [2]

- Syntax of P and IC:
 - $P ::= [\text{Clause}]^*$
 - $\text{Clause} ::= \text{Atom} \leftarrow \text{QConjunction}.$
 - $\text{IC} ::= [\text{IntegrityConstraint}]^*$
 - $\text{QConjunction} ::= [\text{ExistentialQ}]^* [\text{UniversalQ}]^* \text{Conjunction}$
 - $\text{Conjunction} ::= \text{Literal}, \text{Conjunction} \mid \text{Literal}$
 - $\text{ExistentialQ} ::= \exists V \text{ variable}[: \text{Constraints}]$
 - $\text{UniversalQ} ::= \forall V \text{ variable}[: \text{Constraints}]$
 - $\text{Constraints} ::= \text{Constraint} \mid \text{Constraint}, \text{Constraints}$
 - $\text{Literal} ::= \text{DeonticLiteral} \mid \text{Constraint} \mid \text{DefinedLiteral}$
 - $\text{IntegrityConstraint} ::= \text{QConjunction} \rightarrow \text{Disjunction}.$
 - $\text{Disjunction} ::= \text{false} \mid \text{QConjunction} \mid \text{QConjunction} \vee \text{Disjunction}$
 - $G ::= \leftarrow \text{QConjunction}$

Deon⁺ - Conditional Obligations and Deadlines [2]

- Integrity constraints can be exploited to represent conditional obligatoriness and the deontic logic of deadlines.
- Conditional obligations can be simply represented by integrity constraints:
 - e.g. $B \rightarrow \text{Obl } A$ is suitable to represent dyadic deontic operator $\text{Obl}(A|B)$ [2],[6]
- Deontic logics with deadlines and the operator $O(\rho \leq \delta)$ meaning that action ρ ought to be brought about before another action δ happens.
 - mapped into integrity constraint: $\text{hap}(\delta, T_\delta) \rightarrow \text{obl}(\rho, T_\rho : T_\rho \leq T_\delta)$

Conclusions

- In order to tackle the usual weaknesses (paradoxes) of SDL we discussed 2 major perspectives by adding expressiveness to deontic operators:
- Distinguishing between normative ideality and sub-ideality in different forms such as DL and DL*.
- Formalization of a language Deon⁺ by exploiting Abductive Logic Programming and Constraint Logic Programming to add precision towards deontic logic operators and expressivity.

Sources

1. <https://plato.stanford.edu/entries/logic-deontic/>, 12.01.2020
2. Marco Alberti, Marco Gavanelli, Evelina Lamma: "Deon+: Abduction and Constraints for Normative Reasoning"; Chapter out of: A. Artkiss, R. Craven, N Kesim, B. Sadighi, K. Stathis: "logic programs, norms and action, Essays in honor of Marek J. Sergot on the occasion of his 60th birthday", Springer 2012, DOI 10.1007 /978-3-642-29414-3_17
3. Tomer Libal, Mateo Pascucci: "Automated Reasoning in Normative Detachment Structures with Ideal Conditions", 10/2018, <http://arxiv.org/pdf/1810.09993>
4. Christoph Benzmüller, Ali Farjami, Xavier Parent, "A Faithful Semantic Embedding of the Dyadic Deontic Logic in HOL", 2018, <https://christoph-benzmueller.de/papers/R59.pdf>
5. Giada Maggenti, Andrea Bracciali, Paolo Mancarella: "Abduction and Legal Reasoning", 2008

Sources

6. Christoph Benzmüller, Ali Farjami, Xavier Parent: A Dyadic Deontic Logic in HOL, In Deontic Logic and Normative Systems --- 14th International Conference, DEON 2018, Utrecht, The Netherlands, 3-6 July, 2018 (Jan Broersen, Cleo Condoravdi, Shyam Nair, Gabriella Pigozzi, eds.), College Publications, volume 9706, pp. 33-50, 2018
7. J. Carmo and A.J.I. Jones. Completeness and decidability results for a logic of contrary-to-duty conditionals. J. Log. Comput., 23(3):585–626, 2013
8. R.M. Chisholm. Contrary-to-duty imperatives and deontic logic. Analysis, 24:33–36, 1963
9. J. Carmo and A.J.I. Jones. Deontic logic and contrary-to-duties. In D. M. Gabbay and F. Guenther, editors, Handbook of Philosophical Logic: Volume 8, pages 265–343. Springer, Netherlands, Dordrecht, 2002
10. Navarro, P.E. and Rodriguez J.L. (2014) 'Deontic logic and legal systems'. Cambridge University Press

Sources

11. Boella, G., van der Torre, L., Verhagen, H.: Introduction to normative multiagent systems. *Computational and Mathematical Organization Theory* 12, 71–79 (2006)
12. Jones, A. and Pörn, I. (1985), Ideality, sub-ideality and deontic logic. *Synthese* 65(2), 275-290
13. de Boer, M., Gabbay, D.M., Parent, X. and Slavkovic, M. (2012), `Two dimensional Standard Deontic Logic [including a detailed analysis of the 1985 Jones-Pörn deontic logic system]`. *Synthese* 187(2), 623-660

