



Melville® 60 Slabs




 **Pedestrian** - Designed to withstand pedestrian traffic

Melville® 60 Slabs

	Dimensions (mm)	Dimensions (in)
A	60 x 190 x 380	2 3/8 x 7 1/2 x 15
B	60 x 380 x 380	2 3/8 x 15 x 15
C	60 x 380 x 570	2 3/8 x 15 x 22 7/16
Weight/unit (avg.)	20 kg	44 lbs
Area/unit (avg.)	0.14 m ²	1.55 ft ²
Area/layer	0.87 m ²	9.33 ft ²
Area/cube	10.44 m ²	111.96 ft ²
Qty/cube	72 units	72 units
Weight/cube	1465 kg	3225 lbs




Colours


Codes	Colours
PRESTIGE COLOURS	
12053046	Range Amber Beige 
12052732	Rockland Black
12052365	Range Scandina Grey
12052734	Range Margaux Beige
STANDARD COLOURS	
12053045	Range Shaded Grey 
12051945	Range Habano Brown 
12052364	Range Savannah Beige
12052733	Range Newport Grey

Can be double stacked.


Typical row



Laying Patterns



MODULAR PATTERN



LINEAR PATTERN

Notes

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards.

Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.

The Melville 60 slab is compatible with the Melville 60 small rectangle paver for non-vehicular application only.

