![SGS-THOMSON MICROELECTRONICS logo]

HCC/HCF4027B

DUAL-J-K MASTER-SLAVE FLIP-FLOP

- SET-RESET CAPABILITY
- STATIC FLIP-FLOP OPERATION - RETAINS STATE INDEFINITELY WITH CLOCK LEVEL EITHER "HIGH" OR "LOW"
- MEDIUM SPEED OPERATION - 16MHz (typ. clock toggle rate at 10V)
- STANDARDIZED SYMMETRICAL OUTPUT CHARACTERISTICS
- QUIESCENT CURRENT SPECIFIED TO 20V FOR HCC DEVICE
- INPUT CURRENT OF 100nA AT 18V AND 25°C FOR HCC DEVICE
- 100% TESTED FOR QUIESCENT CURRENT
- MEETS ALL REQUIREMENTS OF JEDEC TENTATIVE STANDARD N[0]. 13A, "STANDARD SPECIFICATIONS FOR DESCRIPTION OF "B" SERIES CMOS DEVICES".

EY
(Plastic Package)

F
(Ceramic Frit Seal Package)

M1
(Micro Package)

C1
(Plastic Chip Carrier)

ORDER CODES :

|	
HCC4027BF	HCF4027BM1
HCF4027BEY	HCF4027BC1

DESCRIPTION

The **HCC4027B** (extended temperature range) and **HCF4027B** (intermediate temperature range) are monolithic integrated circuit, available in 16-lead dual in-line plastic or ceramic package and plastic micro package.

The **HCC/HCF4027B** is a single monolithic chip integrated circuit containing two identical complementary-symmetry J-K master-slave flip-flops. Each flip-flop has provisions for individual J, K, Set, Reset, and Clock input signals, Buffered Q and $\overline{Q}$ signals are provided as outputs. This input-output arrangement provides for compatible operation with the **HCC/HCF4013B** dual D-type flip-flop.

The **HCC/HCF4027B** is useful in performing control, register, and toggle functions. Logic levels present at the J and K inputs along with internal self-steering control the state of each flip-flop ; changes in the flip-flop state are synchronous with the positive-going transition of the clock pulse. Set and reset functions are independent of the clock and are initiated when a high level signal is present at either the Set or Reset input.

PIN CONNECTIONS

Q2	1	16	V_DD
$\overline{Q2}$	2	15	Q1
CLOCK 2	3	14	$\overline{Q1}$
RESET 2	4	13	CLOCK 1
K 2	5	12	RESET 1
J 2	6	11	K 1
SET 2	7	10	J 1
V_SS	8	9	SET 1

S-2403

FUNCTIONAL DIAGRAM

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{DD}*	Supply Voltage : **HCC** Types **HCF** Types	-0.5 to $+20$ -0.5 to $+18$	V V
V_i	Input Voltage	-0.5 to $V_{DD} + 0.5$	V
I_I	DC Input Current (any one input)	± 10	mA
P_{tot}	Total Power Dissipation (per package) Dissipation per Output Transistor for T_{op} = Full Package-temperature Range	200 100	mW mW
T_{op}	Operating Temperature : **HCC** Types **HCF** Types	-55 to $+125$ -40 to $+85$	°C °C
T_{stg}	Storage Temperature	-65 to $+150$	°C

Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for external periods may affect device reliability.
* All voltage values are referred to V$_{SS}$ pin voltage .

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Value	Unit
V_{DD}	Supply Voltage : **HCC** Types **HCF** Types	3 to 18 3 to 15	V V
V_I	Input Voltage	0 to V_{DD}	V
T_{op}	Operating Temperature : **HCC** Types **HCF** Types	-55 to $+125$ -40 to $+85$	°C °C

SGS-THOMSON
MICROELECTRONICS

LOGIC DIAGRAM AND TRUTH TABLE

ONE OF TWO IDENTICAL J-K FLIP-FLOPS

TRUTH TABLE

Present State					CL$^\triangle$	Next State		
Inputs				Output		Outputs		
J	K	S	R	Q		Q	$\overline{Q}$	
I	X	O	O	O	_⌐	I	O	
X	O	O	O	I	_⌐	I	O	
O	X	O	O	O	_⌐	O	I	
X	I	O	O	I	_⌐	O	I	
X	X	O	O	X	⌐_			← No Change
X	X	I	O	X	X	I	O	
X	X	O	I	X	X	O	I	
X	X	I	I	X	X	I	I	

LOGIC I = HIGH LEVEL
LOGIC O = LOW LEVEL
∆ - LEVEL CHANGE
X - DON'T CARE

SGS-THOMSON
MICROELECTRONICS

STATIC ELECTRICAL CHARACTERISTICS (over recommended operating conditions)

Symbol	Parameter	Type	V_I (V)	V_O (V)	|I_O| (µA)	V_DD (V)	T_Low* Min.	T_Low* Max.	25°C Min.	25°C Typ.	25°C Max.	T_High* Min.	T_High* Max.	Unit
I_L	Quiescent Current		0/ 5			5		1		0.02	1		30	µA
		HCC Types	0/10			10		2		0.02	2		60	
			0/15			15		4		0.02	4		120	
			0/20			20		20		0.04	20		600	
		HCF Types	0/ 5			5		4		0.02	4		30	
			0/10			10		8		0.02	8		60	
			0/15			15		16		0.02	16		120	
V_{OH}	Output High Voltage		0/ 5		< 1	5	4.95		4.95			4.95		V
			0/10		< 1	10	9.95		9.95			9.95		
			0/15		< 1	15	14.95		14.95			14.95		
V_{OL}	Output Low Voltage		5/0		< 1	5		0.05			0.05		0.05	V
			10/0		< 1	10		0.05			0.05		0.05	
			15/0		< 1	15		0.05			0.05		0.05	
V_{IH}	Input High Voltage			0.5/4.5	< 1	5	3.5		3.5			3.5		V
				1/9	< 1	10	7		7			7		
				1.5/13.5	< 1	15	11		11			11		
V_{IL}	Input Low Voltage			4.5/0.5	< 1	5		1.5			1.5		1.5	V
				9/1	< 1	10		3			3		3	
				13.5/1.5	< 1	15		4			4		4	
I_{OH}	Output Drive Current		0/ 5	2.5		5	− 2		− 1.6		− 3.2	− 1.15		mA
		HCC Types	0/ 5	4.6		5	− 0.64		− 0.51		− 1	− 0.36		
			0/10	9.5		10	− 1.6		− 1.3		− 2.6	− 0.9		
			0/15	13.5		15	− 4.2		− 3.4		− 6.8	− 2.4		
		HCF Types	0/ 5	2.5		5	− 1.53		− 1.36		− 3.2	− 1.1		
			0/ 5	4.6		5	− 0.52		− 0.44		− 1	− 0.36		
			0/10	9.5		10	− 1.3		− 1.1		− 2.6	− 0.9		
			0/15	13.5		15	− 3.6		− 3.0		− 6.8	− 2.4		
I_{OL}	Output Sink Current	HCC Types	0/ 5	0.4		5	0.64		0.51		1	0.36		mA
			0/10	0.5		10	1.6		1.3		2.6	0.9		
			0/15	1.5		15	4.2		3.4		6.8	2.4		
		HCF Types	0/ 5	0.4		5	0.52		0.44		1	0.36		
			0/10	0.5		10	1.3		1.1		2.6	0.9		
			0/15	1.5		15	3.6		3.0		6.8	2.4		
I_{IH}, I_{IL}	Input Leakage Current	HCC Types	0/18 Any Input			18		± 0.1		$±10^{-5}$	± 0.1		± 1	µA
		HCF Types	0/15			15		± 0.3		$±10^{-5}$	± 0.3		± 1	
C_I	Input Capacitance		Any Input							5	7.5			pF

* T_{Low} = − 55°C for **HCC** device : − 40°C for **HCF** device.
* T_{High} = + 125°C for **HCC** device : + 85°C for **HCF** device.
The Noise Margin for both "1" and "0" level is : 1V min. with V_{DD} = 5V, 2V min. with V_{DD} = 10V, 2.5 V min. with V_{DD} = 15V.

SGS-THOMSON MICROELECTRONICS

DYNAMIC ELECTRICAL CHARACTERISTICS ($T_{amb} = 25°C$, $C_L = 50pF$, $R_L = 200k\Omega$, typical temperature coefficient for all $V_{DD} = 0.3\%/°C$ values, all input rise and fall time = 20ns)

| Symbol	Parameter		Test Conditions		Value			Unit
				V_{DD} (V)	Min.	Typ.	Max.	
t_{PLH}, t_{PHL}	Propagation Delay Time	Clock to Q or $\overline{Q}$ Outputs		5		150	300	ns
				10		65	130	
				15		45	90	
t_{PLH}	Propagation Delay Time	Set to Q or Reset to $\overline{Q}$		5		150	300	ns
				10		65	130	
				15		45	90	
t_{PHL}	Propagation Delay Time	Set to $\overline{Q}$ or Reset to Q		5		200	400	
				10		85	170	
				15		60	120	
t_{THL}, t_{TLH}	Transition Time			5		100	200	ns
				10		50	100	
				15		40	80	
t_W	Pulse Width	Clock		5	140	70		ns
				10	60	30		
				15	40	20		
t_W	Pulse Width	Set or Reset		5	180	90		
				10	80	40		
				15	50	25		
t_r, t_f	Clock Input Rise or Fall Time			5			15	µs
				10			4	
				15			1	
t_{setup}	Setup Time	Data		5	200	100		ns
				10	75	35		
				15	50	25		
f_{max}	Maximum Clock Input Frequency *	Toggle Mode		5	3.5	7		MHz
				10	8	16		
				15	12	24		

* Input tr, tf = 5ns.

**SGS-THOMSON**
MICROELECTRONICS

Typical Output Low (sink) Current Characteristics.

Minimum Output Low (sink) Current Characteristics.

Typical Output High (source) Current Characteristics.

Minimum Output High (source) Current Characteristics.

Typical Propagation Delay Time vs.Load Capacitance (CLOCK or SET to Q, CLOCK or RESET to Q̄).

Typical Propagation Delay Time vs. Load Capacitance (SET to Q̄ or RESET to Q).

SGS-THOMSON
MICROELECTRONICS

Typical Maximum Clock Frequency vs. Supply Voltage (Toggle Mode).

Typical Dynamic Power Dissipation/ Per Device vs.Frequency.

TEST CIRCUITS

Quiescent Device Current.

Input Voltage.

Input Leakage Current.

SGS-THOMSON
MICROELECTRONICS

Plastic DIP16 (0.25) MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
a1	0.51			0.020		
B	0.77		1.65	0.030		0.065
b		0.5			0.020	
b1		0.25			0.010	
D			20			0.787
E		8.5			0.335	
e		2.54			0.100	
e3		17.78			0.700	
F			7.1			0.280
I			5.1			0.201
L		3.3			0.130	
Z			1.27			0.050

P001C

SGS-THOMSON
MICROELECTRONICS

Ceramic DIP16/1 MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A			20			0.787
B			7			0.276
D		3.3			0.130	
E	0.38			0.015		
e3		17.78			0.700	
F	2.29		2.79	0.090		0.110
G	0.4		0.55	0.016		0.022
H	1.17		1.52	0.046		0.060
L	0.22		0.31	0.009		0.012
M	0.51		1.27	0.020		0.050
N			10.3			0.406
P	7.8		8.05	0.307		0.317
Q			5.08			0.200

P053D

SGS-THOMSON
MICROELECTRONICS

SO16 (Narrow) MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A			1.75			0.068
a1	0.1		0.2	0.004		0.007
a2			1.65			0.064
b	0.35		0.46	0.013		0.018
b1	0.19		0.25	0.007		0.010
C		0.5			0.019	
c1	45° (typ.)					
D	9.8		10	0.385		0.393
E	5.8		6.2	0.228		0.244
e		1.27			0.050	
e3		8.89			0.350	
F	3.8		4.0	0.149		0.157
G	4.6		5.3	0.181		0.208
L	0.5		1.27	0.019		0.050
M			0.62			0.024
S	8° (max.)					

P013H

SGS-THOMSON
MICROELECTRONICS

PLCC20 MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	9.78		10.03	0.385		0.395
B	8.89		9.04	0.350		0.356
D	4.2		4.57	0.165		0.180
d1		2.54			0.100	
d2		0.56			0.022	
E	7.37		8.38	0.290		0.330
e		1.27			0.050	
e3		5.08			0.200	
F		0.38			0.015	
G			0.101			0.004
M		1.27			0.050	
M1		1.14			0.045	

P027A

SGS-THOMSON
MICROELECTRONICS

SGS-THOMSON
MICROELECTRONICS