DATA SHEET

For a complete data sheet, please also download:

- The IC04 LOCMOS HE4000B Logic
  Family Specifications HEF, HEC

- The IC04 LOCMOS HE4000B Logic
  Package Outlines/Information HEF, HEC

HEF4555B
MSI
Dual 1-of-4 decoder/demultiplexer

Product specification

File under Integrated Circuits, IC04

January 1995

**Philips
Semiconductors**

PHILIPS

Dual 1-of-4 decoder/demultiplexer

HEF4555B
MSI

DESCRIPTION

The HEF4555B is a dual 1-of-4 decoder/demultiplexer. Each has two address inputs (A_0 and A_1), an active LOW enable input ($\overline{E}$) and four mutually exclusive outputs which are active HIGH (O_0 to O_3). When used as a decoder, $\overline{E}$ when HIGH, forces O_0 to O_3 LOW. When used as a demultiplexer, the appropriate output is selected by the information on A_0 and A_1 with $\overline{E}$ as data input. All unselected outputs are LOW.

Fig.1 Functional diagram.

Fig.2 Pinning diagram.

HEF4555BP(N): 16-lead DIL; plastic
(SOT38-1)
HEF4555BD(F): 16-lead DIL; ceramic (cerdip)
(SOT74)
HEF4555BT(D): 16-lead SO; plastic
(SOT109-1)
( ): Package Designator North America

PINNING

$\overline{E}$	enable inputs (active LOW)
A_0 and A_1	address inputs
O_0 to O_3	outputs (active HIGH)

FAMILY DATA, I_{DD} LIMITS category MSI

See Family Specifications

Dual 1-of-4 decoder/demultiplexer

Fig.3 Logic diagram (one decoder/multiplexer).

TRUTH TABLE

INPUTS			OUTPUTS			
$\overline{E}$	A_0	A_1	O_0	O_1	O_2	O_3
L	L	L	H	L	L	L
L	H	L	L	H	L	L
L	L	H	L	L	H	L
L	H	H	L	L	L	H
H	X	X	L	L	L	L

Notes

1. H = HIGH state (the more positive voltage)

2. L = LOW state (the less positive voltage)

3. X = state is immaterial

AC CHARACTERISTICS

$V_{SS} = 0$ V; $T_{amb} = 25$ °C; $C_L = 50$ pF; input transition times ≤ 20 ns

	V_{DD} V	SYMBOL	MIN.	TYP.	MAX.		TYPICAL EXTRAPOLATION FORMULA
Propagation delays							
$A_n \rightarrow O_n$	5			115	230	ns	88 ns + (0,55 ns/pF) C_L
HIGH to LOW	10	t_{PHL}		45	90	ns	34 ns + (0,23 ns/pF) C_L
	15			30	65	ns	22 ns + (0,16 ns/pF) C_L
	5			140	280	ns	113 ns + (0,55 ns/pF) C_L
LOW to HIGH	10	t_{PLH}		55	105	ns	44 ns + (0,23 ns/pF) C_L
	15			40	75	ns	32 ns + (0,16 ns/pF) C_L
$\overline{E}_n \rightarrow O_n$	5			125	250	ns	98 ns + (0,55 ns/pF) C_L
HIGH to LOW	10	t_{PHL}		50	95	ns	39 ns + (0,23 ns/pF) C_L
	15			30	65	ns	22 ns + (0,16 ns/pF) C_L
	5			150	295	ns	123 ns + (0,55 ns/pF) C_L
LOW to HIGH	10	t_{PLH}		55	110	ns	44 ns + (0,23 ns/pF) C_L
	15			40	75	ns	32 ns + (0,16 ns/pF) C_L
Output transition times	5			60	120	ns	10 ns + ((1,0 ns/pF) C_L
HIGH to LOW	10	t_{THL}		30	60	ns	9 ns + (0,42 ns/pF) C_L
	15			20	40	ns	6 ns + (0,28 ns/pF) C_L
	5			60	120	ns	10 ns + (1,0 ns/pF) C_L
LOW to HIGH	10	t_{TLH}		30	60	ns	9 ns + (0,42 ns/pF) C_L
	15			20	40	ns	6 ns + (0,28 ns/pF) C_L

	V_{DD} V	TYPICAL FORMULA FOR P (μW)	
Dynamic power	5	$4500\, f_i + \sum (f_o C_L) \times V_{DD}^2$	where
dissipation per	10	$18\,800\, f_i + \sum (f_o C_L) \times V_{DD}^2$	f_i = input freq. (MHz)
package (P)	15	$45\,700\, f_i + \sum (f_o C_L) \times V_{DD}^2$	f_o = output freq. (MHz)
			C_L = load capacitance (pF)
			$\sum (f_o C_L)$ = sum of outputs
			V_{DD} = supply voltage (V)

APPLICATION INFORMATION

Some examples of applications for the HEF4555B are:

- Code conversion.
- Address decoding.
- Demultiplexing: when using the enable input as data input.