DATA SHEET

For a complete data sheet, please also download:

• The IC04 LOCMOS HE4000B Logic
  Family Specifications HEF, HEC

• The IC04 LOCMOS HE4000B Logic
  Package Outlines/Information HEF, HEC

HEF4086B
gates
4-wide 2-input AND-OR-invert gate

Product specification

File under Integrated Circuits, IC04

January 1995

Philips
Semiconductors

PHILIPS

PHILIPS

4-wide 2-input AND-OR-invert gate

HEF4086B
gates

DESCRIPTION

The HEF4086B is a 4-wide 2-input AND-OR-invert (AOI) gate with two additional inputs (I_8 or $\bar{I}_9$) which can be used as either expander or inhibit inputs by connecting them to any standard LOCMOS output. A HIGH on I_8 or a LOW on $\bar{I}_9$ forces the output (O) LOW independent of the other eight inputs (I_0 to I_7). The output (O) is fully buffered for highest noise immunity and pattern insensitivity of output impedance.


Fig.2 Pinning diagram.

HEF4086BP(N):   14-lead DIL; plastic
                         (SOT27-1)
HEF4086BD(F):   14-lead DIL; ceramic (cerdip)
                         (SOT73)
HEF4086BT(D):   14-lead SO; plastic
                         (SOT108-1)
( ): Package Designator North America

Fig.1 Functional diagram.

PINNING

I_0 to I_8	gate inputs
$\bar{I}_9$	gate input (active LOW)
O	output (active LOW)

FAMILY DATA, I_{DD} LIMITS category GATES

See Family Specifications

4-wide 2-input AND-OR-invert gate

Fig.3 Logic diagram.

LOGIC EQUATION

$$O = \overline{I_0 \cdot I_1 + I_2 \cdot I_3 + I_4 \cdot I_5 + I_6 \cdot I_7 + I_8 + I_9}$$

4-wide 2-input AND-OR-invert gate

AC CHARACTERISTICS

V_{SS} = 0 V; T_{amb} = 25 °C; C_L = 50 pF; input transition times ≤ 20 ns

	V_{DD} V	SYMBOL	TYP.	MAX.		TYPICAL EXTRAPOLATION FORMULA
Propagation delays						
I_0 to $I_7 \rightarrow$ O	5		90	180	ns	63 ns + (0,55 ns/pF) C_L
HIGH to LOW	10	t_{PHL}	30	65	ns	19 ns + (0,23 ns/pF) C_L
	15		20	40	ns	12 ns + (0,16 ns/pF) C_L
	5		80	155	ns	53 ns + (0,55 ns/pF) C_L
LOW to HIGH	10	t_{PLH}	30	60	ns	19 ns + (0,23 ns/pF) C_L
	15		20	40	ns	12 ns + (0,16 ns/pF) C_L
$I_8 \rightarrow$ O	5		70	140	ns	43 ns + (0,55 ns/pF) C_L
HIGH to LOW	10	t_{PHL}	25	55	ns	14 ns + (0,23 ns/pF) C_L
	15		20	40	ns	12 ns + (0,16 ns/pF) C_L
	5		55	115	ns	28 ns + (0,55 ns/pF) C_L
LOW to HIGH	10	t_{PLH}	20	40	ns	9 ns + (0,23 ns/pF) C_L
	15		15	25	ns	7 ns + (0,16 ns/pF) C_L
$\overline{I}_9 \rightarrow$ O	5		55	105	ns	28 ns + (0,55 ns/pF) C_L
HIGH to LOW	10	t_{PHL}	20	45	ns	9 ns + (0,23 ns/pF) C_L
	15		15	30	ns	7 ns + (0,16 ns/pF) C_L
	5		45	90	ns	18 ns + (0,55 ns/pF) C_L
LOW to HIGH	10	t_{PLH}	15	35	ns	4 ns + (0,23 ns/pF) C_L
	15		10	25	ns	2 ns + (0,16 ns/pF) C_L
Output transition times	5		60	120	ns	10 ns + (1,0 ns/pF) C_L
HIGH to LOW	10	t_{THL}	30	60	ns	9 ns + (0,42 ns/pF) C_L
	15		20	40	ns	6 ns + (0,28 ns/pF) C_L
	5		60	120	ns	10 ns + (1,0 ns/pF) C_L
LOW to HIGH	10	t_{TLH}	30	60	ns	9 ns + (0,42 ns/pF) C_L
	15		20	40	ns	6 ns + (0,28 ns/pF) C_L

	V_{DD} V	TYPICAL FORMULA FOR P (μW)	
Dynamic power	5	525 f_i + Σ ($f_o C_L$) × V_{DD}^2	where
dissipation per	10	2600 f_i + Σ ($f_o C_L$) × V_{DD}^2	f_i = input freq. (MHz)
package (P)	15	7300 f_i + Σ ($f_o C_L$) × V_{DD}^2	f_o = output freq. (MHz)
			C_L = load capacitance (pF)
			Σ ($f_o C_L$) = sum of outputs
			V_{DD} = supply voltage (V)

4-wide 2-input AND-OR-invert gate

APPLICATION INFORMATION

Figure 4 shows two HEF4086B ICs connected to obtain an 8-wide 2-input AOI function.
The output (O_A) of the first IC is fed directly into the $\bar{I}_{9B}$ gate input of the second IC. Similarly,
any NAND gate output can be fed directly into the $\bar{I}_9$ gate input to obtain a 5-wide AOI function.
In addition, any AND gate output can be fed directly into the I_8 gate input with the same result.


Fig.4 Two HEF4086B ICs connected as an 8-wide 2-input AOI gate.

Logic equation for Fig.4:

$$O_B = \overline{I_{0A} \cdot I_{1A} + I_{2A} \cdot I_{3A} + I_{4A} \cdot I_{5A} + I_{6A} \cdot I_{7A} + I_{0B} \cdot I_{1B} + I_{2B} \cdot I_{3B} + I_{4B} \cdot I_{5B} + I_{6B} \cdot I_{7B}}$$