

simulation & inference of transients

Carl Boettiger, Jorge Arroyo Esquivel, Junjie Jiang, Jody Reimer, Henry Scharf, Elizabeth Wolkovich, and Kai Zhu


2019-09-10

```
library(tidyverse)
library(parallel)
library(nimble)
```


```
N <- 1e4
r <- 0.05; K <- 2
a <- 0.023; H <- 0.3; Q <- 3
x0 <- 0.2; sigma <- 0.02
growth <- function(x, r, K) x * r * (1 - x / K)
consumption <- function(x, a, H, Q) a * x^Q / (x^Q + H^Q)
```

```
theory <-
  tibble(x = seq(0,K, length.out = 100)) %>%
  mutate(g = growth(x, r, K),
         c = consumption(x, a, H, Q)) %>%
  mutate(potential = - cumsum(g - c)) %>%
  gather(curve, y, -x, -potential)
```

```
theory %>%
  ggplot(aes(x, y, col = curve)) +
  geom_line(lwd = 1)
```



```
theory %>%  
  ggplot(aes(x, potential)) +  
  geom_line(lwd = 1)
```



```
## define truncated normal distribution ----
dtruncnorm <- nimbleFunction(
  run = function(x = double(0), mean = double(0),
                 sd = double(0), log = integer(0, default = 0)) {
    returnType(double(0))
    log_prob <- dnorm(x = x, mean = mean, sd = sd, log = 1) -
      pnorm(q = 0, mean = -mean, sd = sd, log = 1)
    if(log) return(log_prob)
    else return(exp(log_prob))
  })

rtruncnorm <- nimbleFunction(
  run = function(n = integer(0, default = 1), mean = double(0),
                 sd = double(0)) {
    returnType(double(0))
    if(n != 1) print("rtruncnorm only allows n = 1; using n = 1.")
    draw <- rnorm(n = 1, mean = mean, sd = sd)
    while(draw < 0)
      draw <- rnorm(n = 1, mean = mean, sd = sd)
    return(draw)
  })

# Define stochastic model in BUGS notation ----
may <- nimble::nimbleCode({
  log(r) ~ dnorm(mu_r, sd_r)
  log(K) ~ dnorm(mu_K, sd_K)
  log(a) ~ dnorm(mu_a, sd_a)
  log(H) ~ dnorm(mu_H, sd_H)
  log(Q) ~ dnorm(mu_Q, sd_Q)
})
```

```

x0 ~ dtruncnorm(mu_x0, sd_x0)
log(sigma) ~ dnorm(mu_sigma, sd_sigma)
x[1] <- x0
for(t in 1:(N - 1)){
  mu[t] <- x[t] + x[t] * r * (1 - x[t] / K) - a * x[t]^Q / (x[t]^Q + H^Q)
  x[t + 1] ~ dtruncnorm(mean = mu[t], sd = sigma)
}
})
# constants ----
constants <- list(
  N = N,
  mu_r = log(r), sd_r = 1,
  mu_K = log(K), sd_K = 1,
  mu_a = log(a), sd_a = 1,
  mu_H = log(H), sd_H = 1,
  mu_Q = log(Q), sd_Q = 1,
  mu_x0 = x0, sd_x0 = 1,
  mu_sigma = log(sigma), sd_sigma = 1
)
## inits ----
inits <- list("log_r" = log(r), "log_K" = log(K),
             "log_a" = log(a), "log_H" = log(H), "log_Q" = log(Q),
             "log_sigma" = log(sigma), "x0" = x0)
# define and compile model ----
model <- nimbleModel(code = may, constants = constants, inits = inits)

```

defining model...

Registering the following user-provided distributions: dtruncnorm .

NIMBLE has registered dtruncnorm as a distribution based on its use in BUGS code. Note that if you m

building model...

setting data and initial values...

running calculate on model (any error reports that follow may simply reflect missing values in model

checking model sizes and dimensions... This model is not fully initialized. This is not an error. To

model building finished.

```
cmodel <- compileNimble(model)
```

compiling... this may take a minute. Use 'showCompilerOutput = TRUE' to see C++ compilation details.


compilation finished.

```
set.seed(1)
```

```
simulate(cmodel, nodes = c('x', 'mu'))
```

```
df <- tibble(t = seq_along(cmodel$x), x = cmodel$x)
```

```
df %>% filter(t < 4000) %>% ggplot(aes(t, x)) + geom_line()
```



```
dnorm_mod <- function(x, mean, sd, log = T){
  dnorm(x = x, mean = mean, sd = sd, log = log) -
    log(1 - pnorm(q = 0, mean = mean, sd = sd))
}

get_ll <- function(x, r, K, a, H, Q, sigma){
  TIME <- length(x)
  mu <- x + x * r * (1 - x / K) - a * x^Q / (x^Q + H^Q)
  sum(dnorm_mod(x = x[-1], mean = mu[-TIME], sd = sigma, log = T))
}

##
grid_r <- seq(1e-2, 1e-1, l=5e1)
ll_r <- sapply(grid_r, function(r) get_ll(a = cmodel$a, x = cmodel$x, r = r, K = cmodel$K,
                                          H = cmodel$H, Q = cmodel$Q, sigma = cmodel$sigma))

##
grid_K <- seq(1, 5, l=5e1)
ll_K <- sapply(grid_K, function(K) get_ll(a = cmodel$a, x = cmodel$x, r = cmodel$r, K = K,
                                          H = cmodel$H, Q = cmodel$Q, sigma = cmodel$sigma))

##
grid_a <- seq(1e-3, 1e-1, l=5e1)
ll_a <- sapply(grid_a, function(a) get_ll(a = a, x = cmodel$x, r = cmodel$r, K = cmodel$K,
                                          H = cmodel$H, Q = cmodel$Q, sigma = cmodel$sigma))

##
grid_H <- exp(seq(log(1e-2), log(0.7), l=5e1))
ll_H <- sapply(grid_H, function(H) get_ll(a = cmodel$a, x = cmodel$x, r = cmodel$r, K = cmodel$K,
                                          H = H, Q = cmodel$Q, sigma = cmodel$sigma))

##
grid_Q <- exp(seq(log(1.5), log(8), l=5e1))
```







```

ll_Q <- sapply(grid_Q, function(Q) get_ll(a = cmodel$a, x = cmodel$x, r = cmodel$r, K = cmodel$K,
                                          H = cmodel$H, Q = Q, sigma = cmodel$sigma))

##
grid_sigma <- exp(seq(log(1e-2), log(1e-1), l=5e1))
ll_sigma <- sapply(grid_sigma, function(sigma)
  get_ll(a = cmodel$a, x = cmodel$x, r = cmodel$r, K = cmodel$K,
        H = cmodel$H, Q = cmodel$Q, sigma = sigma))

##
layout(matrix(1:6, 3, 2)); par(mar = c(4.1, 2, 1, 1))
plot(grid_r, (ll_r - max(ll_r)), type = "l", main = "r")
abline(v = cmodel$r)
plot(grid_K, (ll_K - max(ll_K)), type = "l", main = "K")
abline(v = cmodel$K)
plot(grid_a, (ll_a - max(ll_a)), type = "l", main = "a")
abline(v = cmodel$a)
plot(grid_H, (ll_H - max(ll_H)), type = "l", main = "H")
abline(v = cmodel$H)
plot(grid_Q, (ll_Q - max(ll_Q)), type = "l", main = "Q", log = "x")
abline(v = cmodel$Q)
plot(grid_sigma, (ll_sigma - max(ll_sigma)), log = "x", type = "l", main = "sigma")
abline(v = cmodel$sigma)

```







```

ll_QH <- apply(expand.grid(grid_Q, grid_H), 1, function(pair)
  if(pair[2] > (0.6 / 3) * pair[1] + 0.18 - (0.6 / 3)) NA else
  get_ll(a = cmodel$a, x = cmodel$x, r = cmodel$r, K = cmodel$K,
    H = pair[2], Q = pair[1], sigma = cmodel$sigma))
ll_Ka <- apply(expand.grid(grid_K, grid_a), 1, function(pair)
  get_ll(a = pair[2], x = cmodel$x, r = cmodel$r, K = pair[1],
    H = cmodel$H, Q = cmodel$Q, sigma = cmodel$sigma))
ll_rK <- apply(expand.grid(grid_r, grid_K), 1, function(pair)
  get_ll(x = cmodel$x, r = pair[1], K = pair[2], a = cmodel$a,
    H = cmodel$H, Q = cmodel$Q, sigma = cmodel$sigma))
ll_Ksigma <- apply(expand.grid(grid_K, grid_sigma), 1, function(pair)
  get_ll(x = cmodel$x, r = cmodel$r, K = pair[1], a = cmodel$a,
    H = cmodel$H, Q = cmodel$Q, sigma = pair[2]))

layout(matrix(1:4, 2, 2)); par(mar = c(4, 4, 1, 1))
image(grid_Q, grid_H, matrix((ll_QH - max(ll_QH, na.rm = T)), length(grid_Q), length(grid_H)))
points(cmodel$Q, cmodel$H)
##
image(grid_K, grid_a, matrix((ll_Ka - max(ll_Ka)), length(grid_K), length(grid_a)))
points(cmodel$K, cmodel$a)
##
image(grid_r, grid_K, matrix((ll_rK - max(ll_rK)), length(grid_r), length(grid_K)))
points(cmodel$r, cmodel$K)
##
image(grid_K, grid_sigma, matrix((ll_Ksigma - max(ll_Ksigma)), length(grid_a), length(grid_sigma)))
points(cmodel$K, cmodel$sigma)

```

```
model$setData(x = cmodel$x)
cmodel <- compileNimble(model)
```

```
## compiling... this may take a minute. Use 'showCompilerOutput = TRUE' to see C++ compilation details.
```

```
## compilation finished.
```

```
## block sampler
system.time({
  mcmcConf <- configureMCMC(model)
  mcmcConf$getSamplers()
  mcmcConf$removeSamplers(c("x0"))
  mcmcConf$addSampler(target = c("log_r", "log_K", "log_a",
                                "log_H", "log_Q", "log_sigma"),
                      type = 'RW_block')
  mcmcConf$getSamplers()
})
```

```
## Note: Assigning an RW_block sampler to nodes with very different scales can result in low MCMC efficiency.
```

```
##   user  system elapsed
##  8.943   0.116   9.212
```

```
system.time({
  mcmc <- buildMCMC(mcmcConf)
  Cmcmc <- compileNimble(mcmc, project = model)
})
```

```
## compiling... this may take a minute. Use 'showCompilerOutput = TRUE' to see C++ compilation details.
```

```
## compilation finished.
```

```
##   user  system elapsed
## 21.280   0.975  24.477
```

```
##
n_iterations <- 1e4
system.time({
  Cmcmc$run(n_iterations, nburnin = n_iterations / 2)
})
```

```
## |-----|-----|-----|-----|
## |-----|-----|-----|-----|
```

```
##   user  system elapsed
## 183.879   1.670 193.582
```

```
samples <- as.matrix(Cmcmc$mvSamples)
```









```
layout(matrix(1:8, 4, 2))
plot(exp(samples[, 'log_r']), type = "l", main = "r")
abline(h = r)
plot(exp(samples[, 'log_K']), type = "l", main = "K")
abline(h = K)
plot(exp(samples[, 'log_a']), type = "l", main = "a",
     ylim = range(exp(samples[, 'log_a']), a))
abline(h = a)
plot(exp(samples[, 'log_H']), type = "l", main = "H")
abline(h = H)
plot(exp(samples[, 'log_Q']), type = "l", main = "Q", log = "y")
```

```

abline(h = Q)
plot(exp(samples[, 'log_sigma']), type = "l", main = "sigma")
abline(h = sigma)
plot(samples[, 'x0'], type = "l", main = "x0")
abline(h = x0)
corrplot::corrplot(cor(samples[, c("log_r", "log_K", "log_a", "log_H", "log_Q", "log_sigma", "x0")]))

## Warning in cor(samples[, c("log_r", "log_K", "log_a", "log_H", "log_Q", :
## the standard deviation is zero


```



```

x <- seq(0, 2, l=1e2)
potential <- function(x = seq(0, 2, l = 1e2), a, r, H, Q, K){
  - cumsum(growth(x = x, r = r, K = K) -
    consumption(x = x, a = a, H = H, Q = Q))
}
potential_curves <- apply(samples, 1, function(row){
  potential(x = x, a = exp(row['log_a']), r = exp(row['log_r']),
    H = exp(row['log_H']), Q = exp(row['log_Q']), K = exp(row['log_K']))
})
subset <- sample(1:nrow(samples), min(400, nrow(samples)))
matplot(x, potential_curves[, subset], type = "l", lty = 1,
  col = scales::alpha(1, 1e-2), lwd = 2)
lines(x, potential(x = x, a = a, r = r, H = H, Q = Q, K = K), lwd = 2)

```




```

cl <- makeForkCluster(2)
mus <- parApply(cl, samples[sample(1:nrow(samples), 100), ], 1,
  function(row){
    x <- rep(NA, N); x[1] <- row['x0']
    mu <- rep(NA, N - 1)
    for(t in 1:(N - 1)){
      mu[t] <-
        x[t] + x[t] * exp(row['log_r']) *
          (1 - x[t] / exp(row['log_K'])) -
        exp(row['log_a']) *
          x[t]^exp(row['log_Q']) / (x[t]^exp(row['log_Q']) +
            exp(row['log_H'])^exp(row['log_Q']))
      x[t + 1] <- rtruncnorm(mean = mu[t], sd = exp(row['log_sigma']))
    }
    return(mu)
  })
stopCluster(cl)
matplot(mus, type = "l", col = scales::alpha(1, 0.01), lty = 1)

```

```
lines(cmodel$mu)
```



Notice a , r , and K are highly correlated. Taking out two of them stabilizes somewhat, but dependence in the posterior distributions arises between other variables.

```
## block sampler
system.time({
  mcmcConf <- configureMCMC(model)
  mcmcConf$getSamplers()
  mcmcConf$removeSamplers(c("log_a", "log_K", "x0"))
  mcmcConf$addSampler(target = c("log_r", "log_H", "log_Q", "log_sigma"),
                      type = 'RW_block')
  mcmcConf$getSamplers()
})
```

Note: Assigning an RW_block sampler to nodes with very different scales can result in low MCMC efficiency.

```
## user system elapsed
## 8.839 0.097 9.069
```

```
system.time({
  mcmc <- buildMCMC(mcmcConf)
  Cmcmc <- compileNimble(mcmc, project = model, resetFunctions = T)
})
```

compiling... this may take a minute. Use 'showCompilerOutput = TRUE' to see C++ compilation details.

compilation finished.

```
## user system elapsed
## 19.996 1.327 21.850
```

```
##
n_iterations <- 1e4
system.time({
  Cmcmc$run(n_iterations, nburnin = n_iterations / 2)
})
```







```
## |-----|-----|-----|-----|
```

```
## |-----|
##      user  system elapsed
## 117.640    0.938 120.318

samples_no_a_K <- as.matrix(Cmcmc$mvSamples)

layout(matrix(1:6, 3, 2))
plot(exp(samples_no_a_K[, 'log_r']), type = "l", main = "r")
abline(h = r)
plot(exp(samples_no_a_K[, 'log_H']), type = "l", main = "H")
abline(h = H)
plot(exp(samples_no_a_K[, 'log_Q']), type = "l", main = "Q", log = "y")
abline(h = Q)
plot(exp(samples_no_a_K[, 'log_sigma']), type = "l", main = "sigma")
abline(h = sigma)
plot(samples_no_a_K[, 'x0'], type = "l", main = "x0")
abline(h = x0)
corrplot::corrplot(cor(samples_no_a_K[, c("log_r", "log_H", "log_Q", "log_sigma", "x0")]))


## Warning in cor(samples_no_a_K[, c("log_r", "log_H", "log_Q", "log_sigma", :
## the standard deviation is zero
```




```

x <- seq(0, 2, l=1e2)
potential_curves <- apply(samples_no_a_K, 1, function(row){
  potential(x = x, a = exp(row['log_a']), r = exp(row['log_r']),
    H = exp(row['log_H']), Q = exp(row['log_Q']), K = exp(row['log_K']))
})
matplot(x, potential_curves[, subset], type = "l", lty = 1,
  col = scales::alpha(1, 1e-2), lwd = 2)
lines(x, potential(x = x, a = a, r = r, H = H, Q = Q, K = K), lwd = 2)


```



```

cl <- makeForkCluster(2)
mus_no_a_K <- parApply(cl, samples_no_a_K[sample(1:nrow(samples_no_a_K), 100), ], 1,
  function(row){
    x <- rep(NA, N); x[1] <- row['x0']
    mu <- rep(NA, N - 1)
    for(t in 1:(N - 1)){
      mu[t] <-
        x[t] + x[t] * exp(row['log_r']) *
          (1 - x[t] / exp(row['log_K'])) -
        exp(row['log_a']) *
          x[t]^exp(row['log_Q']) / (x[t]^exp(row['log_Q']) +
            exp(row['log_H'])^exp(row['log_Q']))
      x[t + 1] <- rtruncnorm(mean = mu[t], sd = exp(row['log_sigma']))
    }
    return(mu)
  })
stopCluster(cl)
matplot(mus_no_a_K, type = "l", col = scales::alpha(1, 0.01), lty = 1)
lines(cmodel$mu)

```



```

N_intro <- 700
constants$N <- N_intro
model <- nimbleModel(code = may, constants = constants, inits = inits)
model$setData(x = cmodel$x[1:N_intro])
cmodel <- compileNimble(model)
## block sampler
system.time({
  mcmcConf <- configureMCMC(model)
  mcmcConf$getSamplers()
  mcmcConf$removeSamplers(c("x0"))
  mcmcConf$addSampler(target = c("log_r", "log_K", "log_a",
                                "log_H", "log_Q", "log_sigma"),
                      type = 'RW_block')
  mcmcConf$getSamplers()
})
system.time({
  mcmc <- buildMCMC(mcmcConf)
  Cmcmc <- compileNimble(mcmc, project = model)
})
##
n_iterations <- 1e4
system.time({
  Cmcmc$run(n_iterations, nburnin = n_iterations / 2)
})
samples <- as.matrix(Cmcmc$mvSamples)

```

```

layout(matrix(1:8, 4, 2))
plot(exp(samples[, 'log_r']), type = "l", main = "r")
abline(h = r)
plot(exp(samples[, 'log_K']), type = "l", main = "K")
abline(h = K)
plot(exp(samples[, 'log_a']), type = "l", main = "a",
      ylim = range(exp(samples[, 'log_a']), a))
abline(h = a)
plot(exp(samples[, 'log_H']), type = "l", main = "H")

```

```

abline(h = H)
plot(exp(samples[, 'log_Q']), type = "l", main = "Q", log = "y")
abline(h = Q)
plot(exp(samples[, 'log_sigma']), type = "l", main = "sigma")
abline(h = sigma)
plot(samples[, 'x0'], type = "l", main = "x0")
abline(h = x0)
corrplot::corrplot(cor(samples[, c("log_r", "log_K", "log_a", "log_H", "log_Q", "log_sigma", "x0")]))

x <- seq(0, 2, l=1e2)
potential <- function(x = seq(0, 2, l = 1e2), a, r, H, Q, K){
  - cumsum(growth(x = x, r = r, K = K) -
            consumption(x = x, a = a, H = H, Q = Q))
}
potential_curves <- apply(samples, 1, function(row){
  potential(x = x, a = exp(row['log_a']), r = exp(row['log_r']),
            H = exp(row['log_H']), Q = exp(row['log_Q']), K = exp(row['log_K']))
})
subset <- sample(1:nrow(samples), min(400, nrow(samples)))
matplot(x, potential_curves[, subset], type = "l", lty = 1,
        col = scales::alpha(1, 1e-2), lwd = 2)
lines(x, potential(x = x, a = a, r = r, H = H, Q = Q, K = K), lwd = 2)

cl <- makeForkCluster(2)
mus <- parApply(cl, samples[sample(1:nrow(samples), 100), ], 1,
               function(row){
  x <- rep(NA, N); x[1] <- row['x0']
  mu <- rep(NA, N - 1)
  for(t in 1:(N - 1)){
    mu[t] <-
      x[t] + x[t] * exp(row['log_r']) *
        (1 - x[t] / exp(row['log_K'])) -
      exp(row['log_a']) *
        x[t]^exp(row['log_Q']) / (x[t]^(row['log_Q']) +
      exp(row['log_H'])^(row['log_Q']))
    x[t + 1] <- rtruncnorm(mean = mu[t], sd = exp(row['log_sigma']))
  }
  return(mu)
})
stopCluster(cl)
matplot(mus, type = "l", col = scales::alpha(1, 0.01), lty = 1)
lines(cmodel$mu)

```