

**computer science**

# pandas for data (science)

- **syntax errors**: raised while the interpreter while executing the program reaches an instruction that does not match syntax rules (the first time the instruction is executed)
- unexpected behavior (**exceptions**): raised while the interpreter executes the program, due to a situation (data) not taken into account while writing the program



# get data from csv file

`read_csv(csvfilename):` returns a dataframe from with the data from the csvfilename

`df = pd.read_csv("SBP.csv")`



```
SBP_before,SBP_after
125,118
132,134
138,130
120,124
125,105
127,130
136,130
139,132
131,123
132,128
135,126
136,140
128,135
127,126
130,132
```



	SBP_before	SBP_after
0	125	118
1	132	134
2	138	130
3	120	124
4	125	105
5	127	130
6	136	130
7	139	132
8	131	123
9	132	128
10	135	126
11	136	140
12	128	135
13	127	126
14	130	132

`len(df)`

returns the number of row in the dataframe

# handling missing data

`fillna(_value_)`

```
[>>> df=df.fillna(0.0)
```

```
[>>> df
```

	SBP_before	SBP_after
0	125	118.0
1	132	134.0
2	138	130.0
3	120	124.0
4	125	105.0
5	127	130.0
6	136	130.0
7	139	132.0
8	131	123.0
9	132	128.0
10	135	126.0
11	136	140.0
12	128	135.0
13	127	126.0
14	130	132.0
15	134	0.0



replace NaN with a value

	SBP_before	SBP_after
0	125	118.0
1	132	134.0
2	138	130.0
3	120	124.0
4	125	105.0
5	127	130.0
6	136	130.0
7	139	132.0
8	131	123.0
9	132	128.0
10	135	126.0
11	136	140.0
12	128	135.0
13	127	126.0
14	130	132.0
15	134	NaN

`dropna()`

```
[>>> df = df.dropna()
```

```
[>>> df
```

	SBP_before	SBP_after
0	125	118.0
1	132	134.0
2	138	130.0
3	120	124.0
4	125	105.0
5	127	130.0
6	136	130.0
7	139	132.0
8	131	123.0
9	132	128.0
10	135	126.0
11	136	140.0
12	128	135.0
13	127	126.0
14	130	132.0

remove when incomplete →

# selecting rows (subset observation)

- by position

`df.iloc[fromrow:torow]`

```
[>>> dfw.iloc[1:5]
      n type  alpha  value
1    5  TTT   0.01   NaN
2    5  OTT   0.05    0.0
3    5  OTT   0.01   NaN
4    6  TTT   0.05    0.0
```

```
[>>> dfw = pd.read_csv("../WSRTdf.csv")
[>>> dfw
```

	n	type	alpha	value
0	5	TTT	0.05	NaN
1	5	TTT	0.01	NaN
2	5	OTT	0.05	0.0
3	5	OTT	0.01	NaN
4	6	TTT	0.05	0.0

..	..	...	...	...
99	29	OTT	0.01	110.0
100	30	TTT	0.05	137.0
101	30	TTT	0.01	109.0
102	30	OTT	0.05	151.0
103	30	OTT	0.01	120.0

```
[104 rows x 4 columns]
```

# selecting rows (subset observation) 2


- by value in one ...

... or more columns



# creating new data

`df['NewColumnName'] = df.ExistingColumn` *operator* variable



```
[>>> df['Difference'] = df.SBP_before - df.SBP_after  
[>>> df
```

	SBP_before	SBP_after	Difference
0	125	118	7
1	132	134	-2
2	138	130	8
3	120	124	-4
4	125	105	20
5	127	130	-3
6	136	130	6
7	139	132	7
8	131	123	8
9	132	128	4
10	135	126	9
11	136	140	-4
12	128	135	-7
13	127	126	1
14	130	132	-2

`df['Difference'] = df.SBP_before - df.SBP_after`

# creating new data 2

`df['NewColumnName'] = df.ExistingColumn` *operator* variable

`df['AbsDiff'] = abs(df.Difference)`

```
[>>> df['AbsDiff'] = abs(df.Difference)
```

```
[>>> df
```

	SBP_before	SBP_after	Difference	AbsDiff
0	125	118	7	7
1	132	134	-2	2
2	138	130	8	8
3	120	124	-4	4
4	125	105	20	20
5	127	130	-3	3
6	136	130	6	6
7	139	132	7	7
8	131	123	8	8
9	132	128	4	4
10	135	126	9	9
11	136	140	-4	4
12	128	135	-7	7
13	127	126	1	1
14	130	132	-2	2



# creating new data, selectively



# sorting

*list* of columns



`sort_values(by, ascending):` sorts with respect to values in columns, in ascending (default) or descending order

it is not "in place"

```
df = df.sort_values("AbsDiff")
```



# sorting 2

```
df = df.sort_values("AbsDiff")
```

```
[>>> df = df.sort_values("AbsDiff")
```

```
[>>> df
```

	SBP_before	SBP_after	Difference	AbsDiff
13	127	126	1	1
1	132	134	-2	2
14	130	132	-2	2
5	127	130	-3	3
3	120	124	-4	4
9	132	128	4	4
11	136	140	-4	4
6	136	130	6	6
0	125	118	7	7
7	139	132	7	7
12	128	135	-7	7
2	138	130	8	8
8	131	123	8	8
10	135	126	9	9
4	125	105	20	20

```
[>>> df = df.sort_values("Difference")
```

```
[>>> df
```

	SBP_before	SBP_after	Difference	AbsDiff
12	128	135	-7	7
3	120	124	-4	4
11	136	140	-4	4
5	127	130	-3	3
1	132	134	-2	2
14	130	132	-2	2
13	127	126	1	1
9	132	128	4	4
6	136	130	6	6
0	125	118	7	7
7	139	132	7	7
2	138	130	8	8
8	131	123	8	8
10	135	126	9	9
4	125	105	20	20

```
df = df.sort_values("Difference")
```

# sorting 3

sort by this then by this



```
df = df.sort_values(["AbsDiff", "Difference"])
```

```
[>>> df = df.sort_values(["AbsDiff", "Difference"])
```

```
[>>> df
```

	SBP_before	SBP_after	Difference	AbsDiff
13	127	126	1	1
1	132	134	-2	2
14	130	132	-2	2
5	127	130	-3	3
3	120	124	-4	4
11	136	140	-4	4
9	132	128	4	4
6	136	130	6	6
12	128	135	-7	7
0	125	118	7	7
7	139	132	7	7
2	138	130	8	8
8	131	123	8	8
10	135	126	9	9
4	125	105	20	20

# ranking data

`rank(method="..."):`

returns a rank of every  
respective index of a series  
passed.

The rank is returned on the  
basis of position after sorting

`df["AbsDiff"].rank()`



# ranking data 2

extra column

`df["AbsDiff"].rank()` ➡ `df["Ranks"] = df["AbsDiff"].rank()`

with sorting

	SBP_before	SBP_after	Difference	AbsDiff	Ranks
13	127	126	1	1	1.0
1	132	134	-2	2	2.5
14	130	132	-2	2	2.5
5	127	130	-3	3	4.0
3	120	124	-4	4	6.0
11	136	140	-4	4	6.0
9	132	128	4	4	6.0
6	136	130	6	6	8.0
12	128	135	-7	7	10.0
0	125	118	7	7	10.0
7	139	132	7	7	10.0
2	138	130	8	8	12.5
8	131	123	8	8	12.5
10	135	126	9	9	14.0
4	125	105	20	20	15.0

	SBP_before	SBP_after	Difference	AbsDiff	Ranks
0	125	118	7	7	10.0
1	132	134	-2	2	2.5
2	138	130	8	8	12.5
3	120	124	-4	4	6.0
4	125	105	20	20	15.0
5	127	130	-3	3	4.0
6	136	130	6	6	8.0
7	139	132	7	7	10.0
8	131	123	8	8	12.5
9	132	128	4	4	6.0
10	135	126	9	9	14.0
11	136	140	-4	4	6.0
12	128	135	-7	7	10.0
13	127	126	1	1	1.0
14	130	132	-2	2	2.5

without sorting

# creating new data, selectively

```
df['R+'] = df['Ranks']*(df['Difference'] > 0)
```

1 when true  
0 when false

```
[>>> df['R+'] = df['Ranks']*(df['Difference'] > 0)
```

```
[>>> df
```

	SBP_before	SBP_after	Difference	AbsDiff	Ranks	R+
13	127	126	1	1	1.0	1.0
1	132	134	-2	2	2.5	0.0
14	130	132	-2	2	2.5	0.0
5	127	130	-3	3	4.0	0.0
3	120	124	-4	4	6.0	0.0
11	136	140	-4	4	6.0	0.0
9	132	128	4	4	6.0	6.0
6	136	130	6	6	8.0	8.0
12	128	135	-7	7	10.0	0.0
0	125	118	7	7	10.0	10.0
7	139	132	7	7	10.0	10.0
2	138	130	8	8	12.5	12.5
8	131	123	8	8	12.5	12.5
10	135	126	9	9	14.0	14.0
4	125	105	20	20	15.0	15.0

# dataframes

`df[col]`      select column

`df.iloc[rowlabel]`      select row by label

