Hack 2.0

Computer Science I

Department of Computer Science & Engineering
University of Nebraska–Lincoln

Introduction

Hack session activities are small weekly programming assignments intended to get you started on full programming assignments. Collaboration is allowed and, in fact, *highly encouraged*. You may start on the activity before your hack session, but during the hack session you must either be actively working on this activity or *helping others* work on the activity. You are graded using the same rubric as assignments so documentation, style, design and correctness are all important. This activity is due at 23:59:59 on the Monday following the hack session in which it is assigned according to the CSE system clock.

Problem Statement

Consider two locations, an origin and a destination, on the globe identified by their latitude and longitude. The distance between these two locations can be computed using the Spherical Law of Cosines. In particular, the distance d is

$$d = \arccos\left(\sin(\varphi_1)\sin(\varphi_2) + \cos(\varphi_1)\cos(\varphi_2)\cos(\Delta)\right) \cdot R$$

where

- φ_1 is the latitude of location A, φ_2 is the latitude of location B
- Δ is the difference between location B's longitude and location A's longitude
- R is the (average) radius of the earth, 6,371 kilometers

Write a program that *prompts* the user to enter the latitude and longitude of two locations and then computes the distance between them using the above formula. Note that latitude

inputs will be in degrees and in the range [-90, 90] and longitude will be in degrees in the range [-180, 180]. Negative values correspond to the western and southern hemispheres.

Note that the formula above assumes that latitude and longitude are measured in radians $r, -\pi \le r \le \pi$. You can convert from degrees deg to radians r using the formula

$$r = \frac{deg}{180} \cdot \pi$$

Your output should look something like the following.

Location Distance

Origin: (41.948300, -87.655600) Destination: (40.820600, -96.705600)

Air distance is 764.990931 kms

Instructions

- You are encouraged to collaborate any number of students before, during, and after your scheduled hack session.
- Design at least 3 test cases *before* you begin designing or implementing your program. Test cases are input-output pairs that are known to be correct using means other than your program.
- Include the name(s) of everyone who worked together on this activity in your source file's header.
- Name your program <code>airDistance.c</code>, and turn it in via webhandin, making sure that it runs and executes correctly in the webgrader. Each individual student will need to hand in their own copy and will receive their own individual grade.