

System Parameters (defined by hardware)			Profiles (usage of each component mode - defined by software and usage)		
form the datasheets			"off"	"sensing"	"interactive"
Processor	ESP-32C3				
Active	51	mW	0%	2%	60%
Idle	11	mW	0%	8%	35%
Sleep	1	mW	100%	90%	5%
LED					
On	4	mW	0%	1%	40%
Sensor					
On	4	mW	0%	2%	80%
Idle	4	mW	0%	0%	0%
Off	0	mW	100%	98%	20%
Display					
On	71	mW	0%	5%	30%
Off (leakage)	0	mW	100%	95%	70%
Radio					
Data Rate	1150	bps	0%	0%	0%
Standby Power	201	mW	0%	1%	70%
TX Power	3	mW	0%	0%	30%
RX Power-Not M	0	mW	0%	0%	0%
Battery					
Capacity	500	mAh	12	11	1 hours/day typical usage
Nominal Voltage	4	V			
Regulator Efficiency	88%				

Total power in profile (mw)						Maximum Time		
"off"	0.5946	mW	2738.0	hours	off: 1628 / 0.5946			
"sensing"	7.1491358	mW	228.0	hours	sensing: 1628 / 7.149			
"interactive"	202.86259	mW	8.0	hours	interactive: 1628 / 202.86			
Effective Battery Capacity								
1628 mW*h								
Days of Use	5.64	days						
Hours of Use	135.37	hours						

REFLECTIONS : WHAT YOU LEARN FROM ANALYZING YOUR POWER. TALK ABOUT SOME POTENTIAL TRADEOFFS.