

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?-

resolvent =

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent =

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent =

**Initialize resolvent to goal  $G$  (the query)**

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

    replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output no

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **father(fred,pebbles),**  
**mother(pebbles,chip)**

**Initialize resolvent to goal G (the query)**

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

    replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
*else* output no

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = father(fred,pebbles),  
                    mother(pebbles,chip)

Initialize resolvent to goal  $G$  (the query)

**while resolvent not empty do**

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output no

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = father(fred,pebbles),  
                    mother(pebbles,chip)

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

**select a goal  $A$  from the resolvent**

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **father(fred,pebbles),**  
                  mother(pebbles,chip)

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

**select a goal  $A$  from the resolvent**

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **father(fred,pebbles),**  
                  mother(pebbles,chip)

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

**choose a ground instance of a clause**

$A' :- B_1, \dots, B_n$  from program  $P$

**such that  $A$  and  $A'$  are identical**

**(if no such goal and clause exist, exit**  
        **the while loop)**

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*



# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **father(fred,pebbles),**  
                  **mother(pebbles,chip)**

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

**choose a ground instance of a clause**

$A' :- B_1, \dots, B_n$  from program  $P$

**such that  $A$  and  $A'$  are identical**

**(if no such goal and clause exist, exit**  
        **the while loop)**

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **father(fred,pebbles),**  
                  mother(pebbles,chip)

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

**replace  $A$  by  $B_1, \dots, B_n$  in the resolvent**

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **father(fred,pebbles),**  
                  **mother(pebbles,chip)**

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

**replace  $A$  by  $B_1, \dots, B_n$  in the resolvent**

**(huh? Well, if there is no  $B_1, \dots, B_n$  then**  
    **there's an identity and goal  $A$  is true)**

*If* the resolvent is empty, *then* output yes,  
    *else* output no

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **true**,  
                  mother(pebbles,chip)

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

**replace  $A$  by  $B_1, \dots, B_n$  in the resolvent**

    (huh? Well, if there is no  $B_1, \dots, B_n$  then  
    **there's an identity and goal  $A$  is true**)

*If* the resolvent is empty, *then* output yes,  
    *else* output no

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = mother(pebbles,chip)

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

**replace  $A$  by  $B_1, \dots, B_n$  in the resolvent**

    (huh? Well, if there is no  $B_1, \dots, B_n$  then  
    **there's an identity and goal  $A$  is true**)

*If* the resolvent is empty, *then* output yes,  
*else* output no

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = mother(pebbles,chip)

Initialize resolvent to goal  $G$  (the query)

**while resolvent not empty do**

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = mother(pebbles,chip)

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

**select a goal  $A$  from the resolvent**

choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

such that  $A$  and  $A'$  are identical

(if no such goal and clause exist, exit  
the while loop)

replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
*else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **mother(pebbles,chip)**

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

**select a goal  $A$  from the resolvent**

choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

such that  $A$  and  $A'$  are identical

(if no such goal and clause exist, exit  
the while loop)

replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
*else* output *no*



# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **mother(pebbles,chip)**

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

**choose a ground instance of a clause**

$A' :- B_1, \dots, B_n$  from program  $P$

**such that  $A$  and  $A'$  are identical**

**(if no such goal and clause exist, exit the while loop)**

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,

*else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **mother(pebbles,chip)**

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

**choose a ground instance of a clause**

$A' :- B_1, \dots, B_n$  from program  $P$

**such that  $A$  and  $A'$  are identical**

**(if no such goal and clause exist, exit the while loop)**

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,

*else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent = **mother(pebbles,chip)**

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

**replace  $A$  by  $B_1, \dots, B_n$  in the resolvent**

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent =

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

**replace  $A$  by  $B_1, \dots, B_n$  in the resolvent**

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent =

Initialize resolvent to goal  $G$  (the query)

**while resolvent not empty do**

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

        replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

*If* the resolvent is empty, *then* output yes,  
    *else* output *no*

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

resolvent =

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

    replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

***If the resolvent is empty, then output yes,  
else output no***

# What happens to a query?

The program ( $P$ ):

```
father(fred,pebbles).  
father(bamm-bamm,roxy).  
father(barney,bamm-bamm).  
father(bamm-bamm,chip).  
mother(pebbles,roxy).  
mother(pebbles,chip).  
mother(wilma,pebbles).  
mother(betty,bamm-bamm).
```

?- father(fred,pebbles),mother(pebbles,chip).

**Yes**

resolvent =

Initialize resolvent to goal  $G$  (the query)

*while* resolvent not empty *do*

    select a goal  $A$  from the resolvent

    choose a ground instance of a clause

$A' :- B_1, \dots, B_n$  from program  $P$

        such that  $A$  and  $A'$  are identical

        (if no such goal and clause exist, exit  
        the while loop)

    replace  $A$  by  $B_1, \dots, B_n$  in the resolvent

***If the resolvent is empty, then output yes,  
else output no***

Questions?