

Package ‘ConvenienceFunctions’

October 14, 2021

Type Package

Title Convenience functions for R for QBS181

Version 0.1.0

Author Carly Bobak

Description We provide general utilities for common tasks in data wrangling

License MIT

Depends R (\geq 3.5.0)

Encoding UTF-8

LazyData true

Imports stats,
ggplot2

RoxygenNote 7.1.2

R topics documented:

completeFun	<i>Drop NAs by Columns</i>
-------------	----------------------------

Description

Remove NAs based on specified columns in the data

Usage

```
completeFun(data, desiredCols)
```

Arguments

data	data.frame object of variations
desiredCols	list of columns from which incomplete cases should be dropped

Value

dataframe with removed observations

Examples

```
data<-data.frame(a=1:4,b=c("a","b","c","d"),c=c(NA,"keep",NA,"keep"))
completeFun(data,c("c"))
```

factorial	<i>Factorial</i>
-----------	------------------

Description

Function to calculate the factorial of a variable

Usage

```
factorial(x)
```

Arguments

x numeric vector

Value

numeric value of factorial

Examples

```
factorial(5)
```

gm_mean	<i>Geometric mean</i>
---------	-----------------------

Description

Function to calculate the geometric mean of a variable

Usage

```
gm_mean(x, na.rm = TRUE)
```

Arguments

x numeric vector

Value

numeric value of geometric mean

Examples

```
x<-c(1,1,3,5,6,6)
gm_mean(x)
```

Modes	<i>Mode</i>
-------	-------------

Description

Function to calculate the mode of a variable

Usage

```
Modes(x)
```

Arguments

x numeric vector

Value

numeric vector of modes

Examples

```
x<-c(1,1,3,5,6,6)
Modes(x)
```

nonUnique	<i>Non-unique</i>
-----------	-------------------

Description

Function that returns all non-unique values in a vector

Usage

```
nonUnique(x)
```

Arguments

x numeric or character vector

Value

numeric or character vector of non-unique values

Examples

```
x<-c(1,1,3,5,6,6)
nonUnique(x)
```